



Catalina

Connector

port=80

(Implementation of a Coyote connector)

URIEncoding	UTF-8	(Character encoding used to decode the URI)
acceptCount	100	(The accept count for this Connector)
address	null	(The IP address on which to bind)
ajpFlush	null	(Send AJP flush package for each explicit flush)
allowTrace	false	(Allow disabling TRACE method)
allowedRequestAttributesPattern	null	(Regular expression that any custom request attributes must match else the request will be rejected)
ciphers	HIGH:!aNULL:!eNULL:!EXPORT:!DES:!RC4:!MD5:!kRSA	(Comma-separated list of requested cipher suites)
ciphersUsed	null	(Array of ciphers suites in use)
className	null	(Fully qualified class name of the managed object)
connectionLinger	-1	(Linger value on the incoming connection)
connectionTimeout	20 000	(Timeout value on the incoming connection)
enableLookups	false	(The 'enable DNS lookups' flag for this Connector)
executorName	Internal	(The name of the executor - if any - associated with this Connector)
keepAliveTimeout	20 000	(The number of milliseconds Tomcat will wait for a subsequent request before closing the connection)
localPort	80	(The port number on which this connector is listening to requests. If the special value for port of zero is used then this method will report the actual port bound.)
maxHeaderCount	100	(The maximum number of headers that are allowed by the container. 100 by default. A value of less than 0 means no limit.)
maxKeepAliveRequests	100	(Maximum number of Keep-Alive requests to honor per connection)
maxParameterCount	1 000	(The maximum number of parameters (GET plus POST) which will be automatically parsed by the container. 10000 by default. A value of less than 0 means no limit.)
maxPostSize	2 097 152	(Maximum size in bytes of a POST which will be handled by the servlet API provided features)
maxSavePostSize	4 096	(Maximum size of a POST which will be saved by the container during authentication)
maxSwallowSize	2 097 152	(The maximum number of request body bytes to be swallowed by Tomcat for an aborted upload)
maxThreads	200	(The maximum number of request processing threads to be created for the internal Executor. -1 indicates an external Executor is being used.)
minSpareThreads	10	(The number of request processing threads that will be created for the internal Executor. -1 indicates an external Executor is being used.)
modelerType	null	(Type of the modeled resource. Can be set only once)
packetSize	null	(The ajp packet size.)
port	80	(The port number (excluding any offset) on which this connector is configured to listen for requests. The special value of 0 means select a random free port when the socket is bound.)
portOffset	0	(The offset that will be applied to port to determine the actual port number used.)
portWithOffset	80	(The actual port number (including any offset) on which this connector is configured to listen for requests.)
processorCache	200	(The processor cache size.)
protocol	HTTP/1.1	(Coyote protocol handler in use)
protocolHandlerClassName	org.apache.coyote.http11.Http11NioProtocol	(Coyote Protocol handler class name)
proxyName	null	(The Server name to which we should pretend requests to this Connector)
proxyPort	0	(The Server port to which we should pretend requests to this Connector)
redirectPort	443	(The redirect port (excluding any offset) for non-SSL to SSL redirects)
redirectPortWithOffset	443	(The actual redirect port (including any offset) for non-SSL to SSL redirects.)
scheme	http	(Protocol name for this Connector (http, https))
secretRequired	null	(Must secret be set to a non-null, non-zero-length String?)
secure	false	(Is this a secure (SSL) Connector?)
sslProtocols	null	(Comma-separated list of SSL protocol variants to be enabled)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
tcpNoDelay	true	(Should we use TCP no delay?)
threadPriority	5	(The thread priority for processors using the internal Executor. -1 indicates an external Executor is being used.)
useBodyEncodingForURI	false	(Should the body encoding be used for URI query parameters)
useIPVHosts	false	(Should IP-based virtual hosting be used?)
xpoweredBy	false	(Is generation of X-Powered-By response header enabled/disabled?)

DataSource

host=localhost,context=/demo,class=javax.sql.DataSource,name="jdbc/demo_javamelody"

abandonedUsageTracking	false	(Inspected attribute abandonedUsageTracking)
accessToUnderlyingConnectionAllowed	false	(Inspected attribute accessToUnderlyingConnectionAllowed)
autoCommitOnReturn	true	(Inspected attribute autoCommitOnReturn)
cacheState	true	(Inspected attribute cacheState)
closed	false	(Inspected attribute closed)
connectionFactoryClassName	null	(Inspected attribute connectionFactoryClassName)
connectionInitSqlsAsArray	[]	(Inspected attribute connectionInitSqlsAsArray)
defaultAutoCommit	null	(Inspected attribute defaultAutoCommit)
defaultCatalog	null	(Inspected attribute defaultCatalog)
defaultQueryTimeout	null	(Inspected attribute defaultQueryTimeout)
defaultReadOnly	null	(Inspected attribute defaultReadOnly)

defaultSchema	null	(Inspected attribute defaultSchema)
defaultTransactionIsolation	-1	(Inspected attribute defaultTransactionIsolation)
disconnectionSqlCodesAsArray	[]	(Inspected attribute disconnectionSqlCodesAsArray)
driverClassName	org.h2.Driver	(Inspected attribute driverClassName)
enableAutoCommitOnReturn	true	(Inspected attribute enableAutoCommitOnReturn)
evictionPolicyClassName	org.apache.tomcat.dbcp.pool2.impl.DefaultEvictionPolicy	(Inspected attribute evictionPolicyClassName)
fastFailValidation	false	(Inspected attribute fastFailValidation)
initialSize	0	(Inspected attribute initialSize)
jmxName	Catalina:type=DataSource,host=localhost,context=/demo,class=javax.sql.DataSource,name="jdbc/demo_javamelody"	(Inspected attribute jmxName)
lifo	true	(Inspected attribute lifo)
logAbandoned	false	(Inspected attribute logAbandoned)
logExpiredConnections	true	(Inspected attribute logExpiredConnections)
maxConnLifetimeMillis	-1	(Inspected attribute maxConnLifetimeMillis)
maxIdle	10	(Inspected attribute maxIdle)
maxOpenPreparedStatements	-1	(Inspected attribute maxOpenPreparedStatements)
maxTotal	100	(Inspected attribute maxTotal)
maxWaitMillis	30 000	(Inspected attribute maxWaitMillis)
minEvictableIdleTimeMillis	1 800 000	(Inspected attribute minEvictableIdleTimeMillis)
minIdle	0	(Inspected attribute minIdle)
modelerType	org.apache.tomcat.dbcp.dbcp2.BasicDataSource	(Type of the modeled resource. Can be set only once)
numActive	7	(Inspected attribute numActive)
numIdle	5	(Inspected attribute numIdle)
numTestsPerEvictionRun	3	(Inspected attribute numTestsPerEvictionRun)
poolPreparedStatements	false	(Inspected attribute poolPreparedStatements)
removeAbandonedOnBorrow	false	(Inspected attribute removeAbandonedOnBorrow)
removeAbandonedOnMaintenance	false	(Inspected attribute removeAbandonedOnMaintenance)
removeAbandonedTimeout	300	(Inspected attribute removeAbandonedTimeout)
rollbackOnReturn	true	(Inspected attribute rollbackOnReturn)
softMinEvictableIdleTimeMillis	-1	(Inspected attribute softMinEvictableIdleTimeMillis)
testOnBorrow	true	(Inspected attribute testOnBorrow)
testOnCreate	false	(Inspected attribute testOnCreate)
testOnReturn	false	(Inspected attribute testOnReturn)
testWhileIdle	false	(Inspected attribute testWhileIdle)
timeBetweenEvictionRunsMillis	-1	(Inspected attribute timeBetweenEvictionRunsMillis)
url	jdbc:h2:/opt/data/demo/h2	(Inspected attribute url)
username	sa	(Inspected attribute username)
validationQuery	null	(Inspected attribute validationQuery)
validationQueryTimeout	-1	(Inspected attribute validationQueryTimeout)

host=localhost,context=/demo,class=javax.sql.DataSource,name="jdbc/demo_javamelody",connectionpool=connections

AbandonedConfig	false
BlockWhenExhausted	true
BorrowedCount	34 308
Closed	false
CreatedCount	12

CreationStackTrace

```

java.lang.Exception
at
org.apache.tomcat.dbcp.pool2.impl.BaseGenericObjectPool.<init>(BaseGenericObjectPool.java:147)
at
org.apache.tomcat.dbcp.pool2.impl.GenericObjectPool.<init>(GenericObjectPool.java:109)
at
org.apache.tomcat.dbcp.dbcp2.BasicDataSource.createObjectPool(BasicDataSource.java:628)
at
org.apache.tomcat.dbcp.dbcp2.BasicDataSource.createConnectionPool(BasicDataSource.java:492)
at
org.apache.tomcat.dbcp.dbcp2.BasicDataSource.createDataSource(BasicDataSource.java:558)
at
org.apache.tomcat.dbcp.dbcp2.BasicDataSource.getConnection(BasicDataSource.java:753)
at
java.base/jdk.internal.reflect.NativeMethodAccessorImpl.invoke0(Native Method)
at
java.base/jdk.internal.reflect.NativeMethodAccessorImpl.invoke(NativeMethodAccessorImpl.java:62)
at
java.base/jdk.internal.reflect.DelegatingMethodAccessorImpl.invoke(DelegatingMethodAccessorImpl.java:43)
at
java.base/java.lang.reflect.Method.invoke(Method.java:566)
at
net.bull.javamelody.JdbcWrapper$3.invoke(JdbcWrapper.java:812)
at
net.bull.javamelody.JdbcWrapper$DelegatingInvocationHandler.invoke(JdbcWrapper.java:306)
at
com.sun.proxy.$Proxy5.getConnection(Unknown Source)
at
net.bull.javamelody.internal.model.JavaInformations.buildDataBaseVersion(JavaInformations.java:426)
at
net.bull.javamelody.internal.model.JavaInformations.<init>(JavaInformations.java:200)
at
net.bull.javamelody.internal.web.MonitoringController.doActionIfNeededAndReport(MonitoringController.java:158)
at
net.bull.javamelody.MonitoringFilter.doMonitoring(MonitoringFilter.java:408)
at
net.bull.javamelody.MonitoringFilter.doFilter(MonitoringFilter.java:206)
at
org.apache.catalina.core.ApplicationFilterChain.internalDoFilter(ApplicationFilterChain.java:193)
at
org.apache.catalina.core.ApplicationFilterChain.doFilter(ApplicationFilterChain.java:166)
at
fr.spi4j.filter.HttpSessionFilter.doFilter(HttpSessionFilter.java:69)
at
org.apache.catalina.core.ApplicationFilterChain.internalDoFilter(ApplicationFilterChain.java:193)
at
org.apache.catalina.core.ApplicationFilterChain.doFilter(ApplicationFilterChain.java:166)
at
net.bull.javamelody.MonitoringFilter.doFilter(MonitoringFilter.java:199)
at
org.apache.catalina.core.ApplicationFilterChain.internalDoFilter(ApplicationFilterChain.java:193)
at
org.apache.catalina.core.ApplicationFilterChain.doFilter(ApplicationFilterChain.java:166)
at
fr.spi4j.filter.ForbiddenActionsFilter.doFilter(ForbiddenActionsFilter.java:24)
at
org.apache.catalina.core.ApplicationFilterChain.internalDoFilter(ApplicationFilterChain.java:193)
at
org.apache.catalina.core.ApplicationFilterChain.doFilter(ApplicationFilterChain.java:166)
at
fr.spi4j.lib.security.RemoteUserFilter.doFilter(RemoteUserFilter.java:66)
at
org.apache.catalina.core.ApplicationFilterChain.internalDoFilter(ApplicationFilterChain.java:193)
at
org.apache.catalina.core.ApplicationFilterChain.doFilter(ApplicationFilterChain.java:166)
at
org.apache.catalina.core.StandardWrapperValve.invoke(StandardWrapperValve.java:202)
at
org.apache.catalina.core.StandardContextValve.invoke(StandardContextValve.java:96)
at
org.apache.catalina.authenticator.AuthenticatorBase.invoke(AuthenticatorBase.java:541)
at
org.apache.catalina.core.StandardHostValve.invoke(StandardHostValve.java:139)
at
org.apache.catalina.valves.ErrorReportValve.invoke(ErrorReportValve.java:92)
at
org.apache.catalina.valves.AbstractAccessLogValve.invoke(AbstractAccessLogValve.java:688)
at
org.apache.catalina.core.StandardEngineValve.invoke(StandardEngineValve.java:74)
at
org.apache.catalina.connector.CoyoteAdapter.service(CoyoteAdapter.java:343)
at
org.apache.coyote.http11.Http11Processor.service(Http11Processor.java:373)
at
org.apache.coyote.AbstractProcessorLight.process(AbstractProcessorLight.java:65)
at
org.apache.coyote.AbstractProtocol$ConnectionHandler.process(AbstractProtocol.java:868)
at
org.apache.tomcat.util.net.NioEndpoint$SocketProcessor.doRun(NioEndpoint.java:1594)
at
org.apache.tomcat.util.net.SocketProcessorBase.run(SocketProcessorBase.java:49)
at
java.base/java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1128)
at
java.base/java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:628)
at
org.apache.tomcat.util.threads.TaskThread$WrappingRunnable.run(TaskThread.java:61)
at
java.base/java.lang.Thread.run(Thread.java:834)

```

DestroyedByBorrowValidationCount	0
DestroyedByEvictorCount	0
DestroyedCount	0
FactoryType	org.apache.tomcat.dbcp.dbcp2.PoolableConnectionFactory<org.apache.tomcat.dbcp.dbcp2.PoolableConnection>
Fairness	false
Lifo	true
LogAbandoned	false
MaxBorrowWaitTimeMillis	50
MaxIdle	10
MaxTotal	100
MaxWaitMillis	30 000
MeanActiveTimeMillis	0
MeanBorrowWaitTimeMillis	0
MeanIdleTimeMillis	187
MinEvictableIdleTimeMillis	1 800 000
MinIdle	0
NumActive	7
NumIdle	5
NumTestsPerEvictionRun	3
NumWaiters	0
RemoveAbandonedOnBorrow	false
RemoveAbandonedOnMaintenance	false
RemoveAbandonedTimeout	2 147 483 647
ReturnedCount	34 301
TestOnBorrow	true
TestOnCreate	false
TestOnReturn	false
TestWhileIdle	false
TimeBetweenEvictionRunsMillis	-1

host=localhost,context=/demo,class=javax.sql.DataSource,name="jdbc/demo_javamelody",connectionpool=connections,connection=1

AutoCommit	false
CacheState	true
Catalog	H2
Closed	false
Holdability	1
ReadOnly	false
Schema	PUBLIC
ToString	624369456, URL=jdbc:h2:/opt/data/demo/h2, UserName=SA, H2 JDBC Driver
TransactionIsolation	2

host=localhost,context=/demo,class=javax.sql.DataSource,name="jdbc/demo_javamelody",connectionpool=connections,connection=10

AutoCommit	false
CacheState	true
Catalog	H2
Closed	false
Holdability	1
ReadOnly	false
Schema	PUBLIC
ToString	1830274022, URL=jdbc:h2:/opt/data/demo/h2, UserName=SA, H2 JDBC Driver
TransactionIsolation	2

host=localhost,context=/demo,class=javax.sql.DataSource,name="jdbc/demo_javamelody",connectionpool=connections,connection=11

CacheState	true
Closed	true
ToString	573234594, URL=jdbc:h2:/opt/data/demo/h2, UserName=SA, H2 JDBC Driver

host=localhost,context=/demo,class=javax.sql.DataSource,name="jdbc/demo_javamelody",connectionpool=connections,connection=12

CacheState	true
Closed	true
ToString	1001749773, URL=jdbc:h2:/opt/data/demo/h2, UserName=SA, H2 JDBC Driver

host=localhost,context=/demo,class=javax.sql.DataSource,name="jdbc/demo_javamelody",connectionpool=connections,connection=2

AutoCommit	false
CacheState	true
Catalog	H2
Closed	false
Holdability	1
ReadOnly	false
Schema	PUBLIC
ToString	350738318, URL=jdbc:h2:/opt/data/demo/h2, UserName=SA, H2 JDBC Driver
TransactionIsolation	2

```
host=localhost,context=/demo,class=javax.sql.DataSource,name="jdbc/demo_javamelody",connectionpool=connections,connection=3
AutoCommit                false
CacheState                 true
Catalog                   H2
Closed                    false
Holdability                1
ReadOnly                  false
Schema                    PUBLIC
ToString                  433765637, URL=jdbc:h2:/opt/data/demo/h2, UserName=SA, H2
                           JDBC Driver
TransactionIsolation       2
```

```
host=localhost,context=/demo,class=javax.sql.DataSource,name="jdbc/demo_javamelody",connectionpool=connections,connection=4
AutoCommit                false
CacheState                 true
Catalog                   H2
Closed                    false
Holdability                1
ReadOnly                  false
Schema                    PUBLIC
ToString                  1093355932, URL=jdbc:h2:/opt/data/demo/h2, UserName=SA, H2
                           JDBC Driver
TransactionIsolation       2
```

```
host=localhost,context=/demo,class=javax.sql.DataSource,name="jdbc/demo_javamelody",connectionpool=connections,connection=5
CacheState                 true
Closed                    true
ToString                  460349393, URL=jdbc:h2:/opt/data/demo/h2, UserName=SA, H2
                           JDBC Driver
```

```
host=localhost,context=/demo,class=javax.sql.DataSource,name="jdbc/demo_javamelody",connectionpool=connections,connection=6
CacheState                 true
Closed                    true
ToString                  1204544911, URL=jdbc:h2:/opt/data/demo/h2, UserName=SA, H2
                           JDBC Driver
```

```
host=localhost,context=/demo,class=javax.sql.DataSource,name="jdbc/demo_javamelody",connectionpool=connections,connection=7
AutoCommit                false
CacheState                 true
Catalog                   H2
Closed                    false
Holdability                1
ReadOnly                  false
Schema                    PUBLIC
ToString                  2088016940, URL=jdbc:h2:/opt/data/demo/h2, UserName=SA, H2
                           JDBC Driver
TransactionIsolation       2
```

```
host=localhost,context=/demo,class=javax.sql.DataSource,name="jdbc/demo_javamelody",connectionpool=connections,connection=8
AutoCommit                false
CacheState                 true
Catalog                   H2
Closed                    false
Holdability                1
ReadOnly                  false
Schema                    PUBLIC
ToString                  1973103755, URL=jdbc:h2:/opt/data/demo/h2, UserName=SA, H2
                           JDBC Driver
TransactionIsolation       2
```

```
host=localhost,context=/demo,class=javax.sql.DataSource,name="jdbc/demo_javamelody",connectionpool=connections,connection=9
CacheState                 true
Closed                    true
ToString                  644919127, URL=jdbc:h2:/opt/data/demo/h2, UserName=SA, H2
                           JDBC Driver
```

Deployer

host=localhost

(Startup event listener for a Host that configures the properties of that Host, and the associated defined contexts)

className	org.apache.catalina.startup.HostConfig	(Fully qualified class name of the managed object)
configBaseName	/opt/apache-tomcat-9.0.33/conf/Catalina/localhost	(The base directory for Context configuration files)
contextClass	org.apache.catalina.core.StandardContext	(The Java class name of the Context implementation we should use)
copyXML	false	(The copy XML config file flag for this component)
deployXML	true	(The deploy XML config file flag for this component)
modelerType	org.apache.catalina.startup.HostConfig	(Type of the modeled resource. Can be set only once)
unpackWARs	false	(The unpack WARs flag)

Engine

(Standard Engine Component)

backgroundProcessorDelay	10	(The processor delay for this component.)
catalinaBase	/opt/apache-tomcat-9.0.33	(Base (instance) directory for this Engine, typically same as catalina.base system property)
defaultHost	localhost	(Name of the default Host for this Engine)
jvmRoute	null	(Route used for load balancing)
managedResource	StandardEngine[Catalina]	(The managed resource this MBean is associated with)
modelerType	org.apache.catalina.core.StandardEngine	(Type of the modeled resource. Can be set only once)
name	Catalina	(Unique name of this Engine)
realm	LockOutRealm[StandardEngine[Catalina]]	(Associated realm.)
startChildren	true	(Will children be started automatically when they are added.)
startStopThreads	1	(The number of threads to use when starting and stopping child Hosts)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

Filter

WebModule=//localhost/,name=Tomcat WebSocket (JSR356) Filter,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet-filter definition)

filterClass	org.apache.tomcat.websocket.server.WsFilter	(Fully qualified class name of the filter object)
filterInitParameterMap	{}	(Return the initialization parameters associated with this filter)
filterName	Tomcat WebSocket (JSR356) Filter	(The name used to reference the filter in web.xml)
modelerType	org.apache.catalina.core.ApplicationFilterConfig	(Type of the modeled resource. Can be set only once)

WebModule=//localhost/demo,name=Tomcat WebSocket (JSR356) Filter,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet-filter definition)

filterClass	org.apache.tomcat.websocket.server.WsFilter	(Fully qualified class name of the filter object)
filterInitParameterMap	{}	(Return the initialization parameters associated with this filter)
filterName	Tomcat WebSocket (JSR356) Filter	(The name used to reference the filter in web.xml)
modelerType	org.apache.catalina.core.ApplicationFilterConfig	(Type of the modeled resource. Can be set only once)

WebModule=//localhost/demo,name=forbiddenActions,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet-filter definition)

filterClass	ForbiddenActionsFilter	(Fully qualified class name of the filter object)
filterInitParameterMap	{}	(Return the initialization parameters associated with this filter)
filterName	forbiddenActions	(The name used to reference the filter in web.xml)
modelerType	org.apache.catalina.core.ApplicationFilterConfig	(Type of the modeled resource. Can be set only once)

WebModule=//localhost/demo,name=httpSessionInThread,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet-filter definition)

filterClass	fr.sp4j.filter.HttpSessionFilter	(Fully qualified class name of the filter object)
filterInitParameterMap	{}	(Return the initialization parameters associated with this filter)
filterName	httpSessionInThread	(The name used to reference the filter in web.xml)
modelerType	org.apache.catalina.core.ApplicationFilterConfig	(Type of the modeled resource. Can be set only once)

WebModule=//localhost/demo,name=javamelody,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet-filter definition)

filterClass	net.bull.javamelody.MonitoringFilter	(Fully qualified class name of the filter object)
filterInitParameterMap	{}	(Return the initialization parameters associated with this filter)
filterName	javamelody	(The name used to reference the filter in web.xml)
modelerType	org.apache.catalina.core.ApplicationFilterConfig	(Type of the modeled resource. Can be set only once)

WebModule=//localhost/demo,name=monitoring,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet-filter definition)

filterClass	net.bull.javamelody.MonitoringFilter	(Fully qualified class name of the filter object)
filterInitParameterMap	{}	(Return the initialization parameters associated with this filter)
filterName	monitoring	(The name used to reference the filter in web.xml)
modelerType	org.apache.catalina.core.ApplicationFilterConfig	(Type of the modeled resource. Can be set only once)

WebModule=//localhost/demo,name=remoteUser,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet-filter definition)

filterClass	fr.sp4j.lib.security.RemoteUserFilter	(Fully qualified class name of the filter object)
filterInitParameterMap	{}	(Return the initialization parameters associated with this filter)
filterName	remoteUser	(The name used to reference the filter in web.xml)
modelerType	org.apache.catalina.core.ApplicationFilterConfig	(Type of the modeled resource. Can be set only once)

WebModule=//localhost/downloads,name=Tomcat WebSocket (JSR356) Filter,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet-filter definition)

filterClass	org.apache.tomcat.websocket.server.WsFilter	(Fully qualified class name of the filter object)
filterInitParameterMap	{}	(Return the initialization parameters associated with this filter)
filterName	Tomcat WebSocket (JSR356) Filter	(The name used to reference the filter in web.xml)
modelerType	org.apache.catalina.core.ApplicationFilterConfig	(Type of the modeled resource. Can be set only once)

WebModule=//localhost/usage,name=Tomcat WebSocket (JSR356) Filter,J2EEApplication=none,J2EEServer=none

Monitoring JavaMelody sur /demo_vps363300.ovh.net

(Wrapper that represents an individual servlet-filter definition)

filterClass	org.apache.tomcat.websocket.server.WsFilter	(Fully qualified class name of the filter object)
filterInitParameterMap	{}	(Return the initialization parameters associated with this filter)
filterName	Tomcat WebSocket (JSR356) Filter	(The name used to reference the filter in web.xml)
modelerType	org.apache.catalina.core.ApplicationFilterConfig	(Type of the modeled resource. Can be set only once)

WebModule=//localhost/usage,name=basic-auth,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet-filter definition)

filterClass	net.bull.javamelody.usagestats.BasicAuthFilter	(Fully qualified class name of the filter object)
filterInitParameterMap	{}	(Return the initialization parameters associated with this filter)
filterName	basic-auth	(The name used to reference the filter in web.xml)
modelerType	org.apache.catalina.core.ApplicationFilterConfig	(Type of the modeled resource. Can be set only once)

WebModule=//localhost/usage,name=gzip,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet-filter definition)

filterClass	net.bull.javamelody.usagestats.GzipFilter	(Fully qualified class name of the filter object)
filterInitParameterMap	{}	(Return the initialization parameters associated with this filter)
filterName	gzip	(The name used to reference the filter in web.xml)
modelerType	org.apache.catalina.core.ApplicationFilterConfig	(Type of the modeled resource. Can be set only once)

WebModule=//localhost/usage,name=javamelody,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet-filter definition)

filterClass	net.bull.javamelody.MonitoringFilter	(Fully qualified class name of the filter object)
filterInitParameterMap	{}	(Return the initialization parameters associated with this filter)
filterName	javamelody	(The name used to reference the filter in web.xml)
modelerType	org.apache.catalina.core.ApplicationFilterConfig	(Type of the modeled resource. Can be set only once)

GlobalRequestProcessor

name="http-nio-80"

(Runtime information of a group of requests)

bytesReceived	66 757	(Amount of data received, in bytes)
bytesSent	3 232 721 422	(Amount of data sent, in bytes)
errorCount	67 213	(Number of errors)
maxTime	102 701	(Maximum time to process a request)
modelerType	org.apache.coyote.RequestGroupInfo	(Type of the modeled resource. Can be set only once)
processingTime	50 343 065	(Total time to process the requests)
requestCount	23 894 626	(Number of requests processed)

Host

host=localhost

(Standard Host Component)

aliases	[]	(Host aliases)
appBase	webapps	(The application root for this Host)
autoDeploy	true	(The auto deploy flag for this Host)
backgroundProcessorDelay	-1	(The processor delay for this component.)
children	[Catalina:j2eeType=WebModule,name=//localhost/,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=WebModule,name=//localhost/downloads,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=WebModule,name=//localhost/demo,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=WebModule,name=//localhost/usage,J2EEApplication=none,J2EEServer=none]	(Object names of all children)
configClass	org.apache.catalina.startup.ContextConfig	(The configuration class for contexts)
contextClass	org.apache.catalina.core.StandardContext	(The Java class name of the default Context implementation class for deployed web applications.)
copyXML	false	(Should XML files be copied to \$CATALINA_BASE/conf/{engine}/{host} by default when a web application is deployed?)
createDirs	true	(Should we create directories upon startup for appBase and xmlBase?)
deployIgnore	null	(Paths within appBase ignored for automatic deployment)
deployOnStartup	true	(The deploy on startup flag for this Host)
deployXML	true	(deploy Context XML config files property)
errorReportValveClass	org.apache.catalina.valves.ErrorReportValve	(The Java class name of the default error reporter implementation class for deployed web applications.)
managedResource	StandardEngine[Catalina].StandardHost[localhost]	(The managed resource this MBean is associated with)
modelerType	org.apache.catalina.core.StandardHost	(Type of the modeled resource. Can be set only once)
name	localhost	(Unique name of this Host)
realm	LockOutRealm[StandardEngine[Catalina]]	(Associated realm.)
startChildren	true	(Will children be started automatically when they are added?)
startStopThreads	1	(The number of threads to use when starting, stopping and deploying child Contexts)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
undeployOldVersions	false	(Determines if old versions of applications deployed using parallel deployment are automatically undeployed when no longer used. Requires autoDeploy to be enabled.)
unpackWARs	false	(Unpack WARs property)
valveNames	[Catalina:type=Valve,host=localhost,name=AccessLogValve, Catalina:type=Valve,host=localhost,name=ErrorReportValve, Catalina:type=Valve,host=localhost,name=StandardHostValve]	(Return the MBean Names of the Valves associated with this Host)
workDir	null	(Work Directory base for applications)
xmlBase	null	(The XML root for this Host.)

JspMonitor

WebModule=//localhost/,name=jsp,J2EEApplication=none,J2EEServer=none

(JSP Monitoring)

jspCount	1	(The number of JSPs that have been loaded into a webapp)
jspQueueLength	-1	(The length of the JSP queue (if enabled via maxLoadedJsps))
jspReloadCount	0	(The number of JSPs that have been reloaded)
jspUnloadCount	0	(The number of JSPs that have been unloaded)
modelerType	org.apache.jasper.servlet.JspServlet	(Type of the modeled resource. Can be set only once)

WebModule=//localhost/demo,name=jsp,J2EEApplication=none,J2EEServer=none

(JSP Monitoring)

jspCount	1	(The number of JSPs that have been loaded into a webapp)
jspQueueLength	-1	(The length of the JSP queue (if enabled via maxLoadedJsps))
jspReloadCount	0	(The number of JSPs that have been reloaded)
jspUnloadCount	0	(The number of JSPs that have been unloaded)
modelerType	org.apache.jasper.servlet.JspServlet	(Type of the modeled resource. Can be set only once)

WebModule=//localhost/downloads,name=jsp,J2EEApplication=none,J2EEServer=none

(JSP Monitoring)

jspCount	0	(The number of JSPs that have been loaded into a webapp)
jspQueueLength	-1	(The length of the JSP queue (if enabled via maxLoadedJsps))
jspReloadCount	0	(The number of JSPs that have been reloaded)
jspUnloadCount	0	(The number of JSPs that have been unloaded)
modelerType	org.apache.jasper.servlet.JspServlet	(Type of the modeled resource. Can be set only once)

WebModule=//localhost/usage,name=jsp,J2EEApplication=none,J2EEServer=none

(JSP Monitoring)

jspCount	1	(The number of JSPs that have been loaded into a webapp)
jspQueueLength	-1	(The length of the JSP queue (if enabled via maxLoadedJsps))
jspReloadCount	0	(The number of JSPs that have been reloaded)
jspUnloadCount	0	(The number of JSPs that have been unloaded)
modelerType	org.apache.jasper.servlet.JspServlet	(Type of the modeled resource. Can be set only once)

Loader

host=localhost,context=/

(ClassLoader implementation which is specialized for handling web applications)

className	org.apache.catalina.loader.WebappLoader	(Fully qualified class name of the managed object)
delegate	false	(The 'follow standard delegation model' flag that will be used to configure our ClassLoader)
loaderRepositories	[]	(Repositories set in the real loader)
loaderRepositoriesString		(Repositories set in the real loader)
modelerType	org.apache.catalina.loader.WebappLoader	(Type of the modeled resource. Can be set only once)
reloadable	false	(The reloadable flag for this Loader)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

host=localhost,context=/demo

(ClassLoader implementation which is specialized for handling web applications)

className	org.apache.catalina.loader.WebappLoader	(Fully qualified class name of the managed object)
delegate	false	(The 'follow standard delegation model' flag that will be used to configure our ClassLoader)

loaderRepositories	<pre>[war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/classes, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdocreport.core-1.0.4.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/ehcache-core-2.6.8.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/log4j-1.2.17.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/spi4j-lib-security-server-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/slf4j-api-1.6.1.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/jta-1.1.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdocreport.template.freemarker-1.0.4.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/xpp3_min-1.1.4c.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/gwt-servlet-2.7.0.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/spi4j-gwt-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdocreport.document-1.0.4.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/itext-2.1.7.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdocreport.template-1.0.4.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/freemarker-2.3.16.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdocreport.converter-1.0.4.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/validation-api-1.0.0.GA.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/appwhite1-commons-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdocreport.document.docx-1.0.4.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/spi4j-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/robin-1.5.9.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdocreport.document.odt-1.0.4.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/spi4j-ui-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/javamelody-core-1.98.0.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/spi4j-doc-report-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdocreport.document.pptx-1.0.4.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/spi4j-lib-security-commons-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/appwhite1-server-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/referentiel-server-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/h2-1.4.200.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/xstream-1.4.11.1.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/referentiel-commons-1.7-SNAPSHOT.jar]</pre>	(Repositories set in the real loader)
loaderRepositoriesString	<pre>war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/classes:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdocreport.core-1.0.4.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/ehcache-core-2.6.8.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/log4j-1.2.17.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/spi4j-lib-security-server-1.7-SNAPSHOT.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/slf4j-api-1.6.1.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/jta-1.1.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdocreport.template.freemarker-1.0.4.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/xpp3_min-1.1.4c.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/gwt-servlet-2.7.0.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/spi4j-gwt-1.7-SNAPSHOT.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdocreport.document-1.0.4.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/itext-2.1.7.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdocreport.template-1.0.4.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/freemarker-2.3.16.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdocreport.converter-1.0.4.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/validation-api-1.0.0.GA.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/appwhite1-commons-1.7-SNAPSHOT.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdocreport.document.docx-1.0.4.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/spi4j-1.7-SNAPSHOT.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/robin-1.5.9.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdocreport.document.odt-1.0.4.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/spi4j-ui-1.7-SNAPSHOT.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/javamelody-core-1.98.0.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/spi4j-doc-report-1.7-SNAPSHOT.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdocreport.document.pptx-1.0.4.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/spi4j-lib-security-commons-1.7-SNAPSHOT.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/appwhite1-server-1.7-SNAPSHOT.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/referentiel-server-1.7-SNAPSHOT.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/h2-1.4.200.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/xstream-1.4.11.1.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/referentiel-commons-1.7-SNAPSHOT.jar:</pre>	(Repositories set in the real loader)
modelerType	org.apache.catalina.loader.WebappLoader	(Type of the modeled resource. Can be set only once)
reloadable	false	(The reloadable flag for this Loader)

stateName STARTED (The name of the LifecycleState that this component is currently in)

host=localhost,context=/downloads

(ClassLoader implementation which is specialized for handling web applications)

className	org.apache.catalina.loader.WebappLoader	(Fully qualified class name of the managed object)
delegate	false	(The 'follow standard delegation model' flag that will be used to configure our ClassLoader)
loaderRepositories	[]	(Repositories set in the real loader)
loaderRepositoriesString		(Repositories set in the real loader)
modelerType	org.apache.catalina.loader.WebappLoader	(Type of the modeled resource. Can be set only once)
reloadable	false	(The reloadable flag for this Loader)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

host=localhost,context=/usage

(ClassLoader implementation which is specialized for handling web applications)

className	org.apache.catalina.loader.WebappLoader	(Fully qualified class name of the managed object)
delegate	false	(The 'follow standard delegation model' flag that will be used to configure our ClassLoader)
loaderRepositories	[war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/classes;war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/itext-2.1.7.jar;war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/commons-csv-1.10.0.jar;war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/log4j-1.2.17.jar;war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/jrobin-1.5.9.jar;war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/geoip-api-1.3.1.jar;war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/gson-2.10.1.jar;war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/javamelody-core-1.98.0.jar]	(Repositories set in the real loader)
loaderRepositoriesString	war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/classes;war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/itext-2.1.7.jar;war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/commons-csv-1.10.0.jar;war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/log4j-1.2.17.jar;war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/jrobin-1.5.9.jar;war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/geoip-api-1.3.1.jar;war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/gson-2.10.1.jar;war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/javamelody-core-1.98.0.jar;	(Repositories set in the real loader)
modelerType	org.apache.catalina.loader.WebappLoader	(Type of the modeled resource. Can be set only once)
reloadable	false	(The reloadable flag for this Loader)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

MBeanFactory

(Factory for MBeans and corresponding components)

modelerType	org.apache.catalina.mbeans.MBeanFactory	(Type of the modeled resource. Can be set only once)
-------------	---	--

Manager

host=localhost,context=/

(Standard implementation of the Manager interface)

activeSessions	5	(Number of active sessions at this moment)
className	org.apache.catalina.session.StandardManager	(Fully qualified class name of the managed object)
duplicates	0	(Number of duplicated session ids generated)
expiredSessions	12 211	(Number of sessions that expired (doesn't include explicit invalidations))
jvmRoute	null	(Retrieve the JvmRoute for the enclosing Engine)
maxActive	45	(Maximum number of active sessions so far)
maxActiveSessions	-1	(The maximum number of active Sessions allowed, or -1 for no limit)
modelerType	org.apache.catalina.session.StandardManager	(Type of the modeled resource. Can be set only once)
name	StandardManager	(The descriptive name of this Manager implementation (for logging))
pathname	SESSIONS.ser	(Path name of the disk file in which active sessions)
persistAuthentication	false	(Indicates whether sessions shall persist authentication information when being persisted (e.g. across application restarts).)
processExpiresFrequency	6	(The frequency of the manager checks (expiration and passivation))
processingTime	2 641	(Time spent doing housekeeping and expiration)
rejectedSessions	0	(Number of sessions we rejected due to maxActive being reached)
secureRandomAlgorithm	SHA1PRNG	(The secure random number generator algorithm name)
secureRandomClass	null	(The secure random number generator class name)
secureRandomProvider	null	(The secure random number generator provider name)
sessionAttributeNameFilter	null	(The string pattern used for including session attributes in distribution. Null means all attributes are included.)
sessionAttributeValueClassNameFilter	null	(The regular expression used to filter session attributes based on the implementation class of the value. The regular expression is anchored and must match the fully qualified class name.)
sessionAverageAliveTime	18	(Average time an expired session had been alive)
sessionCounter	12 216	(Total number of sessions created by this manager)
sessionCreateRate	0	(Session creation rate in sessions per minute)
sessionExpireRate	0	(Session expiration rate in sessions per minute)
sessionMaxAliveTime	3 240	(Longest time an expired session had been alive)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
warnOnSessionAttributeFilterFailure	false	(Should a WARN level log message be generated if a session attribute fails to match sessionAttributeNameFilter or sessionAttributeValueClassNameFilter?)

host=localhost,context=/demo

(Standard implementation of the Manager interface)

activeSessions	57	(Number of active sessions at this moment)
className	org.apache.catalina.session.StandardManager	(Fully qualified class name of the managed object)
duplicates	0	(Number of duplicated session ids generated)
expiredSessions	92 850	(Number of sessions that expired (doesn't include explicit invalidations))
jvmRoute	null	(Retrieve the JvmRoute for the enclosing Engine)
maxActive	646	(Maximum number of active sessions so far)
maxActiveSessions	-1	(The maximum number of active Sessions allowed, or -1 for no limit)
modelerType	org.apache.catalina.session.StandardManager	(Type of the modeled resource. Can be set only once)
name	StandardManager	(The descriptive name of this Manager implementation (for logging))
pathname	SESSIONS.ser	(Path name of the disk file in which active sessions)
persistAuthentication	false	(Indicates whether sessions shall persist authentication information when being persisted (e.g. across application restarts).)
processExpiresFrequency	6	(The frequency of the manager checks (expiration and passivation))
processingTime	4 678	(Time spent doing housekeeping and expiration)
rejectedSessions	0	(Number of sessions we rejected due to maxActive being reached)
secureRandomAlgorithm	SHA1PRNG	(The secure random number generator algorithm name)
secureRandomClass	null	(The secure random number generator class name)
secureRandomProvider	null	(The secure random number generator provider name)
sessionAttributeNameFilter	null	(The string pattern used for including session attributes in distribution. Null means all attributes are included.)
sessionAttributeValueClassNameFilter	null	(The regular expression used to filter session attributes based on the implementation class of the value. The regular expression is anchored and must match the fully qualified class name.)
sessionAverageAliveTime	18	(Average time an expired session had been alive)
sessionCounter	92 907	(Total number of sessions created by this manager)
sessionCreateRate	1	(Session creation rate in sessions per minute)
sessionExpireRate	1	(Session expiration rate in sessions per minute)
sessionMaxAliveTime	3 753	(Longest time an expired session had been alive)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
warnOnSessionAttributeFilterFailure	false	(Should a WARN level log message be generated if a session attribute fails to match sessionAttributeNameFilter or sessionAttributeValueClassNameFilter?)

host=localhost,context=/downloads

(Standard implementation of the Manager interface)

activeSessions	0	(Number of active sessions at this moment)
className	org.apache.catalina.session.StandardManager	(Fully qualified class name of the managed object)
duplicates	0	(Number of duplicated session ids generated)
expiredSessions	0	(Number of sessions that expired (doesn't include explicit invalidations))
jvmRoute	null	(Retrieve the JvmRoute for the enclosing Engine)
maxActive	0	(Maximum number of active sessions so far)
maxActiveSessions	-1	(The maximum number of active Sessions allowed, or -1 for no limit)
modelerType	org.apache.catalina.session.StandardManager	(Type of the modeled resource. Can be set only once)
name	StandardManager	(The descriptive name of this Manager implementation (for logging))
pathname	SESSIONS.ser	(Path name of the disk file in which active sessions)
persistAuthentication	false	(Indicates whether sessions shall persist authentication information when being persisted (e.g. across application restarts).)
processExpiresFrequency	6	(The frequency of the manager checks (expiration and passivation))
processingTime	95	(Time spent doing housekeeping and expiration)
rejectedSessions	0	(Number of sessions we rejected due to maxActive being reached)
secureRandomAlgorithm	SHA1PRNG	(The secure random number generator algorithm name)
secureRandomClass	null	(The secure random number generator class name)
secureRandomProvider	null	(The secure random number generator provider name)
sessionAttributeNameFilter	null	(The string pattern used for including session attributes in distribution. Null means all attributes are included.)
sessionAttributeValueClassNameFilter	null	(The regular expression used to filter session attributes based on the implementation class of the value. The regular expression is anchored and must match the fully qualified class name.)
sessionAverageAliveTime	0	(Average time an expired session had been alive)
sessionCounter	0	(Total number of sessions created by this manager)
sessionCreateRate	0	(Session creation rate in sessions per minute)
sessionExpireRate	0	(Session expiration rate in sessions per minute)
sessionMaxAliveTime	0	(Longest time an expired session had been alive)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
warnOnSessionAttributeFilterFailure	false	(Should a WARN level log message be generated if a session attribute fails to match sessionAttributeNameFilter or sessionAttributeValueClassNameFilter?)

host=localhost,context=/usage

(Standard implementation of the Manager interface)

activeSessions	0	(Number of active sessions at this moment)
className	org.apache.catalina.session.StandardManager	(Fully qualified class name of the managed object)
duplicates	0	(Number of duplicated session ids generated)
expiredSessions	3	(Number of sessions that expired (doesn't include explicit invalidations))
jvmRoute	null	(Retrieve the JvmRoute for the enclosing Engine)
maxActive	1	(Maximum number of active sessions so far)
maxActiveSessions	-1	(The maximum number of active Sessions allowed, or -1 for no limit)
modelerType	org.apache.catalina.session.StandardManager	(Type of the modeled resource. Can be set only once)
name	StandardManager	(The descriptive name of this Manager implementation (for logging))

pathname	SESSIONS.ser	(Path name of the disk file in which active sessions)
persistAuthentication	false	(Indicates whether sessions shall persist authentication information when being persisted (e.g. across application restarts).)
processExpiresFrequency	6	(The frequency of the manager checks (expiration and passivation))
processingTime	70	(Time spent doing housekeeping and expiration)
rejectedSessions	0	(Number of sessions we rejected due to maxActive being reached)
secureRandomAlgorithm	SHA1PRNG	(The secure random number generator algorithm name)
secureRandomClass	null	(The secure random number generator class name)
secureRandomProvider	null	(The secure random number generator provider name)
sessionAttributeNameFilter	null	(The string pattern used for including session attributes in distribution. Null means all attributes are included.)
sessionAttributeValueClassNameFilter	null	(The regular expression used to filter session attributes based on the implementation class of the value. The regular expression is anchored and must match the fully qualified class name.)
sessionAverageAliveTime	614	(Average time an expired session had been alive)
sessionCounter	3	(Total number of sessions created by this manager)
sessionCreateRate	0	(Session creation rate in sessions per minute)
sessionExpireRate	0	(Session expiration rate in sessions per minute)
sessionMaxAliveTime	1 897	(Longest time an expired session had been alive)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
warnOnSessionAttributeFilterFailure	false	(Should a WARN level log message be generated if a session attribute fails to match sessionAttributeNameFilter or sessionAttributeValueClassNameFilter?)

Mapper

(Maps requests received by the associated connector to Hosts, Contexts and Wrappers)

modelerType	org.apache.catalina.mapper.MapperListener	(Type of the modeled resource. Can be set only once)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

NamingResources

(Holds and manages the naming resources defined in the J2EE Enterprise Naming Context and their associated JNDI context)

container	StandardServer[8005]	(The container with which the naming resources are associated.)
environments	[]	(MBean Names of the set of defined environment entries for this web application)
modelerType	org.apache.catalina.deploy.NamingResourcesImpl	(Type of the modeled resource. Can be set only once)
resourceLinks	[]	(MBean Names of all the defined resource link references for this application.)

host=localhost,context=/

(Holds and manages the naming resources defined in the J2EE Enterprise Naming Context and their associated JNDI context)

container	StandardEngine[Catalina].StandardHost[localhost].StandardContext[]	(The container with which the naming resources are associated.)
environments	[]	(MBean Names of the set of defined environment entries for this web application)
modelerType	org.apache.catalina.deploy.NamingResourcesImpl	(Type of the modeled resource. Can be set only once)
resourceLinks	[]	(MBean Names of all the defined resource link references for this application.)
resources	[]	(MBean Names of all the defined resource references for this application.)

host=localhost,context=/demo

(Holds and manages the naming resources defined in the J2EE Enterprise Naming Context and their associated JNDI context)

container	StandardEngine[Catalina].StandardHost[localhost].StandardContext[/demo]	(The container with which the naming resources are associated.)
environments	[]	(MBean Names of the set of defined environment entries for this web application)
modelerType	org.apache.catalina.deploy.NamingResourcesImpl	(Type of the modeled resource. Can be set only once)
resourceLinks	[]	(MBean Names of all the defined resource link references for this application.)

host=localhost,context=/downloads

(Holds and manages the naming resources defined in the J2EE Enterprise Naming Context and their associated JNDI context)

container	StandardEngine[Catalina].StandardHost[localhost].StandardContext[/downloads]	(The container with which the naming resources are associated.)
environments	[]	(MBean Names of the set of defined environment entries for this web application)
modelerType	org.apache.catalina.deploy.NamingResourcesImpl	(Type of the modeled resource. Can be set only once)
resourceLinks	[]	(MBean Names of all the defined resource link references for this application.)
resources	[]	(MBean Names of all the defined resource references for this application.)

host=localhost,context=/usage

(Holds and manages the naming resources defined in the J2EE Enterprise Naming Context and their associated JNDI context)

container	StandardEngine[Catalina].StandardHost[localhost].StandardContext[/usage]	(The container with which the naming resources are associated.)
environments	[]	(MBean Names of the set of defined environment entries for this web application)
modelerType	org.apache.catalina.deploy.NamingResourcesImpl	(Type of the modeled resource. Can be set only once)
resourceLinks	[]	(MBean Names of all the defined resource link references for this application.)
resources	[]	(MBean Names of all the defined resource references for this application.)

ParallelWebappClassLoader

host=localhost,context=/

(ClassLoader implementation which is specialized for handling web applications and is capable of loading classes in parallel)

URLs	[]	(The URLs of this loader)
className	org.apache.catalina.loader.ParallelWebappClassLoader	(Fully qualified class name of the managed object)
contextName	ROOT	(Name of the webapp context)
delegate	false	(The 'follow standard delegation model' flag that will be used to configure our ClassLoader)
modelerType	org.apache.catalina.loader.ParallelWebappClassLoader	(Type of the modeled resource. Can be set only once)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

host=localhost,context=/demo

(ClassLoader implementation which is specialized for handling web applications and is capable of loading classes in parallel)

URLs	[war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/classes/, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdocreport.core-1.0.4.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/ehcache-core-2.6.8.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/log4j-1.2.17.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/spi4j-lib-security-server-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/slf4j-api-1.6.1.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/jta-1.1.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdocreport.template.freemarker-1.0.4.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/xpp3_min-1.1.4c.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/gwt-servlet-2.7.0.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/spi4j-gwt-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdocreport.document-1.0.4.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/text-2.1.7.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdocreport.template-1.0.4.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/freemarker-2.3.16.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdocreport.converter-1.0.4.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/validation-api-1.0.0.GA.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/appwhite1-commons-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdocreport.document.docx-1.0.4.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/spi4j-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/robin-1.5.9.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdocreport.document.odt-1.0.4.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/spi4j-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/javamelody-core-1.98.0.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/spi4j-doc-report-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdocreport.document.pptx-1.0.4.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/spi4j-lib-security-commons-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/appwhite1-server-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/referentiel-server-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/h2-1.4.200.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/xstream-1.4.11.1.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/referentiel-commons-1.7-SNAPSHOT.jar]	(The URLs of this loader)
className	org.apache.catalina.loader.ParallelWebappClassLoader	(Fully qualified class name of the managed object)
contextName	demo	(Name of the webapp context)
delegate	false	(The 'follow standard delegation model' flag that will be used to configure our ClassLoader)
modelerType	org.apache.catalina.loader.ParallelWebappClassLoader	(Type of the modeled resource. Can be set only once)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

host=localhost,context=/downloads

(ClassLoader implementation which is specialized for handling web applications and is capable of loading classes in parallel)

URLs	[]	(The URLs of this loader)
className	org.apache.catalina.loader.ParallelWebappClassLoader	(Fully qualified class name of the managed object)
contextName	downloads	(Name of the webapp context)
delegate	false	(The 'follow standard delegation model' flag that will be used to configure our ClassLoader)
modelerType	org.apache.catalina.loader.ParallelWebappClassLoader	(Type of the modeled resource. Can be set only once)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

host=localhost,context=/usage

(ClassLoader implementation which is specialized for handling web applications and is capable of loading classes in parallel)

URLs	[war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/classes/, war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/text-2.1.7.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/commons-csv-1.10.0.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/log4j-1.2.17.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/robin-1.5.9.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/geoip-api-1.3.1.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/gson-2.10.1.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/javamelody-core-1.98.0.jar]	(The URLs of this loader)
className	org.apache.catalina.loader.ParallelWebappClassLoader	(Fully qualified class name of the managed object)

contextName	usage	(Name of the webapp context)
delegate	false	(The 'follow standard delegation model' flag that will be used to configure our ClassLoader)
modelerType	org.apache.catalina.loader.ParallelWebappClassLoader	(Type of the modeled resource. Can be set only once)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

ProtocolHandler

port=80

acceptCount	100	(Inspected attribute acceptCount)
acceptorThreadCount	1	(Inspected attribute acceptorThreadCount)
acceptorThreadPriority	5	(Inspected attribute acceptorThreadPriority)
algorithm	SunX509	(Inspected attribute algorithm)
allowHostHeaderMismatch	false	(Inspected attribute allowHostHeaderMismatch)
allowedTrailerHeaders		(Inspected attribute allowedTrailerHeaders)
aprRequired	false	(Inspected attribute aprRequired)
ciphers	HIGH:!aNULL:!eNULL:!EXPORT:!DES:!RC4:!MD5:!kRSA	(Inspected attribute ciphers)
clientAuth	NONE	(Inspected attribute clientAuth)
clientCertProvider	null	(Inspected attribute clientCertProvider)
compressibleMimeType	text/html,text/xml,text/plain,text/css,text/javascript,application/javascript,application/json,application/xml	(Inspected attribute compressibleMimeType)
compressibleMimeTypes	[text/html, text/xml, text/plain, text/css, text/javascript, application/javascript, application/json, application/xml]	(Inspected attribute compressibleMimeTypes)
compression	off	(Inspected attribute compression)
compressionMinSize	2 048	(Inspected attribute compressionMinSize)
connectionCount	126	(Inspected attribute connectionCount)
connectionLinger	-1	(Inspected attribute connectionLinger)
connectionTimeout	20 000	(Inspected attribute connectionTimeout)
connectionUploadTimeout	300 000	(Inspected attribute connectionUploadTimeout)
crlFile	null	(Inspected attribute crlFile)
defaultSSLHostConfigName	_default_	(Inspected attribute defaultSSLHostConfigName)
disableUploadTimeout	true	(Inspected attribute disableUploadTimeout)
domain	Catalina	(Inspected attribute domain)
keepAliveTimeout	20 000	(Inspected attribute keepAliveTimeout)
keyAlias	null	(Inspected attribute keyAlias)
keyPass	null	(Inspected attribute keyPass)
keystoreFile	null	(Inspected attribute keystoreFile)
keystorePass	null	(Inspected attribute keystorePass)
keystoreProvider	null	(Inspected attribute keystoreProvider)
keystoreType	null	(Inspected attribute keystoreType)
localPort	80	(Inspected attribute localPort)
maxConnections	8 192	(Inspected attribute maxConnections)
maxExtensionSize	8 192	(Inspected attribute maxExtensionSize)
maxHeaderCount	100	(Inspected attribute maxHeaderCount)
maxHttpHeaderSize	8 192	(Inspected attribute maxHttpHeaderSize)
maxKeepAliveRequests	100	(Inspected attribute maxKeepAliveRequests)
maxSavePostSize	4 096	(Inspected attribute maxSavePostSize)
maxSwallowSize	2 097 152	(Inspected attribute maxSwallowSize)
maxThreads	200	(Inspected attribute maxThreads)
maxTrailerSize	8 192	(Inspected attribute maxTrailerSize)
minSpareThreads	10	(Inspected attribute minSpareThreads)
modelerType	org.apache.coyote.http11.Http11NioProtocol	(Type of the modeled resource. Can be set only once)
name	"http-nio-80"	(Inspected attribute name)
nameIndex	1	(Inspected attribute nameIndex)
noCompressionStrongETag	true	(Inspected attribute noCompressionStrongETag)
noCompressionUserAgents	null	(Inspected attribute noCompressionUserAgents)
objectName	Catalina:type=ProtocolHandler,port=80	(Inspected attribute objectName)
paused	false	(Inspected attribute paused)
pollerThreadCount	1	(Inspected attribute pollerThreadCount)
pollerThreadPriority	5	(Inspected attribute pollerThreadPriority)
port	80	(Inspected attribute port)
portOffset	0	(Inspected attribute portOffset)
portWithOffset	80	(Inspected attribute portWithOffset)
processorCache	200	(Inspected attribute processorCache)
rejectIllegalHeader	true	(Inspected attribute rejectIllegalHeader)
rejectIllegalHeaderName	true	(Inspected attribute rejectIllegalHeaderName)
relaxedPathChars	null	(Inspected attribute relaxedPathChars)
relaxedQueryChars	null	(Inspected attribute relaxedQueryChars)
restrictedUserAgents	null	(Inspected attribute restrictedUserAgents)
sSLCACertificateFile	null	(Inspected attribute sSLCACertificateFile)
sSLCACertificatePath	null	(Inspected attribute sSLCACertificatePath)
sSLCARevocationFile	null	(Inspected attribute sSLCARevocationFile)
sSLCARevocationPath	null	(Inspected attribute sSLCARevocationPath)
sSLCertificateChainFile	null	(Inspected attribute sSLCertificateChainFile)
sSLCertificateFile	null	(Inspected attribute sSLCertificateFile)
sSLCertificateKeyFile	null	(Inspected attribute sSLCertificateKeyFile)
sSLCipherSuite	HIGH:!aNULL:!eNULL:!EXPORT:!DES:!RC4:!MD5:!kRSA	(Inspected attribute sSLCipherSuite)
sSLDisableCompression	true	(Inspected attribute sSLDisableCompression)

sSLDisableSessionTickets	false	(Inspected attribute sSLDisableSessionTickets)
sSLEnabled	false	(Inspected attribute sSLEnabled)
sSLHonorCipherOrder	false	(Inspected attribute sSLHonorCipherOrder)
sSLPassword	null	(Inspected attribute sSLPassword)
sSLProtocol		(Inspected attribute sSLProtocol)
sSLVerifyClient	NONE	(Inspected attribute sSLVerifyClient)
sSLVerifyDepth	10	(Inspected attribute sSLVerifyDepth)
secure	false	(Inspected attribute secure)
selectorTimeout	1 000	(Inspected attribute selectorTimeout)
sendfileSupported	true	(Inspected attribute sendfileSupported)
server	null	(Inspected attribute server)
serverRemoveAppProvidedValues	false	(Inspected attribute serverRemoveAppProvidedValues)
sessionCacheSize	-1	(Inspected attribute sessionCacheSize)
sessionTimeout	86 400	(Inspected attribute sessionTimeout)
sniParseLimit	65 536	(Inspected attribute sniParseLimit)
sslEnabledProtocols		(Inspected attribute sslEnabledProtocols)
sslImplementationName	null	(Inspected attribute sslImplementationName)
sslProtocol	TLS	(Inspected attribute sslProtocol)
tcpNoDelay	true	(Inspected attribute tcpNoDelay)
threadPriority	5	(Inspected attribute threadPriority)
trustManagerClassName	null	(Inspected attribute trustManagerClassName)
trustMaxCertLength	10	(Inspected attribute trustMaxCertLength)
truststoreAlgorithm	PKIX	(Inspected attribute truststoreAlgorithm)
truststoreFile	null	(Inspected attribute truststoreFile)
truststorePass	null	(Inspected attribute truststorePass)
truststoreProvider	null	(Inspected attribute truststoreProvider)
truststoreType	JKS	(Inspected attribute truststoreType)
useKeepAliveResponseHeader	true	(Inspected attribute useKeepAliveResponseHeader)
useSendfile	true	(Inspected attribute useSendfile)
useServerCipherSuitesOrder	false	(Inspected attribute useServerCipherSuitesOrder)

Realm

realmPath=/realm0

(Realm implementation that can be used to wrap existing realms to provide a user lock-out capability)

allRolesMode	strict	(The all roles mode.)
cacheRemovalWarningTime	3 600	(If a failed user is removed from the cache because the cache is too big before it has been in the cache for at least this period of time (in seconds) a warning message will be logged. Defaults to 3600 (1 hour).)
cacheSize	1 000	(Number of users that have failed authentication to keep in cache. Over time the cache will grow to this size and may not shrink. Defaults to 1000.)
className	org.apache.catalina.realm.LockOutRealm	(Fully qualified class name of the managed object)
failureCount	5	(The number of times in a row a user has to fail authentication to be locked out. Defaults to 5.)
lockOutTime	300	(The time (in seconds) a user is locked out for after too many authentication failures. Defaults to 300 (5 minutes).)
modelerType	org.apache.catalina.realm.LockOutRealm	(Type of the modeled resource. Can be set only once)
realmPath	/realm0	(The realm path)
realms	[Catalina:type=Realm,realmPath=/realm0/realm0]	(The set of realms that the lockout realm is wrapping)
validate	true	(The 'validate certificate chains' flag.)

realmPath=/realm0/realm0

(Realm connected to a UserDatabase as a global JNDI resource)

allRolesMode	strict	(The all roles mode.)
className	org.apache.catalina.realm.UserDatabaseRealm	(Fully qualified class name of the managed object)
modelerType	org.apache.catalina.realm.UserDatabaseRealm	(Type of the modeled resource. Can be set only once)
realmPath	/realm0/realm0	(The realm path)
resourceName	UserDatabase	(The global JNDI name of the UserDatabase resource to use)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
validate	true	(The 'validate certificate chains' flag.)

RequestProcessor

worker="http-nio-80",name=HttpRequest1

bytesReceived	8 002	(Inspected attribute bytesReceived)
bytesSent	191 006 828	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	2 788	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	64	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/demo/monitoring	(Inspected attribute maxRequestUri)
maxTime	60 778	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	3 008 275	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)

requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1 349 501	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest1	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest10		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	1	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 169	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 169	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 169	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest10	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest100		
bytesReceived	2 031	(Inspected attribute bytesReceived)
bytesSent	206 678 309	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	3 467	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	101	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/demo/monitoring	(Inspected attribute maxRequestUri)
maxTime	36 566	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	3 711 418	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1 433 362	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest100	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest101		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 121	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 121	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 121	(Inspected attribute processingTime)

protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest101	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest102		
bytesReceived	3 341	(Introspected attribute bytesReceived)
bytesSent	157 424 919	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	3 101	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	69	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/demo/monitoring	(Introspected attribute maxRequestUri)
maxTime	30 742	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	2 308 867	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1 361 148	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest102	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest103		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	60	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 120	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 120	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 120	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest103	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest104		
bytesReceived	856	(Introspected attribute bytesReceived)
bytesSent	17 968 796	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	250	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	100	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/demo/monitoring	(Introspected attribute maxRequestUri)

maxTime	27 580	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	548 700	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	200 890	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest104	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest105

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 074	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 074	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 074	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest105	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest106

bytesReceived	6 162	(Inspected attribute bytesReceived)
bytesSent	208 989 935	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	4 852	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	11	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/demo/monitoring	(Inspected attribute maxRequestUri)
maxTime	46 375	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	3 102 089	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1 732 332	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest106	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest107

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)

errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 023	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 023	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 023	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest107	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest108

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	974	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	974	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	974	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest108	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest109

bytesReceived	694	(Inspected attribute bytesReceived)
bytesSent	11 670 102	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	52	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	98	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/demo/monitoring	(Inspected attribute maxRequestUri)
maxTime	34 867	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	364 135	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	52 077	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest109	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest11

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 169	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 169	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 169	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest11	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest110

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	914	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	914	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	914	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest110	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest111

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	916	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	916	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	916	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest111	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)

stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest112		
bytesReceived	1 504	(Inspected attribute bytesReceived)
bytesSent	188 729 160	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	3 102	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	0	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/demo/monitoring	(Inspected attribute maxRequestUri)
maxTime	64 100	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	2 496 886	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1 563 522	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest112	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest113		
bytesReceived	9 528	(Inspected attribute bytesReceived)
bytesSent	332 499 463	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	7 077	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	54	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/demo/monitoring	(Inspected attribute maxRequestUri)
maxTime	62 644	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	4 074 493	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	178.177.26.225	(Inspected attribute remoteAddr)
remoteAddrForwarded	178.177.26.225	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	2 247 380	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest113	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest114		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	6 544 489	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	11	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	98	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/demo/monitoring	(Inspected attribute maxRequestUri)
maxTime	30 505	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	342 106	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)

requestCount	2 625	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest114	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest115		
bytesReceived	2 574	(Inspected attribute bytesReceived)
bytesSent	39 704 213	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	552	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	0	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/demo/monitoring	(Inspected attribute maxRequestUri)
maxTime	37 697	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	637 405	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	369 180	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest115	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest116		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	999 398	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	11	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	103	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/demo/monitoring	(Inspected attribute maxRequestUri)
maxTime	31 173	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	101 176	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	260	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest116	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest117		
bytesReceived	3 902	(Inspected attribute bytesReceived)
bytesSent	224 539 283	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	6 209	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	0	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/demo/monitoring	(Inspected attribute maxRequestUri)
maxTime	62 665	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	3 945 224	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)

remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1 689 585	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest117	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest118

bytesReceived	162	(Inspected attribute bytesReceived)
bytesSent	91 029 192	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	1 978	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	62	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/demo/monitoring	(Inspected attribute maxRequestUri)
maxTime	19 418	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 189 585	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	766 476	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest118	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest119

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	688	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	688	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	688	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest119	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest12

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	1	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 168	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 168	(Inspected attribute maxTime)

method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 168	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest12	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest120

bytesReceived	2 822	(Inspected attribute bytesReceived)
bytesSent	274 688 856	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	3 299	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/demo/monitoring	(Inspected attribute maxRequestUri)
maxTime	61 598	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	4 580 423	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1 624 986	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest120	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest121

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	615	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	615	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	615	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest121	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest122

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)

globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	602	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	602	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	602	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest122	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest123

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	579	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	579	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	579	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest123	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest124

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	562	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	562	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	562	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest124	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest125

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	548	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	548	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	548	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest125	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest126

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	514	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	514	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	514	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest126	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest127

bytesReceived	11 371	(Inspected attribute bytesReceived)
bytesSent	339 445 354	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	4 775	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	72	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/demo/monitoring	(Inspected attribute maxRequestUri)
maxTime	102 701	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	5 242 713	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	2 548 103	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest127	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)

virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest128		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	451	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	451	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	451	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest128	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest129		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	423	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	423	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	423	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest129	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest13		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 167	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 167	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 167	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)

requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest13	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest130		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	378	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	378	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	378	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest130	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest131		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	376	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	376	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	376	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest131	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest132		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	323	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	323	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	323	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)

remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest132	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest133		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	321	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	321	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	321	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest133	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest134		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	173	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	173	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	173	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest134	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest135		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	135	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	135	(Inspected attribute maxTime)
method	null	(Inspected attribute method)

modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	135	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest135	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest136

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	131	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	131	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	131	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest136	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest137

bytesReceived	1 988	(Inspected attribute bytesReceived)
bytesSent	45 417 910	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	1 216	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	99	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/demo/monitoring	(Inspected attribute maxRequestUri)
maxTime	29 429	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	809 028	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	405 696	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest137	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest138

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	120	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)

lastRequestProcessingTime	1	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	2	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	2	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest138	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest14

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 167	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 167	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 167	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest14	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest15

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 166	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 166	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 166	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest15	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest16

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 166	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 166	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 166	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest16	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest17

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	1	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 166	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 166	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 166	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest17	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest18

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 165	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 165	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 165	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest18	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)

virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest19		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 164	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 164	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 164	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest19	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest2		
bytesReceived	1 296	(Inspected attribute bytesReceived)
bytesSent	144 835 059	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	4 510	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	54	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/demo/monitoring	(Inspected attribute maxRequestUri)
maxTime	82 515	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	2 298 397	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1 094 690	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest2	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest20		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 163	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 163	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 163	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)

requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest20	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest21		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	1	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 163	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 163	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 163	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest21	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest22		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 162	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 162	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 162	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest22	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest23		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 162	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 162	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 162	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)

remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest23	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest24		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 162	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 162	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 162	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest24	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest25		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	1	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 161	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 161	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 161	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest25	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest26		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 160	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 160	(Inspected attribute maxTime)
method	null	(Inspected attribute method)

modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 160	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest26	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest27		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	1	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 159	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 159	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 159	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest27	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest28		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 035	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 035	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 035	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest28	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest29		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)

lastRequestProcessingTime	1 158	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 158	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 158	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest29	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest3

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	4 839 492	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	9	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	98	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/demo/monitoring	(Inspected attribute maxRequestUri)
maxTime	37 529	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	275 559	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1 391	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest3	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest30

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	1	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 158	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 158	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 158	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest30	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest31

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 158	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 158	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 158	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest31	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest32

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 157	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 157	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 157	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest32	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest33

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 157	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 157	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 157	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest33	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)

virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest34		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 143	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 143	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 143	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest34	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest35		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 155	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 155	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 155	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest35	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest36		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 154	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 154	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 154	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)

requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest36	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest37		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 154	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 154	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 154	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest37	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest38		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	1	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 154	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 154	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 154	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest38	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest39		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 153	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 153	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 153	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)

remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest39	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest4		
bytesReceived	162	(Inspected attribute bytesReceived)
bytesSent	25 780 442	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	843	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	99	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/demo/monitoring	(Inspected attribute maxRequestUri)
maxTime	37 580	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	548 387	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	221 496	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest4	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest40		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 152	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 152	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 152	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest40	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest41		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 151	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 151	(Inspected attribute maxTime)
method	null	(Inspected attribute method)

modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 151	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest41	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest42		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	1	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 151	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 151	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 151	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest42	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest43		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 151	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 151	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 151	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest43	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest44		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)

lastRequestProcessingTime	1 150	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 150	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 150	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest44	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest45

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 150	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 150	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 150	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest45	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest46

bytesReceived	4 290	(Inspected attribute bytesReceived)
bytesSent	220 522 766	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	4 342	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	4	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/demo/monitoring	(Inspected attribute maxRequestUri)
maxTime	20 380	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	3 238 331	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1 779 269	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest46	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest47

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 149	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 149	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 149	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest47	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest48

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	1	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 149	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 149	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 149	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest48	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest49

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	1	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 147	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 147	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 147	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest49	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)

virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest5		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	120	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	0	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 172	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 172	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	2	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest5	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest50		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 138	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 138	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 138	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest50	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest51		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 146	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 146	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 146	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)

requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest51	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest52

bytesReceived	2 169	(Inspected attribute bytesReceived)
bytesSent	184 621 825	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	format=pdf&part=mbeans	(Inspected attribute currentQueryString)
currentUri	/demo/monitoring	(Inspected attribute currentUri)
errorCount	8 542	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/demo/monitoring	(Inspected attribute maxRequestUri)
maxTime	82 674	(Inspected attribute maxTime)
method	GET	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	2 929 504	(Inspected attribute processingTime)
protocol	HTTP/1.1	(Inspected attribute protocol)
remoteAddr	216.73.216.135	(Inspected attribute remoteAddr)
remoteAddrForwarded	216.73.216.135	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1 378 943	(Inspected attribute requestCount)
requestProcessingTime	143	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest52	(Inspected attribute rpName)
serverPort	80	(Inspected attribute serverPort)
stage	3	(Inspected attribute stage)
virtualHost	javamelody.org	(Inspected attribute virtualHost)
workerThreadName	http-nio-80-exec-176	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest53

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 146	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 146	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 146	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest53	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest54

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 145	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 145	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 145	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)

remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest54	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest55		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 145	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 145	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 145	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest55	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest56		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 144	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 144	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 144	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest56	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest57		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 144	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 144	(Inspected attribute maxTime)
method	null	(Inspected attribute method)

modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 144	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest57	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest58		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	1	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 143	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 143	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 143	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest58	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest59		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 142	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 142	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 142	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest59	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest6		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	360	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	1	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)

lastRequestProcessingTime	0	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 172	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 172	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	6	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest6	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest60

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 142	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 142	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 142	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest60	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest61

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 141	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 141	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 141	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest61	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest62

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	1	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 141	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 141	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 141	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest62	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest63

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 140	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 140	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 140	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest63	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest64

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 140	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 140	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 140	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest64	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)

virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest65		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 139	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 139	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 139	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest65	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest66		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 131	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 131	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 131	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest66	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest67		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	1	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 138	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 138	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 138	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)

requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest67	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest68		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	1	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 137	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 137	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 137	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest68	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest69		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 137	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 137	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 137	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest69	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest7		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	120	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	1	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	0	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 170	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 170	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)

remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	2	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest7	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest70		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 137	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 137	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 137	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest70	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest71		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	1	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 136	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 136	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 136	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest71	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest72		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	1	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 136	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 136	(Inspected attribute maxTime)
method	null	(Inspected attribute method)

modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 136	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest72	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest73		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 136	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 136	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 136	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest73	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest74		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 134	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 134	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 134	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest74	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest75		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)

lastRequestProcessingTime	1 134	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 134	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 134	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest75	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest76

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 133	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 133	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 133	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest76	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest77

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 133	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 133	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 133	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest77	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest78

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 132	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 132	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 132	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest78	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest79

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 132	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 132	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 132	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest79	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest8

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 170	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 170	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 170	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest8	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)

virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest80		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 131	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 131	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 131	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest80	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest81		
bytesReceived	3 903	(Inspected attribute bytesReceived)
bytesSent	314 778 187	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	6 204	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	0	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/demo/monitoring	(Inspected attribute maxRequestUri)
maxTime	34 748	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	4 471 079	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	2 071 589	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest81	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest82		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 130	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 130	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 130	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)

requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest82	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest83		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 124	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 124	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 124	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest83	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest84		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 129	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 129	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 129	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest84	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest85		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 129	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 129	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 129	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)

remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest85	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest86		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 128	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 128	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 128	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest86	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest87		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 123	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 123	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 123	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest87	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest88		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 128	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 128	(Inspected attribute maxTime)
method	null	(Inspected attribute method)

modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 128	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest88	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest89		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 127	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 127	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 127	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest89	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest9		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 170	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 170	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 170	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest9	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest90		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)

lastRequestProcessingTime	1 126	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 126	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 126	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest90	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest91

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	1	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 125	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 125	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 125	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest91	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest92

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	1	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 125	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 125	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 125	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest92	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest93

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	1	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 125	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 125	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 125	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest93	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest94

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	1	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 124	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 124	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 124	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest94	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest95

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 124	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 124	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 124	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest95	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)

virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest96		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 124	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 124	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 124	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest96	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest97		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 122	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 122	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 122	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest97	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest98		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 122	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 122	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 122	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)

requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest98	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest99

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 121	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	1 121	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 121	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest99	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

Resource**resourcetype=Context,host=localhost,context=/demo,class=javax.sql.DataSource,name="jdbc/demo_javamelody"**

(Representation of a resource reference for a web application)

auth	Container	(The authorization requirement for this resource)
description	Datasource	(The description of this resource)
name	jdbc/demo_javamelody	(The name of this resource)
scope	Shareable	(The sharing scope of this resource factory)
type	javax.sql.DataSource	(The type of this environment entry)

resourcetype=Global,class=org.apache.catalina.UserDatabase,name="UserDatabase"

(Representation of a resource reference for a web application)

auth	Container	(The authorization requirement for this resource)
description	User database that can be updated and saved	(The description of this resource)
name	UserDatabase	(The name of this resource)
scope	Shareable	(The sharing scope of this resource factory)
type	org.apache.catalina.UserDatabase	(The type of this environment entry)

SSLHostConfig**ThreadPool="http-nio-80",name="_default_"**

caCertificateFile	null	(Inspected attribute caCertificateFile)
caCertificatePath	null	(Inspected attribute caCertificatePath)
certificateChainFile	null	(Inspected attribute certificateChainFile)
certificateFile	null	(Inspected attribute certificateFile)
certificateKeyAlias	null	(Inspected attribute certificateKeyAlias)
certificateKeyFile	null	(Inspected attribute certificateKeyFile)
certificateKeyPassword	null	(Inspected attribute certificateKeyPassword)
certificateKeystoreFile	null	(Inspected attribute certificateKeystoreFile)
certificateKeystorePassword	null	(Inspected attribute certificateKeystorePassword)
certificateKeystoreProvider	null	(Inspected attribute certificateKeystoreProvider)
certificateKeystoreType	null	(Inspected attribute certificateKeystoreType)
certificateRevocationListFile	null	(Inspected attribute certificateRevocationListFile)
certificateRevocationListPath	null	(Inspected attribute certificateRevocationListPath)
certificateVerificationAsString	NONE	(Inspected attribute certificateVerificationAsString)
certificateVerificationDepth	10	(Inspected attribute certificateVerificationDepth)
certificateVerificationDepthConfigured	false	(Inspected attribute certificateVerificationDepthConfigured)
ciphers	HIGH:!aNULL:!eNULL:!EXPORT:!DES:!RC4:!MD5:!kRSA	(Inspected attribute ciphers)
disableCompression	true	(Inspected attribute disableCompression)
disableSessionTickets	false	(Inspected attribute disableSessionTickets)
enabledCiphers	null	(Inspected attribute enabledCiphers)
enabledProtocols	null	(Inspected attribute enabledProtocols)
honorCipherOrder	false	(Inspected attribute honorCipherOrder)
hostName	_default_	(Inspected attribute hostName)

insecureRenegotiation	false	(Inspected attribute insecureRenegotiation)
keyManagerAlgorithm	SunX509	(Inspected attribute keyManagerAlgorithm)
modelerType	org.apache.tomcat.util.net.SSLHostConfig	(Type of the modeled resource. Can be set only once)
objectName	Catalina:type=SSLHostConfig,ThreadPool=http-nio-80,name=_default_	(Inspected attribute objectName)
openSslConf	null	(Inspected attribute openSslConf)
openSslConfContext	0	(Inspected attribute openSslConfContext)
openSslContext	0	(Inspected attribute openSslContext)
revocationEnabled	false	(Inspected attribute revocationEnabled)
sessionCacheSize	-1	(Inspected attribute sessionCacheSize)
sessionTimeout	86 400	(Inspected attribute sessionTimeout)
sslProtocol	TLS	(Inspected attribute sslProtocol)
trustManagerClassName	null	(Inspected attribute trustManagerClassName)
truststoreAlgorithm	PKIX	(Inspected attribute truststoreAlgorithm)
truststoreFile	null	(Inspected attribute truststoreFile)
truststorePassword	null	(Inspected attribute truststorePassword)
truststoreProvider	null	(Inspected attribute truststoreProvider)
truststoreType	JKS	(Inspected attribute truststoreType)

Server

(Standard Server Component)

address	localhost	(The address on which we wait for shutdown commands.)
managedResource	StandardServer[8005]	(The managed resource this MBean is associated with)
modelerType	org.apache.catalina.core.StandardServer	(Type of the modeled resource. Can be set only once)
port	8 005	(TCP port (excluding any offset) for shutdown messages)
portOffset	0	(The offset applied to port and to the port attributes of any nested connectors)
portWithOffset	8 005	(Actual TCP port (including any offset) for shutdown messages)
serverBuilt	Mar 11 2020 09:31:38 UTC	(Tomcat server built timestamp)
serverInfo	Apache Tomcat/9.0.33	(Tomcat server release identifier)
serverNumber	9.0.33.0	(Tomcat server's version number)
serviceNames	[Catalina:type=Service]	(Object names of all services we know about)
shutdown	SHUTDOWN	(Shutdown password)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

Service

(Standard Service Component)

connectorNames	[Catalina:type=Connector,port=80]	(ObjectNames of the connectors)
managedResource	StandardService[Catalina]	(The managed resource this MBean is associated with)
modelerType	org.apache.catalina.core.StandardService	(Type of the modeled resource. Can be set only once)
name	Catalina	(Unique name of this Service)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

Servlet

WebModule=//localhost/,name=default,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	45 254	(Error count)
loadOnStartup	1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	0	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	49	(Maximum processing time of a request)
minTime	0	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=//localhost/,name=default,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	9 424	(Total execution time of the servlet's service method)
requestCount	45 254	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	org.apache.catalina.servlets.DefaultServlet	(The run-as identity for this servlet.)
singleThreadModel	false	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=//localhost/,name=jsp,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)

errorCount	48	(Error count)
loadOnStartup	3	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	0	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	87	(Maximum processing time of a request)
minTime	0	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=localhost,name=jsp,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	8 900	(Total execution time of the servlet's service method)
requestCount	12 460	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	org.apache.jasper.servlet.JspServlet	(The run-as identity for this servlet.)
singleThreadModel	false	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=localhost/demo,name=AdresseService,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	-1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	0	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	0	(Maximum processing time of a request)
minTime	9 223 372 036 854 775 807	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=localhost/demo,name=AdresseService,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	0	(Total execution time of the servlet's service method)
requestCount	0	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	fr.appwhite1.server.business.annuaire.AdresseGwtServiceImpl	(The run-as identity for this servlet.)
singleThreadModel	null	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=localhost/demo,name=AuthenticationService,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	307	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	-1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	307	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	11 272	(Maximum processing time of a request)
minTime	1	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=localhost/demo,name=AuthenticationService,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	23 306	(Total execution time of the servlet's service method)
requestCount	169	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	fr.appwhite1.server.business.secu.AuthenticationGwtServiceImpl	(The run-as identity for this servlet.)
singleThreadModel	false	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=localhost/demo,name=BuildInfoServlet,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	2	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)

loadOnStartup	1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	2	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	0	(Maximum processing time of a request)
minTime	9 223 372 036 854 775 807	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=/localhost/demo,name=BuildInfoServlet,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	0	(Total execution time of the servlet's service method)
requestCount	0	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	fr.appwhite1.Appli1BuildInfoServlet	(The run-as identity for this servlet.)
singleThreadModel	false	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=/localhost/demo,name=CompetenceService,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	-1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	0	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	0	(Maximum processing time of a request)
minTime	9 223 372 036 854 775 807	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=/localhost/demo,name=CompetenceService,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	0	(Total execution time of the servlet's service method)
requestCount	0	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	fr.appwhite1.server.business.annuaire.CompetenceGwtServiceImpl	(The run-as identity for this servlet.)
singleThreadModel	null	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=/localhost/demo,name=GradeService,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	1	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	-1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	1	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	5 214	(Maximum processing time of a request)
minTime	1	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=/localhost/demo,name=GradeService,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	5 504	(Total execution time of the servlet's service method)
requestCount	68	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	fr.referentiel.server.business.ref.GradeGwtServiceImpl	(The run-as identity for this servlet.)
singleThreadModel	false	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=/localhost/demo,name=MailService,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	-1	(The load-on-startup order value (negative value means load on first call) for this servlet.)

loadTime	0	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	0	(Maximum processing time of a request)
minTime	9 223 372 036 854 775 807	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=/localhost/demo,name=MailService,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	0	(Total execution time of the servlet's service method)
requestCount	0	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	fr.appwhite1.server.business.annuaire.MailGwtServiceImpl	(The run-as identity for this servlet.)
singleThreadModel	null	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=/localhost/demo,name=PermissionService,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	-1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	0	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	0	(Maximum processing time of a request)
minTime	9 223 372 036 854 775 807	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=/localhost/demo,name=PermissionService,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	0	(Total execution time of the servlet's service method)
requestCount	0	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	fr.appwhite1.server.business.secu.PermissionGwtServiceImpl	(The run-as identity for this servlet.)
singleThreadModel	null	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=/localhost/demo,name=PersonneService,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	-1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	0	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	18 691	(Maximum processing time of a request)
minTime	3	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=/localhost/demo,name=PersonneService,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	26 043	(Total execution time of the servlet's service method)
requestCount	128	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	fr.appwhite1.server.business.annuaire.PersonneGwtServiceImpl	(The run-as identity for this servlet.)
singleThreadModel	false	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=/localhost/demo,name=PrintUtilsService,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	-1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	0	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)

maxTime	0	(Maximum processing time of a request)
minTime	9 223 372 036 854 775 807	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=//localhost/demo,name=PrintUtilsService,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	0	(Total execution time of the servlet's service method)
requestCount	0	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	fr.appwhite1.server.business.utils.PrintUtilsGwtServiceImpl	(The run-as identity for this servlet.)
singleThreadModel	null	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=//localhost/demo,name=RoleService,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	-1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	0	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	0	(Maximum processing time of a request)
minTime	9 223 372 036 854 775 807	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=//localhost/demo,name=RoleService,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	0	(Total execution time of the servlet's service method)
requestCount	0	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	fr.appwhite1.server.business.secu.RoleGwtServiceImpl	(The run-as identity for this servlet.)
singleThreadModel	null	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=//localhost/demo,name=TelephoneService,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	-1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	0	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	0	(Maximum processing time of a request)
minTime	9 223 372 036 854 775 807	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=//localhost/demo,name=TelephoneService,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	0	(Total execution time of the servlet's service method)
requestCount	0	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	fr.appwhite1.server.business.annuaire.TelephoneGwtServiceImpl	(The run-as identity for this servlet.)
singleThreadModel	null	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=//localhost/demo,name=UtilisateurService,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	-1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	0	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	0	(Maximum processing time of a request)
minTime	9 223 372 036 854 775 807	(Minimum processing time of a request)

modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet.WebModule=/localhost/demo,name=UtilisateurService,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	0	(Total execution time of the servlet's service method)
requestCount	0	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	fr.appwhite1.server.business.secu.UtilisateurGwtServiceImpl	(The run-as identity for this servlet.)
singleThreadModel	null	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=/localhost/demo,name=default,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	2	(Time taken to load the Servlet class)
countAllocated	1	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	15 184	(Error count)
loadOnStartup	1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	2	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	64 100	(Maximum processing time of a request)
minTime	0	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet.WebModule=/localhost/demo,name=default,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	27 274 805	(Total execution time of the servlet's service method)
requestCount	147 228	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	org.apache.catalina.servlets.DefaultServlet	(The run-as identity for this servlet.)
singleThreadModel	false	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=/localhost/demo,name=jsp,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	3	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	30	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	0	(Maximum processing time of a request)
minTime	9 223 372 036 854 775 807	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet.WebModule=/localhost/demo,name=jsp,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	0	(Total execution time of the servlet's service method)
requestCount	0	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	org.apache.jasper.servlet.JspServlet	(The run-as identity for this servlet.)
singleThreadModel	false	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=/localhost/downloads,name=default,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	46	(Error count)
loadOnStartup	1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	0	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	19	(Maximum processing time of a request)
minTime	0	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)

objectName	Catalina:j2eeType=Servlet,WebModule=/localhost/downloads,name=default,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	63	(Total execution time of the servlet's service method)
requestCount	60	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	org.apache.catalina.servlets.DefaultServlet	(The run-as identity for this servlet.)
singleThreadModel	false	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=/localhost/downloads,name=jsp,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	3	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	1	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	0	(Maximum processing time of a request)
minTime	9 223 372 036 854 775 807	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=/localhost/downloads,name=jsp,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	0	(Total execution time of the servlet's service method)
requestCount	0	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	org.apache.jasper.servlet.JspServlet	(The run-as identity for this servlet.)
singleThreadModel	false	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=/localhost/usage,name=admin,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	3	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	2	(Error count)
loadOnStartup	1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	26	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	1 528	(Maximum processing time of a request)
minTime	0	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=/localhost/usage,name=admin,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	1 553	(Total execution time of the servlet's service method)
requestCount	7	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	net.bull.javamelody.usagestats.AdminServlet	(The run-as identity for this servlet.)
singleThreadModel	false	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=/localhost/usage,name=default,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	3	(Error count)
loadOnStartup	1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	0	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	4	(Maximum processing time of a request)
minTime	0	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=/localhost/usage,name=default,J2EEApplication=none,J2EEServer=none	(Name of the object)

processingTime	85	(Total execution time of the servlet's service method)
requestCount	94	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	org.apache.catalina.servlets.DefaultServlet	(The run-as identity for this servlet.)
singleThreadModel	false	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=//localhost/usage,name=jsp,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	1	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	3	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	1	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	0	(Maximum processing time of a request)
minTime	9 223 372 036 854 775 807	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=//localhost/usage,name=jsp,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	0	(Total execution time of the servlet's service method)
requestCount	0	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	org.apache.jasper.servlet.JspServlet	(The run-as identity for this servlet.)
singleThreadModel	false	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=//localhost/usage,name=usagstats,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	39	(Error count)
loadOnStartup	1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	441 890	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	22 329	(Maximum processing time of a request)
minTime	0	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=//localhost/usage,name=usagstats,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	6 005 955	(Total execution time of the servlet's service method)
requestCount	23 682 764	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	net.bull.javamelody.usagstats.UsageStatsServlet	(The run-as identity for this servlet.)
singleThreadModel	false	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

StringCache

accessCount	95 895 189	(Inspected attribute accessCount)
byteEnabled	true	(Inspected attribute byteEnabled)
cacheSize	200	(Inspected attribute cacheSize)
charEnabled	false	(Inspected attribute charEnabled)
hitCount	71 754 202	(Inspected attribute hitCount)
modelerType	org.apache.tomcat.util.buf.StringCache	(Type of the modeled resource. Can be set only once)
trainThreshold	20 000	(Inspected attribute trainThreshold)

ThreadPool

name="http-nio-80"

acceptCount	100
acceptorThreadCount	1
acceptorThreadPriority	5
alpnSupported	false
bindOnInit	true
connectionCount	126
connectionLinger	-1
connectionTimeout	20 000
currentThreadCount	47

currentThreadsBusy	1
daemon	true
defaultSSLHostConfigName	__default__
deferAccept	false
domain	Catalina
executorTerminationTimeoutMillis	5 000
keepAliveCount	0
keepAliveTimeout	20 000
localPort	80
maxConnections	8 192
maxKeepAliveRequests	100
maxThreads	200
minSpareThreads	10
modelerType	org.apache.tomcat.util.net.NioEndpoint
name	http-nio-80
paused	false
pollerThreadCount	1
pollerThreadPriority	5
port	80
portOffset	0
portWithOffset	80
running	true
sSLEnabled	false
selectorTimeout	1 000
sniParseLimit	65 536
sslImplementation	null
sslImplementationName	null
tcpNoDelay	true
threadPriority	5
useInheritedChannel	false
useSendfile	true

name="http-nio-80",subType=SocketProperties

appReadBufSize	8 192	(Inspected attribute appReadBufSize)
appWriteBufSize	8 192	(Inspected attribute appWriteBufSize)
bufferPool	500	(Inspected attribute bufferPool)
bufferPoolSize	104 857 600	(Inspected attribute bufferPoolSize)
directBuffer	false	(Inspected attribute directBuffer)
directBufferPool	500	(Inspected attribute directBufferPool)
directSslBuffer	false	(Inspected attribute directSslBuffer)
eventCache	500	(Inspected attribute eventCache)
modelerType	org.apache.tomcat.util.net.SocketProperties	(Type of the modeled resource. Can be set only once)
processorCache	500	(Inspected attribute processorCache)
soLingerOn	false	(Inspected attribute soLingerOn)
soLingerTime	-1	(Inspected attribute soLingerTime)
soTimeout	20 000	(Inspected attribute soTimeout)
tcpNoDelay	true	(Inspected attribute tcpNoDelay)
timeoutInterval	1 000	(Inspected attribute timeoutInterval)
unlockTimeout	250	(Inspected attribute unlockTimeout)

UtilityExecutor

activeCount	0	(Inspected attribute activeCount)
completedTaskCount	4 492 095	(Inspected attribute completedTaskCount)
continueExistingPeriodicTasksAfterShutdownPolicy	false	(Inspected attribute continueExistingPeriodicTasksAfterShutdownPolicy)
corePoolSize	2	(Inspected attribute corePoolSize)
executeExistingDelayedTasksAfterShutdownPolicy	false	(Inspected attribute executeExistingDelayedTasksAfterShutdownPolicy)
largestPoolSize	2	(Inspected attribute largestPoolSize)
maximumPoolSize	2 147 483 647	(Inspected attribute maximumPoolSize)
modelerType	java.util.concurrent.ScheduledThreadPoolExecutor	(Type of the modeled resource. Can be set only once)
poolSize	2	(Inspected attribute poolSize)
removeOnCancelPolicy	true	(Inspected attribute removeOnCancelPolicy)
shutdown	false	(Inspected attribute shutdown)
taskCount	4 492 101	(Inspected attribute taskCount)
terminated	false	(Inspected attribute terminated)
terminating	false	(Inspected attribute terminating)

Valve

host=localhost,context=/,name=NonLoginAuthenticator

(An Authenticator and Valve implementation that checks only security constraints not involving user authentication)

cache	true	(Should we cache authenticated Principals if the request is part of an HTTP session?)
changeSessionIdOnAuthentication	true	(Controls if the session ID is changed if a session exists at the point where users are authenticated)
className	org.apache.catalina.authenticator.NonLoginAuthenticator	(Fully qualified class name of the managed object)
disableProxyCaching	true	(Controls the caching of pages that are protected by security constraints)
modelerType	org.apache.catalina.authenticator.NonLoginAuthenticator	(Type of the modeled resource. Can be set only once)
securePagesWithPragma	false	(Controls the caching of pages that are protected by security constraints)

<p>stateName</p> <p>STARTED</p>	<p>(The name of the LifecycleState that this component is currently in)</p>
<p>host=localhost,context=/,name=StandardContextValve (Valve that implements the default basic behavior for the StandardContext container implementation)</p>	
<p>asyncSupported true</p> <p>className org.apache.catalina.core.StandardContextValve</p> <p>modelerType org.apache.catalina.core.StandardContextValve</p> <p>stateName STARTED</p>	<p>(Does this valve support async reporting?)</p> <p>(Fully qualified class name of the managed object)</p> <p>(Type of the modeled resource. Can be set only once)</p> <p>(The name of the LifecycleState that this component is currently in)</p>
<p>host=localhost,context=/demo,name=NonLoginAuthenticator (An Authenticator and Valve implementation that checks only security constraints not involving user authentication)</p>	
<p>cache true</p> <p>changeSessionIdOnAuthentication true</p> <p>className org.apache.catalina.authenticator.NonLoginAuthenticator</p> <p>disableProxyCaching true</p> <p>modelerType org.apache.catalina.authenticator.NonLoginAuthenticator</p> <p>securePagesWithPragma false</p> <p>stateName STARTED</p>	<p>(Should we cache authenticated Principals if the request is part of an HTTP session?)</p> <p>(Controls if the session ID is changed if a session exists at the point where users are authenticated)</p> <p>(Fully qualified class name of the managed object)</p> <p>(Controls the caching of pages that are protected by security constraints)</p> <p>(Type of the modeled resource. Can be set only once)</p> <p>(Controls the caching of pages that are protected by security constraints)</p> <p>(The name of the LifecycleState that this component is currently in)</p>
<p>host=localhost,context=/demo,name=StandardContextValve (Valve that implements the default basic behavior for the StandardContext container implementation)</p>	
<p>asyncSupported true</p> <p>className org.apache.catalina.core.StandardContextValve</p> <p>modelerType org.apache.catalina.core.StandardContextValve</p> <p>stateName STARTED</p>	<p>(Does this valve support async reporting?)</p> <p>(Fully qualified class name of the managed object)</p> <p>(Type of the modeled resource. Can be set only once)</p> <p>(The name of the LifecycleState that this component is currently in)</p>
<p>host=localhost,context=/downloads,name=NonLoginAuthenticator (An Authenticator and Valve implementation that checks only security constraints not involving user authentication)</p>	
<p>cache true</p> <p>changeSessionIdOnAuthentication true</p> <p>className org.apache.catalina.authenticator.NonLoginAuthenticator</p> <p>disableProxyCaching true</p> <p>modelerType org.apache.catalina.authenticator.NonLoginAuthenticator</p> <p>securePagesWithPragma false</p> <p>stateName STARTED</p>	<p>(Should we cache authenticated Principals if the request is part of an HTTP session?)</p> <p>(Controls if the session ID is changed if a session exists at the point where users are authenticated)</p> <p>(Fully qualified class name of the managed object)</p> <p>(Controls the caching of pages that are protected by security constraints)</p> <p>(Type of the modeled resource. Can be set only once)</p> <p>(Controls the caching of pages that are protected by security constraints)</p> <p>(The name of the LifecycleState that this component is currently in)</p>
<p>host=localhost,context=/downloads,name=StandardContextValve (Valve that implements the default basic behavior for the StandardContext container implementation)</p>	
<p>asyncSupported true</p> <p>className org.apache.catalina.core.StandardContextValve</p> <p>modelerType org.apache.catalina.core.StandardContextValve</p> <p>stateName STARTED</p>	<p>(Does this valve support async reporting?)</p> <p>(Fully qualified class name of the managed object)</p> <p>(Type of the modeled resource. Can be set only once)</p> <p>(The name of the LifecycleState that this component is currently in)</p>
<p>host=localhost,context=/usage,name=NonLoginAuthenticator (An Authenticator and Valve implementation that checks only security constraints not involving user authentication)</p>	
<p>cache true</p> <p>changeSessionIdOnAuthentication true</p> <p>className org.apache.catalina.authenticator.NonLoginAuthenticator</p> <p>disableProxyCaching true</p> <p>modelerType org.apache.catalina.authenticator.NonLoginAuthenticator</p> <p>securePagesWithPragma false</p> <p>stateName STARTED</p>	<p>(Should we cache authenticated Principals if the request is part of an HTTP session?)</p> <p>(Controls if the session ID is changed if a session exists at the point where users are authenticated)</p> <p>(Fully qualified class name of the managed object)</p> <p>(Controls the caching of pages that are protected by security constraints)</p> <p>(Type of the modeled resource. Can be set only once)</p> <p>(Controls the caching of pages that are protected by security constraints)</p> <p>(The name of the LifecycleState that this component is currently in)</p>
<p>host=localhost,context=/usage,name=StandardContextValve (Valve that implements the default basic behavior for the StandardContext container implementation)</p>	
<p>asyncSupported true</p> <p>className org.apache.catalina.core.StandardContextValve</p> <p>modelerType org.apache.catalina.core.StandardContextValve</p> <p>stateName STARTED</p>	<p>(Does this valve support async reporting?)</p> <p>(Fully qualified class name of the managed object)</p> <p>(Type of the modeled resource. Can be set only once)</p> <p>(The name of the LifecycleState that this component is currently in)</p>
<p>host=localhost,name=AccessLogValve (Valve that generates a web server access log)</p>	
<p>asyncSupported true</p> <p>buffered true</p> <p>checkExists false</p> <p>className org.apache.catalina.valves.AccessLogValve</p> <p>condition null</p> <p>conditionIf null</p>	<p>(Does this valve support async reporting.)</p> <p>(Flag to buffering.)</p> <p>(Check for file existence before logging.)</p> <p>(Fully qualified class name of the managed object)</p> <p>(The value to look for conditional logging. The same as conditionUnless.)</p> <p>(The value to look for conditional logging.)</p>

conditionUnless	null	(The value to look for conditional logging.)
directory	logs	(The directory in which log files are created)
enabled	true	(Enable Access Logging)
encoding	null	(Character set used to write the log file)
fileDateFormat	.yyyy-MM-dd	(The format for the date for date based log rotation)
locale	en_US	(The locale used to format timestamps in the access log lines)
modelerType	org.apache.catalina.valves.AccessLogValve	(Type of the modeled resource. Can be set only once)
pattern	%h %l %u %t "%r" %s %b	(The pattern used to format our access log lines)
prefix	localhost_access_log	(The prefix that is added to log file filenames)
renameOnRotate	false	(Flag to defer inclusion of the date stamp in the log file name until rotation.)
rotatable	true	(Flag to indicate automatic log rotation.)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
suffix	.txt	(The suffix that is added to log file filenames)

host=localhost,name=ErrorReportValve

(Implementation of a Valve that outputs HTML error pages)

asyncSupported	true	(Does this valve support async reporting.)
className	org.apache.catalina.valves.ErrorReportValve	(Fully qualified class name of the managed object)
modelerType	org.apache.catalina.valves.ErrorReportValve	(Type of the modeled resource. Can be set only once)
showReport	true	(Enables/Disables full error reports)
showServerInfo	true	(Enables/Disables server info on error pages)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

host=localhost,name=StandardHostValve

(Valve that implements the default basic behavior for the StandardHost container implementation)

asyncSupported	true	(Does this valve support async reporting?)
className	org.apache.catalina.core.StandardHostValve	(Fully qualified class name of the managed object)
modelerType	org.apache.catalina.core.StandardHostValve	(Type of the modeled resource. Can be set only once)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

name=StandardEngineValve

(Valve that implements the default basic behavior for the StandardEngine container implementation)

asyncSupported	true	(Does this valve support async reporting?)
className	org.apache.catalina.core.StandardEngineValve	(Fully qualified class name of the managed object)
modelerType	org.apache.catalina.core.StandardEngineValve	(Type of the modeled resource. Can be set only once)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule**name=/localhost/,J2EEApplication=none,J2EEServer=none**

(Standard Context Component)

altDDName	null	(The alternate deployment descriptor name.)
antiResourceLocking	false	(Take care to not lock resources)
baseName	ROOT	(The base name used for directories, WAR files (with .war appended) and context.xml files (with .xml appended).)
children	[Catalina:j2eeType=Servlet,WebModule=/localhost/,name=default,J2EEApplication=none,J2EEServer=none,Catalina:j2eeType=Servlet,WebModule=/localhost/,name=jsp,J2EEApplication=none,J2EEServer=none]	(Object names of all children)
clearReferencesRmiTargets	true	(Should Tomcat look for memory leaks in RMI Targets and clear them if found as a work around for application coding errors?)
clearReferencesStopThreads	false	(Should Tomcat attempt to terminate threads that have been started by the web application? Advisable to be used only in a development environment.)
clearReferencesStopTimerThreads	false	(Should Tomcat attempt to terminate TimerThreads that have been started by the web application? Advisable to be used only in a development environment.)
clearReferencesThreadLocals	true	(Should Tomcat attempt to clear ThreadLocal variables that have been populated with classes loaded by the web application?)
configFile	null	(Location of the context.xml resource or file)
configured	true	(The correctly configured flag for this Context.)
cookies	true	(Should we attempt to use cookies for session id communication?)
crossContext	false	(Should we allow the ServletContext.getContext() method to access the context of other web applications in this server?)
defaultContextXml	null	(Location of the default context.xml resource or file)
defaultWebXml	null	(Location of the default web.xml resource or file)
delegate	false	
displayName	null	(The display name of this web application)
distributable	false	(The distributable flag for this web application.)
docBase	ROOT	(The document root for this web application)
encodedPath		(The encoded path)
errorCount	45 302	(Cumulative error count of all servlets in this context)
ignoreAnnotations	false	(Ignore annotations flag.)
instanceManager	org.apache.catalina.core.DefaultInstanceManager@16ce10d8	(Object that creates and destroys servlets, filters, and listeners. Include dependency injection and postConstruct/preDestroy handling)
javaVMs	null	(The Java virtual machines on which this module is running)
loader	WebappLoader[StandardEngine[Catalina].StandardHost[localhost].StandardContext[]]	(Associated loader.)
logEffectiveWebXml	false	(Should the effective web.xml be logged when the context starts?)
logger	org.apache.juli.logging.DirectJDKLog@3beb831d	(Associated logger.)
managedResource	StandardEngine[Catalina].StandardHost[localhost].StandardContext[]	(The managed resource this MBean is associated with)
manager	StandardManager[StandardEngine[Catalina].StandardHost[localhost].StandardContext[]]	(Associated manager.)

mapperContextRootRedirectEnabled	true	(Should the Mapper be used for context root redirects)
mapperDirectoryRedirectEnabled	false	(Should the Mapper be used for directory redirects)
maxTime	87	(Maximum execution time of all servlets in this context)
minTime	0	(Minimum execution time of all servlets in this context)
modelerType	org.apache.catalina.core.StandardContext	(Type of the modeled resource. Can be set only once)
name		(The name of this Context)
namingContextListener	org.apache.catalina.core.NamingContextListener@3b03a88e	(Associated naming context listener.)
objectName	Catalina:j2eeType=WebModule,name=/localhost/,J2EEApplication=none,J2EEServer=none	(Name of the object)
originalDocBase	null	(The original document root for this web application)
override	false	(The default context.xml override flag for this web application)
parentClassLoader	java.net.URLClassLoader@6f1fba17	(Parent class loader.)
path		(The context path for this Context)
paused	false	(The request processing pause flag (while reloading occurs))
privileged	false	(Access to tomcat internals)
processingTime	18 324	(Cumulative execution times of all servlets in this context)
publicId	null	(The public identifier of the DTD for the web application deployment descriptor version that is being parsed)
realm	LockOutRealm[StandardEngine[Catalina]]	(Associated realm.)
reloadable	false	(The reloadable flag for this web application)
renewThreadsWhenStoppingContext	true	(Should Tomcat renew the threads of the thread pool when the application is stopped to avoid memory leaks because of uncleaned ThreadLocal variables.)
requestCount	57 714	(Cumulative request count of all servlets in this context)
server	null	(The J2EE Server this module is deployed on)
sessionCookieDomain	null	(The domain to use for session cookies.'null' indicates that the domain is controlled by the application.)
sessionCookieName	null	(The name to use for session cookies.'null' indicates that the name is controlled by the application.)
sessionCookiePath	null	(The path to use for session cookies.'null' indicates that the path is controlled by the application.)
sessionTimeout	30	(The session timeout (in minutes) for this web application)
startTime	1 763 407 080 118	(Time (in milliseconds since January 1, 1970, 00:00:00) when this context was started)
startupTime	0	(Time (in milliseconds) it took to start this context)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
swallowOutput	false	(Flag to set to cause the system.out and system.err to be redirected to the logger when executing a servlet)
tldScanTime	0	(Time spend scanning jars for TLDs for this context)
tldValidation	false	(Should the parsing of *.tld files be performed by a validating parser?)
unloadDelay	2 000	(Amount of ms that the container will wait for servlets to unload)
unpackWAR	true	(Unpack WAR property)
useHttpOnly	true	(Indicates that session cookies should use HttpOnly)
useNaming	true	(Create a JNDI naming context for this application?)
useRelativeRedirects	true	(When generating location headers for 302 responses, should a relative URI be used?)
webappVersion		(The version of this web application - used in parallel deployment to differentiate different versions of the same web application)
welcomeFiles	[index.html, index.htm, index.jsp]	(The welcome files for this context)
workDir	work/Catalina/localhost/ROOT	(The pathname to the work directory for this context)
xmlNamespaceAware	false	(Should the parsing of web.xml and web-fragment.xml files be performed by a namespace aware parser?)
xmlValidation	false	(Should the parsing of web.xml and web-fragment.xml files be performed by a validating parser?)

name=/localhost/demo,J2EEApplication=none,J2EEServer=none

(Standard Context Component)		
altDDName	null	(The alternate deployment descriptor name.)
antiResourceLocking	false	(Take care to not lock resources)
baseName	demo	(The base name used for directories, WAR files (with .war appended) and context.xml files (with .xml appended).)
children	[Catalina:j2eeType=Servlet,WebModule=/localhost/demo,name=CompetenceService,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=Servlet,WebModule=/localhost/demo,name=Gra deService,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=Servlet,WebModule=/localhost/demo,name=Per soneService,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=Servlet,WebModule=/localhost/demo,name=Print UtilsService,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=Servlet,WebModule=/localhost/demo,name=Adr esseService,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=Servlet,WebModule=/localhost/demo,name=Utili sateurService,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=Servlet,WebModule=/localhost/demo,name=jsp,J 2EEApplication=none,J2EEServer=none, Catalina:j2eeType=Servlet,WebModule=/localhost/demo,name=Buil dInfoServlet,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=Servlet,WebModule=/localhost/demo,name=Per missionService,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=Servlet,WebModule=/localhost/demo,name=defa ult,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=Servlet,WebModule=/localhost/demo,name=Mail Service,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=Servlet,WebModule=/localhost/demo,name=Role Service,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=Servlet,WebModule=/localhost/demo,name=Tele phoneService,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=Servlet,WebModule=/localhost/demo,name=Auth entificationService,J2EEApplication=none,J2EEServer=none]	(Object names of all children)
clearReferencesRmiTargets	true	(Should Tomcat look for memory leaks in RMI Targets and clear them if found as a work around for application coding errors?)
clearReferencesStopThreads	false	(Should Tomcat attempt to terminate threads that have been started by the web application? Advisable to be used only in a development environment.)
clearReferencesStopTimerThreads	false	(Should Tomcat attempt to terminate TimerThreads that have been started by the web application? Advisable to be used only in a development environment.)

clearReferencesThreadLocals	true	(Should Tomcat attempt to clear ThreadLocal variables that have been populated with classes loaded by the web application?)
configFile	file:/opt/apache-tomcat-9.0.33/conf/Catalina/localhost/demo.xml	(Location of the context.xml resource or file)
configured	true	(The correctly configured flag for this Context.)
cookies	true	(Should we attempt to use cookies for session id communication?)
crossContext	false	(Should we allow the ServletContext.getContext() method to access the context of other web applications in this server?)
defaultContextXml	null	(Location of the default context.xml resource or file)
defaultWebXml	null	(Location of the default web.xml resource or file)
delegate	false	
displayName	null	(The display name of this web application)
distributable	false	(The distributable flag for this web application.)
docBase	demo.war	(The document root for this web application)
encodedPath	/demo	(The encoded path)
errorCount	15 184	(Cumulative error count of all servlets in this context)
ignoreAnnotations	false	(Ignore annotations flag.)
instanceManager	org.apache.catalina.core.DefaultInstanceManager@39194cd9	(Object that creates and destroys servlets, filters, and listeners. Include dependency injection and postConstruct/preDestroy handling)
javaVMs	null	(The Java virtual machines on which this module is running)
loader	WebappLoader[StandardEngine[Catalina].StandardHost[localhost].StandardContext[/demo]]	(Associated loader.)
logEffectiveWebXml	false	(Should the effective web.xml be logged when the context starts?)
logger	org.apache.juli.logging.DirectJDKLog@40d04149	(Associated logger.)
managedResource	StandardEngine[Catalina].StandardHost[localhost].StandardContext[/demo]	(The managed resource this MBean is associated with)
manager	StandardManager[StandardEngine[Catalina].StandardHost[localhost].StandardContext[/demo]]	(Associated manager.)
mapperContextRootRedirectEnabled	true	(Should the Mapper be used for context root redirects)
mapperDirectoryRedirectEnabled	false	(Should the Mapper be used for directory redirects)
maxTime	64 100	(Maximum execution time of all servlets in this context)
minTime	0	(Minimum execution time of all servlets in this context)
modelerType	org.apache.catalina.core.StandardContext	(Type of the modeled resource. Can be set only once)
name	/demo	(The name of this Context)
namingContextListener	org.apache.catalina.core.NamingContextListener@1cf8ee5b	(Associated naming context listener.)
objectName	Catalina:j2eeType=WebModule,name=/localhost/demo,J2EEApplication=none,J2EEServer=none	(Name of the object)
originalDocBase	/opt/apache-tomcat-9.0.33/webapps/demo	(The original document root for this web application)
override	false	(The default context.xml override flag for this web application)
parentClassLoader	java.net.URLClassLoader@6f1fba17	(Parent class loader.)
path	/demo	(The context path for this Context)
paused	false	(The request processing pause flag (while reloading occurs))
privileged	false	(Access to tomcat internals)
processingTime	27 329 668	(Cumulative execution times of all servlets in this context)
publicId	null	(The public identifier of the DTD for the web application deployment descriptor version that is being parsed)
realm	LockOutRealm[StandardEngine[Catalina]]	(Associated realm.)
reloadable	false	(The reloadable flag for this web application)
renewThreadsWhenStoppingContext	true	(Should Tomcat renew the threads of the thread pool when the application is stopped to avoid memory leaks because of uncleaned ThreadLocal variables.)
requestCount	147 594	(Cumulative request count of all servlets in this context)
server	null	(The J2EE Server this module is deployed on)
sessionCookieDomain	null	(The domain to use for session cookies.'null' indicates that the domain is controlled by the application.)
sessionCookieName	null	(The name to use for session cookies.'null' indicates that the name is controlled by the application.)
sessionCookiePath	null	(The path to use for session cookies.'null' indicates that the path is controlled by the application.)
sessionTimeout	30	(The session timeout (in minutes) for this web application)
startTime	1 763 406 633 076	(Time (in milliseconds since January 1, 1970, 00:00:00) when this context was started)
startupTime	2 462	(Time (in milliseconds) it took to start this context)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
swallowOutput	false	(Flag to set to cause the system.out and system.err to be redirected to the logger when executing a servlet)
tdlScanTime	0	(Time spend scanning jars for TLDs for this context)
tdlValidation	false	(Should the parsing of *.tdl files be performed by a validating parser?)
unloadDelay	2 000	(Amount of ms that the container will wait for servlets to unload)
unpackWAR	true	(Unpack WAR property)
useHttpOnly	true	(Indicates that session cookies should use HttpOnly)
useNaming	true	(Create a JNDI naming context for this application?)
useRelativeRedirects	true	(When generating location headers for 302 responses, should a relative URI be used?)
webappVersion		(The version of this web application - used in parallel deployment to differentiate different versions of the same web application)
welcomeFiles	[index.html]	(The welcome files for this context)
workDir	work/Catalina/localhost/demo	(The pathname to the work directory for this context)
xmlNamespaceAware	false	(Should the parsing of web.xml and web-fragment.xml files be performed by a namespace aware parser?)
xmlValidation	false	(Should the parsing of web.xml and web-fragment.xml files be performed by a validating parser?)

name=/localhost/downloads,J2EEApplication=none,J2EEServer=none

(Standard Context Component)

altDDName	null	(The alternate deployment descriptor name.)
antiResourceLocking	false	(Take care to not lock resources)

baseName	downloads	(The base name used for directories, WAR files (with .war appended) and context.xml files (with .xml appended).)
children	[Catalina:j2eeType=Servlet,WebModule=/localhost/downloads,name=default,J2EEApplication=none,J2EEServer=none,Catalina:j2eeType=Servlet,WebModule=/localhost/downloads,name=jsp,J2EEApplication=none,J2EEServer=none]	(Object names of all children)
clearReferencesRmiTargets	true	(Should Tomcat look for memory leaks in RMI Targets and clear them if found as a work around for application coding errors?)
clearReferencesStopThreads	false	(Should Tomcat attempt to terminate threads that have been started by the web application? Advisable to be used only in a development environment.)
clearReferencesStopTimerThreads	false	(Should Tomcat attempt to terminate TimerThreads that have been started by the web application? Advisable to be used only in a development environment.)
clearReferencesThreadLocals	true	(Should Tomcat attempt to clear ThreadLocal variables that have been populated with classes loaded by the web application?)
configFile	null	(Location of the context.xml resource or file)
configured	true	(The correctly configured flag for this Context.)
cookies	true	(Should we attempt to use cookies for session id communication?)
crossContext	false	(Should we allow the ServletContext.getContext() method to access the context of other web applications in this server?)
defaultContextXml	null	(Location of the default context.xml resource or file)
defaultWebXml	null	(Location of the default web.xml resource or file)
delegate	false	
displayName	null	(The display name of this web application)
distributable	false	(The distributable flag for this web application.)
docBase	downloads	(The document root for this web application)
encodedPath	/downloads	(The encoded path)
errorCount	46	(Cumulative error count of all servlets in this context)
ignoreAnnotations	false	(Ignore annotations flag.)
instanceManager	org.apache.catalina.core.DefaultInstanceManager@3d8ccc45	(Object that creates and destroys servlets, filters, and listeners. Include dependency injection and postConstruct/preDestroy handling)
javaVMs	null	(The Java virtual machines on which this module is running)
loader	WebappLoader[StandardEngine[Catalina].StandardHost[localhost].StandardContext[/downloads]]	(Associated loader.)
logEffectiveWebXml	false	(Should the effective web.xml be logged when the context starts?)
logger	org.apache.juli.logging.DirectJDKLog@7cf9d787	(Associated logger.)
managedResource	StandardEngine[Catalina].StandardHost[localhost].StandardContext[/downloads]	(The managed resource this MBean is associated with)
manager	StandardManager[StandardEngine[Catalina].StandardHost[localhost].StandardContext[/downloads]]	(Associated manager.)
mapperContextRootRedirectEnabled	true	(Should the Mapper be used for context root redirects)
mapperDirectoryRedirectEnabled	false	(Should the Mapper be used for directory redirects)
maxTime	19	(Maximum execution time of all servlets in this context)
minTime	0	(Minimum execution time of all servlets in this context)
modelerType	org.apache.catalina.core.StandardContext	(Type of the modeled resource. Can be set only once)
name	/downloads	(The name of this Context)
namingContextListener	org.apache.catalina.core.NamingContextListener@1bed406e	(Associated naming context listener.)
objectName	Catalina:j2eeType=WebModule,name=/localhost/downloads,J2EEApplication=none,J2EEServer=none	(Name of the object)
originalDocBase	null	(The original document root for this web application)
override	false	(The default context.xml override flag for this web application)
parentClassLoader	java.net.URLClassLoader@6f1fba17	(Parent class loader.)
path	/downloads	(The context path for this Context)
paused	false	(The request processing pause flag (while reloading occurs))
privileged	false	(Access to tomcat internals)
processingTime	63	(Cumulative execution times of all servlets in this context)
publicId	null	(The public identifier of the DTD for the web application deployment descriptor version that is being parsed)
realm	LockOutRealm[StandardEngine[Catalina]]	(Associated realm.)
reloadable	false	(The reloadable flag for this web application)
renewThreadsWhenStoppingContext	true	(Should Tomcat renew the threads of the thread pool when the application is stopped to avoid memory leaks because of uncleaned ThreadLocal variables.)
requestCount	60	(Cumulative request count of all servlets in this context)
server	null	(The J2EE Server this module is deployed on)
sessionCookieDomain	null	(The domain to use for session cookies.'null' indicates that the domain is controlled by the application.)
sessionCookieName	null	(The name to use for session cookies.'null' indicates that the name is controlled by the application.)
sessionCookiePath	null	(The path to use for session cookies.'null' indicates that the path is controlled by the application.)
sessionTimeout	30	(The session timeout (in minutes) for this web application)
startTime	1 763 407 080 038	(Time (in milliseconds since January 1, 1970, 00:00:00) when this context was started)
startupTime	1	(Time (in milliseconds) it took to start this context)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
swallowOutput	false	(Flag to set to cause the system.out and system.err to be redirected to the logger when executing a servlet)
tldScanTime	0	(Time spend scanning jars for TLDs for this context)
tldValidation	false	(Should the parsing of *.tld files be performed by a validating parser?)
unloadDelay	2 000	(Amount of ms that the container will wait for servlets to unload)
unpackWAR	true	(Unpack WAR property)
useHttpOnly	true	(Indicates that session cookies should use HttpOnly)
useNaming	true	(Create a JNDI naming context for this application?)
useRelativeRedirects	true	(When generating location headers for 302 responses, should a relative URI be used?)
webappVersion		(The version of this web application - used in parallel deployment to differentiate different versions of the same web application)

welcomeFiles	[index.html, index.htm, index.jsp]	(The welcome files for this context)
workDir	work/Catalina/localhost/downloads	(The pathname to the work directory for this context)
xmlNamespaceAware	false	(Should the parsing of web.xml and web-fragment.xml files be performed by a namespace aware parser?)
xmlValidation	false	(Should the parsing of web.xml and web-fragment.xml files be performed by a validating parser?)

name=/localhost/usage,J2EEApplication=none,J2EEServer=none

(Standard Context Component)		
altDDName	null	(The alternate deployment descriptor name.)
antiResourceLocking	false	(Take care to not lock resources)
baseName	usage	(The base name used for directories, WAR files (with .war appended) and context.xml files (with .xml appended).)
children	[Catalina:j2eeType=Servlet,WebModule=/localhost/usage,name=defaut,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=Servlet,WebModule=/localhost/usage,name=jsp,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=Servlet,WebModule=/localhost/usage,name=usagestats,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=Servlet,WebModule=/localhost/usage,name=admin,J2EEApplication=none,J2EEServer=none]	(Object names of all children)
clearReferencesRmiTargets	true	(Should Tomcat look for memory leaks in RMI Targets and clear them if found as a work around for application coding errors?)
clearReferencesStopThreads	false	(Should Tomcat attempt to terminate threads that have been started by the web application? Advisable to be used only in a development environment.)
clearReferencesStopTimerThreads	false	(Should Tomcat attempt to terminate TimerThreads that have been started by the web application? Advisable to be used only in a development environment.)
clearReferencesThreadLocals	true	(Should Tomcat attempt to clear ThreadLocal variables that have been populated with classes loaded by the web application?)
configFile	file:/opt/apache-tomcat-9.0.33/conf/Catalina/localhost/usage.xml	(Location of the context.xml resource or file)
configured	true	(The correctly configured flag for this Context.)
cookies	true	(Should we attempt to use cookies for session id communication?)
crossContext	false	(Should we allow the ServletContext.getContext() method to access the context of other web applications in this server?)
defaultContextXml	null	(Location of the default context.xml resource or file)
defaultWebXml	null	(Location of the default web.xml resource or file)
delegate	false	
displayName	javamelody-usagestats	(The display name of this web application)
distributable	true	(The distributable flag for this web application.)
docBase	usage.war	(The document root for this web application)
encodedPath	/usage	(The encoded path)
errorCount	44	(Cumulative error count of all servlets in this context)
ignoreAnnotations	false	(Ignore annotations flag.)
instanceManager	org.apache.catalina.core.DefaultInstanceManager@7d0836ca	(Object that creates and destroys servlets, filters, and listeners. Include dependency injection and postConstruct/preDestroy handling)
javaVMs	null	(The Java virtual machines on which this module is running)
loader	WebappLoader[StandardEngine[Catalina],StandardHost[localhost],StandardContext[/usage]]	(Associated loader.)
logEffectiveWebXml	false	(Should the effective web.xml be logged when the context starts?)
logger	org.apache.juli.logging.DirectJDKLog@258d44eb	(Associated logger.)
managedResource	StandardEngine[Catalina],StandardHost[localhost],StandardContext[/usage]	(The managed resource this MBean is associated with)
manager	StandardManager[StandardEngine[Catalina],StandardHost[localhost],StandardContext[/usage]]	(Associated manager.)
mapperContextRootRedirectEnabled	true	(Should the Mapper be used for context root redirects)
mapperDirectoryRedirectEnabled	false	(Should the Mapper be used for directory redirects)
maxTime	22.329	(Maximum execution time of all servlets in this context)
minTime	0	(Minimum execution time of all servlets in this context)
modelerType	org.apache.catalina.core.StandardContext	(Type of the modeled resource. Can be set only once)
name	/usage	(The name of this Context)
namingContextListener	org.apache.catalina.core.NamingContextListener@74b63bbb	(Associated naming context listener.)
objectName	Catalina:j2eeType=WebModule,name=/localhost/usage,J2EEApplication=none,J2EEServer=none	(Name of the object)
originalDocBase	/opt/apache-tomcat-9.0.33/webapps/usage	(The original document root for this web application)
override	false	(The default context.xml override flag for this web application)
parentClassLoader	java.net.URLClassLoader@6f1fba17	(Parent class loader.)
path	/usage	(The context path for this Context)
paused	false	(The request processing pause flag (while reloading occurs))
privileged	false	(Access to tomcat internals)
processingTime	6.007.593	(Cumulative execution times of all servlets in this context)
publicId	null	(The public identifier of the DTD for the web application deployment descriptor version that is being parsed)
realm	LockOutRealm[StandardEngine[Catalina]]	(Associated realm.)
reloadable	false	(The reloadable flag for this web application)
renewThreadsWhenStoppingContext	true	(Should Tomcat renew the threads of the thread pool when the application is stopped to avoid memory leaks because of uncleaned ThreadLocal variables.)
requestCount	23.682.866	(Cumulative request count of all servlets in this context)
server	null	(The J2EE Server this module is deployed on)
sessionCookieDomain	null	(The domain to use for session cookies.'null' indicates that the domain is controlled by the application.)
sessionCookieName	null	(The name to use for session cookies.'null' indicates that the name is controlled by the application.)
sessionCookiePath	null	(The path to use for session cookies.'null' indicates that the path is controlled by the application.)
sessionTimeout	30	(The session timeout (in minutes) for this web application)
startTime	1.763.407.079.922	(Time (in milliseconds since January 1, 1970, 00:00:00) when this context was started)

startupTime	190	(Time (in milliseconds) it took to start this context)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
swallowOutput	false	(Flag to set to cause the system.out and system.err to be redirected to the logger when executing a servlet)
tldScanTime	0	(Time spend scanning jars for TLDs for this context)
tldValidation	false	(Should the parsing of *.tld files be performed by a validating parser?)
unloadDelay	2 000	(Amount of ms that the container will wait for servlets to unload)
unpackWAR	true	(Unpack WAR property)
useHttpOnly	true	(Indicates that session cookies should use HttpOnly)
useNaming	true	(Create a JNDI naming context for this application?)
useRelativeRedirects	true	(When generating location headers for 302 responses, should a relative URI be used?)
webappVersion		(The version of this web application - used in parallel deployment to differentiate different versions of the same web application)
welcomeFiles	[index.html]	(The welcome files for this context)
workDir	work/Catalina/localhost/usage	(The pathname to the work directory for this context)
xmlNamespaceAware	false	(Should the parsing of web.xml and web-fragment.xml files be performed by a namespace aware parser?)
xmlValidation	false	(Should the parsing of web.xml and web-fragment.xml files be performed by a validating parser?)

WebResourceRoot

host=localhost,context=/

(Provides the resources implementation for a web application)

allowLinking	false	(Does this resources implementation allow the use of symbolic links?)
cachingAllowed	true	(Is in memory caching of resource content and metadata enabled?)
modelerType	org.apache.catalina.webresources.StandardRoot	(Type of the modeled resource. Can be set only once)
stateName	STARTED	(The current Lifecycle state of this object)
trackLockedFiles	false	(Does this resources implementation track requests that lock files?)
trackedResources	[]	(List of resources currently being tracked for possible resource leaks)

host=localhost,context=/,name=Cache

(Provides caching of resource metadata and content)

hitCount	131 641	(The number of requests for resources that were served from the cache)
lookupCount	141 895	(The number of requests for resources)
maxSize	10 240	(The maximum permitted size of the cache in kB)
modelerType	org.apache.catalina.webresources.Cache	(Type of the modeled resource. Can be set only once)
objectMaxSize	512	(The maximum permitted size for a single object in the cache in kB)
size	4 996	(The current estimate of the cache size in kB)
ttl	5 000	(The time-to-live for cache entries in milliseconds)

host=localhost,context=/demo

(Provides the resources implementation for a web application)

allowLinking	false	(Does this resources implementation allow the use of symbolic links?)
cachingAllowed	true	(Is in memory caching of resource content and metadata enabled?)
modelerType	org.apache.catalina.webresources.StandardRoot	(Type of the modeled resource. Can be set only once)
stateName	STARTED	(The current Lifecycle state of this object)
trackLockedFiles	false	(Does this resources implementation track requests that lock files?)
trackedResources	[]	(List of resources currently being tracked for possible resource leaks)

host=localhost,context=/demo,name=Cache

(Provides caching of resource metadata and content)

hitCount	187 014	(The number of requests for resources that were served from the cache)
lookupCount	187 309	(The number of requests for resources)
maxSize	10 240	(The maximum permitted size of the cache in kB)
modelerType	org.apache.catalina.webresources.Cache	(Type of the modeled resource. Can be set only once)
objectMaxSize	512	(The maximum permitted size for a single object in the cache in kB)
size	2 623	(The current estimate of the cache size in kB)
ttl	5 000	(The time-to-live for cache entries in milliseconds)

host=localhost,context=/downloads

(Provides the resources implementation for a web application)

allowLinking	false	(Does this resources implementation allow the use of symbolic links?)
cachingAllowed	true	(Is in memory caching of resource content and metadata enabled?)
modelerType	org.apache.catalina.webresources.StandardRoot	(Type of the modeled resource. Can be set only once)
stateName	STARTED	(The current Lifecycle state of this object)
trackLockedFiles	false	(Does this resources implementation track requests that lock files?)
trackedResources	[]	(List of resources currently being tracked for possible resource leaks)

host=localhost,context=/downloads,name=Cache

(Provides caching of resource metadata and content)

hitCount	39	(The number of requests for resources that were served from the cache)
lookupCount	85	(The number of requests for resources)
maxSize	10 240	(The maximum permitted size of the cache in kB)
modelerType	org.apache.catalina.webresources.Cache	(Type of the modeled resource. Can be set only once)

objectMaxSize	512	(The maximum permitted size for a single object in the cache in kB)
size	21	(The current estimate of the cache size in kB)
ttl	5 000	(The time-to-live for cache entries in milliseconds)

host=localhost,context=/usage

(Provides the resources implementation for a web application)

allowLinking	false	(Does this resources implementation allow the use of symbolic links?)
cachingAllowed	true	(Is in memory caching of resource content and metadata enabled?)
modelerType	org.apache.catalina.webresources.StandardRoot	(Type of the modeled resource. Can be set only once)
stateName	STARTED	(The current Lifecycle state of this object)
trackLockedFiles	false	(Does this resources implementation track requests that lock files?)
trackedResources	[]	(List of resources currently being tracked for possible resource leaks)

host=localhost,context=/usage,name=Cache

(Provides caching of resource metadata and content)

hitCount	472	(The number of requests for resources that were served from the cache)
lookupCount	509	(The number of requests for resources)
maxSize	10 240	(The maximum permitted size of the cache in kB)
modelerType	org.apache.catalina.webresources.Cache	(Type of the modeled resource. Can be set only once)
objectMaxSize	512	(The maximum permitted size for a single object in the cache in kB)
size	38	(The current estimate of the cache size in kB)
ttl	5 000	(The time-to-live for cache entries in milliseconds)

JMImplementation

MBeanServerDelegate

(Represents the MBean server from the management point of view.)

ImplementationName	JMX	(The JMX implementation name (the name of this product))
ImplementationVendor	Oracle Corporation	(the JMX implementation vendor (the vendor of this product).)
ImplementationVersion	11.0.6+10	(The JMX implementation version (the version of this product).)
MBeanServerId	vps363300.ovh.net_1763406487222	(The MBean server agent identification)
SpecificationName	Java Management Extensions	(The full name of the JMX specification implemented by this product.)
SpecificationVendor	Oracle Corporation	(The vendor of the JMX specification implemented by this product.)
SpecificationVersion	1.4	(The version of the JMX specification implemented by this product.)

Users

UserDatabase

database=UserDatabase

(In-memory user and group database)

groups	[]	(MBean Names of all defined groups)
modelerType	org.apache.catalina.users.MemoryUserDatabase	(Type of the modeled resource. Can be set only once)
pathname	conf/tomcat-users.xml	(Relative or absolute pathname to database file)
readonly	true	(No persistent save of the user database)
roles	[]	(MBean Names of all defined roles)
users	[]	(MBean Names of all defined users)
writeable	true	(Check if user database is writeable)

com.sun.management

DiagnosticCommand

(Diagnostic Commands)

HotSpotDiagnostic

DiagnosticOptions

```
{(name=HeapDumpBeforeFullGC, origin=DEFAULT, value=false, writeable=true),
(name=HeapDumpAfterFullGC, origin=DEFAULT, value=false, writeable=true),
(name=HeapDumpOnOutOfMemoryError, origin=DEFAULT, value=false, writeable=true),
(name=HeapDumpPath, origin=DEFAULT, value=, writeable=true),
(name=PrintClassHistogram, origin=DEFAULT, value=false, writeable=true),
(name=MinHeapFreeRatio, origin=DEFAULT, value=40, writeable=true),
(name=MaxHeapFreeRatio, origin=DEFAULT, value=70, writeable=true),
(name=PrintConcurrentLocks, origin=DEFAULT, value=false, writeable=true),
(name=CMSAbortablePrecleanWaitMillis, origin=DEFAULT, value=100, writeable=true),
(name=CMSWaitDuration, origin=DEFAULT, value=2000, writeable=true),
(name=CMSTriggerInterval, origin=DEFAULT, value=-1, writeable=true)}
```

ObjectName com.sun.management:type=HotSpotDiagnostic

java.lang

ClassLoading

LoadedClassCount	9 169
ObjectName	java.lang:type=ClassLoading
TotalLoadedClassCount	21 053
UnloadedClassCount	11 884
Verbose	false

CodeCacheManager

type=MemoryManager

MemoryPoolNames

Name

ObjectName

Valid

[CodeHeap 'non-nmethods',
CodeHeap 'profiled nmethods',
CodeHeap 'non-profiled nmethods']

CodeCacheManager

java.lang:type=MemoryManager,name=CodeCacheManager

true

CodeHeap 'non-nmethods'

type=MemoryPool

CollectionUsage

CollectionUsageThresholdSupported

MemoryManagerNames

Name

ObjectName

PeakUsage

Type

Usage

UsageThreshold

UsageThresholdCount

UsageThresholdExceeded

UsageThresholdSupported

Valid

null

false

[CodeCacheManager]

CodeHeap 'non-nmethods'

java.lang:type=MemoryPool,name=CodeHeap 'non-nmethods'

{committed=2 555 904, init=2 555 904, max=5 828 608,
used=1 499 520}

NON_HEAP

{committed=2 555 904, init=2 555 904, max=5 828 608,
used=1 443 328}

0

0

false

true

true

CodeHeap 'non-profiled nmethods'

type=MemoryPool

CollectionUsage

CollectionUsageThresholdSupported

MemoryManagerNames

Name

ObjectName

PeakUsage

Type

Usage

UsageThreshold

UsageThresholdCount

UsageThresholdExceeded

UsageThresholdSupported

Valid

null

false

[CodeCacheManager]

CodeHeap 'non-profiled nmethods'

java.lang:type=MemoryPool,name=CodeHeap 'non-profiled
nmethods'{committed=26 542 080, init=2 555 904, max=122 916 864,
used=24 945 536}

NON_HEAP

{committed=26 542 080, init=2 555 904, max=122 916 864,
used=24 868 480}

0

0

false

true

true

CodeHeap 'profiled nmethods'

type=MemoryPool

CollectionUsage

CollectionUsageThresholdSupported

MemoryManagerNames

Name

ObjectName

PeakUsage

Type

Usage

UsageThreshold

UsageThresholdCount

UsageThresholdExceeded

UsageThresholdSupported

Valid

null

false

[CodeCacheManager]

CodeHeap 'profiled nmethods'

java.lang:type=MemoryPool,name=CodeHeap 'profiled nmethods'

{committed=23 527 424, init=2 555 904, max=122 912 768,
used=23 038 080}

NON_HEAP

{committed=23 527 424, init=2 555 904, max=122 912 768,
used=17 282 304}

0

0

false

true

true

Compilation

CompilationTimeMonitoringSupported

Name

ObjectName

TotalCompilationTime

true

HotSpot 64-Bit Tiered Compilers

java.lang:type=Compilation

578 217

Compressed Class Space

type=MemoryPool

CollectionUsage

CollectionUsageThresholdSupported

MemoryManagerNames

Name

ObjectName

PeakUsage

null

false

[Metaspace Manager]

Compressed Class Space

java.lang:type=MemoryPool,name=Compressed Class Space

{committed=7 430 144, init=0, max=1 073 741 824, used=6 792 504}

Type	NON_HEAP
Usage	{committed=7 430 144, init=0, max=1 073 741 824, used=6 682 240}
UsageThreshold	0
UsageThresholdCount	0
UsageThresholdExceeded	false
UsageThresholdSupported	true
Valid	true

Copy

type=GarbageCollector

CollectionCount	54 811
CollectionTime	2 125 844
LastGcInfo	{GcThreadCount=1, duration=37, endTime=3 594 319 532, id=54 811, memoryUsageAfterGc={GcThreadCount=1, duration=37, endTime=3594319532, id=54811, memoryUsageAfterGc={key=CodeHeap 'profiled nmethods', value={committed=23527424, init=2555904, max=122912768, used=17249664}}, {key=Eden Space, value={committed=87031808, init=8912896, max=136445952, used=0}}, {key=CodeHeap 'non-profiled nmethods', value={committed=26542080, init=2555904, max=122916864, used=24871040}}, {key=Survivor Space, value={committed=10813440, init=1114112, max=17039360, used=3494568}}, {key=Compressed Class Space, value={committed=7430144, init=0, max=1073741824, used=6680032}}, {key=Metaspace, value={committed=78471168, init=0, max=-1, used=75750944}}, {key=CodeHeap 'non-nmethods', value={committed=2555904, init=2555904, max=5828608, used=1443328}}, {key=Tenured Gen, value={committed=217190400, init=22413312, max=341180416, used=98491352}}}, memoryUsageBeforeGc={key=CodeHeap 'profiled nmethods', value={committed=23527424, init=2555904, max=122912768, used=17249664}}, {key=Eden Space, value={committed=87031808, init=8912896, max=136445952, used=87031808}}, {key=CodeHeap 'non-profiled nmethods', value={committed=26542080, init=2555904, max=122916864, used=24871040}}, {key=Survivor Space, value={committed=10813440, init=1114112, max=17039360, used=3026648}}, {key=Compressed Class Space, value={committed=7430144, init=0, max=1073741824, used=6680032}}, {key=Metaspace, value={committed=78471168, init=0, max=-1, used=75750944}}, {key=CodeHeap 'non-nmethods', value={committed=2555904, init=2555904, max=5828608, used=1443328}}, {key=Tenured Gen, value={committed=217190400, init=22413312, max=341180416, used=98491352}}}, startTime=3594319495}, memoryUsageBeforeGc={GcThreadCount=1, duration=37, endTime=3594319532, id=54811, memoryUsageAfterGc={key=CodeHeap 'profiled nmethods', value={committed=23527424, init=2555904, max=122912768, used=17249664}}, {key=Eden Space, value={committed=87031808, init=8912896, max=136445952, used=0}}, {key=CodeHeap 'non-profiled nmethods', value={committed=26542080, init=2555904, max=122916864, used=24871040}}, {key=Survivor Space, value={committed=10813440, init=1114112, max=17039360, used=3494568}}, {key=Compressed Class Space, value={committed=7430144, init=0, max=1073741824, used=6680032}}, {key=Metaspace, value={committed=78471168, init=0, max=-1, used=75750944}}, {key=CodeHeap 'non-nmethods', value={committed=2555904, init=2555904, max=5828608, used=1443328}}, {key=Tenured Gen, value={committed=217190400, init=22413312, max=341180416, used=98491352}}}, memoryUsageBeforeGc={key=CodeHeap 'profiled nmethods', value={committed=23527424, init=2555904, max=122912768, used=17249664}}, {key=Eden Space, value={committed=87031808, init=8912896, max=136445952, used=87031808}}, {key=CodeHeap 'non-profiled nmethods', value={committed=26542080, init=2555904, max=122916864, used=24871040}}, {key=Survivor Space, value={committed=10813440, init=1114112, max=17039360, used=3026648}}, {key=Compressed Class Space, value={committed=7430144, init=0, max=1073741824, used=6680032}}, {key=Metaspace, value={committed=78471168, init=0, max=-1, used=75750944}}, {key=CodeHeap 'non-nmethods', value={committed=2555904, init=2555904, max=5828608, used=1443328}}, {key=Tenured Gen, value={committed=217190400, init=22413312, max=341180416, used=98491352}}}, startTime=3594319495}, startTime=3 594 319 495}
MemoryPoolNames	[Eden Space, Survivor Space]
Name	Copy
ObjectName	java.lang:type=GarbageCollector,name=Copy
Valid	true

Eden Space

type=MemoryPool

CollectionUsage	{committed=87 031 808, init=8 912 896, max=136 445 952, used=0}
CollectionUsageThreshold	0
CollectionUsageThresholdCount	0
CollectionUsageThresholdExceeded	false
CollectionUsageThresholdSupported	true
MemoryManagerNames	[Copy, MarkSweepCompact]
Name	Eden Space
ObjectName	java.lang:type=MemoryPool,name=Eden Space
PeakUsage	{committed=136 445 952, init=8 912 896, max=136 445 952, used=136 445 952}
Type	HEAP
Usage	{committed=87 031 808, init=8 912 896, max=136 445 952, used=11 105 392}
UsageThresholdSupported	false
Valid	true

MarkSweepCompact

type=GarbageCollector

CollectionCount	2 405
CollectionTime	2 004 409

```

LastGcInfo
{GcThreadCount=1, duration=211, endTime=3 577 538 581,
id=2 405, memoryUsageAfterGc={GcThreadCount=1, duration=211,
endTime=3577538581, id=2405,
memoryUsageAfterGc={key=CodeHeap 'profiled nmethods',
value=(committed=23527424, init=2555904, max=122912768,
used=17251584)}, {key=Eden Space,
value=(committed=114950144, init=8912896, max=136445952,
used=0)}, {key=CodeHeap 'non-profiled nmethods',
value=(committed=26542080, init=2555904, max=122916864,
used=24880000)}, {key=Survivor Space,
value=(committed=14352384, init=1114112, max=17039360,
used=0)}, {key=Compressed Class Space,
value=(committed=7430144, init=0, max=1073741824,
used=6630904)}, {key=Metaspace, value=(committed=78471168,
init=0, max=-1, used=75413856)}, {key=CodeHeap 'non-nmethods',
value=(committed=2555904, init=2555904, max=5828608,
used=1443328)}, {key=Tenured Gen, value=(committed=287207424,
init=22413312, max=341180416, used=65156824)}},
memoryUsageBeforeGc={key=CodeHeap 'profiled nmethods',
value=(committed=23527424, init=2555904, max=122912768,
used=17251584)}, {key=Eden Space,
value=(committed=114950144, init=8912896, max=136445952,
used=770048)}, {key=CodeHeap 'non-profiled nmethods',
value=(committed=26542080, init=2555904, max=122916864,
used=24880000)}, {key=Survivor Space,
value=(committed=14352384, init=1114112, max=17039360,
used=0)}, {key=Compressed Class Space,
value=(committed=7430144, init=0, max=1073741824,
used=6630904)}, {key=Metaspace, value=(committed=78471168,
init=0, max=-1, used=75413856)}, {key=CodeHeap 'non-nmethods',
value=(committed=2555904, init=2555904, max=5828608,
used=1443328)}, {key=Tenured Gen, value=(committed=287207424,
init=22413312, max=341180416, used=65125032)}},
startTime=3577538370},
memoryUsageBeforeGc={GcThreadCount=1, duration=211,
endTime=3577538581, id=2405,
memoryUsageAfterGc={key=CodeHeap 'profiled nmethods',
value=(committed=23527424, init=2555904, max=122912768,
used=17251584)}, {key=Eden Space,
value=(committed=114950144, init=8912896, max=136445952,
used=0)}, {key=CodeHeap 'non-profiled nmethods',
value=(committed=26542080, init=2555904, max=122916864,
used=24880000)}, {key=Survivor Space,
value=(committed=14352384, init=1114112, max=17039360,
used=0)}, {key=Compressed Class Space,
value=(committed=7430144, init=0, max=1073741824,
used=6630904)}, {key=Metaspace, value=(committed=78471168,
init=0, max=-1, used=75413856)}, {key=CodeHeap 'non-nmethods',
value=(committed=2555904, init=2555904, max=5828608,
used=1443328)}, {key=Tenured Gen, value=(committed=287207424,
init=22413312, max=341180416, used=65156824)}},
memoryUsageBeforeGc={key=CodeHeap 'profiled nmethods',
value=(committed=23527424, init=2555904, max=122912768,
used=17251584)}, {key=Eden Space,
value=(committed=114950144, init=8912896, max=136445952,
used=770048)}, {key=CodeHeap 'non-profiled nmethods',
value=(committed=26542080, init=2555904, max=122916864,
used=24880000)}, {key=Survivor Space,
value=(committed=14352384, init=1114112, max=17039360,
used=0)}, {key=Compressed Class Space,
value=(committed=7430144, init=0, max=1073741824,
used=6630904)}, {key=Metaspace, value=(committed=78471168,
init=0, max=-1, used=75413856)}, {key=CodeHeap 'non-nmethods',
value=(committed=2555904, init=2555904, max=5828608,
used=1443328)}, {key=Tenured Gen, value=(committed=287207424,
init=22413312, max=341180416, used=65125032)}},
startTime=3577538370}, startTime=3 577 538 370)

MemoryPoolNames
[Eden Space,
Survivor Space,
Tenured Gen]

Name
MarkSweepCompact

ObjectName
java.lang:type=GarbageCollector,name=MarkSweepCompact

Valid
true

```

Memory

```

HeapMemoryUsage
{committed=315 035 648, init=33 554 432, max=494 665 728,
used=114 992 616}

NonHeapMemoryUsage
{committed=138 526 720, init=7 667 712, max=-1, used=126 115 488}

ObjectName
java.lang:type=Memory

ObjectPendingFinalizationCount
0

Verbose
false

```

Metaspace

```

type=MemoryPool
CollectionUsage
null
CollectionUsageThresholdSupported
false
MemoryManagerNames
[Metaspace Manager]
Name
Metaspace
ObjectName
java.lang:type=MemoryPool,name=Metaspace
PeakUsage
{committed=78 471 168, init=0, max=-1, used=76 039 080}
Type
NON_HEAP
Usage
{committed=78 471 168, init=0, max=-1, used=75 758 000}
UsageThreshold
0
UsageThresholdCount
0
UsageThresholdExceeded
false
UsageThresholdSupported
true
Valid
true

```

Metaspace Manager

```

type=MemoryManager
MemoryPoolNames
[Metaspace,
Compressed Class Space]
Name
Metaspace Manager
ObjectName
java.lang:type=MemoryManager,name=Metaspace Manager
Valid
true

```

OperatingSystem

Arch	amd64
AvailableProcessors	1
CommittedVirtualMemorySize	2 886 533 120
FreePhysicalMemorySize	274 112 512
FreeSwapSpaceSize	0
MaxFileDescriptorCount	500 000
Name	Linux
ObjectName	java.lang:type=OperatingSystem
OpenFileDescriptorCount	195
ProcessCpuLoad	0
ProcessCpuTime	78 490 890 000 000
SystemCpuLoad	1
SystemLoadAverage	0
TotalPhysicalMemorySize	2 045 435 904
TotalSwapSpaceSize	0
Version	3.10.0-1160.114.2.el7.x86_64

Runtime

BootClassPathSupported	false
ClassPath	/opt/tomcat/bin/bootstrap.jar:/opt/tomcat/bin/tomcat-juli.jar
InputArguments	[-add-opens=java.base/java.lang=ALL-UNNAMED, --add-opens=java.base/java.io=ALL-UNNAMED, --add-opens=java.rmi/sun.rmi.transport=ALL-UNNAMED, -Djava.util.logging.config.file=/opt/tomcat/conf/logging.properties, -Djava.util.logging.manager=org.apache.juli.ClassLoaderLogManager, -Djdk.tls.ephemeralDHKeySize=2048, -Djava.protocol.handler.pkgs=org.apache.catalina.webresources, -Dorg.apache.catalina.security.SecurityListener.UMASK=0027, -Djava.security.egd=file:/dev/./urandom, -Dignore.endorsed.dirs=, -Dcatalina.base=/opt/tomcat, -Dcatalina.home=/opt/tomcat, -Djava.io.tmpdir=/opt/tomcat/temp]
LibraryPath	/usr/java/packages/lib:/usr/lib64:/lib64:/lib:/usr/lib
ManagementSpecVersion	2.0
Name	31087@vps363300.ovh.net
ObjectName	java.lang:type=Runtime
Pid	31 087
SpecName	Java Virtual Machine Specification
SpecVendor	Oracle Corporation
SpecVersion	11
StartTime	1 763 406 485 899

SystemProperties	<pre> {{key=awt.toolkit, value=sun.awt.X11.XToolkit}, key=java.specification.version, value=11}, key=sun.cpu.isalist, value=}, key=sun.jnu.encoding, value=ANSI_X3.4-1968}, key=java.class.path, value=/opt/tomcat/bin/bootstrap.jar:/opt/tomcat/bin/tomcat-juli.jar}, key=pid, value=31087}, key=java.vm.vendor, value=AdoptOpenJDK}, key=sun.arch.data.model, value=64}, key=sun.font.fontmanager, value=sun.awt.X11FontManager}, key=java.vendor.url, value=https://adoptopenjdk.net/}, key=catalina.useNaming, value=true}, key=user.timezone, value=Europe/Paris}, key=os.name, value=Linux}, key=java.vm.specification.version, value=11}, key=sun.java.launcher, value=SUN_STANDARD}, key=user.country, value=US}, key=sun.boot.library.path, value=/opt/jdk-11.0.6+10/lib}, key=sun.java.command, value=org.apache.catalina.startup.Bootstrap start}, key=jdk.debug, value=release}, key=sun.cpu.endian, value=little}, key=user.home, value=/root}, key=user.language, value=en}, key=java.specification.vendor, value=Oracle Corporation}, key=java.naming.factory.url.pkgs, value=org.apache.naming}, key=java.version.date, value=2020-01-14}, key=java.home, value=/opt/jdk-11.0.6+10}, key=ignore.endorsed.dirs, value=}, key=file.separator, value=/}, key=java.vm.compressedOopsMode, value=32-bit}, key=line.separator, value= }, key=java.specification.name, value=Java Platform API Specification}, key=java.vm.specification.vendor, value=Oracle Corporation}, key=java.awt.graphicsenv, value=sun.awt.X11GraphicsEnvironment}, key=package.access, value=sun.org.apache.catalina.org.apache.coyote.org.apache.jasper .org.apache.tomcat}, key=package.definition, value=sun.java.org.apache.catalina.org.apache.coyote.org.apache.j asper.org.apache.naming.org.apache.tomcat}, key=jdk.tls.ephemeralDHKeySize, value=2048}, key=server.loader, value=}, key=java.util.logging.config.file, value=/opt/tomcat/conf/logging.properties}, key=java.protocol.handler.pkgs, value=org.apache.catalina.webresources}, key=sun.management.compiler, value=HotSpot 64-Bit Tiered Compilers}, key=java.runtime.version, value=11.0.6+10}, key=java.naming.factory.initial, value=org.apache.naming.java.javaURLContextFactory}, key=user.name, value=root}, key=path.separator, value=}, key=java.security.egd, value=file:/dev/.urandom}, key=common.loader, value=\${catalina.base}/lib/*:\${catalina.base}/lib/*.jar:\${catalina.home }/lib/*:\${catalina.home}/lib/*.jar}, key=os.version, value=3.10.0-1160.114.2.el7.x86_64}, key=java.runtime.name, value=OpenJDK Runtime Environment}, key=file.encoding, value=UTF-8}, key=java.vm.name, value=OpenJDK 64-Bit Server VM}, key=java.vendor.version, value=AdoptOpenJDK}, key=org.apache.catalina.security.SecurityListener.UMASK, value=0027}, key=java.vendor.url.bug, value=https://github.com/AdoptOpenJDK/openjdk-support/issues}, key=java.io.tmpdir, value=/opt/tomcat/temp}, key=tomcat.util.scan.StandardJarScanFilter.jarsToScan, value=log4j- taglib.jar,log4j-web.jar,log4jjavascript.jar,slf4j-taglib.jar}, key=catalina.home, value=/opt/apache-tomcat-9.0.33}, key=java.version, value=11.0.6}, key=tomcat.util.scan.StandardJarScanFilter.jarsToSkip, value=annotations-api.jar,ant-junit.jar,ant-launcher.jar,ant.jar,asm- *.jar,aspectj.jar,bootstrap.jar,catalina-ant.jar,catalina-ha.jar,catalina- ssi.jar,catalina-storeconfig.jar,catalina-tribes.jar,catalina.jar,cglib- *.jar,coertura-*.jar,commons-beanutils.jar,commons- codec.jar,commons-collections.jar,commons-daemon.jar,commons- dbcp.jar,commons-digester.jar,commons-fileupload.jar,commons- httpclient.jar,commons-io.jar,commons-lang.jar,commons- logging.jar,commons-math.jar,commons-pool.jar,dom4j- *.jar,easymock.jar,ecj-*.jar,el-api.jar,geronimo-spec- jaxrpc.jar,h2.jar,hamcrest.jar,hibernate.jar,httpClient.jar,icu4j- *.jar,jasper-el.jar,jasper.jar,jaspic-api.jar,jaxb-*.jar,jaxen-*.jar,jdom- .jar,jetty-*.jar,jmx-tools.jar,jmx.jar,jsp-api.jar,jstl.jar,jta.jar,junit- *.jar,junit.jar,log4j.jar,mail.jar,objenesis.jar,oraclepk.jar,oro- *.jar,servlet-api.jar,servlet-api.jar,slf4j.jar,taglibs-standard-spec- .jar,tagsoup.jar,tomcat-api.jar,tomcat-coyote.jar,tomcat- dbcp.jar,tomcat-11n.jar,tomcat-jdbc.jar,tomcat-jni.jar,tomcat-juli- adapters.jar,tomcat-juli.jar,tomcat-util-scan.jar,tomcat-util.jar,tomcat- websocket.jar,tools.jar,websocket-api.jar,wsdl4j.jar,xercesImpl.jar,xml- apis.jar,xmlParserAPIs.jar,xmlParserAPIs.xom.jar}, key=user.dir, value=/}, key=os.arch, value=amd64}, key=java.vm.specification.name, value=Java Virtual Machine Specification}, key=java.awt.printerjob, value=sun.print.PSPrinterJob}, key=sun.os.patch.level, value=unknown}, key=catalina.base, value=/opt/apache-tomcat-9.0.33}, key=shared.loader, value=}, key=java.util.logging.manager, value=org.apache.juli.ClassLoaderLogManager}, key=java.library.path, value=/usr/java/packages/lib:/usr/lib64:/lib64:/lib:/usr/lib}, key=java.vendor, value=AdoptOpenJDK}, key=java.vm.info, value=mixed mode}, key=java.vm.version, value=11.0.6+10}, key=sun.io.unicode.encoding, value=UnicodeLittle}, key=tomcat.util.buf.StringCache.byte.enabled, value=true}, key=java.class.version, value=55.0}} </pre>
Uptime	3 594 428 042
VmName	OpenJDK 64-Bit Server VM
VmVendor	AdoptOpenJDK
VmVersion	11.0.6+10

Survivor Space

type=MemoryPool

CollectionUsage	(committed=10 813 440, init=1 114 112, max=17 039 360, used=3 494 568)
CollectionUsageThreshold	0
CollectionUsageThresholdCount	0
CollectionUsageThresholdExceeded	false
CollectionUsageThresholdSupported	true
MemoryManagerNames	[Copy, MarkSweepCompact]

Monitoring JavaMelody sur /demo_vps363300.ovh.net

Name	Survivor Space
ObjectName	java.lang:type=MemoryPool,name=Survivor Space
PeakUsage	{committed=17 039 360, init=1 114 112, max=17 039 360, used=17 039 360}
Type	HEAP
Usage	{committed=10 813 440, init=1 114 112, max=17 039 360, used=3 494 568}
UsageThresholdSupported	false
Valid	true

Tenured Gen

type=MemoryPool

CollectionUsage	{committed=287 207 424, init=22 413 312, max=341 180 416, used=65 156 824}
CollectionUsageThreshold	0
CollectionUsageThresholdCount	0
CollectionUsageThresholdExceeded	false
CollectionUsageThresholdSupported	true
MemoryManagerNames	[MarkSweepCompact]
Name	Tenured Gen
ObjectName	java.lang:type=MemoryPool,name=Tenured Gen
PeakUsage	{committed=341 180 416, init=22 413 312, max=341 180 416, used=341 180 416}
Type	HEAP
Usage	{committed=217 190 400, init=22 413 312, max=341 180 416, used=98 491 352}
UsageThreshold	0
UsageThresholdCount	0
UsageThresholdExceeded	false
UsageThresholdSupported	true
Valid	true

Threading

AllThreadIds	[J@675f3a70
CurrentThreadCpuTime	276 453 627 246
CurrentThreadCpuTimeSupported	true
CurrentThreadUserTime	237 080 000 000
DaemonThreadCount	61
ObjectMonitorUsageSupported	true
ObjectName	java.lang:type=Threading
PeakThreadCount	155
SynchronizerUsageSupported	true
ThreadAllocatedMemoryEnabled	true
ThreadAllocatedMemorySupported	true
ThreadContentionMonitoringEnabled	false
ThreadContentionMonitoringSupported	true
ThreadCount	66
ThreadCpuTimeEnabled	true
ThreadCpuTimeSupported	true
TotalStartedThreadCount	1 407

java.nio

direct

type=BufferPool

Count	50
MemoryUsed	429 482
Name	direct
ObjectName	java.nio:type=BufferPool,name=direct
TotalCapacity	429 482

mapped

type=BufferPool

Count	0
MemoryUsed	0
Name	mapped
ObjectName	java.nio:type=BufferPool,name=mapped
TotalCapacity	0

java.util.logging

Logging

LoggerNames

```
[
org.apache.catalina.core.ContainerBase.[Catalina],
org.apache.catalina.session,
org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo].[
default],
sun.net.www.protocol.http,
org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo].[
TelephoneService],
org.apache.tomcat.dbcp.dbcp2.BasicDataSource,
org.apache.catalina.core.ApplicationFilterConfig,
org.apache.jasper,
org.apache.jasper.servlet.JasperInitializer,
org.apache.jasper.compiler.Compiler,
org.apache.catalina.util,
org.apache.tomcat.util.descriptor.web.WebXmlParser,
org.apache.catalina.webresources,
jdk.event,
org.apache.tomcat.util.net,
org.apache.tomcat.util.digester.Digester,
sun.awt.multiscreen.SunDisplayChanger,
sun.awt.X11GraphicsEnvironment,
org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo].[
GradeService],
org.apache.jasper.compiler,
org.apache.tomcat.util.descriptor.web,
org.apache.jasper.servlet.JspServlet,
org.apache.tomcat.websocket,
org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo],
org.apache.catalina.webresources.JarWarResource,
org.apache.tomcat.dbcp,
org.apache.tomcat.dbcp.dbcp2.ObjectNameWrapper,
org.apache.tomcat.util.descriptor,
org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo].[
MailService],
org.apache.catalina,
sun.net.www.protocol.http.HttpURLConnection,
org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo].[
AdresseService],
org.apache.tomcat,
org.apache.jasper.servlet,
org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo].[
PersonneService],
org.apache.catalina.webresources.JarResourceRoot,
jdk.event.security,
org.apache.tomcat.util.digester.Digester.sax,
org.apache.jasper.JspCompilationContext,
org.apache,
org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo].[
CompetenceService],
sun.net,
org.apache.catalina.core.ContainerBase,
org.apache.tomcat.util.descriptor.web.WebXml,
org.apache.jasper.servlet.TldScanner,
org.apache.jasper.compiler.JDTCompiler,
org.apache.tomcat.util.descriptor.tld,
org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo].[
AuthenticationService],
sun,
sun.net.www.protocol,
sun.net.www,
sun.awt.multiscreen,
org.apache.jasper.EmbeddedServletOptions,
org.apache.tomcat.dbcp.dbcp2,
org.apache.jasper.compiler.JspConfig,
org.apache.tomcat.util.scan,
org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo].[
PermissionService],
org.apache.tomcat.dbcp.dbcp2.BasicDataSourceFactory,
org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo].[
BuildInfoServlet],
org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo].[
RoleService],
org.apache.catalina.core.ContainerBase.[Catalina].[localhost],
org.apache.tomcat.util.digester,
org.apache.catalina.util.SessionIdGeneratorBase,
org.apache.tomcat.util.net.SSLHostConfig,
org.apache.tomcat.dbcp.dbcp2.PoolableConnectionFactory,
sun.awt.screen,
org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo].[
UtilisateurService],
sun.awt.screen.X11GraphicsEnvironment,
org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo].[
jsp],
org.apache.tomcat.dbcp.dbcp2.PoolingDataSource,
sun.awt,
org,
org.apache.catalina.session.ManagerBase,
org.apache.catalina.authenticator.AuthenticatorBase,
org.apache.catalina.session.StandardManager,
org.apache.tomcat.util.descriptor.tld.TldParser,
org.apache.catalina.authenticator,
org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo].[
PrintUtilsService],
jdk,
org.apache.jasper.servlet.JspServletWrapper,
org.apache.tomcat.util,
org.apache.tomcat.util.net.SSLHostConfigCertificate,
org.apache.jasper.compiler.JspRuntimeContext,
org.apache.catalina.core.StandardWrapper,
org.apache.tomcat.util.scan.StandardJarScanner,
org.apache.tomcat.websocket.WsWebSocketContainer,
org.apache.catalina.core]
]
```

ObjectName

java.util.logging:type=Logging

jdk.management.jfr
FlightRecorder

Configurations

```

{{contents=<?xml version="1.0" encoding="UTF-8"?>
<!--
Recommended way to edit .jfc files is to use Java Mission Control,
see Window -> Flight Recorder Template Manager.
-->
<configuration version="2.0" label="Profiling" description="Low
overhead configuration for profiling, typically around 2 % overhead."
provider="Oracle">

  <event name="jdk.ThreadAllocationStatistics">
    <setting name="enabled">true</setting>
    <setting name="period">everyChunk</setting>
  </event>

  <event name="jdk.ClassLoadingStatistics">
    <setting name="enabled">true</setting>
    <setting name="period">1000 ms</setting>
  </event>

  <event name="jdk.ClassLoaderStatistics">
    <setting name="enabled">true</setting>
    <setting name="period">everyChunk</setting>
  </event>

  <event name="jdk.JavaThreadStatistics">
    <setting name="enabled">true</setting>
    <setting name="period">1000 ms</setting>
  </event>

  <event name="jdk.ThreadStart">
    <setting name="enabled">true</setting>
  </event>

  <event name="jdk.ThreadEnd">
    <setting name="enabled">true</setting>
  </event>

  <event name="jdk.ThreadSleep">
    <setting name="enabled">true</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold" control="synchronization-threshold">10
ms</setting>
  </event>

  <event name="jdk.ThreadPark">
    <setting name="enabled">true</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold" control="synchronization-threshold">10
ms</setting>
  </event>

  <event name="jdk.JavaMonitorEnter">
    <setting name="enabled">true</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold" control="synchronization-threshold">10
ms</setting>
  </event>

  <event name="jdk.JavaMonitorWait">
    <setting name="enabled">true</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold" control="synchronization-threshold">10
ms</setting>
  </event>

  <event name="jdk.JavaMonitorInflate">
    <setting name="enabled">true</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold" control="synchronization-threshold">10
ms</setting>
  </event>

  <event name="jdk.BiasedLockRevocation">
    <setting name="enabled">true</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.BiasedLockSelfRevocation">
    <setting name="enabled">true</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.BiasedLockClassRevocation">
    <setting name="enabled">true</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.ReservedStackActivation">
    <setting name="enabled">true</setting>
    <setting name="stackTrace">true</setting>
  </event>

  <event name="jdk.ClassLoad">
    <setting name="enabled" control="class-loading-
enabled">false</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.ClassDefine">
    <setting name="enabled" control="class-loading-
enabled">false</setting>
    <setting name="stackTrace">true</setting>
  </event>

  <event name="jdk.ClassUnload">
    <setting name="enabled" control="class-loading-
enabled">false</setting>
  </event>

  <event name="jdk.JVMInformation">
    <setting name="enabled">true</setting>
    <setting name="period">beginChunk</setting>
  </event>

  <event name="jdk.InitialSystemProperty">
    <setting name="enabled">true</setting>
    <setting name="period">beginChunk</setting>
  </event>

  <event name="jdk.ExecutionSample">
    <setting name="enabled" control="method-sampling-
enabled">true</setting>
    <setting name="period" control="method-sampling-java-
interval">10 ms</setting>
  </event>

  <event name="jdk.NativeMethodSample">
    <setting name="enabled" control="method-sampling-
enabled">true</setting>
    <setting name="period" control="method-sampling-native-
interval">20 ms</setting>
  </event>

```

```

<event name="jdk.SafepointBegin">
  <setting name="enabled">true</setting>
  <setting name="threshold">0 ms</setting>
</event>

<event name="jdk.SafepointStateSynchronization">
  <setting name="enabled">>false</setting>
  <setting name="threshold">0 ms</setting>
</event>

<event name="jdk.SafepointWaitBlocked">
  <setting name="enabled">>false</setting>
  <setting name="threshold">0 ms</setting>
</event>

<event name="jdk.SafepointCleanup">
  <setting name="enabled">>false</setting>
  <setting name="threshold">0 ms</setting>
</event>

<event name="jdk.SafepointCleanupTask">
  <setting name="enabled">>false</setting>
  <setting name="threshold">0 ms</setting>
</event>

<event name="jdk.SafepointEnd">
  <setting name="enabled">>false</setting>
  <setting name="threshold">0 ms</setting>
</event>

<event name="jdk.ExecuteVMOperation">
  <setting name="enabled">true</setting>
  <setting name="threshold">0 ms</setting>
</event>

<event name="jdk.Shutdown">
  <setting name="enabled">true</setting>
  <setting name="stackTrace">true</setting>
</event>

<event name="jdk.ThreadDump">
  <setting name="enabled" control="thread-dump-
enabled">true</setting>
  <setting name="period" control="thread-dump-interval">60
s</setting>
</event>

<event name="jdk.IntFlag">
  <setting name="enabled">true</setting>
  <setting name="period">beginChunk</setting>
</event>

<event name="jdk.UnsignedIntFlag">
  <setting name="enabled">true</setting>
  <setting name="period">beginChunk</setting>
</event>

<event name="jdk.LongFlag">
  <setting name="enabled">true</setting>
  <setting name="period">beginChunk</setting>
</event>

<event name="jdk.UnsignedLongFlag">
  <setting name="enabled">true</setting>
  <setting name="period">beginChunk</setting>
</event>

<event name="jdk.DoubleFlag">
  <setting name="enabled">true</setting>
  <setting name="period">beginChunk</setting>
</event>

<event name="jdk.BooleanFlag">
  <setting name="enabled">true</setting>
  <setting name="period">beginChunk</setting>
</event>

<event name="jdk.StringFlag">
  <setting name="enabled">true</setting>
  <setting name="period">beginChunk</setting>
</event>

<event name="jdk.IntFlagChanged">
  <setting name="enabled">true</setting>
</event>

<event name="jdk.UnsignedIntFlagChanged">
  <setting name="enabled">true</setting>
</event>

<event name="jdk.LongFlagChanged">
  <setting name="enabled">true</setting>
</event>

<event name="jdk.UnsignedLongFlagChanged">
  <setting name="enabled">true</setting>
</event>

<event name="jdk.DoubleFlagChanged">
  <setting name="enabled">true</setting>
</event>

<event name="jdk.BooleanFlagChanged">
  <setting name="enabled">true</setting>
</event>

<event name="jdk.StringFlagChanged">
  <setting name="enabled">true</setting>
</event>

<event name="jdk.ObjectCount">
  <setting name="enabled" control="memory-profiling-enabled-
all">>false</setting>
  <setting name="period">everyChunk</setting>
</event>

<event name="jdk.GCConfiguration">
  <setting name="enabled" control="gc-enabled-
normal">true</setting>
  <setting name="period">everyChunk</setting>
</event>

<event name="jdk.GCHeapConfiguration">
  <setting name="enabled" control="gc-enabled-
normal">true</setting>
  <setting name="period">beginChunk</setting>
</event>

<event name="jdk.YoungGenerationConfiguration">
  <setting name="enabled" control="gc-enabled-
normal">true</setting>
  <setting name="period">beginChunk</setting>
</event>

<event name="jdk.GCTLABConfiguration">
  <setting name="enabled" control="gc-enabled-
normal">true</setting>

```

```

<setting name="period">beginChunk</setting>
</event>

<event name="jdk.GCSurvivorConfiguration">
<setting name="enabled" control="gc-enabled-normal">true</setting>
<setting name="period">beginChunk</setting>
</event>

<event name="jdk.ObjectCountAfterGC">
<setting name="enabled">>false</setting>
</event>

<event name="jdk.GCHeapSummary">
<setting name="enabled" control="gc-enabled-normal">true</setting>
</event>

<event name="jdk.PSHeapSummary">
<setting name="enabled" control="gc-enabled-normal">true</setting>
</event>

<event name="jdk.G1HeapSummary">
<setting name="enabled" control="gc-enabled-normal">true</setting>
</event>

<event name="jdk.MetaspaceSummary">
<setting name="enabled" control="gc-enabled-normal">true</setting>
</event>

<event name="jdk.MetaspaceGCThreshold">
<setting name="enabled" control="gc-enabled-normal">true</setting>
</event>

<event name="jdk.MetaspaceAllocationFailure">
<setting name="enabled" control="gc-enabled-normal">true</setting>
<setting name="stackTrace">true</setting>
</event>

<event name="jdk.MetaspaceOOM">
<setting name="enabled" control="gc-enabled-normal">true</setting>
<setting name="stackTrace">true</setting>
</event>

<event name="jdk.MetaspaceChunkFreeListSummary">
<setting name="enabled" control="gc-enabled-normal">true</setting>
</event>

<event name="jdk.GarbageCollection">
<setting name="enabled" control="gc-enabled-normal">true</setting>
<setting name="threshold">0 ms</setting>
</event>

<event name="jdk.ParallelOldGarbageCollection">
<setting name="enabled" control="gc-enabled-normal">true</setting>
<setting name="threshold">0 ms</setting>
</event>

<event name="jdk.YoungGarbageCollection">
<setting name="enabled" control="gc-enabled-normal">true</setting>
<setting name="threshold">0 ms</setting>
</event>

<event name="jdk.OldGarbageCollection">
<setting name="enabled" control="gc-enabled-normal">true</setting>
<setting name="threshold">0 ms</setting>
</event>

<event name="jdk.G1GarbageCollection">
<setting name="enabled" control="gc-enabled-normal">true</setting>
<setting name="threshold">0 ms</setting>
</event>

<event name="jdk.GCPhasePause">
<setting name="enabled" control="gc-enabled-normal">true</setting>
<setting name="threshold">0 ms</setting>
</event>

<event name="jdk.GCPhasePauseLevel1">
<setting name="enabled" control="gc-enabled-normal">true</setting>
<setting name="threshold">0 ms</setting>
</event>

<event name="jdk.GCPhasePauseLevel2">
<setting name="enabled" control="gc-enabled-normal">true</setting>
<setting name="threshold">0 ms</setting>
</event>

<event name="jdk.GCPhasePauseLevel3">
<setting name="enabled" control="gc-enabled-all">>false</setting>
<setting name="threshold">0 ms</setting>
</event>

<event name="jdk.GCPhasePauseLevel4">
<setting name="enabled" control="gc-enabled-all">>false</setting>
<setting name="threshold">0 ms</setting>
</event>

<event name="jdk.GCPhaseConcurrent">
<setting name="enabled" control="gc-enabled-all">true</setting>
<setting name="threshold">0 ms</setting>
</event>

<event name="jdk.GCReferenceStatistics">
<setting name="enabled" control="gc-enabled-normal">true</setting>
</event>

<event name="jdk.PromotionFailed">
<setting name="enabled" control="gc-enabled-normal">true</setting>
</event>

<event name="jdk.EvacuationFailed">
<setting name="enabled" control="gc-enabled-normal">true</setting>
</event>

<event name="jdk.EvacuationInformation">
<setting name="enabled" control="gc-enabled-normal">true</setting>
</event>

```

```

<event name="jdk.G1MMU">
  <setting name="enabled" control="gc-enabled-normal">true</setting>
</event>

<event name="jdk.G1EvacuationYoungStatistics">
  <setting name="enabled" control="gc-enabled-normal">true</setting>
</event>

<event name="jdk.G1EvacuationOldStatistics">
  <setting name="enabled" control="gc-enabled-normal">true</setting>
</event>

<event name="jdk.G1BasicHOP">
  <setting name="enabled" control="gc-enabled-normal">true</setting>
</event>

<event name="jdk.G1AdaptiveHOP">
  <setting name="enabled" control="gc-enabled-normal">true</setting>
</event>

<event name="jdk.PromoteObjectInNewPLAB">
  <setting name="enabled" control="memory-profiling-enabled-medium">true</setting>
</event>

<event name="jdk.PromoteObjectOutsidePLAB">
  <setting name="enabled" control="memory-profiling-enabled-medium">true</setting>
</event>

<event name="jdk.ConcurrentModeFailure">
  <setting name="enabled" control="gc-enabled-normal">true</setting>
</event>

<event name="jdk.AllocationRequiringGC">
  <setting name="enabled" control="gc-enabled-all">>false</setting>
  <setting name="stackTrace">true</setting>
</event>

<event name="jdk.TenuringDistribution">
  <setting name="enabled" control="gc-enabled-normal">true</setting>
</event>

<event name="jdk.G1HeapRegionInformation">
  <setting name="enabled" control="gc-enabled-all">>false</setting>
  <setting name="period">everyChunk</setting>
</event>

<event name="jdk.G1HeapRegionTypeChange">
  <setting name="enabled" control="gc-enabled-all">>false</setting>
</event>

<event name="jdk.OldObjectSample">
  <setting name="enabled" control="memory-leak-detection-enabled">true</setting>
  <setting name="stackTrace" control="memory-leak-detection-stack-trace">true</setting>
  <setting name="cutoff" control="memory-leak-detection-cutoff">0ns</setting>
</event>

<event name="jdk.CompilerConfiguration">
  <setting name="enabled" control="compiler-enabled">true</setting>
  <setting name="period">beginChunk</setting>
</event>

<event name="jdk.CompilerStatistics">
  <setting name="enabled" control="compiler-enabled">true</setting>
  <setting name="period">1000 ms</setting>
</event>

<event name="jdk.Compilation">
  <setting name="enabled" control="compiler-enabled">true</setting>
  <setting name="threshold" control="compiler-compilation-threshold">100 ms</setting>
</event>

<event name="jdk.CompilerPhase">
  <setting name="enabled" control="compiler-enabled">true</setting>
  <setting name="threshold" control="compiler-phase-threshold">10s</setting>
</event>

<event name="jdk.CompilationFailure">
  <setting name="enabled" control="compiler-enabled-failure">true</setting>
</event>

<event name="jdk.CompilerInlining">
  <setting name="enabled" control="compiler-enabled-failure">>false</setting>
</event>

<event name="jdk.CodeSweeperConfiguration">
  <setting name="enabled" control="compiler-enabled">true</setting>
  <setting name="period">beginChunk</setting>
</event>

<event name="jdk.CodeSweeperStatistics">
  <setting name="enabled" control="compiler-enabled">true</setting>
  <setting name="period">everyChunk</setting>
</event>

<event name="jdk.SweepCodeCache">
  <setting name="enabled" control="compiler-enabled">true</setting>
  <setting name="threshold" control="compiler-sweeper-threshold">100 ms</setting>
</event>

<event name="jdk.CodeCacheConfiguration">
  <setting name="enabled" control="compiler-enabled">true</setting>
  <setting name="period">beginChunk</setting>
</event>

<event name="jdk.CodeCacheStatistics">
  <setting name="enabled" control="compiler-enabled">true</setting>
  <setting name="period">everyChunk</setting>
</event>

<event name="jdk.CodeCacheFull">
  <setting name="enabled" control="compiler-enabled">true</setting>

```

```

</event>
<event name="jdk.OSInformation">
  <setting name="enabled">true</setting>
  <setting name="period">beginChunk</setting>
</event>
<event name="jdk.VirtualizationInformation">
  <setting name="enabled">true</setting>
  <setting name="period">beginChunk</setting>
</event>
<event name="jdk.CPUInformation">
  <setting name="enabled">true</setting>
  <setting name="period">beginChunk</setting>
</event>
<event name="jdk.ThreadContextSwitchRate">
  <setting name="enabled" control="compiler-
enabled">true</setting>
  <setting name="period">10 s</setting>
</event>
<event name="jdk.CPULoad">
  <setting name="enabled">true</setting>
  <setting name="period">1000 ms</setting>
</event>
<event name="jdk.ThreadCPULoad">
  <setting name="enabled">true</setting>
  <setting name="period">10 s</setting>
</event>
<event name="jdk.CPUTimeStampCounter">
  <setting name="enabled">true</setting>
  <setting name="period">beginChunk</setting>
</event>
<event name="jdk.SystemProcess">
  <setting name="enabled">true</setting>
  <setting name="period">endChunk</setting>
</event>
<event name="jdk.NetworkUtilization">
  <setting name="enabled">true</setting>
  <setting name="period">5 s</setting>
</event>
<event name="jdk.InitialEnvironmentVariable">
  <setting name="enabled">true</setting>
  <setting name="period">beginChunk</setting>
</event>
<event name="jdk.PhysicalMemory">
  <setting name="enabled">true</setting>
  <setting name="period">everyChunk</setting>
</event>
<event name="jdk.ObjectAllocationInNewTLAB">
  <setting name="enabled" control="memory-profiling-enabled-
medium">true</setting>
  <setting name="stackTrace">true</setting>
</event>
<event name="jdk.ObjectAllocationOutsideTLAB">
  <setting name="enabled" control="memory-profiling-enabled-
medium">true</setting>
  <setting name="stackTrace">true</setting>
</event>
<event name="jdk.NativeLibrary">
  <setting name="enabled">true</setting>
  <setting name="period">everyChunk</setting>
</event>
<event name="jdk.ModuleRequire">
  <setting name="enabled">true</setting>
  <setting name="period">endChunk</setting>
</event>
<event name="jdk.ModuleExport">
  <setting name="enabled">true</setting>
  <setting name="period">endChunk</setting>
</event>
<event name="jdk.FileForce">
  <setting name="enabled">true</setting>
  <setting name="stackTrace">true</setting>
  <setting name="threshold" control="file-io-threshold">10
ms</setting>
</event>
<event name="jdk.FileRead">
  <setting name="enabled">true</setting>
  <setting name="stackTrace">true</setting>
  <setting name="threshold" control="file-io-threshold">10
ms</setting>
</event>
<event name="jdk.FileWrite">
  <setting name="enabled">true</setting>
  <setting name="stackTrace">true</setting>
  <setting name="threshold" control="file-io-threshold">10
ms</setting>
</event>
<event name="jdk.SocketRead">
  <setting name="enabled">true</setting>
  <setting name="stackTrace">true</setting>
  <setting name="threshold" control="socket-io-threshold">10
ms</setting>
</event>
<event name="jdk.SocketWrite">
  <setting name="enabled">true</setting>
  <setting name="stackTrace">true</setting>
  <setting name="threshold" control="socket-io-threshold">10
ms</setting>
</event>
<event name="jdk.SecurityPropertyModification">
  <setting name="enabled">>false</setting>
  <setting name="stackTrace">true</setting>
</event>
<event name="jdk.TLSHandshake">
  <setting name="enabled">>false</setting>
  <setting name="stackTrace">true</setting>
</event>
<event name="jdk.X509Validation">
  <setting name="enabled">>false</setting>
  <setting name="stackTrace">true</setting>
</event>
<event name="jdk.X509Certificate">
  <setting name="enabled">>false</setting>
  <setting name="stackTrace">true</setting>

```

```

</event>

<event name="jdk.JavaExceptionThrow">
  <setting name="enabled" control="enable-
exceptions">false</setting>
  <setting name="stackTrace">true</setting>
</event>

<event name="jdk.JavaErrorThrow">
  <setting name="enabled" control="enable-errors">true</setting>
  <setting name="stackTrace">true</setting>
</event>

<event name="jdk.ExceptionStatistics">
  <setting name="enabled">true</setting>
  <setting name="period">1000 ms</setting>
</event>

<event name="jdk.ActiveRecording">
  <setting name="enabled">true</setting>
</event>

<event name="jdk.ActiveSetting">
  <setting name="enabled">true</setting>
</event>

<event name="jdk.DataLoss">
  <setting name="enabled">true</setting>
</event>

<event name="jdk.DumpReason">
  <setting name="enabled">true</setting>
</event>

<event name="jdk.ZPageAllocation">
  <setting name="enabled">true</setting>
  <setting name="threshold">10 ms</setting>
</event>

<event name="jdk.ZThreadPhase">
  <setting name="enabled">true</setting>
  <setting name="threshold">0 ms</setting>
</event>

<event name="jdk.ZStatisticsCounter">
  <setting name="threshold">10 ms</setting>
  <setting name="enabled">true</setting>
</event>

<event name="jdk.ZStatisticsSampler">
  <setting name="enabled">true</setting>
  <setting name="threshold">10 ms</setting>
</event>

<!--
  Contents of the control element is not read by the JVM, it's used
  by Java Mission Control to change settings that carry the control
  attribute.
-->
<control>
  <selection name="gc-level" default="detailed" label="Garbage
Collector">
    <option label="Off" name="off">off</option>
    <option label="Normal" name="detailed">normal</option>
    <option label="All" name="all">all</option>
  </selection>

  <condition name="gc-enabled-normal" true="true" false="false">
    <or>
      <test name="gc-level" operator="equal" value="normal"/>
      <test name="gc-level" operator="equal" value="all"/>
    </or>
  </condition>

  <condition name="gc-enabled-all" true="true" false="false">
    <test name="gc-level" operator="equal" value="all"/>
  </condition>

  <selection name="memory-profiling" default="medium"
label="Memory Profiling">
    <option label="Off" name="off">off</option>
    <option label="Object Allocation and Promotion"
name="medium">medium</option>
    <option label="All, including Heap Statistics (May cause long full
GCs)" name="all">all</option>
  </selection>

  <condition name="memory-profiling-enabled-medium" true="true"
false="false">
    <or>
      <test name="memory-profiling" operator="equal"
value="medium"/>
      <test name="memory-profiling" operator="equal" value="all"/>
    </or>
  </condition>

  <condition name="memory-profiling-enabled-all" true="true"
false="false">
    <test name="memory-profiling" operator="equal" value="all"/>
  </condition>

  <selection name="compiler-level" default="detailed"
label="Compiler">
    <option label="Off" name="off">off</option>
    <option label="Normal" name="normal">normal</option>
    <option label="Detailed" name="detailed">detailed</option>
    <option label="All" name="all">all</option>
  </selection>

```

```

<condition name="compiler-enabled" true="false" false="true">
  <test name="compiler-level" operator="equal" value="off"/>
</condition>

<condition name="compiler-enabled-failure" true="true"
false="false">
  <or>
    <test name="compiler-level" operator="equal" value="detailed"/>
    <test name="compiler-level" operator="equal" value="all"/>
  </or>
</condition>

<condition name="compiler-sweeper-threshold" true="0 ms"
false="100 ms">
  <test name="compiler-level" operator="equal" value="all"/>
</condition>

<condition name="compiler-compilation-threshold" true="1000
ms">
  <test name="compiler-level" operator="equal" value="normal"/>
</condition>

<condition name="compiler-compilation-threshold" true="100 ms">
  <test name="compiler-level" operator="equal" value="detailed"/>
</condition>

<condition name="compiler-compilation-threshold" true="0 ms">
  <test name="compiler-level" operator="equal" value="all"/>
</condition>

<condition name="compiler-phase-threshold" true="60 s">
  <test name="compiler-level" operator="equal" value="normal"/>
</condition>

<condition name="compiler-phase-threshold" true="10 s">
  <test name="compiler-level" operator="equal" value="detailed"/>
</condition>

<condition name="compiler-phase-threshold" true="0 s">
  <test name="compiler-level" operator="equal" value="all"/>
</condition>

<selection name="method-sampling-interval" default="normal"
label="Method Sampling">
  <option label="Off" name="off">off</option>
  <option label="Normal" name="normal">normal</option>
  <option label="High" name="high">high</option>
  <option label="Ludicrous (High Overhead)"
name="ludicrous">ludicrous</option>
</selection>

<condition name="method-sampling-java-interval" true="999 d">
  <test name="method-sampling-interval" operator="equal"
value="off"/>
</condition>

<condition name="method-sampling-java-interval" true="20 ms">
  <test name="method-sampling-interval" operator="equal"
value="normal"/>
</condition>

<condition name="method-sampling-java-interval" true="10 ms">
  <test name="method-sampling-interval" operator="equal"
value="high"/>
</condition>

<condition name="method-sampling-java-interval" true="1 ms">
  <test name="method-sampling-interval" operator="equal"
value="ludicrous"/>
</condition>

<condition name="method-sampling-native-interval" true="999 d">
  <test name="method-sampling-interval" operator="equal"
value="off"/>
</condition>

<condition name="method-sampling-native-interval" true="20 ms">
  <or>
    <test name="method-sampling-interval" operator="equal"
value="normal"/>
    <test name="method-sampling-interval" operator="equal"
value="high"/>
    <test name="method-sampling-interval" operator="equal"
value="ludicrous"/>
  </or>
</condition>

<condition name="method-sampling-enabled" true="false"
false="true">
  <test name="method-sampling-interval" operator="equal"
value="off"/>
</condition>

<selection name="thread-dump-interval" default="everyMinute"
label="Thread Dump">
  <option label="Off" name="off">999 d</option>
  <option label="At least Once"
name="normal">everyChunk</option>
  <option label="Every 60 s" name="everyMinute">60 s</option>
  <option label="Every 10 s" name="everyTenSecond">10
s</option>
  <option label="Every 1 s" name="everySecond">1 s</option>
</selection>

<condition name="thread-dump-enabled" true="false" false="true">
  <test name="thread-dump-interval" operator="equal" value="999
d"/>
</condition>

<selection name="exception-level" default="errors"
label="Exceptions">
  <option label="Off" name="off">off</option>
  <option label="Errors Only" name="errors">errors</option>
  <option label="All Exceptions, including Errors"
name="all">all</option>
</selection>

<condition name="enable-errors" true="true" false="false">
  <or>
    <test name="exception-level" operator="equal" value="errors"/>
    <test name="exception-level" operator="equal" value="all"/>
  </or>
</condition>

<condition name="enable-exceptions" true="true" false="false">
  <test name="exception-level" operator="equal" value="all"/>
</condition>

<selection name="memory-leak-detection" default="medium"
label="Memory Leak Detection">
  <option label="Off" name="off">off</option>
  <option label="Object Types" name="minimal">minimal</option>
  <option label="Object Types + Allocation Stack Traces"
name="medium">medium</option>
  <option label="Object Types + Allocation Stack Traces + Path to
GC Root" name="full">full</option>
</selection>

```

```

<condition name="memory-leak-detection-enabled" true="false"
false="true">
  <test name="memory-leak-detection" operator="equal"
value="off"/>
</condition>

<condition name="memory-leak-detection-stack-trace" true="true"
false="false">
  <or>
    <test name="memory-leak-detection" operator="equal"
value="medium"/>
    <test name="memory-leak-detection" operator="equal"
value="full"/>
  </or>
</condition>

<condition name="memory-leak-detection-cutoff" true="1 h"
false="0 ns">
  <test name="memory-leak-detection" operator="equal"
value="full"/>
</condition>

<text name="synchronization-threshold" label="Synchronization
Threshold" contentType="timespan" minimum="0 s">10 ms</text>

<text name="file-io-threshold" label="File I/O Threshold"
contentType="timespan" minimum="0 s">10 ms</text>

<text name="socket-io-threshold" label="Socket I/O Threshold"
contentType="timespan" minimum="0 s">10 ms</text>

<flag name="class-loading-enabled" label="Class
Loading">false</flag>

</control>

</configuration>
<description=Low overhead configuration for profiling, typically around
2 % overhead., label=Profiling, name=profile, provider=Oracle,
settings={key=jdk.ThreadAllocationStatistics#enabled, value=true},
{key=jdk.ThreadAllocationStatistics#period, value=everyChunk},
{key=jdk.ClassLoadingStatistics#enabled, value=true},
{key=jdk.ClassLoadingStatistics#period, value=1000 ms},
{key=jdk.ClassLoaderStatistics#enabled, value=true},
{key=jdk.ClassLoaderStatistics#period, value=everyChunk},
{key=jdk.JavaThreadStatistics#enabled, value=true},
{key=jdk.JavaThreadStatistics#period, value=1000 ms},
{key=jdk.ThreadStart#enabled, value=true},
{key=jdk.ThreadEnd#enabled, value=true},
{key=jdk.ThreadSleep#enabled, value=true},
{key=jdk.ThreadSleep#stackTrace, value=true},
{key=jdk.ThreadSleep#threshold, value=10 ms},
{key=jdk.ThreadPark#enabled, value=true},
{key=jdk.ThreadPark#stackTrace, value=true},
{key=jdk.ThreadPark#threshold, value=10 ms},
{key=jdk.JavaMonitorEnter#enabled, value=true},
{key=jdk.JavaMonitorEnter#stackTrace, value=true},
{key=jdk.JavaMonitorEnter#threshold, value=10 ms},
{key=jdk.JavaMonitorWait#enabled, value=true},
{key=jdk.JavaMonitorWait#stackTrace, value=true},
{key=jdk.JavaMonitorWait#threshold, value=10 ms},
{key=jdk.JavaMonitorInflate#enabled, value=true},
{key=jdk.JavaMonitorInflate#stackTrace, value=true},
{key=jdk.JavaMonitorInflate#threshold, value=10 ms},
{key=jdk.BiasedLockRevocation#enabled, value=true},
{key=jdk.BiasedLockRevocation#stackTrace, value=true},
{key=jdk.BiasedLockRevocation#threshold, value=0 ms},
{key=jdk.BiasedLockSelfRevocation#enabled, value=true},
{key=jdk.BiasedLockSelfRevocation#stackTrace, value=true},
{key=jdk.BiasedLockSelfRevocation#threshold, value=0 ms},
{key=jdk.BiasedLockClassRevocation#enabled, value=true},
{key=jdk.BiasedLockClassRevocation#stackTrace, value=true},
{key=jdk.BiasedLockClassRevocation#threshold, value=0 ms},
{key=jdk.ReservedStackActivation#enabled, value=true},
{key=jdk.ReservedStackActivation#stackTrace, value=true},
{key=jdk.ClassLoad#enabled, value=false},
{key=jdk.ClassLoad#stackTrace, value=true},
{key=jdk.ClassLoad#threshold, value=0 ms},
{key=jdk.ClassDefine#enabled, value=false},
{key=jdk.ClassDefine#stackTrace, value=true},
{key=jdk.ClassUnload#enabled, value=false},
{key=jdk.JVMInformation#enabled, value=true},
{key=jdk.JVMInformation#period, value=beginChunk},
{key=jdk.InitialSystemProperty#enabled, value=true},
{key=jdk.InitialSystemProperty#period, value=beginChunk},
{key=jdk.ExecutionSample#enabled, value=true},
{key=jdk.ExecutionSample#period, value=10 ms},
{key=jdk.NativeMethodSample#enabled, value=true},
{key=jdk.NativeMethodSample#period, value=20 ms},
{key=jdk.SafePointBegin#enabled, value=true},
{key=jdk.SafePointBegin#threshold, value=0 ms},
{key=jdk.SafePointStateSynchronization#enabled, value=false},
{key=jdk.SafePointStateSynchronization#threshold, value=0 ms},
{key=jdk.SafePointWaitBlocked#enabled, value=false},
{key=jdk.SafePointWaitBlocked#threshold, value=0 ms},
{key=jdk.SafePointCleanup#enabled, value=false},
{key=jdk.SafePointCleanup#threshold, value=0 ms},
{key=jdk.SafePointCleanupTask#enabled, value=false},
{key=jdk.SafePointCleanupTask#threshold, value=0 ms},
{key=jdk.SafePointEnd#enabled, value=false},
{key=jdk.SafePointEnd#threshold, value=0 ms},
{key=jdk.ExecuteVMOperation#enabled, value=true},
{key=jdk.ExecuteVMOperation#threshold, value=0 ms},
{key=jdk.Shutdown#enabled, value=true},
{key=jdk.Shutdown#stackTrace, value=true},
{key=jdk.ThreadDump#enabled, value=true},
{key=jdk.ThreadDump#period, value=60 s}, {key=jdk.IntFlag#enabled,
value=true}, {key=jdk.IntFlag#period, value=beginChunk},
{key=jdk.UnsignedIntFlag#enabled, value=true},
{key=jdk.UnsignedIntFlag#period, value=beginChunk},
{key=jdk.LongFlag#enabled, value=true}, {key=jdk.LongFlag#period,
value=beginChunk}, {key=jdk.UnsignedLongFlag#enabled,
value=true}, {key=jdk.UnsignedLongFlag#period, value=beginChunk},
{key=jdk.DoubleFlag#enabled, value=true},
{key=jdk.DoubleFlag#period, value=beginChunk},
{key=jdk.BooleanFlag#enabled, value=true},
{key=jdk.BooleanFlag#period, value=beginChunk},
{key=jdk.StringFlag#enabled, value=true}, {key=jdk.StringFlag#period,
value=beginChunk}, {key=jdk.IntFlagChanged#enabled, value=true},
{key=jdk.UnsignedIntFlagChanged#enabled, value=true},
{key=jdk.LongFlagChanged#enabled, value=true},
{key=jdk.UnsignedLongFlagChanged#enabled, value=true},
{key=jdk.DoubleFlagChanged#enabled, value=true},
{key=jdk.BooleanFlagChanged#enabled, value=true},
{key=jdk.StringFlagChanged#enabled, value=true},
{key=jdk.ObjectCount#enabled, value=false},
{key=jdk.ObjectCount#period, value=everyChunk},
{key=jdk.GCConfiguration#enabled, value=true},
{key=jdk.GCConfiguration#period, value=everyChunk},
{key=jdk.GCHeapConfiguration#enabled, value=true},
{key=jdk.GCHeapConfiguration#period, value=beginChunk},
{key=jdk.YoungGenerationConfiguration#enabled, value=true},
{key=jdk.YoungGenerationConfiguration#period, value=beginChunk},
{key=jdk.GCTLABConfiguration#enabled, value=true},
{key=jdk.GCTLABConfiguration#period, value=beginChunk},
{key=jdk.GCSurvivorConfiguration#enabled, value=true},
{key=jdk.GCSurvivorConfiguration#period, value=beginChunk},
{key=jdk.ObjectCountAfterGC#enabled, value=false},

```



```

{key=jdk.GCHeapSummary#enabled, value=true},
{key=jdk.PSHeapSummary#enabled, value=true},
{key=jdk.G1HeapSummary#enabled, value=true},
{key=jdk.MetaspaceSummary#enabled, value=true},
{key=jdk.MetaspaceGCThreshold#enabled, value=true},
{key=jdk.MetaspaceAllocationFailure#enabled, value=true},
{key=jdk.MetaspaceAllocationFailure#stackTrace, value=true},
{key=jdk.MetaspaceOOM#enabled, value=true},
{key=jdk.MetaspaceOOM#stackTrace, value=true},
{key=jdk.MetaspaceChunkFreeListSummary#enabled, value=true},
{key=jdk.GarbageCollection#enabled, value=true},
{key=jdk.GarbageCollection#threshold, value=0 ms},
{key=jdk.ParallelOldGarbageCollection#enabled, value=true},
{key=jdk.ParallelOldGarbageCollection#threshold, value=0 ms},
{key=jdk.YoungGarbageCollection#enabled, value=true},
{key=jdk.YoungGarbageCollection#threshold, value=0 ms},
{key=jdk.OldGarbageCollection#enabled, value=true},
{key=jdk.OldGarbageCollection#threshold, value=0 ms},
{key=jdk.G1GarbageCollection#enabled, value=true},
{key=jdk.G1GarbageCollection#threshold, value=0 ms},
{key=jdk.GCPhasePause#enabled, value=true},
{key=jdk.GCPhasePause#threshold, value=0 ms},
{key=jdk.GCPhasePauseLevel1#enabled, value=true},
{key=jdk.GCPhasePauseLevel1#threshold, value=0 ms},
{key=jdk.GCPhasePauseLevel2#enabled, value=true},
{key=jdk.GCPhasePauseLevel2#threshold, value=0 ms},
{key=jdk.GCPhasePauseLevel3#enabled, value=false},
{key=jdk.GCPhasePauseLevel3#threshold, value=0 ms},
{key=jdk.GCPhasePauseLevel4#enabled, value=false},
{key=jdk.GCPhasePauseLevel4#threshold, value=0 ms},
{key=jdk.GCPhaseConcurrent#enabled, value=true},
{key=jdk.GCPhaseConcurrent#threshold, value=0 ms},
{key=jdk.GCReferenceStatistics#enabled, value=true},
{key=jdk.PromotionFailed#enabled, value=true},
{key=jdk.EvacuationFailed#enabled, value=true},
{key=jdk.EvacuationInformation#enabled, value=true},
{key=jdk.G1MMU#enabled, value=true},
{key=jdk.G1EvacuationYoungStatistics#enabled, value=true},
{key=jdk.G1EvacuationOldStatistics#enabled, value=true},
{key=jdk.G1BasicHOP#enabled, value=true},
{key=jdk.G1AdaptiveHOP#enabled, value=true},
{key=jdk.PromoteObjectInNewPLAB#enabled, value=true},
{key=jdk.PromoteObjectOutsidePLAB#enabled, value=true},
{key=jdk.ConcurrentModeFailure#enabled, value=true},
{key=jdk.AllocationRequiringGC#enabled, value=false},
{key=jdk.AllocationRequiringGC#stackTrace, value=true},
{key=jdk.TenuringDistribution#enabled, value=true},
{key=jdk.G1HeapRegionInformation#enabled, value=false},
{key=jdk.G1HeapRegionInformation#period, value=everyChunk},
{key=jdk.G1HeapRegionTypeChange#enabled, value=false},
{key=jdk.OldObjectSample#enabled, value=true},
{key=jdk.OldObjectSample#stackTrace, value=true},
{key=jdk.OldObjectSample#cutoff, value=0 ns},
{key=jdk.CompilerConfiguration#enabled, value=true},
{key=jdk.CompilerConfiguration#period, value=beginChunk},
{key=jdk.CompilerStatistics#enabled, value=true},
{key=jdk.CompilerStatistics#period, value=1000 ms},
{key=jdk.Compilation#enabled, value=true},
{key=jdk.Compilation#threshold, value=100 ms},
{key=jdk.CompilerPhase#enabled, value=true},
{key=jdk.CompilerPhase#threshold, value=10 s},
{key=jdk.CompilationFailure#enabled, value=true},
{key=jdk.CompilerInlining#enabled, value=false},
{key=jdk.CodeSweeperConfiguration#enabled, value=true},
{key=jdk.CodeSweeperConfiguration#period, value=beginChunk},
{key=jdk.CodeSweeperStatistics#enabled, value=true},
{key=jdk.CodeSweeperStatistics#period, value=everyChunk},
{key=jdk.SweepCodeCache#enabled, value=true},
{key=jdk.SweepCodeCache#threshold, value=100 ms},
{key=jdk.CodeCacheConfiguration#enabled, value=true},
{key=jdk.CodeCacheConfiguration#period, value=beginChunk},
{key=jdk.CodeCacheStatistics#enabled, value=true},
{key=jdk.CodeCacheStatistics#period, value=everyChunk},
{key=jdk.CodeCacheFull#enabled, value=true},
{key=jdk.OSInformation#enabled, value=true},
{key=jdk.OSInformation#period, value=beginChunk},
{key=jdk.VirtualizationInformation#enabled, value=true},
{key=jdk.VirtualizationInformation#period, value=beginChunk},
{key=jdk.CPUInformation#enabled, value=true},
{key=jdk.CPUInformation#period, value=beginChunk},
{key=jdk.ThreadContextSwitchRate#enabled, value=true},
{key=jdk.ThreadContextSwitchRate#period, value=10 s},
{key=jdk.CPULoad#enabled, value=true}, {key=jdk.CPULoad#period, value=1000 ms},
{key=jdk.ThreadCPULoad#enabled, value=true},
{key=jdk.ThreadCPULoad#period, value=10 s},
{key=jdk.CPUTimeStampCounter#enabled, value=true},
{key=jdk.CPUTimeStampCounter#period, value=beginChunk},
{key=jdk.SystemProcess#enabled, value=true},
{key=jdk.SystemProcess#period, value=endChunk},
{key=jdk.NetworkUtilization#enabled, value=true},
{key=jdk.NetworkUtilization#period, value=5 s},
{key=jdk.InitialEnvironmentVariable#enabled, value=true},
{key=jdk.InitialEnvironmentVariable#period, value=beginChunk},
{key=jdk.PhysicalMemory#enabled, value=true},
{key=jdk.PhysicalMemory#period, value=everyChunk},
{key=jdk.ObjectAllocationInNewTLAB#enabled, value=true},
{key=jdk.ObjectAllocationInNewTLAB#stackTrace, value=true},
{key=jdk.ObjectAllocationOutsideTLAB#enabled, value=true},
{key=jdk.ObjectAllocationOutsideTLAB#stackTrace, value=true},
{key=jdk.NativeLibrary#enabled, value=true},
{key=jdk.NativeLibrary#period, value=everyChunk},
{key=jdk.ModuleRequire#enabled, value=true},
{key=jdk.ModuleRequire#period, value=endChunk},
{key=jdk.ModuleExport#enabled, value=true},
{key=jdk.ModuleExport#period, value=endChunk},
{key=jdk.FileForce#enabled, value=true},
{key=jdk.FileForce#stackTrace, value=true},
{key=jdk.FileForce#threshold, value=10 ms},
{key=jdk.FileRead#enabled, value=true},
{key=jdk.FileRead#stackTrace, value=true},
{key=jdk.FileRead#threshold, value=10 ms},
{key=jdk.FileWrite#enabled, value=true},
{key=jdk.FileWrite#stackTrace, value=true},
{key=jdk.FileWrite#threshold, value=10 ms},
{key=jdk.SocketRead#enabled, value=true},
{key=jdk.SocketRead#stackTrace, value=true},
{key=jdk.SocketRead#threshold, value=10 ms},
{key=jdk.SocketWrite#enabled, value=true},
{key=jdk.SocketWrite#stackTrace, value=true},
{key=jdk.SocketWrite#threshold, value=10 ms},
{key=jdk.SecurityPropertyModification#enabled, value=false},
{key=jdk.SecurityPropertyModification#stackTrace, value=true},
{key=jdk.TLSHandshake#enabled, value=false},
{key=jdk.TLSHandshake#stackTrace, value=true},
{key=jdk.X509Validation#enabled, value=false},
{key=jdk.X509Validation#stackTrace, value=true},
{key=jdk.X509Certificate#enabled, value=false},
{key=jdk.X509Certificate#stackTrace, value=true},
{key=jdk.JavaExceptionThrow#enabled, value=false},
{key=jdk.JavaExceptionThrow#stackTrace, value=true},
{key=jdk.JavaErrorThrow#enabled, value=true},
{key=jdk.JavaErrorThrow#stackTrace, value=true},
{key=jdk.ExceptionStatistics#enabled, value=true},
{key=jdk.ExceptionStatistics#period, value=1000 ms},
{key=jdk.ActiveRecording#enabled, value=true},
{key=jdk.ActiveSetting#enabled, value=true},
{key=jdk.DataLoss#enabled, value=true},
{key=jdk.DumpReason#enabled, value=true},

```

```

{key=jdk.ZPageAllocation#enabled, value=true},
{key=jdk.ZPageAllocation#threshold, value=10 ms},
{key=jdk.ZThreadPhase#enabled, value=true},
{key=jdk.ZThreadPhase#threshold, value=0 ms},
{key=jdk.ZStatisticsCounter#threshold, value=10 ms},
{key=jdk.ZStatisticsCounter#enabled, value=true},
{key=jdk.ZStatisticsSampler#enabled, value=true},
{key=jdk.ZStatisticsSampler#threshold, value=10 ms}},
{contents=<?xml version="1.0" encoding="UTF-8"?>

<!--
Recommended way to edit .jfc files is to use Java Mission Control,
see Window -> Flight Recorder Template Manager.
-->

<configuration version="2.0" label="Continuous" description="Low
overhead configuration safe for continuous use in production
environments, typically less than 1 % overhead." provider="Oracle">

<event name="jdk.ThreadAllocationStatistics">
<setting name="enabled">true</setting>
<setting name="period">everyChunk</setting>
</event>

<event name="jdk.ClassLoadingStatistics">
<setting name="enabled">true</setting>
<setting name="period">1000 ms</setting>
</event>

<event name="jdk.ClassLoaderStatistics">
<setting name="enabled">true</setting>
<setting name="period">everyChunk</setting>
</event>

<event name="jdk.JavaThreadStatistics">
<setting name="enabled">true</setting>
<setting name="period">1000 ms</setting>
</event>

<event name="jdk.ThreadStart">
<setting name="enabled">true</setting>
</event>

<event name="jdk.ThreadEnd">
<setting name="enabled">true</setting>
</event>

<event name="jdk.ThreadSleep">
<setting name="enabled">true</setting>
<setting name="stackTrace">true</setting>
<setting name="threshold" control="synchronization-threshold">20
ms</setting>
</event>

<event name="jdk.ThreadPark">
<setting name="enabled">true</setting>
<setting name="stackTrace">true</setting>
<setting name="threshold" control="synchronization-threshold">20
ms</setting>
</event>

<event name="jdk.JavaMonitorEnter">
<setting name="enabled">true</setting>
<setting name="stackTrace">true</setting>
<setting name="threshold" control="synchronization-threshold">20
ms</setting>
</event>

<event name="jdk.JavaMonitorWait">
<setting name="enabled">true</setting>
<setting name="stackTrace">true</setting>
<setting name="threshold" control="synchronization-threshold">20
ms</setting>
</event>

<event name="jdk.JavaMonitorInflate">
<setting name="enabled">>false</setting>
<setting name="stackTrace">true</setting>
<setting name="threshold" control="synchronization-threshold">20
ms</setting>
</event>

<event name="jdk.BiasedLockRevocation">
<setting name="enabled">true</setting>
<setting name="stackTrace">true</setting>
<setting name="threshold">0 ms</setting>
</event>

<event name="jdk.BiasedLockSelfRevocation">
<setting name="enabled">true</setting>
<setting name="stackTrace">true</setting>
<setting name="threshold">0 ms</setting>
</event>

<event name="jdk.BiasedLockClassRevocation">
<setting name="enabled">true</setting>
<setting name="stackTrace">true</setting>
<setting name="threshold">0 ms</setting>
</event>

<event name="jdk.ReservedStackActivation">
<setting name="enabled">true</setting>
<setting name="stackTrace">true</setting>
</event>

<event name="jdk.ClassLoad">
<setting name="enabled" control="class-loading-
enabled">false</setting>
<setting name="stackTrace">true</setting>
<setting name="threshold">0 ms</setting>
</event>

<event name="jdk.ClassDefine">
<setting name="enabled" control="class-loading-
enabled">false</setting>
<setting name="stackTrace">true</setting>
</event>

<event name="jdk.ClassUnload">
<setting name="enabled" control="class-loading-
enabled">false</setting>
</event>

<event name="jdk.JVMInformation">
<setting name="enabled">true</setting>
<setting name="period">beginChunk</setting>
</event>

<event name="jdk.InitialSystemProperty">
<setting name="enabled">true</setting>
<setting name="period">beginChunk</setting>
</event>

<event name="jdk.ExecutionSample">
<setting name="enabled" control="method-sampling-
enabled">true</setting>
<setting name="period" control="method-sampling-java-
interval">20 ms</setting>

```

```

</event>
<event name="jdk.NativeMethodSample">
  <setting name="enabled" control="method-sampling-
enabled">true</setting>
  <setting name="period" control="method-sampling-native-
interval">20 ms</setting>
</event>
<event name="jdk.SafepointBegin">
  <setting name="enabled">true</setting>
  <setting name="threshold">10 ms</setting>
</event>
<event name="jdk.SafepointStateSynchronization">
  <setting name="enabled">false</setting>
  <setting name="threshold">10 ms</setting>
</event>
<event name="jdk.SafepointWaitBlocked">
  <setting name="enabled">false</setting>
  <setting name="threshold">10 ms</setting>
</event>
<event name="jdk.SafepointCleanup">
  <setting name="enabled">false</setting>
  <setting name="threshold">10 ms</setting>
</event>
<event name="jdk.SafepointCleanupTask">
  <setting name="enabled">false</setting>
  <setting name="threshold">10 ms</setting>
</event>
<event name="jdk.SafepointEnd">
  <setting name="enabled">false</setting>
  <setting name="threshold">10 ms</setting>
</event>
<event name="jdk.ExecuteVMOperation">
  <setting name="enabled">true</setting>
  <setting name="threshold">10 ms</setting>
</event>
<event name="jdk.Shutdown">
  <setting name="enabled">true</setting>
  <setting name="stackTrace">true</setting>
</event>
<event name="jdk.ThreadDump">
  <setting name="enabled" control="thread-dump-
enabled">true</setting>
  <setting name="period" control="thread-dump-
interval">everyChunk</setting>
</event>
<event name="jdk.IntFlag">
  <setting name="enabled">true</setting>
  <setting name="period">beginChunk</setting>
</event>
<event name="jdk.UnsignedIntFlag">
  <setting name="enabled">true</setting>
  <setting name="period">beginChunk</setting>
</event>
<event name="jdk.LongFlag">
  <setting name="enabled">true</setting>
  <setting name="period">beginChunk</setting>
</event>
<event name="jdk.UnsignedLongFlag">
  <setting name="enabled">true</setting>
  <setting name="period">beginChunk</setting>
</event>
<event name="jdk.DoubleFlag">
  <setting name="enabled">true</setting>
  <setting name="period">beginChunk</setting>
</event>
<event name="jdk.BooleanFlag">
  <setting name="enabled">true</setting>
  <setting name="period">beginChunk</setting>
</event>
<event name="jdk.StringFlag">
  <setting name="enabled">true</setting>
  <setting name="period">beginChunk</setting>
</event>
<event name="jdk.IntFlagChanged">
  <setting name="enabled">true</setting>
</event>
<event name="jdk.UnsignedIntFlagChanged">
  <setting name="enabled">true</setting>
</event>
<event name="jdk.LongFlagChanged">
  <setting name="enabled">true</setting>
</event>
<event name="jdk.UnsignedLongFlagChanged">
  <setting name="enabled">true</setting>
</event>
<event name="jdk.DoubleFlagChanged">
  <setting name="enabled">true</setting>
</event>
<event name="jdk.BooleanFlagChanged">
  <setting name="enabled">true</setting>
</event>
<event name="jdk.StringFlagChanged">
  <setting name="enabled">true</setting>
</event>
<event name="jdk.ObjectCount">
  <setting name="enabled" control="memory-profiling-enabled-
all">false</setting>
  <setting name="period">everyChunk</setting>
</event>
<event name="jdk.GCConfiguration">
  <setting name="enabled" control="gc-enabled-
normal">true</setting>
  <setting name="period">everyChunk</setting>
</event>
<event name="jdk.GCHeapConfiguration">
  <setting name="enabled" control="gc-enabled-
normal">true</setting>
  <setting name="period">beginChunk</setting>
</event>
<event name="jdk.YoungGenerationConfiguration">

```

```

    <setting name="enabled" control="gc-enabled-normal">true</setting>
    <setting name="period">beginChunk</setting>
  </event>

  <event name="jdk.GCTLABConfiguration">
    <setting name="enabled" control="gc-enabled-normal">true</setting>
    <setting name="period">beginChunk</setting>
  </event>

  <event name="jdk.GCSurvivorConfiguration">
    <setting name="enabled" control="gc-enabled-normal">true</setting>
    <setting name="period">beginChunk</setting>
  </event>

  <event name="jdk.ObjectCountAfterGC">
    <setting name="enabled">>false</setting>
  </event>

  <event name="jdk.GCHeapSummary">
    <setting name="enabled" control="gc-enabled-normal">true</setting>
  </event>

  <event name="jdk.PSHeapSummary">
    <setting name="enabled" control="gc-enabled-normal">true</setting>
  </event>

  <event name="jdk.G1HeapSummary">
    <setting name="enabled" control="gc-enabled-normal">true</setting>
  </event>

  <event name="jdk.MetaspaceSummary">
    <setting name="enabled" control="gc-enabled-normal">true</setting>
  </event>

  <event name="jdk.MetaspaceGCThreshold">
    <setting name="enabled" control="gc-enabled-normal">true</setting>
  </event>

  <event name="jdk.MetaspaceAllocationFailure">
    <setting name="enabled" control="gc-enabled-normal">true</setting>
    <setting name="stackTrace">true</setting>
  </event>

  <event name="jdk.MetaspaceOOM">
    <setting name="enabled" control="gc-enabled-normal">true</setting>
    <setting name="stackTrace">true</setting>
  </event>

  <event name="jdk.MetaspaceChunkFreeListSummary">
    <setting name="enabled" control="gc-enabled-normal">true</setting>
  </event>

  <event name="jdk.GarbageCollection">
    <setting name="enabled" control="gc-enabled-normal">true</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.ParallelOldGarbageCollection">
    <setting name="enabled" control="gc-enabled-normal">true</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.YoungGarbageCollection">
    <setting name="enabled" control="gc-enabled-normal">true</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.OldGarbageCollection">
    <setting name="enabled" control="gc-enabled-normal">true</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.G1GarbageCollection">
    <setting name="enabled" control="gc-enabled-normal">true</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.GCPhasePause">
    <setting name="enabled" control="gc-enabled-normal">true</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.GCPhasePauseLevel1">
    <setting name="enabled" control="gc-enabled-normal">true</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.GCPhasePauseLevel2">
    <setting name="enabled" control="gc-enabled-normal">true</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.GCPhasePauseLevel3">
    <setting name="enabled" control="gc-enabled-all">>false</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.GCPhasePauseLevel4">
    <setting name="enabled" control="gc-enabled-all">>false</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.GCPhaseConcurrent">
    <setting name="enabled" control="gc-enabled-all">true</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.GCReferenceStatistics">
    <setting name="enabled" control="gc-enabled-normal">true</setting>
  </event>

  <event name="jdk.PromotionFailed">
    <setting name="enabled" control="gc-enabled-normal">true</setting>
  </event>

  <event name="jdk.EvacuationFailed">
    <setting name="enabled" control="gc-enabled-

```

```

normal">true</setting>
</event>

<event name="jdk.EvacuationInformation">
<setting name="enabled" control="gc-enabled-
normal">true</setting>
</event>

<event name="jdk.G1MMU">
<setting name="enabled" control="gc-enabled-
normal">true</setting>
</event>

<event name="jdk.G1EvacuationYoungStatistics">
<setting name="enabled" control="gc-enabled-
normal">true</setting>
</event>

<event name="jdk.G1EvacuationOldStatistics">
<setting name="enabled" control="gc-enabled-
normal">true</setting>
</event>

<event name="jdk.G1BasicHOP">
<setting name="enabled" control="gc-enabled-
normal">true</setting>
</event>

<event name="jdk.G1AdaptiveHOP">
<setting name="enabled" control="gc-enabled-
normal">true</setting>
</event>

<event name="jdk.PromoteObjectInNewPLAB">
<setting name="enabled" control="memory-profiling-enabled-
medium">false</setting>
</event>

<event name="jdk.PromoteObjectOutsidePLAB">
<setting name="enabled" control="memory-profiling-enabled-
medium">false</setting>
</event>

<event name="jdk.ConcurrentModeFailure">
<setting name="enabled" control="gc-enabled-
normal">true</setting>
</event>

<event name="jdk.AllocationRequiringGC">
<setting name="enabled" control="gc-enabled-all">false</setting>
<setting name="stackTrace">true</setting>
</event>

<event name="jdk.TenuringDistribution">
<setting name="enabled" control="gc-enabled-
normal">true</setting>
</event>

<event name="jdk.G1HeapRegionInformation">
<setting name="enabled" control="gc-enabled-all">false</setting>
<setting name="period">everyChunk</setting>
</event>

<event name="jdk.G1HeapRegionTypeChange">
<setting name="enabled" control="gc-enabled-all">false</setting>
</event>

<event name="jdk.OldObjectSample">
<setting name="enabled" control="memory-leak-detection-
enabled">true</setting>
<setting name="stackTrace" control="memory-leak-detection-
stack-trace">false</setting>
<setting name="cutoff" control="memory-leak-detection-cutoff">0
ns</setting>
</event>

<event name="jdk.CompilerConfiguration">
<setting name="enabled" control="compiler-
enabled">true</setting>
<setting name="period">beginChunk</setting>
</event>

<event name="jdk.CompilerStatistics">
<setting name="enabled" control="compiler-
enabled">true</setting>
<setting name="period">1000 ms</setting>
</event>

<event name="jdk.Compilation">
<setting name="enabled" control="compiler-
enabled">true</setting>
<setting name="threshold" control="compiler-compilation-
threshold">1000 ms</setting>
</event>

<event name="jdk.CompilerPhase">
<setting name="enabled" control="compiler-
enabled">true</setting>
<setting name="threshold" control="compiler-phase-threshold">60
s</setting>
</event>

<event name="jdk.CompilationFailure">
<setting name="enabled" control="compiler-enabled-
failure">false</setting>
</event>

<event name="jdk.CompilerInlining">
<setting name="enabled" control="compiler-enabled-
failure">false</setting>
</event>

<event name="jdk.CodeSweeperConfiguration">
<setting name="enabled" control="compiler-
enabled">true</setting>
<setting name="period">beginChunk</setting>
</event>

<event name="jdk.CodeSweeperStatistics">
<setting name="enabled" control="compiler-
enabled">true</setting>
<setting name="period">everyChunk</setting>
</event>

<event name="jdk.SweepCodeCache">
<setting name="enabled" control="compiler-
enabled">true</setting>
<setting name="threshold" control="compiler-sweeper-
threshold">100 ms</setting>
</event>

<event name="jdk.CodeCacheConfiguration">
<setting name="enabled" control="compiler-
enabled">true</setting>
<setting name="period">beginChunk</setting>
</event>

<event name="jdk.CodeCacheStatistics">

```

```

    <setting name="enabled" control="compiler-
enabled">true</setting>
    <setting name="period">everyChunk</setting>
  </event>

  <event name="jdk.CodeCacheFull">
    <setting name="enabled" control="compiler-
enabled">true</setting>
  </event>

  <event name="jdk.OSInformation">
    <setting name="enabled">true</setting>
    <setting name="period">beginChunk</setting>
  </event>

  <event name="jdk.VirtualizationInformation">
    <setting name="enabled">true</setting>
    <setting name="period">beginChunk</setting>
  </event>

  <event name="jdk.CPUInformation">
    <setting name="enabled">true</setting>
    <setting name="period">beginChunk</setting>
  </event>

  <event name="jdk.ThreadContextSwitchRate">
    <setting name="enabled" control="compiler-
enabled">true</setting>
    <setting name="period">10 s</setting>
  </event>

  <event name="jdk.CPULoad">
    <setting name="enabled">true</setting>
    <setting name="period">1000 ms</setting>
  </event>

  <event name="jdk.ThreadCPULoad">
    <setting name="enabled">true</setting>
    <setting name="period">10 s</setting>
  </event>

  <event name="jdk.CPUTimeStampCounter">
    <setting name="enabled">true</setting>
    <setting name="period">beginChunk</setting>
  </event>

  <event name="jdk.SystemProcess">
    <setting name="enabled">true</setting>
    <setting name="period">endChunk</setting>
  </event>

  <event name="jdk.NetworkUtilization">
    <setting name="enabled">true</setting>
    <setting name="period">5 s</setting>
  </event>

  <event name="jdk.InitialEnvironmentVariable">
    <setting name="enabled">true</setting>
    <setting name="period">beginChunk</setting>
  </event>

  <event name="jdk.PhysicalMemory">
    <setting name="enabled">true</setting>
    <setting name="period">everyChunk</setting>
  </event>

  <event name="jdk.ObjectAllocationInNewTLAB">
    <setting name="enabled" control="memory-profiling-enabled-
medium">false</setting>
    <setting name="stackTrace">true</setting>
  </event>

  <event name="jdk.ObjectAllocationOutsideTLAB">
    <setting name="enabled" control="memory-profiling-enabled-
medium">false</setting>
    <setting name="stackTrace">true</setting>
  </event>

  <event name="jdk.NativeLibrary">
    <setting name="enabled">true</setting>
    <setting name="period">everyChunk</setting>
  </event>

  <event name="jdk.ModuleRequire">
    <setting name="enabled">true</setting>
    <setting name="period">endChunk</setting>
  </event>

  <event name="jdk.ModuleExport">
    <setting name="enabled">true</setting>
    <setting name="period">endChunk</setting>
  </event>

  <event name="jdk.FileForce">
    <setting name="enabled">true</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold" control="file-io-threshold">20
ms</setting>
  </event>

  <event name="jdk.FileRead">
    <setting name="enabled">true</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold" control="file-io-threshold">20
ms</setting>
  </event>

  <event name="jdk.FileWrite">
    <setting name="enabled">true</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold" control="file-io-threshold">20
ms</setting>
  </event>

  <event name="jdk.SocketRead">
    <setting name="enabled">true</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold" control="socket-io-threshold">20
ms</setting>
  </event>

  <event name="jdk.SocketWrite">
    <setting name="enabled">true</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold" control="socket-io-threshold">20
ms</setting>
  </event>

  <event name="jdk.SecurityPropertyModification">
    <setting name="enabled">false</setting>
    <setting name="stackTrace">true</setting>
  </event>

  <event name="jdk.TLSHandshake">
    <setting name="enabled">false</setting>
    <setting name="stackTrace">true</setting>
  </event>

```

```

<event name="jdk.X509Validation">
  <setting name="enabled">false</setting>
  <setting name="stackTrace">true</setting>
</event>

<event name="jdk.X509Certificate">
  <setting name="enabled">false</setting>
  <setting name="stackTrace">true</setting>
</event>

<event name="jdk.JavaExceptionThrow">
  <setting name="enabled" control="enable-
exceptions">false</setting>
  <setting name="stackTrace">true</setting>
</event>

<event name="jdk.JavaErrorThrow">
  <setting name="enabled" control="enable-errors">true</setting>
  <setting name="stackTrace">true</setting>
</event>

<event name="jdk.ExceptionStatistics">
  <setting name="enabled">true</setting>
  <setting name="period">1000 ms</setting>
</event>

<event name="jdk.ActiveRecording">
  <setting name="enabled">true</setting>
</event>

<event name="jdk.ActiveSetting">
  <setting name="enabled">true</setting>
</event>

<event name="jdk.DataLoss">
  <setting name="enabled">true</setting>
</event>

<event name="jdk.DumpReason">
  <setting name="enabled">true</setting>
</event>

<event name="jdk.ZPageAllocation">
  <setting name="enabled">true</setting>
  <setting name="threshold">10 ms</setting>
</event>

<event name="jdk.ZThreadPhase">
  <setting name="enabled">true</setting>
  <setting name="threshold">0 ms</setting>
</event>

<event name="jdk.ZStatisticsCounter">
  <setting name="enabled">true</setting>
  <setting name="threshold">10 ms</setting>
</event>

<event name="jdk.ZStatisticsSampler">
  <setting name="enabled">true</setting>
  <setting name="threshold">10 ms</setting>
</event>

```

```

<!--
  Contents of the control element is not read by the JVM, it's used
  by Java Mission Control to change settings that carry the control
  attribute.
-->
<control>
  <selection name="gc-level" default="detailed" label="Garbage
Collector">
    <option label="Off" name="off">off</option>
    <option label="Normal" name="detailed">normal</option>
    <option label="All" name="all">all</option>
  </selection>

  <condition name="gc-enabled-normal" true="true" false="false">
    <or>
      <test name="gc-level" operator="equal" value="normal"/>
      <test name="gc-level" operator="equal" value="all"/>
    </or>
  </condition>

  <condition name="gc-enabled-all" true="true" false="false">
    <test name="gc-level" operator="equal" value="all"/>
  </condition>

  <selection name="memory-profiling" default="off" label="Memory
Profiling">
    <option label="Off" name="off">off</option>
    <option label="Object Allocation and Promotion"
name="medium">medium</option>
    <option label="All, including Heap Statistics (May cause long full
GCs)" name="all">all</option>
  </selection>

  <condition name="memory-profiling-enabled-medium" true="true"
false="false">
    <or>
      <test name="memory-profiling" operator="equal"
value="medium"/>
      <test name="memory-profiling" operator="equal" value="all"/>
    </or>
  </condition>

  <condition name="memory-profiling-enabled-all" true="true"
false="false">
    <test name="memory-profiling" operator="equal" value="all"/>
  </condition>

  <selection name="compiler-level" default="normal"

```

```

label="Compiler">
  <option label="Off" name="off">off</option>
  <option label="Normal" name="normal">normal</option>
  <option label="Detailed" name="detailed">detailed</option>
  <option label="All" name="all">all</option>
</selection>

<condition name="compiler-enabled" true="false" false="true">
  <test name="compiler-level" operator="equal" value="off"/>
</condition>

<condition name="compiler-enabled-failure" true="true"
false="false">
  <or>
    <test name="compiler-level" operator="equal" value="detailed"/>
    <test name="compiler-level" operator="equal" value="all"/>
  </or>
</condition>

<condition name="compiler-sweeper-threshold" true="0 ms"
false="100 ms">
  <test name="compiler-level" operator="equal" value="all"/>
</condition>

<condition name="compiler-compilation-threshold" true="1000
ms">
  <test name="compiler-level" operator="equal" value="normal"/>
</condition>

<condition name="compiler-compilation-threshold" true="100 ms">
  <test name="compiler-level" operator="equal" value="detailed"/>
</condition>

<condition name="compiler-compilation-threshold" true="0 ms">
  <test name="compiler-level" operator="equal" value="all"/>
</condition>

<condition name="compiler-phase-threshold" true="60 s">
  <test name="compiler-level" operator="equal" value="normal"/>
</condition>

<condition name="compiler-phase-threshold" true="10 s">
  <test name="compiler-level" operator="equal" value="detailed"/>
</condition>

<condition name="compiler-phase-threshold" true="0 s">
  <test name="compiler-level" operator="equal" value="all"/>
</condition>

<selection name="method-sampling-interval" default="normal"
label="Method Sampling">
  <option label="Off" name="off">off</option>
  <option label="Normal" name="normal">normal</option>
  <option label="High" name="high">high</option>
  <option label="Ludicrous (High Overhead)"
name="ludicrous">ludicrous</option>
</selection>

<condition name="method-sampling-java-interval" true="999 d">
  <test name="method-sampling-interval" operator="equal"
value="off"/>
</condition>

<condition name="method-sampling-java-interval" true="20 ms">
  <test name="method-sampling-interval" operator="equal"
value="normal"/>
</condition>

<condition name="method-sampling-java-interval" true="10 ms">
  <test name="method-sampling-interval" operator="equal"
value="high"/>
</condition>

<condition name="method-sampling-java-interval" true="1 ms">
  <test name="method-sampling-interval" operator="equal"
value="ludicrous"/>
</condition>

<condition name="method-sampling-native-interval" true="999 d">
  <test name="method-sampling-interval" operator="equal"
value="off"/>
</condition>

<condition name="method-sampling-native-interval" true="20 ms">
  <or>
    <test name="method-sampling-interval" operator="equal"
value="normal"/>
    <test name="method-sampling-interval" operator="equal"
value="high"/>
    <test name="method-sampling-interval" operator="equal"
value="ludicrous"/>
  </or>
</condition>

<condition name="method-sampling-enabled" true="false"
false="true">
  <test name="method-sampling-interval" operator="equal"
value="off"/>
</condition>

<selection name="thread-dump-interval" default="normal"
label="Thread Dump">
  <option label="Off" name="off">999 d</option>
  <option label="At least Once"
name="normal">everyChunk</option>
  <option label="Every 60 s" name="everyMinute">60 s</option>
  <option label="Every 10 s" name="everyTenSecond">10
s</option>
  <option label="Every 1 s" name="everySecond">1 s</option>
</selection>

<condition name="thread-dump-enabled" true="false" false="true">
  <test name="thread-dump-interval" operator="equal" value="999
d"/>
</condition>

<selection name="exception-level" default="errors"
label="Exceptions">
  <option label="Off" name="off">off</option>
  <option label="Errors Only" name="errors">errors</option>
  <option label="All Exceptions, including Errors"
name="all">all</option>
</selection>

<condition name="enable-errors" true="true" false="false">
  <or>
    <test name="exception-level" operator="equal" value="errors"/>
    <test name="exception-level" operator="equal" value="all"/>
  </or>
</condition>

<condition name="enable-exceptions" true="true" false="false">
  <test name="exception-level" operator="equal" value="all"/>
</condition>

<selection name="memory-leak-detection" default="minimal"
label="Memory Leak Detection">
  <option label="Off" name="off">off</option>

```



```

<option label="Object Types" name="minimal">minimal</option>
<option label="Object Types + Allocation Stack Traces"
name="medium">medium</option>
<option label="Object Types + Allocation Stack Traces + Path to
GC Root" name="full">full</option>
</selection>

<condition name="memory-leak-detection-enabled" true="false"
false="true">
<test name="memory-leak-detection" operator="equal"
value="off"/>
</condition>

<condition name="memory-leak-detection-stack-trace" true="true"
false="false">
<or>
<test name="memory-leak-detection" operator="equal"
value="medium"/>
<test name="memory-leak-detection" operator="equal"
value="full"/>
</or>
</condition>

<condition name="memory-leak-detection-cutoff" true="1 h"
false="0 ns">
<test name="memory-leak-detection" operator="equal"
value="full"/>
</condition>

<text name="synchronization-threshold" label="Synchronization
Threshold" contentType="timespan" minimum="0 s">20 ms</text>

<text name="file-io-threshold" label="File I/O Threshold"
contentType="timespan" minimum="0 s">20 ms</text>

<text name="socket-io-threshold" label="Socket I/O Threshold"
contentType="timespan" minimum="0 s">20 ms</text>

<flag name="class-loading-enabled" label="Class
Loading">false</flag>

</control>

</configuration>
, description=Low overhead configuration safe for continuous use in
production environments, typically less than 1 % overhead.,
label=Continuous, name=default, provider=Oracle,
settings={
{key=jdk.ThreadAllocationStatistics#enabled, value=true},
{key=jdk.ThreadAllocationStatistics#period, value=everyChunk},
{key=jdk.ClassLoadingStatistics#enabled, value=true},
{key=jdk.ClassLoadingStatistics#period, value=1000 ms},
{key=jdk.ClassLoaderStatistics#enabled, value=true},
{key=jdk.ClassLoaderStatistics#period, value=everyChunk},
{key=jdk.JavaThreadStatistics#enabled, value=true},
{key=jdk.JavaThreadStatistics#period, value=1000 ms},
{key=jdk.ThreadStart#enabled, value=true},
{key=jdk.ThreadEnd#enabled, value=true},
{key=jdk.ThreadSleep#enabled, value=true},
{key=jdk.ThreadSleep#stackTrace, value=true},
{key=jdk.ThreadSleep#threshold, value=20 ms},
{key=jdk.ThreadPark#enabled, value=true},
{key=jdk.ThreadPark#stackTrace, value=true},
{key=jdk.ThreadPark#threshold, value=20 ms},
{key=jdk.JavaMonitorEnter#enabled, value=true},
{key=jdk.JavaMonitorEnter#stackTrace, value=true},
{key=jdk.JavaMonitorEnter#threshold, value=20 ms},
{key=jdk.JavaMonitorWait#enabled, value=true},
{key=jdk.JavaMonitorWait#stackTrace, value=true},
{key=jdk.JavaMonitorWait#threshold, value=20 ms},
{key=jdk.JavaMonitorInflate#enabled, value=false},
{key=jdk.JavaMonitorInflate#stackTrace, value=true},
{key=jdk.JavaMonitorInflate#threshold, value=20 ms},
{key=jdk.BiasedLockRevocation#enabled, value=true},
{key=jdk.BiasedLockRevocation#stackTrace, value=true},
{key=jdk.BiasedLockRevocation#threshold, value=0 ms},
{key=jdk.BiasedLockSelfRevocation#enabled, value=true},
{key=jdk.BiasedLockSelfRevocation#stackTrace, value=true},
{key=jdk.BiasedLockSelfRevocation#threshold, value=0 ms},
{key=jdk.BiasedLockClassRevocation#enabled, value=true},
{key=jdk.BiasedLockClassRevocation#stackTrace, value=true},
{key=jdk.BiasedLockClassRevocation#threshold, value=0 ms},
{key=jdk.ReservedStackActivation#enabled, value=true},
{key=jdk.ReservedStackActivation#stackTrace, value=true},
{key=jdk.ClassLoad#enabled, value=false},
{key=jdk.ClassLoad#stackTrace, value=true},
{key=jdk.ClassLoad#threshold, value=0 ms},
{key=jdk.ClassDefine#enabled, value=false},
{key=jdk.ClassDefine#stackTrace, value=true},
{key=jdk.ClassUnload#enabled, value=false},
{key=jdk.JVMInformation#enabled, value=true},
{key=jdk.JVMInformation#period, value=beginChunk},
{key=jdk.InitialSystemProperty#enabled, value=true},
{key=jdk.InitialSystemProperty#period, value=beginChunk},
{key=jdk.ExecutionSample#enabled, value=true},
{key=jdk.ExecutionSample#period, value=20 ms},
{key=jdk.NativeMethodSample#enabled, value=true},
{key=jdk.NativeMethodSample#period, value=20 ms},
{key=jdk.SafePointBegin#enabled, value=true},
{key=jdk.SafePointBegin#threshold, value=10 ms},
{key=jdk.SafePointStateSynchronization#enabled, value=false},
{key=jdk.SafePointStateSynchronization#threshold, value=10 ms},
{key=jdk.SafePointWaitBlocked#enabled, value=false},
{key=jdk.SafePointWaitBlocked#threshold, value=10 ms},
{key=jdk.SafePointCleanup#enabled, value=false},
{key=jdk.SafePointCleanup#threshold, value=10 ms},
{key=jdk.SafePointCleanupTask#enabled, value=false},
{key=jdk.SafePointCleanupTask#threshold, value=10 ms},
{key=jdk.SafePointEnd#enabled, value=false},
{key=jdk.SafePointEnd#threshold, value=10 ms},
{key=jdk.ExecuteVMOperation#enabled, value=true},
{key=jdk.ExecuteVMOperation#threshold, value=10 ms},
{key=jdk.Shutdown#enabled, value=true},
{key=jdk.Shutdown#stackTrace, value=true},
{key=jdk.ThreadDump#enabled, value=true},
{key=jdk.ThreadDump#period, value=everyChunk},
{key=jdk.IntFlag#enabled, value=true}, {key=jdk.IntFlag#period,
value=beginChunk}, {key=jdk.UnsignedIntFlag#enabled, value=true},
{key=jdk.UnsignedIntFlag#period, value=beginChunk},
{key=jdk.LongFlag#enabled, value=true}, {key=jdk.LongFlag#period,
value=beginChunk}, {key=jdk.UnsignedLongFlag#enabled,
value=true}, {key=jdk.UnsignedLongFlag#period, value=beginChunk},
{key=jdk.DoubleFlag#enabled, value=true},
{key=jdk.DoubleFlag#period, value=beginChunk},
{key=jdk.BooleanFlag#enabled, value=true},
{key=jdk.BooleanFlag#period, value=beginChunk},
{key=jdk.StringFlag#enabled, value=true}, {key=jdk.StringFlag#period,
value=beginChunk}, {key=jdk.IntFlagChanged#enabled, value=true},
{key=jdk.UnsignedIntFlagChanged#enabled, value=true},
{key=jdk.LongFlagChanged#enabled, value=true},
{key=jdk.UnsignedLongFlagChanged#enabled, value=true},
{key=jdk.DoubleFlagChanged#enabled, value=true},
{key=jdk.BooleanFlagChanged#enabled, value=true},
{key=jdk.StringFlagChanged#enabled, value=true},
{key=jdk.ObjectCount#enabled, value=false},
{key=jdk.ObjectCount#period, value=everyChunk},
{key=jdk.GCConfiguration#enabled, value=true},
{key=jdk.GCConfiguration#period, value=everyChunk},
{key=jdk.GCHeapConfiguration#enabled, value=true},

```

```

{key=jdk.GCHeapConfiguration#period, value=beginChunk},
{key=jdk.YoungGenerationConfiguration#enabled, value=true},
{key=jdk.YoungGenerationConfiguration#period, value=beginChunk},
{key=jdk.GCTLABConfiguration#enabled, value=true},
{key=jdk.GCTLABConfiguration#period, value=beginChunk},
{key=jdk.GCSurvivorConfiguration#enabled, value=true},
{key=jdk.GCSurvivorConfiguration#period, value=beginChunk},
{key=jdk.ObjectCountAfterGC#enabled, value=false},
{key=jdk.GCHeapSummary#enabled, value=true},
{key=jdk.PSHeapSummary#enabled, value=true},
{key=jdk.G1HeapSummary#enabled, value=true},
{key=jdk.MetaspaceSummary#enabled, value=true},
{key=jdk.MetaspaceGCThreshold#enabled, value=true},
{key=jdk.MetaspaceAllocationFailure#enabled, value=true},
{key=jdk.MetaspaceAllocationFailure#stackTrace, value=true},
{key=jdk.MetaspaceOOM#enabled, value=true},
{key=jdk.MetaspaceOOM#stackTrace, value=true},
{key=jdk.MetaspaceChunkFreeListSummary#enabled, value=true},
{key=jdk.GarbageCollection#enabled, value=true},
{key=jdk.GarbageCollection#threshold, value=0 ms},
{key=jdk.ParallelOldGarbageCollection#enabled, value=true},
{key=jdk.ParallelOldGarbageCollection#threshold, value=0 ms},
{key=jdk.YoungGarbageCollection#enabled, value=true},
{key=jdk.YoungGarbageCollection#threshold, value=0 ms},
{key=jdk.OldGarbageCollection#enabled, value=true},
{key=jdk.OldGarbageCollection#threshold, value=0 ms},
{key=jdk.G1GarbageCollection#enabled, value=true},
{key=jdk.G1GarbageCollection#threshold, value=0 ms},
{key=jdk.GCPhasePause#enabled, value=true},
{key=jdk.GCPhasePause#threshold, value=0 ms},
{key=jdk.GCPhasePauseLevel1#enabled, value=true},
{key=jdk.GCPhasePauseLevel1#threshold, value=0 ms},
{key=jdk.GCPhasePauseLevel2#enabled, value=true},
{key=jdk.GCPhasePauseLevel2#threshold, value=0 ms},
{key=jdk.GCPhasePauseLevel3#enabled, value=false},
{key=jdk.GCPhasePauseLevel3#threshold, value=0 ms},
{key=jdk.GCPhasePauseLevel4#enabled, value=false},
{key=jdk.GCPhasePauseLevel4#threshold, value=0 ms},
{key=jdk.GCPhaseConcurrent#enabled, value=true},
{key=jdk.GCPhaseConcurrent#threshold, value=0 ms},
{key=jdk.GCReferenceStatistics#enabled, value=true},
{key=jdk.PromotionFailed#enabled, value=true},
{key=jdk.EvacuationFailed#enabled, value=true},
{key=jdk.EvacuationInformation#enabled, value=true},
{key=jdk.G1MMU#enabled, value=true},
{key=jdk.G1EvacuationYoungStatistics#enabled, value=true},
{key=jdk.G1EvacuationOldStatistics#enabled, value=true},
{key=jdk.G1BasicHOP#enabled, value=true},
{key=jdk.G1AdaptiveHOP#enabled, value=true},
{key=jdk.PromoteObjectInNewTLAB#enabled, value=false},
{key=jdk.PromoteObjectOutsideTLAB#enabled, value=false},
{key=jdk.ConcurrentModeFailure#enabled, value=true},
{key=jdk.AllocationRequiringGC#enabled, value=false},
{key=jdk.AllocationRequiringGC#stackTrace, value=true},
{key=jdk.TenuringDistribution#enabled, value=true},
{key=jdk.G1HeapRegionInformation#enabled, value=false},
{key=jdk.G1HeapRegionInformation#period, value=everyChunk},
{key=jdk.G1HeapRegionTypeChange#enabled, value=false},
{key=jdk.OldObjectSample#enabled, value=true},
{key=jdk.OldObjectSample#stackTrace, value=false},
{key=jdk.OldObjectSample#cutoff, value=0 ns},
{key=jdk.CompilerConfiguration#enabled, value=true},
{key=jdk.CompilerConfiguration#period, value=beginChunk},
{key=jdk.CompilerStatistics#enabled, value=true},
{key=jdk.CompilerStatistics#period, value=1000 ms},
{key=jdk.Compilation#enabled, value=true},
{key=jdk.Compilation#threshold, value=1000 ms},
{key=jdk.CompilerPhase#enabled, value=true},
{key=jdk.CompilerPhase#threshold, value=60 s},
{key=jdk.CompilationFailure#enabled, value=false},
{key=jdk.CompilerInlining#enabled, value=false},
{key=jdk.CodeSweeperConfiguration#enabled, value=true},
{key=jdk.CodeSweeperConfiguration#period, value=beginChunk},
{key=jdk.CodeSweeperStatistics#enabled, value=true},
{key=jdk.CodeSweeperStatistics#period, value=everyChunk},
{key=jdk.SweepCodeCache#enabled, value=true},
{key=jdk.SweepCodeCache#threshold, value=100 ms},
{key=jdk.CodeCacheConfiguration#enabled, value=true},
{key=jdk.CodeCacheConfiguration#period, value=beginChunk},
{key=jdk.CodeCacheStatistics#enabled, value=true},
{key=jdk.CodeCacheStatistics#period, value=everyChunk},
{key=jdk.CodeCacheFull#enabled, value=true},
{key=jdk.OSInformation#enabled, value=true},
{key=jdk.OSInformation#period, value=beginChunk},
{key=jdk.VirtualizationInformation#enabled, value=true},
{key=jdk.VirtualizationInformation#period, value=beginChunk},
{key=jdk.CPUInformation#enabled, value=true},
{key=jdk.CPUInformation#period, value=beginChunk},
{key=jdk.ThreadContextSwitchRate#enabled, value=true},
{key=jdk.ThreadContextSwitchRate#period, value=10 s},
{key=jdk.CPULoad#enabled, value=true}, {key=jdk.CPULoad#period, value=1000 ms}, {key=jdk.ThreadCPULoad#enabled, value=true},
{key=jdk.ThreadCPULoad#period, value=10 s},
{key=jdk.CPUTimeStampCounter#enabled, value=true},
{key=jdk.CPUTimeStampCounter#period, value=beginChunk},
{key=jdk.SystemProcess#enabled, value=true},
{key=jdk.SystemProcess#period, value=endChunk},
{key=jdk.NetworkUtilization#enabled, value=true},
{key=jdk.NetworkUtilization#period, value=5 s},
{key=jdk.InitialEnvironmentVariable#enabled, value=true},
{key=jdk.InitialEnvironmentVariable#period, value=beginChunk},
{key=jdk.PhysicalMemory#enabled, value=true},
{key=jdk.PhysicalMemory#period, value=everyChunk},
{key=jdk.ObjectAllocationInNewTLAB#enabled, value=false},
{key=jdk.ObjectAllocationInNewTLAB#stackTrace, value=true},
{key=jdk.ObjectAllocationOutsideTLAB#enabled, value=false},
{key=jdk.ObjectAllocationOutsideTLAB#stackTrace, value=true},
{key=jdk.NativeLibrary#enabled, value=true},
{key=jdk.NativeLibrary#period, value=everyChunk},
{key=jdk.ModuleRequire#enabled, value=true},
{key=jdk.ModuleRequire#period, value=endChunk},
{key=jdk.ModuleExport#enabled, value=true},
{key=jdk.ModuleExport#period, value=endChunk},
{key=jdk.FileForce#enabled, value=true},
{key=jdk.FileForce#stackTrace, value=true},
{key=jdk.FileForce#threshold, value=20 ms},
{key=jdk.FileRead#enabled, value=true},
{key=jdk.FileRead#stackTrace, value=true},
{key=jdk.FileRead#threshold, value=20 ms},
{key=jdk.FileWrite#enabled, value=true},
{key=jdk.FileWrite#stackTrace, value=true},
{key=jdk.FileWrite#threshold, value=20 ms},
{key=jdk.SocketRead#enabled, value=true},
{key=jdk.SocketRead#stackTrace, value=true},
{key=jdk.SocketRead#threshold, value=20 ms},
{key=jdk.SocketWrite#enabled, value=true},
{key=jdk.SocketWrite#stackTrace, value=true},
{key=jdk.SocketWrite#threshold, value=20 ms},
{key=jdk.SecurityPropertyModification#enabled, value=false},
{key=jdk.SecurityPropertyModification#stackTrace, value=true},
{key=jdk.TLSHandshake#enabled, value=false},
{key=jdk.TLSHandshake#stackTrace, value=true},
{key=jdk.X509Validation#enabled, value=false},
{key=jdk.X509Validation#stackTrace, value=true},
{key=jdk.X509Certificate#enabled, value=false},
{key=jdk.X509Certificate#stackTrace, value=true},
{key=jdk.JavaExceptionThrow#enabled, value=false},
{key=jdk.JavaExceptionThrow#stackTrace, value=true},

```

```
{key=jdk.JavaErrorThrow#enabled, value=true},  
{key=jdk.JavaErrorThrow#stackTrace, value=true},  
{key=jdk.ExceptionStatistics#enabled, value=true},  
{key=jdk.ExceptionStatistics#period, value=1000 ms},  
{key=jdk.ActiveRecording#enabled, value=true},  
{key=jdk.ActiveSetting#enabled, value=true},  
{key=jdk.DataLoss#enabled, value=true},  
{key=jdk.DumpReason#enabled, value=true},  
{key=jdk.ZPageAllocation#enabled, value=true},  
{key=jdk.ZPageAllocation#threshold, value=10 ms},  
{key=jdk.ZThreadPhase#enabled, value=true},  
{key=jdk.ZThreadPhase#threshold, value=0 ms},  
{key=jdk.ZStatisticsCounter#enabled, value=true},  
{key=jdk.ZStatisticsCounter#threshold, value=10 ms},  
{key=jdk.ZStatisticsSampler#enabled, value=true},  
{key=jdk.ZStatisticsSampler#threshold, value=10 ms}}]]]]
```

EventTypes

```

[[categoryNames=[Java Development Kit, Security],
description=Modification of Security property, id=8512, label=Security
Property Modification, name=jdk.SecurityPropertyModification,
settingDescriptors=[[contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled],
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold},
{contentType=jdk.jfr.BooleanField, defaultValue=false,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}]],
{categoryNames=[Java Development Kit, Security],
description=Parameters used in TLS Handshake, id=6328, label=TLS
Handshake, name=jdk.TLSHandshake,
settingDescriptors=[[contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled],
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold},
{contentType=jdk.jfr.BooleanField, defaultValue=false,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}]],
{categoryNames=[Java Development Kit, Security], description=Serial
numbers from X.509 Certificates forming chain of trust, id=6299,
label=X509 Validation, name=jdk.X509Validation,
settingDescriptors=[[contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled],
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold},
{contentType=jdk.jfr.BooleanField, defaultValue=false,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}]],
{categoryNames=[Java Development Kit, Security], description=Details
of X.509 Certificate parsed by JDK, id=5619, label=X509 Certificate,
name=jdk.X509Certificate,
settingDescriptors=[[contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled],
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold},
{contentType=jdk.jfr.BooleanField, defaultValue=false,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}]],
{categoryNames=[Flight Recorder], description=null, id=8510,
label=Flight Recording, name=jdk.ActiveRecording,
settingDescriptors=[[contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled],
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold},
{contentType=jdk.jfr.BooleanField, defaultValue=false,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}]],
{categoryNames=[Flight Recorder], description=null, id=8508,
label=Recording Setting, name=jdk.ActiveSetting,
settingDescriptors=[[contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled],
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold},
{contentType=jdk.jfr.BooleanField, defaultValue=false,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}]],
{categoryNames=[Java Application], description=An object derived
from java.lang.Error has been created. OutOfMemoryErrors are
ignored, id=8506, label=Java Error, name=jdk.JavaErrorThrow,
settingDescriptors=[[contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled],
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold},
{contentType=jdk.jfr.BooleanField, defaultValue=false,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}]],
{categoryNames=[Java Application, Statistics], description=Number of
objects derived from java.lang.Throwable that have been created,
id=8504, label=Exception Statistics, name=jdk.ExceptionStatistics,
settingDescriptors=[[contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled], {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]],
{categoryNames=[Java Application], description=An object derived
from java.lang.Exception has been created, id=8502, label=Java
Exception, name=jdk.JavaExceptionThrow,
settingDescriptors=[[contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled],
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold},
{contentType=jdk.jfr.BooleanField, defaultValue=false,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}]],
{categoryNames=[Java Application], description=Writing data to a
socket, id=8500, label=Socket Write, name=jdk.SocketWrite,
settingDescriptors=[[contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled],
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold},
{contentType=jdk.jfr.BooleanField, defaultValue=false,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}]],
{categoryNames=[Java Application], description=Reading data from a
socket, id=8498, label=Socket Read, name=jdk.SocketRead,
settingDescriptors=[[contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled],
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold},
{contentType=jdk.jfr.BooleanField, defaultValue=false,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}]],
{categoryNames=[Java Application], description=Writing data to a file,
id=8496, label=File Write, name=jdk.FileWrite,
settingDescriptors=[[contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled],
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold},
{contentType=jdk.jfr.BooleanField, defaultValue=false,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}]],
{categoryNames=[Java Application], description=Reading data from a
file, id=8494, label=File Read, name=jdk.FileRead,
settingDescriptors=[[contentType=jdk.jfr.BooleanField,

```

```

defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled),
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold),
{contentType=jdk.jfr.BooleanField, defaultValue=false,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}},
{categoryNames=Java Application, description=Force updates to be
written to file, id=8492, label=File Force, name=jdk.FileForce,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled),
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold),
{contentType=jdk.jfr.BooleanField, defaultValue=false,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}},
{categoryNames=Java Application, description=null, id=255,
label=Java Thread Start, name=jdk.ThreadStart,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled)},
{categoryNames=Java Application, description=null, id=256,
label=Java Thread End, name=jdk.ThreadEnd,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled)},
{categoryNames=Java Application, description=null, id=257,
label=Java Thread Sleep, name=jdk.ThreadSleep,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled),
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold),
{contentType=jdk.jfr.BooleanField, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}},
{categoryNames=Java Application, description=null, id=259,
label=Java Monitor Blocked, name=jdk.JavaMonitorEnter,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled),
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold),
{contentType=jdk.jfr.BooleanField, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}},
{categoryNames=Java Application, description=null, id=261,
label=Java Monitor Inflated, name=jdk.JavaMonitorInflate,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled),
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold),
{contentType=jdk.jfr.BooleanField, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}},
{categoryNames=Java Virtual Machine, Runtime,
description=Revoked bias of object, id=262, label=Biased Lock
Revocation, name=jdk.BiasedLockRevocation,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled),
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold),
{contentType=jdk.jfr.BooleanField, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}},
{categoryNames=Java Virtual Machine, Runtime,
description=Revoked bias of object biased towards own thread,
id=263, label=Biased Lock Self Revocation,
name=jdk.BiasedLockSelfRevocation,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled),
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold),
{contentType=jdk.jfr.BooleanField, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}},
{categoryNames=Java Virtual Machine, Runtime,
description=Revoked biases for all instances of a class, id=264,
label=Biased Lock Class Revocation,
name=jdk.BiasedLockClassRevocation,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled),
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold),
{contentType=jdk.jfr.BooleanField, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}},
{categoryNames=Java Virtual Machine, Class Loading,
description=Activation of Reserved Stack Area caused by stack
overflow with ReservedStackAccess annotated method in call stack,
id=265, label=Reserved Stack Activation,
name=jdk.ReservedStackActivation,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled),
{contentType=jdk.jfr.BooleanField, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}},
{categoryNames=Java Virtual Machine, Class Loading,
description=null, id=266, label=Class Load, name=jdk.ClassLoad,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled),

```

```

{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold},
{contentType=jdk.jfr.BooleanFlag, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}},
{categoryNames=Java Virtual Machine, Class Loading,
description=null, id=267, label=Class Define, name=jdk.ClassDefine,
settingDescriptors=[[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled],
{contentType=jdk.jfr.BooleanFlag, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}}],
{categoryNames=Java Virtual Machine, Class Loading,
description=null, id=268, label=Class Unload, name=jdk.ClassUnload,
settingDescriptors=[[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}}],
{categoryNames=Java Virtual Machine, Flag, description=null,
id=269, label=Int Flag Changed, name=jdk.IntFlagChanged,
settingDescriptors=[[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}}],
{categoryNames=Java Virtual Machine, Flag, description=null,
id=270, label=Unsigned Int Flag Changed,
name=jdk.UnsignedIntFlagChanged,
settingDescriptors=[[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}}],
{categoryNames=Java Virtual Machine, Flag, description=null,
id=271, label=Long Flag Changed, name=jdk.LongFlagChanged,
settingDescriptors=[[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}}],
{categoryNames=Java Virtual Machine, Flag, description=null,
id=272, label=Unsigned Long Flag Changed,
name=jdk.UnsignedLongFlagChanged,
settingDescriptors=[[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}}],
{categoryNames=Java Virtual Machine, Flag, description=null,
id=273, label=Double Flag Changed, name=jdk.DoubleFlagChanged,
settingDescriptors=[[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}}],
{categoryNames=Java Virtual Machine, Flag, description=null,
id=274, label=Boolean Flag Changed,
name=jdk.BooleanFlagChanged,
settingDescriptors=[[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}}],
{categoryNames=Java Virtual Machine, Flag, description=null,
id=275, label=String Flag Changed, name=jdk.StringFlagChanged,
settingDescriptors=[[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}}],
{categoryNames=Java Virtual Machine, GC, Heap, description=null,
id=278, label=Heap Summary, name=jdk.GCHeapSummary,
settingDescriptors=[[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}}],
{categoryNames=Java Virtual Machine, GC, Heap, description=null,
id=280, label=Metaspace Summary, name=jdk.MetaspaceSummary,
settingDescriptors=[[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}}],
{categoryNames=Java Virtual Machine, GC, Metaspace,
description=null, id=281, label=Metaspace GC Threshold,
name=jdk.MetaspaceGCThreshold,
settingDescriptors=[[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}}],
{categoryNames=Java Virtual Machine, GC, Metaspace,
description=null, id=282, label=Metaspace Allocation Failure,
name=jdk.MetaspaceAllocationFailure,
settingDescriptors=[[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.BooleanFlag, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}}],
{categoryNames=Java Virtual Machine, GC, Metaspace,
description=null, id=283, label=Metaspace Out of Memory,
name=jdk.MetaspaceOOM,
settingDescriptors=[[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.BooleanFlag, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}}],
{categoryNames=Java Virtual Machine, GC, Metaspace,
description=null, id=284, label=Metaspace Chunk Free List Summary,
name=jdk.MetaspaceChunkFreeListSummary,
settingDescriptors=[[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}}],
{categoryNames=Java Virtual Machine, GC, Heap, description=null,
id=285, label=Parallel Scavenge Heap Summary,
name=jdk.PSHeapSummary,
settingDescriptors=[[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}}],
{categoryNames=Java Virtual Machine, GC, Heap, description=null,
id=286, label=G1 Heap Summary, name=jdk.G1HeapSummary,
settingDescriptors=[[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}}],
{categoryNames=Java Virtual Machine, GC, Collector,
description=Garbage collection performed by the JVM, id=287,
label=Garbage Collection, name=jdk.GarbageCollection,
settingDescriptors=[[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}}],
{categoryNames=Java Virtual Machine, GC, Collector,
description=Extra information specific to Parallel Old Garbage
Collections, id=288, label=Parallel Old Garbage Collection,
name=jdk.ParallelOldGarbageCollection,
settingDescriptors=[[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}}],
{categoryNames=Java Virtual Machine, GC, Collector,
description=Extra information specific to Young Garbage Collections,
id=289, label=Young Garbage Collection,
name=jdk.YoungGarbageCollection,
settingDescriptors=[[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}}],
{categoryNames=Java Virtual Machine, GC, Collector,

```

```

description=Extra information specific to Old Garbage Collections,
id=290, label=Old Garbage Collection,
name=jdk.OldGarbageCollection,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}},
{categoryNames=Java Virtual Machine, GC, Collector},
description=Extra information specific to G1 Garbage Collections,
id=291, label=G1 Garbage Collection,
name=jdk.G1GarbageCollection,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}},
{categoryNames=Java Virtual Machine, GC, Detailed},
description=null, id=292, label=G1 MMU Information,
name=jdk.G1MMU,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}},
{categoryNames=Java Virtual Machine, GC, Detailed},
description=null, id=293, label=Evacuation Information,
name=jdk.EvacuationInformation,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}},
{categoryNames=Java Virtual Machine, GC, Reference},
description=Total count of processed references during GC, id=294,
label=GC Reference Statistics, name=jdk.GCReferenceStatistics,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}},
{categoryNames=Java Virtual Machine, GC, Detailed},
description=null, id=296, label=Object Count after GC,
name=jdk.ObjectCountAfterGC,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}},
{categoryNames=Java Virtual Machine, GC, Detailed},
description=Memory related evacuation statistics during GC for the
young generation, id=298, label=G1 Evacuation Statistics for Young,
name=jdk.G1EvacuationYoungStatistics,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}},
{categoryNames=Java Virtual Machine, GC, Detailed},
description=Memory related evacuation statistics during GC for the old
generation, id=299, label=G1 Evacuation Memory Statistics for Old,
name=jdk.G1EvacuationOldStatistics,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}},
{categoryNames=Java Virtual Machine, GC, Detailed},
description=Basic statistics related to current IHOP calculation, id=300,
label=G1 Basic IHOP Statistics, name=jdk.G1BasicIHOP,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}},
{categoryNames=Java Virtual Machine, GC, Detailed},
description=Statistics related to current adaptive IHOP calculation,
id=301, label=G1 Adaptive IHOP Statistics,
name=jdk.G1AdaptiveIHOP,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}},
{categoryNames=Java Virtual Machine, GC, Detailed},
description=Object survived scavenge and was copied to a new
Promotion Local Allocation Buffer (PLAB). Supported GCs are Parallel
Scavenge, G1 and CMS with Parallel New. Due to promotion being
done in parallel an object might be reported multiple times as the GC
threads race to copy all objects., id=302, label=Promotion in new
PLAB, name=jdk.PromoteObjectInNewPLAB,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}},
{categoryNames=Java Virtual Machine, GC, Detailed},
description=Object survived scavenge and was copied directly to the
heap. Supported GCs are Parallel Scavenge, G1 and CMS with
Parallel New. Due to promotion being done in parallel an object might
be reported multiple times as the GC threads race to copy all objects.,
id=303, label=Promotion outside PLAB,
name=jdk.PromoteObjectOutsidePLAB,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}},
{categoryNames=Java Virtual Machine, GC, Detailed},
description=Promotion of an object failed, id=304, label=Promotion
Failed, name=jdk.PromotionFailed,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}},
{categoryNames=Java Virtual Machine, GC, Detailed},
description=Evacuation of an object failed, id=305, label=Evacuation
Failed, name=jdk.EvacuationFailed,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}},
{categoryNames=Java Virtual Machine, GC, Detailed},
description=Concurrent Mode failed, id=306, label=Concurrent Mode
Failure, name=jdk.ConcurrentModeFailure,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}},
{categoryNames=Java Virtual Machine, GC, Phases},
description=null, id=307, label=GC Phase Pause,
name=jdk.GCPhasePause,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}},
{categoryNames=Java Virtual Machine, GC, Phases},
description=null, id=308, label=GC Phase Pause Level 1,
name=jdk.GCPhasePauseLevel1,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}},
{categoryNames=Java Virtual Machine, GC, Phases},
description=null, id=309, label=GC Phase Pause Level 2,
name=jdk.GCPhasePauseLevel2,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}},
{categoryNames=Java Virtual Machine, GC, Phases},
description=null, id=310, label=GC Phase Pause Level 3,
name=jdk.GCPhasePauseLevel3,

```

```

settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}},
{categoryNames=Java Virtual Machine, GC, Phases},
description=null, id=311, label=GC Phase Pause Level 4,
name=jdk.GCPhasePauseLevel4,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}},
{categoryNames=Java Virtual Machine, GC, Phases},
description=null, id=312, label=GC Phase Concurrent,
name=jdk.GCPhaseConcurrent,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}},
{categoryNames=Java Virtual Machine, GC, Detailed},
description=null, id=313, label=Allocation Requiring GC,
name=jdk.AllocationRequiringGC,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.BooleanField, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}},
{categoryNames=Java Virtual Machine, GC, Detailed},
description=null, id=314, label=Tenuring Distribution,
name=jdk.TenuringDistribution,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{categoryNames=Java Virtual Machine, GC, Detailed},
description=Information about a G1 heap region type change, id=315,
label=G1 Heap Region Type Change,
name=jdk.G1HeapRegionTypeChange,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{categoryNames=Java Virtual Machine, Compiler}, description=null,
id=316, label=Compilation, name=jdk.Compilation,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}},
{categoryNames=Java Virtual Machine, Compiler}, description=null,
id=317, label=Compiler Phase, name=jdk.CompilerPhase,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}},
{categoryNames=Java Virtual Machine, Compiler}, description=null,
id=318, label=Compilation Failure, name=jdk.CompilationFailure,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{categoryNames=Java Virtual Machine, Compiler, Optimization},
description=null, id=320, label=Method Inlining,
name=jdk.CompilerInlining,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{categoryNames=Java Virtual Machine, Code Sweeper},
description=null, id=321, label=Sweep Code Cache,
name=jdk.SweepCodeCache,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}},
{categoryNames=Java Virtual Machine, Code Cache},
description=null, id=322, label=Code Cache Full,
name=jdk.CodeCacheFull,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{categoryNames=Java Virtual Machine, Runtime, Safepoint},
description=Safepointing begin, id=323, label=Safepoint Begin,
name=jdk.SafepointBegin,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}},
{categoryNames=Java Virtual Machine, Runtime, Safepoint},
description=Synchronize run state of threads, id=324, label=Safepoint
State Synchronization, name=jdk.SafepointStateSynchronization,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}},
{categoryNames=Java Virtual Machine, Runtime, Safepoint},
description=Safepointing begin waiting on running threads to block,
id=325, label=Safepoint Wait Blocked,
name=jdk.SafepointWaitBlocked,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}},
{categoryNames=Java Virtual Machine, Runtime, Safepoint},
description=Safepointing begin running cleanup tasks, id=326,
label=Safepoint Cleanup, name=jdk.SafepointCleanup,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}},
{categoryNames=Java Virtual Machine, Runtime, Safepoint},
description=Safepointing begin running cleanup tasks, id=327,
label=Safepoint Cleanup Task, name=jdk.SafepointCleanupTask,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}},
{categoryNames=Java Virtual Machine, Runtime, Safepoint},
description=Safepointing end, id=328, label=Safepoint End,
name=jdk.SafepointEnd,
settingDescriptors={contentType=jdk.jfr.BooleanField,

```



```

defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled),
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}},
{categoryNames=[Java Virtual Machine, Runtime],
description=Execution of a VM Operation, id=329, label=VM
Operation, name=jdk.ExecuteVMOperation,
settingDescriptors=[[contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled),
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}},
{categoryNames=[Java Virtual Machine, Runtime], description=JVM
shutting down, id=330, label=JVM Shutdown, name=jdk.Shutdown,
settingDescriptors=[[contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled),
{contentType=jdk.jfr.BooleanField, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}},
{categoryNames=[Java Application], description=Allocation in new
Thread Local Allocation Buffer, id=331, label=Allocation in new TLAB,
name=jdk.ObjectAllocationInNewTLAB,
settingDescriptors=[[contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled),
{contentType=jdk.jfr.BooleanField, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}},
{categoryNames=[Java Application], description=Allocation outside
Thread Local Allocation Buffers, id=332, label=Allocation outside
TLAB, name=jdk.ObjectAllocationOutsideTLAB,
settingDescriptors=[[contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled),
{contentType=jdk.jfr.BooleanField, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace},
{contentType=jdk.jfr.Timespan, defaultValue=infinity, description=Limit
running time of event, label=Cutoff, name=cutoff,
typeName=jdk.settings.Cutoff}},
{categoryNames=[Flight Recorder], description=Who requested the
recording and why, id=334, label=Recording Reason,
name=jdk.DumpReason,
settingDescriptors=[[contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled)},
{categoryNames=[Flight Recorder], description=Data could not be
copied out from a buffer, typically because of contention, id=335,
label=Data Loss, name=jdk.DataLoss,
settingDescriptors=[[contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled)},
{categoryNames=[Java Virtual Machine], description=Description of
JVM and the Java application, id=336, label=JVM Information,
name=jdk.JVMInformation,
settingDescriptors=[[contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled), {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}},
{categoryNames=[Operating System], description=null, id=337,
label=OS Information, name=jdk.OSInformation,
settingDescriptors=[[contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled), {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}},
{categoryNames=[Operating System], description=null, id=338,
label=Virtualization Information, name=jdk.VirtualizationInformation,
settingDescriptors=[[contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled), {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}},
{categoryNames=[Java Virtual Machine], description=System Property
at JVM start, id=339, label=Initial System Property,
name=jdk.InitialSystemProperty,
settingDescriptors=[[contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled), {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}},
{categoryNames=[Operating System], description=null, id=340,
label=Initial Environment Variable,
name=jdk.InitialEnvironmentVariable,
settingDescriptors=[[contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled), {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}},
{categoryNames=[Operating System], description=null, id=341,
label=System Process, name=jdk.SystemProcess,
settingDescriptors=[[contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled), {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}},
{categoryNames=[Operating System, Processor], description=null,
id=342, label=CPU Information, name=jdk.CPUInformation,
settingDescriptors=[[contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled), {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}},
{categoryNames=[Operating System, Processor], description=null,
id=343, label=CPU Time Stamp Counter,
name=jdk.CPUTimeStampCounter,
settingDescriptors=[[contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled), {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}},
{categoryNames=[Operating System, Processor], description=OS CPU
Load, id=344, label=CPU Load, name=jdk.CPULoad,
settingDescriptors=[[contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled), {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}},
{categoryNames=[Operating System, Processor], description=null,
id=345, label=Thread CPU Load, name=jdk.ThreadCPULoad,
settingDescriptors=[[contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled), {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}},

```

```

{categoryNames=[Operating System, Processor], description=null,
id=346, label=Thread Context Switch Rate,
name=jdk.ThreadContextSwitchRate,
settingDescriptors=[{contentType=jdk.jfr.BooleanField,
description=Record event, label=Enabled,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}],
{categoryNames=[Operating System, Network], description=null,
id=347, label=Network Utilization, name=jdk.NetworkUtilization,
settingDescriptors=[{contentType=jdk.jfr.BooleanField,
description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}],
{categoryNames=[Java Application, Statistics], description=null,
id=348, label=Java Thread Statistics, name=jdk.JavaThreadStatistics,
settingDescriptors=[{contentType=jdk.jfr.BooleanField,
description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}],
{categoryNames=[Java Application, Statistics], description=null,
id=349, label=Class Loading Statistics,
name=jdk.ClassLoadingStatistics,
settingDescriptors=[{contentType=jdk.jfr.BooleanField,
description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}],
{categoryNames=[Java Application, Statistics], description=null,
id=350, label=Class Loader Statistics,
name=jdk.ClassLoaderStatistics,
settingDescriptors=[{contentType=jdk.jfr.BooleanField,
description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}],
{categoryNames=[Java Application, Statistics], description=null,
id=351, label=Thread Allocation Statistics,
name=jdk.ThreadAllocationStatistics,
settingDescriptors=[{contentType=jdk.jfr.BooleanField,
description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}],
{categoryNames=[Operating System, Memory], description=OS
Physical Memory, id=352, label=Physical Memory,
name=jdk.PhysicalMemory,
settingDescriptors=[{contentType=jdk.jfr.BooleanField,
description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}],
{categoryNames=[Java Virtual Machine, Profiling],
description=Snapshot of a threads state, id=353, label=Method
Profiling Sample, name=jdk.ExecutionSample,
settingDescriptors=[{contentType=jdk.jfr.BooleanField,
description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}],
{categoryNames=[Java Virtual Machine, Profiling],
description=Snapshot of a threads state when in native, id=354,
label=Method Profiling Sample Native,
name=jdk.NativeMethodSample,
settingDescriptors=[{contentType=jdk.jfr.BooleanField,
description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}],
{categoryNames=[Java Virtual Machine, Runtime], description=null,
id=355, label=Thread Dump, name=jdk.ThreadDump,
settingDescriptors=[{contentType=jdk.jfr.BooleanField,
description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}],
{categoryNames=[Java Virtual Machine, Runtime], description=null,
id=356, label=Native Library, name=jdk.NativeLibrary,
settingDescriptors=[{contentType=jdk.jfr.BooleanField,
description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}],
{categoryNames=[Java Virtual Machine, Runtime, Modules],
description=A directed edge representing a dependency, id=357,
label=Module Require, name=jdk.ModuleRequire,
settingDescriptors=[{contentType=jdk.jfr.BooleanField,
description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}],
{categoryNames=[Java Virtual Machine, Runtime, Modules],
description=null, id=358, label=Module Export,
name=jdk.ModuleExport,
settingDescriptors=[{contentType=jdk.jfr.BooleanField,
description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}],
{categoryNames=[Java Virtual Machine, Compiler], description=null,
id=359, label=Compiler Statistics, name=jdk.CompilerStatistics,
settingDescriptors=[{contentType=jdk.jfr.BooleanField,
description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}],
{categoryNames=[Java Virtual Machine, Compiler], description=null,
id=360, label=Compiler Configuration,
name=jdk.CompilerConfiguration,
settingDescriptors=[{contentType=jdk.jfr.BooleanField,
description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}],
{categoryNames=[Java Virtual Machine, Code Cache],
description=null, id=361, label=Code Cache Statistics,
name=jdk.CodeCacheStatistics,
settingDescriptors=[{contentType=jdk.jfr.BooleanField,
description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}],
{categoryNames=[Java Virtual Machine, Code Cache],
description=null, id=362, label=Code Cache Configuration,
name=jdk.CodeCacheConfiguration,
settingDescriptors=[{contentType=jdk.jfr.BooleanField,
description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}],
{categoryNames=[Java Virtual Machine, Code Sweeper],
description=null, id=363, label=Code Sweeper Statistics,
name=jdk.CodeSweeperStatistics,
settingDescriptors=[{contentType=jdk.jfr.BooleanField,
description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,

```

```

defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}),
{categoryNames=Java Virtual Machine, Code Sweeper},
description=null, id=364, label=Code Sweeper Configuration,
name=jdk.CodeSweeperConfiguration,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}),
{categoryNames=Java Virtual Machine, Flag}, description=null,
id=365, label=Int Flag, name=jdk.IntFlag,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}),
{categoryNames=Java Virtual Machine, Flag}, description=null,
id=366, label=Unsigned Int Flag, name=jdk.UnsignedIntFlag,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}),
{categoryNames=Java Virtual Machine, Flag}, description=null,
id=367, label=Long Flag, name=jdk.LongFlag,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}),
{categoryNames=Java Virtual Machine, Flag}, description=null,
id=368, label=Unsigned Long Flag, name=jdk.UnsignedLongFlag,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}),
{categoryNames=Java Virtual Machine, Flag}, description=null,
id=369, label=Double Flag, name=jdk.DoubleFlag,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}),
{categoryNames=Java Virtual Machine, Flag}, description=null,
id=370, label=Boolean Flag, name=jdk.BooleanField,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}),
{categoryNames=Java Virtual Machine, Flag}, description=null,
id=371, label=String Flag, name=jdk.StringFlag,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}),
{categoryNames=Java Virtual Machine, GC, Detailed},
description=null, id=372, label=Object Count, name=jdk.ObjectCount,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}),
{categoryNames=Java Virtual Machine, GC, Detailed},
description=Information about a specific heap region in the G1 GC,
id=373, label=G1 Heap Region Information,
name=jdk.G1HeapRegionInformation,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}),
{categoryNames=Java Virtual Machine, GC, Configuration},
description=The configuration of the garbage collector, id=374,
label=GC Configuration, name=jdk.GCConfiguration,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}),
{categoryNames=Java Virtual Machine, GC, Configuration},
description=The configuration of the survivors of garbage collection,
id=375, label=GC Survivor Configuration,
name=jdk.GCSurvivorConfiguration,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}),
{categoryNames=Java Virtual Machine, GC, Configuration},
description=The configuration of the Thread Local Allocation Buffers
(TLABs), id=376, label=TLAB Configuration,
name=jdk.GCTLABConfiguration,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}),
{categoryNames=Java Virtual Machine, GC, Configuration},
description=The configuration of the garbage collected heap, id=377,
label=GC Heap Configuration, name=jdk.GCHeapConfiguration,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}),
{categoryNames=Java Virtual Machine, GC, Configuration},
description=The configuration of the young generation of the garbage
collected heap, id=378, label=Young Generation Configuration,
name=jdk.YoungGenerationConfiguration,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}),
{categoryNames=Java Virtual Machine, GC, Detailed},
description=Allocation of a ZPage, id=379, label=ZPage Allocation,
name=jdk.ZPageAllocation,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}}),
{categoryNames=Java Virtual Machine, GC, Detailed},
description=null, id=380, label=ZGC Thread Phase,
name=jdk.ZThreadPhase,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}}),
{categoryNames=Java Virtual Machine, GC, Detailed},
description=null, id=381, label=Z Statistics Counter,

```

ObjectName
Recordings

```
name=jdk.ZStatisticsCounter,  
settingDescriptors={contentType=jdk.jfr.BooleanField,  
defaultValue=false, description=Record event, label=Enabled,  
name=enabled, typeName=jdk.settings.Enabled},  
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record  
event with duration above or equal to threshold, label=Threshold,  
name=threshold, typeName=jdk.settings.Threshold}},  
{categoryNames={Java Virtual Machine, GC, Detailed},  
description=null, id=382, label=Z Statistics Sampler,  
name=jdk.ZStatisticsSampler,  
settingDescriptors={contentType=jdk.jfr.BooleanField,  
defaultValue=false, description=Record event, label=Enabled,  
name=enabled, typeName=jdk.settings.Enabled},  
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record  
event with duration above or equal to threshold, label=Threshold,  
name=threshold, typeName=jdk.settings.Threshold}}}]  
jdk.management.jfr.type=FlightRecorder  
[]
```