



Catalina

Connector

port=80

(Implementation of a Coyote connector)

URIEncoding	UTF-8	(Character encoding used to decode the URI)
acceptCount	100	(The accept count for this Connector)
address	null	(The IP address on which to bind)
ajpFlush	null	(Send AJP flush package for each explicit flush)
allowTrace	false	(Allow disabling TRACE method)
allowedRequestAttributesPattern	null	(Regular expression that any custom request attributes must match else the request will be rejected)
ciphers	HIGH:!aNULL:!eNULL:!EXPORT:!DES:!RC4:!MD5:!kRSA	(Comma-separated list of requested cipher suites)
ciphersUsed	null	(Array of ciphers suites in use)
className	null	(Fully qualified class name of the managed object)
connectionLinger	-1	(Linger value on the incoming connection)
connectionTimeout	20 000	(Timeout value on the incoming connection)
enableLookups	false	(The 'enable DNS lookups' flag for this Connector)
executorName	Internal	(The name of the executor - if any - associated with this Connector)
keepAliveTimeout	20 000	(The number of milliseconds Tomcat will wait for a subsequent request before closing the connection)
localPort	80	(The port number on which this connector is listening to requests. If the special value for port of zero is used then this method will report the actual port bound.)
maxHeaderCount	100	(The maximum number of headers that are allowed by the container. 100 by default. A value of less than 0 means no limit.)
maxKeepAliveRequests	100	(Maximum number of Keep-Alive requests to honor per connection)
maxParameterCount	1 000	(The maximum number of parameters (GET plus POST) which will be automatically parsed by the container. 10000 by default. A value of less than 0 means no limit.)
maxPostSize	2 097 152	(Maximum size in bytes of a POST which will be handled by the servlet API provided features)
maxSavePostSize	4 096	(Maximum size of a POST which will be saved by the container during authentication)
maxSwallowSize	2 097 152	(The maximum number of request body bytes to be swallowed by Tomcat for an aborted upload)
maxThreads	200	(The maximum number of request processing threads to be created for the internal Executor. -1 indicates an external Executor is being used.)
minSpareThreads	10	(The number of request processing threads that will be created for the internal Executor. -1 indicates an external Executor is being used.)
modelerType	null	(Type of the modeled resource. Can be set only once)
packetSize	null	(The ajp packet size.)
port	80	(The port number (excluding any offset) on which this connector is configured to listen for requests. The special value of 0 means select a random free port when the socket is bound.)
portOffset	0	(The offset that will be applied to port to determine the actual port number used.)
portWithOffset	80	(The actual port number (including any offset) on which this connector is configured to listen for requests.)
processorCache	200	(The processor cache size.)
protocol	HTTP/1.1	(Coyote protocol handler in use)
protocolHandlerClassName	org.apache.coyote.http11.Http11NioProtocol	(Coyote Protocol handler class name)
proxyName	null	(The Server name to which we should pretend requests to this Connector)
proxyPort	0	(The Server port to which we should pretend requests to this Connector)
redirectPort	443	(The redirect port (excluding any offset) for non-SSL to SSL redirects)
redirectPortWithOffset	443	(The actual redirect port (including any offset) for non-SSL to SSL redirects.)
scheme	http	(Protocol name for this Connector (http, https))
secretRequired	null	(Must secret be set to a non-null, non-zero-length String?)
secure	false	(Is this a secure (SSL) Connector?)
sslProtocols	null	(Comma-separated list of SSL protocol variants to be enabled)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
tcpNoDelay	true	(Should we use TCP no delay?)
threadPriority	5	(The thread priority for processors using the internal Executor. -1 indicates an external Executor is being used.)
useBodyEncodingForURI	false	(Should the body encoding be used for URI query parameters)
useIPVHosts	false	(Should IP-based virtual hosting be used?)
xpoweredBy	false	(Is generation of X-Powered-By response header enabled/disabled?)

DataSource

host=localhost,context=/demo,class=javax.sql.DataSource,name="jdbc/demo_javamelody"

abandonedUsageTracking	false	(Inspected attribute abandonedUsageTracking)
accessToUnderlyingConnectionAllowed	false	(Inspected attribute accessToUnderlyingConnectionAllowed)
autoCommitOnReturn	true	(Inspected attribute autoCommitOnReturn)
cacheState	true	(Inspected attribute cacheState)
closed	false	(Inspected attribute closed)
connectionFactoryClassName	null	(Inspected attribute connectionFactoryClassName)
connectionInitSqlsAsArray	[]	(Inspected attribute connectionInitSqlsAsArray)
defaultAutoCommit	null	(Inspected attribute defaultAutoCommit)
defaultCatalog	null	(Inspected attribute defaultCatalog)
defaultQueryTimeout	null	(Inspected attribute defaultQueryTimeout)
defaultReadOnly	null	(Inspected attribute defaultReadOnly)

defaultSchema	null	(Inspected attribute defaultSchema)
defaultTransactionIsolation	-1	(Inspected attribute defaultTransactionIsolation)
disconnectionSqlCodesAsArray	[]	(Inspected attribute disconnectionSqlCodesAsArray)
driverClassName	org.h2.Driver	(Inspected attribute driverClassName)
enableAutoCommitOnReturn	true	(Inspected attribute enableAutoCommitOnReturn)
evictionPolicyClassName	org.apache.tomcat.dbcp.pool2.impl.DefaultEvictionPolicy	(Inspected attribute evictionPolicyClassName)
fastFailValidation	false	(Inspected attribute fastFailValidation)
initialSize	0	(Inspected attribute initialSize)
jmxName	Catalina:type=DataSource,host=localhost,context=/demo,class=javax.sql.DataSource,name="jdbc/demo_javamelody"	(Inspected attribute jmxName)
lifo	true	(Inspected attribute lifo)
logAbandoned	false	(Inspected attribute logAbandoned)
logExpiredConnections	true	(Inspected attribute logExpiredConnections)
maxConnLifetimeMillis	-1	(Inspected attribute maxConnLifetimeMillis)
maxIdle	10	(Inspected attribute maxIdle)
maxOpenPreparedStatements	-1	(Inspected attribute maxOpenPreparedStatements)
maxTotal	100	(Inspected attribute maxTotal)
maxWaitMillis	30 000	(Inspected attribute maxWaitMillis)
minEvictableIdleTimeMillis	1 800 000	(Inspected attribute minEvictableIdleTimeMillis)
minIdle	0	(Inspected attribute minIdle)
modelerType	org.apache.tomcat.dbcp.dbcp2.BasicDataSource	(Type of the modeled resource. Can be set only once)
numActive	10	(Inspected attribute numActive)
numIdle	1	(Inspected attribute numIdle)
numTestsPerEvictionRun	3	(Inspected attribute numTestsPerEvictionRun)
poolPreparedStatements	false	(Inspected attribute poolPreparedStatements)
removeAbandonedOnBorrow	false	(Inspected attribute removeAbandonedOnBorrow)
removeAbandonedOnMaintenance	false	(Inspected attribute removeAbandonedOnMaintenance)
removeAbandonedTimeout	300	(Inspected attribute removeAbandonedTimeout)
rollbackOnReturn	true	(Inspected attribute rollbackOnReturn)
softMinEvictableIdleTimeMillis	-1	(Inspected attribute softMinEvictableIdleTimeMillis)
testOnBorrow	true	(Inspected attribute testOnBorrow)
testOnCreate	false	(Inspected attribute testOnCreate)
testOnReturn	false	(Inspected attribute testOnReturn)
testWhileIdle	false	(Inspected attribute testWhileIdle)
timeBetweenEvictionRunsMillis	-1	(Inspected attribute timeBetweenEvictionRunsMillis)
url	jdbc:h2:/opt/data/demo/h2	(Inspected attribute url)
username	sa	(Inspected attribute username)
validationQuery	null	(Inspected attribute validationQuery)
validationQueryTimeout	-1	(Inspected attribute validationQueryTimeout)

host=localhost,context=/demo,class=javax.sql.DataSource,name="jdbc/demo_javamelody",connectionpool=connections

AbandonedConfig	false
BlockWhenExhausted	true
BorrowedCount	1 277
Closed	false
CreatedCount	11

CreationStackTrace

```

java.lang.Exception
at
org.apache.tomcat.dbcp.pool2.impl.BaseGenericObjectPool.<init>(BaseGenericObjectPool.java:147)
at
org.apache.tomcat.dbcp.pool2.impl.GenericObjectPool.<init>(GenericObjectPool.java:109)
at
org.apache.tomcat.dbcp.dbcp2.BasicDataSource.createObjectPool(BasicDataSource.java:628)
at
org.apache.tomcat.dbcp.dbcp2.BasicDataSource.createConnectionPool(BasicDataSource.java:492)
at
org.apache.tomcat.dbcp.dbcp2.BasicDataSource.createDataSource(BasicDataSource.java:558)
at
org.apache.tomcat.dbcp.dbcp2.BasicDataSource.getConnection(BasicDataSource.java:753)
at
java.base/jdk.internal.reflect.NativeMethodAccessorImpl.invoke0(Native Method)
at
java.base/jdk.internal.reflect.NativeMethodAccessorImpl.invoke(NativeMethodAccessorImpl.java:62)
at
java.base/jdk.internal.reflect.DelegatingMethodAccessorImpl.invoke(DelegatingMethodAccessorImpl.java:43)
at
java.base/java.lang.reflect.Method.invoke(Method.java:566)
at
net.bull.javamelody.JdbcWrapper$3.invoke(JdbcWrapper.java:812)
at
net.bull.javamelody.JdbcWrapper$DelegatingInvocationHandler.invoke(JdbcWrapper.java:306)
at
com.sun.proxy.$Proxy5.getConnection(Unknown Source)
at
net.bull.javamelody.internal.model.JavaInformations.buildDataBaseVersion(JavaInformations.java:426)
at
net.bull.javamelody.internal.model.JavaInformations.<init>(JavaInformations.java:200)
at
net.bull.javamelody.internal.web.MonitoringController.doActionIfNeededAndReport(MonitoringController.java:158)
at
net.bull.javamelody.MonitoringFilter.doMonitoring(MonitoringFilter.java:408)
at
net.bull.javamelody.MonitoringFilter.doFilter(MonitoringFilter.java:206)
at
org.apache.catalina.core.ApplicationFilterChain.internalDoFilter(ApplicationFilterChain.java:193)
at
org.apache.catalina.core.ApplicationFilterChain.doFilter(ApplicationFilterChain.java:166)
at
fr.spi4j.filter.HttpSessionFilter.doFilter(HttpSessionFilter.java:69)
at
org.apache.catalina.core.ApplicationFilterChain.internalDoFilter(ApplicationFilterChain.java:193)
at
org.apache.catalina.core.ApplicationFilterChain.doFilter(ApplicationFilterChain.java:166)
at
net.bull.javamelody.MonitoringFilter.doFilter(MonitoringFilter.java:199)
at
org.apache.catalina.core.ApplicationFilterChain.internalDoFilter(ApplicationFilterChain.java:193)
at
org.apache.catalina.core.ApplicationFilterChain.doFilter(ApplicationFilterChain.java:166)
at
fr.spi4j.filter.ForbiddenActionsFilter.doFilter(ForbiddenActionsFilter.java:24)
at
org.apache.catalina.core.ApplicationFilterChain.internalDoFilter(ApplicationFilterChain.java:193)
at
org.apache.catalina.core.ApplicationFilterChain.doFilter(ApplicationFilterChain.java:166)
at
fr.spi4j.lib.security.RemoteUserFilter.doFilter(RemoteUserFilter.java:66)
at
org.apache.catalina.core.ApplicationFilterChain.internalDoFilter(ApplicationFilterChain.java:193)
at
org.apache.catalina.core.ApplicationFilterChain.doFilter(ApplicationFilterChain.java:166)
at
org.apache.catalina.core.StandardWrapperValve.invoke(StandardWrapperValve.java:202)
at
org.apache.catalina.core.StandardContextValve.invoke(StandardContextValve.java:96)
at
org.apache.catalina.authenticator.AuthenticatorBase.invoke(AuthenticatorBase.java:541)
at
org.apache.catalina.core.StandardHostValve.invoke(StandardHostValve.java:139)
at
org.apache.catalina.valves.ErrorReportValve.invoke(ErrorReportValve.java:92)
at
org.apache.catalina.valves.AbstractAccessLogValve.invoke(AbstractAccessLogValve.java:688)
at
org.apache.catalina.core.StandardEngineValve.invoke(StandardEngineValve.java:74)
at
org.apache.catalina.connector.CoyoteAdapter.service(CoyoteAdapter.java:343)
at
org.apache.coyote.http11.Http11Processor.service(Http11Processor.java:373)
at
org.apache.coyote.AbstractProcessorLight.process(AbstractProcessorLight.java:65)
at
org.apache.coyote.AbstractProtocol$ConnectionHandler.process(AbstractProtocol.java:868)
at
org.apache.tomcat.util.net.NioEndpoint$SocketProcessor.doRun(NioEndpoint.java:1594)
at
org.apache.tomcat.util.net.SocketProcessorBase.run(SocketProcessorBase.java:49)
at
java.base/java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1128)
at
java.base/java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:628)
at
org.apache.tomcat.util.threads.TaskThread$WrappingRunnable.run(TaskThread.java:61)
at
java.base/java.lang.Thread.run(Thread.java:834)

```

```

DestroyedByBorrowValidationCount      0
DestroyedByEvictorCount               0
DestroyedCount                        0
FactoryType                          org.apache.tomcat.dbcp.dbcp2.PoolableConnectionFactory<org.apa
che.tomcat.dbcp.dbcp2.PoolableConnection>
Fairness                              false
Lifo                                  true
LogAbandoned                         false
MaxBorrowWaitTimeMillis               39
MaxIdle                               10
MaxTotal                              100
MaxWaitMillis                         30 000
MeanActiveTimeMillis                  0
MeanBorrowWaitTimeMillis              0
MeanIdleTimeMillis                    1 418 302
MinEvictableIdleTimeMillis            1 800 000
MinIdle                               0
NumActive                             10
NumIdle                               1
NumTestsPerEvictionRun                 3
NumWaiters                            0
RemoveAbandonedOnBorrow               false
RemoveAbandonedOnMaintenance          false
RemoveAbandonedTimeout                2 147 483 647
ReturnedCount                         1 267
TestOnBorrow                          true
TestOnCreate                          false
TestOnReturn                          false
TestWhileIdle                         false
TimeBetweenEvictionRunsMillis          -1
    
```

host=localhost,context=/demo,class=javax.sql.DataSource,name="jdbc/demo_javamelody",connectionpool=connections,connection=1

```

AutoCommit                            false
CacheState                             true
Catalog                                H2
Closed                                 false
Holdability                            1
ReadOnly                               false
Schema                                 PUBLIC
ToString                               783024975, URL=jdbc:h2:/opt/data/demo/h2, UserName=SA, H2
JDBC Driver
TransactionIsolation                   2
    
```

host=localhost,context=/demo,class=javax.sql.DataSource,name="jdbc/demo_javamelody",connectionpool=connections,connection=10

```

AutoCommit                            false
CacheState                             true
Catalog                                H2
Closed                                 false
Holdability                            1
ReadOnly                               false
Schema                                 PUBLIC
ToString                               1977401306, URL=jdbc:h2:/opt/data/demo/h2, UserName=SA, H2
JDBC Driver
TransactionIsolation                   2
    
```

host=localhost,context=/demo,class=javax.sql.DataSource,name="jdbc/demo_javamelody",connectionpool=connections,connection=11

```

CacheState                             true
Closed                                 true
ToString                               185971658, URL=jdbc:h2:/opt/data/demo/h2, UserName=SA, H2
JDBC Driver
    
```

host=localhost,context=/demo,class=javax.sql.DataSource,name="jdbc/demo_javamelody",connectionpool=connections,connection=2

```

AutoCommit                            false
CacheState                             true
Catalog                                H2
Closed                                 false
Holdability                            1
ReadOnly                               false
Schema                                 PUBLIC
ToString                               521692877, URL=jdbc:h2:/opt/data/demo/h2, UserName=SA, H2
JDBC Driver
TransactionIsolation                   2
    
```

host=localhost,context=/demo,class=javax.sql.DataSource,name="jdbc/demo_javamelody",connectionpool=connections,connection=3

```

AutoCommit                            false
CacheState                             true
Catalog                                H2
Closed                                 false
Holdability                            1
    
```

ReadOnly	false
Schema	PUBLIC
ToString	20922323593, URL=jdbc:h2:opt/data/demo/h2, UserName=SA, H2 JDBC Driver
TransactionIsolation	2

host=localhost,context=/demo,class=javax.sql.DataSource,name="jdbc/demo_javamelody",connectionpool=connections,connection=4

AutoCommit	false
CacheState	true
Catalog	H2
Closed	false
Holdability	1
ReadOnly	false
Schema	PUBLIC
ToString	12506223593, URL=jdbc:h2:opt/data/demo/h2, UserName=SA, H2 JDBC Driver
TransactionIsolation	2

host=localhost,context=/demo,class=javax.sql.DataSource,name="jdbc/demo_javamelody",connectionpool=connections,connection=5

AutoCommit	false
CacheState	true
Catalog	H2
Closed	false
Holdability	1
ReadOnly	false
Schema	PUBLIC
ToString	405065432, URL=jdbc:h2:opt/data/demo/h2, UserName=SA, H2 JDBC Driver
TransactionIsolation	2

host=localhost,context=/demo,class=javax.sql.DataSource,name="jdbc/demo_javamelody",connectionpool=connections,connection=6

AutoCommit	false
CacheState	true
Catalog	H2
Closed	false
Holdability	1
ReadOnly	false
Schema	PUBLIC
ToString	77647732, URL=jdbc:h2:opt/data/demo/h2, UserName=SA, H2 JDBC Driver
TransactionIsolation	2

host=localhost,context=/demo,class=javax.sql.DataSource,name="jdbc/demo_javamelody",connectionpool=connections,connection=7

AutoCommit	false
CacheState	true
Catalog	H2
Closed	false
Holdability	1
ReadOnly	false
Schema	PUBLIC
ToString	1337016279, URL=jdbc:h2:opt/data/demo/h2, UserName=SA, H2 JDBC Driver
TransactionIsolation	2

host=localhost,context=/demo,class=javax.sql.DataSource,name="jdbc/demo_javamelody",connectionpool=connections,connection=8

AutoCommit	false
CacheState	true
Catalog	H2
Closed	false
Holdability	1
ReadOnly	false
Schema	PUBLIC
ToString	1108511127, URL=jdbc:h2:opt/data/demo/h2, UserName=SA, H2 JDBC Driver
TransactionIsolation	2

host=localhost,context=/demo,class=javax.sql.DataSource,name="jdbc/demo_javamelody",connectionpool=connections,connection=9

AutoCommit	false
CacheState	true
Catalog	H2
Closed	false
Holdability	1
ReadOnly	false
Schema	PUBLIC
ToString	2084091035, URL=jdbc:h2:opt/data/demo/h2, UserName=SA, H2 JDBC Driver
TransactionIsolation	2

Deployer

host=localhost

(Startup event listener for a Host that configures the properties of that Host, and the associated defined contexts)

className	org.apache.catalina.startup.HostConfig	(Fully qualified class name of the managed object)
configBaseName	/opt/apache-tomcat-9.0.33/conf/Catalina/localhost	(The base directory for Context configuration files)
contextClass	org.apache.catalina.core.StandardContext	(The Java class name of the Context implementation we should use)
copyXML	false	(The copy XML config file flag for this component)
deployXML	true	(The deploy XML config file flag for this component)
modelerType	org.apache.catalina.startup.HostConfig	(Type of the modeled resource. Can be set only once)
unpackWARs	false	(The unpack WARs flag)

Engine

(Standard Engine Component)

backgroundProcessorDelay	10	(The processor delay for this component.)
catalinaBase	/opt/apache-tomcat-9.0.33	(Base (instance) directory for this Engine, typically same as catalina.base system property)
defaultHost	localhost	(Name of the default Host for this Engine)
jvmRoute	null	(Route used for load balancing)
managedResource	StandardEngine[Catalina]	(The managed resource this MBean is associated with)
modelerType	org.apache.catalina.core.StandardEngine	(Type of the modeled resource. Can be set only once)
name	Catalina	(Unique name of this Engine)
realm	LockOutRealm[StandardEngine[Catalina]]	(Associated realm.)
startChildren	true	(Will children be started automatically when they are added.)
startStopThreads	1	(The number of threads to use when starting and stopping child Hosts)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

Filter

WebModule=//localhost/,name=Tomcat WebSocket (JSR356) Filter,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet-filter definition)

filterClass	org.apache.tomcat.websocket.server.WsFilter	(Fully qualified class name of the filter object)
filterInitParameterMap	{}	(Return the initialization parameters associated with this filter)
filterName	Tomcat WebSocket (JSR356) Filter	(The name used to reference the filter in web.xml)
modelerType	org.apache.catalina.core.ApplicationFilterConfig	(Type of the modeled resource. Can be set only once)

WebModule=//localhost/demo,name=Tomcat WebSocket (JSR356) Filter,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet-filter definition)

filterClass	org.apache.tomcat.websocket.server.WsFilter	(Fully qualified class name of the filter object)
filterInitParameterMap	{}	(Return the initialization parameters associated with this filter)
filterName	Tomcat WebSocket (JSR356) Filter	(The name used to reference the filter in web.xml)
modelerType	org.apache.catalina.core.ApplicationFilterConfig	(Type of the modeled resource. Can be set only once)

WebModule=//localhost/demo,name=forbiddenActions,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet-filter definition)

filterClass	ForbiddenActionsFilter	(Fully qualified class name of the filter object)
filterInitParameterMap	{}	(Return the initialization parameters associated with this filter)
filterName	forbiddenActions	(The name used to reference the filter in web.xml)
modelerType	org.apache.catalina.core.ApplicationFilterConfig	(Type of the modeled resource. Can be set only once)

WebModule=//localhost/demo,name=httpSessionInThread,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet-filter definition)

filterClass	fr.spi4j.filter.HttpSessionFilter	(Fully qualified class name of the filter object)
filterInitParameterMap	{}	(Return the initialization parameters associated with this filter)
filterName	httpSessionInThread	(The name used to reference the filter in web.xml)
modelerType	org.apache.catalina.core.ApplicationFilterConfig	(Type of the modeled resource. Can be set only once)

WebModule=//localhost/demo,name=javamelody,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet-filter definition)

filterClass	net.bull.javamelody.MonitoringFilter	(Fully qualified class name of the filter object)
filterInitParameterMap	{}	(Return the initialization parameters associated with this filter)
filterName	javamelody	(The name used to reference the filter in web.xml)
modelerType	org.apache.catalina.core.ApplicationFilterConfig	(Type of the modeled resource. Can be set only once)

WebModule=//localhost/demo,name=monitoring,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet-filter definition)

filterClass	net.bull.javamelody.MonitoringFilter	(Fully qualified class name of the filter object)
filterInitParameterMap	{}	(Return the initialization parameters associated with this filter)
filterName	monitoring	(The name used to reference the filter in web.xml)
modelerType	org.apache.catalina.core.ApplicationFilterConfig	(Type of the modeled resource. Can be set only once)

WebModule=//localhost/demo,name=remoteUser,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet-filter definition)

filterClass	fr.spi4j.lib.security.RemoteUserFilter	(Fully qualified class name of the filter object)
filterInitParameterMap	{}	(Return the initialization parameters associated with this filter)
filterName	remoteUser	(The name used to reference the filter in web.xml)

modelerType org.apache.catalina.core.ApplicationFilterConfig (Type of the modeled resource. Can be set only once)

WebModule=//localhost/downloads,name=Tomcat WebSocket (JSR356) Filter,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet-filter definition)

filterClass org.apache.tomcat.websocket.server.WsFilter (Fully qualified class name of the filter object)
 filterInitParameterMap {} (Return the initialization parameters associated with this filter)
 filterName Tomcat WebSocket (JSR356) Filter (The name used to reference the filter in web.xml)
 modelerType org.apache.catalina.core.ApplicationFilterConfig (Type of the modeled resource. Can be set only once)

WebModule=//localhost/usage,name=Tomcat WebSocket (JSR356) Filter,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet-filter definition)

filterClass org.apache.tomcat.websocket.server.WsFilter (Fully qualified class name of the filter object)
 filterInitParameterMap {} (Return the initialization parameters associated with this filter)
 filterName Tomcat WebSocket (JSR356) Filter (The name used to reference the filter in web.xml)
 modelerType org.apache.catalina.core.ApplicationFilterConfig (Type of the modeled resource. Can be set only once)

WebModule=//localhost/usage,name=basic-auth,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet-filter definition)

filterClass net.bull.javamelody.usagstats.BasicAuthFilter (Fully qualified class name of the filter object)
 filterInitParameterMap {} (Return the initialization parameters associated with this filter)
 filterName basic-auth (The name used to reference the filter in web.xml)
 modelerType org.apache.catalina.core.ApplicationFilterConfig (Type of the modeled resource. Can be set only once)

WebModule=//localhost/usage,name=gzip,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet-filter definition)

filterClass net.bull.javamelody.usagstats.GzipFilter (Fully qualified class name of the filter object)
 filterInitParameterMap {} (Return the initialization parameters associated with this filter)
 filterName gzip (The name used to reference the filter in web.xml)
 modelerType org.apache.catalina.core.ApplicationFilterConfig (Type of the modeled resource. Can be set only once)

WebModule=//localhost/usage,name=javamelody,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet-filter definition)

filterClass net.bull.javamelody.MonitoringFilter (Fully qualified class name of the filter object)
 filterInitParameterMap {} (Return the initialization parameters associated with this filter)
 filterName javamelody (The name used to reference the filter in web.xml)
 modelerType org.apache.catalina.core.ApplicationFilterConfig (Type of the modeled resource. Can be set only once)

GlobalRequestProcessor

name="http-nio-80"

(Runtime information of a group of requests)

bytesReceived 27 822 (Amount of data received, in bytes)
 bytesSent 675 516 990 (Amount of data sent, in bytes)
 errorCount 16 919 (Number of errors)
 maxTime 20 309 (Maximum time to process a request)
 modelerType org.apache.coyote.RequestGroupInfo (Type of the modeled resource. Can be set only once)
 processingTime 8 054 265 (Total time to process the requests)
 requestCount 6 563 926 (Number of requests processed)

Host

host=localhost

(Standard Host Component)

aliases [] (Host aliases)
 appBase webapps (The application root for this Host)
 autoDeploy true (The auto deploy flag for this Host)
 backgroundProcessorDelay -1 (The processor delay for this component.)
 children [Catalina:j2eeType=WebModule,name=//localhost/,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=WebModule,name=//localhost/downloads,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=WebModule,name=//localhost/demo,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=WebModule,name=//localhost/usage,J2EEApplication=none,J2EEServer=none] (Object names of all children)
 configClass org.apache.catalina.startup.ContextConfig (The configuration class for contexts)
 contextClass org.apache.catalina.core.StandardContext (The Java class name of the default Context implementation class for deployed web applications.)
 copyXML false (Should XML files be copied to \$CATALINA_BASE/conf/(engine)/(host) by default when a web application is deployed?)
 createDirs true (Should we create directories upon startup for appBase and xmlBase?)
 deployIgnore null (Paths within appBase ignored for automatic deployment)
 deployOnStartup true (The deploy on startup flag for this Host)
 deployXML true (deploy Context XML config files property)
 errorReportValveClass org.apache.catalina.valves.ErrorReportValve (The Java class name of the default error reporter implementation class for deployed web applications.)
 managedResource StandardEngine[Catalina].StandardHost[localhost] (The managed resource this MBean is associated with)
 modelerType org.apache.catalina.core.StandardHost (Type of the modeled resource. Can be set only once)
 name localhost (Unique name of this Host)
 realm LockOutRealm[StandardEngine[Catalina]] (Associated realm.)
 startChildren true (Will children be started automatically when they are added?)

Monitoring JavaMelody sur /demo_vps363300.ovh.net

startStopThreads	1	(The number of threads to use when starting, stopping and deploying child Contexts)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
undeployOldVersions	false	(Determines if old versions of applications deployed using parallel deployment are automatically undeployed when no longer used. Requires autoDeploy to be enabled.)
unpackWARs	false	(Unpack WARs property)
valveNames	[Catalina.type=Valve,host=localhost,name=AccessLogValve,Catalina.type=Valve,host=localhost,name=ErrorReportValve,Catalina.type=Valve,host=localhost,name=StandardHostValve]	(Return the MBean Names of the Valves associated with this Host)
workDir	null	(Work Directory base for applications)
xmlBase	null	(The XML root for this Host.)

JspMonitor

WebModule=//localhost/,name=jsp,J2EEApplication=none,J2EEServer=none

(JSP Monitoring)

jspCount	1	(The number of JSPs that have been loaded into a webapp)
jspQueueLength	-1	(The length of the JSP queue (if enabled via maxLoadedJsps))
jspReloadCount	0	(The number of JSPs that have been reloaded)
jspUnloadCount	0	(The number of JSPs that have been unloaded)
modelerType	org.apache.jasper.servlet.JspServlet	(Type of the modeled resource. Can be set only once)

WebModule=//localhost/demo,name=jsp,J2EEApplication=none,J2EEServer=none

(JSP Monitoring)

jspCount	1	(The number of JSPs that have been loaded into a webapp)
jspQueueLength	-1	(The length of the JSP queue (if enabled via maxLoadedJsps))
jspReloadCount	0	(The number of JSPs that have been reloaded)
jspUnloadCount	0	(The number of JSPs that have been unloaded)
modelerType	org.apache.jasper.servlet.JspServlet	(Type of the modeled resource. Can be set only once)

WebModule=//localhost/downloads,name=jsp,J2EEApplication=none,J2EEServer=none

(JSP Monitoring)

jspCount	0	(The number of JSPs that have been loaded into a webapp)
jspQueueLength	-1	(The length of the JSP queue (if enabled via maxLoadedJsps))
jspReloadCount	0	(The number of JSPs that have been reloaded)
jspUnloadCount	0	(The number of JSPs that have been unloaded)
modelerType	org.apache.jasper.servlet.JspServlet	(Type of the modeled resource. Can be set only once)

WebModule=//localhost/usage,name=jsp,J2EEApplication=none,J2EEServer=none

(JSP Monitoring)

jspCount	0	(The number of JSPs that have been loaded into a webapp)
jspQueueLength	-1	(The length of the JSP queue (if enabled via maxLoadedJsps))
jspReloadCount	0	(The number of JSPs that have been reloaded)
jspUnloadCount	0	(The number of JSPs that have been unloaded)
modelerType	org.apache.jasper.servlet.JspServlet	(Type of the modeled resource. Can be set only once)

Loader

host=localhost,context=/

(ClassLoader implementation which is specialized for handling web applications)

className	org.apache.catalina.loader.WebappLoader	(Fully qualified class name of the managed object)
delegate	false	(The 'follow standard delegation model' flag that will be used to configure our ClassLoader)
loaderRepositories	[]	(Repositories set in the real loader)
loaderRepositoriesString		(Repositories set in the real loader)
modelerType	org.apache.catalina.loader.WebappLoader	(Type of the modeled resource. Can be set only once)
reloadable	false	(The reloadable flag for this Loader)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

host=localhost,context=/demo

(ClassLoader implementation which is specialized for handling web applications)

className	org.apache.catalina.loader.WebappLoader	(Fully qualified class name of the managed object)
delegate	false	(The 'follow standard delegation model' flag that will be used to configure our ClassLoader)

loaderRepositories	<pre>[war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/classes, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdoctestreport.core-1.0.4.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/ehcache-core-2.6.8.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/log4j-1.2.17.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/spi4j-lib-security-server-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/slf4j-api-1.6.1.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/jta-1.1.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdoctestreport.template.freemarker-1.0.4.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/xpp3_min-1.1.4c.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/gwt-servlet-2.7.0.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/spi4j-gwt-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdoctestreport.document-1.0.4.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/text-2.1.7.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdoctestreport.template-1.0.4.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/freemarker-2.3.16.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdoctestreport.converter-1.0.4.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/validation-api-1.0.0.GA.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/appwhite-1-commons-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdoctestreport.document.docx-1.0.4.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/spi4j-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/robin-1.5.9.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdoctestreport.document.odt-1.0.4.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/spi4j-ui-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/javamelody-core-1.98.0.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/spi4j-doc-report-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdoctestreport.document.pptx-1.0.4.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/spi4j-lib-security-commons-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/appwhite-1-server-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/referentiel-server-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/h2-1.4.200.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/xstream-1.4.11.1.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/referentiel-commons-1.7-SNAPSHOT.jar]</pre>	(Repositories set in the real loader)
loaderRepositoriesString	<pre>war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/classes:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdoctestreport.core-1.0.4.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/ehcache-core-2.6.8.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/log4j-1.2.17.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/spi4j-lib-security-server-1.7-SNAPSHOT.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/slf4j-api-1.6.1.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/jta-1.1.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdoctestreport.template.freemarker-1.0.4.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/xpp3_min-1.1.4c.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/gwt-servlet-2.7.0.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/spi4j-gwt-1.7-SNAPSHOT.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdoctestreport.document-1.0.4.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/text-2.1.7.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdoctestreport.template-1.0.4.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/freemarker-2.3.16.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdoctestreport.converter-1.0.4.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/validation-api-1.0.0.GA.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/appwhite-1-commons-1.7-SNAPSHOT.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdoctestreport.document.docx-1.0.4.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/spi4j-1.7-SNAPSHOT.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/robin-1.5.9.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdoctestreport.document.odt-1.0.4.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/spi4j-ui-1.7-SNAPSHOT.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/javamelody-core-1.98.0.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/spi4j-doc-report-1.7-SNAPSHOT.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdoctestreport.document.pptx-1.0.4.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/spi4j-lib-security-commons-1.7-SNAPSHOT.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/appwhite-1-server-1.7-SNAPSHOT.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/referentiel-server-1.7-SNAPSHOT.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/h2-1.4.200.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/xstream-1.4.11.1.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/referentiel-commons-1.7-SNAPSHOT.jar:</pre>	(Repositories set in the real loader)
modelerType reloadable	<pre>org.apache.catalina.loader.WebappLoader false</pre>	(Type of the modeled resource. Can be set only once) (The reloadable flag for this Loader)

stateName	STARTED	(The name of the LifecycleState that this component is currently in)
-----------	---------	--

host=localhost,context=/downloads

(Classloader implementation which is specialized for handling web applications)

className	org.apache.catalina.loader.WebappLoader	(Fully qualified class name of the managed object)
delegate	false	(The 'follow standard delegation model' flag that will be used to configure our ClassLoader)
loaderRepositories	[]	(Repositories set in the real loader)
loaderRepositoriesString		(Repositories set in the real loader)
modelerType	org.apache.catalina.loader.WebappLoader	(Type of the modeled resource. Can be set only once)
reloadable	false	(The reloadable flag for this Loader)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

host=localhost,context=/usage

(Classloader implementation which is specialized for handling web applications)

className	org.apache.catalina.loader.WebappLoader	(Fully qualified class name of the managed object)
delegate	false	(The 'follow standard delegation model' flag that will be used to configure our ClassLoader)
loaderRepositories	[war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/classes;war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/itext-2.1.7.jar;war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/commons-csv-1.10.0.jar;war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/log4j-1.2.17.jar;war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/jrobin-1.5.9.jar;war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/geoip-api-1.3.1.jar;war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/gson-2.10.1.jar;war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/javamelody-core-1.98.0.jar]	(Repositories set in the real loader)
loaderRepositoriesString	war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/classes;war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/itext-2.1.7.jar;war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/commons-csv-1.10.0.jar;war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/log4j-1.2.17.jar;war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/jrobin-1.5.9.jar;war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/geoip-api-1.3.1.jar;war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/gson-2.10.1.jar;war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/javamelody-core-1.98.0.jar;	(Repositories set in the real loader)
modelerType	org.apache.catalina.loader.WebappLoader	(Type of the modeled resource. Can be set only once)
reloadable	false	(The reloadable flag for this Loader)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

MBeanFactory

(Factory for MBeans and corresponding components)

modelerType	org.apache.catalina.mbeans.MBeanFactory	(Type of the modeled resource. Can be set only once)
-------------	---	--

Manager**host=localhost,context=/**

(Standard implementation of the Manager interface)

activeSessions	6	(Number of active sessions at this moment)
className	org.apache.catalina.session.StandardManager	(Fully qualified class name of the managed object)
duplicates	0	(Number of duplicated session ids generated)
expiredSessions	3 848	(Number of sessions that expired (doesn't include explicit invalidations))
jvmRoute	null	(Retrieve the JvmRoute for the enclosing Engine)
maxActive	179	(Maximum number of active sessions so far)
maxActiveSessions	-1	(The maximum number of active Sessions allowed, or -1 for no limit)
modelerType	org.apache.catalina.session.StandardManager	(Type of the modeled resource. Can be set only once)
name	StandardManager	(The descriptive name of this Manager implementation (for logging))
pathname	SESSIONS.ser	(Path name of the disk file in which active sessions)
persistAuthentication	false	(Indicates whether sessions shall persist authentication information when being persisted (e.g. across application restarts).)
processExpiresFrequency	6	(The frequency of the manager checks (expiration and passivation))
processingTime	839	(Time spent doing housekeeping and expiration)
rejectedSessions	0	(Number of sessions we rejected due to maxActive being reached)
secureRandomAlgorithm	SHA1PRNG	(The secure random number generator algorithm name)
secureRandomClass	null	(The secure random number generator class name)
secureRandomProvider	null	(The secure random number generator provider name)
sessionAttributeNameFilter	null	(The string pattern used for including session attributes in distribution. Null means all attributes are included.)
sessionAttributeValueClassNameFilter	null	(The regular expression used to filter session attributes based on the implementation class of the value. The regular expression is anchored and must match the fully qualified class name.)
sessionAverageAliveTime	18	(Average time an expired session had been alive)
sessionCounter	3 854	(Total number of sessions created by this manager)
sessionCreateRate	0	(Session creation rate in sessions per minute)
sessionExpireRate	0	(Session expiration rate in sessions per minute)
sessionMaxAliveTime	1 948	(Longest time an expired session had been alive)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
warnOnSessionAttributeFilterFailure	false	(Should a WARN level log message be generated if a session attribute fails to match sessionAttributeNameFilter or sessionAttributeValueClassNameFilter?)

host=localhost,context=/demo

(Standard implementation of the Manager interface)

activeSessions	287	(Number of active sessions at this moment)
className	org.apache.catalina.session.StandardManager	(Fully qualified class name of the managed object)
duplicates	0	(Number of duplicated session ids generated)
expiredSessions	10 846	(Number of sessions that expired (doesn't include explicit invalidations))
jvmRoute	null	(Retrieve the JvmRoute for the enclosing Engine)
maxActive	1 334	(Maximum number of active sessions so far)
maxActiveSessions	-1	(The maximum number of active Sessions allowed, or -1 for no limit)
modelerType	org.apache.catalina.session.StandardManager	(Type of the modeled resource. Can be set only once)
name	StandardManager	(The descriptive name of this Manager implementation (for logging))
pathname	SESSIONS.ser	(Path name of the disk file in which active sessions)
persistAuthentication	false	(Indicates whether sessions shall persist authentication information when being persisted (e.g. across application restarts).)
processExpiresFrequency	6	(The frequency of the manager checks (expiration and passivation))
processingTime	1 077	(Time spent doing housekeeping and expiration)
rejectedSessions	0	(Number of sessions we rejected due to maxActive being reached)
secureRandomAlgorithm	SHA1PRNG	(The secure random number generator algorithm name)
secureRandomClass	null	(The secure random number generator class name)
secureRandomProvider	null	(The secure random number generator provider name)
sessionAttributeNameFilter	null	(The string pattern used for including session attributes in distribution. Null means all attributes are included.)
sessionAttributeValueClassNameFilter	null	(The regular expression used to filter session attributes based on the implementation class of the value. The regular expression is anchored and must match the fully qualified class name.)
sessionAverageAliveTime	18	(Average time an expired session had been alive)
sessionCounter	11 133	(Total number of sessions created by this manager)
sessionCreateRate	72	(Session creation rate in sessions per minute)
sessionExpireRate	0	(Session expiration rate in sessions per minute)
sessionMaxAliveTime	3 398	(Longest time an expired session had been alive)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
warnOnSessionAttributeFilterFailure	false	(Should a WARN level log message be generated if a session attribute fails to match sessionAttributeNameFilter or sessionAttributeValueClassNameFilter?)

host=localhost,context=/downloads

(Standard implementation of the Manager interface)

activeSessions	0	(Number of active sessions at this moment)
className	org.apache.catalina.session.StandardManager	(Fully qualified class name of the managed object)
duplicates	0	(Number of duplicated session ids generated)
expiredSessions	0	(Number of sessions that expired (doesn't include explicit invalidations))
jvmRoute	null	(Retrieve the JvmRoute for the enclosing Engine)
maxActive	0	(Maximum number of active sessions so far)
maxActiveSessions	-1	(The maximum number of active Sessions allowed, or -1 for no limit)
modelerType	org.apache.catalina.session.StandardManager	(Type of the modeled resource. Can be set only once)
name	StandardManager	(The descriptive name of this Manager implementation (for logging))
pathname	SESSIONS.ser	(Path name of the disk file in which active sessions)
persistAuthentication	false	(Indicates whether sessions shall persist authentication information when being persisted (e.g. across application restarts).)
processExpiresFrequency	6	(The frequency of the manager checks (expiration and passivation))
processingTime	107	(Time spent doing housekeeping and expiration)
rejectedSessions	0	(Number of sessions we rejected due to maxActive being reached)
secureRandomAlgorithm	SHA1PRNG	(The secure random number generator algorithm name)
secureRandomClass	null	(The secure random number generator class name)
secureRandomProvider	null	(The secure random number generator provider name)
sessionAttributeNameFilter	null	(The string pattern used for including session attributes in distribution. Null means all attributes are included.)
sessionAttributeValueClassNameFilter	null	(The regular expression used to filter session attributes based on the implementation class of the value. The regular expression is anchored and must match the fully qualified class name.)
sessionAverageAliveTime	0	(Average time an expired session had been alive)
sessionCounter	0	(Total number of sessions created by this manager)
sessionCreateRate	0	(Session creation rate in sessions per minute)
sessionExpireRate	0	(Session expiration rate in sessions per minute)
sessionMaxAliveTime	0	(Longest time an expired session had been alive)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
warnOnSessionAttributeFilterFailure	false	(Should a WARN level log message be generated if a session attribute fails to match sessionAttributeNameFilter or sessionAttributeValueClassNameFilter?)

host=localhost,context=/usage

(Standard implementation of the Manager interface)

activeSessions	0	(Number of active sessions at this moment)
className	org.apache.catalina.session.StandardManager	(Fully qualified class name of the managed object)
duplicates	0	(Number of duplicated session ids generated)
expiredSessions	0	(Number of sessions that expired (doesn't include explicit invalidations))
jvmRoute	null	(Retrieve the JvmRoute for the enclosing Engine)
maxActive	0	(Maximum number of active sessions so far)
maxActiveSessions	-1	(The maximum number of active Sessions allowed, or -1 for no limit)
modelerType	org.apache.catalina.session.StandardManager	(Type of the modeled resource. Can be set only once)
name	StandardManager	(The descriptive name of this Manager implementation (for logging))

pathname	SESSIONS.ser	(Path name of the disk file in which active sessions)
persistAuthentication	false	(Indicates whether sessions shall persist authentication information when being persisted (e.g. across application restarts).)
processExpiresFrequency	6	(The frequency of the manager checks (expiration and passivation))
processingTime	15	(Time spent doing housekeeping and expiration)
rejectedSessions	0	(Number of sessions we rejected due to maxActive being reached)
secureRandomAlgorithm	SHA1PRNG	(The secure random number generator algorithm name)
secureRandomClass	null	(The secure random number generator class name)
secureRandomProvider	null	(The secure random number generator provider name)
sessionAttributeNameFilter	null	(The string pattern used for including session attributes in distribution. Null means all attributes are included.)
sessionAttributeValueClassNameFilter	null	(The regular expression used to filter session attributes based on the implementation class of the value. The regular expression is anchored and must match the fully qualified class name.)
sessionAverageAliveTime	0	(Average time an expired session had been alive)
sessionCounter	0	(Total number of sessions created by this manager)
sessionCreateRate	0	(Session creation rate in sessions per minute)
sessionExpireRate	0	(Session expiration rate in sessions per minute)
sessionMaxAliveTime	0	(Longest time an expired session had been alive)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
warnOnSessionAttributeFilterFailure	false	(Should a WARN level log message be generated if a session attribute fails to match sessionAttributeNameFilter or sessionAttributeValueClassNameFilter?)

Mapper

(Maps requests received by the associated connector to Hosts, Contexts and Wrappers)

modelerType	org.apache.catalina.mapper.MapperListener	(Type of the modeled resource. Can be set only once)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

NamingResources

(Holds and manages the naming resources defined in the J2EE Enterprise Naming Context and their associated JNDI context)

container	StandardServer[8005]	(The container with which the naming resources are associated.)
environments	[]	(MBean Names of the set of defined environment entries for this web application)
modelerType	org.apache.catalina.deploy.NamingResourcesImpl	(Type of the modeled resource. Can be set only once)
resourceLinks	[]	(MBean Names of all the defined resource link references for this application.)

host=localhost,context=/

(Holds and manages the naming resources defined in the J2EE Enterprise Naming Context and their associated JNDI context)

container	StandardEngine[Catalina].StandardHost[localhost].StandardContext[]	(The container with which the naming resources are associated.)
environments	[]	(MBean Names of the set of defined environment entries for this web application)
modelerType	org.apache.catalina.deploy.NamingResourcesImpl	(Type of the modeled resource. Can be set only once)
resourceLinks	[]	(MBean Names of all the defined resource link references for this application.)
resources	[]	(MBean Names of all the defined resource references for this application.)

host=localhost,context=/demo

(Holds and manages the naming resources defined in the J2EE Enterprise Naming Context and their associated JNDI context)

container	StandardEngine[Catalina].StandardHost[localhost].StandardContext[/demo]	(The container with which the naming resources are associated.)
environments	[]	(MBean Names of the set of defined environment entries for this web application)
modelerType	org.apache.catalina.deploy.NamingResourcesImpl	(Type of the modeled resource. Can be set only once)
resourceLinks	[]	(MBean Names of all the defined resource link references for this application.)

host=localhost,context=/downloads

(Holds and manages the naming resources defined in the J2EE Enterprise Naming Context and their associated JNDI context)

container	StandardEngine[Catalina].StandardHost[localhost].StandardContext[/downloads]	(The container with which the naming resources are associated.)
environments	[]	(MBean Names of the set of defined environment entries for this web application)
modelerType	org.apache.catalina.deploy.NamingResourcesImpl	(Type of the modeled resource. Can be set only once)
resourceLinks	[]	(MBean Names of all the defined resource link references for this application.)
resources	[]	(MBean Names of all the defined resource references for this application.)

host=localhost,context=/usage

(Holds and manages the naming resources defined in the J2EE Enterprise Naming Context and their associated JNDI context)

container	StandardEngine[Catalina].StandardHost[localhost].StandardContext[/usage]	(The container with which the naming resources are associated.)
environments	[]	(MBean Names of the set of defined environment entries for this web application)
modelerType	org.apache.catalina.deploy.NamingResourcesImpl	(Type of the modeled resource. Can be set only once)
resourceLinks	[]	(MBean Names of all the defined resource link references for this application.)
resources	[]	(MBean Names of all the defined resource references for this application.)

ParallelWebappClassLoader

host=localhost,context=/

(ClassLoader implementation which is specialized for handling web applications and is capable of loading classes in parallel)

URLs	[]	(The URLs of this loader)
className	org.apache.catalina.loader.ParallelWebappClassLoader	(Fully qualified class name of the managed object)
contextName	ROOT	(Name of the webapp context)
delegate	false	(The 'follow standard delegation model' flag that will be used to configure our ClassLoader)
modelerType	org.apache.catalina.loader.ParallelWebappClassLoader	(Type of the modeled resource. Can be set only once)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

host=localhost,context=/demo

(ClassLoader implementation which is specialized for handling web applications and is capable of loading classes in parallel)

URLs	[war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/classes/, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdocreport.core-1.0.4.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/ehcache-core-2.6.8.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/log4j-1.2.17.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/spi4j-lib-security-server-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/slf4j-api-1.6.1.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/jta-1.1.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdocreport.template.freemarker-1.0.4.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/xpp3_min-1.1.4c.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/gwt-servlet-2.7.0.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/spi4j-gwt-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdocreport.document-1.0.4.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/text-2.1.7.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdocreport.template-1.0.4.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/freemarker-2.3.16.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdocreport.converter-1.0.4.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/validation-api-1.0.0.GA.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/appwhite1-commons-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdocreport.document.docx-1.0.4.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/spi4j-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/robin-1.5.9.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdocreport.document.odt-1.0.4.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/spi4j-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/javamelody-core-1.98.0.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/spi4j-doc-report-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdocreport.document.pptx-1.0.4.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/spi4j-lib-security-commons-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/appwhite1-server-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/referentiel-server-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/h2-1.4.200.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/xstream-1.4.11.1.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/referentiel-commons-1.7-SNAPSHOT.jar]	(The URLs of this loader)
className	org.apache.catalina.loader.ParallelWebappClassLoader	(Fully qualified class name of the managed object)
contextName	demo	(Name of the webapp context)
delegate	false	(The 'follow standard delegation model' flag that will be used to configure our ClassLoader)
modelerType	org.apache.catalina.loader.ParallelWebappClassLoader	(Type of the modeled resource. Can be set only once)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

host=localhost,context=/downloads

(ClassLoader implementation which is specialized for handling web applications and is capable of loading classes in parallel)

URLs	[]	(The URLs of this loader)
className	org.apache.catalina.loader.ParallelWebappClassLoader	(Fully qualified class name of the managed object)
contextName	downloads	(Name of the webapp context)
delegate	false	(The 'follow standard delegation model' flag that will be used to configure our ClassLoader)
modelerType	org.apache.catalina.loader.ParallelWebappClassLoader	(Type of the modeled resource. Can be set only once)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

host=localhost,context=/usage

(ClassLoader implementation which is specialized for handling web applications and is capable of loading classes in parallel)

URLs	[war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/classes/, war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/text-2.1.7.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/commons-csv-1.10.0.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/log4j-1.2.17.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/robin-1.5.9.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/geoip-api-1.3.1.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/gson-2.10.1.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/javamelody-core-1.98.0.jar]	(The URLs of this loader)
className	org.apache.catalina.loader.ParallelWebappClassLoader	(Fully qualified class name of the managed object)

contextName	usage	(Name of the webapp context)
delegate	false	(The 'follow standard delegation model' flag that will be used to configure our ClassLoader)
modelerType	org.apache.catalina.loader.ParallelWebappClassLoader	(Type of the modeled resource. Can be set only once)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

ProtocolHandler

port=80

acceptCount	100	(Inspected attribute acceptCount)
acceptorThreadCount	1	(Inspected attribute acceptorThreadCount)
acceptorThreadPriority	5	(Inspected attribute acceptorThreadPriority)
algorithm	SunX509	(Inspected attribute algorithm)
allowHostHeaderMismatch	false	(Inspected attribute allowHostHeaderMismatch)
allowedTrailerHeaders		(Inspected attribute allowedTrailerHeaders)
aprRequired	false	(Inspected attribute aprRequired)
ciphers	HIGH:!aNULL:!eNULL:!EXPORT:!DES:!RC4:!MD5:!kRSA	(Inspected attribute ciphers)
clientAuth	NONE	(Inspected attribute clientAuth)
clientCertProvider	null	(Inspected attribute clientCertProvider)
compressibleMimeType	text/html,text/xml,text/plain,text/css,text/javascript,application/javascript,application/json,application/xml	(Inspected attribute compressibleMimeType)
compressibleMimeTypes	[text/html, text/xml, text/plain, text/css, text/javascript, application/javascript, application/json, application/xml]	(Inspected attribute compressibleMimeTypes)
compression	off	(Inspected attribute compression)
compressionMinSize	2 048	(Inspected attribute compressionMinSize)
connectionCount	56	(Inspected attribute connectionCount)
connectionLinger	-1	(Inspected attribute connectionLinger)
connectionTimeout	20 000	(Inspected attribute connectionTimeout)
connectionUploadTimeout	300 000	(Inspected attribute connectionUploadTimeout)
crlFile	null	(Inspected attribute crlFile)
defaultSSLHostConfigName	_default_	(Inspected attribute defaultSSLHostConfigName)
disableUploadTimeout	true	(Inspected attribute disableUploadTimeout)
domain	Catalina	(Inspected attribute domain)
keepAliveTimeout	20 000	(Inspected attribute keepAliveTimeout)
keyAlias	null	(Inspected attribute keyAlias)
keyPass	null	(Inspected attribute keyPass)
keystoreFile	null	(Inspected attribute keystoreFile)
keystorePass	null	(Inspected attribute keystorePass)
keystoreProvider	null	(Inspected attribute keystoreProvider)
keystoreType	null	(Inspected attribute keystoreType)
localPort	80	(Inspected attribute localPort)
maxConnections	8 192	(Inspected attribute maxConnections)
maxExtensionSize	8 192	(Inspected attribute maxExtensionSize)
maxHeaderCount	100	(Inspected attribute maxHeaderCount)
maxHttpHeaderSize	8 192	(Inspected attribute maxHttpHeaderSize)
maxKeepAliveRequests	100	(Inspected attribute maxKeepAliveRequests)
maxSavePostSize	4 096	(Inspected attribute maxSavePostSize)
maxSwallowSize	2 097 152	(Inspected attribute maxSwallowSize)
maxThreads	200	(Inspected attribute maxThreads)
maxTrailerSize	8 192	(Inspected attribute maxTrailerSize)
minSpareThreads	10	(Inspected attribute minSpareThreads)
modelerType	org.apache.coyote.http11.Http11NioProtocol	(Type of the modeled resource. Can be set only once)
name	"http-nio-80"	(Inspected attribute name)
nameIndex	1	(Inspected attribute nameIndex)
noCompressionStrongETag	true	(Inspected attribute noCompressionStrongETag)
noCompressionUserAgents	null	(Inspected attribute noCompressionUserAgents)
objectName	Catalina:type=ProtocolHandler,port=80	(Inspected attribute objectName)
paused	false	(Inspected attribute paused)
pollerThreadCount	1	(Inspected attribute pollerThreadCount)
pollerThreadPriority	5	(Inspected attribute pollerThreadPriority)
port	80	(Inspected attribute port)
portOffset	0	(Inspected attribute portOffset)
portWithOffset	80	(Inspected attribute portWithOffset)
processorCache	200	(Inspected attribute processorCache)
rejectIllegalHeader	true	(Inspected attribute rejectIllegalHeader)
rejectIllegalHeaderName	true	(Inspected attribute rejectIllegalHeaderName)
relaxedPathChars	null	(Inspected attribute relaxedPathChars)
relaxedQueryChars	null	(Inspected attribute relaxedQueryChars)
restrictedUserAgents	null	(Inspected attribute restrictedUserAgents)
sSLCACertificateFile	null	(Inspected attribute sSLCACertificateFile)
sSLCACertificatePath	null	(Inspected attribute sSLCACertificatePath)
sSLCARevocationFile	null	(Inspected attribute sSLCARevocationFile)
sSLCARevocationPath	null	(Inspected attribute sSLCARevocationPath)
sSLCertificateChainFile	null	(Inspected attribute sSLCertificateChainFile)
sSLCertificateFile	null	(Inspected attribute sSLCertificateFile)
sSLCertificateKeyFile	null	(Inspected attribute sSLCertificateKeyFile)
sSLCipherSuite	HIGH:!aNULL:!eNULL:!EXPORT:!DES:!RC4:!MD5:!kRSA	(Inspected attribute sSLCipherSuite)
sSLDisableCompression	true	(Inspected attribute sSLDisableCompression)

sSLDisableSessionTickets	false	(Inspected attribute sSLDisableSessionTickets)
sSLEnabled	false	(Inspected attribute sSLEnabled)
sSLHonorCipherOrder	false	(Inspected attribute sSLHonorCipherOrder)
sSLPassword	null	(Inspected attribute sSLPassword)
sSLProtocol		(Inspected attribute sSLProtocol)
sSLVerifyClient	NONE	(Inspected attribute sSLVerifyClient)
sSLVerifyDepth	10	(Inspected attribute sSLVerifyDepth)
secure	false	(Inspected attribute secure)
selectorTimeout	1 000	(Inspected attribute selectorTimeout)
sendfileSupported	true	(Inspected attribute sendfileSupported)
server	null	(Inspected attribute server)
serverRemoveAppProvidedValues	false	(Inspected attribute serverRemoveAppProvidedValues)
sessionCacheSize	-1	(Inspected attribute sessionCacheSize)
sessionTimeout	86 400	(Inspected attribute sessionTimeout)
sniParseLimit	65 536	(Inspected attribute sniParseLimit)
sslEnabledProtocols		(Inspected attribute sslEnabledProtocols)
sslImplementationName	null	(Inspected attribute sslImplementationName)
sslProtocol	TLS	(Inspected attribute sslProtocol)
tcpNoDelay	true	(Inspected attribute tcpNoDelay)
threadPriority	5	(Inspected attribute threadPriority)
trustManagerClassName	null	(Inspected attribute trustManagerClassName)
trustMaxCertLength	10	(Inspected attribute trustMaxCertLength)
truststoreAlgorithm	PKIX	(Inspected attribute truststoreAlgorithm)
truststoreFile	null	(Inspected attribute truststoreFile)
truststorePass	null	(Inspected attribute truststorePass)
truststoreProvider	null	(Inspected attribute truststoreProvider)
truststoreType	JKS	(Inspected attribute truststoreType)
useKeepAliveResponseHeader	true	(Inspected attribute useKeepAliveResponseHeader)
useSendfile	true	(Inspected attribute useSendfile)
useServerCipherSuitesOrder	false	(Inspected attribute useServerCipherSuitesOrder)

Realm

realmPath=/realm0

(Realm implementation that can be used to wrap existing realms to provide a user lock-out capability)

allRolesMode	strict	(The all roles mode.)
cacheRemovalWarningTime	3 600	(If a failed user is removed from the cache because the cache is too big before it has been in the cache for at least this period of time (in seconds) a warning message will be logged. Defaults to 3600 (1 hour).)
cacheSize	1 000	(Number of users that have failed authentication to keep in cache. Over time the cache will grow to this size and may not shrink. Defaults to 1000.)
className	org.apache.catalina.realm.LockOutRealm	(Fully qualified class name of the managed object)
failureCount	5	(The number of times in a row a user has to fail authentication to be locked out. Defaults to 5.)
lockOutTime	300	(The time (in seconds) a user is locked out for after too many authentication failures. Defaults to 300 (5 minutes).)
modelerType	org.apache.catalina.realm.LockOutRealm	(Type of the modeled resource. Can be set only once)
realmPath	/realm0	(The realm path)
realms	[Catalina:type=Realm,realmPath=/realm0/realm0]	(The set of realms that the lockout realm is wrapping)
validate	true	(The 'validate certificate chains' flag.)

realmPath=/realm0/realm0

(Realm connected to a UserDatabase as a global JNDI resource)

allRolesMode	strict	(The all roles mode.)
className	org.apache.catalina.realm.UserDatabaseRealm	(Fully qualified class name of the managed object)
modelerType	org.apache.catalina.realm.UserDatabaseRealm	(Type of the modeled resource. Can be set only once)
realmPath	/realm0/realm0	(The realm path)
resourceName	UserDatabase	(The global JNDI name of the UserDatabase resource to use)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
validate	true	(The 'validate certificate chains' flag.)

RequestProcessor

worker="http-nio-80",name=HttpRequest1

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	879	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	879	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	879	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)

requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest1	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest10		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	875	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	875	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	875	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest10	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest100		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	828	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	828	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	828	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest100	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest101		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	831	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	831	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	831	(Inspected attribute processingTime)

protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest101	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest102

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	60	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	830	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	830	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	830	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest102	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest103

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	60	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	827	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	827	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	827	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest103	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest104

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	60	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	830	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)

maxTime	830	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	830	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest104	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest105

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	829	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	829	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	829	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest105	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest106

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	623	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	623	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	623	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest106	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest107

bytesReceived	6 140	(Inspected attribute bytesReceived)
bytesSent	82 338 397	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	class=net.sf.ehcache.config.Configuration&part=source	(Inspected attribute currentQueryString)
currentUri	/demo/monitoring	(Inspected attribute currentUri)

errorCount	1 446	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	0	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/	(Inspected attribute maxRequestUri)
maxTime	20 008	(Inspected attribute maxTime)
method	GET	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	903 086	(Inspected attribute processingTime)
protocol	HTTP/1.1	(Inspected attribute protocol)
remoteAddr	3.17.175.167	(Inspected attribute remoteAddr)
remoteAddrForwarded	3.17.175.167	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1 012 138	(Inspected attribute requestCount)
requestProcessingTime	1 581	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest107	(Inspected attribute rpName)
serverPort	80	(Inspected attribute serverPort)
stage	3	(Inspected attribute stage)
virtualHost	javamelody.org	(Inspected attribute virtualHost)
workerThreadName	http-nio-80-exec-45	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest108

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	530	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	530	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	530	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest108	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest109

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	487	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	487	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	487	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest109	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest11

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	1	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	874	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	874	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	874	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest11	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest110

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	406	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	406	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	406	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest110	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest111

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	383	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	383	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	383	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest111	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)

stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest112		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	60	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	317	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	317	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	317	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest112	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest113		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	60	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	303	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	303	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	303	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest113	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest114		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	60	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	268	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	268	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	268	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)

requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest114	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest115

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	244	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	244	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	244	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest115	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest116

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	221	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	221	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	221	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest116	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest117

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	206	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	206	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	206	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)

remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest117	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest118

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	11 873	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	95	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/demo/monitoring	(Inspected attribute maxRequestUri)
maxTime	234	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	416	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	8	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest118	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest119

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	80	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	80	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	80	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest119	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest12

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	874	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	874	(Inspected attribute maxTime)

method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	874	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest12	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest120

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	49	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	49	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	49	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest120	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest121

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	14	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	14	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	14	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest121	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest13

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)

globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	874	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	874	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	874	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest13	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest14

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	873	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	873	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	873	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest14	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest15

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	874	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	874	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	874	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest15	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest16

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	873	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	873	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	873	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest16	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest17

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	873	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	873	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	873	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest17	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest18

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	872	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	872	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	872	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest18	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)

virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest19		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	872	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	872	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	872	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest19	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest2		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	873	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	873	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	873	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest2	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest20		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	706	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	706	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	706	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)

requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest20	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest21		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	871	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	871	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	871	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest21	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest22		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	871	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	871	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	871	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest22	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest23		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	872	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	872	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	872	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)

remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest23	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest24		
bytesReceived	3 034	(Inspected attribute bytesReceived)
bytesSent	134 369 103	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	2 164	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	396	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/demo/monitoring	(Inspected attribute maxRequestUri)
maxTime	20 191	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 657 084	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1 455 567	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest24	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest25		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	871	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	871	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	871	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest25	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest26		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	870	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	870	(Inspected attribute maxTime)
method	null	(Inspected attribute method)

modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	870	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest26	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest27		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	870	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	870	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	870	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest27	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest28		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	861	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	861	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	861	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest28	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest29		
bytesReceived	6 544	(Inspected attribute bytesReceived)
bytesSent	211 471 544	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	4 079	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)

lastRequestProcessingTime	0	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/demo/monitoring	(Inspected attribute maxRequestUri)
maxTime	20 309	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	2 242 059	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1 817 941	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest29	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest3

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	873	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	873	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	873	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest3	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest30

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	869	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	869	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	869	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest30	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest31

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	869	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	869	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	869	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest31	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest32

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	868	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	868	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	868	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest32	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest33

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	868	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	868	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	868	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest33	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)

virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest34		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	857	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	857	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	857	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest34	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest35		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	867	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	867	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	867	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest35	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest36		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	1	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	867	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	867	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	867	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)

requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest36	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest37

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	867	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	867	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	867	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest37	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest38

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	857	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	857	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	857	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest38	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest39

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	866	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	866	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	866	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)

remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest39	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest4		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	871	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	871	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	871	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest4	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest40		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	856	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	856	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	856	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest40	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest41		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	1	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	856	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	856	(Inspected attribute maxTime)
method	null	(Inspected attribute method)

modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	856	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest41	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest42		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	852	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	852	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	852	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest42	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest43		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	864	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	864	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	864	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest43	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest44		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	1	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)

lastRequestProcessingTime	863	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	863	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	863	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest44	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest45

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	854	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	854	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	854	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest45	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest46

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	863	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	863	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	863	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest46	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest47

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	1	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	862	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	862	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	862	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest47	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest48

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	1	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	862	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	862	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	862	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest48	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest49

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	862	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	862	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	862	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest49	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)

virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest5		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	877	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	877	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	877	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest5	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest50		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	862	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	862	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	862	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest50	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest51		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	1	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	861	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	861	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	861	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)

requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest51	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest52

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	856	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	856	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	856	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest52	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest53

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	856	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	856	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	856	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest53	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest54

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	855	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	855	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	855	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)

remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest54	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest55		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	855	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	855	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	855	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest55	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest56		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	853	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	853	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	853	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest56	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest57		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	1	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	853	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	853	(Inspected attribute maxTime)
method	null	(Inspected attribute method)

modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	853	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest57	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest58

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	852	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	852	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	852	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest58	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest59

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	1	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	852	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	852	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	852	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest59	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest6

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)

lastRequestProcessingTime	871	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	871	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	871	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest6	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest60

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	1	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	858	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	858	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	858	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest60	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest61

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	857	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	857	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	857	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest61	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest62

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	857	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	857	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	857	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest62	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest63

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	856	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	856	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	856	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest63	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest64

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	1	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	856	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	856	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	856	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest64	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)

virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest65		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	855	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	855	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	855	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest65	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest66		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	856	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	856	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	856	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest66	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest67		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	1	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	855	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	855	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	855	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)

requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest67	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest68		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	848	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	848	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	848	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest68	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest69		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	848	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	848	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	848	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest69	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest7		
bytesReceived	6 587	(Inspected attribute bytesReceived)
bytesSent	116 381 693	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	class=java.util.Collections%24EmptySet&part=source	(Inspected attribute currentQueryString)
currentUri	/demo/monitoring	(Inspected attribute currentUri)
errorCount	5 109	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	1 366	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/demo/appli1/PersonneService	(Inspected attribute maxRequestUri)
maxTime	17 949	(Inspected attribute maxTime)
method	GET	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 398 849	(Inspected attribute processingTime)
protocol	HTTP/1.1	(Inspected attribute protocol)
remoteAddr	3.17.175.167	(Inspected attribute remoteAddr)

remoteAddrForwarded	3.17.175.167	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1 167 829	(Inspected attribute requestCount)
requestProcessingTime	1 849	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest7	(Inspected attribute rpName)
serverPort	80	(Inspected attribute serverPort)
stage	3	(Inspected attribute stage)
virtualHost	javamelody.org	(Inspected attribute virtualHost)
workerThreadName	http-nio-80-exec-17	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest70		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	1	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	847	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	847	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	847	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest70	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest71		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	844	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	844	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	844	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest71	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest72		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	846	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	846	(Inspected attribute maxTime)
method	null	(Inspected attribute method)

modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	846	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest72	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest73		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	1	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	846	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	846	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	846	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest73	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest74		
bytesReceived	397	(Inspected attribute bytesReceived)
bytesSent	15 728 891	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	class=net.sf.ehcache.CacheManager%241&part=source	(Inspected attribute currentQueryString)
currentUri	/demo/monitoring	(Inspected attribute currentUri)
errorCount	302	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	0	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/	(Inspected attribute maxRequestUri)
maxTime	20 003	(Inspected attribute maxTime)
method	GET	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	247 882	(Inspected attribute processingTime)
protocol	HTTP/1.1	(Inspected attribute protocol)
remoteAddr	3.17.175.167	(Inspected attribute remoteAddr)
remoteAddrForwarded	3.17.175.167	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	123 926	(Inspected attribute requestCount)
requestProcessingTime	1 913	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest74	(Inspected attribute rpName)
serverPort	80	(Inspected attribute serverPort)
stage	3	(Inspected attribute stage)
virtualHost	javamelody.org	(Inspected attribute virtualHost)
workerThreadName	http-nio-80-exec-117	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest75		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	1	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)

lastRequestProcessingTime	845	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	845	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	845	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest75	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest76

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	841	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	841	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	841	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest76	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest77

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	4 898 208	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	1 162	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	31	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	6 292	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	73 310	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	53 592	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest77	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest78

bytesReceived	1 706	(Inspected attribute bytesReceived)
bytesSent	42 477 678	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	1 856	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	788	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/demo/monitoring	(Inspected attribute maxRequestUri)
maxTime	20 192	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	528 387	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	422 189	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest78	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest79

bytesReceived	2 798	(Inspected attribute bytesReceived)
bytesSent	9 233 451	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	format=pdf&part=mbeans	(Inspected attribute currentQueryString)
currentUri	/demo/monitoring	(Inspected attribute currentUri)
errorCount	59	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	559	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/demo/monitoring	(Inspected attribute maxRequestUri)
maxTime	9 596	(Inspected attribute maxTime)
method	GET	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	104 213	(Inspected attribute processingTime)
protocol	HTTP/1.1	(Inspected attribute protocol)
remoteAddr	3.133.147.193	(Inspected attribute remoteAddr)
remoteAddrForwarded	3.133.147.193	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	75 998	(Inspected attribute requestCount)
requestProcessingTime	636	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest79	(Inspected attribute rpName)
serverPort	80	(Inspected attribute serverPort)
stage	3	(Inspected attribute stage)
virtualHost	javamelody.org	(Inspected attribute virtualHost)
workerThreadName	http-nio-80-exec-87	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest8

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	875	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	875	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	875	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest8	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)

virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest80		
bytesReceived	454	(Introspected attribute bytesReceived)
bytesSent	45 482 922	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	class=java.lang.management.DefaultPlatformMBeanProvider%245&parl=source	(Introspected attribute currentQueryString)
currentUri	/demo/monitoring	(Introspected attribute currentUri)
errorCount	574	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	2	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/demo/monitoring	(Introspected attribute maxRequestUri)
maxTime	20 189	(Introspected attribute maxTime)
method	GET	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	649 598	(Introspected attribute processingTime)
protocol	HTTP/1.1	(Introspected attribute protocol)
remoteAddr	3.17.175.167	(Introspected attribute remoteAddr)
remoteAddrForwarded	3.17.175.167	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	345 914	(Introspected attribute requestCount)
requestProcessingTime	1 098	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest80	(Introspected attribute rpName)
serverPort	80	(Introspected attribute serverPort)
stage	3	(Introspected attribute stage)
virtualHost	javamelody.org	(Introspected attribute virtualHost)
workerThreadName	http-nio-80-exec-124	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest81		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	12 814	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	88	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	849	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 154	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	4	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest81	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest82		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	24 333	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	20	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	802	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 399	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	95	(Introspected attribute requestCount)

requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest82	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest83		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	840	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	840	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	840	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest83	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest84		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	840	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	840	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	840	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest84	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest85		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	839	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	839	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	839	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)

remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest85	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest86		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	1	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	839	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	839	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	839	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest86	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest87		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	838	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	838	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	838	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest87	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest88		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	838	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	838	(Inspected attribute maxTime)
method	null	(Inspected attribute method)

modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	838	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest88	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest89		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	837	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	837	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	837	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest89	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest9		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	1	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	875	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	875	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	875	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest9	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest90		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	1	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)

lastRequestProcessingTime	834	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	834	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	834	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest90	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest91

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	10 456	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	1	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	92	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	845	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 163	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	3	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest91	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest92

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	833	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	833	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	833	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest92	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest93

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	833	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	833	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	833	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest93	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest94

bytesReceived	162	(Inspected attribute bytesReceived)
bytesSent	13 069 207	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	147	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	810	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/demo/monitoring	(Inspected attribute maxRequestUri)
maxTime	18 240	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	162 101	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	88 615	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest94	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest95

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	834	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	834	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	834	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest95	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)

virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest96		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	817	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	817	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	817	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest96	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest97		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	0	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	833	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	833	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	833	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest97	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest98		
bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	1	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	832	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	832	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	832	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)

requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest98	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest99

bytesReceived	0	(Inspected attribute bytesReceived)
bytesSent	60	(Inspected attribute bytesSent)
contentLength	-1	(Inspected attribute contentLength)
currentQueryString	null	(Inspected attribute currentQueryString)
currentUri	null	(Inspected attribute currentUri)
errorCount	1	(Inspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Inspected attribute globalProcessor)
lastRequestProcessingTime	832	(Inspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Inspected attribute maxRequestUri)
maxTime	832	(Inspected attribute maxTime)
method	null	(Inspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	832	(Inspected attribute processingTime)
protocol	null	(Inspected attribute protocol)
remoteAddr	null	(Inspected attribute remoteAddr)
remoteAddrForwarded	null	(Inspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Inspected attribute requestBytesReceived)
requestBytesSent	0	(Inspected attribute requestBytesSent)
requestCount	1	(Inspected attribute requestCount)
requestProcessingTime	0	(Inspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest99	(Inspected attribute rpName)
serverPort	-1	(Inspected attribute serverPort)
stage	7	(Inspected attribute stage)
virtualHost	null	(Inspected attribute virtualHost)
workerThreadName	null	(Inspected attribute workerThreadName)

Resource**resourcetype=Context,host=localhost,context=/demo,class=javax.sql.DataSource,name="jdbc/demo_javamelody"**

(Representation of a resource reference for a web application)

auth	Container	(The authorization requirement for this resource)
description	Datasource	(The description of this resource)
name	jdbc/demo_javamelody	(The name of this resource)
scope	Shareable	(The sharing scope of this resource factory)
type	javax.sql.DataSource	(The type of this environment entry)

resourcetype=Global,class=org.apache.catalina.UserDatabase,name="UserDatabase"

(Representation of a resource reference for a web application)

auth	Container	(The authorization requirement for this resource)
description	User database that can be updated and saved	(The description of this resource)
name	UserDatabase	(The name of this resource)
scope	Shareable	(The sharing scope of this resource factory)
type	org.apache.catalina.UserDatabase	(The type of this environment entry)

SSLHostConfig**ThreadPool="http-nio-80",name="_default_"**

caCertificateFile	null	(Inspected attribute caCertificateFile)
caCertificatePath	null	(Inspected attribute caCertificatePath)
certificateChainFile	null	(Inspected attribute certificateChainFile)
certificateFile	null	(Inspected attribute certificateFile)
certificateKeyAlias	null	(Inspected attribute certificateKeyAlias)
certificateKeyFile	null	(Inspected attribute certificateKeyFile)
certificateKeyPassword	null	(Inspected attribute certificateKeyPassword)
certificateKeystoreFile	null	(Inspected attribute certificateKeystoreFile)
certificateKeystorePassword	null	(Inspected attribute certificateKeystorePassword)
certificateKeystoreProvider	null	(Inspected attribute certificateKeystoreProvider)
certificateKeystoreType	null	(Inspected attribute certificateKeystoreType)
certificateRevocationListFile	null	(Inspected attribute certificateRevocationListFile)
certificateRevocationListPath	null	(Inspected attribute certificateRevocationListPath)
certificateVerificationAsString	NONE	(Inspected attribute certificateVerificationAsString)
certificateVerificationDepth	10	(Inspected attribute certificateVerificationDepth)
certificateVerificationDepthConfigured	false	(Inspected attribute certificateVerificationDepthConfigured)
ciphers	HIGH:!aNULL:!eNULL:!EXPORT:!DES:!RC4:!MD5:!kRSA	(Inspected attribute ciphers)
disableCompression	true	(Inspected attribute disableCompression)
disableSessionTickets	false	(Inspected attribute disableSessionTickets)
enabledCiphers	null	(Inspected attribute enabledCiphers)
enabledProtocols	null	(Inspected attribute enabledProtocols)
honorCipherOrder	false	(Inspected attribute honorCipherOrder)
hostName	_default_	(Inspected attribute hostName)

insecureRenegotiation	false	(Inspected attribute insecureRenegotiation)
keyManagerAlgorithm	SunX509	(Inspected attribute keyManagerAlgorithm)
modelerType	org.apache.tomcat.util.net.SSLHostConfig	(Type of the modeled resource. Can be set only once)
objectName	Catalina:type=SSLHostConfig,ThreadPool="http-nio-80",name=_default_	(Inspected attribute objectName)
openSslConf	null	(Inspected attribute openSslConf)
openSslConfContext	0	(Inspected attribute openSslConfContext)
openSslContext	0	(Inspected attribute openSslContext)
revocationEnabled	false	(Inspected attribute revocationEnabled)
sessionCacheSize	-1	(Inspected attribute sessionCacheSize)
sessionTimeout	86 400	(Inspected attribute sessionTimeout)
sslProtocol	TLS	(Inspected attribute sslProtocol)
trustManagerClassName	null	(Inspected attribute trustManagerClassName)
truststoreAlgorithm	PKIX	(Inspected attribute truststoreAlgorithm)
truststoreFile	null	(Inspected attribute truststoreFile)
truststorePassword	null	(Inspected attribute truststorePassword)
truststoreProvider	null	(Inspected attribute truststoreProvider)
truststoreType	JKS	(Inspected attribute truststoreType)

Server

(Standard Server Component)

address	localhost	(The address on which we wait for shutdown commands.)
managedResource	StandardServer[8005]	(The managed resource this MBean is associated with)
modelerType	org.apache.catalina.core.StandardServer	(Type of the modeled resource. Can be set only once)
port	8 005	(TCP port (excluding any offset) for shutdown messages)
portOffset	0	(The offset applied to port and to the port attributes of any nested connectors)
portWithOffset	8 005	(Actual TCP port (including any offset) for shutdown messages)
serverBuilt	Mar 11 2020 09:31:38 UTC	(Tomcat server built timestamp)
serverInfo	Apache Tomcat/9.0.33	(Tomcat server release identifier)
serverNumber	9.0.33.0	(Tomcat server's version number)
serviceNames	[Catalina:type=Service]	(Object names of all services we know about)
shutdown	SHUTDOWN	(Shutdown password)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

Service

(Standard Service Component)

connectorNames	[Catalina:type=Connector,port=80]	(ObjectNames of the connectors)
managedResource	StandardService[Catalina]	(The managed resource this MBean is associated with)
modelerType	org.apache.catalina.core.StandardService	(Type of the modeled resource. Can be set only once)
name	Catalina	(Unique name of this Service)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

Servlet

WebModule=//localhost/,name=default,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	1	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	9 017	(Error count)
loadOnStartup	1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	1	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	38	(Maximum processing time of a request)
minTime	0	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=//localhost/,name=default,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	1 819	(Total execution time of the servlet's service method)
requestCount	9 017	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	org.apache.catalina.servlets.DefaultServlet	(The run-as identity for this servlet.)
singleThreadModel	false	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=//localhost/,name=jsp,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)

errorCount	331	(Error count)
loadOnStartup	3	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	0	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	329	(Maximum processing time of a request)
minTime	0	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=localhost,name=jsp,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	4 317	(Total execution time of the servlet's service method)
requestCount	4 262	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	org.apache.jasper.servlet.JspServlet	(The run-as identity for this servlet.)
singleThreadModel	false	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=localhost/demo,name=AdresseService,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	-1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	0	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	0	(Maximum processing time of a request)
minTime	9 223 372 036 854 775 807	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=localhost/demo,name=AdresseService,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	0	(Total execution time of the servlet's service method)
requestCount	0	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	fr.appwhite1.server.business.annuaire.AdresseGwtServiceImpl	(The run-as identity for this servlet.)
singleThreadModel	null	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=localhost/demo,name=AuthenticationService,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	1 019	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	1	(Error count)
loadOnStartup	-1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	1 019	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	11 815	(Maximum processing time of a request)
minTime	1	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=localhost/demo,name=AuthenticationService,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	23 415	(Total execution time of the servlet's service method)
requestCount	77	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	fr.appwhite1.server.business.secu.AuthenticationGwtServiceImpl	(The run-as identity for this servlet.)
singleThreadModel	false	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=localhost/demo,name=BuildInfoServlet,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	2	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)

loadOnStartup	1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	2	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	0	(Maximum processing time of a request)
minTime	9 223 372 036 854 775 807	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=/localhost/demo,name=BuildInfoServlet,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	0	(Total execution time of the servlet's service method)
requestCount	0	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	fr.appwhite1.Appl1BuildInfoServlet	(The run-as identity for this servlet.)
singleThreadModel	false	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=/localhost/demo,name=CompetenceService,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	-1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	0	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	0	(Maximum processing time of a request)
minTime	9 223 372 036 854 775 807	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=/localhost/demo,name=CompetenceService,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	0	(Total execution time of the servlet's service method)
requestCount	0	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	fr.appwhite1.server.business.annuaire.CompetenceGwtServiceImpl	(The run-as identity for this servlet.)
singleThreadModel	null	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=/localhost/demo,name=GradeService,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	1	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	-1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	1	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	5 864	(Maximum processing time of a request)
minTime	1	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=/localhost/demo,name=GradeService,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	5 976	(Total execution time of the servlet's service method)
requestCount	29	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	fr.referentiel.server.business.ref.GradeGwtServiceImpl	(The run-as identity for this servlet.)
singleThreadModel	false	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=/localhost/demo,name=MailService,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	-1	(The load-on-startup order value (negative value means load on first call) for this servlet.)

loadTime	0	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	0	(Maximum processing time of a request)
minTime	9 223 372 036 854 775 807	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=/localhost/demo,name=MailService,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	0	(Total execution time of the servlet's service method)
requestCount	0	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	fr.appwhite1.server.business.annuaire.MailGwtServiceImpl	(The run-as identity for this servlet.)
singleThreadModel	null	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=/localhost/demo,name=PermissionService,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	-1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	0	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	0	(Maximum processing time of a request)
minTime	9 223 372 036 854 775 807	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=/localhost/demo,name=PermissionService,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	0	(Total execution time of the servlet's service method)
requestCount	0	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	fr.appwhite1.server.business.secu.PermissionGwtServiceImpl	(The run-as identity for this servlet.)
singleThreadModel	null	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=/localhost/demo,name=PersonneService,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	1	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	-1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	1	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	17 949	(Maximum processing time of a request)
minTime	5	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=/localhost/demo,name=PersonneService,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	20 258	(Total execution time of the servlet's service method)
requestCount	49	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	fr.appwhite1.server.business.annuaire.PersonneGwtServiceImpl	(The run-as identity for this servlet.)
singleThreadModel	false	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=/localhost/demo,name=PrintUtilsService,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	-1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	0	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)

maxTime	0	(Maximum processing time of a request)
minTime	9 223 372 036 854 775 807	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=/localhost/demo,name=PrintUtilsService,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	0	(Total execution time of the servlet's service method)
requestCount	0	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	fr.appwhite1.server.business.utils.PrintUtilsGwtServiceImpl	(The run-as identity for this servlet.)
singleThreadModel	null	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=/localhost/demo,name=RoleService,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	-1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	0	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	0	(Maximum processing time of a request)
minTime	9 223 372 036 854 775 807	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=/localhost/demo,name=RoleService,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	0	(Total execution time of the servlet's service method)
requestCount	0	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	fr.appwhite1.server.business.secu.RoleGwtServiceImpl	(The run-as identity for this servlet.)
singleThreadModel	null	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=/localhost/demo,name=TelephoneService,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	-1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	0	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	0	(Maximum processing time of a request)
minTime	9 223 372 036 854 775 807	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=/localhost/demo,name=TelephoneService,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	0	(Total execution time of the servlet's service method)
requestCount	0	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	fr.appwhite1.server.business.annuaire.TelephoneGwtServiceImpl	(The run-as identity for this servlet.)
singleThreadModel	null	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=/localhost/demo,name=UtilisateurService,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	-1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	0	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	0	(Maximum processing time of a request)
minTime	9 223 372 036 854 775 807	(Minimum processing time of a request)

modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet.WebModule=/localhost/demo,name=UtilisateurService,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	0	(Total execution time of the servlet's service method)
requestCount	0	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	fr.appwhite1.server.business.secu.UtilisateurGwtServiceImpl	(The run-as identity for this servlet.)
singleThreadModel	null	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=/localhost/demo,name=default,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	1	(Time taken to load the Servlet class)
countAllocated	5	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	4 593	(Error count)
loadOnStartup	1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	1	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	20 309	(Maximum processing time of a request)
minTime	0	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet.WebModule=/localhost/demo,name=default,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	2 615 390	(Total execution time of the servlet's service method)
requestCount	19 905	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	org.apache.catalina.servlets.DefaultServlet	(The run-as identity for this servlet.)
singleThreadModel	false	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=/localhost/demo,name=jsp,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	1	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	3	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	52	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	0	(Maximum processing time of a request)
minTime	9 223 372 036 854 775 807	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet.WebModule=/localhost/demo,name=jsp,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	0	(Total execution time of the servlet's service method)
requestCount	0	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	org.apache.jasper.servlet.JspServlet	(The run-as identity for this servlet.)
singleThreadModel	false	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=/localhost/downloads,name=default,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	10	(Error count)
loadOnStartup	1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	0	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	1	(Maximum processing time of a request)
minTime	0	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)

objectName	Catalina:j2eeType=Servlet,WebModule=/localhost/downloads,name=default,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	2	(Total execution time of the servlet's service method)
requestCount	10	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	org.apache.catalina.servlets.DefaultServlet	(The run-as identity for this servlet.)
singleThreadModel	false	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=/localhost/downloads,name=jsp,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	1	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	3	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	2	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	0	(Maximum processing time of a request)
minTime	9 223 372 036 854 775 807	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=/localhost/downloads,name=jsp,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	0	(Total execution time of the servlet's service method)
requestCount	0	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	org.apache.jasper.servlet.JspServlet	(The run-as identity for this servlet.)
singleThreadModel	false	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=/localhost/usage,name=admin,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	1	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	3	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	0	(Maximum processing time of a request)
minTime	9 223 372 036 854 775 807	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=/localhost/usage,name=admin,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	0	(Total execution time of the servlet's service method)
requestCount	0	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	net.bull.javamelody.usagestats.AdminServlet	(The run-as identity for this servlet.)
singleThreadModel	false	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=/localhost/usage,name=default,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	10	(Error count)
loadOnStartup	1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	0	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	28	(Maximum processing time of a request)
minTime	0	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=/localhost/usage,name=default,J2EEApplication=none,J2EEServer=none	(Name of the object)

processingTime	53	(Total execution time of the servlet's service method)
requestCount	24	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	org.apache.catalina.servlets.DefaultServlet	(The run-as identity for this servlet.)
singleThreadModel	false	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=//localhost/usage,name=jsp,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	3	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	0	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	0	(Maximum processing time of a request)
minTime	9 223 372 036 854 775 807	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=//localhost/usage,name=jsp,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	0	(Total execution time of the servlet's service method)
requestCount	0	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	org.apache.jasper.servlet.JspServlet	(The run-as identity for this servlet.)
singleThreadModel	false	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=//localhost/usage,name=usagstats,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	30	(Error count)
loadOnStartup	1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	405 330	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	764	(Maximum processing time of a request)
minTime	0	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=//localhost/usage,name=usagstats,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	1 584 373	(Total execution time of the servlet's service method)
requestCount	6 527 712	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	net.bull.javamelody.usagstats.UsageStatsServlet	(The run-as identity for this servlet.)
singleThreadModel	false	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

StringCache

accessCount	26 227 741	(Inspected attribute accessCount)
byteEnabled	true	(Inspected attribute byteEnabled)
cacheSize	200	(Inspected attribute cacheSize)
charEnabled	false	(Inspected attribute charEnabled)
hitCount	19 639 281	(Inspected attribute hitCount)
modelerType	org.apache.tomcat.util.buf.StringCache	(Type of the modeled resource. Can be set only once)
trainThreshold	20 000	(Inspected attribute trainThreshold)

ThreadPool

name="http-nio-80"

acceptCount	100
acceptorThreadCount	1
acceptorThreadPriority	5
alpnSupported	false
bindOnInit	true
connectionCount	54
connectionLinger	-1
connectionTimeout	20 000
currentThreadCount	46

currentThreadsBusy	5
daemon	true
defaultSSLHostConfigName	__default__
deferAccept	false
domain	Catalina
executorTerminationTimeoutMillis	5 000
keepAliveCount	1
keepAliveTimeout	20 000
localPort	80
maxConnections	8 192
maxKeepAliveRequests	100
maxThreads	200
minSpareThreads	10
modelerType	org.apache.tomcat.util.net.NioEndpoint
name	http-nio-80
paused	false
pollerThreadCount	1
pollerThreadPriority	5
port	80
portOffset	0
portWithOffset	80
running	true
sSLEnabled	false
selectorTimeout	1 000
sniParseLimit	65 536
sslImplementation	null
sslImplementationName	null
tcpNoDelay	true
threadPriority	5
useInheritedChannel	false
useSendfile	true

name="http-nio-80",subType=SocketProperties

appReadBufSize	8 192	(Inspected attribute appReadBufSize)
appWriteBufSize	8 192	(Inspected attribute appWriteBufSize)
bufferPool	500	(Inspected attribute bufferPool)
bufferPoolSize	104 857 600	(Inspected attribute bufferPoolSize)
directBuffer	false	(Inspected attribute directBuffer)
directBufferPool	500	(Inspected attribute directBufferPool)
directSslBuffer	false	(Inspected attribute directSslBuffer)
eventCache	500	(Inspected attribute eventCache)
modelerType	org.apache.tomcat.util.net.SocketProperties	(Type of the modeled resource. Can be set only once)
processorCache	500	(Inspected attribute processorCache)
soLingerOn	false	(Inspected attribute soLingerOn)
soLingerTime	-1	(Inspected attribute soLingerTime)
soTimeout	20 000	(Inspected attribute soTimeout)
tcpNoDelay	true	(Inspected attribute tcpNoDelay)
timeoutInterval	1 000	(Inspected attribute timeoutInterval)
unlockTimeout	250	(Inspected attribute unlockTimeout)

UtilityExecutor

activeCount	0	(Inspected attribute activeCount)
completedTaskCount	1 420 587	(Inspected attribute completedTaskCount)
continueExistingPeriodicTasksAfterShutdownPolicy	false	(Inspected attribute continueExistingPeriodicTasksAfterShutdownPolicy)
corePoolSize	2	(Inspected attribute corePoolSize)
executeExistingDelayedTasksAfterShutdownPolicy	false	(Inspected attribute executeExistingDelayedTasksAfterShutdownPolicy)
largestPoolSize	2	(Inspected attribute largestPoolSize)
maximumPoolSize	2 147 483 647	(Inspected attribute maximumPoolSize)
modelerType	java.util.concurrent.ScheduledThreadPoolExecutor	(Type of the modeled resource. Can be set only once)
poolSize	2	(Inspected attribute poolSize)
removeOnCancelPolicy	true	(Inspected attribute removeOnCancelPolicy)
shutdown	false	(Inspected attribute shutdown)
taskCount	1 420 593	(Inspected attribute taskCount)
terminated	false	(Inspected attribute terminated)
terminating	false	(Inspected attribute terminating)

Valve

host=localhost,context=/,name=NonLoginAuthenticator

(An Authenticator and Valve implementation that checks only security constraints not involving user authentication)

cache	true	(Should we cache authenticated Principals if the request is part of an HTTP session?)
changeSessionIdOnAuthentication	true	(Controls if the session ID is changed if a session exists at the point where users are authenticated)
className	org.apache.catalina.authenticator.NonLoginAuthenticator	(Fully qualified class name of the managed object)
disableProxyCaching	true	(Controls the caching of pages that are protected by security constraints)
modelerType	org.apache.catalina.authenticator.NonLoginAuthenticator	(Type of the modeled resource. Can be set only once)
securePagesWithPragma	false	(Controls the caching of pages that are protected by security constraints)

<p>stateName</p> <p>STARTED</p>	<p>(The name of the LifecycleState that this component is currently in)</p>
<p>host=localhost,context=/,name=StandardContextValve (Valve that implements the default basic behavior for the StandardContext container implementation)</p>	
<p>asyncSupported true</p> <p>className org.apache.catalina.core.StandardContextValve</p> <p>modelerType org.apache.catalina.core.StandardContextValve</p> <p>stateName STARTED</p>	<p>(Does this valve support async reporting?)</p> <p>(Fully qualified class name of the managed object)</p> <p>(Type of the modeled resource. Can be set only once)</p> <p>(The name of the LifecycleState that this component is currently in)</p>
<p>host=localhost,context=/demo,name=NonLoginAuthenticator (An Authenticator and Valve implementation that checks only security constraints not involving user authentication)</p>	
<p>cache true</p> <p>changeSessionIdOnAuthentication true</p> <p>className org.apache.catalina.authenticator.NonLoginAuthenticator</p> <p>disableProxyCaching true</p> <p>modelerType org.apache.catalina.authenticator.NonLoginAuthenticator</p> <p>securePagesWithPragma false</p> <p>stateName STARTED</p>	<p>(Should we cache authenticated Principals if the request is part of an HTTP session?)</p> <p>(Controls if the session ID is changed if a session exists at the point where users are authenticated)</p> <p>(Fully qualified class name of the managed object)</p> <p>(Controls the caching of pages that are protected by security constraints)</p> <p>(Type of the modeled resource. Can be set only once)</p> <p>(Controls the caching of pages that are protected by security constraints)</p> <p>(The name of the LifecycleState that this component is currently in)</p>
<p>host=localhost,context=/demo,name=StandardContextValve (Valve that implements the default basic behavior for the StandardContext container implementation)</p>	
<p>asyncSupported true</p> <p>className org.apache.catalina.core.StandardContextValve</p> <p>modelerType org.apache.catalina.core.StandardContextValve</p> <p>stateName STARTED</p>	<p>(Does this valve support async reporting?)</p> <p>(Fully qualified class name of the managed object)</p> <p>(Type of the modeled resource. Can be set only once)</p> <p>(The name of the LifecycleState that this component is currently in)</p>
<p>host=localhost,context=/downloads,name=NonLoginAuthenticator (An Authenticator and Valve implementation that checks only security constraints not involving user authentication)</p>	
<p>cache true</p> <p>changeSessionIdOnAuthentication true</p> <p>className org.apache.catalina.authenticator.NonLoginAuthenticator</p> <p>disableProxyCaching true</p> <p>modelerType org.apache.catalina.authenticator.NonLoginAuthenticator</p> <p>securePagesWithPragma false</p> <p>stateName STARTED</p>	<p>(Should we cache authenticated Principals if the request is part of an HTTP session?)</p> <p>(Controls if the session ID is changed if a session exists at the point where users are authenticated)</p> <p>(Fully qualified class name of the managed object)</p> <p>(Controls the caching of pages that are protected by security constraints)</p> <p>(Type of the modeled resource. Can be set only once)</p> <p>(Controls the caching of pages that are protected by security constraints)</p> <p>(The name of the LifecycleState that this component is currently in)</p>
<p>host=localhost,context=/downloads,name=StandardContextValve (Valve that implements the default basic behavior for the StandardContext container implementation)</p>	
<p>asyncSupported true</p> <p>className org.apache.catalina.core.StandardContextValve</p> <p>modelerType org.apache.catalina.core.StandardContextValve</p> <p>stateName STARTED</p>	<p>(Does this valve support async reporting?)</p> <p>(Fully qualified class name of the managed object)</p> <p>(Type of the modeled resource. Can be set only once)</p> <p>(The name of the LifecycleState that this component is currently in)</p>
<p>host=localhost,context=/usage,name=NonLoginAuthenticator (An Authenticator and Valve implementation that checks only security constraints not involving user authentication)</p>	
<p>cache true</p> <p>changeSessionIdOnAuthentication true</p> <p>className org.apache.catalina.authenticator.NonLoginAuthenticator</p> <p>disableProxyCaching true</p> <p>modelerType org.apache.catalina.authenticator.NonLoginAuthenticator</p> <p>securePagesWithPragma false</p> <p>stateName STARTED</p>	<p>(Should we cache authenticated Principals if the request is part of an HTTP session?)</p> <p>(Controls if the session ID is changed if a session exists at the point where users are authenticated)</p> <p>(Fully qualified class name of the managed object)</p> <p>(Controls the caching of pages that are protected by security constraints)</p> <p>(Type of the modeled resource. Can be set only once)</p> <p>(Controls the caching of pages that are protected by security constraints)</p> <p>(The name of the LifecycleState that this component is currently in)</p>
<p>host=localhost,context=/usage,name=StandardContextValve (Valve that implements the default basic behavior for the StandardContext container implementation)</p>	
<p>asyncSupported true</p> <p>className org.apache.catalina.core.StandardContextValve</p> <p>modelerType org.apache.catalina.core.StandardContextValve</p> <p>stateName STARTED</p>	<p>(Does this valve support async reporting?)</p> <p>(Fully qualified class name of the managed object)</p> <p>(Type of the modeled resource. Can be set only once)</p> <p>(The name of the LifecycleState that this component is currently in)</p>
<p>host=localhost,name=AccessLogValve (Valve that generates a web server access log)</p>	
<p>asyncSupported true</p> <p>buffered true</p> <p>checkExists false</p> <p>className org.apache.catalina.valves.AccessLogValve</p> <p>condition null</p> <p>conditionIf null</p>	<p>(Does this valve support async reporting.)</p> <p>(Flag to buffering.)</p> <p>(Check for file existence before logging.)</p> <p>(Fully qualified class name of the managed object)</p> <p>(The value to look for conditional logging. The same as conditionUnless.)</p> <p>(The value to look for conditional logging.)</p>

conditionUnless	null	(The value to look for conditional logging.)
directory	logs	(The directory in which log files are created)
enabled	true	(Enable Access Logging)
encoding	null	(Character set used to write the log file)
fileDateFormat	.yyyy-MM-dd	(The format for the date for date based log rotation)
locale	en_US	(The locale used to format timestamps in the access log lines)
modelerType	org.apache.catalina.valves.AccessLogValve	(Type of the modeled resource. Can be set only once)
pattern	%h %l %u %t "%r" %s %b	(The pattern used to format our access log lines)
prefix	localhost_access_log	(The prefix that is added to log file filenames)
renameOnRotate	false	(Flag to defer inclusion of the date stamp in the log file name until rotation.)
rotatable	true	(Flag to indicate automatic log rotation.)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
suffix	.txt	(The suffix that is added to log file filenames)

host=localhost,name=ErrorReportValve

(Implementation of a Valve that outputs HTML error pages)

asyncSupported	true	(Does this valve support async reporting.)
className	org.apache.catalina.valves.ErrorReportValve	(Fully qualified class name of the managed object)
modelerType	org.apache.catalina.valves.ErrorReportValve	(Type of the modeled resource. Can be set only once)
showReport	true	(Enables/Disables full error reports)
showServerInfo	true	(Enables/Disables server info on error pages)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

host=localhost,name=StandardHostValve

(Valve that implements the default basic behavior for the StandardHost container implementation)

asyncSupported	true	(Does this valve support async reporting?)
className	org.apache.catalina.core.StandardHostValve	(Fully qualified class name of the managed object)
modelerType	org.apache.catalina.core.StandardHostValve	(Type of the modeled resource. Can be set only once)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

name=StandardEngineValve

(Valve that implements the default basic behavior for the StandardEngine container implementation)

asyncSupported	true	(Does this valve support async reporting?)
className	org.apache.catalina.core.StandardEngineValve	(Fully qualified class name of the managed object)
modelerType	org.apache.catalina.core.StandardEngineValve	(Type of the modeled resource. Can be set only once)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule**name=/localhost/,J2EEApplication=none,J2EEServer=none**

(Standard Context Component)

altDDName	null	(The alternate deployment descriptor name.)
antiResourceLocking	false	(Take care to not lock resources)
baseName	ROOT	(The base name used for directories, WAR files (with .war appended) and context.xml files (with .xml appended).)
children	[Catalina:j2eeType=Servlet,WebModule=/localhost/,name=default,J2EEApplication=none,J2EEServer=none,Catalina:j2eeType=Servlet,WebModule=/localhost/,name=jsp,J2EEApplication=none,J2EEServer=none]	(Object names of all children)
clearReferencesRmiTargets	true	(Should Tomcat look for memory leaks in RMI Targets and clear them if found as a work around for application coding errors?)
clearReferencesStopThreads	false	(Should Tomcat attempt to terminate threads that have been started by the web application? Advisable to be used only in a development environment.)
clearReferencesStopTimerThreads	false	(Should Tomcat attempt to terminate TimerThreads that have been started by the web application? Advisable to be used only in a development environment.)
clearReferencesThreadLocals	true	(Should Tomcat attempt to clear ThreadLocal variables that have been populated with classes loaded by the web application?)
configFile	null	(Location of the context.xml resource or file)
configured	true	(The correctly configured flag for this Context.)
cookies	true	(Should we attempt to use cookies for session id communication?)
crossContext	false	(Should we allow the ServletContext.getContext() method to access the context of other web applications in this server?)
defaultContextXml	null	(Location of the default context.xml resource or file)
defaultWebXml	null	(Location of the default web.xml resource or file)
delegate	false	
displayName	null	(The display name of this web application)
distributable	false	(The distributable flag for this web application.)
docBase	ROOT	(The document root for this web application)
encodedPath		(The encoded path)
errorCount	9 348	(Cumulative error count of all servlets in this context)
ignoreAnnotations	false	(Ignore annotations flag.)
instanceManager	org.apache.catalina.core.DefaultInstanceManager@70aa5bbe	(Object that creates and destroys servlets, filters, and listeners. Include dependency injection and postConstruct/preDestroy handling)
javaVMs	null	(The Java virtual machines on which this module is running)
loader	WebappLoader[StandardEngine[Catalina].StandardHost[localhost].StandardContext[]]	(Associated loader.)
logEffectiveWebXml	false	(Should the effective web.xml be logged when the context starts?)
logger	org.apache.juli.logging.DirectJDKLog@4d3de674	(Associated logger.)
managedResource	StandardEngine[Catalina].StandardHost[localhost].StandardContext[]	(The managed resource this MBean is associated with)
manager	StandardManager[StandardEngine[Catalina].StandardHost[localhost].StandardContext[]]	(Associated manager.)

mapperContextRootRedirectEnabled	true	(Should the Mapper be used for context root redirects)
mapperDirectoryRedirectEnabled	false	(Should the Mapper be used for directory redirects)
maxTime	329	(Maximum execution time of all servlets in this context)
minTime	0	(Minimum execution time of all servlets in this context)
modelerType	org.apache.catalina.core.StandardContext	(Type of the modeled resource. Can be set only once)
name		(The name of this Context)
namingContextListener	org.apache.catalina.core.NamingContextListener@6d6a6f31	(Associated naming context listener.)
objectName	Catalina:j2eeType=WebModule,name=/localhost/,J2EEApplication=none,J2EEServer=none	(Name of the object)
originalDocBase	null	(The original document root for this web application)
override	false	(The default context.xml override flag for this web application)
parentClassLoader	java.net.URLClassLoader@3e9b1010	(Parent class loader.)
path		(The context path for this Context)
paused	false	(The request processing pause flag (while reloading occurs))
privileged	false	(Access to tomcat internals)
processingTime	6 136	(Cumulative execution times of all servlets in this context)
publicId	null	(The public identifier of the DTD for the web application deployment descriptor version that is being parsed)
realm	LockOutRealm[StandardEngine[Catalina]]	(Associated realm.)
reloadable	false	(The reloadable flag for this web application)
renewThreadsWhenStoppingContext	true	(Should Tomcat renew the threads of the thread pool when the application is stopped to avoid memory leaks because of uncleaned ThreadLocal variables.)
requestCount	13 279	(Cumulative request count of all servlets in this context)
server	null	(The J2EE Server this module is deployed on)
sessionCookieDomain	null	(The domain to use for session cookies.'null' indicates that the domain is controlled by the application.)
sessionCookieName	null	(The name to use for session cookies.'null' indicates that the name is controlled by the application.)
sessionCookiePath	null	(The path to use for session cookies.'null' indicates that the path is controlled by the application.)
sessionTimeout	30	(The session timeout (in minutes) for this web application)
startTime	1 734 895 393 050	(Time (in milliseconds since January 1, 1970, 00:00:00) when this context was started)
startupTime	0	(Time (in milliseconds) it took to start this context)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
swallowOutput	false	(Flag to set to cause the system.out and system.err to be redirected to the logger when executing a servlet)
tldScanTime	0	(Time spend scanning jars for TLDs for this context)
tldValidation	false	(Should the parsing of *.tld files be performed by a validating parser?)
unloadDelay	2 000	(Amount of ms that the container will wait for servlets to unload)
unpackWAR	true	(Unpack WAR property)
useHttpOnly	true	(Indicates that session cookies should use HttpOnly)
useNaming	true	(Create a JNDI naming context for this application?)
useRelativeRedirects	true	(When generating location headers for 302 responses, should a relative URI be used?)
webappVersion		(The version of this web application - used in parallel deployment to differentiate different versions of the same web application)
welcomeFiles	[index.html, index.htm, index.jsp]	(The welcome files for this context)
workDir	work/Catalina/localhost/ROOT	(The pathname to the work directory for this context)
xmlNamespaceAware	false	(Should the parsing of web.xml and web-fragment.xml files be performed by a namespace aware parser?)
xmlValidation	false	(Should the parsing of web.xml and web-fragment.xml files be performed by a validating parser?)

name=/localhost/demo,J2EEApplication=none,J2EEServer=none

(Standard Context Component)		
altDDName	null	(The alternate deployment descriptor name.)
antiResourceLocking	false	(Take care to not lock resources)
baseName	demo	(The base name used for directories, WAR files (with .war appended) and context.xml files (with .xml appended).)
children	[Catalina:j2eeType=Servlet,WebModule=/localhost/demo,name=CompetenceService,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=Servlet,WebModule=/localhost/demo,name=Gra deService,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=Servlet,WebModule=/localhost/demo,name=Per soneService,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=Servlet,WebModule=/localhost/demo,name=Print UtilsService,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=Servlet,WebModule=/localhost/demo,name=Adr esseService,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=Servlet,WebModule=/localhost/demo,name=Utili sateurService,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=Servlet,WebModule=/localhost/demo,name=jsp,J 2EEApplication=none,J2EEServer=none, Catalina:j2eeType=Servlet,WebModule=/localhost/demo,name=Buil dInfoServlet,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=Servlet,WebModule=/localhost/demo,name=Per missionService,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=Servlet,WebModule=/localhost/demo,name=defa ult,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=Servlet,WebModule=/localhost/demo,name=Mail Service,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=Servlet,WebModule=/localhost/demo,name=Role Service,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=Servlet,WebModule=/localhost/demo,name=Tele phoneService,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=Servlet,WebModule=/localhost/demo,name=Auth entificationService,J2EEApplication=none,J2EEServer=none]	(Object names of all children)
clearReferencesRmiTargets	true	(Should Tomcat look for memory leaks in RMI Targets and clear them if found as a work around for application coding errors?)
clearReferencesStopThreads	false	(Should Tomcat attempt to terminate threads that have been started by the web application? Advisable to be used only in a development environment.)
clearReferencesStopTimerThreads	false	(Should Tomcat attempt to terminate TimerThreads that have been started by the web application? Advisable to be used only in a development environment.)

clearReferencesThreadLocals	true	(Should Tomcat attempt to clear ThreadLocal variables that have been populated with classes loaded by the web application?)
configFile	file:/opt/apache-tomcat-9.0.33/conf/Catalina/localhost/demo.xml	(Location of the context.xml resource or file)
configured	true	(The correctly configured flag for this Context.)
cookies	true	(Should we attempt to use cookies for session id communication?)
crossContext	false	(Should we allow the ServletContext.getContext() method to access the context of other web applications in this server?)
defaultContextXml	null	(Location of the default context.xml resource or file)
defaultWebXml	null	(Location of the default web.xml resource or file)
delegate	false	
displayName	null	(The display name of this web application)
distributable	false	(The distributable flag for this web application.)
docBase	demo.war	(The document root for this web application)
encodedPath	/demo	(The encoded path)
errorCount	4 594	(Cumulative error count of all servlets in this context)
ignoreAnnotations	false	(Ignore annotations flag.)
instanceManager	org.apache.catalina.core.DefaultInstanceManager@27331ba2	(Object that creates and destroys servlets, filters, and listeners. Include dependency injection and postConstruct/preDestroy handling)
javaVMs	null	(The Java virtual machines on which this module is running)
loader	WebappLoader[StandardEngine[Catalina].StandardHost[localhost].StandardContext[/demo]]	(Associated loader.)
logEffectiveWebXml	false	(Should the effective web.xml be logged when the context starts?)
logger	org.apache.juli.logging.DirectJDKLog@6c661be9	(Associated logger.)
managedResource	StandardEngine[Catalina].StandardHost[localhost].StandardContext[/demo]	(The managed resource this MBean is associated with)
manager	StandardManager[StandardEngine[Catalina].StandardHost[localhost].StandardContext[/demo]]	(Associated manager.)
mapperContextRootRedirectEnabled	true	(Should the Mapper be used for context root redirects)
mapperDirectoryRedirectEnabled	false	(Should the Mapper be used for directory redirects)
maxTime	20 309	(Maximum execution time of all servlets in this context)
minTime	0	(Minimum execution time of all servlets in this context)
modelerType	org.apache.catalina.core.StandardContext	(Type of the modeled resource. Can be set only once)
name	/demo	(The name of this Context)
namingContextListener	org.apache.catalina.core.NamingContextListener@74c56a8b	(Associated naming context listener.)
objectName	Catalina:j2eeType=WebModule,name=/localhost/demo,J2EEApplication=none,J2EEServer=none	(Name of the object)
originalDocBase	/opt/apache-tomcat-9.0.33/webapps/demo	(The original document root for this web application)
override	false	(The default context.xml override flag for this web application)
parentClassLoader	java.net.URLClassLoader@3e9b1010	(Parent class loader.)
path	/demo	(The context path for this Context)
paused	false	(The request processing pause flag (while reloading occurs))
privileged	false	(Access to tomcat internals)
processingTime	2 667 925	(Cumulative execution times of all servlets in this context)
publicId	null	(The public identifier of the DTD for the web application deployment descriptor version that is being parsed)
realm	LockOutRealm[StandardEngine[Catalina]]	(Associated realm.)
reloadable	false	(The reloadable flag for this web application)
renewThreadsWhenStoppingContext	true	(Should Tomcat renew the threads of the thread pool when the application is stopped to avoid memory leaks because of uncleaned ThreadLocal variables.)
requestCount	20 060	(Cumulative request count of all servlets in this context)
server	null	(The J2EE Server this module is deployed on)
sessionCookieDomain	null	(The domain to use for session cookies.'null' indicates that the domain is controlled by the application.)
sessionCookieName	null	(The name to use for session cookies.'null' indicates that the name is controlled by the application.)
sessionCookiePath	null	(The path to use for session cookies.'null' indicates that the path is controlled by the application.)
sessionTimeout	30	(The session timeout (in minutes) for this web application)
startTime	1 734 894 983 149	(Time (in milliseconds since January 1, 1970, 00:00:00) when this context was started)
startupTime	2 167	(Time (in milliseconds) it took to start this context)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
swallowOutput	false	(Flag to set to cause the system.out and system.err to be redirected to the logger when executing a servlet)
tdScanTime	0	(Time spend scanning jars for TLDs for this context)
tdValidation	false	(Should the parsing of *.tld files be performed by a validating parser?)
unloadDelay	2 000	(Amount of ms that the container will wait for servlets to unload)
unpackWAR	true	(Unpack WAR property)
useHttpOnly	true	(Indicates that session cookies should use HttpOnly)
useNaming	true	(Create a JNDI naming context for this application?)
useRelativeRedirects	true	(When generating location headers for 302 responses, should a relative URI be used?)
webappVersion		(The version of this web application - used in parallel deployment to differentiate different versions of the same web application)
welcomeFiles	[index.html]	(The welcome files for this context)
workDir	work/Catalina/localhost/demo	(The pathname to the work directory for this context)
xmlNamespaceAware	false	(Should the parsing of web.xml and web-fragment.xml files be performed by a namespace aware parser?)
xmlValidation	false	(Should the parsing of web.xml and web-fragment.xml files be performed by a validating parser?)

name=/localhost/downloads,J2EEApplication=none,J2EEServer=none

(Standard Context Component)

altDDName	null	(The alternate deployment descriptor name.)
antiResourceLocking	false	(Take care to not lock resources)

baseName	downloads	(The base name used for directories, WAR files (with .war appended) and context.xml files (with .xml appended).)
children	[Catalina:j2eeType=Servlet,WebModule=/localhost/downloads,name=default,J2EEApplication=none,J2EEServer=none,Catalina:j2eeType=Servlet,WebModule=/localhost/downloads,name=jsp,J2EEApplication=none,J2EEServer=none]	(Object names of all children)
clearReferencesRmiTargets	true	(Should Tomcat look for memory leaks in RMI Targets and clear them if found as a work around for application coding errors?)
clearReferencesStopThreads	false	(Should Tomcat attempt to terminate threads that have been started by the web application? Advisable to be used only in a development environment.)
clearReferencesStopTimerThreads	false	(Should Tomcat attempt to terminate TimerThreads that have been started by the web application? Advisable to be used only in a development environment.)
clearReferencesThreadLocals	true	(Should Tomcat attempt to clear ThreadLocal variables that have been populated with classes loaded by the web application?)
configFile	null	(Location of the context.xml resource or file)
configured	true	(The correctly configured flag for this Context.)
cookies	true	(Should we attempt to use cookies for session id communication?)
crossContext	false	(Should we allow the ServletContext.getContext() method to access the context of other web applications in this server?)
defaultContextXml	null	(Location of the default context.xml resource or file)
defaultWebXml	null	(Location of the default web.xml resource or file)
delegate	false	
displayName	null	(The display name of this web application)
distributable	false	(The distributable flag for this web application.)
docBase	downloads	(The document root for this web application)
encodedPath	/downloads	(The encoded path)
errorCount	10	(Cumulative error count of all servlets in this context)
ignoreAnnotations	false	(Ignore annotations flag.)
instanceManager	org.apache.catalina.core.DefaultInstanceManager@3f2abae8	(Object that creates and destroys servlets, filters, and listeners. Include dependency injection and postConstruct/preDestroy handling)
javaVMs	null	(The Java virtual machines on which this module is running)
loader	WebappLoader[StandardEngine[Catalina].StandardHost[localhost].StandardContext[/downloads]]	(Associated loader.)
logEffectiveWebXml	false	(Should the effective web.xml be logged when the context starts?)
logger	org.apache.juli.logging.DirectJDKLog@23ab0249	(Associated logger.)
managedResource	StandardEngine[Catalina].StandardHost[localhost].StandardContext[/downloads]	(The managed resource this MBean is associated with)
manager	StandardManager[StandardEngine[Catalina].StandardHost[localhost].StandardContext[/downloads]]	(Associated manager.)
mapperContextRootRedirectEnabled	true	(Should the Mapper be used for context root redirects)
mapperDirectoryRedirectEnabled	false	(Should the Mapper be used for directory redirects)
maxTime	1	(Maximum execution time of all servlets in this context)
minTime	0	(Minimum execution time of all servlets in this context)
modelerType	org.apache.catalina.core.StandardContext	(Type of the modeled resource. Can be set only once)
name	/downloads	(The name of this Context)
namingContextListener	org.apache.catalina.core.NamingContextListener@1875e0e	(Associated naming context listener.)
objectName	Catalina:j2eeType=WebModule,name=/localhost/downloads,J2EEApplication=none,J2EEServer=none	(Name of the object)
originalDocBase	null	(The original document root for this web application)
override	false	(The default context.xml override flag for this web application)
parentClassLoader	java.net.URLClassLoader@3e9b1010	(Parent class loader.)
path	/downloads	(The context path for this Context)
paused	false	(The request processing pause flag (while reloading occurs))
privileged	false	(Access to tomcat internals)
processingTime	2	(Cumulative execution times of all servlets in this context)
publicId	null	(The public identifier of the DTD for the web application deployment descriptor version that is being parsed)
realm	LockOutRealm[StandardEngine[Catalina]]	(Associated realm.)
reloadable	false	(The reloadable flag for this web application)
renewThreadsWhenStoppingContext	true	(Should Tomcat renew the threads of the thread pool when the application is stopped to avoid memory leaks because of uncleaned ThreadLocal variables.)
requestCount	10	(Cumulative request count of all servlets in this context)
server	null	(The J2EE Server this module is deployed on)
sessionCookieDomain	null	(The domain to use for session cookies.'null' indicates that the domain is controlled by the application.)
sessionCookieName	null	(The name to use for session cookies.'null' indicates that the name is controlled by the application.)
sessionCookiePath	null	(The path to use for session cookies.'null' indicates that the path is controlled by the application.)
sessionTimeout	30	(The session timeout (in minutes) for this web application)
startTime	1 734 895 393 003	(Time (in milliseconds since January 1, 1970, 00:00:00) when this context was started)
startupTime	0	(Time (in milliseconds) it took to start this context)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
swallowOutput	false	(Flag to set to cause the system.out and system.err to be redirected to the logger when executing a servlet)
tldScanTime	0	(Time spend scanning jars for TLDs for this context)
tldValidation	false	(Should the parsing of *.tld files be performed by a validating parser?)
unloadDelay	2 000	(Amount of ms that the container will wait for servlets to unload)
unpackWAR	true	(Unpack WAR property)
useHttpOnly	true	(Indicates that session cookies should use HttpOnly)
useNaming	true	(Create a JNDI naming context for this application?)
useRelativeRedirects	true	(When generating location headers for 302 responses, should a relative URI be used?)
webappVersion		(The version of this web application - used in parallel deployment to differentiate different versions of the same web application)

welcomeFiles	[index.html, index.htm, index.jsp]	(The welcome files for this context)
workDir	work/Catalina/localhost/downloads	(The pathname to the work directory for this context)
xmlNamespaceAware	false	(Should the parsing of web.xml and web-fragment.xml files be performed by a namespace aware parser?)
xmlValidation	false	(Should the parsing of web.xml and web-fragment.xml files be performed by a validating parser?)

name=//localhost/usage,J2EEApplication=none,J2EEServer=none

(Standard Context Component)		
altDDName	null	(The alternate deployment descriptor name.)
antiResourceLocking	false	(Take care to not lock resources)
baseName	usage	(The base name used for directories, WAR files (with .war appended) and context.xml files (with .xml appended).)
children	[Catalina:j2eeType=Servlet,WebModule=//localhost/usage,name=defaut,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=Servlet,WebModule=//localhost/usage,name=jsp,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=Servlet,WebModule=//localhost/usage,name=usagestats,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=Servlet,WebModule=//localhost/usage,name=admin,J2EEApplication=none,J2EEServer=none]	(Object names of all children)
clearReferencesRmiTargets	true	(Should Tomcat look for memory leaks in RMI Targets and clear them if found as a work around for application coding errors?)
clearReferencesStopThreads	false	(Should Tomcat attempt to terminate threads that have been started by the web application? Advisable to be used only in a development environment.)
clearReferencesStopTimerThreads	false	(Should Tomcat attempt to terminate TimerThreads that have been started by the web application? Advisable to be used only in a development environment.)
clearReferencesThreadLocals	true	(Should Tomcat attempt to clear ThreadLocal variables that have been populated with classes loaded by the web application?)
configFile	file:/opt/apache-tomcat-9.0.33/conf/Catalina/localhost/usage.xml	(Location of the context.xml resource or file)
configured	true	(The correctly configured flag for this Context.)
cookies	true	(Should we attempt to use cookies for session id communication?)
crossContext	false	(Should we allow the ServletContext.getContext() method to access the context of other web applications in this server?)
defaultContextXml	null	(Location of the default context.xml resource or file)
defaultWebXml	null	(Location of the default web.xml resource or file)
delegate	false	
displayName	javamelody-usagestats	(The display name of this web application)
distributable	true	(The distributable flag for this web application.)
docBase	usage.war	(The document root for this web application)
encodedPath	/usage	(The encoded path)
errorCount	40	(Cumulative error count of all servlets in this context)
ignoreAnnotations	false	(Ignore annotations flag.)
instanceManager	org.apache.catalina.core.DefaultInstanceManager@4df3f37a	(Object that creates and destroys servlets, filters, and listeners. Include dependency injection and postConstruct/preDestroy handling)
javaVMs	null	(The Java virtual machines on which this module is running)
loader	WebappLoader[StandardEngine[Catalina],StandardHost[localhost],StandardContext[/usage]]	(Associated loader.)
logEffectiveWebXml	false	(Should the effective web.xml be logged when the context starts?)
logger	org.apache.juli.logging.DirectJDKLog@bd8c15e	(Associated logger.)
managedResource	StandardEngine[Catalina],StandardHost[localhost],StandardContext[/usage]	(The managed resource this MBean is associated with)
manager	StandardManager[StandardEngine[Catalina],StandardHost[localhost],StandardContext[/usage]]	(Associated manager.)
mapperContextRootRedirectEnabled	true	(Should the Mapper be used for context root redirects)
mapperDirectoryRedirectEnabled	false	(Should the Mapper be used for directory redirects)
maxTime	764	(Maximum execution time of all servlets in this context)
minTime	0	(Minimum execution time of all servlets in this context)
modelerType	org.apache.catalina.core.StandardContext	(Type of the modeled resource. Can be set only once)
name	/usage	(The name of this Context)
namingContextListener	org.apache.catalina.core.NamingContextListener@36f7b016	(Associated naming context listener.)
objectName	Catalina:j2eeType=WebModule,name=//localhost/usage,J2EEApplication=none,J2EEServer=none	(Name of the object)
originalDocBase	/opt/apache-tomcat-9.0.33/webapps/usage	(The original document root for this web application)
override	false	(The default context.xml override flag for this web application)
parentClassLoader	java.net.URLClassLoader@3e9b1010	(Parent class loader.)
path	/usage	(The context path for this Context)
paused	false	(The request processing pause flag (while reloading occurs))
privileged	false	(Access to tomcat internals)
processingTime	1 584 426	(Cumulative execution times of all servlets in this context)
publicId	null	(The public identifier of the DTD for the web application deployment descriptor version that is being parsed)
realm	LockOutRealm[StandardEngine[Catalina]]	(Associated realm.)
reloadable	false	(The reloadable flag for this web application)
renewThreadsWhenStoppingContext	true	(Should Tomcat renew the threads of the thread pool when the application is stopped to avoid memory leaks because of uncleaned ThreadLocal variables.)
requestCount	6 527 736	(Cumulative request count of all servlets in this context)
server	null	(The J2EE Server this module is deployed on)
sessionCookieDomain	null	(The domain to use for session cookies.'null' indicates that the domain is controlled by the application.)
sessionCookieName	null	(The name to use for session cookies.'null' indicates that the name is controlled by the application.)
sessionCookiePath	null	(The path to use for session cookies.'null' indicates that the path is controlled by the application.)
sessionTimeout	30	(The session timeout (in minutes) for this web application)
startTime	1 734 895 392 953	(Time (in milliseconds since January 1, 1970, 00:00:00) when this context was started)

startupTime	175	(Time (in milliseconds) it took to start this context)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
swallowOutput	false	(Flag to set to cause the system.out and system.err to be redirected to the logger when executing a servlet)
tldScanTime	0	(Time spend scanning jars for TLDs for this context)
tldValidation	false	(Should the parsing of *.tld files be performed by a validating parser?)
unloadDelay	2 000	(Amount of ms that the container will wait for servlets to unload)
unpackWAR	true	(Unpack WAR property)
useHttpOnly	true	(Indicates that session cookies should use HttpOnly)
useNaming	true	(Create a JNDI naming context for this application?)
useRelativeRedirects	true	(When generating location headers for 302 responses, should a relative URI be used?)
webappVersion		(The version of this web application - used in parallel deployment to differentiate different versions of the same web application)
welcomeFiles	[index.html]	(The welcome files for this context)
workDir	work/Catalina/localhost/usage	(The pathname to the work directory for this context)
xmlNamespaceAware	false	(Should the parsing of web.xml and web-fragment.xml files be performed by a namespace aware parser?)
xmlValidation	false	(Should the parsing of web.xml and web-fragment.xml files be performed by a validating parser?)

WebResourceRoot

host=localhost,context=/

(Provides the resources implementation for a web application)

allowLinking	false	(Does this resources implementation allow the use of symbolic links?)
cachingAllowed	true	(Is in memory caching of resource content and metadata enabled?)
modelerType	org.apache.catalina.webresources.StandardRoot	(Type of the modeled resource. Can be set only once)
stateName	STARTED	(The current Lifecycle state of this object)
trackLockedFiles	false	(Does this resources implementation track requests that lock files?)
trackedResources	[]	(List of resources currently being tracked for possible resource leaks)

host=localhost,context=/,name=Cache

(Provides caching of resource metadata and content)

hitCount	32 758	(The number of requests for resources that were served from the cache)
lookupCount	36 408	(The number of requests for resources)
maxSize	10 240	(The maximum permitted size of the cache in kB)
modelerType	org.apache.catalina.webresources.Cache	(Type of the modeled resource. Can be set only once)
objectMaxSize	512	(The maximum permitted size for a single object in the cache in kB)
size	1 778	(The current estimate of the cache size in kB)
ttl	5 000	(The time-to-live for cache entries in milliseconds)

host=localhost,context=/demo

(Provides the resources implementation for a web application)

allowLinking	false	(Does this resources implementation allow the use of symbolic links?)
cachingAllowed	true	(Is in memory caching of resource content and metadata enabled?)
modelerType	org.apache.catalina.webresources.StandardRoot	(Type of the modeled resource. Can be set only once)
stateName	STARTED	(The current Lifecycle state of this object)
trackLockedFiles	false	(Does this resources implementation track requests that lock files?)
trackedResources	[]	(List of resources currently being tracked for possible resource leaks)

host=localhost,context=/demo,name=Cache

(Provides caching of resource metadata and content)

hitCount	20 835	(The number of requests for resources that were served from the cache)
lookupCount	21 055	(The number of requests for resources)
maxSize	10 240	(The maximum permitted size of the cache in kB)
modelerType	org.apache.catalina.webresources.Cache	(Type of the modeled resource. Can be set only once)
objectMaxSize	512	(The maximum permitted size for a single object in the cache in kB)
size	2 559	(The current estimate of the cache size in kB)
ttl	5 000	(The time-to-live for cache entries in milliseconds)

host=localhost,context=/downloads

(Provides the resources implementation for a web application)

allowLinking	false	(Does this resources implementation allow the use of symbolic links?)
cachingAllowed	true	(Is in memory caching of resource content and metadata enabled?)
modelerType	org.apache.catalina.webresources.StandardRoot	(Type of the modeled resource. Can be set only once)
stateName	STARTED	(The current Lifecycle state of this object)
trackLockedFiles	false	(Does this resources implementation track requests that lock files?)
trackedResources	[]	(List of resources currently being tracked for possible resource leaks)

host=localhost,context=/downloads,name=Cache

(Provides caching of resource metadata and content)

hitCount	6	(The number of requests for resources that were served from the cache)
lookupCount	23	(The number of requests for resources)
maxSize	10 240	(The maximum permitted size of the cache in kB)
modelerType	org.apache.catalina.webresources.Cache	(Type of the modeled resource. Can be set only once)

objectMaxSize	512	(The maximum permitted size for a single object in the cache in kB)
size	8	(The current estimate of the cache size in kB)
ttl	5 000	(The time-to-live for cache entries in milliseconds)

host=localhost,context=/usage

(Provides the resources implementation for a web application)

allowLinking	false	(Does this resources implementation allow the use of symbolic links?)
cachingAllowed	true	(Is in memory caching of resource content and metadata enabled?)
modelerType	org.apache.catalina.webresources.StandardRoot	(Type of the modeled resource. Can be set only once)
stateName	STARTED	(The current Lifecycle state of this object)
trackLockedFiles	false	(Does this resources implementation track requests that lock files?)
trackedResources	[]	(List of resources currently being tracked for possible resource leaks)

host=localhost,context=/usage,name=Cache

(Provides caching of resource metadata and content)

hitCount	149	(The number of requests for resources that were served from the cache)
lookupCount	180	(The number of requests for resources)
maxSize	10 240	(The maximum permitted size of the cache in kB)
modelerType	org.apache.catalina.webresources.Cache	(Type of the modeled resource. Can be set only once)
objectMaxSize	512	(The maximum permitted size for a single object in the cache in kB)
size	34	(The current estimate of the cache size in kB)
ttl	5 000	(The time-to-live for cache entries in milliseconds)

JMImplementation

MBeanServerDelegate

(Represents the MBean server from the management point of view.)

ImplementationName	JMX	(The JMX implementation name (the name of this product))
ImplementationVendor	Oracle Corporation	(the JMX implementation vendor (the vendor of this product).)
ImplementationVersion	11.0.6+10	(The JMX implementation version (the version of this product).)
MBeanServerId	vps363300.ovh.net_1734894847964	(The MBean server agent identification)
SpecificationName	Java Management Extensions	(The full name of the JMX specification implemented by this product.)
SpecificationVendor	Oracle Corporation	(The vendor of the JMX specification implemented by this product.)
SpecificationVersion	1.4	(The version of the JMX specification implemented by this product.)

Users

UserDatabase

database=UserDatabase

(In-memory user and group database)

groups	[]	(MBean Names of all defined groups)
modelerType	org.apache.catalina.users.MemoryUserDatabase	(Type of the modeled resource. Can be set only once)
pathname	conf/tomcat-users.xml	(Relative or absolute pathname to database file)
readonly	true	(No persistent save of the user database)
roles	[]	(MBean Names of all defined roles)
users	[]	(MBean Names of all defined users)
writeable	true	(Check if user database is writeable)

com.sun.management

DiagnosticCommand

(Diagnostic Commands)

HotSpotDiagnostic

DiagnosticOptions

```
{(name=HeapDumpBeforeFullGC, origin=DEFAULT, value=false, writeable=true),
(name=HeapDumpAfterFullGC, origin=DEFAULT, value=false, writeable=true),
(name=HeapDumpOnOutOfMemoryError, origin=DEFAULT, value=false, writeable=true),
(name=HeapDumpPath, origin=DEFAULT, value=, writeable=true),
(name=PrintClassHistogram, origin=DEFAULT, value=false, writeable=true),
(name=MintHeapFreeRatio, origin=DEFAULT, value=40, writeable=true),
(name=MaxHeapFreeRatio, origin=DEFAULT, value=70, writeable=true),
(name=PrintConcurrentLocks, origin=DEFAULT, value=false, writeable=true),
(name=CMSAbortablePrecleanWaitMillis, origin=DEFAULT, value=100, writeable=true),
(name=CMSWaitDuration, origin=DEFAULT, value=2000, writeable=true),
(name=CMSTriggerInterval, origin=DEFAULT, value=-1, writeable=true)}
```

ObjectName com.sun.management:type=HotSpotDiagnostic

java.lang

ClassLoading

LoadedClassCount	8 421
ObjectName	java.lang:type=ClassLoading
TotalLoadedClassCount	11 329
UnloadedClassCount	2 908
Verbose	false

CodeCacheManager

type=MemoryManager

MemoryPoolNames

Name

ObjectName

Valid

[CodeHeap 'non-nmethods',
CodeHeap 'profiled nmethods',
CodeHeap 'non-profiled nmethods']

CodeCacheManager

java.lang:type=MemoryManager,name=CodeCacheManager

true

CodeHeap 'non-nmethods'

type=MemoryPool

CollectionUsage

CollectionUsageThresholdSupported

MemoryManagerNames

Name

ObjectName

PeakUsage

Type

Usage

UsageThreshold

UsageThresholdCount

UsageThresholdExceeded

UsageThresholdSupported

Valid

null

false

[CodeCacheManager]

CodeHeap 'non-nmethods'

java.lang:type=MemoryPool,name=CodeHeap 'non-nmethods'

{committed=2 555 904, init=2 555 904, max=5 828 608,
used=1 479 424}

NON_HEAP

{committed=2 555 904, init=2 555 904, max=5 828 608,
used=1 422 720}

0

0

false

true

true

CodeHeap 'non-profiled nmethods'

type=MemoryPool

CollectionUsage

CollectionUsageThresholdSupported

MemoryManagerNames

Name

ObjectName

PeakUsage

Type

Usage

UsageThreshold

UsageThresholdCount

UsageThresholdExceeded

UsageThresholdSupported

Valid

null

false

[CodeCacheManager]

CodeHeap 'non-profiled nmethods'

java.lang:type=MemoryPool,name=CodeHeap 'non-profiled
nmethods'{committed=19 726 336, init=2 555 904, max=122 916 864,
used=19 085 056}

NON_HEAP

{committed=19 726 336, init=2 555 904, max=122 916 864,
used=19 058 944}

0

0

false

true

true

CodeHeap 'profiled nmethods'

type=MemoryPool

CollectionUsage

CollectionUsageThresholdSupported

MemoryManagerNames

Name

ObjectName

PeakUsage

Type

Usage

UsageThreshold

UsageThresholdCount

UsageThresholdExceeded

UsageThresholdSupported

Valid

null

false

[CodeCacheManager]

CodeHeap 'profiled nmethods'

java.lang:type=MemoryPool,name=CodeHeap 'profiled nmethods'

{committed=20 840 448, init=2 555 904, max=122 912 768,
used=20 524 928}

NON_HEAP

{committed=20 840 448, init=2 555 904, max=122 912 768,
used=17 053 696}

0

0

false

true

true

Compilation

CompilationTimeMonitoringSupported

Name

ObjectName

TotalCompilationTime

true

HotSpot 64-Bit Tiered Compilers

java.lang:type=Compilation

347 039

Compressed Class Space

type=MemoryPool

CollectionUsage

CollectionUsageThresholdSupported

MemoryManagerNames

Name

ObjectName

PeakUsage

null

false

[Metaspace Manager]

Compressed Class Space

java.lang:type=MemoryPool,name=Compressed Class Space

{committed=6 684 672, init=0, max=1 073 741 824, used=6 075 288}

Type	NON_HEAP
Usage	{committed=6 684 672, init=0, max=1 073 741 824, used=6 034 848}
UsageThreshold	0
UsageThresholdCount	0
UsageThresholdExceeded	false
UsageThresholdSupported	true
Valid	true

Copy

type=GarbageCollector

CollectionCount	15 819
CollectionTime	524 353
LastGchInfo	{GcThreadCount=1, duration=24, endTime=1 137 044 954, id=15 819, memoryUsageAfterGc={GcThreadCount=1, duration=24, endTime=1 137 044 954, id=15 819, memoryUsageAfterGc={key=CodeHeap 'profiled nmethods', value={committed=20840448, init=2555904, max=122912768, used=17047552}, {key=Eden Space, value={committed=130809856, init=8912896, max=136445952, used=0}, {key=CodeHeap 'non-profiled nmethods', value={committed=19726336, init=2555904, max=122916864, used=19057664}, {key=Survivor Space, value={committed=16318464, init=1114112, max=17039360, used=7254392}, {key=Compressed Class Space, value={committed=6684672, init=0, max=1073741824, used=6026016}, {key=Metaspace, value={committed=68026368, init=0, max=-1, used=65845008}, {key=CodeHeap 'non-nmethods', value={committed=2555904, init=2555904, max=5828608, used=1422720}, {key=Tenured Gen, value={committed=326733824, init=22413312, max=341180416, used=89241096}}, memoryUsageBeforeGc={key=CodeHeap 'profiled nmethods', value={committed=20840448, init=2555904, max=122912768, used=17047552}, {key=Eden Space, value={committed=130809856, init=8912896, max=136445952, used=130702656}, {key=CodeHeap 'non-profiled nmethods', value={committed=19726336, init=2555904, max=122916864, used=19057664}, {key=Survivor Space, value={committed=16318464, init=1114112, max=17039360, used=5843088}, {key=Compressed Class Space, value={committed=6684672, init=0, max=1073741824, used=6026016}, {key=Metaspace, value={committed=68026368, init=0, max=-1, used=65845008}, {key=CodeHeap 'non-nmethods', value={committed=2555904, init=2555904, max=5828608, used=1422720}, {key=Tenured Gen, value={committed=326733824, init=22413312, max=341180416, used=89241096}}, startTime=1 137 044 930}, memoryUsageBeforeGc={GcThreadCount=1, duration=24, endTime=1 137 044 954, id=15 819, memoryUsageAfterGc={key=CodeHeap 'profiled nmethods', value={committed=20840448, init=2555904, max=122912768, used=17047552}, {key=Eden Space, value={committed=130809856, init=8912896, max=136445952, used=0}, {key=CodeHeap 'non-profiled nmethods', value={committed=19726336, init=2555904, max=122916864, used=19057664}, {key=Survivor Space, value={committed=16318464, init=1114112, max=17039360, used=7254392}, {key=Compressed Class Space, value={committed=6684672, init=0, max=1073741824, used=6026016}, {key=Metaspace, value={committed=68026368, init=0, max=-1, used=65845008}, {key=CodeHeap 'non-nmethods', value={committed=2555904, init=2555904, max=5828608, used=1422720}, {key=Tenured Gen, value={committed=326733824, init=22413312, max=341180416, used=89241096}}, memoryUsageBeforeGc={key=CodeHeap 'profiled nmethods', value={committed=20840448, init=2555904, max=122912768, used=17047552}, {key=Eden Space, value={committed=130809856, init=8912896, max=136445952, used=130702656}, {key=CodeHeap 'non-profiled nmethods', value={committed=19726336, init=2555904, max=122916864, used=19057664}, {key=Survivor Space, value={committed=16318464, init=1114112, max=17039360, used=5843088}, {key=Compressed Class Space, value={committed=6684672, init=0, max=1073741824, used=6026016}, {key=Metaspace, value={committed=68026368, init=0, max=-1, used=65845008}, {key=CodeHeap 'non-nmethods', value={committed=2555904, init=2555904, max=5828608, used=1422720}, {key=Tenured Gen, value={committed=326733824, init=22413312, max=341180416, used=89241096}}, startTime=1 137 044 930}, startTime=1 137 044 930}
MemoryPoolNames	[Eden Space, Survivor Space]
Name	Copy
ObjectName	java.lang:type=GarbageCollector,name=Copy
Valid	true

Eden Space

type=MemoryPool

CollectionUsage	{committed=130 809 856, init=8 912 896, max=136 445 952, used=0}
CollectionUsageThreshold	0
CollectionUsageThresholdCount	0
CollectionUsageThresholdExceeded	false
CollectionUsageThresholdSupported	true
MemoryManagerNames	[Copy, MarkSweepCompact]
Name	Eden Space
ObjectName	java.lang:type=MemoryPool,name=Eden Space
PeakUsage	{committed=136 445 952, init=8 912 896, max=136 445 952, used=136 445 952}
Type	HEAP
Usage	{committed=130 809 856, init=8 912 896, max=136 445 952, used=32 483 464}
UsageThresholdSupported	false
Valid	true

MarkSweepCompact

type=GarbageCollector

CollectionCount	541
CollectionTime	334 719
LastGcInfo	{GcThreadCount=1, duration=113, endTime=1 117 803 512, id=541, memoryUsageAfterGc={key=CodeHeap 'profiled nmethods', value=(committed=20840448, init=2555904, max=122912768, used=17140864)}, (key=Eden Space, value=(committed=136445952, init=8912896, max=136445952, used=0)}, (key=CodeHeap 'non-profiled nmethods', value=(committed=19464192, init=2555904, max=122916864, used=18753664)}, (key=Survivor Space, value=(committed=17039360, init=1114112, max=17039360, used=0)}, (key=Compressed Class Space, value=(committed=6684672, init=0, max=1073741824, used=6003992)}, (key=Metaspace, value=(committed=67764224, init=0, max=-1, used=65653528)}, (key=CodeHeap 'non-nmethods', value=(committed=2555904, init=2555904, max=5828608, used=1422720)}, (key=Tenured Gen, value=(committed=341180416, init=22413312, max=341180416, used=5902552))}, memoryUsageBeforeGc={key=CodeHeap 'profiled nmethods', value=(committed=20840448, init=2555904, max=122912768, used=17140864)}, (key=Eden Space, value=(committed=136445952, init=8912896, max=136445952, used=227352)}, (key=CodeHeap 'non-profiled nmethods', value=(committed=19464192, init=2555904, max=122916864, used=18753664)}, (key=Survivor Space, value=(committed=17039360, init=1114112, max=17039360, used=0)}, (key=Compressed Class Space, value=(committed=6684672, init=0, max=1073741824, used=6003992)}, (key=Metaspace, value=(committed=67764224, init=0, max=-1, used=65653528)}, (key=CodeHeap 'non-nmethods', value=(committed=2555904, init=2555904, max=5828608, used=1422720)}, (key=Tenured Gen, value=(committed=341180416, init=22413312, max=341180416, used=58926488))}, startTime=1117803399}, memoryUsageBeforeGc={GcThreadCount=1, duration=113, endTime=1117803512, id=541, memoryUsageAfterGc={key=CodeHeap 'profiled nmethods', value=(committed=20840448, init=2555904, max=122912768, used=17140864)}, (key=Eden Space, value=(committed=136445952, init=8912896, max=136445952, used=0)}, (key=CodeHeap 'non-profiled nmethods', value=(committed=19464192, init=2555904, max=122916864, used=18753664)}, (key=Survivor Space, value=(committed=17039360, init=1114112, max=17039360, used=0)}, (key=Compressed Class Space, value=(committed=6684672, init=0, max=1073741824, used=6003992)}, (key=Metaspace, value=(committed=67764224, init=0, max=-1, used=65653528)}, (key=CodeHeap 'non-nmethods', value=(committed=2555904, init=2555904, max=5828608, used=1422720)}, (key=Tenured Gen, value=(committed=341180416, init=22413312, max=341180416, used=5902552))}, memoryUsageBeforeGc={key=CodeHeap 'profiled nmethods', value=(committed=20840448, init=2555904, max=122912768, used=17140864)}, (key=Eden Space, value=(committed=136445952, init=8912896, max=136445952, used=227352)}, (key=CodeHeap 'non-profiled nmethods', value=(committed=19464192, init=2555904, max=122916864, used=18753664)}, (key=Survivor Space, value=(committed=17039360, init=1114112, max=17039360, used=0)}, (key=Compressed Class Space, value=(committed=6684672, init=0, max=1073741824, used=6003992)}, (key=Metaspace, value=(committed=67764224, init=0, max=-1, used=65653528)}, (key=CodeHeap 'non-nmethods', value=(committed=2555904, init=2555904, max=5828608, used=1422720)}, (key=Tenured Gen, value=(committed=341180416, init=22413312, max=341180416, used=58926488))}, startTime=1117803399}, startTime=1 117 803 399}
MemoryPoolNames	[Eden Space, Survivor Space, Tenured Gen]
Name	MarkSweepCompact
ObjectName	java.lang:type=GarbageCollector,name=MarkSweepCompact
Valid	true

Memory

HeapMemoryUsage	{committed=473 862 144, init=33 554 432, max=494 665 728, used=131 552 112}
NonHeapMemoryUsage	{committed=117 833 728, init=7 667 712, max=-1, used=109 538 688}
ObjectName	java.lang:type=Memory
ObjectPendingFinalizationCount	0
Verbose	false

Metaspace

type=MemoryPool

CollectionUsage	null
CollectionUsageThresholdSupported	false
MemoryManagerNames	[Metaspace Manager]
Name	Metaspace
ObjectName	java.lang:type=MemoryPool,name=Metaspace
PeakUsage	{committed=68 026 368, init=0, max=-1, used=65 897 080}
Type	NON_HEAP
Usage	{committed=68 026 368, init=0, max=-1, used=65 897 080}
UsageThreshold	0
UsageThresholdCount	0
UsageThresholdExceeded	false
UsageThresholdSupported	true
Valid	true

Metaspace Manager

type=MemoryManager

MemoryPoolNames	[Metaspace, Compressed Class Space]
Name	Metaspace Manager
ObjectName	java.lang:type=MemoryManager,name=Metaspace Manager

Valid true

OperatingSystem

Arch	amd64
AvailableProcessors	1
CommittedVirtualMemorySize	2 966 552 576
FreePhysicalMemorySize	86 253 568
FreeSwapSpaceSize	0
MaxFileDescriptorCount	4 096
Name	Linux
ObjectName	java.lang:type=OperatingSystem
OpenFileDescriptorCount	124
ProcessCpuLoad	0
ProcessCpuTime	19 465 420 000 000
SystemCpuLoad	1
SystemLoadAverage	1
TotalPhysicalMemorySize	2 045 435 904
TotalSwapSpaceSize	0
Version	3.10.0-1160.114.2.el7.x86_64

Runtime

BootClassPathSupported	false
ClassPath	/opt/tomcat/bin/bootstrap.jar:/opt/tomcat/bin/tomcat-juli.jar
InputArguments	[-add-opens=java.base/java.lang=ALL-UNNAMED, --add-opens=java.base/java.io=ALL-UNNAMED, --add-opens=java.rmi/sun.rmi.transport=ALL-UNNAMED, -Djava.util.logging.config.file=/opt/tomcat/conf/logging.properties, -Djava.util.logging.manager=org.apache.juli.ClassLoaderLogManager, -Djdk.tls.ephemeralDHKeySize=2048, -Djava.protocol.handler.pkgs=org.apache.catalina.webresources, -Dorg.apache.catalina.security.SecurityListener.UMASK=0027, -Djava.security.egd=file:/dev/./urandom, -Dignore.endorsed.dirs=, -Dcatalina.base=/opt/tomcat, -Dcatalina.home=/opt/tomcat, -Djava.io.tmpdir=/opt/tomcat/temp]
LibraryPath	/usr/java/packages/lib:/usr/lib64:/lib64:/lib:/usr/lib
ManagementSpecVersion	2.0
Name	809@vps363300.ovh.net
ObjectName	java.lang:type=Runtime
Pid	809
SpecName	Java Virtual Machine Specification
SpecVendor	Oracle Corporation
SpecVersion	11
StartTime	1 734 894 846 208

SystemProperties

```

{{key=awt.toolkit, value=sun.awt.X11.XToolkit},
{key=java.specification.version, value=11},
{key=sun.cpu.isalist, value=},
{key=sun.jnu.encoding, value=UTF-8},
{key=java.class.path,
value=/opt/tomcat/bin/bootstrap.jar:/opt/tomcat/bin/tomcat-juli.jar},
{key=pid, value=809},
{key=java.vm.vendor, value=AdoptOpenJDK},
{key=sun.arch.data.model, value=64},
{key=sun.font.fontmanager, value=sun.awt.X11FontManager},
{key=java.vendor.url, value=https://adoptopenjdk.net/},
{key=catalina.useNaming, value=true},
{key=user.timezone, value=Europe/Paris},
{key=os.name, value=Linux},
{key=java.vm.specification.version, value=11},
{key=sun.java.launcher, value=SUN_STANDARD},
{key=user.country, value=US},
{key=sun.boot.library.path, value=/opt/jdk-11.0.6+10/lib},
{key=sun.java.command, value=org.apache.catalina.startup.Bootstrap
start},
{key=jdk.debug, value=release},
{key=sun.cpu.endian, value=little},
{key=user.home, value=/root},
{key=user.language, value=en},
{key=java.specification.vendor, value=Oracle Corporation},
{key=java.naming.factory.url.pkgs, value=org.apache.naming},
{key=java.version.date, value=2020-01-14},
{key=java.home, value=/opt/jdk-11.0.6+10},
{key=ignore.endorsed.dirs, value=},
{key=file.separator, value=/},
{key=java.vm.compressedOopsMode, value=32-bit},
{key=line.separator, value=
},
{key=java.specification.name, value=Java Platform API Specification},
{key=java.vm.specification.vendor, value=Oracle Corporation},
{key=java.awt.graphicsenv, value=sun.awt.X11GraphicsEnvironment},
{key=package.access,
value=sun.,org.apache.catalina.,org.apache.coyote.,org.apache.jasper
.,org.apache.tomcat.},
{key=package.definition,
value=sun.,java.,org.apache.catalina.,org.apache.coyote.,org.apache.j
asper.,org.apache.naming.,org.apache.tomcat.},
{key=jdk.tls.ephemeralDHKeySize, value=2048},
{key=server.loader, value=},
{key=java.util.logging.config.file,
value=/opt/tomcat/conf/logging.properties},
{key=java.protocol.handler.pkgs,
value=org.apache.catalina.webresources},
{key=sun.management.compiler, value=HotSpot 64-Bit Tiered
Compilers},
{key=java.runtime.version, value=11.0.6+10},
{key=java.naming.factory.initial,
value=org.apache.naming.java.javaURLContextFactory},
{key=user.name, value=root},
{key=path.separator, value=},
{key=java.security.egd, value=file:/dev/.urandom},
{key=common.loader,
value=${catalina.base}/lib/*:${catalina.base}/lib/*.jar:${catalina.home
}/lib/*:${catalina.home}/lib/*.jar},
{key=os.version, value=3.10.0-1160.114.2.el7.x86_64},
{key=java.runtime.name, value=OpenJDK Runtime Environment},
{key=file.encoding, value=UTF-8},
{key=java.vm.name, value=OpenJDK 64-Bit Server VM},
{key=java.vendor.version, value=AdoptOpenJDK},
{key=org.apache.catalina.security.SecurityListener.UMASK,
value=0027},
{key=java.vendor.url.bug,
value=https://github.com/AdoptOpenJDK/openjdk-support/issues},
{key=java.io.tmpdir, value=/opt/tomcat/temp},
{key=tomcat.util.scan.StandardJarScanFilter.jarsToScan, value=log4j-
taglib.jar,log4j-web.jar,log4jjavascript.jar,slf4j-taglib.jar},
{key=catalina.home, value=/opt/apache-tomcat-9.0.33},
{key=java.version, value=11.0.6},
{key=tomcat.util.scan.StandardJarScanFilter.jarsToSkip,
value=annotations-api.jar,ant-junit.jar,ant-launcher.jar,ant.jar,asm-
*.jar,aspectj.jar,bootstrap.jar,catalina-ant.jar,catalina-ha.jar,catalina-
ssi.jar,catalina-storeconfig.jar,catalina-tribes.jar,catalina.jar,cglib-
*.jar,coertura-*.jar,commons-beanutils.jar,commons-
codec.jar,commons-collections.jar,commons-daemon.jar,commons-
dbcp.jar,commons-digester.jar,commons-fileupload.jar,commons-
httpclient.jar,commons-io.jar,commons-lang.jar,commons-
logging.jar,commons-math.jar,commons-pool.jar,dom4j-
*.jar,easymock.jar,ecj-*.jar,el-api.jar,geronimo-spec-
jaxrpc.jar,h2.jar,hamcrest.jar,hibernate.jar,httpClient.jar,icu4j-
*.jar,jasper-el.jar,jasper.jar,jaspic-api.jar,jaxb-*.jar,jaxen-*.jar,jdom-
.jar,jetty-*.jar,jmx-tools.jar,jmx.jar,jsp-api.jar,jstl.jar,jta.jar,junit-
*.jar,junit.jar,log4j.jar,mail.jar,objenesis.jar,oraclepk.jar,oro-
*.jar,servlet-api.jar,servlet-api.jar,slf4j.jar,taglibs-standard-spec-
.jar,tagsoup.jar,tomcat-api.jar,tomcat-coyote.jar,tomcat-
dbcp.jar,tomcat-118n-*.jar,tomcat-jdbc.jar,tomcat-jni.jar,tomcat-juli-
adapters.jar,tomcat-juli.jar,tomcat-util-scan.jar,tomcat-util.jar,tomcat-
websocket.jar,tools.jar,websocket-api.jar,wsdl4j.jar,xercesImpl.jar,xml-
apis.jar,xmlParserAPIs-*.jar,xmlParserAPIs.jar,xom-*.jar},
{key=user.dir, value=/},
{key=os.arch, value=amd64},
{key=java.vm.specification.name, value=Java Virtual Machine
Specification},
{key=java.awt.printerjob, value=sun.print.PSPrinterJob},
{key=sun.os.patch.level, value=unknown},
{key=catalina.base, value=/opt/apache-tomcat-9.0.33},
{key=shared.loader, value=},
{key=java.util.logging.manager,
value=org.apache.juli.ClassLoaderLogManager},
{key=java.library.path,
value=/usr/java/packages/lib:/usr/lib64:/lib64:/lib:/usr/lib},
{key=java.vendor, value=AdoptOpenJDK},
{key=java.vm.info, value=mixed mode},
{key=java.vm.version, value=11.0.6+10},
{key=sun.io.unicode.encoding, value=UnicodeLittle},
{key=tomcat.util.buf.StringCache.byte.enabled, value=true},
{key=java.class.version, value=55.0}}

```

Uptime

1 137 045 244

VmName

OpenJDK 64-Bit Server VM

VmVendor

AdoptOpenJDK

VmVersion

11.0.6+10

Survivor Space

type=MemoryPool

```

CollectionUsage (committed=16 318 464, init=1 114 112, max=17 039 360,
used=7 254 392)
CollectionUsageThreshold 0
CollectionUsageThresholdCount 0
CollectionUsageThresholdExceeded false
CollectionUsageThresholdSupported true
MemoryManagerNames [Copy,
MarkSweepCompact]

```



```

Name                               Survivor Space
ObjectName                           java.lang:type=MemoryPool,name=Survivor Space
PeakUsage                             {committed=17 039 360, init=1 114 112, max=17 039 360,
used=17 039 360}

Type                                  HEAP
Usage                                 {committed=16 318 464, init=1 114 112, max=17 039 360,
used=7 254 392}

UsageThresholdSupported              false
Valid                                 true
    
```

Tenured Gen

type=MemoryPool

```

CollectionUsage                       {committed=341 180 416, init=22 413 312, max=341 180 416,
used=59 002 552}

CollectionUsageThreshold               0
CollectionUsageThresholdCount         0
CollectionUsageThresholdExceeded      false
CollectionUsageThresholdSupported     true
MemoryManagerNames                    [MarkSweepCompact]
Name                                   Tenured Gen
ObjectName                             java.lang:type=MemoryPool,name=Tenured Gen
PeakUsage                              {committed=341 180 416, init=22 413 312, max=341 180 416,
used=341 180 416}

Type                                  HEAP
Usage                                 {committed=326 733 824, init=22 413 312, max=341 180 416,
used=89 241 096}

UsageThreshold                        0
UsageThresholdCount                   0
UsageThresholdExceeded                false
UsageThresholdSupported               true
Valid                                 true
    
```

Threading

```

AllThreadIds                          [J@36931d6c
CurrentThreadCpuTime                  94 474 212 455
CurrentThreadCpuTimeSupported         true
CurrentThreadUserTime                 72 990 000 000
DaemonThreadCount                     61
ObjectMonitorUsageSupported          true
ObjectName                             java.lang:type=Threading
PeakThreadCount                       139
SynchronizerUsageSupported           true
ThreadAllocatedMemoryEnabled          true
ThreadAllocatedMemorySupported       true
ThreadContentionMonitoringEnabled     false
ThreadContentionMonitoringSupported   true
ThreadCount                           66
ThreadCpuTimeEnabled                  true
ThreadCpuTimeSupported                true
TotalStartedThreadCount               469
    
```

java.nio

direct

type=BufferPool

```

Count                                  48
MemoryUsed                             405 504
Name                                    direct
ObjectName                             java.nio:type=BufferPool,name=direct
TotalCapacity                          405 504
    
```

mapped

type=BufferPool

```

Count                                  0
MemoryUsed                             0
Name                                    mapped
ObjectName                             java.nio:type=BufferPool,name=mapped
TotalCapacity                          0
    
```

java.util.logging

Logging

LoggerNames

```
[
org.apache.catalina.core.ContainerBase.[Catalina],
org.apache.catalina.session,
org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo].[
default],
sun.net.www.protocol.http,
org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo].[
TelephoneService],
org.apache.tomcat.dbcp.dbcp2.BasicDataSource,
org.apache.catalina.core.ApplicationFilterConfig,
org.apache.jasper,
org.apache.jasper.servlet.JasperInitializer,
org.apache.jasper.compiler.Compiler,
org.apache.catalina.util,
org.apache.tomcat.util.descriptor.web.WebXmlParser,
org.apache.catalina.webresources,
jdk.event,
org.apache.tomcat.util.net,
org.apache.tomcat.util.digester.Digester,
sun.awt.multiscreen.SunDisplayChanger,
sun.awt.X11GraphicsEnvironment,
org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo].[
GradeService],
org.apache.jasper.compiler,
org.apache.tomcat.util.descriptor.web,
org.apache.jasper.servlet.JspServlet,
org.apache.tomcat.websocket,
org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo],
org.apache.catalina.webresources.JarWarResource,
org.apache.tomcat.dbcp,
org.apache.tomcat.dbcp.dbcp2.ObjectNameWrapper,
org.apache.tomcat.util.descriptor,
org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo].[
MailService],
org.apache.catalina,
sun.net.www.protocol.http.HttpURLConnection,
org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo].[
AdresseService],
org.apache.tomcat,
org.apache.jasper.servlet,
org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo].[
PersonneService],
org.apache.catalina.webresources.JarResourceRoot,
jdk.event.security,
org.apache.tomcat.util.digester.Digester.sax,
org.apache.jasper.JspCompilationContext,
org.apache,
org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo].[
CompetenceService],
sun.net,
org.apache.catalina.core.ContainerBase,
org.apache.tomcat.util.descriptor.web.WebXml,
org.apache.jasper.servlet.TldScanner,
org.apache.jasper.compiler.JDTCompiler,
org.apache.tomcat.util.descriptor.tld,
org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo].[
AuthenticationService],
sun,
sun.net.www.protocol,
sun.awt.multiscreen,
sun.net.www,
org.apache.jasper.EmbeddedServletOptions,
org.apache.tomcat.dbcp.dbcp2,
org.apache.jasper.compiler.JspConfig,
org.apache.tomcat.util.scan,
org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo].[
PermissionService],
org.apache.tomcat.dbcp.dbcp2.BasicDataSourceFactory,
org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo].[
BuildInfoServlet],
org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo].[
RoleService],
org.apache.catalina.core.ContainerBase.[Catalina].[localhost],
org.apache.tomcat.util.digester,
org.apache.catalina.util.SessionIdGeneratorBase,
org.apache.tomcat.util.net.SSLHostConfig,
org.apache.tomcat.dbcp.dbcp2.PoolableConnectionFactory,
sun.awt.screen,
org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo].[
UtilisateurService],
sun.awt.screen.X11GraphicsEnvironment,
org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo].[
jsp],
org.apache.tomcat.dbcp.dbcp2.PoolingDataSource,
sun.awt,
org,
org.apache.catalina.session.ManagerBase,
org.apache.catalina.authenticator.AuthenticatorBase,
org.apache.catalina.session.StandardManager,
org.apache.tomcat.util.descriptor.tld.TldParser,
org.apache.catalina.authenticator,
org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo].[
PrintUtilsService],
jdk,
org.apache.jasper.servlet.JspServletWrapper,
org.apache.tomcat.util,
org.apache.tomcat.util.net.SSLHostConfigCertificate,
org.apache.jasper.compiler.JspRuntimeContext,
org.apache.catalina.core.StandardWrapper,
org.apache.tomcat.util.scan.StandardJarScanner,
org.apache.tomcat.websocket.WsWebSocketContainer,
org.apache.catalina.core]

```

ObjectName

java.util.logging:type=Logging

jdk.management.jfr
FlightRecorder

Configurations

```

{{contents=<?xml version="1.0" encoding="UTF-8"?>
<!--
Recommended way to edit .jfc files is to use Java Mission Control,
see Window -> Flight Recorder Template Manager.
-->
<configuration version="2.0" label="Profiling" description="Low
overhead configuration for profiling, typically around 2 % overhead."
provider="Oracle">

  <event name="jdk.ThreadAllocationStatistics">
    <setting name="enabled">true</setting>
    <setting name="period">everyChunk</setting>
  </event>

  <event name="jdk.ClassLoadingStatistics">
    <setting name="enabled">true</setting>
    <setting name="period">1000 ms</setting>
  </event>

  <event name="jdk.ClassLoaderStatistics">
    <setting name="enabled">true</setting>
    <setting name="period">everyChunk</setting>
  </event>

  <event name="jdk.JavaThreadStatistics">
    <setting name="enabled">true</setting>
    <setting name="period">1000 ms</setting>
  </event>

  <event name="jdk.ThreadStart">
    <setting name="enabled">true</setting>
  </event>

  <event name="jdk.ThreadEnd">
    <setting name="enabled">true</setting>
  </event>

  <event name="jdk.ThreadSleep">
    <setting name="enabled">true</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold" control="synchronization-threshold">10
ms</setting>
  </event>

  <event name="jdk.ThreadPark">
    <setting name="enabled">true</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold" control="synchronization-threshold">10
ms</setting>
  </event>

  <event name="jdk.JavaMonitorEnter">
    <setting name="enabled">true</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold" control="synchronization-threshold">10
ms</setting>
  </event>

  <event name="jdk.JavaMonitorWait">
    <setting name="enabled">true</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold" control="synchronization-threshold">10
ms</setting>
  </event>

  <event name="jdk.JavaMonitorInflate">
    <setting name="enabled">true</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold" control="synchronization-threshold">10
ms</setting>
  </event>

  <event name="jdk.BiasedLockRevocation">
    <setting name="enabled">true</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.BiasedLockSelfRevocation">
    <setting name="enabled">true</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.BiasedLockClassRevocation">
    <setting name="enabled">true</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.ReservedStackActivation">
    <setting name="enabled">true</setting>
    <setting name="stackTrace">true</setting>
  </event>

  <event name="jdk.ClassLoad">
    <setting name="enabled" control="class-loading-
enabled">false</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.ClassDefine">
    <setting name="enabled" control="class-loading-
enabled">false</setting>
    <setting name="stackTrace">true</setting>
  </event>

  <event name="jdk.ClassUnload">
    <setting name="enabled" control="class-loading-
enabled">false</setting>
  </event>

  <event name="jdk.JVMInformation">
    <setting name="enabled">true</setting>
    <setting name="period">beginChunk</setting>
  </event>

  <event name="jdk.InitialSystemProperty">
    <setting name="enabled">true</setting>
    <setting name="period">beginChunk</setting>
  </event>

  <event name="jdk.ExecutionSample">
    <setting name="enabled" control="method-sampling-
enabled">true</setting>
    <setting name="period" control="method-sampling-java-
interval">10 ms</setting>
  </event>

  <event name="jdk.NativeMethodSample">
    <setting name="enabled" control="method-sampling-
enabled">true</setting>
    <setting name="period" control="method-sampling-native-
interval">20 ms</setting>
  </event>

```

```

<event name="jdk.SafepointBegin">
  <setting name="enabled">true</setting>
  <setting name="threshold">0 ms</setting>
</event>

<event name="jdk.SafepointStateSynchronization">
  <setting name="enabled">>false</setting>
  <setting name="threshold">0 ms</setting>
</event>

<event name="jdk.SafepointWaitBlocked">
  <setting name="enabled">>false</setting>
  <setting name="threshold">0 ms</setting>
</event>

<event name="jdk.SafepointCleanup">
  <setting name="enabled">>false</setting>
  <setting name="threshold">0 ms</setting>
</event>

<event name="jdk.SafepointCleanupTask">
  <setting name="enabled">>false</setting>
  <setting name="threshold">0 ms</setting>
</event>

<event name="jdk.SafepointEnd">
  <setting name="enabled">>false</setting>
  <setting name="threshold">0 ms</setting>
</event>

<event name="jdk.ExecuteVMOperation">
  <setting name="enabled">true</setting>
  <setting name="threshold">0 ms</setting>
</event>

<event name="jdk.Shutdown">
  <setting name="enabled">true</setting>
  <setting name="stackTrace">true</setting>
</event>

<event name="jdk.ThreadDump">
  <setting name="enabled" control="thread-dump-
enabled">true</setting>
  <setting name="period" control="thread-dump-interval">60
s</setting>
</event>

<event name="jdk.IntFlag">
  <setting name="enabled">true</setting>
  <setting name="period">beginChunk</setting>
</event>

<event name="jdk.UnsignedIntFlag">
  <setting name="enabled">true</setting>
  <setting name="period">beginChunk</setting>
</event>

<event name="jdk.LongFlag">
  <setting name="enabled">true</setting>
  <setting name="period">beginChunk</setting>
</event>

<event name="jdk.UnsignedLongFlag">
  <setting name="enabled">true</setting>
  <setting name="period">beginChunk</setting>
</event>

<event name="jdk.DoubleFlag">
  <setting name="enabled">true</setting>
  <setting name="period">beginChunk</setting>
</event>

<event name="jdk.BooleanFlag">
  <setting name="enabled">true</setting>
  <setting name="period">beginChunk</setting>
</event>

<event name="jdk.StringFlag">
  <setting name="enabled">true</setting>
  <setting name="period">beginChunk</setting>
</event>

<event name="jdk.IntFlagChanged">
  <setting name="enabled">true</setting>
</event>

<event name="jdk.UnsignedIntFlagChanged">
  <setting name="enabled">true</setting>
</event>

<event name="jdk.LongFlagChanged">
  <setting name="enabled">true</setting>
</event>

<event name="jdk.UnsignedLongFlagChanged">
  <setting name="enabled">true</setting>
</event>

<event name="jdk.DoubleFlagChanged">
  <setting name="enabled">true</setting>
</event>

<event name="jdk.BooleanFlagChanged">
  <setting name="enabled">true</setting>
</event>

<event name="jdk.StringFlagChanged">
  <setting name="enabled">true</setting>
</event>

<event name="jdk.ObjectCount">
  <setting name="enabled" control="memory-profiling-enabled-
all">>false</setting>
  <setting name="period">everyChunk</setting>
</event>

<event name="jdk.GCConfiguration">
  <setting name="enabled" control="gc-enabled-
normal">true</setting>
  <setting name="period">everyChunk</setting>
</event>

<event name="jdk.GCHeapConfiguration">
  <setting name="enabled" control="gc-enabled-
normal">true</setting>
  <setting name="period">beginChunk</setting>
</event>

<event name="jdk.YoungGenerationConfiguration">
  <setting name="enabled" control="gc-enabled-
normal">true</setting>
  <setting name="period">beginChunk</setting>
</event>

<event name="jdk.GCTLABConfiguration">
  <setting name="enabled" control="gc-enabled-
normal">true</setting>

```

```

<setting name="period">beginChunk</setting>
</event>

<event name="jdk.GCSurvivorConfiguration">
<setting name="enabled" control="gc-enabled-normal">true</setting>
<setting name="period">beginChunk</setting>
</event>

<event name="jdk.ObjectCountAfterGC">
<setting name="enabled">>false</setting>
</event>

<event name="jdk.GCHeapSummary">
<setting name="enabled" control="gc-enabled-normal">true</setting>
</event>

<event name="jdk.PSHeapSummary">
<setting name="enabled" control="gc-enabled-normal">true</setting>
</event>

<event name="jdk.G1HeapSummary">
<setting name="enabled" control="gc-enabled-normal">true</setting>
</event>

<event name="jdk.MetaspaceSummary">
<setting name="enabled" control="gc-enabled-normal">true</setting>
</event>

<event name="jdk.MetaspaceGCThreshold">
<setting name="enabled" control="gc-enabled-normal">true</setting>
</event>

<event name="jdk.MetaspaceAllocationFailure">
<setting name="enabled" control="gc-enabled-normal">true</setting>
<setting name="stackTrace">true</setting>
</event>

<event name="jdk.MetaspaceOOM">
<setting name="enabled" control="gc-enabled-normal">true</setting>
<setting name="stackTrace">true</setting>
</event>

<event name="jdk.MetaspaceChunkFreeListSummary">
<setting name="enabled" control="gc-enabled-normal">true</setting>
</event>

<event name="jdk.GarbageCollection">
<setting name="enabled" control="gc-enabled-normal">true</setting>
<setting name="threshold">0 ms</setting>
</event>

<event name="jdk.ParallelOldGarbageCollection">
<setting name="enabled" control="gc-enabled-normal">true</setting>
<setting name="threshold">0 ms</setting>
</event>

<event name="jdk.YoungGarbageCollection">
<setting name="enabled" control="gc-enabled-normal">true</setting>
<setting name="threshold">0 ms</setting>
</event>

<event name="jdk.OldGarbageCollection">
<setting name="enabled" control="gc-enabled-normal">true</setting>
<setting name="threshold">0 ms</setting>
</event>

<event name="jdk.G1GarbageCollection">
<setting name="enabled" control="gc-enabled-normal">true</setting>
<setting name="threshold">0 ms</setting>
</event>

<event name="jdk.GCPhasePause">
<setting name="enabled" control="gc-enabled-normal">true</setting>
<setting name="threshold">0 ms</setting>
</event>

<event name="jdk.GCPhasePauseLevel1">
<setting name="enabled" control="gc-enabled-normal">true</setting>
<setting name="threshold">0 ms</setting>
</event>

<event name="jdk.GCPhasePauseLevel2">
<setting name="enabled" control="gc-enabled-normal">true</setting>
<setting name="threshold">0 ms</setting>
</event>

<event name="jdk.GCPhasePauseLevel3">
<setting name="enabled" control="gc-enabled-all">>false</setting>
<setting name="threshold">0 ms</setting>
</event>

<event name="jdk.GCPhasePauseLevel4">
<setting name="enabled" control="gc-enabled-all">>false</setting>
<setting name="threshold">0 ms</setting>
</event>

<event name="jdk.GCPhaseConcurrent">
<setting name="enabled" control="gc-enabled-all">>true</setting>
<setting name="threshold">0 ms</setting>
</event>

<event name="jdk.GCReferenceStatistics">
<setting name="enabled" control="gc-enabled-normal">true</setting>
</event>

<event name="jdk.PromotionFailed">
<setting name="enabled" control="gc-enabled-normal">true</setting>
</event>

<event name="jdk.EvacuationFailed">
<setting name="enabled" control="gc-enabled-normal">true</setting>
</event>

<event name="jdk.EvacuationInformation">
<setting name="enabled" control="gc-enabled-normal">true</setting>
</event>

```

```

<event name="jdk.G1MMU">
  <setting name="enabled" control="gc-enabled-normal">true</setting>
</event>

<event name="jdk.G1EvacuationYoungStatistics">
  <setting name="enabled" control="gc-enabled-normal">true</setting>
</event>

<event name="jdk.G1EvacuationOldStatistics">
  <setting name="enabled" control="gc-enabled-normal">true</setting>
</event>

<event name="jdk.G1BasicHOP">
  <setting name="enabled" control="gc-enabled-normal">true</setting>
</event>

<event name="jdk.G1AdaptiveHOP">
  <setting name="enabled" control="gc-enabled-normal">true</setting>
</event>

<event name="jdk.PromoteObjectInNewPLAB">
  <setting name="enabled" control="memory-profiling-enabled-medium">true</setting>
</event>

<event name="jdk.PromoteObjectOutsidePLAB">
  <setting name="enabled" control="memory-profiling-enabled-medium">true</setting>
</event>

<event name="jdk.ConcurrentModeFailure">
  <setting name="enabled" control="gc-enabled-normal">true</setting>
</event>

<event name="jdk.AllocationRequiringGC">
  <setting name="enabled" control="gc-enabled-all">>false</setting>
  <setting name="stackTrace">true</setting>
</event>

<event name="jdk.TenuringDistribution">
  <setting name="enabled" control="gc-enabled-normal">true</setting>
</event>

<event name="jdk.G1HeapRegionInformation">
  <setting name="enabled" control="gc-enabled-all">>false</setting>
  <setting name="period">everyChunk</setting>
</event>

<event name="jdk.G1HeapRegionTypeChange">
  <setting name="enabled" control="gc-enabled-all">>false</setting>
</event>

<event name="jdk.OldObjectSample">
  <setting name="enabled" control="memory-leak-detection-enabled">true</setting>
  <setting name="stackTrace" control="memory-leak-detection-stack-trace">true</setting>
  <setting name="cutoff" control="memory-leak-detection-cutoff">0ns</setting>
</event>

<event name="jdk.CompilerConfiguration">
  <setting name="enabled" control="compiler-enabled">true</setting>
  <setting name="period">beginChunk</setting>
</event>

<event name="jdk.CompilerStatistics">
  <setting name="enabled" control="compiler-enabled">true</setting>
  <setting name="period">1000 ms</setting>
</event>

<event name="jdk.Compilation">
  <setting name="enabled" control="compiler-enabled">true</setting>
  <setting name="threshold" control="compiler-compilation-threshold">100 ms</setting>
</event>

<event name="jdk.CompilerPhase">
  <setting name="enabled" control="compiler-enabled">true</setting>
  <setting name="threshold" control="compiler-phase-threshold">10s</setting>
</event>

<event name="jdk.CompilationFailure">
  <setting name="enabled" control="compiler-enabled-failure">true</setting>
</event>

<event name="jdk.CompilerInlining">
  <setting name="enabled" control="compiler-enabled-failure">>false</setting>
</event>

<event name="jdk.CodeSweeperConfiguration">
  <setting name="enabled" control="compiler-enabled">true</setting>
  <setting name="period">beginChunk</setting>
</event>

<event name="jdk.CodeSweeperStatistics">
  <setting name="enabled" control="compiler-enabled">true</setting>
  <setting name="period">everyChunk</setting>
</event>

<event name="jdk.SweepCodeCache">
  <setting name="enabled" control="compiler-enabled">true</setting>
  <setting name="threshold" control="compiler-sweeper-threshold">100 ms</setting>
</event>

<event name="jdk.CodeCacheConfiguration">
  <setting name="enabled" control="compiler-enabled">true</setting>
  <setting name="period">beginChunk</setting>
</event>

<event name="jdk.CodeCacheStatistics">
  <setting name="enabled" control="compiler-enabled">true</setting>
  <setting name="period">everyChunk</setting>
</event>

<event name="jdk.CodeCacheFull">
  <setting name="enabled" control="compiler-enabled">true</setting>

```

```

</event>
<event name="jdk.OSInformation">
  <setting name="enabled">true</setting>
  <setting name="period">beginChunk</setting>
</event>
<event name="jdk.VirtualizationInformation">
  <setting name="enabled">true</setting>
  <setting name="period">beginChunk</setting>
</event>
<event name="jdk.CPUInformation">
  <setting name="enabled">true</setting>
  <setting name="period">beginChunk</setting>
</event>
<event name="jdk.ThreadContextSwitchRate">
  <setting name="enabled" control="compiler-
enabled">true</setting>
  <setting name="period">10 s</setting>
</event>
<event name="jdk.CPULoad">
  <setting name="enabled">true</setting>
  <setting name="period">1000 ms</setting>
</event>
<event name="jdk.ThreadCPULoad">
  <setting name="enabled">true</setting>
  <setting name="period">10 s</setting>
</event>
<event name="jdk.CPUTimeStampCounter">
  <setting name="enabled">true</setting>
  <setting name="period">beginChunk</setting>
</event>
<event name="jdk.SystemProcess">
  <setting name="enabled">true</setting>
  <setting name="period">endChunk</setting>
</event>
<event name="jdk.NetworkUtilization">
  <setting name="enabled">true</setting>
  <setting name="period">5 s</setting>
</event>
<event name="jdk.InitialEnvironmentVariable">
  <setting name="enabled">true</setting>
  <setting name="period">beginChunk</setting>
</event>
<event name="jdk.PhysicalMemory">
  <setting name="enabled">true</setting>
  <setting name="period">everyChunk</setting>
</event>
<event name="jdk.ObjectAllocationInNewTLAB">
  <setting name="enabled" control="memory-profiling-enabled-
medium">true</setting>
  <setting name="stackTrace">true</setting>
</event>
<event name="jdk.ObjectAllocationOutsideTLAB">
  <setting name="enabled" control="memory-profiling-enabled-
medium">true</setting>
  <setting name="stackTrace">true</setting>
</event>
<event name="jdk.NativeLibrary">
  <setting name="enabled">true</setting>
  <setting name="period">everyChunk</setting>
</event>
<event name="jdk.ModuleRequire">
  <setting name="enabled">true</setting>
  <setting name="period">endChunk</setting>
</event>
<event name="jdk.ModuleExport">
  <setting name="enabled">true</setting>
  <setting name="period">endChunk</setting>
</event>
<event name="jdk.FileForce">
  <setting name="enabled">true</setting>
  <setting name="stackTrace">true</setting>
  <setting name="threshold" control="file-io-threshold">10
ms</setting>
</event>
<event name="jdk.FileRead">
  <setting name="enabled">true</setting>
  <setting name="stackTrace">true</setting>
  <setting name="threshold" control="file-io-threshold">10
ms</setting>
</event>
<event name="jdk.FileWrite">
  <setting name="enabled">true</setting>
  <setting name="stackTrace">true</setting>
  <setting name="threshold" control="file-io-threshold">10
ms</setting>
</event>
<event name="jdk.SocketRead">
  <setting name="enabled">true</setting>
  <setting name="stackTrace">true</setting>
  <setting name="threshold" control="socket-io-threshold">10
ms</setting>
</event>
<event name="jdk.SocketWrite">
  <setting name="enabled">true</setting>
  <setting name="stackTrace">true</setting>
  <setting name="threshold" control="socket-io-threshold">10
ms</setting>
</event>
<event name="jdk.SecurityPropertyModification">
  <setting name="enabled">>false</setting>
  <setting name="stackTrace">true</setting>
</event>
<event name="jdk.TLSHandshake">
  <setting name="enabled">>false</setting>
  <setting name="stackTrace">true</setting>
</event>
<event name="jdk.X509Validation">
  <setting name="enabled">>false</setting>
  <setting name="stackTrace">true</setting>
</event>
<event name="jdk.X509Certificate">
  <setting name="enabled">>false</setting>
  <setting name="stackTrace">true</setting>

```

```

</event>

<event name="jdk.JavaExceptionThrow">
  <setting name="enabled" control="enable-
exceptions">false</setting>
  <setting name="stackTrace">true</setting>
</event>

<event name="jdk.JavaErrorThrow">
  <setting name="enabled" control="enable-errors">true</setting>
  <setting name="stackTrace">true</setting>
</event>

<event name="jdk.ExceptionStatistics">
  <setting name="enabled">true</setting>
  <setting name="period">1000 ms</setting>
</event>

<event name="jdk.ActiveRecording">
  <setting name="enabled">true</setting>
</event>

<event name="jdk.ActiveSetting">
  <setting name="enabled">true</setting>
</event>

<event name="jdk.DataLoss">
  <setting name="enabled">true</setting>
</event>

<event name="jdk.DumpReason">
  <setting name="enabled">true</setting>
</event>

<event name="jdk.ZPageAllocation">
  <setting name="enabled">true</setting>
  <setting name="threshold">10 ms</setting>
</event>

<event name="jdk.ZThreadPhase">
  <setting name="enabled">true</setting>
  <setting name="threshold">0 ms</setting>
</event>

<event name="jdk.ZStatisticsCounter">
  <setting name="threshold">10 ms</setting>
  <setting name="enabled">true</setting>
</event>

<event name="jdk.ZStatisticsSampler">
  <setting name="enabled">true</setting>
  <setting name="threshold">10 ms</setting>
</event>

```

```

<!--
  Contents of the control element is not read by the JVM, it's used
  by Java Mission Control to change settings that carry the control
  attribute.
-->
<control>

  <selection name="gc-level" default="detailed" label="Garbage
Collector">
    <option label="Off" name="off">off</option>
    <option label="Normal" name="detailed">normal</option>
    <option label="All" name="all">all</option>
  </selection>

  <condition name="gc-enabled-normal" true="true" false="false">
    <or>
      <test name="gc-level" operator="equal" value="normal"/>
      <test name="gc-level" operator="equal" value="all"/>
    </or>
  </condition>

  <condition name="gc-enabled-all" true="true" false="false">
    <test name="gc-level" operator="equal" value="all"/>
  </condition>

  <selection name="memory-profiling" default="medium"
label="Memory Profiling">
    <option label="Off" name="off">off</option>
    <option label="Object Allocation and Promotion"
name="medium">medium</option>
    <option label="All, including Heap Statistics (May cause long full
GCs)" name="all">all</option>
  </selection>

  <condition name="memory-profiling-enabled-medium" true="true"
false="false">
    <or>
      <test name="memory-profiling" operator="equal"
value="medium"/>
      <test name="memory-profiling" operator="equal" value="all"/>
    </or>
  </condition>

  <condition name="memory-profiling-enabled-all" true="true"
false="false">
    <test name="memory-profiling" operator="equal" value="all"/>
  </condition>

  <selection name="compiler-level" default="detailed"
label="Compiler">
    <option label="Off" name="off">off</option>
    <option label="Normal" name="normal">normal</option>
    <option label="Detailed" name="detailed">detailed</option>
    <option label="All" name="all">all</option>
  </selection>

```



```

<condition name="compiler-enabled" true="false" false="true">
  <test name="compiler-level" operator="equal" value="off"/>
</condition>

<condition name="compiler-enabled-failure" true="true"
false="false">
  <or>
    <test name="compiler-level" operator="equal" value="detailed"/>
    <test name="compiler-level" operator="equal" value="all"/>
  </or>
</condition>

<condition name="compiler-sweeper-threshold" true="0 ms"
false="100 ms">
  <test name="compiler-level" operator="equal" value="all"/>
</condition>

<condition name="compiler-compilation-threshold" true="1000
ms">
  <test name="compiler-level" operator="equal" value="normal"/>
</condition>

<condition name="compiler-compilation-threshold" true="100 ms">
  <test name="compiler-level" operator="equal" value="detailed"/>
</condition>

<condition name="compiler-compilation-threshold" true="0 ms">
  <test name="compiler-level" operator="equal" value="all"/>
</condition>

<condition name="compiler-phase-threshold" true="60 s">
  <test name="compiler-level" operator="equal" value="normal"/>
</condition>

<condition name="compiler-phase-threshold" true="10 s">
  <test name="compiler-level" operator="equal" value="detailed"/>
</condition>

<condition name="compiler-phase-threshold" true="0 s">
  <test name="compiler-level" operator="equal" value="all"/>
</condition>

<selection name="method-sampling-interval" default="normal"
label="Method Sampling">
  <option label="Off" name="off">off</option>
  <option label="Normal" name="normal">normal</option>
  <option label="High" name="high">high</option>
  <option label="Ludicrous (High Overhead)"
name="ludicrous">ludicrous</option>
</selection>

<condition name="method-sampling-java-interval" true="999 d">
  <test name="method-sampling-interval" operator="equal"
value="off"/>
</condition>

<condition name="method-sampling-java-interval" true="20 ms">
  <test name="method-sampling-interval" operator="equal"
value="normal"/>
</condition>

<condition name="method-sampling-java-interval" true="10 ms">
  <test name="method-sampling-interval" operator="equal"
value="high"/>
</condition>

<condition name="method-sampling-java-interval" true="1 ms">
  <test name="method-sampling-interval" operator="equal"
value="ludicrous"/>
</condition>

<condition name="method-sampling-native-interval" true="999 d">
  <test name="method-sampling-interval" operator="equal"
value="off"/>
</condition>

<condition name="method-sampling-native-interval" true="20 ms">
  <or>
    <test name="method-sampling-interval" operator="equal"
value="normal"/>
    <test name="method-sampling-interval" operator="equal"
value="high"/>
    <test name="method-sampling-interval" operator="equal"
value="ludicrous"/>
  </or>
</condition>

<condition name="method-sampling-enabled" true="false"
false="true">
  <test name="method-sampling-interval" operator="equal"
value="off"/>
</condition>

<selection name="thread-dump-interval" default="everyMinute"
label="Thread Dump">
  <option label="Off" name="off">999 d</option>
  <option label="At least Once"
name="normal">everyChunk</option>
  <option label="Every 60 s" name="everyMinute">60 s</option>
  <option label="Every 10 s" name="everyTenSecond">10
s</option>
  <option label="Every 1 s" name="everySecond">1 s</option>
</selection>

<condition name="thread-dump-enabled" true="false" false="true">
  <test name="thread-dump-interval" operator="equal" value="999
d"/>
</condition>

<selection name="exception-level" default="errors"
label="Exceptions">
  <option label="Off" name="off">off</option>
  <option label="Errors Only" name="errors">errors</option>
  <option label="All Exceptions, including Errors"
name="all">all</option>
</selection>

<condition name="enable-errors" true="true" false="false">
  <or>
    <test name="exception-level" operator="equal" value="errors"/>
    <test name="exception-level" operator="equal" value="all"/>
  </or>
</condition>

<condition name="enable-exceptions" true="true" false="false">
  <test name="exception-level" operator="equal" value="all"/>
</condition>

<selection name="memory-leak-detection" default="medium"
label="Memory Leak Detection">
  <option label="Off" name="off">off</option>
  <option label="Object Types" name="minimal">minimal</option>
  <option label="Object Types + Allocation Stack Traces"
name="medium">medium</option>
  <option label="Object Types + Allocation Stack Traces + Path to
GC Root" name="full">full</option>
</selection>

```

```

<condition name="memory-leak-detection-enabled" true="false"
false="true">
  <test name="memory-leak-detection" operator="equal"
value="off"/>
</condition>

<condition name="memory-leak-detection-stack-trace" true="true"
false="false">
  <or>
    <test name="memory-leak-detection" operator="equal"
value="medium"/>
    <test name="memory-leak-detection" operator="equal"
value="full"/>
  </or>
</condition>

<condition name="memory-leak-detection-cutoff" true="1 h"
false="0 ns">
  <test name="memory-leak-detection" operator="equal"
value="full"/>
</condition>

<text name="synchronization-threshold" label="Synchronization
Threshold" contentType="timespan" minimum="0 s">10 ms</text>

<text name="file-io-threshold" label="File I/O Threshold"
contentType="timespan" minimum="0 s">10 ms</text>

<text name="socket-io-threshold" label="Socket I/O Threshold"
contentType="timespan" minimum="0 s">10 ms</text>

<flag name="class-loading-enabled" label="Class
Loading">false</flag>

</control>

</configuration>
<description=Low overhead configuration for profiling, typically around
2 % overhead., label=Profiling, name=profile, provider=Oracle,
settings={key=jdk.ThreadAllocationStatistics#enabled, value=true},
{key=jdk.ThreadAllocationStatistics#period, value=everyChunk},
{key=jdk.ClassLoadingStatistics#enabled, value=true},
{key=jdk.ClassLoadingStatistics#period, value=1000 ms},
{key=jdk.ClassLoaderStatistics#enabled, value=true},
{key=jdk.ClassLoaderStatistics#period, value=everyChunk},
{key=jdk.JavaThreadStatistics#enabled, value=true},
{key=jdk.JavaThreadStatistics#period, value=1000 ms},
{key=jdk.ThreadStart#enabled, value=true},
{key=jdk.ThreadEnd#enabled, value=true},
{key=jdk.ThreadSleep#enabled, value=true},
{key=jdk.ThreadSleep#stackTrace, value=true},
{key=jdk.ThreadSleep#threshold, value=10 ms},
{key=jdk.ThreadPark#enabled, value=true},
{key=jdk.ThreadPark#stackTrace, value=true},
{key=jdk.ThreadPark#threshold, value=10 ms},
{key=jdk.JavaMonitorEnter#enabled, value=true},
{key=jdk.JavaMonitorEnter#stackTrace, value=true},
{key=jdk.JavaMonitorEnter#threshold, value=10 ms},
{key=jdk.JavaMonitorWait#enabled, value=true},
{key=jdk.JavaMonitorWait#stackTrace, value=true},
{key=jdk.JavaMonitorWait#threshold, value=10 ms},
{key=jdk.JavaMonitorInflate#enabled, value=true},
{key=jdk.JavaMonitorInflate#stackTrace, value=true},
{key=jdk.JavaMonitorInflate#threshold, value=10 ms},
{key=jdk.BiasedLockRevocation#enabled, value=true},
{key=jdk.BiasedLockRevocation#stackTrace, value=true},
{key=jdk.BiasedLockRevocation#threshold, value=0 ms},
{key=jdk.BiasedLockSelfRevocation#enabled, value=true},
{key=jdk.BiasedLockSelfRevocation#stackTrace, value=true},
{key=jdk.BiasedLockSelfRevocation#threshold, value=0 ms},
{key=jdk.BiasedLockClassRevocation#enabled, value=true},
{key=jdk.BiasedLockClassRevocation#stackTrace, value=true},
{key=jdk.BiasedLockClassRevocation#threshold, value=0 ms},
{key=jdk.ReservedStackActivation#enabled, value=true},
{key=jdk.ReservedStackActivation#stackTrace, value=true},
{key=jdk.ClassLoad#enabled, value=false},
{key=jdk.ClassLoad#stackTrace, value=true},
{key=jdk.ClassLoad#threshold, value=0 ms},
{key=jdk.ClassDefine#enabled, value=false},
{key=jdk.ClassDefine#stackTrace, value=true},
{key=jdk.ClassUnload#enabled, value=false},
{key=jdk.JVMInformation#enabled, value=true},
{key=jdk.JVMInformation#period, value=beginChunk},
{key=jdk.InitialSystemProperty#enabled, value=true},
{key=jdk.InitialSystemProperty#period, value=beginChunk},
{key=jdk.ExecutionSample#enabled, value=true},
{key=jdk.ExecutionSample#period, value=10 ms},
{key=jdk.NativeMethodSample#enabled, value=true},
{key=jdk.NativeMethodSample#period, value=20 ms},
{key=jdk.SafePointBegin#enabled, value=true},
{key=jdk.SafePointBegin#threshold, value=0 ms},
{key=jdk.SafePointStateSynchronization#enabled, value=false},
{key=jdk.SafePointStateSynchronization#threshold, value=0 ms},
{key=jdk.SafePointWaitBlocked#enabled, value=false},
{key=jdk.SafePointWaitBlocked#threshold, value=0 ms},
{key=jdk.SafePointCleanup#enabled, value=false},
{key=jdk.SafePointCleanup#threshold, value=0 ms},
{key=jdk.SafePointCleanupTask#enabled, value=false},
{key=jdk.SafePointCleanupTask#threshold, value=0 ms},
{key=jdk.SafePointEnd#enabled, value=false},
{key=jdk.SafePointEnd#threshold, value=0 ms},
{key=jdk.ExecuteVMOperation#enabled, value=true},
{key=jdk.ExecuteVMOperation#threshold, value=0 ms},
{key=jdk.Shutdown#enabled, value=true},
{key=jdk.Shutdown#stackTrace, value=true},
{key=jdk.ThreadDump#enabled, value=true},
{key=jdk.ThreadDump#period, value=60 s}, {key=jdk.IntFlag#enabled,
value=true}, {key=jdk.IntFlag#period, value=beginChunk},
{key=jdk.UnsignedIntFlag#enabled, value=true},
{key=jdk.UnsignedIntFlag#period, value=beginChunk},
{key=jdk.LongFlag#enabled, value=true}, {key=jdk.LongFlag#period,
value=beginChunk}, {key=jdk.UnsignedLongFlag#enabled,
value=true}, {key=jdk.UnsignedLongFlag#period, value=beginChunk},
{key=jdk.DoubleFlag#enabled, value=true},
{key=jdk.DoubleFlag#period, value=beginChunk},
{key=jdk.BooleanFlag#enabled, value=true},
{key=jdk.BooleanFlag#period, value=beginChunk},
{key=jdk.StringFlag#enabled, value=true}, {key=jdk.StringFlag#period,
value=beginChunk}, {key=jdk.IntFlagChanged#enabled, value=true},
{key=jdk.UnsignedIntFlagChanged#enabled, value=true},
{key=jdk.LongFlagChanged#enabled, value=true},
{key=jdk.UnsignedLongFlagChanged#enabled, value=true},
{key=jdk.DoubleFlagChanged#enabled, value=true},
{key=jdk.BooleanFlagChanged#enabled, value=true},
{key=jdk.StringFlagChanged#enabled, value=true},
{key=jdk.ObjectCount#enabled, value=false},
{key=jdk.ObjectCount#period, value=everyChunk},
{key=jdk.GCConfiguration#enabled, value=true},
{key=jdk.GCConfiguration#period, value=everyChunk},
{key=jdk.GCHeapConfiguration#enabled, value=true},
{key=jdk.GCHeapConfiguration#period, value=beginChunk},
{key=jdk.YoungGenerationConfiguration#enabled, value=true},
{key=jdk.YoungGenerationConfiguration#period, value=beginChunk},
{key=jdk.GCTLABConfiguration#enabled, value=true},
{key=jdk.GCTLABConfiguration#period, value=beginChunk},
{key=jdk.GCSurvivorConfiguration#enabled, value=true},
{key=jdk.GCSurvivorConfiguration#period, value=beginChunk},
{key=jdk.ObjectCountAfterGC#enabled, value=false},

```

```

{key=jdk.GCHeapSummary#enabled, value=true},
{key=jdk.PSHeapSummary#enabled, value=true},
{key=jdk.G1HeapSummary#enabled, value=true},
{key=jdk.MetaspaceSummary#enabled, value=true},
{key=jdk.MetaspaceGCThreshold#enabled, value=true},
{key=jdk.MetaspaceAllocationFailure#enabled, value=true},
{key=jdk.MetaspaceAllocationFailure#stackTrace, value=true},
{key=jdk.MetaspaceOOM#enabled, value=true},
{key=jdk.MetaspaceOOM#stackTrace, value=true},
{key=jdk.MetaspaceChunkFreeListSummary#enabled, value=true},
{key=jdk.GarbageCollection#enabled, value=true},
{key=jdk.GarbageCollection#threshold, value=0 ms},
{key=jdk.ParallelOldGarbageCollection#enabled, value=true},
{key=jdk.ParallelOldGarbageCollection#threshold, value=0 ms},
{key=jdk.YoungGarbageCollection#enabled, value=true},
{key=jdk.YoungGarbageCollection#threshold, value=0 ms},
{key=jdk.OldGarbageCollection#enabled, value=true},
{key=jdk.OldGarbageCollection#threshold, value=0 ms},
{key=jdk.G1GarbageCollection#enabled, value=true},
{key=jdk.G1GarbageCollection#threshold, value=0 ms},
{key=jdk.GCPhasePause#enabled, value=true},
{key=jdk.GCPhasePause#threshold, value=0 ms},
{key=jdk.GCPhasePauseLevel1#enabled, value=true},
{key=jdk.GCPhasePauseLevel1#threshold, value=0 ms},
{key=jdk.GCPhasePauseLevel2#enabled, value=true},
{key=jdk.GCPhasePauseLevel2#threshold, value=0 ms},
{key=jdk.GCPhasePauseLevel3#enabled, value=false},
{key=jdk.GCPhasePauseLevel3#threshold, value=0 ms},
{key=jdk.GCPhasePauseLevel4#enabled, value=false},
{key=jdk.GCPhasePauseLevel4#threshold, value=0 ms},
{key=jdk.GCPhaseConcurrent#enabled, value=true},
{key=jdk.GCPhaseConcurrent#threshold, value=0 ms},
{key=jdk.GCReferenceStatistics#enabled, value=true},
{key=jdk.PromotionFailed#enabled, value=true},
{key=jdk.EvacuationFailed#enabled, value=true},
{key=jdk.EvacuationInformation#enabled, value=true},
{key=jdk.G1MMU#enabled, value=true},
{key=jdk.G1EvacuationYoungStatistics#enabled, value=true},
{key=jdk.G1EvacuationOldStatistics#enabled, value=true},
{key=jdk.G1BasicHOP#enabled, value=true},
{key=jdk.G1AdaptiveHOP#enabled, value=true},
{key=jdk.PromoteObjectInNewPLAB#enabled, value=true},
{key=jdk.PromoteObjectOutsidePLAB#enabled, value=true},
{key=jdk.ConcurrentModeFailure#enabled, value=true},
{key=jdk.AllocationRequiringGC#enabled, value=false},
{key=jdk.AllocationRequiringGC#stackTrace, value=true},
{key=jdk.TenuringDistribution#enabled, value=true},
{key=jdk.G1HeapRegionInformation#enabled, value=false},
{key=jdk.G1HeapRegionInformation#period, value=everyChunk},
{key=jdk.G1HeapRegionTypeChange#enabled, value=false},
{key=jdk.OldObjectSample#enabled, value=true},
{key=jdk.OldObjectSample#stackTrace, value=true},
{key=jdk.OldObjectSample#cutoff, value=0 ns},
{key=jdk.CompilerConfiguration#enabled, value=true},
{key=jdk.CompilerConfiguration#period, value=beginChunk},
{key=jdk.CompilerStatistics#enabled, value=true},
{key=jdk.CompilerStatistics#period, value=1000 ms},
{key=jdk.Compilation#enabled, value=true},
{key=jdk.Compilation#threshold, value=100 ms},
{key=jdk.CompilerPhase#enabled, value=true},
{key=jdk.CompilerPhase#threshold, value=10 s},
{key=jdk.CompilationFailure#enabled, value=true},
{key=jdk.CompilerInlining#enabled, value=false},
{key=jdk.CodeSweeperConfiguration#enabled, value=true},
{key=jdk.CodeSweeperConfiguration#period, value=beginChunk},
{key=jdk.CodeSweeperStatistics#enabled, value=true},
{key=jdk.CodeSweeperStatistics#period, value=everyChunk},
{key=jdk.SweepCodeCache#enabled, value=true},
{key=jdk.SweepCodeCache#threshold, value=100 ms},
{key=jdk.CodeCacheConfiguration#enabled, value=true},
{key=jdk.CodeCacheConfiguration#period, value=beginChunk},
{key=jdk.CodeCacheStatistics#enabled, value=true},
{key=jdk.CodeCacheStatistics#period, value=everyChunk},
{key=jdk.CodeCacheFull#enabled, value=true},
{key=jdk.OSInformation#enabled, value=true},
{key=jdk.OSInformation#period, value=beginChunk},
{key=jdk.VirtualizationInformation#enabled, value=true},
{key=jdk.VirtualizationInformation#period, value=beginChunk},
{key=jdk.CPUInformation#enabled, value=true},
{key=jdk.CPUInformation#period, value=beginChunk},
{key=jdk.ThreadContextSwitchRate#enabled, value=true},
{key=jdk.ThreadContextSwitchRate#period, value=10 s},
{key=jdk.CPULoad#enabled, value=true}, {key=jdk.CPULoad#period, value=1000 ms},
{key=jdk.ThreadCPULoad#enabled, value=true},
{key=jdk.ThreadCPULoad#period, value=10 s},
{key=jdk.CPUTimeStampCounter#enabled, value=true},
{key=jdk.CPUTimeStampCounter#period, value=beginChunk},
{key=jdk.SystemProcess#enabled, value=true},
{key=jdk.SystemProcess#period, value=endChunk},
{key=jdk.NetworkUtilization#enabled, value=true},
{key=jdk.NetworkUtilization#period, value=5 s},
{key=jdk.InitialEnvironmentVariable#enabled, value=true},
{key=jdk.InitialEnvironmentVariable#period, value=beginChunk},
{key=jdk.PhysicalMemory#enabled, value=true},
{key=jdk.PhysicalMemory#period, value=everyChunk},
{key=jdk.ObjectAllocationInNewTLAB#enabled, value=true},
{key=jdk.ObjectAllocationInNewTLAB#stackTrace, value=true},
{key=jdk.ObjectAllocationOutsideTLAB#enabled, value=true},
{key=jdk.ObjectAllocationOutsideTLAB#stackTrace, value=true},
{key=jdk.NativeLibrary#enabled, value=true},
{key=jdk.NativeLibrary#period, value=everyChunk},
{key=jdk.ModuleRequire#enabled, value=true},
{key=jdk.ModuleRequire#period, value=endChunk},
{key=jdk.ModuleExport#enabled, value=true},
{key=jdk.ModuleExport#period, value=endChunk},
{key=jdk.FileForce#enabled, value=true},
{key=jdk.FileForce#stackTrace, value=true},
{key=jdk.FileForce#threshold, value=10 ms},
{key=jdk.FileRead#enabled, value=true},
{key=jdk.FileRead#stackTrace, value=true},
{key=jdk.FileRead#threshold, value=10 ms},
{key=jdk.FileWrite#enabled, value=true},
{key=jdk.FileWrite#stackTrace, value=true},
{key=jdk.FileWrite#threshold, value=10 ms},
{key=jdk.SocketRead#enabled, value=true},
{key=jdk.SocketRead#stackTrace, value=true},
{key=jdk.SocketRead#threshold, value=10 ms},
{key=jdk.SocketWrite#enabled, value=true},
{key=jdk.SocketWrite#stackTrace, value=true},
{key=jdk.SocketWrite#threshold, value=10 ms},
{key=jdk.SecurityPropertyModification#enabled, value=false},
{key=jdk.SecurityPropertyModification#stackTrace, value=true},
{key=jdk.TLSHandshake#enabled, value=false},
{key=jdk.TLSHandshake#stackTrace, value=true},
{key=jdk.X509Validation#enabled, value=false},
{key=jdk.X509Validation#stackTrace, value=true},
{key=jdk.X509Certificate#enabled, value=false},
{key=jdk.X509Certificate#stackTrace, value=true},
{key=jdk.JavaExceptionThrow#enabled, value=false},
{key=jdk.JavaExceptionThrow#stackTrace, value=true},
{key=jdk.JavaErrorThrow#enabled, value=true},
{key=jdk.JavaErrorThrow#stackTrace, value=true},
{key=jdk.ExceptionStatistics#enabled, value=true},
{key=jdk.ExceptionStatistics#period, value=1000 ms},
{key=jdk.ActiveRecording#enabled, value=true},
{key=jdk.ActiveSetting#enabled, value=true},
{key=jdk.DataLoss#enabled, value=true},
{key=jdk.DumpReason#enabled, value=true},

```

```

{key=jdk.ZPageAllocation#enabled, value=true},
{key=jdk.ZPageAllocation#threshold, value=10 ms},
{key=jdk.ZThreadPhase#enabled, value=true},
{key=jdk.ZThreadPhase#threshold, value=0 ms},
{key=jdk.ZStatisticsCounter#threshold, value=10 ms},
{key=jdk.ZStatisticsCounter#enabled, value=true},
{key=jdk.ZStatisticsSampler#enabled, value=true},
{key=jdk.ZStatisticsSampler#threshold, value=10 ms}},
{contents=<?xml version="1.0" encoding="UTF-8"?>

<!--
Recommended way to edit .jfc files is to use Java Mission Control,
see Window -> Flight Recorder Template Manager.
-->

<configuration version="2.0" label="Continuous" description="Low
overhead configuration safe for continuous use in production
environments, typically less than 1 % overhead." provider="Oracle">

  <event name="jdk.ThreadAllocationStatistics">
    <setting name="enabled">true</setting>
    <setting name="period">everyChunk</setting>
  </event>

  <event name="jdk.ClassLoadingStatistics">
    <setting name="enabled">true</setting>
    <setting name="period">1000 ms</setting>
  </event>

  <event name="jdk.ClassLoaderStatistics">
    <setting name="enabled">true</setting>
    <setting name="period">everyChunk</setting>
  </event>

  <event name="jdk.JavaThreadStatistics">
    <setting name="enabled">true</setting>
    <setting name="period">1000 ms</setting>
  </event>

  <event name="jdk.ThreadStart">
    <setting name="enabled">true</setting>
  </event>

  <event name="jdk.ThreadEnd">
    <setting name="enabled">true</setting>
  </event>

  <event name="jdk.ThreadSleep">
    <setting name="enabled">true</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold" control="synchronization-threshold">20
ms</setting>
  </event>

  <event name="jdk.ThreadPark">
    <setting name="enabled">true</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold" control="synchronization-threshold">20
ms</setting>
  </event>

  <event name="jdk.JavaMonitorEnter">
    <setting name="enabled">true</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold" control="synchronization-threshold">20
ms</setting>
  </event>

  <event name="jdk.JavaMonitorWait">
    <setting name="enabled">true</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold" control="synchronization-threshold">20
ms</setting>
  </event>

  <event name="jdk.JavaMonitorInflate">
    <setting name="enabled">false</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold" control="synchronization-threshold">20
ms</setting>
  </event>

  <event name="jdk.BiasedLockRevocation">
    <setting name="enabled">true</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.BiasedLockSelfRevocation">
    <setting name="enabled">true</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.BiasedLockClassRevocation">
    <setting name="enabled">true</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.ReservedStackActivation">
    <setting name="enabled">true</setting>
    <setting name="stackTrace">true</setting>
  </event>

  <event name="jdk.ClassLoad">
    <setting name="enabled" control="class-loading-
enabled">false</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.ClassDefine">
    <setting name="enabled" control="class-loading-
enabled">false</setting>
    <setting name="stackTrace">true</setting>
  </event>

  <event name="jdk.ClassUnload">
    <setting name="enabled" control="class-loading-
enabled">false</setting>
  </event>

  <event name="jdk.JVMInformation">
    <setting name="enabled">true</setting>
    <setting name="period">beginChunk</setting>
  </event>

  <event name="jdk.InitialSystemProperty">
    <setting name="enabled">true</setting>
    <setting name="period">beginChunk</setting>
  </event>

  <event name="jdk.ExecutionSample">
    <setting name="enabled" control="method-sampling-
enabled">true</setting>
    <setting name="period" control="method-sampling-java-
interval">20 ms</setting>

```

```

</event>
<event name="jdk.NativeMethodSample">
  <setting name="enabled" control="method-sampling-
enabled">true</setting>
  <setting name="period" control="method-sampling-native-
interval">20 ms</setting>
</event>
<event name="jdk.SafepointBegin">
  <setting name="enabled">true</setting>
  <setting name="threshold">10 ms</setting>
</event>
<event name="jdk.SafepointStateSynchronization">
  <setting name="enabled">false</setting>
  <setting name="threshold">10 ms</setting>
</event>
<event name="jdk.SafepointWaitBlocked">
  <setting name="enabled">false</setting>
  <setting name="threshold">10 ms</setting>
</event>
<event name="jdk.SafepointCleanup">
  <setting name="enabled">false</setting>
  <setting name="threshold">10 ms</setting>
</event>
<event name="jdk.SafepointCleanupTask">
  <setting name="enabled">false</setting>
  <setting name="threshold">10 ms</setting>
</event>
<event name="jdk.SafepointEnd">
  <setting name="enabled">false</setting>
  <setting name="threshold">10 ms</setting>
</event>
<event name="jdk.ExecuteVMOperation">
  <setting name="enabled">true</setting>
  <setting name="threshold">10 ms</setting>
</event>
<event name="jdk.Shutdown">
  <setting name="enabled">true</setting>
  <setting name="stackTrace">true</setting>
</event>
<event name="jdk.ThreadDump">
  <setting name="enabled" control="thread-dump-
enabled">true</setting>
  <setting name="period" control="thread-dump-
interval">everyChunk</setting>
</event>
<event name="jdk.IntFlag">
  <setting name="enabled">true</setting>
  <setting name="period">beginChunk</setting>
</event>
<event name="jdk.UnsignedIntFlag">
  <setting name="enabled">true</setting>
  <setting name="period">beginChunk</setting>
</event>
<event name="jdk.LongFlag">
  <setting name="enabled">true</setting>
  <setting name="period">beginChunk</setting>
</event>
<event name="jdk.UnsignedLongFlag">
  <setting name="enabled">true</setting>
  <setting name="period">beginChunk</setting>
</event>
<event name="jdk.DoubleFlag">
  <setting name="enabled">true</setting>
  <setting name="period">beginChunk</setting>
</event>
<event name="jdk.BooleanFlag">
  <setting name="enabled">true</setting>
  <setting name="period">beginChunk</setting>
</event>
<event name="jdk.StringFlag">
  <setting name="enabled">true</setting>
  <setting name="period">beginChunk</setting>
</event>
<event name="jdk.IntFlagChanged">
  <setting name="enabled">true</setting>
</event>
<event name="jdk.UnsignedIntFlagChanged">
  <setting name="enabled">true</setting>
</event>
<event name="jdk.LongFlagChanged">
  <setting name="enabled">true</setting>
</event>
<event name="jdk.UnsignedLongFlagChanged">
  <setting name="enabled">true</setting>
</event>
<event name="jdk.DoubleFlagChanged">
  <setting name="enabled">true</setting>
</event>
<event name="jdk.BooleanFlagChanged">
  <setting name="enabled">true</setting>
</event>
<event name="jdk.StringFlagChanged">
  <setting name="enabled">true</setting>
</event>
<event name="jdk.ObjectCount">
  <setting name="enabled" control="memory-profiling-enabled-
all">false</setting>
  <setting name="period">everyChunk</setting>
</event>
<event name="jdk.GCConfiguration">
  <setting name="enabled" control="gc-enabled-
normal">true</setting>
  <setting name="period">everyChunk</setting>
</event>
<event name="jdk.GCHeapConfiguration">
  <setting name="enabled" control="gc-enabled-
normal">true</setting>
  <setting name="period">beginChunk</setting>
</event>
<event name="jdk.YoungGenerationConfiguration">

```

```

    <setting name="enabled" control="gc-enabled-normal">true</setting>
    <setting name="period">beginChunk</setting>
  </event>

  <event name="jdk.GCTLABConfiguration">
    <setting name="enabled" control="gc-enabled-normal">true</setting>
    <setting name="period">beginChunk</setting>
  </event>

  <event name="jdk.GCSurvivorConfiguration">
    <setting name="enabled" control="gc-enabled-normal">true</setting>
    <setting name="period">beginChunk</setting>
  </event>

  <event name="jdk.ObjectCountAfterGC">
    <setting name="enabled">false</setting>
  </event>

  <event name="jdk.GCHeapSummary">
    <setting name="enabled" control="gc-enabled-normal">true</setting>
  </event>

  <event name="jdk.PSHeapSummary">
    <setting name="enabled" control="gc-enabled-normal">true</setting>
  </event>

  <event name="jdk.G1HeapSummary">
    <setting name="enabled" control="gc-enabled-normal">true</setting>
  </event>

  <event name="jdk.MetaspaceSummary">
    <setting name="enabled" control="gc-enabled-normal">true</setting>
  </event>

  <event name="jdk.MetaspaceGCThreshold">
    <setting name="enabled" control="gc-enabled-normal">true</setting>
  </event>

  <event name="jdk.MetaspaceAllocationFailure">
    <setting name="enabled" control="gc-enabled-normal">true</setting>
    <setting name="stackTrace">true</setting>
  </event>

  <event name="jdk.MetaspaceOOM">
    <setting name="enabled" control="gc-enabled-normal">true</setting>
    <setting name="stackTrace">true</setting>
  </event>

  <event name="jdk.MetaspaceChunkFreeListSummary">
    <setting name="enabled" control="gc-enabled-normal">true</setting>
  </event>

  <event name="jdk.GarbageCollection">
    <setting name="enabled" control="gc-enabled-normal">true</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.ParallelOldGarbageCollection">
    <setting name="enabled" control="gc-enabled-normal">true</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.YoungGarbageCollection">
    <setting name="enabled" control="gc-enabled-normal">true</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.OldGarbageCollection">
    <setting name="enabled" control="gc-enabled-normal">true</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.G1GarbageCollection">
    <setting name="enabled" control="gc-enabled-normal">true</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.GCPhasePause">
    <setting name="enabled" control="gc-enabled-normal">true</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.GCPhasePauseLevel1">
    <setting name="enabled" control="gc-enabled-normal">true</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.GCPhasePauseLevel2">
    <setting name="enabled" control="gc-enabled-normal">true</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.GCPhasePauseLevel3">
    <setting name="enabled" control="gc-enabled-all">false</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.GCPhasePauseLevel4">
    <setting name="enabled" control="gc-enabled-all">false</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.GCPhaseConcurrent">
    <setting name="enabled" control="gc-enabled-all">true</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.GCReferenceStatistics">
    <setting name="enabled" control="gc-enabled-normal">true</setting>
  </event>

  <event name="jdk.PromotionFailed">
    <setting name="enabled" control="gc-enabled-normal">true</setting>
  </event>

  <event name="jdk.EvacuationFailed">
    <setting name="enabled" control="gc-enabled-

```

```

normal">true</setting>
</event>

<event name="jdk.EvacuationInformation">
<setting name="enabled" control="gc-enabled-
normal">true</setting>
</event>

<event name="jdk.G1MMU">
<setting name="enabled" control="gc-enabled-
normal">true</setting>
</event>

<event name="jdk.G1EvacuationYoungStatistics">
<setting name="enabled" control="gc-enabled-
normal">true</setting>
</event>

<event name="jdk.G1EvacuationOldStatistics">
<setting name="enabled" control="gc-enabled-
normal">true</setting>
</event>

<event name="jdk.G1BasicHOP">
<setting name="enabled" control="gc-enabled-
normal">true</setting>
</event>

<event name="jdk.G1AdaptiveHOP">
<setting name="enabled" control="gc-enabled-
normal">true</setting>
</event>

<event name="jdk.PromoteObjectInNewPLAB">
<setting name="enabled" control="memory-profiling-enabled-
medium">false</setting>
</event>

<event name="jdk.PromoteObjectOutsidePLAB">
<setting name="enabled" control="memory-profiling-enabled-
medium">false</setting>
</event>

<event name="jdk.ConcurrentModeFailure">
<setting name="enabled" control="gc-enabled-
normal">true</setting>
</event>

<event name="jdk.AllocationRequiringGC">
<setting name="enabled" control="gc-enabled-all">false</setting>
<setting name="stackTrace">true</setting>
</event>

<event name="jdk.TenuringDistribution">
<setting name="enabled" control="gc-enabled-
normal">true</setting>
</event>

<event name="jdk.G1HeapRegionInformation">
<setting name="enabled" control="gc-enabled-all">false</setting>
<setting name="period">everyChunk</setting>
</event>

<event name="jdk.G1HeapRegionTypeChange">
<setting name="enabled" control="gc-enabled-all">false</setting>
</event>

<event name="jdk.OldObjectSample">
<setting name="enabled" control="memory-leak-detection-
enabled">true</setting>
<setting name="stackTrace" control="memory-leak-detection-
stack-trace">false</setting>
<setting name="cutoff" control="memory-leak-detection-cutoff">0
ns</setting>
</event>

<event name="jdk.CompilerConfiguration">
<setting name="enabled" control="compiler-
enabled">true</setting>
<setting name="period">beginChunk</setting>
</event>

<event name="jdk.CompilerStatistics">
<setting name="enabled" control="compiler-
enabled">true</setting>
<setting name="period">1000 ms</setting>
</event>

<event name="jdk.Compilation">
<setting name="enabled" control="compiler-
enabled">true</setting>
<setting name="threshold" control="compiler-compilation-
threshold">1000 ms</setting>
</event>

<event name="jdk.CompilerPhase">
<setting name="enabled" control="compiler-
enabled">true</setting>
<setting name="threshold" control="compiler-phase-threshold">60
s</setting>
</event>

<event name="jdk.CompilationFailure">
<setting name="enabled" control="compiler-enabled-
failure">false</setting>
</event>

<event name="jdk.CompilerInlining">
<setting name="enabled" control="compiler-enabled-
failure">false</setting>
</event>

<event name="jdk.CodeSweeperConfiguration">
<setting name="enabled" control="compiler-
enabled">true</setting>
<setting name="period">beginChunk</setting>
</event>

<event name="jdk.CodeSweeperStatistics">
<setting name="enabled" control="compiler-
enabled">true</setting>
<setting name="period">everyChunk</setting>
</event>

<event name="jdk.SweepCodeCache">
<setting name="enabled" control="compiler-
enabled">true</setting>
<setting name="threshold" control="compiler-sweeper-
threshold">100 ms</setting>
</event>

<event name="jdk.CodeCacheConfiguration">
<setting name="enabled" control="compiler-
enabled">true</setting>
<setting name="period">beginChunk</setting>
</event>

<event name="jdk.CodeCacheStatistics">

```

```

    <setting name="enabled" control="compiler-
enabled">true</setting>
    <setting name="period">everyChunk</setting>
  </event>

  <event name="jdk.CodeCacheFull">
    <setting name="enabled" control="compiler-
enabled">true</setting>
  </event>

  <event name="jdk.OSInformation">
    <setting name="enabled">true</setting>
    <setting name="period">beginChunk</setting>
  </event>

  <event name="jdk.VirtualizationInformation">
    <setting name="enabled">true</setting>
    <setting name="period">beginChunk</setting>
  </event>

  <event name="jdk.CPUInformation">
    <setting name="enabled">true</setting>
    <setting name="period">beginChunk</setting>
  </event>

  <event name="jdk.ThreadContextSwitchRate">
    <setting name="enabled" control="compiler-
enabled">true</setting>
    <setting name="period">10 s</setting>
  </event>

  <event name="jdk.CPULoad">
    <setting name="enabled">true</setting>
    <setting name="period">1000 ms</setting>
  </event>

  <event name="jdk.ThreadCPULoad">
    <setting name="enabled">true</setting>
    <setting name="period">10 s</setting>
  </event>

  <event name="jdk.CPUTimeStampCounter">
    <setting name="enabled">true</setting>
    <setting name="period">beginChunk</setting>
  </event>

  <event name="jdk.SystemProcess">
    <setting name="enabled">true</setting>
    <setting name="period">endChunk</setting>
  </event>

  <event name="jdk.NetworkUtilization">
    <setting name="enabled">true</setting>
    <setting name="period">5 s</setting>
  </event>

  <event name="jdk.InitialEnvironmentVariable">
    <setting name="enabled">true</setting>
    <setting name="period">beginChunk</setting>
  </event>

  <event name="jdk.PhysicalMemory">
    <setting name="enabled">true</setting>
    <setting name="period">everyChunk</setting>
  </event>

  <event name="jdk.ObjectAllocationInNewTLAB">
    <setting name="enabled" control="memory-profiling-enabled-
medium">false</setting>
    <setting name="stackTrace">true</setting>
  </event>

  <event name="jdk.ObjectAllocationOutsideTLAB">
    <setting name="enabled" control="memory-profiling-enabled-
medium">false</setting>
    <setting name="stackTrace">true</setting>
  </event>

  <event name="jdk.NativeLibrary">
    <setting name="enabled">true</setting>
    <setting name="period">everyChunk</setting>
  </event>

  <event name="jdk.ModuleRequire">
    <setting name="enabled">true</setting>
    <setting name="period">endChunk</setting>
  </event>

  <event name="jdk.ModuleExport">
    <setting name="enabled">true</setting>
    <setting name="period">endChunk</setting>
  </event>

  <event name="jdk.FileForce">
    <setting name="enabled">true</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold" control="file-io-threshold">20
ms</setting>
  </event>

  <event name="jdk.FileRead">
    <setting name="enabled">true</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold" control="file-io-threshold">20
ms</setting>
  </event>

  <event name="jdk.FileWrite">
    <setting name="enabled">true</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold" control="file-io-threshold">20
ms</setting>
  </event>

  <event name="jdk.SocketRead">
    <setting name="enabled">true</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold" control="socket-io-threshold">20
ms</setting>
  </event>

  <event name="jdk.SocketWrite">
    <setting name="enabled">true</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold" control="socket-io-threshold">20
ms</setting>
  </event>

  <event name="jdk.SecurityPropertyModification">
    <setting name="enabled">false</setting>
    <setting name="stackTrace">true</setting>
  </event>

  <event name="jdk.TLSHandshake">
    <setting name="enabled">false</setting>
    <setting name="stackTrace">true</setting>
  </event>

```



```

<event name="jdk.X509Validation">
  <setting name="enabled">false</setting>
  <setting name="stackTrace">true</setting>
</event>

<event name="jdk.X509Certificate">
  <setting name="enabled">false</setting>
  <setting name="stackTrace">true</setting>
</event>

<event name="jdk.JavaExceptionThrow">
  <setting name="enabled" control="enable-
exceptions">false</setting>
  <setting name="stackTrace">true</setting>
</event>

<event name="jdk.JavaErrorThrow">
  <setting name="enabled" control="enable-errors">true</setting>
  <setting name="stackTrace">true</setting>
</event>

<event name="jdk.ExceptionStatistics">
  <setting name="enabled">true</setting>
  <setting name="period">1000 ms</setting>
</event>

<event name="jdk.ActiveRecording">
  <setting name="enabled">true</setting>
</event>

<event name="jdk.ActiveSetting">
  <setting name="enabled">true</setting>
</event>

<event name="jdk.DataLoss">
  <setting name="enabled">true</setting>
</event>

<event name="jdk.DumpReason">
  <setting name="enabled">true</setting>
</event>

<event name="jdk.ZPageAllocation">
  <setting name="enabled">true</setting>
  <setting name="threshold">10 ms</setting>
</event>

<event name="jdk.ZThreadPhase">
  <setting name="enabled">true</setting>
  <setting name="threshold">0 ms</setting>
</event>

<event name="jdk.ZStatisticsCounter">
  <setting name="enabled">true</setting>
  <setting name="threshold">10 ms</setting>
</event>

<event name="jdk.ZStatisticsSampler">
  <setting name="enabled">true</setting>
  <setting name="threshold">10 ms</setting>
</event>

```

```

<!--
  Contents of the control element is not read by the JVM, it's used
  by Java Mission Control to change settings that carry the control
  attribute.
-->
<control>
  <selection name="gc-level" default="detailed" label="Garbage
Collector">
    <option label="Off" name="off">off</option>
    <option label="Normal" name="detailed">normal</option>
    <option label="All" name="all">all</option>
  </selection>

  <condition name="gc-enabled-normal" true="true" false="false">
    <or>
      <test name="gc-level" operator="equal" value="normal"/>
      <test name="gc-level" operator="equal" value="all"/>
    </or>
  </condition>

  <condition name="gc-enabled-all" true="true" false="false">
    <test name="gc-level" operator="equal" value="all"/>
  </condition>

  <selection name="memory-profiling" default="off" label="Memory
Profiling">
    <option label="Off" name="off">off</option>
    <option label="Object Allocation and Promotion"
name="medium">medium</option>
    <option label="All, including Heap Statistics (May cause long full
GCs)" name="all">all</option>
  </selection>

  <condition name="memory-profiling-enabled-medium" true="true"
false="false">
    <or>
      <test name="memory-profiling" operator="equal"
value="medium"/>
      <test name="memory-profiling" operator="equal" value="all"/>
    </or>
  </condition>

  <condition name="memory-profiling-enabled-all" true="true"
false="false">
    <test name="memory-profiling" operator="equal" value="all"/>
  </condition>

  <selection name="compiler-level" default="normal"

```

```

label="Compiler">
  <option label="Off" name="off">off</option>
  <option label="Normal" name="normal">normal</option>
  <option label="Detailed" name="detailed">detailed</option>
  <option label="All" name="all">all</option>
</selection>

<condition name="compiler-enabled" true="false" false="true">
  <test name="compiler-level" operator="equal" value="off"/>
</condition>

<condition name="compiler-enabled-failure" true="true"
false="false">
  <or>
    <test name="compiler-level" operator="equal" value="detailed"/>
    <test name="compiler-level" operator="equal" value="all"/>
  </or>
</condition>

<condition name="compiler-sweeper-threshold" true="0 ms"
false="100 ms">
  <test name="compiler-level" operator="equal" value="all"/>
</condition>

<condition name="compiler-compilation-threshold" true="1000
ms">
  <test name="compiler-level" operator="equal" value="normal"/>
</condition>

<condition name="compiler-compilation-threshold" true="100 ms">
  <test name="compiler-level" operator="equal" value="detailed"/>
</condition>

<condition name="compiler-compilation-threshold" true="0 ms">
  <test name="compiler-level" operator="equal" value="all"/>
</condition>

<condition name="compiler-phase-threshold" true="60 s">
  <test name="compiler-level" operator="equal" value="normal"/>
</condition>

<condition name="compiler-phase-threshold" true="10 s">
  <test name="compiler-level" operator="equal" value="detailed"/>
</condition>

<condition name="compiler-phase-threshold" true="0 s">
  <test name="compiler-level" operator="equal" value="all"/>
</condition>

<selection name="method-sampling-interval" default="normal"
label="Method Sampling">
  <option label="Off" name="off">off</option>
  <option label="Normal" name="normal">normal</option>
  <option label="High" name="high">high</option>
  <option label="Ludicrous (High Overhead)"
name="ludicrous">ludicrous</option>
</selection>

<condition name="method-sampling-java-interval" true="999 d">
  <test name="method-sampling-interval" operator="equal"
value="off"/>
</condition>

<condition name="method-sampling-java-interval" true="20 ms">
  <test name="method-sampling-interval" operator="equal"
value="normal"/>
</condition>

<condition name="method-sampling-java-interval" true="10 ms">
  <test name="method-sampling-interval" operator="equal"
value="high"/>
</condition>

<condition name="method-sampling-java-interval" true="1 ms">
  <test name="method-sampling-interval" operator="equal"
value="ludicrous"/>
</condition>

<condition name="method-sampling-native-interval" true="999 d">
  <test name="method-sampling-interval" operator="equal"
value="off"/>
</condition>

<condition name="method-sampling-native-interval" true="20 ms">
  <or>
    <test name="method-sampling-interval" operator="equal"
value="normal"/>
    <test name="method-sampling-interval" operator="equal"
value="high"/>
    <test name="method-sampling-interval" operator="equal"
value="ludicrous"/>
  </or>
</condition>

<condition name="method-sampling-enabled" true="false"
false="true">
  <test name="method-sampling-interval" operator="equal"
value="off"/>
</condition>

<selection name="thread-dump-interval" default="normal"
label="Thread Dump">
  <option label="Off" name="off">999 d</option>
  <option label="At least Once"
name="normal">everyChunk</option>
  <option label="Every 60 s" name="everyMinute">60 s</option>
  <option label="Every 10 s" name="everyTenSecond">10
s</option>
  <option label="Every 1 s" name="everySecond">1 s</option>
</selection>

<condition name="thread-dump-enabled" true="false" false="true">
  <test name="thread-dump-interval" operator="equal" value="999
d"/>
</condition>

<selection name="exception-level" default="errors"
label="Exceptions">
  <option label="Off" name="off">off</option>
  <option label="Errors Only" name="errors">errors</option>
  <option label="All Exceptions, including Errors"
name="all">all</option>
</selection>

<condition name="enable-errors" true="true" false="false">
  <or>
    <test name="exception-level" operator="equal" value="errors"/>
    <test name="exception-level" operator="equal" value="all"/>
  </or>
</condition>

<condition name="enable-exceptions" true="true" false="false">
  <test name="exception-level" operator="equal" value="all"/>
</condition>

<selection name="memory-leak-detection" default="minimal"
label="Memory Leak Detection">
  <option label="Off" name="off">off</option>

```

```

<option label="Object Types" name="minimal">minimal</option>
<option label="Object Types + Allocation Stack Traces"
name="medium">medium</option>
<option label="Object Types + Allocation Stack Traces + Path to
GC Root" name="full">full</option>
</selection>

<condition name="memory-leak-detection-enabled" true="false"
false="true">
<test name="memory-leak-detection" operator="equal"
value="off"/>
</condition>

<condition name="memory-leak-detection-stack-trace" true="true"
false="false">
<or>
<test name="memory-leak-detection" operator="equal"
value="medium"/>
<test name="memory-leak-detection" operator="equal"
value="full"/>
</or>
</condition>

<condition name="memory-leak-detection-cutoff" true="1 h"
false="0 ns">
<test name="memory-leak-detection" operator="equal"
value="full"/>
</condition>

<text name="synchronization-threshold" label="Synchronization
Threshold" contentType="timespan" minimum="0 s">20 ms</text>

<text name="file-io-threshold" label="File I/O Threshold"
contentType="timespan" minimum="0 s">20 ms</text>

<text name="socket-io-threshold" label="Socket I/O Threshold"
contentType="timespan" minimum="0 s">20 ms</text>

<flag name="class-loading-enabled" label="Class
Loading">false</flag>

</control>

</configuration>
, description=Low overhead configuration safe for continuous use in
production environments, typically less than 1 % overhead.,
label=Continuous, name=default, provider=Oracle,
settings={
{key=jdk.ThreadAllocationStatistics#enabled, value=true},
{key=jdk.ThreadAllocationStatistics#period, value=everyChunk},
{key=jdk.ClassLoadingStatistics#enabled, value=true},
{key=jdk.ClassLoadingStatistics#period, value=1000 ms},
{key=jdk.ClassLoaderStatistics#enabled, value=true},
{key=jdk.ClassLoaderStatistics#period, value=everyChunk},
{key=jdk.JavaThreadStatistics#enabled, value=true},
{key=jdk.JavaThreadStatistics#period, value=1000 ms},
{key=jdk.ThreadStart#enabled, value=true},
{key=jdk.ThreadEnd#enabled, value=true},
{key=jdk.ThreadSleep#enabled, value=true},
{key=jdk.ThreadSleep#stackTrace, value=true},
{key=jdk.ThreadSleep#threshold, value=20 ms},
{key=jdk.ThreadPark#enabled, value=true},
{key=jdk.ThreadPark#stackTrace, value=true},
{key=jdk.ThreadPark#threshold, value=20 ms},
{key=jdk.JavaMonitorEnter#enabled, value=true},
{key=jdk.JavaMonitorEnter#stackTrace, value=true},
{key=jdk.JavaMonitorEnter#threshold, value=20 ms},
{key=jdk.JavaMonitorWait#enabled, value=true},
{key=jdk.JavaMonitorWait#stackTrace, value=true},
{key=jdk.JavaMonitorWait#threshold, value=20 ms},
{key=jdk.JavaMonitorInflate#enabled, value=false},
{key=jdk.JavaMonitorInflate#stackTrace, value=true},
{key=jdk.JavaMonitorInflate#threshold, value=20 ms},
{key=jdk.BiasedLockRevocation#enabled, value=true},
{key=jdk.BiasedLockRevocation#stackTrace, value=true},
{key=jdk.BiasedLockRevocation#threshold, value=0 ms},
{key=jdk.BiasedLockSelfRevocation#enabled, value=true},
{key=jdk.BiasedLockSelfRevocation#stackTrace, value=true},
{key=jdk.BiasedLockSelfRevocation#threshold, value=0 ms},
{key=jdk.BiasedLockClassRevocation#enabled, value=true},
{key=jdk.BiasedLockClassRevocation#stackTrace, value=true},
{key=jdk.BiasedLockClassRevocation#threshold, value=0 ms},
{key=jdk.ReservedStackActivation#enabled, value=true},
{key=jdk.ReservedStackActivation#stackTrace, value=true},
{key=jdk.ClassLoad#enabled, value=false},
{key=jdk.ClassLoad#stackTrace, value=true},
{key=jdk.ClassLoad#threshold, value=0 ms},
{key=jdk.ClassDefine#enabled, value=false},
{key=jdk.ClassDefine#stackTrace, value=true},
{key=jdk.ClassUnload#enabled, value=false},
{key=jdk.JVMInformation#enabled, value=true},
{key=jdk.JVMInformation#period, value=beginChunk},
{key=jdk.InitialSystemProperty#enabled, value=true},
{key=jdk.InitialSystemProperty#period, value=beginChunk},
{key=jdk.ExecutionSample#enabled, value=true},
{key=jdk.ExecutionSample#period, value=20 ms},
{key=jdk.NativeMethodSample#enabled, value=true},
{key=jdk.NativeMethodSample#period, value=20 ms},
{key=jdk.SafePointBegin#enabled, value=true},
{key=jdk.SafePointBegin#threshold, value=10 ms},
{key=jdk.SafePointStateSynchronization#enabled, value=false},
{key=jdk.SafePointStateSynchronization#threshold, value=10 ms},
{key=jdk.SafePointWaitBlocked#enabled, value=false},
{key=jdk.SafePointWaitBlocked#threshold, value=10 ms},
{key=jdk.SafePointCleanup#enabled, value=false},
{key=jdk.SafePointCleanup#threshold, value=10 ms},
{key=jdk.SafePointCleanupTask#enabled, value=false},
{key=jdk.SafePointCleanupTask#threshold, value=10 ms},
{key=jdk.SafePointEnd#enabled, value=false},
{key=jdk.SafePointEnd#threshold, value=10 ms},
{key=jdk.ExecuteVMOperation#enabled, value=true},
{key=jdk.ExecuteVMOperation#threshold, value=10 ms},
{key=jdk.Shutdown#enabled, value=true},
{key=jdk.Shutdown#stackTrace, value=true},
{key=jdk.ThreadDump#enabled, value=true},
{key=jdk.ThreadDump#period, value=everyChunk},
{key=jdk.IntFlag#enabled, value=true}, {key=jdk.IntFlag#period,
value=beginChunk}, {key=jdk.UnsignedIntFlag#enabled, value=true},
{key=jdk.UnsignedIntFlag#period, value=beginChunk},
{key=jdk.LongFlag#enabled, value=true}, {key=jdk.LongFlag#period,
value=beginChunk}, {key=jdk.UnsignedLongFlag#enabled,
value=true}, {key=jdk.UnsignedLongFlag#period, value=beginChunk},
{key=jdk.DoubleFlag#enabled, value=true},
{key=jdk.DoubleFlag#period, value=beginChunk},
{key=jdk.BooleanFlag#enabled, value=true},
{key=jdk.BooleanFlag#period, value=beginChunk},
{key=jdk.StringFlag#enabled, value=true}, {key=jdk.StringFlag#period,
value=beginChunk}, {key=jdk.IntFlagChanged#enabled, value=true},
{key=jdk.UnsignedIntFlagChanged#enabled, value=true},
{key=jdk.LongFlagChanged#enabled, value=true},
{key=jdk.UnsignedLongFlagChanged#enabled, value=true},
{key=jdk.DoubleFlagChanged#enabled, value=true},
{key=jdk.BooleanFlagChanged#enabled, value=true},
{key=jdk.StringFlagChanged#enabled, value=true},
{key=jdk.ObjectCount#enabled, value=false},
{key=jdk.ObjectCount#period, value=everyChunk},
{key=jdk.GCConfiguration#enabled, value=true},
{key=jdk.GCConfiguration#period, value=everyChunk},
{key=jdk.GCHeapConfiguration#enabled, value=true},

```

```

{key=jdk.GCHeapConfiguration#period, value=beginChunk},
{key=jdk.YoungGenerationConfiguration#enabled, value=true},
{key=jdk.YoungGenerationConfiguration#period, value=beginChunk},
{key=jdk.GCTLABConfiguration#enabled, value=true},
{key=jdk.GCTLABConfiguration#period, value=beginChunk},
{key=jdk.GCSurvivorConfiguration#enabled, value=true},
{key=jdk.GCSurvivorConfiguration#period, value=beginChunk},
{key=jdk.ObjectCountAfterGC#enabled, value=false},
{key=jdk.GCHeapSummary#enabled, value=true},
{key=jdk.PSHeapSummary#enabled, value=true},
{key=jdk.G1HeapSummary#enabled, value=true},
{key=jdk.MetaspaceSummary#enabled, value=true},
{key=jdk.MetaspaceGCThreshold#enabled, value=true},
{key=jdk.MetaspaceAllocationFailure#enabled, value=true},
{key=jdk.MetaspaceAllocationFailure#stackTrace, value=true},
{key=jdk.MetaspaceOOM#enabled, value=true},
{key=jdk.MetaspaceOOM#stackTrace, value=true},
{key=jdk.MetaspaceChunkFreeListSummary#enabled, value=true},
{key=jdk.GarbageCollection#enabled, value=true},
{key=jdk.GarbageCollection#threshold, value=0 ms},
{key=jdk.ParallelOldGarbageCollection#enabled, value=true},
{key=jdk.ParallelOldGarbageCollection#threshold, value=0 ms},
{key=jdk.YoungGarbageCollection#enabled, value=true},
{key=jdk.YoungGarbageCollection#threshold, value=0 ms},
{key=jdk.OldGarbageCollection#enabled, value=true},
{key=jdk.OldGarbageCollection#threshold, value=0 ms},
{key=jdk.G1GarbageCollection#enabled, value=true},
{key=jdk.G1GarbageCollection#threshold, value=0 ms},
{key=jdk.GCPhasePause#enabled, value=true},
{key=jdk.GCPhasePause#threshold, value=0 ms},
{key=jdk.GCPhasePauseLevel1#enabled, value=true},
{key=jdk.GCPhasePauseLevel1#threshold, value=0 ms},
{key=jdk.GCPhasePauseLevel2#enabled, value=true},
{key=jdk.GCPhasePauseLevel2#threshold, value=0 ms},
{key=jdk.GCPhasePauseLevel3#enabled, value=false},
{key=jdk.GCPhasePauseLevel3#threshold, value=0 ms},
{key=jdk.GCPhasePauseLevel4#enabled, value=false},
{key=jdk.GCPhasePauseLevel4#threshold, value=0 ms},
{key=jdk.GCPhaseConcurrent#enabled, value=true},
{key=jdk.GCPhaseConcurrent#threshold, value=0 ms},
{key=jdk.GCReferenceStatistics#enabled, value=true},
{key=jdk.PromotionFailed#enabled, value=true},
{key=jdk.EvacuationFailed#enabled, value=true},
{key=jdk.EvacuationInformation#enabled, value=true},
{key=jdk.G1MMU#enabled, value=true},
{key=jdk.G1EvacuationYoungStatistics#enabled, value=true},
{key=jdk.G1EvacuationOldStatistics#enabled, value=true},
{key=jdk.G1BasicHOP#enabled, value=true},
{key=jdk.G1AdaptiveHOP#enabled, value=true},
{key=jdk.PromoteObjectInNewTLAB#enabled, value=false},
{key=jdk.PromoteObjectOutsideTLAB#enabled, value=false},
{key=jdk.ConcurrentModeFailure#enabled, value=true},
{key=jdk.AllocationRequiringGC#enabled, value=false},
{key=jdk.AllocationRequiringGC#stackTrace, value=true},
{key=jdk.TenuringDistribution#enabled, value=true},
{key=jdk.G1HeapRegionInformation#enabled, value=false},
{key=jdk.G1HeapRegionInformation#period, value=everyChunk},
{key=jdk.G1HeapRegionTypeChange#enabled, value=false},
{key=jdk.OldObjectSample#enabled, value=true},
{key=jdk.OldObjectSample#stackTrace, value=false},
{key=jdk.OldObjectSample#cutoff, value=0 ns},
{key=jdk.CompilerConfiguration#enabled, value=true},
{key=jdk.CompilerConfiguration#period, value=beginChunk},
{key=jdk.CompilerStatistics#enabled, value=true},
{key=jdk.CompilerStatistics#period, value=1000 ms},
{key=jdk.Compilation#enabled, value=true},
{key=jdk.Compilation#threshold, value=1000 ms},
{key=jdk.CompilerPhase#enabled, value=true},
{key=jdk.CompilerPhase#threshold, value=60 s},
{key=jdk.CompilationFailure#enabled, value=false},
{key=jdk.CompilerInlining#enabled, value=false},
{key=jdk.CodeSweeperConfiguration#enabled, value=true},
{key=jdk.CodeSweeperConfiguration#period, value=beginChunk},
{key=jdk.CodeSweeperStatistics#enabled, value=true},
{key=jdk.CodeSweeperStatistics#period, value=everyChunk},
{key=jdk.SweepCodeCache#enabled, value=true},
{key=jdk.SweepCodeCache#threshold, value=100 ms},
{key=jdk.CodeCacheConfiguration#enabled, value=true},
{key=jdk.CodeCacheConfiguration#period, value=beginChunk},
{key=jdk.CodeCacheStatistics#enabled, value=true},
{key=jdk.CodeCacheStatistics#period, value=everyChunk},
{key=jdk.CodeCacheFull#enabled, value=true},
{key=jdk.OSInformation#enabled, value=true},
{key=jdk.OSInformation#period, value=beginChunk},
{key=jdk.VirtualizationInformation#enabled, value=true},
{key=jdk.VirtualizationInformation#period, value=beginChunk},
{key=jdk.CPUInformation#enabled, value=true},
{key=jdk.CPUInformation#period, value=beginChunk},
{key=jdk.ThreadContextSwitchRate#enabled, value=true},
{key=jdk.ThreadContextSwitchRate#period, value=10 s},
{key=jdk.CPULoad#enabled, value=true}, {key=jdk.CPULoad#period, value=1000 ms}, {key=jdk.ThreadCPULoad#enabled, value=true},
{key=jdk.ThreadCPULoad#period, value=10 s},
{key=jdk.CPUTimeStampCounter#enabled, value=true},
{key=jdk.CPUTimeStampCounter#period, value=beginChunk},
{key=jdk.SystemProcess#enabled, value=true},
{key=jdk.SystemProcess#period, value=endChunk},
{key=jdk.NetworkUtilization#enabled, value=true},
{key=jdk.NetworkUtilization#period, value=5 s},
{key=jdk.InitialEnvironmentVariable#enabled, value=true},
{key=jdk.InitialEnvironmentVariable#period, value=beginChunk},
{key=jdk.PhysicalMemory#enabled, value=true},
{key=jdk.PhysicalMemory#period, value=everyChunk},
{key=jdk.ObjectAllocationInNewTLAB#enabled, value=false},
{key=jdk.ObjectAllocationInNewTLAB#stackTrace, value=true},
{key=jdk.ObjectAllocationOutsideTLAB#enabled, value=false},
{key=jdk.ObjectAllocationOutsideTLAB#stackTrace, value=true},
{key=jdk.NativeLibrary#enabled, value=true},
{key=jdk.NativeLibrary#period, value=everyChunk},
{key=jdk.ModuleRequire#enabled, value=true},
{key=jdk.ModuleRequire#period, value=endChunk},
{key=jdk.ModuleExport#enabled, value=true},
{key=jdk.ModuleExport#period, value=endChunk},
{key=jdk.FileForce#enabled, value=true},
{key=jdk.FileForce#stackTrace, value=true},
{key=jdk.FileForce#threshold, value=20 ms},
{key=jdk.FileRead#enabled, value=true},
{key=jdk.FileRead#stackTrace, value=true},
{key=jdk.FileRead#threshold, value=20 ms},
{key=jdk.FileWrite#enabled, value=true},
{key=jdk.FileWrite#stackTrace, value=true},
{key=jdk.FileWrite#threshold, value=20 ms},
{key=jdk.SocketRead#enabled, value=true},
{key=jdk.SocketRead#stackTrace, value=true},
{key=jdk.SocketRead#threshold, value=20 ms},
{key=jdk.SocketWrite#enabled, value=true},
{key=jdk.SocketWrite#stackTrace, value=true},
{key=jdk.SocketWrite#threshold, value=20 ms},
{key=jdk.SecurityPropertyModification#enabled, value=false},
{key=jdk.SecurityPropertyModification#stackTrace, value=true},
{key=jdk.TLSHandshake#enabled, value=false},
{key=jdk.TLSHandshake#stackTrace, value=true},
{key=jdk.X509Validation#enabled, value=false},
{key=jdk.X509Validation#stackTrace, value=true},
{key=jdk.X509Certificate#enabled, value=false},
{key=jdk.X509Certificate#stackTrace, value=true},
{key=jdk.JavaExceptionThrow#enabled, value=false},
{key=jdk.JavaExceptionThrow#stackTrace, value=true},

```

```
{key=jdk.JavaErrorThrow#enabled, value=true},  
{key=jdk.JavaErrorThrow#stackTrace, value=true},  
{key=jdk.ExceptionStatistics#enabled, value=true},  
{key=jdk.ExceptionStatistics#period, value=1000 ms},  
{key=jdk.ActiveRecording#enabled, value=true},  
{key=jdk.ActiveSetting#enabled, value=true},  
{key=jdk.DataLoss#enabled, value=true},  
{key=jdk.DumpReason#enabled, value=true},  
{key=jdk.ZPageAllocation#enabled, value=true},  
{key=jdk.ZPageAllocation#threshold, value=10 ms},  
{key=jdk.ZThreadPhase#enabled, value=true},  
{key=jdk.ZThreadPhase#threshold, value=0 ms},  
{key=jdk.ZStatisticsCounter#enabled, value=true},  
{key=jdk.ZStatisticsCounter#threshold, value=10 ms},  
{key=jdk.ZStatisticsSampler#enabled, value=true},  
{key=jdk.ZStatisticsSampler#threshold, value=10 ms}}]]]]
```

EventTypes

```

[[categoryNames=[Java Development Kit, Security],
description=Modification of Security property, id=9187, label=Security
Property Modification, name=jdk.SecurityPropertyModification,
settingDescriptors=[[contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled],
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold},
{contentType=jdk.jfr.BooleanField, defaultValue=false,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}]],
{categoryNames=[Java Development Kit, Security],
description=Parameters used in TLS Handshake, id=8539, label=TLS
Handshake, name=jdk.TLSHandshake,
settingDescriptors=[[contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled],
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold},
{contentType=jdk.jfr.BooleanField, defaultValue=false,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}]],
{categoryNames=[Java Development Kit, Security], description=Serial
numbers from X.509 Certificates forming chain of trust, id=8450,
label=X509 Validation, name=jdk.X509Validation,
settingDescriptors=[[contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled],
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold},
{contentType=jdk.jfr.BooleanField, defaultValue=false,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}]],
{categoryNames=[Java Development Kit, Security], description=Details
of X.509 Certificate parsed by JDK, id=7898, label=X509 Certificate,
name=jdk.X509Certificate,
settingDescriptors=[[contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled],
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold},
{contentType=jdk.jfr.BooleanField, defaultValue=false,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}]],
{categoryNames=[Flight Recorder], description=null, id=9185,
label=Flight Recording, name=jdk.ActiveRecording,
settingDescriptors=[[contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled],
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold},
{contentType=jdk.jfr.BooleanField, defaultValue=false,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}]],
{categoryNames=[Flight Recorder], description=null, id=9183,
label=Recording Setting, name=jdk.ActiveSetting,
settingDescriptors=[[contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled],
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold},
{contentType=jdk.jfr.BooleanField, defaultValue=false,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}]],
{categoryNames=[Java Application], description=An object derived
from java.lang.Error has been created. OutOfMemoryErrors are
ignored, id=9181, label=Java Error, name=jdk.JavaErrorThrow,
settingDescriptors=[[contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled],
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold},
{contentType=jdk.jfr.BooleanField, defaultValue=false,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}]],
{categoryNames=[Java Application, Statistics], description=Number of
objects derived from java.lang.Throwable that have been created,
id=9179, label=Exception Statistics, name=jdk.ExceptionStatistics,
settingDescriptors=[[contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled], {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]],
{categoryNames=[Java Application], description=An object derived
from java.lang.Exception has been created, id=9177, label=Java
Exception, name=jdk.JavaExceptionThrow,
settingDescriptors=[[contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled],
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold},
{contentType=jdk.jfr.BooleanField, defaultValue=false,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}]],
{categoryNames=[Java Application], description=Writing data to a
socket, id=9175, label=Socket Write, name=jdk.SocketWrite,
settingDescriptors=[[contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled],
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold},
{contentType=jdk.jfr.BooleanField, defaultValue=false,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}]],
{categoryNames=[Java Application], description=Reading data from a
socket, id=9173, label=Socket Read, name=jdk.SocketRead,
settingDescriptors=[[contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled],
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold},
{contentType=jdk.jfr.BooleanField, defaultValue=false,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}]],
{categoryNames=[Java Application], description=Writing data to a file,
id=9171, label=File Write, name=jdk.FileWrite,
settingDescriptors=[[contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled],
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold},
{contentType=jdk.jfr.BooleanField, defaultValue=false,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}]],
{categoryNames=[Java Application], description=Reading data from a
file, id=9169, label=File Read, name=jdk.FileRead,
settingDescriptors=[[contentType=jdk.jfr.BooleanField,

```

```

defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled),
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold),
{contentType=jdk.jfr.BooleanField, defaultValue=false,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}},
{categoryNames=Java Application, description=Force updates to be
written to file, id=9167, label=File Force, name=jdk.FileForce,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled),
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold),
{contentType=jdk.jfr.BooleanField, defaultValue=false,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}},
{categoryNames=Java Application, description=null, id=255,
label=Java Thread Start, name=jdk.ThreadStart,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled)},
{categoryNames=Java Application, description=null, id=256,
label=Java Thread End, name=jdk.ThreadEnd,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled)},
{categoryNames=Java Application, description=null, id=257,
label=Java Thread Sleep, name=jdk.ThreadSleep,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled),
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold),
{contentType=jdk.jfr.BooleanField, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}},
{categoryNames=Java Application, description=null, id=259,
label=Java Monitor Blocked, name=jdk.JavaMonitorEnter,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled),
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold),
{contentType=jdk.jfr.BooleanField, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}},
{categoryNames=Java Application, description=null, id=261,
label=Java Monitor Inflated, name=jdk.JavaMonitorInflate,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled),
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold),
{contentType=jdk.jfr.BooleanField, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}},
{categoryNames=Java Virtual Machine, Runtime,
description=Revoked bias of object, id=262, label=Biased Lock
Revocation, name=jdk.BiasedLockRevocation,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled),
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold),
{contentType=jdk.jfr.BooleanField, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}},
{categoryNames=Java Virtual Machine, Runtime,
description=Revoked bias of object biased towards own thread,
id=263, label=Biased Lock Self Revocation,
name=jdk.BiasedLockSelfRevocation,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled),
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold),
{contentType=jdk.jfr.BooleanField, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}},
{categoryNames=Java Virtual Machine, Runtime,
description=Revoked biases for all instances of a class, id=264,
label=Biased Lock Class Revocation,
name=jdk.BiasedLockClassRevocation,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled),
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold),
{contentType=jdk.jfr.BooleanField, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}},
{categoryNames=Java Virtual Machine, Class Loading,
description=Activation of Reserved Stack Area caused by stack
overflow with ReservedStackAccess annotated method in call stack,
id=265, label=Reserved Stack Activation,
name=jdk.ReservedStackActivation,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled),
{contentType=jdk.jfr.BooleanField, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}},
{categoryNames=Java Virtual Machine, Class Loading,
description=null, id=266, label=Class Load, name=jdk.ClassLoad,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled),

```

```

{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold},
{contentType=jdk.jfr.BooleanFlag, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}},
{categoryNames=Java Virtual Machine, Class Loading,
description=null, id=267, label=Class Define, name=jdk.ClassDefine,
settingDescriptors=[[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.BooleanFlag, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}}],
{categoryNames=Java Virtual Machine, Class Loading,
description=null, id=268, label=Class Unload, name=jdk.ClassUnload,
settingDescriptors=[[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}}],
{categoryNames=Java Virtual Machine, Flag, description=null,
id=269, label=Int Flag Changed, name=jdk.IntFlagChanged,
settingDescriptors=[[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}}],
{categoryNames=Java Virtual Machine, Flag, description=null,
id=270, label=Unsigned Int Flag Changed,
name=jdk.UnsignedIntFlagChanged,
settingDescriptors=[[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}}],
{categoryNames=Java Virtual Machine, Flag, description=null,
id=271, label=Long Flag Changed, name=jdk.LongFlagChanged,
settingDescriptors=[[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}}],
{categoryNames=Java Virtual Machine, Flag, description=null,
id=272, label=Unsigned Long Flag Changed,
name=jdk.UnsignedLongFlagChanged,
settingDescriptors=[[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}}],
{categoryNames=Java Virtual Machine, Flag, description=null,
id=273, label=Double Flag Changed, name=jdk.DoubleFlagChanged,
settingDescriptors=[[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}}],
{categoryNames=Java Virtual Machine, Flag, description=null,
id=274, label=Boolean Flag Changed,
name=jdk.BooleanFlagChanged,
settingDescriptors=[[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}}],
{categoryNames=Java Virtual Machine, Flag, description=null,
id=275, label=String Flag Changed, name=jdk.StringFlagChanged,
settingDescriptors=[[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}}],
{categoryNames=Java Virtual Machine, GC, Heap, description=null,
id=278, label=Heap Summary, name=jdk.GCHeapSummary,
settingDescriptors=[[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}}],
{categoryNames=Java Virtual Machine, GC, Heap, description=null,
id=280, label=Metaspace Summary, name=jdk.MetaspaceSummary,
settingDescriptors=[[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}}],
{categoryNames=Java Virtual Machine, GC, Metaspace,
description=null, id=281, label=Metaspace GC Threshold,
name=jdk.MetaspaceGCThreshold,
settingDescriptors=[[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}}],
{categoryNames=Java Virtual Machine, GC, Metaspace,
description=null, id=282, label=Metaspace Allocation Failure,
name=jdk.MetaspaceAllocationFailure,
settingDescriptors=[[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.BooleanFlag, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}}],
{categoryNames=Java Virtual Machine, GC, Metaspace,
description=null, id=283, label=Metaspace Out of Memory,
name=jdk.MetaspaceOOM,
settingDescriptors=[[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.BooleanFlag, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}}],
{categoryNames=Java Virtual Machine, GC, Metaspace,
description=null, id=284, label=Metaspace Chunk Free List Summary,
name=jdk.MetaspaceChunkFreeListSummary,
settingDescriptors=[[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}}],
{categoryNames=Java Virtual Machine, GC, Heap, description=null,
id=285, label=Parallel Scavenge Heap Summary,
name=jdk.PSHeapSummary,
settingDescriptors=[[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}}],
{categoryNames=Java Virtual Machine, GC, Heap, description=null,
id=286, label=G1 Heap Summary, name=jdk.G1HeapSummary,
settingDescriptors=[[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}}],
{categoryNames=Java Virtual Machine, GC, Collector,
description=Garbage collection performed by the JVM, id=287,
label=Garbage Collection, name=jdk.GarbageCollection,
settingDescriptors=[[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}}],
{categoryNames=Java Virtual Machine, GC, Collector,
description=Extra information specific to Parallel Old Garbage
Collections, id=288, label=Parallel Old Garbage Collection,
name=jdk.ParallelOldGarbageCollection,
settingDescriptors=[[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}}],
{categoryNames=Java Virtual Machine, GC, Collector,
description=Extra information specific to Young Garbage Collections,
id=289, label=Young Garbage Collection,
name=jdk.YoungGarbageCollection,
settingDescriptors=[[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}}],
{categoryNames=Java Virtual Machine, GC, Collector,

```



```

description=Extra information specific to Old Garbage Collections,
id=290, label=Old Garbage Collection,
name=jdk.OldGarbageCollection,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}},
{categoryNames=Java Virtual Machine, GC, Collector},
description=Extra information specific to G1 Garbage Collections,
id=291, label=G1 Garbage Collection,
name=jdk.G1GarbageCollection,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}},
{categoryNames=Java Virtual Machine, GC, Detailed},
description=null, id=292, label=G1 MMU Information,
name=jdk.G1MMU,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{categoryNames=Java Virtual Machine, GC, Detailed},
description=null, id=293, label=Evacuation Information,
name=jdk.EvacuationInformation,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{categoryNames=Java Virtual Machine, GC, Reference},
description=Total count of processed references during GC, id=294,
label=GC Reference Statistics, name=jdk.GCReferenceStatistics,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{categoryNames=Java Virtual Machine, GC, Detailed},
description=null, id=296, label=Object Count after GC,
name=jdk.ObjectCountAfterGC,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{categoryNames=Java Virtual Machine, GC, Detailed},
description=Memory related evacuation statistics during GC for the
young generation, id=298, label=G1 Evacuation Statistics for Young,
name=jdk.G1EvacuationYoungStatistics,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{categoryNames=Java Virtual Machine, GC, Detailed},
description=Memory related evacuation statistics during GC for the old
generation, id=299, label=G1 Evacuation Memory Statistics for Old,
name=jdk.G1EvacuationOldStatistics,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{categoryNames=Java Virtual Machine, GC, Detailed},
description=Basic statistics related to current IHOP calculation, id=300,
label=G1 Basic IHOP Statistics, name=jdk.G1BasicIHOP,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{categoryNames=Java Virtual Machine, GC, Detailed},
description=Statistics related to current adaptive IHOP calculation,
id=301, label=G1 Adaptive IHOP Statistics,
name=jdk.G1AdaptiveIHOP,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{categoryNames=Java Virtual Machine, GC, Detailed},
description=Object survived scavenge and was copied to a new
Promotion Local Allocation Buffer (PLAB). Supported GCs are Parallel
Scavenge, G1 and CMS with Parallel New. Due to promotion being
done in parallel an object might be reported multiple times as the GC
threads race to copy all objects., id=302, label=Promotion in new
PLAB, name=jdk.PromoteObjectInNewPLAB,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{categoryNames=Java Virtual Machine, GC, Detailed},
description=Object survived scavenge and was copied directly to the
heap. Supported GCs are Parallel Scavenge, G1 and CMS with
Parallel New. Due to promotion being done in parallel an object might
be reported multiple times as the GC threads race to copy all objects.,
id=303, label=Promotion outside PLAB,
name=jdk.PromoteObjectOutsidePLAB,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{categoryNames=Java Virtual Machine, GC, Detailed},
description=Promotion of an object failed, id=304, label=Promotion
Failed, name=jdk.PromotionFailed,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{categoryNames=Java Virtual Machine, GC, Detailed},
description=Evacuation of an object failed, id=305, label=Evacuation
Failed, name=jdk.EvacuationFailed,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{categoryNames=Java Virtual Machine, GC, Detailed},
description=Concurrent Mode failed, id=306, label=Concurrent Mode
Failure, name=jdk.ConcurrentModeFailure,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{categoryNames=Java Virtual Machine, GC, Phases},
description=null, id=307, label=GC Phase Pause,
name=jdk.GCPhasePause,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}},
{categoryNames=Java Virtual Machine, GC, Phases},
description=null, id=308, label=GC Phase Pause Level 1,
name=jdk.GCPhasePauseLevel1,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}},
{categoryNames=Java Virtual Machine, GC, Phases},
description=null, id=309, label=GC Phase Pause Level 2,
name=jdk.GCPhasePauseLevel2,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}},
{categoryNames=Java Virtual Machine, GC, Phases},
description=null, id=310, label=GC Phase Pause Level 3,
name=jdk.GCPhasePauseLevel3,

```

```

settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}},
{categoryNames=Java Virtual Machine, GC, Phases},
description=null, id=311, label=GC Phase Pause Level 4,
name=jdk.GCPhasePauseLevel4,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}},
{categoryNames=Java Virtual Machine, GC, Phases},
description=null, id=312, label=GC Phase Concurrent,
name=jdk.GCPhaseConcurrent,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}},
{categoryNames=Java Virtual Machine, GC, Detailed},
description=null, id=313, label=Allocation Requiring GC,
name=jdk.AllocationRequiringGC,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.BooleanField, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}},
{categoryNames=Java Virtual Machine, GC, Detailed},
description=null, id=314, label=Tenuring Distribution,
name=jdk.TenuringDistribution,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{categoryNames=Java Virtual Machine, GC, Detailed},
description=Information about a G1 heap region type change, id=315,
label=G1 Heap Region Type Change,
name=jdk.G1HeapRegionTypeChange,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}},
{categoryNames=Java Virtual Machine, Compiler}, description=null,
id=316, label=Compilation, name=jdk.Compilation,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}},
{categoryNames=Java Virtual Machine, Compiler}, description=null,
id=317, label=Compiler Phase, name=jdk.CompilerPhase,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}},
{categoryNames=Java Virtual Machine, Compiler}, description=null,
id=318, label=Compilation Failure, name=jdk.CompilationFailure,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}},
{categoryNames=Java Virtual Machine, Compiler, Optimization},
description=null, id=320, label=Method Inlining,
name=jdk.CompilerInlining,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}},
{categoryNames=Java Virtual Machine, Code Sweeper},
description=null, id=321, label=Sweep Code Cache,
name=jdk.SweepCodeCache,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}},
{categoryNames=Java Virtual Machine, Code Cache},
description=null, id=322, label=Code Cache Full,
name=jdk.CodeCacheFull,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}},
{categoryNames=Java Virtual Machine, Runtime, Safepoint},
description=Safepointing begin, id=323, label=Safepoint Begin,
name=jdk.SafepointBegin,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}},
{categoryNames=Java Virtual Machine, Runtime, Safepoint},
description=Synchronize run state of threads, id=324, label=Safepoint
State Synchronization, name=jdk.SafepointStateSynchronization,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}},
{categoryNames=Java Virtual Machine, Runtime, Safepoint},
description=Safepointing begin waiting on running threads to block,
id=325, label=Safepoint Wait Blocked,
name=jdk.SafepointWaitBlocked,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}},
{categoryNames=Java Virtual Machine, Runtime, Safepoint},
description=Safepointing begin running cleanup tasks, id=326,
label=Safepoint Cleanup, name=jdk.SafepointCleanup,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}},
{categoryNames=Java Virtual Machine, Runtime, Safepoint},
description=Safepointing begin running cleanup tasks, id=327,
label=Safepoint Cleanup Task, name=jdk.SafepointCleanupTask,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}},
{categoryNames=Java Virtual Machine, Runtime, Safepoint},
description=Safepointing end, id=328, label=Safepoint End,
name=jdk.SafepointEnd,
settingDescriptors={contentType=jdk.jfr.BooleanField,

```

```

defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled),
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}},
{categoryNames=[Java Virtual Machine, Runtime],
description=Execution of a VM Operation, id=329, label=VM
Operation, name=jdk.ExecuteVMOperation,
settingDescriptors=[{contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled),
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}},
{categoryNames=[Java Virtual Machine, Runtime], description=JVM
shutting down, id=330, label=JVM Shutdown, name=jdk.Shutdown,
settingDescriptors=[{contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled),
{contentType=jdk.jfr.BooleanField, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}},
{categoryNames=[Java Application], description=Allocation in new
Thread Local Allocation Buffer, id=331, label=Allocation in new TLAB,
name=jdk.ObjectAllocationInNewTLAB,
settingDescriptors=[{contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled),
{contentType=jdk.jfr.BooleanField, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}},
{categoryNames=[Java Application], description=Allocation outside
Thread Local Allocation Buffers, id=332, label=Allocation outside
TLAB, name=jdk.ObjectAllocationOutsideTLAB,
settingDescriptors=[{contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled),
{contentType=jdk.jfr.BooleanField, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace)},
{categoryNames=[Java Virtual Machine, Profiling], description=A
potential memory leak, id=333, label=Old Object Sample,
name=jdk.OldObjectSample,
settingDescriptors=[{contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled),
{contentType=jdk.jfr.BooleanField, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace)},
{contentType=jdk.jfr.Timespan, defaultValue=infinity, description=Limit
running time of event, label=Cutoff, name=cutoff,
typeName=jdk.settings.Cutoff}},
{categoryNames=[Flight Recorder], description=Who requested the
recording and why, id=334, label=Recording Reason,
name=jdk.DumpReason,
settingDescriptors=[{contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}},
{categoryNames=[Flight Recorder], description=Data could not be
copied out from a buffer, typically because of contention, id=335,
label=Data Loss, name=jdk.DataLoss,
settingDescriptors=[{contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled)},
{categoryNames=[Java Virtual Machine], description=Description of
JVM and the Java application, id=336, label=JVM Information,
name=jdk.JVMInformation,
settingDescriptors=[{contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled), {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}},
{categoryNames=[Operating System], description=null, id=337,
label=OS Information, name=jdk.OSInformation,
settingDescriptors=[{contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled), {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}},
{categoryNames=[Operating System], description=null, id=338,
label=Virtualization Information, name=jdk.VirtualizationInformation,
settingDescriptors=[{contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled), {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}},
{categoryNames=[Java Virtual Machine], description=System Property
at JVM start, id=339, label=Initial System Property,
name=jdk.InitialSystemProperty,
settingDescriptors=[{contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled), {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}},
{categoryNames=[Operating System], description=null, id=340,
label=Initial Environment Variable,
name=jdk.InitialEnvironmentVariable,
settingDescriptors=[{contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled), {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}},
{categoryNames=[Operating System], description=null, id=341,
label=System Process, name=jdk.SystemProcess,
settingDescriptors=[{contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled), {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}},
{categoryNames=[Operating System, Processor], description=null,
id=342, label=CPU Information, name=jdk.CPUInformation,
settingDescriptors=[{contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled), {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}},
{categoryNames=[Operating System, Processor], description=null,
id=343, label=CPU Time Stamp Counter,
name=jdk.CPUTimeStampCounter,
settingDescriptors=[{contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled), {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}},
{categoryNames=[Operating System, Processor], description=OS CPU
Load, id=344, label=CPU Load, name=jdk.CPULoad,
settingDescriptors=[{contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled), {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}},
{categoryNames=[Operating System, Processor], description=null,
id=345, label=Thread CPU Load, name=jdk.ThreadCPULoad,
settingDescriptors=[{contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled), {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}},

```

```

{categoryNames=[Operating System, Processor], description=null,
id=346, label=Thread Context Switch Rate,
name=jdk.ThreadContextSwitchRate,
settingDescriptors=[{contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}],
{categoryNames=[Operating System, Network], description=null,
id=347, label=Network Utilization, name=jdk.NetworkUtilization,
settingDescriptors=[{contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}],
{categoryNames=[Java Application, Statistics], description=null,
id=348, label=Java Thread Statistics, name=jdk.JavaThreadStatistics,
settingDescriptors=[{contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}],
{categoryNames=[Java Application, Statistics], description=null,
id=349, label=Class Loading Statistics,
name=jdk.ClassLoadingStatistics,
settingDescriptors=[{contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}],
{categoryNames=[Java Application, Statistics], description=null,
id=350, label=Class Loader Statistics,
name=jdk.ClassLoaderStatistics,
settingDescriptors=[{contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}],
{categoryNames=[Java Application, Statistics], description=null,
id=351, label=Thread Allocation Statistics,
name=jdk.ThreadAllocationStatistics,
settingDescriptors=[{contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}],
{categoryNames=[Operating System, Memory], description=OS
Physical Memory, id=352, label=Physical Memory,
name=jdk.PhysicalMemory,
settingDescriptors=[{contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}],
{categoryNames=[Java Virtual Machine, Profiling],
description=Snapshot of a threads state, id=353, label=Method
Profiling Sample, name=jdk.ExecutionSample,
settingDescriptors=[{contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}],
{categoryNames=[Java Virtual Machine, Profiling],
description=Snapshot of a threads state when in native, id=354,
label=Method Profiling Sample Native,
name=jdk.NativeMethodSample,
settingDescriptors=[{contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}],
{categoryNames=[Java Virtual Machine, Runtime], description=null,
id=355, label=Thread Dump, name=jdk.ThreadDump,
settingDescriptors=[{contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}],
{categoryNames=[Java Virtual Machine, Runtime], description=null,
id=356, label=Native Library, name=jdk.NativeLibrary,
settingDescriptors=[{contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}],
{categoryNames=[Java Virtual Machine, Runtime, Modules],
description=A directed edge representing a dependency, id=357,
label=Module Require, name=jdk.ModuleRequire,
settingDescriptors=[{contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}],
{categoryNames=[Java Virtual Machine, Runtime, Modules],
description=null, id=358, label=Module Export,
name=jdk.ModuleExport,
settingDescriptors=[{contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}],
{categoryNames=[Java Virtual Machine, Compiler], description=null,
id=359, label=Compiler Statistics, name=jdk.CompilerStatistics,
settingDescriptors=[{contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}],
{categoryNames=[Java Virtual Machine, Compiler], description=null,
id=360, label=Compiler Configuration,
name=jdk.CompilerConfiguration,
settingDescriptors=[{contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}],
{categoryNames=[Java Virtual Machine, Code Cache],
description=null, id=361, label=Code Cache Statistics,
name=jdk.CodeCacheStatistics,
settingDescriptors=[{contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}],
{categoryNames=[Java Virtual Machine, Code Cache],
description=null, id=362, label=Code Cache Configuration,
name=jdk.CodeCacheConfiguration,
settingDescriptors=[{contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}],
{categoryNames=[Java Virtual Machine, Code Sweeper],
description=null, id=363, label=Code Sweeper Statistics,
name=jdk.CodeSweeperStatistics,
settingDescriptors=[{contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,

```

```

defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}),
{categoryNames=Java Virtual Machine, Code Sweeper},
description=null, id=364, label=Code Sweeper Configuration,
name=jdk.CodeSweeperConfiguration,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}),
{categoryNames=Java Virtual Machine, Flag}, description=null,
id=365, label=Int Flag, name=jdk.IntFlag,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}),
{categoryNames=Java Virtual Machine, Flag}, description=null,
id=366, label=Unsigned Int Flag, name=jdk.UnsignedIntFlag,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}),
{categoryNames=Java Virtual Machine, Flag}, description=null,
id=367, label=Long Flag, name=jdk.LongFlag,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}),
{categoryNames=Java Virtual Machine, Flag}, description=null,
id=368, label=Unsigned Long Flag, name=jdk.UnsignedLongFlag,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}),
{categoryNames=Java Virtual Machine, Flag}, description=null,
id=369, label=Double Flag, name=jdk.DoubleFlag,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}),
{categoryNames=Java Virtual Machine, Flag}, description=null,
id=370, label=Boolean Flag, name=jdk.BooleanField,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}),
{categoryNames=Java Virtual Machine, Flag}, description=null,
id=371, label=String Flag, name=jdk.StringFlag,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}),
{categoryNames=Java Virtual Machine, GC, Detailed},
description=null, id=372, label=Object Count, name=jdk.ObjectCount,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}),
{categoryNames=Java Virtual Machine, GC, Detailed},
description=Information about a specific heap region in the G1 GC,
id=373, label=G1 Heap Region Information,
name=jdk.G1HeapRegionInformation,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}),
{categoryNames=Java Virtual Machine, GC, Configuration},
description=The configuration of the garbage collector, id=374,
label=GC Configuration, name=jdk.GCConfiguration,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}),
{categoryNames=Java Virtual Machine, GC, Configuration},
description=The configuration of the survivors of garbage collection,
id=375, label=GC Survivor Configuration,
name=jdk.GCSurvivorConfiguration,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}),
{categoryNames=Java Virtual Machine, GC, Configuration},
description=The configuration of the Thread Local Allocation Buffers
(TLABs), id=376, label=TLAB Configuration,
name=jdk.GCTLABConfiguration,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}),
{categoryNames=Java Virtual Machine, GC, Configuration},
description=The configuration of the garbage collected heap, id=377,
label=GC Heap Configuration, name=jdk.GCHeapConfiguration,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}),
{categoryNames=Java Virtual Machine, GC, Configuration},
description=The configuration of the young generation of the garbage
collected heap, id=378, label=Young Generation Configuration,
name=jdk.YoungGenerationConfiguration,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}}),
{categoryNames=Java Virtual Machine, GC, Detailed},
description=Allocation of a ZPage, id=379, label=ZPage Allocation,
name=jdk.ZPageAllocation,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}}),
{categoryNames=Java Virtual Machine, GC, Detailed},
description=null, id=380, label=ZGC Thread Phase,
name=jdk.ZThreadPhase,
settingDescriptors={contentType=jdk.jfr.BooleanField,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}}),
{categoryNames=Java Virtual Machine, GC, Detailed},
description=null, id=381, label=Z Statistics Counter,

```

ObjectName
Recordings

```
name=jdk.ZStatisticsCounter,  
settingDescriptors={contentType=jdk.jfr.BooleanField,  
defaultValue=false, description=Record event, label=Enabled,  
name=enabled, typeName=jdk.settings.Enabled},  
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record  
event with duration above or equal to threshold, label=Threshold,  
name=threshold, typeName=jdk.settings.Threshold}},  
{categoryNames={Java Virtual Machine, GC, Detailed},  
description=null, id=382, label=Z Statistics Sampler,  
name=jdk.ZStatisticsSampler,  
settingDescriptors={contentType=jdk.jfr.BooleanField,  
defaultValue=false, description=Record event, label=Enabled,  
name=enabled, typeName=jdk.settings.Enabled},  
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record  
event with duration above or equal to threshold, label=Threshold,  
name=threshold, typeName=jdk.settings.Threshold}}}]  
jdk.management.jfr.type=FlightRecorder  
[]
```