MBeans

Catalina

Connector

port=80

(Implementation of a Coyote connector)

URIEncoding	UTF-8	(Character encoding used to decode the URI)
acceptCount	100	(The accept count for this Connector)
address	null	(The IP address on which to bind)
ajpFlush	null	(Send AJP flush package for each explicit flush)
allowTrace	false	(Allow disabling TRACE method)
allowedRequestAttributesPattern	null	(Regular expression that any custom request attributes muct match else the request will be rejected)
ciphers	HIGH:!aNULL:!eNULL:!EXPORT:!DES:!RC4:!MD5:!kRSA	(Comma-separated list of requested cipher suites)
ciphersUsed	null	(Array of ciphers suites in use)
className	null	(Fully qualified class name of the managed object)
connectionLinger	-1	(Linger value on the incoming connection)
connectionTimeout	20 000	(Timeout value on the incoming connection)
enableLookups	false	(The 'enable DNS lookups' flag for this Connector)
executorName	Internal	(The name of the executor - if any - associated with this Connector)
keepAliveTimeout	20 000	(The number of milliseconds Tomcat will wait for a subsequent request before closing the connection)
localPort	80	(The port number on which this connector is listening to requests. If the special value for port of zero is used then this method will report the actual port bound.)
maxHeaderCount	100	(The maximum number of headers that are allowed by the container. 100 by default. A value of less than 0 means no limit.)
maxKeepAliveRequests	100	(Maximum number of Keep-Alive requests to honor per connection)
maxParameterCount	1 000	(The maximum number of parameters (GET plus POST) which will be automatically parsed by the container. 10000 by default. A value of less than 0 means no limit.)
maxPostSize	2 097 152	(Maximum size in bytes of a POST which will be handled by the servlet API provided features)
maxSavePostSize	4 096	(Maximum size of a POST which will be saved by the container during authentication)
maxSwallowSize	2 097 152	(The maximum number of request body bytes to be swallowed by Tomcat for an aborted upload)
maxThreads	200	(The maximum number of request processing threads to be created for the internal Executor. -1 indicates an external Executor is being used.)
minSpareThreads	10	(The number of request processing threads that will be created for the internal Executor. -1 indicates an external Executor is being used.)
modelerType	null	(Type of the modeled resource. Can be set only once)
packetSize	null	(The ajp packet size.)
port	80	(The port number (excluding any offset) on which this connector is configured to listen for requests. The special value of 0 means select a random free port when the socket is bound.)
portOffset	0	(The offset that will be applied to port to determine the actual port number used.)
portWithOffset	80	(The actual port number (including any offset) on which this connector is configured to listen for requests.)
processorCache	200	(The processor cache size.)
protocol	HTTP/1.1	(Coyote protocol handler in use)
protocolHandlerClassName	org.apache.coyote.http11.Http11NioProtocol	(Coyote Protocol handler class name)
proxyName	null	(The Server name to which we should pretend requests to this Connector)
proxyPort	0	(The Server port to which we should pretend requests to this Connector)
redirectPort	443	(The redirect port (excluding any offset) for non-SSL to SSL redirects)
redirectPortWithOffset	443	(The actual redirect port (including any offset) for non-SSL to SSL redirects.)
scheme	http	(Protocol name for this Connector (http, https))
secretRequired	null	(Must secret be set to a non-null, non-zero-length String?)
secure	false	(Is this a secure (SSL) Connector?)
sslProtocols	null	(Comma-separated list of SSL protocol variants to be enabled)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
tcpNoDelay	true	(Should we use TCP no delay?)
threadPriority	5	(The thread priority for processors using the internal Executor. -1 indicates an external Executor is being used.)
useBodyEncodingForURI	false	(Should the body encoding be used for URI query parameters)
useIPVHosts	false	(Should IP-based virtual hosting be used?)
xpoweredBy	false	(Is generation of X-Powered-By response header enabled/disabled?)

DataSource

host=localhost,context=/demo,class=javax.sql.DataSource,name="jdbc/demo_javamelody"

abandonedUsageTracking	false	(Introspected attribute abandonedUsageTracking)
accessToUnderlyingConnectionAllowed	false	(Introspected attribute accessToUnderlyingConnectionAllowed)
autoCommitOnReturn	true	(Introspected attribute autoCommitOnReturn)
cacheState	true	(Introspected attribute cacheState)
closed	false	(Introspected attribute closed)
connectionFactoryClassName	null	(Introspected attribute connectionFactoryClassName)
connectionInitSqlsAsArray	[]	(Introspected attribute connectionInitSqlsAsArray)
defaultAutoCommit	null	(Introspected attribute defaultAutoCommit)
defaultCatalog	null	(Introspected attribute defaultCatalog)
defaultQueryTimeout	null	(Introspected attribute defaultQueryTimeout)
defaultReadOnly	null	(Introspected attribute defaultReadOnly)

defaultSchema	null	(Introspected attribute defaultSchema)
defaultTransactionIsolation	-1	(Introspected attribute defaultTransactionIsolation)
disconnectionSqlCodesAsArray	[]	(Introspected attribute disconnectionSqlCodesAsArray)
driverClassName	org.h2.Driver	(Introspected attribute driverClassName)
enableAutoCommitOnReturn	true	(Introspected attribute enableAutoCommitOnReturn)
evictionPolicyClassName	org.apache.tomcat.dbcp.pool2.impl.DefaultEvictionPolicy	(Introspected attribute evictionPolicyClassName)
fastFailValidation	false	(Introspected attribute fastFailValidation)
initialSize	0	(Introspected attribute initialSize)
jmxName	Catalina:type=DataSource,host=localhost,context=/demo,class=javax.sql.DataSource,name="jdbc/demo_javamelody"	(Introspected attribute jmxName)
lifo	true	(Introspected attribute lifo)
logAbandoned	false	(Introspected attribute logAbandoned)
logExpiredConnections	true	(Introspected attribute logExpiredConnections)
maxConnLifetimeMillis	-1	(Introspected attribute maxConnLifetimeMillis)
maxIdle	10	(Introspected attribute maxIdle)
maxOpenPreparedStatements	-1	(Introspected attribute maxOpenPreparedStatements)
maxTotal	100	(Introspected attribute maxTotal)
maxWaitMillis	30 000	(Introspected attribute maxWaitMillis)
minEvictableIdleTimeMillis	1 800 000	(Introspected attribute minEvictableIdleTimeMillis)
minIdle	0	(Introspected attribute minIdle)
modelerType	org.apache.tomcat.dbcp.dbcp2.BasicDataSource	(Type of the modeled resource. Can be set only once)
numActive	3	(Introspected attribute numActive)
numIdle	3	(Introspected attribute numIdle)
numTestsPerEvictionRun	3	(Introspected attribute numTestsPerEvictionRun)
poolPreparedStatements	false	(Introspected attribute poolPreparedStatements)
removeAbandonedOnBorrow	false	(Introspected attribute removeAbandonedOnBorrow)
removeAbandonedOnMaintenance	false	(Introspected attribute removeAbandonedOnMaintenance)
removeAbandonedTimeout	300	(Introspected attribute removeAbandonedTimeout)
rollbackOnReturn	true	(Introspected attribute rollbackOnReturn)
softMinEvictableIdleTimeMillis	-1	(Introspected attribute softMinEvictableIdleTimeMillis)
testOnBorrow	true	(Introspected attribute testOnBorrow)
testOnCreate	false	(Introspected attribute testOnCreate)
testOnReturn	false	(Introspected attribute testOnReturn)
testWhileIdle	false	(Introspected attribute testWhileIdle)
timeBetweenEvictionRunsMillis	-1	(Introspected attribute timeBetweenEvictionRunsMillis)
url	jdbc:h2:/opt/data/demo/h2	(Introspected attribute url)
username	sa	(Introspected attribute username)
validationQuery	null	(Introspected attribute validationQuery)
validationQueryTimeout	-1	(Introspected attribute validationQueryTimeout)

host=localhost,context=/demo,class=javax.sql.DataSource,name="jdbc/demo_javamelody",connectionpool=connections

AbandonedConfig	false
BlockWhenExhausted	true
BorrowedCount	9 345
Closed	false
CreatedCount	6

CreationStackTrace	java.lang.Exception at org.apache.tomcat.dbcp.pool2.impl.BaseGenericObjectPool.<init>(BaseGenericObjectPool.java:147) at org.apache.tomcat.dbcp.pool2.impl.GenericObjectPool.<init>(GenericObjectPool.java:109) at org.apache.tomcat.dbcp.dbcp2.BasicDataSource.createObjectPool(BasicDataSource.java:628) at org.apache.tomcat.dbcp.dbcp2.BasicDataSource.createConnectionPool(BasicDataSource.java:492) at org.apache.tomcat.dbcp.dbcp2.BasicDataSource.createDataSource(BasicDataSource.java:558) at org.apache.tomcat.dbcp.dbcp2.BasicDataSource.getConnection(BasicDataSource.java:753) at java.base/jdk.internal.reflect.NativeMethodAccessorImpl.invoke0(Native Method) at java.base/jdk.internal.reflect.NativeMethodAccessorImpl.invoke(NativeMethodAccessorImpl.java:62) at java.base/jdk.internal.reflect.DelegatingMethodAccessorImpl.invoke(DelegatingMethodAccessorImpl.java:43) at java.base/java.lang.reflect.Method.invoke(Method.java:566) at net.bull.javamelody.JdbcWrapper$3.invoke(JdbcWrapper.java:812) at net.bull.javamelody.JdbcWrapper$DelegatingInvocationHandler.invoke(JdbcWrapper.java:306) at com.sun.proxy.$Proxy5.getConnection(Unknown Source) at net.bull.javamelody.internal.model.JavaInformations.buildDataBaseVersion(JavaInformations.java:426) at net.bull.javamelody.internal.model.JavaInformations.<init>(JavaInformations.java:200) at net.bull.javamelody.internal.web.MonitoringController.doActionIfNeededAndReport(MonitoringController.java:158) at net.bull.javamelody.MonitoringFilter.doMonitoring(MonitoringFilter.java:408) at net.bull.javamelody.MonitoringFilter.doFilter(MonitoringFilter.java:206) at org.apache.catalina.core.ApplicationFilterChain.internalDoFilter(ApplicationFilterChain.java:193) at org.apache.catalina.core.ApplicationFilterChain.doFilter(ApplicationFilterChain.java:166) at fr.spi4j.filter.HttpSessionFilter.doFilter(HttpSessionFilter.java:69) at org.apache.catalina.core.ApplicationFilterChain.internalDoFilter(ApplicationFilterChain.java:193) at org.apache.catalina.core.ApplicationFilterChain.doFilter(ApplicationFilterChain.java:166) at net.bull.javamelody.MonitoringFilter.doFilter(MonitoringFilter.java:199) at org.apache.catalina.core.ApplicationFilterChain.internalDoFilter(ApplicationFilterChain.java:193) at org.apache.catalina.core.ApplicationFilterChain.doFilter(ApplicationFilterChain.java:166) at ForbiddenActionsFilter.doFilter(ForbiddenActionsFilter.java:28) at org.apache.catalina.core.ApplicationFilterChain.internalDoFilter(ApplicationFilterChain.java:193) at org.apache.catalina.core.ApplicationFilterChain.doFilter(ApplicationFilterChain.java:166) at fr.spi4j.lib.security.RemoteUserFilter.doFilter(RemoteUserFilter.java:66) at org.apache.catalina.core.ApplicationFilterChain.internalDoFilter(ApplicationFilterChain.java:193) at org.apache.catalina.core.ApplicationFilterChain.doFilter(ApplicationFilterChain.java:166) at org.apache.catalina.core.StandardWrapperValve.invoke(StandardWrapperValve.java:202) at org.apache.catalina.core.StandardContextValve.invoke(StandardContextValve.java:96) at org.apache.catalina.authenticator.AuthenticatorBase.invoke(AuthenticatorBase.java:541) at org.apache.catalina.core.StandardHostValve.invoke(StandardHostValve.java:139) at org.apache.catalina.valves.ErrorReportValve.invoke(ErrorReportValve.java:92) at org.apache.catalina.valves.AbstractAccessLogValve.invoke(AbstractAccessLogValve.java:688) at org.apache.catalina.core.StandardEngineValve.invoke(StandardEngineValve.java:74) at org.apache.catalina.connector.CoyoteAdapter.service(CoyoteAdapter.java:343) at org.apache.coyote.http11.Http11Processor.service(Http11Processor.java:373) at org.apache.coyote.AbstractProcessorLight.process(AbstractProcessorLight.java:65) at org.apache.coyote.AbstractProtocol$ConnectionHandler.process(AbstractProtocol.java:868) at org.apache.tomcat.util.net.NioEndpoint$SocketProcessor.doRun(NioEndpoint.java:1594) at org.apache.tomcat.util.net.SocketProcessorBase.run(SocketProcessorBase.java:49) at java.base/java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1128) at java.base/java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:628) at org.apache.tomcat.util.threads.TaskThread$WrappingRunnable.run(TaskThread.java:61) at java.base/java.lang.Thread.run(Thread.java:834)

DestroyedByBorrowValidationCount	0
DestroyedByEvictorCount	0
DestroyedCount	0
FactoryType	org.apache.tomcat.dbcp.dbcp2.PoolableConnectionFactory<org.apache.tomcat.dbcp.dbcp2.PoolableConnection>
Fairness	false
Lifo	true
LogAbandoned	false
MaxBorrowWaitTimeMillis	85
MaxIdle	10
MaxTotal	100
MaxWaitMillis	30 000
MeanActiveTimeMillis	8
MeanBorrowWaitTimeMillis	0
MeanIdleTimeMillis	1 300
MinEvictableIdleTimeMillis	1 800 000
MinIdle	0
NumActive	3
NumIdle	3
NumTestsPerEvictionRun	3
NumWaiters	0
RemoveAbandonedOnBorrow	false
RemoveAbandonedOnMaintenance	false
RemoveAbandonedTimeout	2 147 483 647
ReturnedCount	9 342
TestOnBorrow	true
TestOnCreate	false
TestOnReturn	false
TestWhileIdle	false
TimeBetweenEvictionRunsMillis	-1

host=localhost,context=/demo,class=javax.sql.DataSource,name="jdbc/demo_javamelody",connectionpool=connections,connection=1

CacheState	true
Closed	true
ToString	1561507060, URL=jdbc:h2:/opt/data/demo/h2, UserName=SA, H2 JDBC Driver

host=localhost,context=/demo,class=javax.sql.DataSource,name="jdbc/demo_javamelody",connectionpool=connections,connection=2

AutoCommit	false
CacheState	true
Catalog	H2
Closed	false
Holdability	1
ReadOnly	false
Schema	PUBLIC
ToString	1228383847, URL=jdbc:h2:/opt/data/demo/h2, UserName=SA, H2 JDBC Driver
TransactionIsolation	2

host=localhost,context=/demo,class=javax.sql.DataSource,name="jdbc/demo_javamelody",connectionpool=connections,connection=3

AutoCommit	false
CacheState	true
Catalog	H2
Closed	false
Holdability	1
ReadOnly	false
Schema	PUBLIC
ToString	681343162, URL=jdbc:h2:/opt/data/demo/h2, UserName=SA, H2 JDBC Driver
TransactionIsolation	2

host=localhost,context=/demo,class=javax.sql.DataSource,name="jdbc/demo_javamelody",connectionpool=connections,connection=4

AutoCommit	false
CacheState	true
Catalog	H2
Closed	false
Holdability	1
ReadOnly	false
Schema	PUBLIC
ToString	988726656, URL=jdbc:h2:/opt/data/demo/h2, UserName=SA, H2 JDBC Driver
TransactionIsolation	2

host=localhost,context=/demo,class=javax.sql.DataSource,name="jdbc/demo_javamelody",connectionpool=connections,connection=5

CacheState	true
Closed	true
ToString	1778853695, URL=jdbc:h2:/opt/data/demo/h2, UserName=SA, H2 JDBC Driver

host=localhost,context=/demo,class=javax.sql.DataSource,name="jdbc/demo_javamelody",connectionpool=connections,connection=6

CacheState	true
Closed	true
ToString	104158289, URL=jdbc:h2:/opt/data/demo/h2, UserName=SA, H2 JDBC Driver

Deployer

host=localhost

(Startup event listener for a Host that configures the properties of that Host, and the associated defined contexts)

className	org.apache.catalina.startup.HostConfig	(Fully qualified class name of the managed object)
configBaseName	/opt/apache-tomcat-9.0.33/conf/Catalina/localhost	(The base directory for Context configuration files)
contextClass	org.apache.catalina.core.StandardContext	(The Java class name of the Context implementation we should use)
copyXML	false	(The copy XML config file flag for this component)
deployXML	true	(The deploy XML config file flag for this component)
modelerType	org.apache.catalina.startup.HostConfig	(Type of the modeled resource. Can be set only once)
unpackWARs	false	(The unpack WARs flag)

Engine

(Standard Engine Component)

backgroundProcessorDelay	10	(The processor delay for this component.)
catalinaBase	/opt/apache-tomcat-9.0.33	(Base (instance) directory for this Engine, typically same as catalina.base system property)
defaultHost	localhost	(Name of the default Host for this Engine)
jvmRoute	null	(Route used for load balancing)
managedResource	StandardEngine[Catalina]	(The managed resource this MBean is associated with)
modelerType	org.apache.catalina.core.StandardEngine	(Type of the modeled resource. Can be set only once)
name	Catalina	(Unique name of this Engine)
realm	LockOutRealm[StandardEngine[Catalina]]	(Associated realm.)
startChildren	true	(Will children be started automatically when they are added.)
startStopThreads	1	(The number of threads to use when starting and stopping child Hosts)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

Filter

WebModule=//localhost/,name=Tomcat WebSocket (JSR356) Filter,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet-filter definition)

filterClass	org.apache.tomcat.websocket.server.WsFilter	(Fully qualified class name of the filter object)
filterInitParameterMap	{}	(Return the initialization parameters associated with this filter)
filterName	Tomcat WebSocket (JSR356) Filter	(The name used to reference the filter in web.xml)
modelerType	org.apache.catalina.core.ApplicationFilterConfig	(Type of the modeled resource. Can be set only once)

WebModule=//localhost/demo,name=Tomcat WebSocket (JSR356) Filter,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet-filter definition)

filterClass	org.apache.tomcat.websocket.server.WsFilter	(Fully qualified class name of the filter object)
filterInitParameterMap	{}	(Return the initialization parameters associated with this filter)
filterName	Tomcat WebSocket (JSR356) Filter	(The name used to reference the filter in web.xml)
modelerType	org.apache.catalina.core.ApplicationFilterConfig	(Type of the modeled resource. Can be set only once)

WebModule=//localhost/demo,name=forbiddenActions,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet-filter definition)

filterClass	ForbiddenActionsFilter	(Fully qualified class name of the filter object)
filterInitParameterMap	{}	(Return the initialization parameters associated with this filter)
filterName	forbiddenActions	(The name used to reference the filter in web.xml)
modelerType	org.apache.catalina.core.ApplicationFilterConfig	(Type of the modeled resource. Can be set only once)

WebModule=//localhost/demo,name=httpSessionInThread,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet-filter definition)

filterClass	fr.spi4j.filter.HttpSessionFilter	(Fully qualified class name of the filter object)
filterInitParameterMap	{}	(Return the initialization parameters associated with this filter)
filterName	httpSessionInThread	(The name used to reference the filter in web.xml)
modelerType	org.apache.catalina.core.ApplicationFilterConfig	(Type of the modeled resource. Can be set only once)

WebModule=//localhost/demo,name=javamelody,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet-filter definition)

filterClass	net.bull.javamelody.MonitoringFilter	(Fully qualified class name of the filter object)
filterInitParameterMap	{}	(Return the initialization parameters associated with this filter)
filterName	javamelody	(The name used to reference the filter in web.xml)
modelerType	org.apache.catalina.core.ApplicationFilterConfig	(Type of the modeled resource. Can be set only once)

WebModule=//localhost/demo,name=monitoring,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet-filter definition)

filterClass	net.bull.javamelody.MonitoringFilter	(Fully qualified class name of the filter object)
filterInitParameterMap	{}	(Return the initialization parameters associated with this filter)
filterName	monitoring	(The name used to reference the filter in web.xml)
modelerType	org.apache.catalina.core.ApplicationFilterConfig	(Type of the modeled resource. Can be set only once)

WebModule=//localhost/demo,name=remoteUser,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet-filter definition)

filterClass	fr.spi4j.lib.security.RemoteUserFilter	(Fully qualified class name of the filter object)
filterInitParameterMap	{}	(Return the initialization parameters associated with this filter)
filterName	remoteUser	(The name used to reference the filter in web.xml)
modelerType	org.apache.catalina.core.ApplicationFilterConfig	(Type of the modeled resource. Can be set only once)

WebModule=//localhost/downloads,name=Tomcat WebSocket (JSR356) Filter,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet-filter definition)

filterClass	org.apache.tomcat.websocket.server.WsFilter	(Fully qualified class name of the filter object)
filterInitParameterMap	{}	(Return the initialization parameters associated with this filter)
filterName	Tomcat WebSocket (JSR356) Filter	(The name used to reference the filter in web.xml)
modelerType	org.apache.catalina.core.ApplicationFilterConfig	(Type of the modeled resource. Can be set only once)

WebModule=//localhost/usage,name=Tomcat WebSocket (JSR356) Filter,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet-filter definition)

filterClass	org.apache.tomcat.websocket.server.WsFilter	(Fully qualified class name of the filter object)
filterInitParameterMap	{}	(Return the initialization parameters associated with this filter)
filterName	Tomcat WebSocket (JSR356) Filter	(The name used to reference the filter in web.xml)
modelerType	org.apache.catalina.core.ApplicationFilterConfig	(Type of the modeled resource. Can be set only once)

WebModule=//localhost/usage,name=basic-auth,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet-filter definition)

filterClass	net.bull.javamelody.usagestats.BasicAuthFilter	(Fully qualified class name of the filter object)
filterInitParameterMap	{}	(Return the initialization parameters associated with this filter)
filterName	basic-auth	(The name used to reference the filter in web.xml)
modelerType	org.apache.catalina.core.ApplicationFilterConfig	(Type of the modeled resource. Can be set only once)

WebModule=//localhost/usage,name=gzip,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet-filter definition)

filterClass	net.bull.javamelody.usagestats.GzipFilter	(Fully qualified class name of the filter object)
filterInitParameterMap	{}	(Return the initialization parameters associated with this filter)
filterName	gzip	(The name used to reference the filter in web.xml)
modelerType	org.apache.catalina.core.ApplicationFilterConfig	(Type of the modeled resource. Can be set only once)

WebModule=//localhost/usage,name=javamelody,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet-filter definition)

filterClass	net.bull.javamelody.MonitoringFilter	(Fully qualified class name of the filter object)
filterInitParameterMap	{}	(Return the initialization parameters associated with this filter)
filterName	javamelody	(The name used to reference the filter in web.xml)
modelerType	org.apache.catalina.core.ApplicationFilterConfig	(Type of the modeled resource. Can be set only once)

GlobalRequestProcessor

name="http-nio-80"

(Runtime information of a group of requests)

bytesReceived	39 079	(Amount of data received, in bytes)
bytesSent	2 315 630 458	(Amount of data sent, in bytes)
errorCount	270 167	(Number of errors)
maxTime	80 227	(Maximum time to process a request)
modelerType	org.apache.coyote.RequestGroupInfo	(Type of the modeled resource. Can be set only once)
processingTime	23 619 939	(Total time to process the requests)
requestCount	22 573 408	(Number of requests processed)

Host

host=localhost

(Standard Host Component)

aliases	[]	(Host aliases)
appBase	webapps	(The application root for this Host)
autoDeploy	true	(The auto deploy flag for this Host)
backgroundProcessorDelay	-1	(The processor delay for this component.)
children	[Catalina:j2eeType=WebModule,name=//localhost/,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=WebModule,name=//localhost/downloads,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=WebModule,name=//localhost/demo,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=WebModule,name=//localhost/usage,J2EEApplication=none,J2EEServer=none]	(Object names of all children)
configClass	org.apache.catalina.startup.ContextConfig	(The configuration class for contexts)
contextClass	org.apache.catalina.core.StandardContext	(The Java class name of the default Context implementation class for deployed web applications.)
copyXML	false	(Should XML files be copied to $CATALINA_BASE/conf/{engine}/{host} by default when a web application is deployed?)
createDirs	true	(Should we create directories upon startup for appBase and xmlBase?)
deployIgnore	null	(Paths within appBase ignored for automatic deployment)
deployOnStartup	true	(The deploy on startup flag for this Host)
deployXML	true	(deploy Context XML config files property)

errorReportValveClass	org.apache.catalina.valves.ErrorReportValve	(The Java class name of the default error reporter implementation class for deployed web applications.)
managedResource	StandardEngine[Catalina].StandardHost[localhost]	(The managed resource this MBean is associated with)
modelerType	org.apache.catalina.core.StandardHost	(Type of the modeled resource. Can be set only once)
name	localhost	(Unique name of this Host)
realm	LockOutRealm[StandardEngine[Catalina]]	(Associated realm.)
startChildren	true	(Will children be started automatically when they are added?)
startStopThreads	1	(The number of threads to use when starting, stopping and deploying child Contexts)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
undeployOldVersions	false	(Determines if old versions of applications deployed using parallel deployment are automatically undeployed when no longer used. Requires autoDeploy to be enabled.)
unpackWARs	false	(Unpack WARs property)
valveNames	[Catalina:type=Valve,host=localhost,name=AccessLogValve, Catalina:type=Valve,host=localhost,name=ErrorReportValve, Catalina:type=Valve,host=localhost,name=StandardHostValve]	(Return the MBean Names of the Valves associated with this Host)
workDir	null	(Work Directory base for applications)
xmlBase	null	(The XML root for this Host.)

JspMonitor

WebModule=//localhost/,name=jsp,J2EEApplication=none,J2EEServer=none

(JSP Monitoring)

jspCount	1	(The number of JSPs that have been loaded into a webapp)
jspQueueLength	-1	(The length of the JSP queue (if enabled via maxLoadedJsps))
jspReloadCount	0	(The number of JSPs that have been reloaded)
jspUnloadCount	0	(The number of JSPs that have been unloaded)
modelerType	org.apache.jasper.servlet.JspServlet	(Type of the modeled resource. Can be set only once)

WebModule=//localhost/demo,name=jsp,J2EEApplication=none,J2EEServer=none

(JSP Monitoring)

jspCount	1	(The number of JSPs that have been loaded into a webapp)
jspQueueLength	-1	(The length of the JSP queue (if enabled via maxLoadedJsps))
jspReloadCount	0	(The number of JSPs that have been reloaded)
jspUnloadCount	0	(The number of JSPs that have been unloaded)
modelerType	org.apache.jasper.servlet.JspServlet	(Type of the modeled resource. Can be set only once)

WebModule=//localhost/downloads,name=jsp,J2EEApplication=none,J2EEServer=none

(JSP Monitoring)

jspCount	0	(The number of JSPs that have been loaded into a webapp)
jspQueueLength	-1	(The length of the JSP queue (if enabled via maxLoadedJsps))
jspReloadCount	0	(The number of JSPs that have been reloaded)
jspUnloadCount	0	(The number of JSPs that have been unloaded)
modelerType	org.apache.jasper.servlet.JspServlet	(Type of the modeled resource. Can be set only once)

WebModule=//localhost/usage,name=jsp,J2EEApplication=none,J2EEServer=none

(JSP Monitoring)

jspCount	0	(The number of JSPs that have been loaded into a webapp)
jspQueueLength	-1	(The length of the JSP queue (if enabled via maxLoadedJsps))
jspReloadCount	0	(The number of JSPs that have been reloaded)
jspUnloadCount	0	(The number of JSPs that have been unloaded)
modelerType	org.apache.jasper.servlet.JspServlet	(Type of the modeled resource. Can be set only once)

Loader

host=localhost,context=/

(Classloader implementation which is specialized for handling web applications)

className	org.apache.catalina.loader.WebappLoader	(Fully qualified class name of the managed object)
delegate	false	(The 'follow standard delegation model' flag that will be used to configure our ClassLoader)
loaderRepositories	[]	(Repositories set in the real loader)
loaderRepositoriesString		(Repositories set in the real loader)
modelerType	org.apache.catalina.loader.WebappLoader	(Type of the modeled resource. Can be set only once)
reloadable	false	(The reloadable flag for this Loader)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

host=localhost,context=/demo

(Classloader implementation which is specialized for handling web applications)

className	org.apache.catalina.loader.WebappLoader	(Fully qualified class name of the managed object)
delegate	false	(The 'follow standard delegation model' flag that will be used to configure our ClassLoader)

loaderRepositories	[war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/classes/, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdocreport.core-1.0.4.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/ehcache-core-2.6.8.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/log4j-1.2.17.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/spi4j-lib-security-server-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/slf4j-api-1.6.1.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/jta-1.1.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdocreport.template.freemarker-1.0.4.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/xpp3_min-1.1.4c.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/gwt-servlet-2.7.0.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/spi4j-gwt-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdocreport.document-1.0.4.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/itext-2.1.7.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdocreport.template-1.0.4.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/freemarker-2.3.16.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdocreport.converter-1.0.4.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/validation-api-1.0.0.GA.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/appwhite1-commons-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdocreport.document.docx-1.0.4.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/spi4j-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/jrobin-1.5.9.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdocreport.document.odt-1.0.4.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/spi4j-ui-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/javamelody-core-1.98.0.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/spi4j-doc-report-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdocreport.document.pptx-1.0.4.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/spi4j-lib-security-commons-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/appwhite1-server-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/referentiel-server-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/h2-1.4.200.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/xstream-1.4.11.1.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/referentiel-commons-1.7-SNAPSHOT.jar]	(Repositories set in the real loader)
loaderRepositoriesString	war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/classes/:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdocreport.core-1.0.4.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/ehcache-core-2.6.8.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/log4j-1.2.17.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/spi4j-lib-security-server-1.7-SNAPSHOT.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/slf4j-api-1.6.1.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/jta-1.1.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdocreport.template.freemarker-1.0.4.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/xpp3_min-1.1.4c.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/gwt-servlet-2.7.0.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/spi4j-gwt-1.7-SNAPSHOT.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdocreport.document-1.0.4.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/itext-2.1.7.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdocreport.template-1.0.4.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/freemarker-2.3.16.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdocreport.converter-1.0.4.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/validation-api-1.0.0.GA.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/appwhite1-commons-1.7-SNAPSHOT.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdocreport.document.docx-1.0.4.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/spi4j-1.7-SNAPSHOT.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/jrobin-1.5.9.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdocreport.document.odt-1.0.4.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/spi4j-ui-1.7-SNAPSHOT.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/javamelody-core-1.98.0.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/spi4j-doc-report-1.7-SNAPSHOT.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdocreport.document.pptx-1.0.4.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/spi4j-lib-security-commons-1.7-SNAPSHOT.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/appwhite1-server-1.7-SNAPSHOT.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/referentiel-server-1.7-SNAPSHOT.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/h2-1.4.200.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/xstream-1.4.11.1.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/referentiel-commons-1.7-SNAPSHOT.jar:	(Repositories set in the real loader)
modelerType	org.apache.catalina.loader.WebappLoader	(Type of the modeled resource. Can be set only once)
reloadable	false	(The reloadable flag for this Loader)

stateName	STARTED	(The name of the LifecycleState that this component is currently in)

host=localhost,context=/downloads

(Classloader implementation which is specialized for handling web applications)

className	org.apache.catalina.loader.WebappLoader	(Fully qualified class name of the managed object)
delegate	false	(The 'follow standard delegation model' flag that will be used to configure our ClassLoader)
loaderRepositories	[]	(Repositories set in the real loader)
loaderRepositoriesString		(Repositories set in the real loader)
modelerType	org.apache.catalina.loader.WebappLoader	(Type of the modeled resource. Can be set only once)
reloadable	false	(The reloadable flag for this Loader)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

host=localhost,context=/usage

(Classloader implementation which is specialized for handling web applications)

className	org.apache.catalina.loader.WebappLoader	(Fully qualified class name of the managed object)
delegate	false	(The 'follow standard delegation model' flag that will be used to configure our ClassLoader)
loaderRepositories	[war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/classes/, war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/javamelody-core-1.99.4.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/jrobin-1.5.9.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/itext-2.1.7.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/gson-2.10.1.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/commons-csv-1.10.0.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/log4j-1.2.17.jar]	(Repositories set in the real loader)
loaderRepositoriesString	war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/classes/:war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/javamelody-core-1.99.4.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/jrobin-1.5.9.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/itext-2.1.7.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/gson-2.10.1.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/commons-csv-1.10.0.jar:war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/log4j-1.2.17.jar:	(Repositories set in the real loader)
modelerType	org.apache.catalina.loader.WebappLoader	(Type of the modeled resource. Can be set only once)
reloadable	false	(The reloadable flag for this Loader)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

MBeanFactory

(Factory for MBeans and corresponding components)

modelerType	org.apache.catalina.mbeans.MBeanFactory	(Type of the modeled resource. Can be set only once)

Manager

host=localhost,context=/

(Standard implementation of the Manager interface)

activeSessions	9	(Number of active sessions at this moment)
className	org.apache.catalina.session.StandardManager	(Fully qualified class name of the managed object)
duplicates	0	(Number of duplicated session ids generated)
expiredSessions	31 285	(Number of sessions that expired (doesn't include explicit invalidations))
jvmRoute	null	(Retrieve the JvmRoute for the enclosing Engine)
maxActive	266	(Maximum number of active sessions so far)
maxActiveSessions	-1	(The maximum number of active Sessions allowed, or -1 for no limit)
modelerType	org.apache.catalina.session.StandardManager	(Type of the modeled resource. Can be set only once)
name	StandardManager	(The descriptive name of this Manager implementation (for logging))
pathname	SESSIONS.ser	(Path name of the disk file in which active sessions)
persistAuthentication	false	(Indicates whether sessions shall persist authentication information when being persisted (e.g. across application restarts).)
processExpiresFrequency	6	(The frequency of the manager checks (expiration and passivation))
processingTime	1 764	(Time spent doing housekeeping and expiration)
rejectedSessions	0	(Number of sessions we rejected due to maxActive being reached)
secureRandomAlgorithm	SHA1PRNG	(The secure random number generator algorithm name)
secureRandomClass	null	(The secure random number generator class name)
secureRandomProvider	null	(The secure random number generator provider name)
sessionAttributeNameFilter	null	(The string pattern used for including session attributes in distribution. Null means all attributes are included.)
sessionAttributeValueClassNameFilter	null	(The regular expression used to filter session attributes based on the implementation class of the value. The regular expression is anchored and must match the fully qualified class name.)
sessionAverageAliveTime	18	(Average time an expired session had been alive)
sessionCounter	31 294	(Total number of sessions created by this manager)
sessionCreateRate	0	(Session creation rate in sessions per minute)
sessionExpireRate	0	(Session expiration rate in sessions per minute)
sessionMaxAliveTime	3 257	(Longest time an expired session had been alive)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
warnOnSessionAttributeFilterFailure	false	(Should a WARN level log message be generated if a session attribute fails to match sessionAttributeNameFilter or sessionAttributeClassNameFilter?)

host=localhost,context=/demo

(Standard implementation of the Manager interface)

activeSessions	11	(Number of active sessions at this moment)
className	org.apache.catalina.session.StandardManager	(Fully qualified class name of the managed object)
duplicates	0	(Number of duplicated session ids generated)
expiredSessions	27 548	(Number of sessions that expired (doesn't include explicit invalidations))
jvmRoute	null	(Retrieve the JvmRoute for the enclosing Engine)
maxActive	597	(Maximum number of active sessions so far)
maxActiveSessions	-1	(The maximum number of active Sessions allowed, or -1 for no limit)
modelerType	org.apache.catalina.session.StandardManager	(Type of the modeled resource. Can be set only once)
name	StandardManager	(The descriptive name of this Manager implementation (for logging))
pathname	SESSIONS.ser	(Path name of the disk file in which active sessions)
persistAuthentication	false	(Indicates whether sessions shall persist authentication information when being persisted (e.g. across application restarts).)
processExpiresFrequency	6	(The frequency of the manager checks (expiration and passivation))
processingTime	1 564	(Time spent doing housekeeping and expiration)
rejectedSessions	0	(Number of sessions we rejected due to maxActive being reached)
secureRandomAlgorithm	SHA1PRNG	(The secure random number generator algorithm name)
secureRandomClass	null	(The secure random number generator class name)
secureRandomProvider	null	(The secure random number generator provider name)
sessionAttributeNameFilter	null	(The string pattern used for including session attributes in distribution. Null means all attributes are included.)
sessionAttributeValueClassNameFilter	null	(The regular expression used to filter session attributes based on the implementation class of the value. The regular expression is anchored and must match the fully qualified class name.)
sessionAverageAliveTime	0	(Average time an expired session had been alive)
sessionCounter	27 559	(Total number of sessions created by this manager)
sessionCreateRate	0	(Session creation rate in sessions per minute)
sessionExpireRate	0	(Session expiration rate in sessions per minute)
sessionMaxAliveTime	3 327	(Longest time an expired session had been alive)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
warnOnSessionAttributeFilterFailure	false	(Should a WARN level log message be generated if a session attribute fails to match sessionAttributeNameFilter or sessionAttributeClassNameFilter?)

host=localhost,context=/downloads

(Standard implementation of the Manager interface)

activeSessions	0	(Number of active sessions at this moment)
className	org.apache.catalina.session.StandardManager	(Fully qualified class name of the managed object)
duplicates	0	(Number of duplicated session ids generated)
expiredSessions	0	(Number of sessions that expired (doesn't include explicit invalidations))
jvmRoute	null	(Retrieve the JvmRoute for the enclosing Engine)
maxActive	0	(Maximum number of active sessions so far)
maxActiveSessions	-1	(The maximum number of active Sessions allowed, or -1 for no limit)
modelerType	org.apache.catalina.session.StandardManager	(Type of the modeled resource. Can be set only once)
name	StandardManager	(The descriptive name of this Manager implementation (for logging))
pathname	SESSIONS.ser	(Path name of the disk file in which active sessions)
persistAuthentication	false	(Indicates whether sessions shall persist authentication information when being persisted (e.g. across application restarts).)
processExpiresFrequency	6	(The frequency of the manager checks (expiration and passivation))
processingTime	108	(Time spent doing housekeeping and expiration)
rejectedSessions	0	(Number of sessions we rejected due to maxActive being reached)
secureRandomAlgorithm	SHA1PRNG	(The secure random number generator algorithm name)
secureRandomClass	null	(The secure random number generator class name)
secureRandomProvider	null	(The secure random number generator provider name)
sessionAttributeNameFilter	null	(The string pattern used for including session attributes in distribution. Null means all attributes are included.)
sessionAttributeValueClassNameFilter	null	(The regular expression used to filter session attributes based on the implementation class of the value. The regular expression is anchored and must match the fully qualified class name.)
sessionAverageAliveTime	0	(Average time an expired session had been alive)
sessionCounter	0	(Total number of sessions created by this manager)
sessionCreateRate	0	(Session creation rate in sessions per minute)
sessionExpireRate	0	(Session expiration rate in sessions per minute)
sessionMaxAliveTime	0	(Longest time an expired session had been alive)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
warnOnSessionAttributeFilterFailure	false	(Should a WARN level log message be generated if a session attribute fails to match sessionAttributeNameFilter or sessionAttributeClassNameFilter?)

host=localhost,context=/usage

(Standard implementation of the Manager interface)

activeSessions	0	(Number of active sessions at this moment)
className	org.apache.catalina.session.StandardManager	(Fully qualified class name of the managed object)
duplicates	0	(Number of duplicated session ids generated)
expiredSessions	0	(Number of sessions that expired (doesn't include explicit invalidations))
jvmRoute	null	(Retrieve the JvmRoute for the enclosing Engine)
maxActive	0	(Maximum number of active sessions so far)
maxActiveSessions	-1	(The maximum number of active Sessions allowed, or -1 for no limit)
modelerType	org.apache.catalina.session.StandardManager	(Type of the modeled resource. Can be set only once)
name	StandardManager	(The descriptive name of this Manager implementation (for logging))

pathname	SESSIONS.ser	(Path name of the disk file in which active sessions)
persistAuthentication	false	(Indicates whether sessions shall persist authentication information when being persisted (e.g. across application restarts).)
processExpiresFrequency	6	(The frequency of the manager checks (expiration and passivation))
processingTime	50	(Time spent doing housekeeping and expiration)
rejectedSessions	0	(Number of sessions we rejected due to maxActive being reached)
secureRandomAlgorithm	SHA1PRNG	(The secure random number generator algorithm name)
secureRandomClass	null	(The secure random number generator class name)
secureRandomProvider	null	(The secure random number generator provider name)
sessionAttributeNameFilter	null	(The string pattern used for including session attributes in distribution. Null means all attributes are included.)
sessionAttributeValueClassNameFilter	null	(The regular expression used to filter session attributes based on the implementation class of the value. The regular expression is anchored and must match the fully qualified class name.)
sessionAverageAliveTime	0	(Average time an expired session had been alive)
sessionCounter	0	(Total number of sessions created by this manager)
sessionCreateRate	0	(Session creation rate in sessions per minute)
sessionExpireRate	0	(Session expiration rate in sessions per minute)
sessionMaxAliveTime	0	(Longest time an expired session had been alive)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
warnOnSessionAttributeFilterFailure	false	(Should a WARN level log message be generated if a session attribute fails to match sessionAttributeNameFilter or sessionAttributeClassNameFilter?)

Mapper

(Maps requests received by the associated connector to Hosts, Contexts and Wrappers)

modelerType	org.apache.catalina.mapper.MapperListener	(Type of the modeled resource. Can be set only once)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

NamingResources

(Holds and manages the naming resources defined in the J2EE Enterprise Naming Context and their associated JNDI context)

container	StandardServer[8005]	(The container with which the naming resources are associated.)
environments	[]	(MBean Names of the set of defined environment entries for this web application)
modelerType	org.apache.catalina.deploy.NamingResourcesImpl	(Type of the modeled resource. Can be set only once)
resourceLinks	[]	(MBean Names of all the defined resource link references for this application.)

host=localhost,context=/

(Holds and manages the naming resources defined in the J2EE Enterprise Naming Context and their associated JNDI context)

container	StandardEngine[Catalina].StandardHost[localhost].StandardContext[]	(The container with which the naming resources are associated.)
environments	[]	(MBean Names of the set of defined environment entries for this web application)
modelerType	org.apache.catalina.deploy.NamingResourcesImpl	(Type of the modeled resource. Can be set only once)
resourceLinks	[]	(MBean Names of all the defined resource link references for this application.)
resources	[]	(MBean Names of all the defined resource references for this application.)

host=localhost,context=/demo

(Holds and manages the naming resources defined in the J2EE Enterprise Naming Context and their associated JNDI context)

container	StandardEngine[Catalina].StandardHost[localhost].StandardContext[/demo]	(The container with which the naming resources are associated.)
environments	[]	(MBean Names of the set of defined environment entries for this web application)
modelerType	org.apache.catalina.deploy.NamingResourcesImpl	(Type of the modeled resource. Can be set only once)
resourceLinks	[]	(MBean Names of all the defined resource link references for this application.)

host=localhost,context=/downloads

(Holds and manages the naming resources defined in the J2EE Enterprise Naming Context and their associated JNDI context)

container	StandardEngine[Catalina].StandardHost[localhost].StandardContext[/downloads]	(The container with which the naming resources are associated.)
environments	[]	(MBean Names of the set of defined environment entries for this web application)
modelerType	org.apache.catalina.deploy.NamingResourcesImpl	(Type of the modeled resource. Can be set only once)
resourceLinks	[]	(MBean Names of all the defined resource link references for this application.)
resources	[]	(MBean Names of all the defined resource references for this application.)

host=localhost,context=/usage

(Holds and manages the naming resources defined in the J2EE Enterprise Naming Context and their associated JNDI context)

container	StandardEngine[Catalina].StandardHost[localhost].StandardContext[/usage]	(The container with which the naming resources are associated.)
environments	[]	(MBean Names of the set of defined environment entries for this web application)
modelerType	org.apache.catalina.deploy.NamingResourcesImpl	(Type of the modeled resource. Can be set only once)
resourceLinks	[]	(MBean Names of all the defined resource link references for this application.)
resources	[]	(MBean Names of all the defined resource references for this application.)

ParallelWebappClassLoader

host=localhost,context=/

(Classloader implementation which is specialized for handling web applications and is capable of loading classes in parallel)

URLs	[]	(The URLs of this loader)
className	org.apache.catalina.loader.ParallelWebappClassLoader	(Fully qualified class name of the managed object)
contextName	ROOT	(Name of the webapp context)
delegate	false	(The 'follow standard delegation model' flag that will be used to configure our ClassLoader)
modelerType	org.apache.catalina.loader.ParallelWebappClassLoader	(Type of the modeled resource. Can be set only once)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

host=localhost,context=/demo

(Classloader implementation which is specialized for handling web applications and is capable of loading classes in parallel)

URLs	[war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/classes/, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdocreport.core-1.0.4.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/ehcache-core-2.6.8.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/log4j-1.2.17.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/spi4j-lib-security-server-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/slf4j-api-1.6.1.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/jta-1.1.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdocreport.template.freemarker-1.0.4.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/xpp3_min-1.1.4c.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/gwt-servlet-2.7.0.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/spi4j-gwt-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdocreport.document-1.0.4.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/itext-2.1.7.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdocreport.template-1.0.4.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/freemarker-2.3.16.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdocreport.converter-1.0.4.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/validation-api-1.0.0.GA.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/appwhite1-commons-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdocreport.document.docx-1.0.4.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/spi4j-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/jrobin-1.5.9.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdocreport.document.odt-1.0.4.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/spi4j-ui-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/javamelody-core-1.98.0.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/spi4j-doc-report-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/fr.opensagres.xdocreport.document.pptx-1.0.4.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/spi4j-lib-security-commons-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/appwhite1-server-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/referentiel-server-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/h2-1.4.200.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/xstream-1.4.11.1.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*/WEB-INF/lib/referentiel-commons-1.7-SNAPSHOT.jar]	(The URLs of this loader)
className	org.apache.catalina.loader.ParallelWebappClassLoader	(Fully qualified class name of the managed object)
contextName	demo	(Name of the webapp context)
delegate	false	(The 'follow standard delegation model' flag that will be used to configure our ClassLoader)
modelerType	org.apache.catalina.loader.ParallelWebappClassLoader	(Type of the modeled resource. Can be set only once)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

host=localhost,context=/downloads

(Classloader implementation which is specialized for handling web applications and is capable of loading classes in parallel)

URLs	[]	(The URLs of this loader)
className	org.apache.catalina.loader.ParallelWebappClassLoader	(Fully qualified class name of the managed object)
contextName	downloads	(Name of the webapp context)
delegate	false	(The 'follow standard delegation model' flag that will be used to configure our ClassLoader)
modelerType	org.apache.catalina.loader.ParallelWebappClassLoader	(Type of the modeled resource. Can be set only once)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

host=localhost,context=/usage

(Classloader implementation which is specialized for handling web applications and is capable of loading classes in parallel)

URLs	[war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/classes/, war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/javamelody-core-1.99.4.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/jrobin-1.5.9.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/itext-2.1.7.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/gson-2.10.1.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/commons-csv-1.10.0.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/log4j-1.2.17.jar]	(The URLs of this loader)
className	org.apache.catalina.loader.ParallelWebappClassLoader	(Fully qualified class name of the managed object)
contextName	usage	(Name of the webapp context)

delegate	false	(The 'follow standard delegation model' flag that will be used to configure our ClassLoader)
modelerType	org.apache.catalina.loader.ParallelWebappClassLoader	(Type of the modeled resource. Can be set only once)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

ProtocolHandler

port=80

acceptCount	100	(Introspected attribute acceptCount)
acceptorThreadCount	1	(Introspected attribute acceptorThreadCount)
acceptorThreadPriority	5	(Introspected attribute acceptorThreadPriority)
algorithm	SunX509	(Introspected attribute algorithm)
allowHostHeaderMismatch	false	(Introspected attribute allowHostHeaderMismatch)
allowedTrailerHeaders		(Introspected attribute allowedTrailerHeaders)
aprRequired	false	(Introspected attribute aprRequired)
ciphers	HIGH:!aNULL:!eNULL:!EXPORT:!DES:!RC4:!MD5:!kRSA	(Introspected attribute ciphers)
clientAuth	NONE	(Introspected attribute clientAuth)
clientCertProvider	null	(Introspected attribute clientCertProvider)
compressibleMimeType	text/html,text/xml,text/plain,text/css,text/javascript,application/javascript,application/json,application/xml	(Introspected attribute compressibleMimeType)
compressibleMimeTypes	[text/html, text/xml, text/plain, text/css, text/javascript, application/javascript, application/json, application/xml]	(Introspected attribute compressibleMimeTypes)
compression	off	(Introspected attribute compression)
compressionMinSize	2 048	(Introspected attribute compressionMinSize)
connectionCount	68	(Introspected attribute connectionCount)
connectionLinger	-1	(Introspected attribute connectionLinger)
connectionTimeout	20 000	(Introspected attribute connectionTimeout)
connectionUploadTimeout	300 000	(Introspected attribute connectionUploadTimeout)
crlFile	null	(Introspected attribute crlFile)
defaultSSLHostConfigName	_default_	(Introspected attribute defaultSSLHostConfigName)
disableUploadTimeout	true	(Introspected attribute disableUploadTimeout)
domain	Catalina	(Introspected attribute domain)
keepAliveTimeout	20 000	(Introspected attribute keepAliveTimeout)
keyAlias	null	(Introspected attribute keyAlias)
keyPass	null	(Introspected attribute keyPass)
keystoreFile	null	(Introspected attribute keystoreFile)
keystorePass	null	(Introspected attribute keystorePass)
keystoreProvider	null	(Introspected attribute keystoreProvider)
keystoreType	null	(Introspected attribute keystoreType)
localPort	80	(Introspected attribute localPort)
maxConnections	8 192	(Introspected attribute maxConnections)
maxExtensionSize	8 192	(Introspected attribute maxExtensionSize)
maxHeaderCount	100	(Introspected attribute maxHeaderCount)
maxHttpHeaderSize	8 192	(Introspected attribute maxHttpHeaderSize)
maxKeepAliveRequests	100	(Introspected attribute maxKeepAliveRequests)
maxSavePostSize	4 096	(Introspected attribute maxSavePostSize)
maxSwallowSize	2 097 152	(Introspected attribute maxSwallowSize)
maxThreads	200	(Introspected attribute maxThreads)
maxTrailerSize	8 192	(Introspected attribute maxTrailerSize)
minSpareThreads	10	(Introspected attribute minSpareThreads)
modelerType	org.apache.coyote.http11.Http11NioProtocol	(Type of the modeled resource. Can be set only once)
name	"http-nio-80"	(Introspected attribute name)
nameIndex	1	(Introspected attribute nameIndex)
noCompressionStrongETag	true	(Introspected attribute noCompressionStrongETag)
noCompressionUserAgents	null	(Introspected attribute noCompressionUserAgents)
objectName	Catalina:type=ProtocolHandler,port=80	(Introspected attribute objectName)
paused	false	(Introspected attribute paused)
pollerThreadCount	1	(Introspected attribute pollerThreadCount)
pollerThreadPriority	5	(Introspected attribute pollerThreadPriority)
port	80	(Introspected attribute port)
portOffset	0	(Introspected attribute portOffset)
portWithOffset	80	(Introspected attribute portWithOffset)
processorCache	200	(Introspected attribute processorCache)
rejectIllegalHeader	true	(Introspected attribute rejectIllegalHeader)
rejectIllegalHeaderName	true	(Introspected attribute rejectIllegalHeaderName)
relaxedPathChars	null	(Introspected attribute relaxedPathChars)
relaxedQueryChars	null	(Introspected attribute relaxedQueryChars)
restrictedUserAgents	null	(Introspected attribute restrictedUserAgents)
sSLCACertificateFile	null	(Introspected attribute sSLCACertificateFile)
sSLCACertificatePath	null	(Introspected attribute sSLCACertificatePath)
sSLCARevocationFile	null	(Introspected attribute sSLCARevocationFile)
sSLCARevocationPath	null	(Introspected attribute sSLCARevocationPath)
sSLCertificateChainFile	null	(Introspected attribute sSLCertificateChainFile)
sSLCertificateFile	null	(Introspected attribute sSLCertificateFile)
sSLCertificateKeyFile	null	(Introspected attribute sSLCertificateKeyFile)
sSLCipherSuite	HIGH:!aNULL:!eNULL:!EXPORT:!DES:!RC4:!MD5:!kRSA	(Introspected attribute sSLCipherSuite)
sSLDisableCompression	true	(Introspected attribute sSLDisableCompression)
sSLDisableSessionTickets	false	(Introspected attribute sSLDisableSessionTickets)

sSLEnabled	false	(Introspected attribute sSLEnabled)
sSLHonorCipherOrder	false	(Introspected attribute sSLHonorCipherOrder)
sSLPassword	null	(Introspected attribute sSLPassword)
sSLProtocol		(Introspected attribute sSLProtocol)
sSLVerifyClient	NONE	(Introspected attribute sSLVerifyClient)
sSLVerifyDepth	10	(Introspected attribute sSLVerifyDepth)
secure	false	(Introspected attribute secure)
selectorTimeout	1 000	(Introspected attribute selectorTimeout)
sendfileSupported	true	(Introspected attribute sendfileSupported)
server	null	(Introspected attribute server)
serverRemoveAppProvidedValues	false	(Introspected attribute serverRemoveAppProvidedValues)
sessionCacheSize	-1	(Introspected attribute sessionCacheSize)
sessionTimeout	86 400	(Introspected attribute sessionTimeout)
sniParseLimit	65 536	(Introspected attribute sniParseLimit)
sslEnabledProtocols		(Introspected attribute sslEnabledProtocols)
sslImplementationName	null	(Introspected attribute sslImplementationName)
sslProtocol	TLS	(Introspected attribute sslProtocol)
tcpNoDelay	true	(Introspected attribute tcpNoDelay)
threadPriority	5	(Introspected attribute threadPriority)
trustManagerClassName	null	(Introspected attribute trustManagerClassName)
trustMaxCertLength	10	(Introspected attribute trustMaxCertLength)
truststoreAlgorithm	PKIX	(Introspected attribute truststoreAlgorithm)
truststoreFile	null	(Introspected attribute truststoreFile)
truststorePass	null	(Introspected attribute truststorePass)
truststoreProvider	null	(Introspected attribute truststoreProvider)
truststoreType	JKS	(Introspected attribute truststoreType)
useKeepAliveResponseHeader	true	(Introspected attribute useKeepAliveResponseHeader)
useSendfile	true	(Introspected attribute useSendfile)
useServerCipherSuitesOrder	false	(Introspected attribute useServerCipherSuitesOrder)

Realm

realmPath=/realm0

(Realm implementation that can be used to wrap existing realms to provide a user lock-out capability)

allRolesMode	strict	(The all roles mode.)
cacheRemovalWarningTime	3 600	(If a failed user is removed from the cache because the cache is too big before it has been in the cache for at least this period of time (in seconds) a warning message will be logged. Defaults to 3600 (1 hour).)
cacheSize	1 000	(Number of users that have failed authentication to keep in cache. Over time the cache will grow to this size and may not shrink. Defaults to 1000.)
className	org.apache.catalina.realm.LockOutRealm	(Fully qualified class name of the managed object)
failureCount	5	(The number of times in a row a user has to fail authentication to be locked out. Defaults to 5.)
lockOutTime	300	(The time (in seconds) a user is locked out for after too many authentication failures. Defaults to 300 (5 minutes).)
modelerType	org.apache.catalina.realm.LockOutRealm	(Type of the modeled resource. Can be set only once)
realmPath	/realm0	(The realm path)
realms	[Catalina:type=Realm,realmPath=/realm0/realm0]	(The set of realms that the lockout realm is wrapping)
validate	true	(The 'validate certificate chains' flag.)

realmPath=/realm0/realm0

(Realm connected to a UserDatabase as a global JNDI resource)

allRolesMode	strict	(The all roles mode.)
className	org.apache.catalina.realm.UserDatabaseRealm	(Fully qualified class name of the managed object)
modelerType	org.apache.catalina.realm.UserDatabaseRealm	(Type of the modeled resource. Can be set only once)
realmPath	/realm0/realm0	(The realm path)
resourceName	UserDatabase	(The global JNDI name of the UserDatabase resource to use)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
validate	true	(The 'validate certificate chains' flag.)

RequestProcessor

worker="http-nio-80",name=HttpRequest1

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	775	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	2	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	30	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 491	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 650	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)

requestCount	3	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest1	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest10

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 388	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 388	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 388	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest10	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest100

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	1	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 363	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 363	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 363	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest100	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest101

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	2 825	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	4	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	59	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	890	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 468	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)

remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	6	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest101	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest102

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 362	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 362	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 362	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest102	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest103

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 362	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 362	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 362	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest103	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest104

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 362	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 362	(Introspected attribute maxTime)

method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 362	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest104	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest105

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 363	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 363	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 363	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest105	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest106

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 362	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 362	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 362	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest106	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest107

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)

globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 363	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 363	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 363	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest107	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest108

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 360	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 360	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 360	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest108	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest109

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 360	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 360	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 360	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest109	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest11

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 388	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 388	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 388	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest11	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest110

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	709	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	1	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	31	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 247	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 278	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	2	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest110	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest111

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 361	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 361	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 361	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest111	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)

virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest112

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 360	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 360	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 360	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest112	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest113

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 360	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 360	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 360	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest113	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest114

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 360	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 360	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 360	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)

requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest114	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest115

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 360	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 360	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 360	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest115	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest116

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 361	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 361	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 361	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest116	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest117

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 360	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 360	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 360	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)

remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest117	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest118

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	713	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	1	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	12	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 360	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 372	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	2	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest118	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest119

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	711	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	1	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	26	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 363	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 389	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	2	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest119	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest12

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 388	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 388	(Introspected attribute maxTime)
method	null	(Introspected attribute method)

modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 388	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest12	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest120

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	705	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	1	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	28	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 047	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 075	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	2	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest120	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest121

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	977	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	977	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	977	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest121	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest122

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)

lastRequestProcessingTime	919	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	919	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	919	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest122	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest123

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	600	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	600	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	600	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest123	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest124

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	598	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	598	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	598	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest124	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest125

bytesReceived	7 492	(Introspected attribute bytesReceived)
bytesSent	403 233 021	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	graph=sqlHitsRate&part=graph&period=annee	(Introspected attribute currentQueryString)
currentUri	/demo/monitoring	(Introspected attribute currentUri)
errorCount	42 524	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	26	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/demo/monitoring	(Introspected attribute maxRequestUri)
maxTime	44 159	(Introspected attribute maxTime)
method	GET	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	3 823 540	(Introspected attribute processingTime)
protocol	HTTP/1.1	(Introspected attribute protocol)
remoteAddr	216.73.217.98	(Introspected attribute remoteAddr)
remoteAddrForwarded	216.73.217.98	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	4 026 460	(Introspected attribute requestCount)
requestProcessingTime	125	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest125	(Introspected attribute rpName)
serverPort	80	(Introspected attribute serverPort)
stage	3	(Introspected attribute stage)
virtualHost	javamelody.org	(Introspected attribute virtualHost)
workerThreadName	http-nio-80-exec-103	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest126

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	701	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	1	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	28	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	475	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	503	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	2	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest126	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest127

bytesReceived	3 243	(Introspected attribute bytesReceived)
bytesSent	107 883 984	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	format=pdf&part=mbeans	(Introspected attribute currentQueryString)
currentUri	/demo/monitoring	(Introspected attribute currentUri)
errorCount	14 773	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	0	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/demo/appli1/76D8F506E8C1C9F1C97A7B6838FF8BC4.cache.js	(Introspected attribute maxRequestUri)
maxTime	30 982	(Introspected attribute maxTime)
method	GET	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 555 730	(Introspected attribute processingTime)
protocol	HTTP/1.1	(Introspected attribute protocol)
remoteAddr	216.73.217.98	(Introspected attribute remoteAddr)
remoteAddrForwarded	216.73.217.98	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	994 480	(Introspected attribute requestCount)
requestProcessingTime	158	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest127	(Introspected attribute rpName)
serverPort	80	(Introspected attribute serverPort)
stage	3	(Introspected attribute stage)

virtualHost	javamelody.org	(Introspected attribute virtualHost)
workerThreadName	http-nio-80-exec-97	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest128

bytesReceived	12 653	(Introspected attribute bytesReceived)
bytesSent	505 788 361	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	50 044	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	55	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/demo/monitoring	(Introspected attribute maxRequestUri)
maxTime	60 004	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	5 280 595	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	4 788 537	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest128	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest129

bytesReceived	648	(Introspected attribute bytesReceived)
bytesSent	156 766 131	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	28 931	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	0	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/demo/monitoring	(Introspected attribute maxRequestUri)
maxTime	80 227	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 554 812	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1 428 777	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest129	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest13

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 388	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 388	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 388	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)

requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest13	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest130

bytesReceived	3 330	(Introspected attribute bytesReceived)
bytesSent	63 002 104	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	11 709	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	0	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/demo/monitoring	(Introspected attribute maxRequestUri)
maxTime	27 570	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 000 058	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	566 464	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest130	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest131

bytesReceived	3 107	(Introspected attribute bytesReceived)
bytesSent	328 828 720	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	33 324	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	0	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/demo/monitoring	(Introspected attribute maxRequestUri)
maxTime	60 048	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	3 005 775	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	3 268 436	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest131	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest14

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 388	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 388	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 388	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)

remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest14	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest15

bytesReceived	4 140	(Introspected attribute bytesReceived)
bytesSent	375 006 056	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	56 512	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	59	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/demo/monitoring	(Introspected attribute maxRequestUri)
maxTime	60 037	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	3 805 641	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	3 711 006	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest15	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest16

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	1 384	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	2	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	31	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	863	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 368	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	3	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest16	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest17

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 385	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 385	(Introspected attribute maxTime)
method	null	(Introspected attribute method)

modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 385	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest17	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest18

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 385	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 385	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 385	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest18	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest19

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 385	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 385	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 385	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest19	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest2

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)

lastRequestProcessingTime	1 084	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 084	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 084	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest2	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest20

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 383	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 383	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 383	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest20	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest21

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 384	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 384	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 384	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest21	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest22

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 383	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 383	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 383	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest22	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest23

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	1 382	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	2	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	30	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	723	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 284	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	3	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest23	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest24

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 383	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 383	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 383	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest24	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)

virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest25

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 383	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 383	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 383	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest25	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest26

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 384	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 384	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 384	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest26	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest27

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 384	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 384	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 384	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)

requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest27	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest28

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 384	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 384	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 384	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest28	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest29

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	1 383	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	2	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	29	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	721	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 278	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	3	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest29	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest3

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	711	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	1	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	26	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 521	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 547	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)

remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	2	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest3	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest30

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 384	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 384	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 384	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest30	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest31

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	1 387	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	2	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	29	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	676	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 231	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	3	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest31	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest32

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 382	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 382	(Introspected attribute maxTime)
method	null	(Introspected attribute method)

modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 382	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest32	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest33

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	1 411	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	2	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	583	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	583	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 192	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	3	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest33	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest34

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 382	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 382	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 382	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest34	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest35

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)

lastRequestProcessingTime	1 382	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 382	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 382	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest35	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest36

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	1 397	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	2	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	28	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	671	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 221	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	3	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest36	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest37

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 382	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 382	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 382	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest37	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest38

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 382	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 382	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 382	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest38	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest39

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	1	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 380	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 380	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 380	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest39	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest4

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	710	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	1	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	25	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 519	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 544	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	2	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest4	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)

virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest40

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 380	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 380	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 380	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest40	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest41

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	1	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 380	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 380	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 380	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest41	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest42

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 380	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 380	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 380	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)

requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest42	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest43

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 380	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 380	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 380	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest43	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest44

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 380	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 380	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 380	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest44	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest45

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 381	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 381	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 381	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)

remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest45	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest46

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	1	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 380	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 380	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 380	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest46	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest47

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	707	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	1	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	33	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 047	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 080	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	2	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest47	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest48

bytesReceived	4 466	(Introspected attribute bytesReceived)
bytesSent	375 077 730	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	format=xml&graph=threadCount&period=jour	(Introspected attribute currentQueryString)
currentUri	/demo/monitoring	(Introspected attribute currentUri)
errorCount	32 286	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	0	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/demo/monitoring	(Introspected attribute maxRequestUri)
maxTime	42 114	(Introspected attribute maxTime)
method	GET	(Introspected attribute method)

modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	3 430 008	(Introspected attribute processingTime)
protocol	HTTP/1.1	(Introspected attribute protocol)
remoteAddr	216.73.217.98	(Introspected attribute remoteAddr)
remoteAddrForwarded	216.73.217.98	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	3 789 060	(Introspected attribute requestCount)
requestProcessingTime	20	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest48	(Introspected attribute rpName)
serverPort	80	(Introspected attribute serverPort)
stage	3	(Introspected attribute stage)
virtualHost	javamelody.org	(Introspected attribute virtualHost)
workerThreadName	http-nio-80-exec-166	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest49

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 380	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 380	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 380	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest49	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest5

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	705	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	1	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	16	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 519	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 535	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	2	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest5	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest50

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)

lastRequestProcessingTime	1 380	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 380	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 380	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest50	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest51

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	702	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	1	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	32	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 048	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 080	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	2	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest51	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest52

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 378	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 378	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 378	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest52	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest53

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 378	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 378	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 378	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest53	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest54

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 378	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 378	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 378	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest54	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest55

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	1 383	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	2	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	30	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	641	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 178	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	3	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest55	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)

virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest56

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 378	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 378	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 378	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest56	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest57

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 377	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 377	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 377	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest57	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest58

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 376	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 376	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 376	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)

requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest58	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest59

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	711	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	1	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	33	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 063	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 096	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	2	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest59	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest6

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	716	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	1	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	16	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 517	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 533	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	2	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest6	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest60

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	1 383	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	2	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	29	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	602	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 123	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)

remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	3	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest60	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest61

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 376	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 376	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 376	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest61	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest62

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 376	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 376	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 376	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest62	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest63

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 376	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 376	(Introspected attribute maxTime)
method	null	(Introspected attribute method)

modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 376	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest63	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest64

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 376	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 376	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 376	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest64	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest65

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 376	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 376	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 376	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest65	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest66

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)

lastRequestProcessingTime	1 376	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 376	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 376	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest66	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest67

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	716	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	1	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	32	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 086	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 118	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	2	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest67	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest68

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 376	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 376	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 376	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest68	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest69

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	1	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 377	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 377	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 377	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest69	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest7

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	7 126	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	11	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	0	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 516	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 531	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	12	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest7	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest70

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 374	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 374	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 374	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest70	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)

virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest71

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 374	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 374	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 374	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest71	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest72

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 375	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 375	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 375	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest72	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest73

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 374	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 374	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 374	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)

requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest73	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest74

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 375	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 375	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 375	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest74	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest75

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 372	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 372	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 372	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest75	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest76

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 373	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 373	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 373	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)

remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest76	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest77

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 373	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 373	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 373	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest77	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest78

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 372	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 372	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 372	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest78	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest79

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	706	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	1	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	32	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 110	(Introspected attribute maxTime)
method	null	(Introspected attribute method)

modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 142	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	2	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest79	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest8

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	718	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	1	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	26	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 450	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 476	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	2	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest8	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest80

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 372	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 372	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 372	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest80	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest81

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)

lastRequestProcessingTime	1 370	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 370	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 370	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest81	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest82

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 371	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 371	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 371	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest82	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest83

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	1	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 371	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 371	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 371	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest83	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest84

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 371	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 371	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 371	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest84	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest85

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 371	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 371	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 371	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest85	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest86

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 371	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 371	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 371	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest86	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)

virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest87

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	1	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 370	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 370	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 370	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest87	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest88

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 368	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 368	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 368	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest88	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest89

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 368	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 368	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 368	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)

requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest89	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest9

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 389	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 389	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 389	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest9	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest90

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 367	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 367	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 367	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest90	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest91

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	1 383	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	2	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	32	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	835	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 351	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)

remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	3	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest91	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest92

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	707	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	1	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	31	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 179	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 210	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	2	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest92	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest93

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	1	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 367	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 367	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 367	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest93	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest94

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 366	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 366	(Introspected attribute maxTime)
method	null	(Introspected attribute method)

modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 366	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest94	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest95

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 367	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 367	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 367	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest95	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest96

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	3 216	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	4	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	59	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	872	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 459	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	12	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest96	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest97

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)

lastRequestProcessingTime	1 367	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 367	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 367	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest97	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest98

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	63	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1 365	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	1 365	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 365	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest98	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

worker="http-nio-80",name=HttpRequest99

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	709	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	1	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	29	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/	(Introspected attribute maxRequestUri)
maxTime	774	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 326	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	3	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest99	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

Resource

resourcetype=Context,host=localhost,context=/demo,class=javax.sql.DataSource,name="jdbc/demo_javamelody"

(Representation of a resource reference for a web application)

auth	Container	(The authorization requirement for this resource)
description	Datasource	(The description of this resource)
name	jdbc/demo_javamelody	(The name of this resource)
scope	Shareable	(The sharing scope of this resource factory)
type	javax.sql.DataSource	(The type of this environment entry)

resourcetype=Global,class=org.apache.catalina.UserDatabase,name="UserDatabase"

(Representation of a resource reference for a web application)

auth	Container	(The authorization requirement for this resource)
description	User database that can be updated and saved	(The description of this resource)
name	UserDatabase	(The name of this resource)
scope	Shareable	(The sharing scope of this resource factory)
type	org.apache.catalina.UserDatabase	(The type of this environment entry)

SSLHostConfig

ThreadPool="http-nio-80",name="_default_"

caCertificateFile	null	(Introspected attribute caCertificateFile)
caCertificatePath	null	(Introspected attribute caCertificatePath)
certificateChainFile	null	(Introspected attribute certificateChainFile)
certificateFile	null	(Introspected attribute certificateFile)
certificateKeyAlias	null	(Introspected attribute certificateKeyAlias)
certificateKeyFile	null	(Introspected attribute certificateKeyFile)
certificateKeyPassword	null	(Introspected attribute certificateKeyPassword)
certificateKeystoreFile	null	(Introspected attribute certificateKeystoreFile)
certificateKeystorePassword	null	(Introspected attribute certificateKeystorePassword)
certificateKeystoreProvider	null	(Introspected attribute certificateKeystoreProvider)
certificateKeystoreType	null	(Introspected attribute certificateKeystoreType)
certificateRevocationListFile	null	(Introspected attribute certificateRevocationListFile)
certificateRevocationListPath	null	(Introspected attribute certificateRevocationListPath)
certificateVerificationAsString	NONE	(Introspected attribute certificateVerificationAsString)
certificateVerificationDepth	10	(Introspected attribute certificateVerificationDepth)
certificateVerificationDepthConfigured	false	(Introspected attribute certificateVerificationDepthConfigured)
ciphers	HIGH:!aNULL:!eNULL:!EXPORT:!DES:!RC4:!MD5:!kRSA	(Introspected attribute ciphers)
disableCompression	true	(Introspected attribute disableCompression)
disableSessionTickets	false	(Introspected attribute disableSessionTickets)
enabledCiphers	null	(Introspected attribute enabledCiphers)
enabledProtocols	null	(Introspected attribute enabledProtocols)
honorCipherOrder	false	(Introspected attribute honorCipherOrder)
hostName	_default_	(Introspected attribute hostName)
insecureRenegotiation	false	(Introspected attribute insecureRenegotiation)
keyManagerAlgorithm	SunX509	(Introspected attribute keyManagerAlgorithm)
modelerType	org.apache.tomcat.util.net.SSLHostConfig	(Type of the modeled resource. Can be set only once)
objectName	Catalina:type=SSLHostConfig,ThreadPool="http-nio-80",name="_default_"	(Introspected attribute objectName)
openSslConf	null	(Introspected attribute openSslConf)
openSslConfContext	0	(Introspected attribute openSslConfContext)
openSslContext	0	(Introspected attribute openSslContext)
revocationEnabled	false	(Introspected attribute revocationEnabled)
sessionCacheSize	-1	(Introspected attribute sessionCacheSize)
sessionTimeout	86 400	(Introspected attribute sessionTimeout)
sslProtocol	TLS	(Introspected attribute sslProtocol)
trustManagerClassName	null	(Introspected attribute trustManagerClassName)
truststoreAlgorithm	PKIX	(Introspected attribute truststoreAlgorithm)
truststoreFile	null	(Introspected attribute truststoreFile)
truststorePassword	null	(Introspected attribute truststorePassword)
truststoreProvider	null	(Introspected attribute truststoreProvider)
truststoreType	JKS	(Introspected attribute truststoreType)

Server

(Standard Server Component)

address	localhost	(The address on which we wait for shutdown commands.)
managedResource	StandardServer[8005]	(The managed resource this MBean is associated with)
modelerType	org.apache.catalina.core.StandardServer	(Type of the modeled resource. Can be set only once)
port	8 005	(TCP port (excluding any offset) for shutdown messages)
portOffset	0	(The offset applied to port and to the port attributes of any nested connectors)
portWithOffset	8 005	(Actual TCP port (including any offset) for shutdown messages)
serverBuilt	Mar 11 2020 09:31:38 UTC	(Tomcat server built timestamp)
serverInfo	Apache Tomcat/9.0.33	(Tomcat server release identifier)
serverNumber	9.0.33.0	(Tomcat server's version number)
serviceNames	[Catalina:type=Service]	(Object names of all services we know about)
shutdown	SHUTDOWN	(Shutdown password)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

Service

(Standard Service Component)

connectorNames	[Catalina:type=Connector,port=80]	(ObjectNames of the connectors)
managedResource	StandardService[Catalina]	(The managed resource this MBean is associated with)
modelerType	org.apache.catalina.core.StandardService	(Type of the modeled resource. Can be set only once)
name	Catalina	(Unique name of this Service)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

Servlet

WebModule=//localhost/,name=default,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	89 357	(Error count)
loadOnStartup	1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	1	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	23	(Maximum processing time of a request)
minTime	0	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=//localhost/,name=default,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	12 610	(Total execution time of the servlet's service method)
requestCount	89 349	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	org.apache.catalina.servlets.DefaultServlet	(The run-as identity for this servlet.)
singleThreadModel	false	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=//localhost/,name=jsp,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	123	(Error count)
loadOnStartup	3	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	0	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	613	(Maximum processing time of a request)
minTime	0	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=//localhost/,name=jsp,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	9 471	(Total execution time of the servlet's service method)
requestCount	31 716	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	org.apache.jasper.servlet.JspServlet	(The run-as identity for this servlet.)
singleThreadModel	false	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=//localhost/demo,name=AdresseService,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	-1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	0	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	0	(Maximum processing time of a request)
minTime	9 223 372 036 854 775 807	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=//localhost/demo,name=AdresseService,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	0	(Total execution time of the servlet's service method)

requestCount	0	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	fr.appwhite1.server.business.annuaire.AdresseGwtServiceImpl	(The run-as identity for this servlet.)
singleThreadModel	null	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=//localhost/demo,name=AuthentificationService,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	2 428	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	-1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	2 428	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	23 602	(Maximum processing time of a request)
minTime	1	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=//localhost/demo,name=AuthentificationService,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	38 515	(Total execution time of the servlet's service method)
requestCount	171	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	fr.appwhite1.server.business.secu.AuthentificationGwtServiceImpl	(The run-as identity for this servlet.)
singleThreadModel	false	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=//localhost/demo,name=BuildInfoServlet,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	2	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	2	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	0	(Maximum processing time of a request)
minTime	9 223 372 036 854 775 807	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=//localhost/demo,name=BuildInfoServlet,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	0	(Total execution time of the servlet's service method)
requestCount	0	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	fr.appwhite1.Appli1BuildInfoServlet	(The run-as identity for this servlet.)
singleThreadModel	false	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=//localhost/demo,name=CompetenceService,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	-1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	0	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	0	(Maximum processing time of a request)
minTime	9 223 372 036 854 775 807	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=//localhost/demo,name=CompetenceService,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	0	(Total execution time of the servlet's service method)
requestCount	0	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)

servletClass	fr.appwhite1.server.business.annuaire.CompetenceGwtServiceImpl	(The run-as identity for this servlet.)
singleThreadModel	null	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=//localhost/demo,name=GradeService,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	1	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	-1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	2	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	5 839	(Maximum processing time of a request)
minTime	1	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=//localhost/demo,name=GradeService,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	5 936	(Total execution time of the servlet's service method)
requestCount	22	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	fr.referentiel.server.business.ref.GradeGwtServiceImpl	(The run-as identity for this servlet.)
singleThreadModel	false	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=//localhost/demo,name=MailService,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	-1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	0	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	0	(Maximum processing time of a request)
minTime	9 223 372 036 854 775 807	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=//localhost/demo,name=MailService,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	0	(Total execution time of the servlet's service method)
requestCount	0	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	fr.appwhite1.server.business.annuaire.MailGwtServiceImpl	(The run-as identity for this servlet.)
singleThreadModel	null	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=//localhost/demo,name=PermissionService,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	-1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	0	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	0	(Maximum processing time of a request)
minTime	9 223 372 036 854 775 807	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=//localhost/demo,name=PermissionService,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	0	(Total execution time of the servlet's service method)
requestCount	0	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	fr.appwhite1.server.business.secu.PermissionGwtServiceImpl	(The run-as identity for this servlet.)
singleThreadModel	null	(Does this servlet implement the SingleThreadModel interface?)

stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=//localhost/demo,name=PersonneService,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	1	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	-1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	1	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	20 269	(Maximum processing time of a request)
minTime	4	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=//localhost/demo,name=PersonneService,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	23 599	(Total execution time of the servlet's service method)
requestCount	35	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	fr.appwhite1.server.business.annuaire.PersonneGwtServiceImpl	(The run-as identity for this servlet.)
singleThreadModel	false	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=//localhost/demo,name=PrintUtilsService,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	-1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	0	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	0	(Maximum processing time of a request)
minTime	9 223 372 036 854 775 807	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=//localhost/demo,name=PrintUtilsService,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	0	(Total execution time of the servlet's service method)
requestCount	0	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	fr.appwhite1.server.business.utils.PrintUtilsGwtServiceImpl	(The run-as identity for this servlet.)
singleThreadModel	null	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=//localhost/demo,name=RoleService,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	-1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	0	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	0	(Maximum processing time of a request)
minTime	9 223 372 036 854 775 807	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=//localhost/demo,name=RoleService,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	0	(Total execution time of the servlet's service method)
requestCount	0	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	fr.appwhite1.server.business.secu.RoleGwtServiceImpl	(The run-as identity for this servlet.)
singleThreadModel	null	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=//localhost/demo,name=TelephoneService,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	-1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	0	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	0	(Maximum processing time of a request)
minTime	9 223 372 036 854 775 807	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=//localhost/demo,name=TelephoneService,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	0	(Total execution time of the servlet's service method)
requestCount	0	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	fr.appwhite1.server.business.annuaire.TelephoneGwtServiceImpl	(The run-as identity for this servlet.)
singleThreadModel	null	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=//localhost/demo,name=UtilisateurService,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	-1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	0	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	0	(Maximum processing time of a request)
minTime	9 223 372 036 854 775 807	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=//localhost/demo,name=UtilisateurService,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	0	(Total execution time of the servlet's service method)
requestCount	0	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	fr.appwhite1.server.business.secu.UtilisateurGwtServiceImpl	(The run-as identity for this servlet.)
singleThreadModel	null	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=//localhost/demo,name=default,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	2	(Time taken to load the Servlet class)
countAllocated	5	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	169 270	(Error count)
loadOnStartup	1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	2	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	60 048	(Maximum processing time of a request)
minTime	0	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=//localhost/demo,name=default,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	5 347 009	(Total execution time of the servlet's service method)
requestCount	210 470	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	org.apache.catalina.servlets.DefaultServlet	(The run-as identity for this servlet.)
singleThreadModel	false	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=//localhost/demo,name=jsp,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	3	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	30	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	0	(Maximum processing time of a request)
minTime	9 223 372 036 854 775 807	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=//localhost/demo,name=jsp,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	0	(Total execution time of the servlet's service method)
requestCount	0	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	org.apache.jasper.servlet.JspServlet	(The run-as identity for this servlet.)
singleThreadModel	false	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=//localhost/downloads,name=default,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	102	(Error count)
loadOnStartup	1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	0	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	12	(Maximum processing time of a request)
minTime	0	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=//localhost/downloads,name=default,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	49	(Total execution time of the servlet's service method)
requestCount	115	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	org.apache.catalina.servlets.DefaultServlet	(The run-as identity for this servlet.)
singleThreadModel	false	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=//localhost/downloads,name=jsp,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	3	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	1	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	0	(Maximum processing time of a request)
minTime	9 223 372 036 854 775 807	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=//localhost/downloads,name=jsp,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	0	(Total execution time of the servlet's service method)
requestCount	0	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	org.apache.jasper.servlet.JspServlet	(The run-as identity for this servlet.)
singleThreadModel	false	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=//localhost/usage,name=admin,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	1	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	20	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	0	(Maximum processing time of a request)
minTime	9 223 372 036 854 775 807	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=//localhost/usage,name=admin,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	0	(Total execution time of the servlet's service method)
requestCount	0	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	net.bull.javamelody.usagestats.AdminServlet	(The run-as identity for this servlet.)
singleThreadModel	false	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=//localhost/usage,name=default,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	5	(Error count)
loadOnStartup	1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	0	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	7	(Maximum processing time of a request)
minTime	0	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=//localhost/usage,name=default,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	28	(Total execution time of the servlet's service method)
requestCount	30	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	org.apache.catalina.servlets.DefaultServlet	(The run-as identity for this servlet.)
singleThreadModel	false	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=//localhost/usage,name=jsp,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	3	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	0	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	0	(Maximum processing time of a request)
minTime	9 223 372 036 854 775 807	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=//localhost/usage,name=jsp,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	0	(Total execution time of the servlet's service method)
requestCount	0	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	org.apache.jasper.servlet.JspServlet	(The run-as identity for this servlet.)
singleThreadModel	false	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule=//localhost/usage,name=usagestats,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	42	(Error count)
loadOnStartup	1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	285 800	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	6 074	(Maximum processing time of a request)
minTime	0	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=//localhost/usage,name=usagestats,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	4 939 562	(Total execution time of the servlet's service method)
requestCount	22 230 317	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	net.bull.javamelody.usagestats.UsageStatsServlet	(The run-as identity for this servlet.)
singleThreadModel	false	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

StringCache

accessCount	90 704 427	(Introspected attribute accessCount)
byteEnabled	true	(Introspected attribute byteEnabled)
cacheSize	200	(Introspected attribute cacheSize)
charEnabled	false	(Introspected attribute charEnabled)
hitCount	67 935 621	(Introspected attribute hitCount)
modelerType	org.apache.tomcat.util.buf.StringCache	(Type of the modeled resource. Can be set only once)
trainThreshold	20 000	(Introspected attribute trainThreshold)

ThreadPool

name="http-nio-80"

acceptCount	100
acceptorThreadCount	1
acceptorThreadPriority	5
alpnSupported	false
bindOnInit	true
connectionCount	68
connectionLinger	-1
connectionTimeout	20 000
currentThreadCount	46
currentThreadsBusy	3
daemon	true
defaultSSLHostConfigName	_default_
deferAccept	false
domain	Catalina
executorTerminationTimeoutMillis	5 000
keepAliveCount	0
keepAliveTimeout	20 000
localPort	80
maxConnections	8 192
maxKeepAliveRequests	100
maxThreads	200
minSpareThreads	10
modelerType	org.apache.tomcat.util.net.NioEndpoint
name	http-nio-80
paused	false
pollerThreadCount	1
pollerThreadPriority	5
port	80
portOffset	0
portWithOffset	80
running	true
sSLEnabled	false
selectorTimeout	1 000
sniParseLimit	65 536
sslImplementation	null
sslImplementationName	null
tcpNoDelay	true
threadPriority	5
useInheritedChannel	false
useSendfile	true

name="http-nio-80",subType=SocketProperties

appReadBufSize	8 192	(Introspected attribute appReadBufSize)
appWriteBufSize	8 192	(Introspected attribute appWriteBufSize)
bufferPool	500	(Introspected attribute bufferPool)
bufferPoolSize	104 857 600	(Introspected attribute bufferPoolSize)
directBuffer	false	(Introspected attribute directBuffer)
directBufferPool	500	(Introspected attribute directBufferPool)
directSslBuffer	false	(Introspected attribute directSslBuffer)
eventCache	500	(Introspected attribute eventCache)
modelerType	org.apache.tomcat.util.net.SocketProperties	(Type of the modeled resource. Can be set only once)
processorCache	500	(Introspected attribute processorCache)
soLingerOn	false	(Introspected attribute soLingerOn)
soLingerTime	-1	(Introspected attribute soLingerTime)
soTimeout	20 000	(Introspected attribute soTimeout)
tcpNoDelay	true	(Introspected attribute tcpNoDelay)
timeoutInterval	1 000	(Introspected attribute timeoutInterval)
unlockTimeout	250	(Introspected attribute unlockTimeout)

UtilityExecutor

activeCount	0	(Introspected attribute activeCount)
completedTaskCount	4 755 079	(Introspected attribute completedTaskCount)
continueExistingPeriodicTasksAfterShutdownPolicy	false	(Introspected attribute continueExistingPeriodicTasksAfterShutdownPolicy)
corePoolSize	2	(Introspected attribute corePoolSize)
executeExistingDelayedTasksAfterShutdownPolicy	false	(Introspected attribute executeExistingDelayedTasksAfterShutdownPolicy)
largestPoolSize	2	(Introspected attribute largestPoolSize)
maximumPoolSize	2 147 483 647	(Introspected attribute maximumPoolSize)
modelerType	java.util.concurrent.ScheduledThreadPoolExecutor	(Type of the modeled resource. Can be set only once)
poolSize	2	(Introspected attribute poolSize)
removeOnCancelPolicy	true	(Introspected attribute removeOnCancelPolicy)
shutdown	false	(Introspected attribute shutdown)
taskCount	4 755 085	(Introspected attribute taskCount)
terminated	false	(Introspected attribute terminated)
terminating	false	(Introspected attribute terminating)

Valve

host=localhost,context=/,name=NonLoginAuthenticator

(An Authenticator and Valve implementation that checks only security constraints not involving user authentication)

cache	true	(Should we cache authenticated Principals if the request is part of an HTTP session?)
changeSessionIdOnAuthentication	true	(Controls if the session ID is changed if a session exists at the point where users are authenticated)
className	org.apache.catalina.authenticator.NonLoginAuthenticator	(Fully qualified class name of the managed object)
disableProxyCaching	true	(Controls the caching of pages that are protected by security constraints)
modelerType	org.apache.catalina.authenticator.NonLoginAuthenticator	(Type of the modeled resource. Can be set only once)
securePagesWithPragma	false	(Controls the caching of pages that are protected by security constraints)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

host=localhost,context=/,name=StandardContextValve

(Valve that implements the default basic behavior for the StandardContext container implementation)

asyncSupported	true	(Does this valve support async reporting?)
className	org.apache.catalina.core.StandardContextValve	(Fully qualified class name of the managed object)
modelerType	org.apache.catalina.core.StandardContextValve	(Type of the modeled resource. Can be set only once)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

host=localhost,context=/demo,name=NonLoginAuthenticator

(An Authenticator and Valve implementation that checks only security constraints not involving user authentication)

cache	true	(Should we cache authenticated Principals if the request is part of an HTTP session?)
changeSessionIdOnAuthentication	true	(Controls if the session ID is changed if a session exists at the point where users are authenticated)
className	org.apache.catalina.authenticator.NonLoginAuthenticator	(Fully qualified class name of the managed object)
disableProxyCaching	true	(Controls the caching of pages that are protected by security constraints)
modelerType	org.apache.catalina.authenticator.NonLoginAuthenticator	(Type of the modeled resource. Can be set only once)
securePagesWithPragma	false	(Controls the caching of pages that are protected by security constraints)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

host=localhost,context=/demo,name=StandardContextValve

(Valve that implements the default basic behavior for the StandardContext container implementation)

asyncSupported	true	(Does this valve support async reporting?)
className	org.apache.catalina.core.StandardContextValve	(Fully qualified class name of the managed object)
modelerType	org.apache.catalina.core.StandardContextValve	(Type of the modeled resource. Can be set only once)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

host=localhost,context=/downloads,name=NonLoginAuthenticator

(An Authenticator and Valve implementation that checks only security constraints not involving user authentication)

cache	true	(Should we cache authenticated Principals if the request is part of an HTTP session?)
changeSessionIdOnAuthentication	true	(Controls if the session ID is changed if a session exists at the point where users are authenticated)
className	org.apache.catalina.authenticator.NonLoginAuthenticator	(Fully qualified class name of the managed object)
disableProxyCaching	true	(Controls the caching of pages that are protected by security constraints)
modelerType	org.apache.catalina.authenticator.NonLoginAuthenticator	(Type of the modeled resource. Can be set only once)
securePagesWithPragma	false	(Controls the caching of pages that are protected by security constraints)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

host=localhost,context=/downloads,name=StandardContextValve

(Valve that implements the default basic behavior for the StandardContext container implementation)

asyncSupported	true	(Does this valve support async reporting?)
className	org.apache.catalina.core.StandardContextValve	(Fully qualified class name of the managed object)
modelerType	org.apache.catalina.core.StandardContextValve	(Type of the modeled resource. Can be set only once)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

host=localhost,context=/usage,name=NonLoginAuthenticator

(An Authenticator and Valve implementation that checks only security constraints not involving user authentication)

cache	true	(Should we cache authenticated Principals if the request is part of an HTTP session?)
changeSessionIdOnAuthentication	true	(Controls if the session ID is changed if a session exists at the point where users are authenticated)
className	org.apache.catalina.authenticator.NonLoginAuthenticator	(Fully qualified class name of the managed object)
disableProxyCaching	true	(Controls the caching of pages that are protected by security constraints)
modelerType	org.apache.catalina.authenticator.NonLoginAuthenticator	(Type of the modeled resource. Can be set only once)
securePagesWithPragma	false	(Controls the caching of pages that are protected by security constraints)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

host=localhost,context=/usage,name=StandardContextValve

(Valve that implements the default basic behavior for the StandardContext container implementation)

asyncSupported	true	(Does this valve support async reporting?)
className	org.apache.catalina.core.StandardContextValve	(Fully qualified class name of the managed object)
modelerType	org.apache.catalina.core.StandardContextValve	(Type of the modeled resource. Can be set only once)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

host=localhost,name=AccessLogValve

(Valve that generates a web server access log)

asyncSupported	true	(Does this valve support async reporting.)
buffered	true	(Flag to buffering.)
checkExists	false	(Check for file existence before logging.)
className	org.apache.catalina.valves.AccessLogValve	(Fully qualified class name of the managed object)
condition	null	(The value to look for conditional logging. The same as conditionUnless.)
conditionIf	null	(The value to look for conditional logging.)
conditionUnless	null	(The value to look for conditional logging.)
directory	logs	(The directory in which log files are created)
enabled	true	(Enable Access Logging)
encoding	null	(Character set used to write the log file)
fileDateFormat	.yyyy-MM-dd	(The format for the date for date based log rotation)
locale	en_US	(The locale used to format timestamps in the access log lines)
modelerType	org.apache.catalina.valves.AccessLogValve	(Type of the modeled resource. Can be set only once)
pattern	%h %l %u %t "%r" %s %b	(The pattern used to format our access log lines)
prefix	localhost_access_log	(The prefix that is added to log file filenames)
renameOnRotate	false	(Flag to defer inclusion of the date stamp in the log file name until rotation.)
rotatable	true	(Flag to indicate automatic log rotation.)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
suffix	.txt	(The suffix that is added to log file filenames)

host=localhost,name=ErrorReportValve

(Implementation of a Valve that outputs HTML error pages)

asyncSupported	true	(Does this valve support async reporting.)
className	org.apache.catalina.valves.ErrorReportValve	(Fully qualified class name of the managed object)
modelerType	org.apache.catalina.valves.ErrorReportValve	(Type of the modeled resource. Can be set only once)
showReport	true	(Enables/Disables full error reports)
showServerInfo	true	(Enables/Disables server info on error pages)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

host=localhost,name=StandardHostValve

(Valve that implements the default basic behavior for the StandardHost container implementation)

asyncSupported	true	(Does this valve support async reporting?)
className	org.apache.catalina.core.StandardHostValve	(Fully qualified class name of the managed object)

modelerType	org.apache.catalina.core.StandardHostValve	(Type of the modeled resource. Can be set only once)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

name=StandardEngineValve

(Valve that implements the default basic behavior for the StandardEngine container implementation)

asyncSupported	true	(Does this valve support async reporting?)
className	org.apache.catalina.core.StandardEngineValve	(Fully qualified class name of the managed object)
modelerType	org.apache.catalina.core.StandardEngineValve	(Type of the modeled resource. Can be set only once)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

WebModule

name=//localhost/,J2EEApplication=none,J2EEServer=none

(Standard Context Component)

altDDName	null	(The alternate deployment descriptor name.)
antiResourceLocking	false	(Take care to not lock resources)
baseName	ROOT	(The base name used for directories, WAR files (with .war appended) and context.xml files (with .xml appended).)
children	[Catalina:j2eeType=Servlet,WebModule=//localhost/,name=default,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=Servlet,WebModule=//localhost/,name=jsp,J2EEApplication=none,J2EEServer=none]	(Object names of all children)
clearReferencesRmiTargets	true	(Should Tomcat look for memory leaks in RMI Targets and clear them if found as a work around for application coding errors?)
clearReferencesStopThreads	false	(Should Tomcat attempt to terminate threads that have been started by the web application? Advisable to be used only in a development environment.)
clearReferencesStopTimerThreads	false	(Should Tomcat attempt to terminate TimerThreads that have been started by the web application? Advisable to be used only in a development environment.)
clearReferencesThreadLocals	true	(Should Tomcat attempt to clear ThreadLocal variables that have been populated with classes loaded by the web application?)
configFile	null	(Location of the context.xml resource or file)
configured	true	(The correctly configured flag for this Context.)
cookies	true	(Should we attempt to use cookies for session id communication?)
crossContext	false	(Should we allow the ServletContext.getContext() method to access the context of other web applications in this server?)
defaultContextXml	null	(Location of the default context.xml resource or file)
defaultWebXml	null	(Location of the default web.xml resource or file)
delegate	false	
displayName	null	(The display name of this web application)
distributable	false	(The distributable flag for this web application.)
docBase	ROOT	(The document root for this web application)
encodedPath		(The encoded path)
errorCount	89 480	(Cumulative error count of all servlets in this context)
ignoreAnnotations	false	(Ignore annotations flag.)
instanceManager	org.apache.catalina.core.DefaultInstanceManager@5705e10a	(Object that creates and destroys servlets, filters, and listeners. Include dependency injection and postConstruct/preDestroy handling)
javaVMs	null	(The Java virtual machines on which this module is running)
loader	WebappLoader[StandardEngine[Catalina].StandardHost[localhost].StandardContext[]]	(Associated loader.)
logEffectiveWebXml	false	(Should the effective web.xml be logged when the context starts?)
logger	org.apache.juli.logging.DirectJDKLog@2defc9ba	(Associated logger.)
managedResource	StandardEngine[Catalina].StandardHost[localhost].StandardContext[]	(The managed resource this MBean is associated with)
manager	StandardManager[StandardEngine[Catalina].StandardHost[localhost].StandardContext[]]	(Associated manager.)
mapperContextRootRedirectEnabled	true	(Should the Mapper be used for context root redirects)
mapperDirectoryRedirectEnabled	false	(Should the Mapper be used for directory redirects)
maxTime	613	(Maximum execution time of all servlets in this context)
minTime	0	(Minimum execution time of all servlets in this context)
modelerType	org.apache.catalina.core.StandardContext	(Type of the modeled resource. Can be set only once)
name		(The name of this Context)
namingContextListener	org.apache.catalina.core.NamingContextListener@4bada6fb	(Associated naming context listener.)
objectName	Catalina:j2eeType=WebModule,name=//localhost/,J2EEApplication=none,J2EEServer=none	(Name of the object)
originalDocBase	null	(The original document root for this web application)
override	false	(The default context.xml override flag for this web application)
parentClassLoader	java.net.URLClassLoader@3e9b1010	(Parent class loader.)
path		(The context path for this Context)
paused	false	(The request processing pause flag (while reloading occurs))
privileged	false	(Access to tomcat internals)
processingTime	22 081	(Cumulative execution times of all servlets in this context)
publicId	null	(The public identifier of the DTD for the web application deployment descriptor version that is being parsed)
realm	LockOutRealm[StandardEngine[Catalina]]	(Associated realm.)
reloadable	false	(The reloadable flag for this web application)
renewThreadsWhenStoppingContext	true	(Should Tomcat renew the threads of the thread pool when the application is stopped to avoid memory leaks because of uncleaned ThreadLocal variables.)
requestCount	121 065	(Cumulative request count of all servlets in this context)
server	null	(The J2EE Server this module is deployed on)
sessionCookieDomain	null	(The domain to use for session cookies.'null' indicates that the domain is controlled by the application.)
sessionCookieName	null	(The name to use for session cookies.'null' indicates that the name is controlled by the application.)
sessionCookiePath	null	(The path to use for session cookies.'null' indicates that the path is controlled by the application.)
sessionTimeout	30	(The session timeout (in minutes) for this web application)

startTime	1 791 650 661 721	(Time (in milliseconds since January 1, 1970, 00:00:00) when this context was started)
startupTime	0	(Time (in milliseconds) it took to start this context)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
swallowOutput	false	(Flag to set to cause the system.out and system.err to be redirected to the logger when executing a servlet)
tldScanTime	0	(Time spend scanning jars for TLDs for this context)
tldValidation	false	(Should the parsing of *.tld files be performed by a validating parser?)
unloadDelay	2 000	(Amount of ms that the container will wait for servlets to unload)
unpackWAR	true	(Unpack WAR property)
useHttpOnly	true	(Indicates that session cookies should use HttpOnly)
useNaming	true	(Create a JNDI naming context for this application?)
useRelativeRedirects	true	(When generating location headers for 302 responses, should a relative URI be used?)
webappVersion		(The version of this web application - used in parallel deployment to differentiate different versions of the same web application)
welcomeFiles	[index.html, index.htm, index.jsp]	(The welcome files for this context)
workDir	work/Catalina/localhost/ROOT	(The pathname to the work directory for this context)
xmlNamespaceAware	false	(Should the parsing of web.xml and web-fragment.xml files be performed by a namespace aware parser?)
xmlValidation	false	(Should the parsing of web.xml and web-fragment.xml files be performed by a validating parser?)

name=//localhost/demo,J2EEApplication=none,J2EEServer=none

(Standard Context Component)

altDDName	null	(The alternate deployment descriptor name.)
antiResourceLocking	false	(Take care to not lock resources)
baseName	demo	(The base name used for directories, WAR files (with .war appended) and context.xml files (with .xml appended).)
children	[Catalina:j2eeType=Servlet,WebModule=//localhost/demo,name=CompetenceService,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=Servlet,WebModule=//localhost/demo,name=GradeService,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=Servlet,WebModule=//localhost/demo,name=PersonneService,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=Servlet,WebModule=//localhost/demo,name=PrintUtilsService,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=Servlet,WebModule=//localhost/demo,name=AdresseService,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=Servlet,WebModule=//localhost/demo,name=UtilisateurService,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=Servlet,WebModule=//localhost/demo,name=jsp,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=Servlet,WebModule=//localhost/demo,name=BuildInfoServlet,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=Servlet,WebModule=//localhost/demo,name=PermissionService,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=Servlet,WebModule=//localhost/demo,name=default,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=Servlet,WebModule=//localhost/demo,name=MailService,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=Servlet,WebModule=//localhost/demo,name=RoleService,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=Servlet,WebModule=//localhost/demo,name=TelephoneService,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=Servlet,WebModule=//localhost/demo,name=AuthentificationService,J2EEApplication=none,J2EEServer=none]	(Object names of all children)
clearReferencesRmiTargets	true	(Should Tomcat look for memory leaks in RMI Targets and clear them if found as a work around for application coding errors?)
clearReferencesStopThreads	false	(Should Tomcat attempt to terminate threads that have been started by the web application? Advisable to be used only in a development environment.)
clearReferencesStopTimerThreads	false	(Should Tomcat attempt to terminate TimerThreads that have been started by the web application? Advisable to be used only in a development environment.)
clearReferencesThreadLocals	true	(Should Tomcat attempt to clear ThreadLocal variables that have been populated with classes loaded by the web application?)
configFile	file:/opt/apache-tomcat-9.0.33/conf/Catalina/localhost/demo.xml	(Location of the context.xml resource or file)
configured	true	(The correctly configured flag for this Context.)
cookies	true	(Should we attempt to use cookies for session id communication?)
crossContext	false	(Should we allow the ServletContext.getContext() method to access the context of other web applications in this server?)
defaultContextXml	null	(Location of the default context.xml resource or file)
defaultWebXml	null	(Location of the default web.xml resource or file)
delegate	false	
displayName	null	(The display name of this web application)
distributable	false	(The distributable flag for this web application.)
docBase	demo.war	(The document root for this web application)
encodedPath	/demo	(The encoded path)
errorCount	169 270	(Cumulative error count of all servlets in this context)
ignoreAnnotations	false	(Ignore annotations flag.)
instanceManager	org.apache.catalina.core.DefaultInstanceManager@6653de59	(Object that creates and destroys servlets, filters, and listeners. Include dependency injection and postConstruct/preDestroy handling)
javaVMs	null	(The Java virtual machines on which this module is running)
loader	WebappLoader[StandardEngine[Catalina].StandardHost[localhost].StandardContext[/demo]]	(Associated loader.)
logEffectiveWebXml	false	(Should the effective web.xml be logged when the context starts?)
logger	org.apache.juli.logging.DirectJDKLog@6905a166	(Associated logger.)
managedResource	StandardEngine[Catalina].StandardHost[localhost].StandardContext[/demo]	(The managed resource this MBean is associated with)
manager	StandardManager[StandardEngine[Catalina].StandardHost[localhost].StandardContext[/demo]]	(Associated manager.)
mapperContextRootRedirectEnabled	true	(Should the Mapper be used for context root redirects)
mapperDirectoryRedirectEnabled	false	(Should the Mapper be used for directory redirects)
maxTime	60 048	(Maximum execution time of all servlets in this context)
minTime	0	(Minimum execution time of all servlets in this context)

modelerType	org.apache.catalina.core.StandardContext	(Type of the modeled resource. Can be set only once)
name	/demo	(The name of this Context)
namingContextListener	org.apache.catalina.core.NamingContextListener@9d2686c	(Associated naming context listener.)
objectName	Catalina:j2eeType=WebModule,name=//localhost/demo,J2EEApplication=none,J2EEServer=none	(Name of the object)
originalDocBase	/opt/apache-tomcat-9.0.33/webapps/demo	(The original document root for this web application)
override	false	(The default context.xml override flag for this web application)
parentClassLoader	java.net.URLClassLoader@3e9b1010	(Parent class loader.)
path	/demo	(The context path for this Context)
paused	false	(The request processing pause flag (while reloading occurs))
privileged	false	(Access to tomcat internals)
processingTime	5 415 212	(Cumulative execution times of all servlets in this context)
publicId	null	(The public identifier of the DTD for the web application deployment descriptor version that is being parsed)
realm	LockOutRealm[StandardEngine[Catalina]]	(Associated realm.)
reloadable	false	(The reloadable flag for this web application)
renewThreadsWhenStoppingContext	true	(Should Tomcat renew the threads of the thread pool when the application is stopped to avoid memory leaks because of uncleaned ThreadLocal variables.)
requestCount	210 699	(Cumulative request count of all servlets in this context)
server	null	(The J2EE Server this module is deployed on)
sessionCookieDomain	null	(The domain to use for session cookies.'null' indicates that the domain is controlled by the application.)
sessionCookieName	null	(The name to use for session cookies.'null' indicates that the name is controlled by the application.)
sessionCookiePath	null	(The path to use for session cookies.'null' indicates that the path is controlled by the application.)
sessionTimeout	30	(The session timeout (in minutes) for this web application)
startTime	1 791 650 370 937	(Time (in milliseconds since January 1, 1970, 00:00:00) when this context was started)
startupTime	2 379	(Time (in milliseconds) it took to start this context)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
swallowOutput	false	(Flag to set to cause the system.out and system.err to be redirected to the logger when executing a servlet)
tldScanTime	0	(Time spend scanning jars for TLDs for this context)
tldValidation	false	(Should the parsing of *.tld files be performed by a validating parser?)
unloadDelay	2 000	(Amount of ms that the container will wait for servlets to unload)
unpackWAR	true	(Unpack WAR property)
useHttpOnly	true	(Indicates that session cookies should use HttpOnly)
useNaming	true	(Create a JNDI naming context for this application?)
useRelativeRedirects	true	(When generating location headers for 302 responses, should a relative URI be used?)
webappVersion		(The version of this web application - used in parallel deployment to differentiate different versions of the same web application)
welcomeFiles	[index.html]	(The welcome files for this context)
workDir	work/Catalina/localhost/demo	(The pathname to the work directory for this context)
xmlNamespaceAware	false	(Should the parsing of web.xml and web-fragment.xml files be performed by a namespace aware parser?)
xmlValidation	false	(Should the parsing of web.xml and web-fragment.xml files be performed by a validating parser?)

name=//localhost/downloads,J2EEApplication=none,J2EEServer=none

(Standard Context Component)

altDDName	null	(The alternate deployment descriptor name.)
antiResourceLocking	false	(Take care to not lock resources)
baseName	downloads	(The base name used for directories, WAR files (with .war appended) and context.xml files (with .xml appended).)
children	[Catalina:j2eeType=Servlet,WebModule=//localhost/downloads,name=default,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=Servlet,WebModule=//localhost/downloads,name=jsp,J2EEApplication=none,J2EEServer=none]	(Object names of all children)
clearReferencesRmiTargets	true	(Should Tomcat look for memory leaks in RMI Targets and clear them if found as a work around for application coding errors?)
clearReferencesStopThreads	false	(Should Tomcat attempt to terminate threads that have been started by the web application? Advisable to be used only in a development environment.)
clearReferencesStopTimerThreads	false	(Should Tomcat attempt to terminate TimerThreads that have been started by the web application? Advisable to be used only in a development environment.)
clearReferencesThreadLocals	true	(Should Tomcat attempt to clear ThreadLocal variables that have been populated with classes loaded by the web application?)
configFile	null	(Location of the context.xml resource or file)
configured	true	(The correctly configured flag for this Context.)
cookies	true	(Should we attempt to use cookies for session id communication?)
crossContext	false	(Should we allow the ServletContext.getContext() method to access the context of other web applications in this server?)
defaultContextXml	null	(Location of the default context.xml resource or file)
defaultWebXml	null	(Location of the default web.xml resource or file)
delegate	false	
displayName	null	(The display name of this web application)
distributable	false	(The distributable flag for this web application.)
docBase	downloads	(The document root for this web application)
encodedPath	/downloads	(The encoded path)
errorCount	102	(Cumulative error count of all servlets in this context)
ignoreAnnotations	false	(Ignore annotations flag.)
instanceManager	org.apache.catalina.core.DefaultInstanceManager@7d73b998	(Object that creates and destroys servlets, filters, and listeners. Include dependency injection and postConstruct/preDestroy handling)
javaVMs	null	(The Java virtual machines on which this module is running)

loader	WebappLoader[StandardEngine[Catalina].StandardHost[localhost].StandardContext[/downloads]]	(Associated loader.)
logEffectiveWebXml	false	(Should the effective web.xml be logged when the context starts?)
logger	org.apache.juli.logging.DirectJDKLog@83efcd0	(Associated logger.)
managedResource	StandardEngine[Catalina].StandardHost[localhost].StandardContext[/downloads]	(The managed resource this MBean is associated with)
manager	StandardManager[StandardEngine[Catalina].StandardHost[localhost].StandardContext[/downloads]]	(Associated manager.)
mapperContextRootRedirectEnabled	true	(Should the Mapper be used for context root redirects)
mapperDirectoryRedirectEnabled	false	(Should the Mapper be used for directory redirects)
maxTime	12	(Maximum execution time of all servlets in this context)
minTime	0	(Minimum execution time of all servlets in this context)
modelerType	org.apache.catalina.core.StandardContext	(Type of the modeled resource. Can be set only once)
name	/downloads	(The name of this Context)
namingContextListener	org.apache.catalina.core.NamingContextListener@5b4f4674	(Associated naming context listener.)
objectName	Catalina:j2eeType=WebModule,name=//localhost/downloads,J2EEApplication=none,J2EEServer=none	(Name of the object)
originalDocBase	null	(The original document root for this web application)
override	false	(The default context.xml override flag for this web application)
parentClassLoader	java.net.URLClassLoader@3e9b1010	(Parent class loader.)
path	/downloads	(The context path for this Context)
paused	false	(The request processing pause flag (while reloading occurs))
privileged	false	(Access to tomcat internals)
processingTime	49	(Cumulative execution times of all servlets in this context)
publicId	null	(The public identifier of the DTD for the web application deployment descriptor version that is being parsed)
realm	LockOutRealm[StandardEngine[Catalina]]	(Associated realm.)
reloadable	false	(The reloadable flag for this web application)
renewThreadsWhenStoppingContext	true	(Should Tomcat renew the threads of the thread pool when the application is stopped to avoid memory leaks because of uncleaned ThreadLocal variables.)
requestCount	115	(Cumulative request count of all servlets in this context)
server	null	(The J2EE Server this module is deployed on)
sessionCookieDomain	null	(The domain to use for session cookies.'null' indicates that the domain is controlled by the application.)
sessionCookieName	null	(The name to use for session cookies.'null' indicates that the name is controlled by the application.)
sessionCookiePath	null	(The path to use for session cookies.'null' indicates that the path is controlled by the application.)
sessionTimeout	30	(The session timeout (in minutes) for this web application)
startTime	1 791 650 661 660	(Time (in milliseconds since January 1, 1970, 00:00:00) when this context was started)
startupTime	0	(Time (in milliseconds) it took to start this context)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
swallowOutput	false	(Flag to set to cause the system.out and system.err to be redirected to the logger when executing a servlet)
tldScanTime	0	(Time spend scanning jars for TLDs for this context)
tldValidation	false	(Should the parsing of *.tld files be performed by a validating parser?)
unloadDelay	2 000	(Amount of ms that the container will wait for servlets to unload)
unpackWAR	true	(Unpack WAR property)
useHttpOnly	true	(Indicates that session cookies should use HttpOnly)
useNaming	true	(Create a JNDI naming context for this application?)
useRelativeRedirects	true	(When generating location headers for 302 responses, should a relative URI be used?)
webappVersion		(The version of this web application - used in parallel deployment to differentiate different versions of the same web application)
welcomeFiles	[index.html, index.htm, index.jsp]	(The welcome files for this context)
workDir	work/Catalina/localhost/downloads	(The pathname to the work directory for this context)
xmlNamespaceAware	false	(Should the parsing of web.xml and web-fragment.xml files be performed by a namespace aware parser?)
xmlValidation	false	(Should the parsing of web.xml and web-fragment.xml files be performed by a validating parser?)

name=//localhost/usage,J2EEApplication=none,J2EEServer=none

(Standard Context Component)

altDDName	null	(The alternate deployment descriptor name.)
antiResourceLocking	false	(Take care to not lock resources)
baseName	usage	(The base name used for directories, WAR files (with .war appended) and context.xml files (with .xml appended).)
children	[Catalina:j2eeType=Servlet,WebModule=//localhost/usage,name=default,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=Servlet,WebModule=//localhost/usage,name=jsp,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=Servlet,WebModule=//localhost/usage,name=usagestats,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=Servlet,WebModule=//localhost/usage,name=admin,J2EEApplication=none,J2EEServer=none]	(Object names of all children)
clearReferencesRmiTargets	true	(Should Tomcat look for memory leaks in RMI Targets and clear them if found as a work around for application coding errors?)
clearReferencesStopThreads	false	(Should Tomcat attempt to terminate threads that have been started by the web application? Advisable to be used only in a development environment.)
clearReferencesStopTimerThreads	false	(Should Tomcat attempt to terminate TimerThreads that have been started by the web application? Advisable to be used only in a development environment.)
clearReferencesThreadLocals	true	(Should Tomcat attempt to clear ThreadLocal variables that have been populated with classes loaded by the web application?)
configFile	file:/opt/apache-tomcat-9.0.33/conf/Catalina/localhost/usage.xml	(Location of the context.xml resource or file)
configured	true	(The correctly configured flag for this Context.)
cookies	true	(Should we attempt to use cookies for session id communication?)

crossContext	false	(Should we allow the ServletContext.getContext() method to access the context of other web applications in this server?)
defaultContextXml	null	(Location of the default context.xml resource or file)
defaultWebXml	null	(Location of the default web.xml resource or file)
delegate	false	
displayName	javamelody-usagestats	(The display name of this web application)
distributable	true	(The distributable flag for this web application.)
docBase	usage.war	(The document root for this web application)
encodedPath	/usage	(The encoded path)
errorCount	47	(Cumulative error count of all servlets in this context)
ignoreAnnotations	false	(Ignore annotations flag.)
instanceManager	org.apache.catalina.core.DefaultInstanceManager@3ad91a4f	(Object that creates and destroys servlets, filters, and listeners. Include dependency injection and postConstruct/preDestroy handling)
javaVMs	null	(The Java virtual machines on which this module is running)
loader	WebappLoader[StandardEngine[Catalina].StandardHost[localhost].StandardContext[/usage]]	(Associated loader.)
logEffectiveWebXml	false	(Should the effective web.xml be logged when the context starts?)
logger	org.apache.juli.logging.DirectJDKLog@1aab00b3	(Associated logger.)
managedResource	StandardEngine[Catalina].StandardHost[localhost].StandardContext[/usage]	(The managed resource this MBean is associated with)
manager	StandardManager[StandardEngine[Catalina].StandardHost[localhost].StandardContext[/usage]]	(Associated manager.)
mapperContextRootRedirectEnabled	true	(Should the Mapper be used for context root redirects)
mapperDirectoryRedirectEnabled	false	(Should the Mapper be used for directory redirects)
maxTime	6 074	(Maximum execution time of all servlets in this context)
minTime	0	(Minimum execution time of all servlets in this context)
modelerType	org.apache.catalina.core.StandardContext	(Type of the modeled resource. Can be set only once)
name	/usage	(The name of this Context)
namingContextListener	org.apache.catalina.core.NamingContextListener@733607db	(Associated naming context listener.)
objectName	Catalina:j2eeType=WebModule,name=//localhost/usage,J2EEApplication=none,J2EEServer=none	(Name of the object)
originalDocBase	/opt/apache-tomcat-9.0.33/webapps/usage	(The original document root for this web application)
override	false	(The default context.xml override flag for this web application)
parentClassLoader	java.net.URLClassLoader@3e9b1010	(Parent class loader.)
path	/usage	(The context path for this Context)
paused	false	(The request processing pause flag (while reloading occurs))
privileged	false	(Access to tomcat internals)
processingTime	4 939 590	(Cumulative execution times of all servlets in this context)
publicId	null	(The public identifier of the DTD for the web application deployment descriptor version that is being parsed)
realm	LockOutRealm[StandardEngine[Catalina]]	(Associated realm.)
reloadable	false	(The reloadable flag for this web application)
renewThreadsWhenStoppingContext	true	(Should Tomcat renew the threads of the thread pool when the application is stopped to avoid memory leaks because of uncleaned ThreadLocal variables.)
requestCount	22 230 347	(Cumulative request count of all servlets in this context)
server	null	(The J2EE Server this module is deployed on)
sessionCookieDomain	null	(The domain to use for session cookies.'null' indicates that the domain is controlled by the application.)
sessionCookieName	null	(The name to use for session cookies.'null' indicates that the name is controlled by the application.)
sessionCookiePath	null	(The path to use for session cookies.'null' indicates that the path is controlled by the application.)
sessionTimeout	30	(The session timeout (in minutes) for this web application)
startTime	1 791 650 661 621	(Time (in milliseconds since January 1, 1970, 00:00:00) when this context was started)
startupTime	186	(Time (in milliseconds) it took to start this context)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
swallowOutput	false	(Flag to set to cause the system.out and system.err to be redirected to the logger when executing a servlet)
tldScanTime	0	(Time spend scanning jars for TLDs for this context)
tldValidation	false	(Should the parsing of *.tld files be performed by a validating parser?)
unloadDelay	2 000	(Amount of ms that the container will wait for servlets to unload)
unpackWAR	true	(Unpack WAR property)
useHttpOnly	true	(Indicates that session cookies should use HttpOnly)
useNaming	true	(Create a JNDI naming context for this application?)
useRelativeRedirects	true	(When generating location headers for 302 responses, should a relative URI be used?)
webappVersion		(The version of this web application - used in parallel deployment to differentiate different versions of the same web application)
welcomeFiles	[index.html]	(The welcome files for this context)
workDir	work/Catalina/localhost/usage	(The pathname to the work directory for this context)
xmlNamespaceAware	false	(Should the parsing of web.xml and web-fragment.xml files be performed by a namespace aware parser?)
xmlValidation	false	(Should the parsing of web.xml and web-fragment.xml files be performed by a validating parser?)

WebResourceRoot

host=localhost,context=/

(Provides the resources implementation for a web application)

allowLinking	false	(Does this resources implementation allow the use of symbolic links?)
cachingAllowed	true	(Is in memory caching of resource content and metadata enabled?)
modelerType	org.apache.catalina.webresources.StandardRoot	(Type of the modeled resource. Can be set only once)
stateName	STARTED	(The current Lifecycle state of this object)
trackLockedFiles	false	(Does this resources implementation track requests that lock files?)

trackedResources	[]	(List of resources currently being tracked for possible resource leaks)

host=localhost,context=/,name=Cache

(Provides caching of resource metadata and content)

hitCount	247 095	(The number of requests for resources that were served from the cache)
lookupCount	291 083	(The number of requests for resources)
maxSize	10 240	(The maximum permitted size of the cache in kB)
modelerType	org.apache.catalina.webresources.Cache	(Type of the modeled resource. Can be set only once)
objectMaxSize	512	(The maximum permitted size for a single object in the cache in kB)
size	9 215	(The current estimate of the cache size in kB)
ttl	5 000	(The time-to-live for cache entries in milliseconds)

host=localhost,context=/demo

(Provides the resources implementation for a web application)

allowLinking	false	(Does this resources implementation allow the use of symbolic links?)
cachingAllowed	true	(Is in memory caching of resource content and metadata enabled?)
modelerType	org.apache.catalina.webresources.StandardRoot	(Type of the modeled resource. Can be set only once)
stateName	STARTED	(The current Lifecycle state of this object)
trackLockedFiles	false	(Does this resources implementation track requests that lock files?)
trackedResources	[]	(List of resources currently being tracked for possible resource leaks)

host=localhost,context=/demo,name=Cache

(Provides caching of resource metadata and content)

hitCount	81 536	(The number of requests for resources that were served from the cache)
lookupCount	81 798	(The number of requests for resources)
maxSize	10 240	(The maximum permitted size of the cache in kB)
modelerType	org.apache.catalina.webresources.Cache	(Type of the modeled resource. Can be set only once)
objectMaxSize	512	(The maximum permitted size for a single object in the cache in kB)
size	2 609	(The current estimate of the cache size in kB)
ttl	5 000	(The time-to-live for cache entries in milliseconds)

host=localhost,context=/downloads

(Provides the resources implementation for a web application)

allowLinking	false	(Does this resources implementation allow the use of symbolic links?)
cachingAllowed	true	(Is in memory caching of resource content and metadata enabled?)
modelerType	org.apache.catalina.webresources.StandardRoot	(Type of the modeled resource. Can be set only once)
stateName	STARTED	(The current Lifecycle state of this object)
trackLockedFiles	false	(Does this resources implementation track requests that lock files?)
trackedResources	[]	(List of resources currently being tracked for possible resource leaks)

host=localhost,context=/downloads,name=Cache

(Provides caching of resource metadata and content)

hitCount	105	(The number of requests for resources that were served from the cache)
lookupCount	149	(The number of requests for resources)
maxSize	10 240	(The maximum permitted size of the cache in kB)
modelerType	org.apache.catalina.webresources.Cache	(Type of the modeled resource. Can be set only once)
objectMaxSize	512	(The maximum permitted size for a single object in the cache in kB)
size	21	(The current estimate of the cache size in kB)
ttl	5 000	(The time-to-live for cache entries in milliseconds)

host=localhost,context=/usage

(Provides the resources implementation for a web application)

allowLinking	false	(Does this resources implementation allow the use of symbolic links?)
cachingAllowed	true	(Is in memory caching of resource content and metadata enabled?)
modelerType	org.apache.catalina.webresources.StandardRoot	(Type of the modeled resource. Can be set only once)
stateName	STARTED	(The current Lifecycle state of this object)
trackLockedFiles	false	(Does this resources implementation track requests that lock files?)
trackedResources	[]	(List of resources currently being tracked for possible resource leaks)

host=localhost,context=/usage,name=Cache

(Provides caching of resource metadata and content)

hitCount	404	(The number of requests for resources that were served from the cache)
lookupCount	435	(The number of requests for resources)
maxSize	10 240	(The maximum permitted size of the cache in kB)
modelerType	org.apache.catalina.webresources.Cache	(Type of the modeled resource. Can be set only once)
objectMaxSize	512	(The maximum permitted size for a single object in the cache in kB)
size	30	(The current estimate of the cache size in kB)
ttl	5 000	(The time-to-live for cache entries in milliseconds)

JMImplementation

MBeanServerDelegate

(Represents the MBean server from the management point of view.)

ImplementationName	JMX	(The JMX implementation name (the name of this product))
ImplementationVendor	Oracle Corporation	(the JMX implementation vendor (the vendor of this product).)
ImplementationVersion	11.0.6+10	(The JMX implementation version (the version of this product).)
MBeanServerId	vps363300.ovh.net_1791650227819	(The MBean server agent identification)
SpecificationName	Java Management Extensions	(The full name of the JMX specification implemented by this product.)
SpecificationVendor	Oracle Corporation	(The vendor of the JMX specification implemented by this product.)
SpecificationVersion	1.4	(The version of the JMX specification implemented by this product.)

Users

UserDatabase

database=UserDatabase

(In-memory user and group database)

groups	[]	(MBean Names of all defined groups)
modelerType	org.apache.catalina.users.MemoryUserDatabase	(Type of the modeled resource. Can be set only once)
pathname	conf/tomcat-users.xml	(Relative or absolute pathname to database file)
readonly	true	(No persistent save of the user database)
roles	[]	(MBean Names of all defined roles)
users	[]	(MBean Names of all defined users)
writeable	true	(Check if user database is writeable)

com.sun.management

DiagnosticCommand

(Diagnostic Commands)

HotSpotDiagnostic

DiagnosticOptions	[{name=HeapDumpBeforeFullGC, origin=DEFAULT, value=false, writeable=true}, {name=HeapDumpAfterFullGC, origin=DEFAULT, value=false, writeable=true}, {name=HeapDumpOnOutOfMemoryError, origin=DEFAULT, value=false, writeable=true}, {name=HeapDumpPath, origin=DEFAULT, value=, writeable=true}, {name=PrintClassHistogram, origin=DEFAULT, value=false, writeable=true}, {name=MinHeapFreeRatio, origin=DEFAULT, value=40, writeable=true}, {name=MaxHeapFreeRatio, origin=DEFAULT, value=70, writeable=true}, {name=PrintConcurrentLocks, origin=DEFAULT, value=false, writeable=true}, {name=CMSAbortablePrecleanWaitMillis, origin=DEFAULT, value=100, writeable=true}, {name=CMSWaitDuration, origin=DEFAULT, value=2000, writeable=true}, {name=CMSTriggerInterval, origin=DEFAULT, value=-1, writeable=true}]
ObjectName	com.sun.management:type=HotSpotDiagnostic

java.lang

ClassLoading

LoadedClassCount	8 309
ObjectName	java.lang:type=ClassLoading
TotalLoadedClassCount	17 236
UnloadedClassCount	8 927
Verbose	false

CodeCacheManager

type=MemoryManager

MemoryPoolNames	[CodeHeap 'non-nmethods', CodeHeap 'profiled nmethods', CodeHeap 'non-profiled nmethods']
Name	CodeCacheManager
ObjectName	java.lang:type=MemoryManager,name=CodeCacheManager
Valid	true

CodeHeap 'non-nmethods'

type=MemoryPool

CollectionUsage	null
CollectionUsageThresholdSupported	false
MemoryManagerNames	[CodeCacheManager]
Name	CodeHeap 'non-nmethods'
ObjectName	java.lang:type=MemoryPool,name=CodeHeap 'non-nmethods'
PeakUsage	{committed=2 555 904, init=2 555 904, max=5 828 608, used=1 493 760}
Type	NON_HEAP
Usage	{committed=2 555 904, init=2 555 904, max=5 828 608, used=1 419 776}
UsageThreshold	0
UsageThresholdCount	0
UsageThresholdExceeded	false
UsageThresholdSupported	true
Valid	true

CodeHeap 'non-profiled nmethods'

type=MemoryPool

CollectionUsage	null
CollectionUsageThresholdSupported	false
MemoryManagerNames	[CodeCacheManager]
Name	CodeHeap 'non-profiled nmethods'
ObjectName	java.lang:type=MemoryPool,name=CodeHeap 'non-profiled nmethods'
PeakUsage	{committed=22 282 240, init=2 555 904, max=122 916 864, used=21 446 016}
Type	NON_HEAP
Usage	{committed=22 282 240, init=2 555 904, max=122 916 864, used=21 379 456}
UsageThreshold	0
UsageThresholdCount	0
UsageThresholdExceeded	false
UsageThresholdSupported	true
Valid	true

CodeHeap 'profiled nmethods'

type=MemoryPool

CollectionUsage	null
CollectionUsageThresholdSupported	false
MemoryManagerNames	[CodeCacheManager]
Name	CodeHeap 'profiled nmethods'
ObjectName	java.lang:type=MemoryPool,name=CodeHeap 'profiled nmethods'
PeakUsage	{committed=23 003 136, init=2 555 904, max=122 912 768, used=22 435 584}
Type	NON_HEAP
Usage	{committed=23 003 136, init=2 555 904, max=122 912 768, used=15 547 008}
UsageThreshold	0
UsageThresholdCount	0
UsageThresholdExceeded	false
UsageThresholdSupported	true
Valid	true

Compilation

CompilationTimeMonitoringSupported	true
Name	HotSpot 64-Bit Tiered Compilers
ObjectName	java.lang:type=Compilation
TotalCompilationTime	444 802

Compressed Class Space

type=MemoryPool

CollectionUsage	null
CollectionUsageThresholdSupported	false
MemoryManagerNames	[Metaspace Manager]
Name	Compressed Class Space
ObjectName	java.lang:type=MemoryPool,name=Compressed Class Space
PeakUsage	{committed=6 684 672, init=0, max=1 073 741 824, used=6 017 136}
Type	NON_HEAP
Usage	{committed=6 684 672, init=0, max=1 073 741 824, used=5 904 296}
UsageThreshold	0
UsageThresholdCount	0
UsageThresholdExceeded	false
UsageThresholdSupported	true
Valid	true

Copy

type=GarbageCollector

CollectionCount	45 623
CollectionTime	1 538 402

LastGcInfo	{GcThreadCount=1, duration=7, endTime=3 804 769 095, id=45 623, memoryUsageAfterGc={GcThreadCount=1, duration=7, endTime=3804769095, id=45623, memoryUsageAfterGc=[{key=CodeHeap 'profiled nmethods', value={committed=23003136, init=2555904, max=122912768, used=15550720}}, {key=Eden Space, value={committed=80805888, init=8912896, max=136445952, used=0}}, {key=CodeHeap 'non-profiled nmethods', value={committed=22282240, init=2555904, max=122916864, used=21410048}}, {key=Survivor Space, value={committed=10027008, init=1114112, max=17039360, used=4115808}}, {key=Compressed Class Space, value={committed=6684672, init=0, max=1073741824, used=5889944}}, {key=Metaspace, value={committed=68026368, init=0, max=-1, used=65448616}}, {key=CodeHeap 'non-nmethods', value={committed=2555904, init=2555904, max=5828608, used=1419776}}, {key=Tenured Gen, value={committed=201543680, init=22413312, max=341180416, used=61720288}}], memoryUsageBeforeGc=[{key=CodeHeap 'profiled nmethods', value={committed=23003136, init=2555904, max=122912768, used=15550720}}, {key=Eden Space, value={committed=80805888, init=8912896, max=136445952, used=80805856}}, {key=CodeHeap 'non-profiled nmethods', value={committed=22282240, init=2555904, max=122916864, used=21410048}}, {key=Survivor Space, value={committed=10027008, init=1114112, max=17039360, used=2311912}}, {key=Compressed Class Space, value={committed=6684672, init=0, max=1073741824, used=5889944}}, {key=Metaspace, value={committed=68026368, init=0, max=-1, used=65448616}}, {key=CodeHeap 'non-nmethods', value={committed=2555904, init=2555904, max=5828608, used=1419776}}, {key=Tenured Gen, value={committed=201543680, init=22413312, max=341180416, used=61720288}}], startTime=3804769088}, memoryUsageBeforeGc={GcThreadCount=1, duration=7, endTime=3804769095, id=45623, memoryUsageAfterGc=[{key=CodeHeap 'profiled nmethods', value={committed=23003136, init=2555904, max=122912768, used=15550720}}, {key=Eden Space, value={committed=80805888, init=8912896, max=136445952, used=0}}, {key=CodeHeap 'non-profiled nmethods', value={committed=22282240, init=2555904, max=122916864, used=21410048}}, {key=Survivor Space, value={committed=10027008, init=1114112, max=17039360, used=4115808}}, {key=Compressed Class Space, value={committed=6684672, init=0, max=1073741824, used=5889944}}, {key=Metaspace, value={committed=68026368, init=0, max=-1, used=65448616}}, {key=CodeHeap 'non-nmethods', value={committed=2555904, init=2555904, max=5828608, used=1419776}}, {key=Tenured Gen, value={committed=201543680, init=22413312, max=341180416, used=61720288}}], memoryUsageBeforeGc=[{key=CodeHeap 'profiled nmethods', value={committed=23003136, init=2555904, max=122912768, used=15550720}}, {key=Eden Space, value={committed=80805888, init=8912896, max=136445952, used=80805856}}, {key=CodeHeap 'non-profiled nmethods', value={committed=22282240, init=2555904, max=122916864, used=21410048}}, {key=Survivor Space, value={committed=10027008, init=1114112, max=17039360, used=2311912}}, {key=Compressed Class Space, value={committed=6684672, init=0, max=1073741824, used=5889944}}, {key=Metaspace, value={committed=68026368, init=0, max=-1, used=65448616}}, {key=CodeHeap 'non-nmethods', value={committed=2555904, init=2555904, max=5828608, used=1419776}}, {key=Tenured Gen, value={committed=201543680, init=22413312, max=341180416, used=61720288}}], startTime=3804769088}, startTime=3 804 769 088}
MemoryPoolNames	[Eden Space, Survivor Space]
Name	Copy
ObjectName	java.lang:type=GarbageCollector,name=Copy
Valid	true

Eden Space

type=MemoryPool

CollectionUsage	{committed=80 805 888, init=8 912 896, max=136 445 952, used=0}
CollectionUsageThreshold	0
CollectionUsageThresholdCount	0
CollectionUsageThresholdExceeded	false
CollectionUsageThresholdSupported	true
MemoryManagerNames	[Copy, MarkSweepCompact]
Name	Eden Space
ObjectName	java.lang:type=MemoryPool,name=Eden Space
PeakUsage	{committed=136 445 952, init=8 912 896, max=136 445 952, used=136 445 952}
Type	HEAP
Usage	{committed=80 805 888, init=8 912 896, max=136 445 952, used=47 533 752}
UsageThresholdSupported	false
Valid	true

MarkSweepCompact

type=GarbageCollector

CollectionCount	1 053
CollectionTime	568 087

LastGcInfo	{GcThreadCount=1, duration=106, endTime=3 804 740 777, id=1 053, memoryUsageAfterGc={GcThreadCount=1, duration=106, endTime=3804740777, id=1053, memoryUsageAfterGc=[{key=CodeHeap 'profiled nmethods', value={committed=23003136, init=2555904, max=122912768, used=15561600}}, {key=Eden Space, value={committed=80805888, init=8912896, max=136445952, used=0}}, {key=CodeHeap 'non-profiled nmethods', value={committed=22282240, init=2555904, max=122916864, used=21391232}}, {key=Survivor Space, value={committed=10027008, init=1114112, max=17039360, used=0}}, {key=Compressed Class Space, value={committed=6684672, init=0, max=1073741824, used=5888288}}, {key=Metaspace, value={committed=68026368, init=0, max=-1, used=65436360}}, {key=CodeHeap 'non-nmethods', value={committed=2555904, init=2555904, max=5828608, used=1419776}}, {key=Tenured Gen, value={committed=201543680, init=22413312, max=341180416, used=60509136}}], memoryUsageBeforeGc=[{key=CodeHeap 'profiled nmethods', value={committed=23003136, init=2555904, max=122912768, used=15561600}}, {key=Eden Space, value={committed=80805888, init=8912896, max=136445952, used=284976}}, {key=CodeHeap 'non-profiled nmethods', value={committed=22282240, init=2555904, max=122916864, used=21391232}}, {key=Survivor Space, value={committed=10027008, init=1114112, max=17039360, used=0}}, {key=Compressed Class Space, value={committed=6684672, init=0, max=1073741824, used=5888288}}, {key=Metaspace, value={committed=68026368, init=0, max=-1, used=65436360}}, {key=CodeHeap 'non-nmethods', value={committed=2555904, init=2555904, max=5828608, used=1419776}}, {key=Tenured Gen, value={committed=201543680, init=22413312, max=341180416, used=60506072}}], startTime=3804740671}, memoryUsageBeforeGc={GcThreadCount=1, duration=106, endTime=3804740777, id=1053, memoryUsageAfterGc=[{key=CodeHeap 'profiled nmethods', value={committed=23003136, init=2555904, max=122912768, used=15561600}}, {key=Eden Space, value={committed=80805888, init=8912896, max=136445952, used=0}}, {key=CodeHeap 'non-profiled nmethods', value={committed=22282240, init=2555904, max=122916864, used=21391232}}, {key=Survivor Space, value={committed=10027008, init=1114112, max=17039360, used=0}}, {key=Compressed Class Space, value={committed=6684672, init=0, max=1073741824, used=5888288}}, {key=Metaspace, value={committed=68026368, init=0, max=-1, used=65436360}}, {key=CodeHeap 'non-nmethods', value={committed=2555904, init=2555904, max=5828608, used=1419776}}, {key=Tenured Gen, value={committed=201543680, init=22413312, max=341180416, used=60509136}}], memoryUsageBeforeGc=[{key=CodeHeap 'profiled nmethods', value={committed=23003136, init=2555904, max=122912768, used=15561600}}, {key=Eden Space, value={committed=80805888, init=8912896, max=136445952, used=284976}}, {key=CodeHeap 'non-profiled nmethods', value={committed=22282240, init=2555904, max=122916864, used=21391232}}, {key=Survivor Space, value={committed=10027008, init=1114112, max=17039360, used=0}}, {key=Compressed Class Space, value={committed=6684672, init=0, max=1073741824, used=5888288}}, {key=Metaspace, value={committed=68026368, init=0, max=-1, used=65436360}}, {key=CodeHeap 'non-nmethods', value={committed=2555904, init=2555904, max=5828608, used=1419776}}, {key=Tenured Gen, value={committed=201543680, init=22413312, max=341180416, used=60506072}}], startTime=3804740671}, startTime=3 804 740 671}
MemoryPoolNames	[Eden Space, Survivor Space, Tenured Gen]
Name	MarkSweepCompact
ObjectName	java.lang:type=GarbageCollector,name=MarkSweepCompact
Valid	true

Memory

HeapMemoryUsage	{committed=292 376 576, init=33 554 432, max=494 665 728, used=115 365 136}
NonHeapMemoryUsage	{committed=122 552 320, init=7 667 712, max=-1, used=109 857 680}
ObjectName	java.lang:type=Memory
ObjectPendingFinalizationCount	0
Verbose	false

Metaspace

type=MemoryPool

CollectionUsage	null
CollectionUsageThresholdSupported	false
MemoryManagerNames	[Metaspace Manager]
Name	Metaspace
ObjectName	java.lang:type=MemoryPool,name=Metaspace
PeakUsage	{committed=68 026 368, init=0, max=-1, used=66 017 464}
Type	NON_HEAP
Usage	{committed=68 026 368, init=0, max=-1, used=65 529 176}
UsageThreshold	0
UsageThresholdCount	0
UsageThresholdExceeded	false
UsageThresholdSupported	true
Valid	true

Metaspace Manager

type=MemoryManager

MemoryPoolNames	[Metaspace, Compressed Class Space]
Name	Metaspace Manager
ObjectName	java.lang:type=MemoryManager,name=Metaspace Manager
Valid	true

OperatingSystem

Arch	amd64
AvailableProcessors	1
CommittedVirtualMemorySize	2 856 361 984
FreePhysicalMemorySize	274 006 016
FreeSwapSpaceSize	0
MaxFileDescriptorCount	500 000
Name	Linux
ObjectName	java.lang:type=OperatingSystem
OpenFileDescriptorCount	138
ProcessCpuLoad	0
ProcessCpuTime	55 202 790 000 000
SystemCpuLoad	1
SystemLoadAverage	0
TotalPhysicalMemorySize	2 045 435 904
TotalSwapSpaceSize	0
Version	3.10.0-1160.114.2.el7.x86_64

Runtime

BootClassPathSupported	false
ClassPath	/opt/tomcat/bin/bootstrap.jar:/opt/tomcat/bin/tomcat-juli.jar
InputArguments	[--add-opens=java.base/java.lang=ALL-UNNAMED, --add-opens=java.base/java.io=ALL-UNNAMED, --add-opens=java.rmi/sun.rmi.transport=ALL-UNNAMED, -Djava.util.logging.config.file=/opt/tomcat/conf/logging.properties, -Djava.util.logging.manager=org.apache.juli.ClassLoaderLogManager, -Djdk.tls.ephemeralDHKeySize=2048, -Djava.protocol.handler.pkgs=org.apache.catalina.webresources, -Dorg.apache.catalina.security.SecurityListener.UMASK=0027, -Djava.security.egd=file:/dev/./urandom, -Dignore.endorsed.dirs=, -Dcatalina.base=/opt/tomcat, -Dcatalina.home=/opt/tomcat, -Djava.io.tmpdir=/opt/tomcat/temp]
LibraryPath	/usr/java/packages/lib:/usr/lib64:/lib64:/lib:/usr/lib
ManagementSpecVersion	2.0
Name	10314@vps363300.ovh.net
ObjectName	java.lang:type=Runtime
Pid	10 314
SpecName	Java Virtual Machine Specification
SpecVendor	Oracle Corporation
SpecVersion	11
StartTime	1 791 650 226 442

SystemProperties	[{key=awt.toolkit, value=sun.awt.X11.XToolkit}, {key=java.specification.version, value=11}, {key=sun.cpu.isalist, value=}, {key=sun.jnu.encoding, value=ANSI_X3.4-1968}, {key=java.class.path, value=/opt/tomcat/bin/bootstrap.jar:/opt/tomcat/bin/tomcat-juli.jar}, {key=pid, value=10314}, {key=java.vm.vendor, value=AdoptOpenJDK}, {key=sun.arch.data.model, value=64}, {key=sun.font.fontmanager, value=sun.awt.X11FontManager}, {key=java.vendor.url, value=https://adoptopenjdk.net/}, {key=catalina.useNaming, value=true}, {key=user.timezone, value=Europe/Paris}, {key=os.name, value=Linux}, {key=java.vm.specification.version, value=11}, {key=sun.java.launcher, value=SUN_STANDARD}, {key=user.country, value=US}, {key=sun.boot.library.path, value=/opt/jdk-11.0.6+10/lib}, {key=sun.java.command, value=org.apache.catalina.startup.Bootstrap start}, {key=jdk.debug, value=release}, {key=sun.cpu.endian, value=little}, {key=user.home, value=/root}, {key=user.language, value=en}, {key=java.specification.vendor, value=Oracle Corporation}, {key=java.naming.factory.url.pkgs, value=org.apache.naming}, {key=java.version.date, value=2020-01-14}, {key=java.home, value=/opt/jdk-11.0.6+10}, {key=ignore.endorsed.dirs, value=}, {key=file.separator, value=/}, {key=java.vm.compressedOopsMode, value=32-bit}, {key=line.separator, value= }, {key=java.specification.name, value=Java Platform API Specification}, {key=java.vm.specification.vendor, value=Oracle Corporation}, {key=java.awt.graphicsenv, value=sun.awt.X11GraphicsEnvironment}, {key=package.access, value=sun.,org.apache.catalina.,org.apache.coyote.,org.apache.jasper .,org.apache.tomcat.}, {key=package.definition, value=sun.,java.,org.apache.catalina.,org.apache.coyote.,org.apache.j asper.,org.apache.naming.,org.apache.tomcat.}, {key=jdk.tls.ephemeralDHKeySize, value=2048}, {key=server.loader, value=}, {key=java.util.logging.config.file, value=/opt/tomcat/conf/logging.properties}, {key=java.protocol.handler.pkgs, value=org.apache.catalina.webresources}, {key=sun.management.compiler, value=HotSpot 64-Bit Tiered Compilers}, {key=java.runtime.version, value=11.0.6+10}, {key=java.naming.factory.initial, value=org.apache.naming.java.javaURLContextFactory}, {key=user.name, value=root}, {key=path.separator, value=:}, {key=java.security.egd, value=file:/dev/./urandom}, {key=common.loader, value="${catalina.base}/lib","${catalina.base}/lib/*.jar","${catalina.home }/lib","${catalina.home}/lib/*.jar"}, {key=os.version, value=3.10.0-1160.114.2.el7.x86_64}, {key=java.runtime.name, value=OpenJDK Runtime Environment}, {key=file.encoding, value=UTF-8}, {key=java.vm.name, value=OpenJDK 64-Bit Server VM}, {key=java.vendor.version, value=AdoptOpenJDK}, {key=org.apache.catalina.security.SecurityListener.UMASK, value=0027}, {key=java.vendor.url.bug, value=https://github.com/AdoptOpenJDK/openjdk-support/issues}, {key=java.io.tmpdir, value=/opt/tomcat/temp}, {key=tomcat.util.scan.StandardJarScanFilter.jarsToScan, value=log4j- taglib*.jar,log4j-web*.jar,log4javascript*.jar,slf4j-taglib*.jar}, {key=catalina.home, value=/opt/apache-tomcat-9.0.33}, {key=java.version, value=11.0.6}, {key=tomcat.util.scan.StandardJarScanFilter.jarsToSkip, value=annotations-api.jar,ant-junit*.jar,ant-launcher.jar,ant.jar,asm- *.jar,aspectj*.jar,bootstrap.jar,catalina-ant.jar,catalina-ha.jar,catalina- ssi.jar,catalina-storeconfig.jar,catalina-tribes.jar,catalina.jar,cglib- *.jar,cobertura-*.jar,commons-beanutils*.jar,commons- codec*.jar,commons-collections*.jar,commons-daemon.jar,commons- dbcp*.jar,commons-digester*.jar,commons-fileupload*.jar,commons- httpclient*.jar,commons-io*.jar,commons-lang*.jar,commons- logging*.jar,commons-math*.jar,commons-pool*.jar,dom4j- *.jar,easymock-*.jar,ecj-*.jar,el-api.jar,geronimo-spec- jaxrpc*.jar,h2*.jar,hamcrest-*.jar,hibernate*.jar,httpclient*.jar,icu4j- *.jar,jasper-el.jar,jasper.jar,jaspic-api.jar,jaxb-*.jar,jaxen-*.jar,jdom- *.jar,jetty-*.jar,jmx-tools.jar,jmx.jar,jsp-api.jar,jstl.jar,jta*.jar,junit- *.jar,junit.jar,log4j*.jar,mail*.jar,objenesis-*.jar,oraclepki.jar,oro- *.jar,servlet-api-*.jar,servlet-api.jar,slf4j*.jar,taglibs-standard-spec- *.jar,tagsoup-*.jar,tomcat-api.jar,tomcat-coyote.jar,tomcat- dbcp.jar,tomcat-i18n-*.jar,tomcat-jdbc.jar,tomcat-jni.jar,tomcat-juli- adapters.jar,tomcat-juli.jar,tomcat-util-scan.jar,tomcat-util.jar,tomcat- websocket.jar,tools.jar,websocket-api.jar,wsdl4j*.jar,xercesImpl.jar,xml- apis.jar,xmlParserAPIs-*.jar,xmlParserAPIs.jar,xom-*.jar}, {key=user.dir, value=/}, {key=os.arch, value=amd64}, {key=java.vm.specification.name, value=Java Virtual Machine Specification}, {key=java.awt.printerjob, value=sun.print.PSPrinterJob}, {key=sun.os.patch.level, value=unknown}, {key=catalina.base, value=/opt/apache-tomcat-9.0.33}, {key=shared.loader, value=}, {key=java.util.logging.manager, value=org.apache.juli.ClassLoaderLogManager}, {key=java.library.path, value=/usr/java/packages/lib:/usr/lib64:/lib64:/lib:/usr/lib}, {key=java.vendor, value=AdoptOpenJDK}, {key=java.vm.info, value=mixed mode}, {key=java.vm.version, value=11.0.6+10}, {key=sun.io.unicode.encoding, value=UnicodeLittle}, {key=tomcat.util.buf.StringCache.byte.enabled, value=true}, {key=java.class.version, value=55.0}]
Uptime	3 804 769 230
VmName	OpenJDK 64-Bit Server VM
VmVendor	AdoptOpenJDK
VmVersion	11.0.6+10

Survivor Space

type=MemoryPool

CollectionUsage	{committed=10 027 008, init=1 114 112, max=17 039 360, used=4 115 808}
CollectionUsageThreshold	0
CollectionUsageThresholdCount	0
CollectionUsageThresholdExceeded	false
CollectionUsageThresholdSupported	true
MemoryManagerNames	[Copy, MarkSweepCompact]

Name	Survivor Space
ObjectName	java.lang:type=MemoryPool,name=Survivor Space
PeakUsage	{committed=17 039 360, init=1 114 112, max=17 039 360, used=17 039 360}
Type	HEAP
Usage	{committed=10 027 008, init=1 114 112, max=17 039 360, used=4 115 808}
UsageThresholdSupported	false
Valid	true

Tenured Gen

type=MemoryPool

CollectionUsage	{committed=201 543 680, init=22 413 312, max=341 180 416, used=60 509 136}
CollectionUsageThreshold	0
CollectionUsageThresholdCount	0
CollectionUsageThresholdExceeded	false
CollectionUsageThresholdSupported	true
MemoryManagerNames	[MarkSweepCompact]
Name	Tenured Gen
ObjectName	java.lang:type=MemoryPool,name=Tenured Gen
PeakUsage	{committed=341 180 416, init=22 413 312, max=341 180 416, used=341 180 416}
Type	HEAP
Usage	{committed=201 543 680, init=22 413 312, max=341 180 416, used=61 720 288}
UsageThreshold	0
UsageThresholdCount	0
UsageThresholdExceeded	false
UsageThresholdSupported	true
Valid	true

Threading

AllThreadIds	[J@4e303c08
CurrentThreadCpuTime	261 536 925 249
CurrentThreadCpuTimeSupported	true
CurrentThreadUserTime	197 600 000 000
DaemonThreadCount	60
ObjectMonitorUsageSupported	true
ObjectName	java.lang:type=Threading
PeakThreadCount	150
SynchronizerUsageSupported	true
ThreadAllocatedMemoryEnabled	true
ThreadAllocatedMemorySupported	true
ThreadContentionMonitoringEnabled	false
ThreadContentionMonitoringSupported	true
ThreadCount	65
ThreadCpuTimeEnabled	true
ThreadCpuTimeSupported	true
TotalStartedThreadCount	571

java.nio

direct

type=BufferPool

Count	49
MemoryUsed	405 961
Name	direct
ObjectName	java.nio:type=BufferPool,name=direct
TotalCapacity	405 961

mapped

type=BufferPool

Count	0
MemoryUsed	0
Name	mapped
ObjectName	java.nio:type=BufferPool,name=mapped
TotalCapacity	0

java.util.logging

Logging

LoggerNames	[, org.apache.catalina.core.ContainerBase.[Catalina], org.apache.catalina.session, org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo].[default], sun.net.www.protocol.http, org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo].[TelephoneService], org.apache.tomcat.dbcp.dbcp2.BasicDataSource, org.apache.catalina.core.ApplicationFilterConfig, org.apache.jasper, org.apache.jasper.servlet.JasperInitializer, org.apache.jasper.compiler.Compiler, org.apache.catalina.util, org.apache.tomcat.util.descriptor.web.WebXmlParser, org.apache.catalina.webresources, jdk.event, org.apache.tomcat.util.net, org.apache.tomcat.util.digester.Digester, sun.awt.multiscreen.SunDisplayChanger, sun.awt.X11GraphicsEnvironment, org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo].[GradeService], org.apache.jasper.compiler, org.apache.tomcat.util.descriptor.web, org.apache.jasper.servlet.JspServlet, org.apache.tomcat.websocket, org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo], org.apache.catalina.webresources.JarWarResource, org.apache.tomcat.dbcp, org.apache.tomcat.dbcp.dbcp2.ObjectNameWrapper, org.apache.tomcat.util.descriptor, org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo].[MailService], org.apache.catalina, sun.net.www.protocol.http.HttpURLConnection, org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo].[AdresseService], org.apache.tomcat, org.apache.jasper.servlet, org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo].[PersonneService], org.apache.catalina.webresources.JarResourceRoot, jdk.event.security, org.apache.tomcat.util.digester.Digester.sax, org.apache.jasper.JspCompilationContext, org.apache, org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo].[CompetenceService], sun.net, org.apache.catalina.core.ContainerBase, org.apache.tomcat.util.descriptor.web.WebXml, org.apache.jasper.servlet.TldScanner, org.apache.jasper.compiler.JDTCompiler, org.apache.tomcat.util.descriptor.tld, org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo].[AuthentificationService], sun, sun.net.www.protocol, sun.awt.multiscreen, sun.net.www, org.apache.jasper.EmbeddedServletOptions, org.apache.tomcat.dbcp.dbcp2, org.apache.jasper.compiler.JspConfig, org.apache.tomcat.util.scan, org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo].[PermissionService], org.apache.tomcat.dbcp.dbcp2.BasicDataSourceFactory, org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo].[BuildInfoServlet], org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo].[RoleService], org.apache.catalina.core.ContainerBase.[Catalina].[localhost], org.apache.tomcat.util.digester, org.apache.catalina.util.SessionIdGeneratorBase, org.apache.tomcat.util.net.SSLHostConfig, org.apache.tomcat.dbcp.dbcp2.PoolableConnectionFactory, sun.awt.screen, org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo].[UtilisateurService], sun.awt.screen.X11GraphicsEnvironment, org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo].[jsp], org.apache.tomcat.dbcp.dbcp2.PoolingDataSource, sun.awt, org, org.apache.catalina.session.ManagerBase, org.apache.catalina.authenticator.AuthenticatorBase, org.apache.catalina.session.StandardManager, org.apache.tomcat.util.descriptor.tld.TldParser, org.apache.catalina.authenticator, org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo].[PrintUtilsService], jdk, org.apache.jasper.servlet.JspServletWrapper, org.apache.tomcat.util, org.apache.tomcat.util.net.SSLHostConfigCertificate, org.apache.jasper.compiler.JspRuntimeContext, org.apache.catalina.core.StandardWrapper, org.apache.tomcat.util.scan.StandardJarScanner, org.apache.tomcat.websocket.WsWebSocketContainer, org.apache.catalina.core]
ObjectName	java.util.logging:type=Logging

jdk.management.jfr

FlightRecorder

Configurations

[{contents=<?xml version="1.0" encoding="UTF-8"?>

<!--
    Recommended way to edit .jfc files is to use Java Mission Control,
    see Window -> Flight Recorder Template Manager.
-->

<configuration version="2.0" label="Profiling" description="Low
overhead configuration for profiling, typically around 2 % overhead."
provider="Oracle">

  <event name="jdk.ThreadAllocationStatistics">
    <setting name="enabled">true</setting>
    <setting name="period">everyChunk</setting>
  </event>

  <event name="jdk.ClassLoadingStatistics">
    <setting name="enabled">true</setting>
    <setting name="period">1000 ms</setting>
  </event>

  <event name="jdk.ClassLoaderStatistics">
    <setting name="enabled">true</setting>
    <setting name="period">everyChunk</setting>
  </event>

  <event name="jdk.JavaThreadStatistics">
    <setting name="enabled">true</setting>
    <setting name="period">1000 ms</setting>
  </event>

  <event name="jdk.ThreadStart">
    <setting name="enabled">true</setting>
  </event>

  <event name="jdk.ThreadEnd">
    <setting name="enabled">true</setting>
  </event>

  <event name="jdk.ThreadSleep">
    <setting name="enabled">true</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold" control="synchronization-threshold">10
ms</setting>
  </event>

  <event name="jdk.ThreadPark">
    <setting name="enabled">true</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold" control="synchronization-threshold">10
ms</setting>
  </event>

  <event name="jdk.JavaMonitorEnter">
    <setting name="enabled">true</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold" control="synchronization-threshold">10
ms</setting>
  </event>

  <event name="jdk.JavaMonitorWait">
    <setting name="enabled">true</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold" control="synchronization-threshold">10
ms</setting>
  </event>

  <event name="jdk.JavaMonitorInflate">
    <setting name="enabled">true</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold" control="synchronization-threshold">10
ms</setting>
  </event>

  <event name="jdk.BiasedLockRevocation">
    <setting name="enabled">true</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.BiasedLockSelfRevocation">
    <setting name="enabled">true</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.BiasedLockClassRevocation">
    <setting name="enabled">true</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.ReservedStackActivation">
    <setting name="enabled">true</setting>
    <setting name="stackTrace">true</setting>
  </event>

  <event name="jdk.ClassLoad">
    <setting name="enabled" control="class-loading-
enabled">false</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.ClassDefine">
    <setting name="enabled" control="class-loading-
enabled">false</setting>
    <setting name="stackTrace">true</setting>
  </event>

  <event name="jdk.ClassUnload">
    <setting name="enabled" control="class-loading-
enabled">false</setting>
  </event>

  <event name="jdk.JVMInformation">
    <setting name="enabled">true</setting>
    <setting name="period">beginChunk</setting>
  </event>

  <event name="jdk.InitialSystemProperty">
    <setting name="enabled">true</setting>
    <setting name="period">beginChunk</setting>
  </event>

  <event name="jdk.ExecutionSample">
    <setting name="enabled" control="method-sampling-
enabled">true</setting>
    <setting name="period" control="method-sampling-java-
interval">10 ms</setting>
  </event>

  <event name="jdk.NativeMethodSample">
    <setting name="enabled" control="method-sampling-
enabled">true</setting>
    <setting name="period" control="method-sampling-native-
interval">20 ms</setting>
  </event>

```
    <event name="jdk.SafepointBegin">
      <setting name="enabled">true</setting>
      <setting name="threshold">0 ms</setting>
    </event>

    <event name="jdk.SafepointStateSynchronization">
      <setting name="enabled">false</setting>
      <setting name="threshold">0 ms</setting>
    </event>

    <event name="jdk.SafepointWaitBlocked">
      <setting name="enabled">false</setting>
      <setting name="threshold">0 ms</setting>
    </event>

    <event name="jdk.SafepointCleanup">
      <setting name="enabled">false</setting>
      <setting name="threshold">0 ms</setting>
    </event>

    <event name="jdk.SafepointCleanupTask">
      <setting name="enabled">false</setting>
      <setting name="threshold">0 ms</setting>
    </event>

    <event name="jdk.SafepointEnd">
      <setting name="enabled">false</setting>
      <setting name="threshold">0 ms</setting>
    </event>

    <event name="jdk.ExecuteVMOperation">
      <setting name="enabled">true</setting>
      <setting name="threshold">0 ms</setting>
    </event>

    <event name="jdk.Shutdown">
      <setting name="enabled">true</setting>
      <setting name="stackTrace">true</setting>
    </event>

    <event name="jdk.ThreadDump">
      <setting name="enabled" control="thread-dump-
enabled">true</setting>
      <setting name="period" control="thread-dump-interval">60
s</setting>
    </event>

    <event name="jdk.IntFlag">
      <setting name="enabled">true</setting>
      <setting name="period">beginChunk</setting>
    </event>

    <event name="jdk.UnsignedIntFlag">
      <setting name="enabled">true</setting>
      <setting name="period">beginChunk</setting>
    </event>

    <event name="jdk.LongFlag">
      <setting name="enabled">true</setting>
      <setting name="period">beginChunk</setting>
    </event>

    <event name="jdk.UnsignedLongFlag">
      <setting name="enabled">true</setting>
      <setting name="period">beginChunk</setting>
    </event>

    <event name="jdk.DoubleFlag">
      <setting name="enabled">true</setting>
      <setting name="period">beginChunk</setting>
    </event>

    <event name="jdk.BooleanFlag">
      <setting name="enabled">true</setting>
      <setting name="period">beginChunk</setting>
    </event>

    <event name="jdk.StringFlag">
      <setting name="enabled">true</setting>
      <setting name="period">beginChunk</setting>
    </event>

    <event name="jdk.IntFlagChanged">
      <setting name="enabled">true</setting>
    </event>

    <event name="jdk.UnsignedIntFlagChanged">
      <setting name="enabled">true</setting>
    </event>

    <event name="jdk.LongFlagChanged">
      <setting name="enabled">true</setting>
    </event>

    <event name="jdk.UnsignedLongFlagChanged">
      <setting name="enabled">true</setting>
    </event>

    <event name="jdk.DoubleFlagChanged">
      <setting name="enabled">true</setting>
    </event>

    <event name="jdk.BooleanFlagChanged">
      <setting name="enabled">true</setting>
    </event>

    <event name="jdk.StringFlagChanged">
      <setting name="enabled">true</setting>
    </event>

    <event name="jdk.ObjectCount">
      <setting name="enabled" control="memory-profiling-enabled-
all">false</setting>
      <setting name="period">everyChunk</setting>
    </event>

    <event name="jdk.GCConfiguration">
      <setting name="enabled" control="gc-enabled-
normal">true</setting>
      <setting name="period">everyChunk</setting>
    </event>

    <event name="jdk.GCHeapConfiguration">
      <setting name="enabled" control="gc-enabled-
normal">true</setting>
      <setting name="period">beginChunk</setting>
    </event>

    <event name="jdk.YoungGenerationConfiguration">
      <setting name="enabled" control="gc-enabled-
normal">true</setting>
      <setting name="period">beginChunk</setting>
    </event>

    <event name="jdk.GCTLABConfiguration">
      <setting name="enabled" control="gc-enabled-
normal">true</setting>
```

```
    <setting name="period">beginChunk</setting>
  </event>

  <event name="jdk.GCSurvivorConfiguration">
    <setting name="enabled" control="gc-enabled-
normal">true</setting>
    <setting name="period">beginChunk</setting>
  </event>

  <event name="jdk.ObjectCountAfterGC">
    <setting name="enabled">false</setting>
  </event>

  <event name="jdk.GCHeapSummary">
    <setting name="enabled" control="gc-enabled-
normal">true</setting>
  </event>

  <event name="jdk.PSHeapSummary">
    <setting name="enabled" control="gc-enabled-
normal">true</setting>
  </event>

  <event name="jdk.G1HeapSummary">
    <setting name="enabled" control="gc-enabled-
normal">true</setting>
  </event>

  <event name="jdk.MetaspaceSummary">
    <setting name="enabled" control="gc-enabled-
normal">true</setting>
  </event>

  <event name="jdk.MetaspaceGCThreshold">
    <setting name="enabled" control="gc-enabled-
normal">true</setting>
  </event>

  <event name="jdk.MetaspaceAllocationFailure">
    <setting name="enabled" control="gc-enabled-
normal">true</setting>
    <setting name="stackTrace">true</setting>
  </event>

  <event name="jdk.MetaspaceOOM">
    <setting name="enabled" control="gc-enabled-
normal">true</setting>
    <setting name="stackTrace">true</setting>
  </event>

  <event name="jdk.MetaspaceChunkFreeListSummary">
    <setting name="enabled" control="gc-enabled-
normal">true</setting>
  </event>

  <event name="jdk.GarbageCollection">
    <setting name="enabled" control="gc-enabled-
normal">true</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.ParallelOldGarbageCollection">
    <setting name="enabled" control="gc-enabled-
normal">true</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.YoungGarbageCollection">
    <setting name="enabled" control="gc-enabled-
normal">true</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.OldGarbageCollection">
    <setting name="enabled" control="gc-enabled-
normal">true</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.G1GarbageCollection">
    <setting name="enabled" control="gc-enabled-
normal">true</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.GCPhasePause">
    <setting name="enabled" control="gc-enabled-
normal">true</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.GCPhasePauseLevel1">
    <setting name="enabled" control="gc-enabled-
normal">true</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.GCPhasePauseLevel2">
    <setting name="enabled" control="gc-enabled-
normal">true</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.GCPhasePauseLevel3">
    <setting name="enabled" control="gc-enabled-all">false</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.GCPhasePauseLevel4">
    <setting name="enabled" control="gc-enabled-all">false</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.GCPhaseConcurrent">
    <setting name="enabled" control="gc-enabled-all">true</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.GCReferenceStatistics">
    <setting name="enabled" control="gc-enabled-
normal">true</setting>
  </event>

  <event name="jdk.PromotionFailed">
    <setting name="enabled" control="gc-enabled-
normal">true</setting>
  </event>

  <event name="jdk.EvacuationFailed">
    <setting name="enabled" control="gc-enabled-
normal">true</setting>
  </event>

  <event name="jdk.EvacuationInformation">
    <setting name="enabled" control="gc-enabled-
normal">true</setting>
  </event>
```

```
    <event name="jdk.G1MMU">
      <setting name="enabled" control="gc-enabled-
normal">true</setting>
    </event>

    <event name="jdk.G1EvacuationYoungStatistics">
      <setting name="enabled" control="gc-enabled-
normal">true</setting>
    </event>

    <event name="jdk.G1EvacuationOldStatistics">
      <setting name="enabled" control="gc-enabled-
normal">true</setting>
    </event>

    <event name="jdk.G1BasicIHOP">
      <setting name="enabled" control="gc-enabled-
normal">true</setting>
    </event>

    <event name="jdk.G1AdaptiveIHOP">
      <setting name="enabled" control="gc-enabled-
normal">true</setting>
    </event>

    <event name="jdk.PromoteObjectInNewPLAB">
      <setting name="enabled" control="memory-profiling-enabled-
medium">true</setting>
    </event>

    <event name="jdk.PromoteObjectOutsidePLAB">
      <setting name="enabled" control="memory-profiling-enabled-
medium">true</setting>
    </event>

    <event name="jdk.ConcurrentModeFailure">
      <setting name="enabled" control="gc-enabled-
normal">true</setting>
    </event>

    <event name="jdk.AllocationRequiringGC">
      <setting name="enabled" control="gc-enabled-all">false</setting>
      <setting name="stackTrace">true</setting>
    </event>

    <event name="jdk.TenuringDistribution">
      <setting name="enabled" control="gc-enabled-
normal">true</setting>
    </event>

    <event name="jdk.G1HeapRegionInformation">
      <setting name="enabled" control="gc-enabled-all">false</setting>
      <setting name="period">everyChunk</setting>
    </event>

    <event name="jdk.G1HeapRegionTypeChange">
      <setting name="enabled" control="gc-enabled-all">false</setting>
    </event>

    <event name="jdk.OldObjectSample">
      <setting name="enabled" control="memory-leak-detection-
enabled">true</setting>
      <setting name="stackTrace" control="memory-leak-detection-
stack-trace">true</setting>
      <setting name="cutoff" control="memory-leak-detection-cutoff">0
ns</setting>
    </event>

    <event name="jdk.CompilerConfiguration">
      <setting name="enabled" control="compiler-
enabled">true</setting>
      <setting name="period">beginChunk</setting>
    </event>

    <event name="jdk.CompilerStatistics">
      <setting name="enabled" control="compiler-
enabled">true</setting>
      <setting name="period">1000 ms</setting>
    </event>

    <event name="jdk.Compilation">
      <setting name="enabled" control="compiler-
enabled">true</setting>
      <setting name="threshold" control="compiler-compilation-
threshold">100 ms</setting>
    </event>

    <event name="jdk.CompilerPhase">
      <setting name="enabled" control="compiler-
enabled">true</setting>
      <setting name="threshold" control="compiler-phase-threshold">10
s</setting>
    </event>

    <event name="jdk.CompilationFailure">
      <setting name="enabled" control="compiler-enabled-
failure">true</setting>
    </event>

    <event name="jdk.CompilerInlining">
      <setting name="enabled" control="compiler-enabled-
failure">false</setting>
    </event>

    <event name="jdk.CodeSweeperConfiguration">
      <setting name="enabled" control="compiler-
enabled">true</setting>
      <setting name="period">beginChunk</setting>
    </event>

    <event name="jdk.CodeSweeperStatistics">
      <setting name="enabled" control="compiler-
enabled">true</setting>
      <setting name="period">everyChunk</setting>
    </event>

    <event name="jdk.SweepCodeCache">
      <setting name="enabled" control="compiler-
enabled">true</setting>
      <setting name="threshold" control="compiler-sweeper-
threshold">100 ms</setting>
    </event>

    <event name="jdk.CodeCacheConfiguration">
      <setting name="enabled" control="compiler-
enabled">true</setting>
      <setting name="period">beginChunk</setting>
    </event>

    <event name="jdk.CodeCacheStatistics">
      <setting name="enabled" control="compiler-
enabled">true</setting>
      <setting name="period">everyChunk</setting>
    </event>

    <event name="jdk.CodeCacheFull">
      <setting name="enabled" control="compiler-
enabled">true</setting>
```

```
    </event>

    <event name="jdk.OSInformation">
      <setting name="enabled">true</setting>
      <setting name="period">beginChunk</setting>
    </event>

    <event name="jdk.VirtualizationInformation">
     <setting name="enabled">true</setting>
     <setting name="period">beginChunk</setting>
    </event>

    <event name="jdk.CPUInformation">
      <setting name="enabled">true</setting>
      <setting name="period">beginChunk</setting>
    </event>

    <event name="jdk.ThreadContextSwitchRate">
      <setting name="enabled" control="compiler-
enabled">true</setting>
      <setting name="period">10 s</setting>
    </event>

    <event name="jdk.CPULoad">
      <setting name="enabled">true</setting>
      <setting name="period">1000 ms</setting>
    </event>

    <event name="jdk.ThreadCPULoad">
      <setting name="enabled">true</setting>
      <setting name="period">10 s</setting>
    </event>

    <event name="jdk.CPUTimeStampCounter">
      <setting name="enabled">true</setting>
      <setting name="period">beginChunk</setting>
    </event>

    <event name="jdk.SystemProcess">
      <setting name="enabled">true</setting>
      <setting name="period">endChunk</setting>
    </event>

    <event name="jdk.NetworkUtilization">
      <setting name="enabled">true</setting>
      <setting name="period">5 s</setting>
    </event>

    <event name="jdk.InitialEnvironmentVariable">
      <setting name="enabled">true</setting>
      <setting name="period">beginChunk</setting>
    </event>

    <event name="jdk.PhysicalMemory">
      <setting name="enabled">true</setting>
      <setting name="period">everyChunk</setting>
    </event>

    <event name="jdk.ObjectAllocationInNewTLAB">
      <setting name="enabled" control="memory-profiling-enabled-
medium">true</setting>
      <setting name="stackTrace">true</setting>
    </event>

    <event name="jdk.ObjectAllocationOutsideTLAB">
      <setting name="enabled" control="memory-profiling-enabled-
medium">true</setting>
      <setting name="stackTrace">true</setting>
    </event>

    <event name="jdk.NativeLibrary">
      <setting name="enabled">true</setting>
      <setting name="period">everyChunk</setting>
    </event>

    <event name="jdk.ModuleRequire">
      <setting name="enabled">true</setting>
      <setting name="period">endChunk</setting>
    </event>

    <event name="jdk.ModuleExport">
      <setting name="enabled">true</setting>
      <setting name="period">endChunk</setting>
    </event>

    <event name="jdk.FileForce">
      <setting name="enabled">true</setting>
      <setting name="stackTrace">true</setting>
      <setting name="threshold" control="file-io-threshold">10
ms</setting>
    </event>

    <event name="jdk.FileRead">
      <setting name="enabled">true</setting>
      <setting name="stackTrace">true</setting>
      <setting name="threshold" control="file-io-threshold">10
ms</setting>
    </event>

    <event name="jdk.FileWrite">
      <setting name="enabled">true</setting>
      <setting name="stackTrace">true</setting>
      <setting name="threshold" control="file-io-threshold">10
ms</setting>
    </event>

    <event name="jdk.SocketRead">
      <setting name="enabled">true</setting>
      <setting name="stackTrace">true</setting>
      <setting name="threshold" control="socket-io-threshold">10
ms</setting>
    </event>

    <event name="jdk.SocketWrite">
      <setting name="enabled">true</setting>
      <setting name="stackTrace">true</setting>
      <setting name="threshold" control="socket-io-threshold">10
ms</setting>
    </event>

    <event name="jdk.SecurityPropertyModification">
      <setting name="enabled">false</setting>
      <setting name="stackTrace">true</setting>
    </event>

    <event name="jdk.TLSHandshake">
      <setting name="enabled">false</setting>
      <setting name="stackTrace">true</setting>
    </event>

    <event name="jdk.X509Validation">
      <setting name="enabled">false</setting>
      <setting name="stackTrace">true</setting>
    </event>

    <event name="jdk.X509Certificate">
      <setting name="enabled">false</setting>
      <setting name="stackTrace">true</setting>
```

```
    </event>

    <event name="jdk.JavaExceptionThrow">
      <setting name="enabled" control="enable-
exceptions">false</setting>
      <setting name="stackTrace">true</setting>
    </event>

    <event name="jdk.JavaErrorThrow">
      <setting name="enabled" control="enable-errors">true</setting>
      <setting name="stackTrace">true</setting>
    </event>

    <event name="jdk.ExceptionStatistics">
      <setting name="enabled">true</setting>
      <setting name="period">1000 ms</setting>
    </event>

    <event name="jdk.ActiveRecording">
      <setting name="enabled">true</setting>
    </event>

    <event name="jdk.ActiveSetting">
      <setting name="enabled">true</setting>
    </event>

    <event name="jdk.DataLoss">
      <setting name="enabled">true</setting>
    </event>

    <event name="jdk.DumpReason">
      <setting name="enabled">true</setting>
    </event>

    <event name="jdk.ZPageAllocation">
      <setting name="enabled">true</setting>
      <setting name="threshold">10 ms</setting>
    </event>

    <event name="jdk.ZThreadPhase">
      <setting name="enabled">true</setting>
      <setting name="threshold">0 ms</setting>
    </event>

    <event name="jdk.ZStatisticsCounter">
      <setting name="threshold">10 ms</setting>
      <setting name="enabled">true</setting>
    </event>

    <event name="jdk.ZStatisticsSampler">
      <setting name="enabled">true</setting>
      <setting name="threshold">10 ms</setting>
    </event>

    <!--
        Contents of the control element is not read by the JVM, it's used
        by Java Mission Control to change settings that carry the control
attribute.
    -->
    <control>

      <selection name="gc-level" default="detailed" label="Garbage
Collector">
        <option label="Off" name="off">off</option>
        <option label="Normal" name="detailed">normal</option>
        <option label="All" name="all">all</option>
      </selection>

      <condition name="gc-enabled-normal" true="true" false="false">
        <or>
          <test name="gc-level" operator="equal" value="normal"/>
          <test name="gc-level" operator="equal" value="all"/>
        </or>
      </condition>

      <condition name="gc-enabled-all" true="true" false="false">
        <test name="gc-level" operator="equal" value="all"/>
      </condition>

      <selection name="memory-profiling" default="medium"
label="Memory Profiling">
        <option label="Off" name="off">off</option>
        <option label="Object Allocation and Promotion"
name="medium">medium</option>
        <option label="All, including Heap Statistics (May cause long full
GCs)" name="all">all</option>
      </selection>

      <condition name="memory-profiling-enabled-medium" true="true"
false="false">
        <or>
          <test name="memory-profiling" operator="equal"
value="medium"/>
          <test name="memory-profiling" operator="equal" value="all"/>
        </or>
      </condition>

      <condition name="memory-profiling-enabled-all" true="true"
false="false">
        <test name="memory-profiling" operator="equal" value="all"/>
      </condition>

      <selection name="compiler-level" default="detailed"
label="Compiler">
        <option label="Off" name="off">off</option>
        <option label="Normal" name="normal">normal</option>
        <option label="Detailed" name="detailed">detailed</option>
        <option label="All" name="all">all</option>
      </selection>
```

```
    <condition name="compiler-enabled" true="false" false="true">
      <test name="compiler-level" operator="equal" value="off"/>
    </condition>

    <condition name="compiler-enabled-failure" true="true"
false="false">
      <or>
        <test name="compiler-level" operator="equal" value="detailed"/>
        <test name="compiler-level" operator="equal" value="all"/>
      </or>
    </condition>

    <condition name="compiler-sweeper-threshold" true="0 ms"
false="100 ms">
      <test name="compiler-level" operator="equal" value="all"/>
    </condition>

    <condition name="compiler-compilation-threshold" true="1000
ms">
      <test name="compiler-level" operator="equal" value="normal"/>
    </condition>

    <condition name="compiler-compilation-threshold" true="100 ms">
      <test name="compiler-level" operator="equal" value="detailed"/>
    </condition>

    <condition name="compiler-compilation-threshold" true="0 ms">
      <test name="compiler-level" operator="equal" value="all"/>
    </condition>

    <condition name="compiler-phase-threshold" true="60 s">
      <test name="compiler-level" operator="equal" value="normal"/>
    </condition>

    <condition name="compiler-phase-threshold" true="10 s">
      <test name="compiler-level" operator="equal" value="detailed"/>
    </condition>

    <condition name="compiler-phase-threshold" true="0 s">
      <test name="compiler-level" operator="equal" value="all"/>
    </condition>

    <selection name="method-sampling-interval" default="normal"
label="Method Sampling">
      <option label="Off" name="off">off</option>
      <option label="Normal" name="normal">normal</option>
      <option label="High" name="high">high</option>
      <option label="Ludicrous (High Overhead)"
name="ludicrous">ludicrous</option>
    </selection>

    <condition name="method-sampling-java-interval" true="999 d">
      <test name="method-sampling-interval" operator="equal"
value="off"/>
    </condition>

    <condition name="method-sampling-java-interval" true="20 ms">
      <test name="method-sampling-interval" operator="equal"
value="normal"/>
    </condition>

    <condition name="method-sampling-java-interval" true="10 ms">
      <test name="method-sampling-interval" operator="equal"
value="high"/>
    </condition>

    <condition name="method-sampling-java-interval" true="1 ms">
      <test name="method-sampling-interval" operator="equal"
value="ludicrous"/>
    </condition>

    <condition name="method-sampling-native-interval" true="999 d">
      <test name="method-sampling-interval" operator="equal"
value="off"/>
    </condition>

    <condition name="method-sampling-native-interval" true="20 ms">
      <or>
        <test name="method-sampling-interval" operator="equal"
value="normal"/>
        <test name="method-sampling-interval" operator="equal"
value="high"/>
        <test name="method-sampling-interval" operator="equal"
value="ludicrous"/>
      </or>
    </condition>

    <condition name="method-sampling-enabled" true="false"
false="true">
      <test name="method-sampling-interval" operator="equal"
value="off"/>
    </condition>

    <selection name="thread-dump-interval" default="everyMinute"
label="Thread Dump">
      <option label="Off" name="off">999 d</option>
      <option label="At least Once"
name="normal">everyChunk</option>
      <option label="Every 60 s" name="everyMinute">60 s</option>
      <option label="Every 10 s" name="everyTenSecond">10
s</option>
      <option label="Every 1 s" name="everySecond">1 s</option>
    </selection>

    <condition name="thread-dump-enabled" true="false" false="true">
      <test name="thread-dump-interval" operator="equal" value="999
d"/>
    </condition>

    <selection name="exception-level" default="errors"
label="Exceptions">
      <option label="Off" name="off">off</option>
      <option label="Errors Only" name="errors">errors</option>
      <option label="All Exceptions, including Errors"
name="all">all</option>
    </selection>

    <condition name="enable-errors" true="true" false="false">
      <or>
        <test name="exception-level" operator="equal" value="errors"/>
        <test name="exception-level" operator="equal" value="all"/>
      </or>
    </condition>

    <condition name="enable-exceptions" true="true" false="false">
      <test name="exception-level" operator="equal" value="all"/>
    </condition>

    <selection name="memory-leak-detection" default="medium"
label="Memory Leak Detection">
      <option label="Off" name="off">off</option>
      <option label="Object Types" name="minimal">minimal</option>
      <option label="Object Types + Allocation Stack Traces"
name="medium">medium</option>
      <option label="Object Types + Allocation Stack Traces + Path to
GC Root" name="full">full</option>
    </selection>
```

```
    <condition name="memory-leak-detection-enabled" true="false"
false="true">
      <test name="memory-leak-detection" operator="equal"
value="off"/>
    </condition>

    <condition name="memory-leak-detection-stack-trace" true="true"
false="false">
      <or>
        <test name="memory-leak-detection" operator="equal"
value="medium"/>
        <test name="memory-leak-detection" operator="equal"
value="full"/>
      </or>
    </condition>

    <condition name="memory-leak-detection-cutoff" true="1 h"
false="0 ns">
      <test name="memory-leak-detection" operator="equal"
value="full"/>
    </condition>

    <text name="synchronization-threshold" label="Synchronization
Threshold" contentType="timespan" minimum="0 s">10 ms</text>

    <text name="file-io-threshold" label="File I/O Threshold"
contentType="timespan" minimum="0 s">10 ms</text>

    <text name="socket-io-threshold" label="Socket I/O Threshold"
contentType="timespan" minimum="0 s">10 ms</text>

    <flag name="class-loading-enabled" label="Class
Loading">false</flag>

  </control>

</configuration>
, description=Low overhead configuration for profiling, typically around
2 % overhead., label=Profiling, name=profile, provider=Oracle,
settings=[{key=jdk.ThreadAllocationStatistics#enabled, value=true},
{key=jdk.ThreadAllocationStatistics#period, value=everyChunk},
{key=jdk.ClassLoadingStatistics#enabled, value=true},
{key=jdk.ClassLoadingStatistics#period, value=1000 ms},
{key=jdk.ClassLoaderStatistics#enabled, value=true},
{key=jdk.ClassLoaderStatistics#period, value=everyChunk},
{key=jdk.JavaThreadStatistics#enabled, value=true},
{key=jdk.JavaThreadStatistics#period, value=1000 ms},
{key=jdk.ThreadStart#enabled, value=true},
{key=jdk.ThreadEnd#enabled, value=true},
{key=jdk.ThreadSleep#enabled, value=true},
{key=jdk.ThreadSleep#stackTrace, value=true},
{key=jdk.ThreadSleep#threshold, value=10 ms},
{key=jdk.ThreadPark#enabled, value=true},
{key=jdk.ThreadPark#stackTrace, value=true},
{key=jdk.ThreadPark#threshold, value=10 ms},
{key=jdk.JavaMonitorEnter#enabled, value=true},
{key=jdk.JavaMonitorEnter#stackTrace, value=true},
{key=jdk.JavaMonitorEnter#threshold, value=10 ms},
{key=jdk.JavaMonitorWait#enabled, value=true},
{key=jdk.JavaMonitorWait#stackTrace, value=true},
{key=jdk.JavaMonitorWait#threshold, value=10 ms},
{key=jdk.JavaMonitorInflate#enabled, value=true},
{key=jdk.JavaMonitorInflate#stackTrace, value=true},
{key=jdk.JavaMonitorInflate#threshold, value=10 ms},
{key=jdk.BiasedLockRevocation#enabled, value=true},
{key=jdk.BiasedLockRevocation#stackTrace, value=true},
{key=jdk.BiasedLockRevocation#threshold, value=0 ms},
{key=jdk.BiasedLockSelfRevocation#enabled, value=true},
{key=jdk.BiasedLockSelfRevocation#stackTrace, value=true},
{key=jdk.BiasedLockSelfRevocation#threshold, value=0 ms},
{key=jdk.BiasedLockClassRevocation#enabled, value=true},
{key=jdk.BiasedLockClassRevocation#stackTrace, value=true},
{key=jdk.BiasedLockClassRevocation#threshold, value=0 ms},
{key=jdk.ReservedStackActivation#enabled, value=true},
{key=jdk.ReservedStackActivation#stackTrace, value=true},
{key=jdk.ClassLoad#enabled, value=false},
{key=jdk.ClassLoad#stackTrace, value=true},
{key=jdk.ClassLoad#threshold, value=0 ms},
{key=jdk.ClassDefine#enabled, value=false},
{key=jdk.ClassDefine#stackTrace, value=true},
{key=jdk.ClassUnload#enabled, value=false},
{key=jdk.JVMInformation#enabled, value=true},
{key=jdk.JVMInformation#period, value=beginChunk},
{key=jdk.InitialSystemProperty#enabled, value=true},
{key=jdk.InitialSystemProperty#period, value=beginChunk},
{key=jdk.ExecutionSample#enabled, value=true},
{key=jdk.ExecutionSample#period, value=10 ms},
{key=jdk.NativeMethodSample#enabled, value=true},
{key=jdk.NativeMethodSample#period, value=20 ms},
{key=jdk.SafepointBegin#enabled, value=true},
{key=jdk.SafepointBegin#threshold, value=0 ms},
{key=jdk.SafepointStateSynchronization#enabled, value=false},
{key=jdk.SafepointStateSynchronization#threshold, value=0 ms},
{key=jdk.SafepointWaitBlocked#enabled, value=false},
{key=jdk.SafepointWaitBlocked#threshold, value=0 ms},
{key=jdk.SafepointCleanup#enabled, value=false},
{key=jdk.SafepointCleanup#threshold, value=0 ms},
{key=jdk.SafepointCleanupTask#enabled, value=false},
{key=jdk.SafepointCleanupTask#threshold, value=0 ms},
{key=jdk.SafepointEnd#enabled, value=false},
{key=jdk.SafepointEnd#threshold, value=0 ms},
{key=jdk.ExecuteVMOperation#enabled, value=true},
{key=jdk.ExecuteVMOperation#threshold, value=0 ms},
{key=jdk.Shutdown#enabled, value=true},
{key=jdk.Shutdown#stackTrace, value=true},
{key=jdk.ThreadDump#enabled, value=true},
{key=jdk.ThreadDump#period, value=60 s}, {key=jdk.IntFlag#enabled,
value=true}, {key=jdk.IntFlag#period, value=beginChunk},
{key=jdk.UnsignedIntFlag#enabled, value=true},
{key=jdk.UnsignedIntFlag#period, value=beginChunk},
{key=jdk.LongFlag#enabled, value=true}, {key=jdk.LongFlag#period,
value=beginChunk}, {key=jdk.UnsignedLongFlag#enabled,
value=true}, {key=jdk.UnsignedLongFlag#period, value=beginChunk},
{key=jdk.DoubleFlag#enabled, value=true},
{key=jdk.DoubleFlag#period, value=beginChunk},
{key=jdk.BooleanFlag#enabled, value=true},
{key=jdk.BooleanFlag#period, value=beginChunk},
{key=jdk.StringFlag#enabled, value=true}, {key=jdk.StringFlag#period,
value=beginChunk}, {key=jdk.IntFlagChanged#enabled, value=true},
{key=jdk.UnsignedIntFlagChanged#enabled, value=true},
{key=jdk.LongFlagChanged#enabled, value=true},
{key=jdk.UnsignedLongFlagChanged#enabled, value=true},
{key=jdk.DoubleFlagChanged#enabled, value=true},
{key=jdk.BooleanFlagChanged#enabled, value=true},
{key=jdk.StringFlagChanged#enabled, value=true},
{key=jdk.ObjectCount#enabled, value=false},
{key=jdk.ObjectCount#period, value=everyChunk},
{key=jdk.GCConfiguration#enabled, value=true},
{key=jdk.GCConfiguration#period, value=everyChunk},
{key=jdk.GCHeapConfiguration#enabled, value=true},
{key=jdk.GCHeapConfiguration#period, value=beginChunk},
{key=jdk.YoungGenerationConfiguration#enabled, value=true},
{key=jdk.YoungGenerationConfiguration#period, value=beginChunk},
{key=jdk.GCTLABConfiguration#enabled, value=true},
{key=jdk.GCTLABConfiguration#period, value=beginChunk},
{key=jdk.GCSurvivorConfiguration#enabled, value=true},
{key=jdk.GCSurvivorConfiguration#period, value=beginChunk},
{key=jdk.ObjectCountAfterGC#enabled, value=false},
```

{key=jdk.GCHeapSummary#enabled, value=true},
{key=jdk.PSHeapSummary#enabled, value=true},
{key=jdk.G1HeapSummary#enabled, value=true},
{key=jdk.MetaspaceSummary#enabled, value=true},
{key=jdk.MetaspaceGCThreshold#enabled, value=true},
{key=jdk.MetaspaceAllocationFailure#enabled, value=true},
{key=jdk.MetaspaceAllocationFailure#stackTrace, value=true},
{key=jdk.MetaspaceOOM#enabled, value=true},
{key=jdk.MetaspaceOOM#stackTrace, value=true},
{key=jdk.MetaspaceChunkFreeListSummary#enabled, value=true},
{key=jdk.GarbageCollection#enabled, value=true},
{key=jdk.GarbageCollection#threshold, value=0 ms},
{key=jdk.ParallelOldGarbageCollection#enabled, value=true},
{key=jdk.ParallelOldGarbageCollection#threshold, value=0 ms},
{key=jdk.YoungGarbageCollection#enabled, value=true},
{key=jdk.YoungGarbageCollection#threshold, value=0 ms},
{key=jdk.OldGarbageCollection#enabled, value=true},
{key=jdk.OldGarbageCollection#threshold, value=0 ms},
{key=jdk.G1GarbageCollection#enabled, value=true},
{key=jdk.G1GarbageCollection#threshold, value=0 ms},
{key=jdk.GCPhasePause#enabled, value=true},
{key=jdk.GCPhasePause#threshold, value=0 ms},
{key=jdk.GCPhasePauseLevel1#enabled, value=true},
{key=jdk.GCPhasePauseLevel1#threshold, value=0 ms},
{key=jdk.GCPhasePauseLevel2#enabled, value=true},
{key=jdk.GCPhasePauseLevel2#threshold, value=0 ms},
{key=jdk.GCPhasePauseLevel3#enabled, value=false},
{key=jdk.GCPhasePauseLevel3#threshold, value=0 ms},
{key=jdk.GCPhasePauseLevel4#enabled, value=false},
{key=jdk.GCPhasePauseLevel4#threshold, value=0 ms},
{key=jdk.GCPhaseConcurrent#enabled, value=true},
{key=jdk.GCPhaseConcurrent#threshold, value=0 ms},
{key=jdk.GCReferenceStatistics#enabled, value=true},
{key=jdk.PromotionFailed#enabled, value=true},
{key=jdk.EvacuationFailed#enabled, value=true},
{key=jdk.EvacuationInformation#enabled, value=true},
{key=jdk.G1MMU#enabled, value=true},
{key=jdk.G1EvacuationYoungStatistics#enabled, value=true},
{key=jdk.G1EvacuationOldStatistics#enabled, value=true},
{key=jdk.G1BasicIHOP#enabled, value=true},
{key=jdk.G1AdaptiveIHOP#enabled, value=true},
{key=jdk.PromoteObjectInNewPLAB#enabled, value=true},
{key=jdk.PromoteObjectOutsidePLAB#enabled, value=true},
{key=jdk.ConcurrentModeFailure#enabled, value=true},
{key=jdk.AllocationRequiringGC#enabled, value=false},
{key=jdk.AllocationRequiringGC#stackTrace, value=true},
{key=jdk.TenuringDistribution#enabled, value=true},
{key=jdk.G1HeapRegionInformation#enabled, value=false},
{key=jdk.G1HeapRegionInformation#period, value=everyChunk},
{key=jdk.G1HeapRegionTypeChange#enabled, value=false},
{key=jdk.OldObjectSample#enabled, value=true},
{key=jdk.OldObjectSample#stackTrace, value=true},
{key=jdk.OldObjectSample#cutoff, value=0 ns},
{key=jdk.CompilerConfiguration#enabled, value=true},
{key=jdk.CompilerConfiguration#period, value=beginChunk},
{key=jdk.CompilerStatistics#enabled, value=true},
{key=jdk.CompilerStatistics#period, value=1000 ms},
{key=jdk.Compilation#enabled, value=true},
{key=jdk.Compilation#threshold, value=100 ms},
{key=jdk.CompilerPhase#enabled, value=true},
{key=jdk.CompilerPhase#threshold, value=10 s},
{key=jdk.CompilationFailure#enabled, value=true},
{key=jdk.CompilerInlining#enabled, value=false},
{key=jdk.CodeSweeperConfiguration#enabled, value=true},
{key=jdk.CodeSweeperConfiguration#period, value=beginChunk},
{key=jdk.CodeSweeperStatistics#enabled, value=true},
{key=jdk.CodeSweeperStatistics#period, value=everyChunk},
{key=jdk.SweepCodeCache#enabled, value=true},
{key=jdk.SweepCodeCache#threshold, value=100 ms},
{key=jdk.CodeCacheConfiguration#enabled, value=true},
{key=jdk.CodeCacheConfiguration#period, value=beginChunk},
{key=jdk.CodeCacheStatistics#enabled, value=true},
{key=jdk.CodeCacheStatistics#period, value=everyChunk},
{key=jdk.CodeCacheFull#enabled, value=true},
{key=jdk.OSInformation#enabled, value=true},
{key=jdk.OSInformation#period, value=beginChunk},
{key=jdk.VirtualizationInformation#enabled, value=true},
{key=jdk.VirtualizationInformation#period, value=beginChunk},
{key=jdk.CPUInformation#enabled, value=true},
{key=jdk.CPUInformation#period, value=beginChunk},
{key=jdk.ThreadContextSwitchRate#enabled, value=true},
{key=jdk.ThreadContextSwitchRate#period, value=10 s},
{key=jdk.CPULoad#enabled, value=true}, {key=jdk.CPULoad#period,
value=1000 ms}, {key=jdk.ThreadCPULoad#enabled, value=true},
{key=jdk.ThreadCPULoad#period, value=10 s},
{key=jdk.CPUTimeStampCounter#enabled, value=true},
{key=jdk.CPUTimeStampCounter#period, value=beginChunk},
{key=jdk.SystemProcess#enabled, value=true},
{key=jdk.SystemProcess#period, value=endChunk},
{key=jdk.NetworkUtilization#enabled, value=true},
{key=jdk.NetworkUtilization#period, value=5 s},
{key=jdk.InitialEnvironmentVariable#enabled, value=true},
{key=jdk.InitialEnvironmentVariable#period, value=beginChunk},
{key=jdk.PhysicalMemory#enabled, value=true},
{key=jdk.PhysicalMemory#period, value=everyChunk},
{key=jdk.ObjectAllocationInNewTLAB#enabled, value=true},
{key=jdk.ObjectAllocationInNewTLAB#stackTrace, value=true},
{key=jdk.ObjectAllocationOutsideTLAB#enabled, value=true},
{key=jdk.ObjectAllocationOutsideTLAB#stackTrace, value=true},
{key=jdk.NativeLibrary#enabled, value=true},
{key=jdk.NativeLibrary#period, value=everyChunk},
{key=jdk.ModuleRequire#enabled, value=true},
{key=jdk.ModuleRequire#period, value=endChunk},
{key=jdk.ModuleExport#enabled, value=true},
{key=jdk.ModuleExport#period, value=endChunk},
{key=jdk.FileForce#enabled, value=true},
{key=jdk.FileForce#stackTrace, value=true},
{key=jdk.FileForce#threshold, value=10 ms},
{key=jdk.FileRead#enabled, value=true},
{key=jdk.FileRead#stackTrace, value=true},
{key=jdk.FileRead#threshold, value=10 ms},
{key=jdk.FileWrite#enabled, value=true},
{key=jdk.FileWrite#stackTrace, value=true},
{key=jdk.FileWrite#threshold, value=10 ms},
{key=jdk.SocketRead#enabled, value=true},
{key=jdk.SocketRead#stackTrace, value=true},
{key=jdk.SocketRead#threshold, value=10 ms},
{key=jdk.SocketWrite#enabled, value=true},
{key=jdk.SocketWrite#stackTrace, value=true},
{key=jdk.SocketWrite#threshold, value=10 ms},
{key=jdk.SecurityPropertyModification#enabled, value=false},
{key=jdk.SecurityPropertyModification#stackTrace, value=true},
{key=jdk.TLSHandshake#enabled, value=false},
{key=jdk.TLSHandshake#stackTrace, value=true},
{key=jdk.X509Validation#enabled, value=false},
{key=jdk.X509Validation#stackTrace, value=true},
{key=jdk.X509Certificate#enabled, value=false},
{key=jdk.X509Certificate#stackTrace, value=true},
{key=jdk.JavaExceptionThrow#enabled, value=false},
{key=jdk.JavaExceptionThrow#stackTrace, value=true},
{key=jdk.JavaErrorThrow#enabled, value=true},
{key=jdk.JavaErrorThrow#stackTrace, value=true},
{key=jdk.ExceptionStatistics#enabled, value=true},
{key=jdk.ExceptionStatistics#period, value=1000 ms},
{key=jdk.ActiveRecording#enabled, value=true},
{key=jdk.ActiveSetting#enabled, value=true},
{key=jdk.DataLoss#enabled, value=true},
{key=jdk.DumpReason#enabled, value=true},

{key=jdk.ZPageAllocation#enabled, value=true},
{key=jdk.ZPageAllocation#threshold, value=10 ms},
{key=jdk.ZThreadPhase#enabled, value=true},
{key=jdk.ZThreadPhase#threshold, value=0 ms},
{key=jdk.ZStatisticsCounter#threshold, value=10 ms},
{key=jdk.ZStatisticsCounter#enabled, value=true},
{key=jdk.ZStatisticsSampler#enabled, value=true},
{key=jdk.ZStatisticsSampler#threshold, value=10 ms}]},
{contents=<?xml version="1.0" encoding="UTF-8"?>

<!--
    Recommended way to edit .jfc files is to use Java Mission Control,
    see Window -> Flight Recorder Template Manager.
-->

<configuration version="2.0" label="Continuous" description="Low
overhead configuration safe for continuous use in production
environments, typically less than 1 % overhead." provider="Oracle">

  <event name="jdk.ThreadAllocationStatistics">
    <setting name="enabled">true</setting>
    <setting name="period">everyChunk</setting>
  </event>

  <event name="jdk.ClassLoadingStatistics">
    <setting name="enabled">true</setting>
    <setting name="period">1000 ms</setting>
  </event>

  <event name="jdk.ClassLoaderStatistics">
    <setting name="enabled">true</setting>
    <setting name="period">everyChunk</setting>
  </event>

  <event name="jdk.JavaThreadStatistics">
    <setting name="enabled">true</setting>
    <setting name="period">1000 ms</setting>
  </event>

  <event name="jdk.ThreadStart">
    <setting name="enabled">true</setting>
  </event>

  <event name="jdk.ThreadEnd">
    <setting name="enabled">true</setting>
  </event>

  <event name="jdk.ThreadSleep">
    <setting name="enabled">true</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold" control="synchronization-threshold">20
ms</setting>
  </event>

  <event name="jdk.ThreadPark">
    <setting name="enabled">true</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold" control="synchronization-threshold">20
ms</setting>
  </event>

  <event name="jdk.JavaMonitorEnter">
    <setting name="enabled">true</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold" control="synchronization-threshold">20
ms</setting>
  </event>

  <event name="jdk.JavaMonitorWait">
    <setting name="enabled">true</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold" control="synchronization-threshold">20
ms</setting>
  </event>

  <event name="jdk.JavaMonitorInflate">
    <setting name="enabled">false</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold" control="synchronization-threshold">20
ms</setting>
  </event>

  <event name="jdk.BiasedLockRevocation">
    <setting name="enabled">true</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.BiasedLockSelfRevocation">
    <setting name="enabled">true</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.BiasedLockClassRevocation">
    <setting name="enabled">true</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.ReservedStackActivation">
    <setting name="enabled">true</setting>
    <setting name="stackTrace">true</setting>
  </event>

  <event name="jdk.ClassLoad">
    <setting name="enabled" control="class-loading-
enabled">false</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.ClassDefine">
    <setting name="enabled" control="class-loading-
enabled">false</setting>
    <setting name="stackTrace">true</setting>
  </event>

  <event name="jdk.ClassUnload">
    <setting name="enabled" control="class-loading-
enabled">false</setting>
  </event>

  <event name="jdk.JVMInformation">
    <setting name="enabled">true</setting>
    <setting name="period">beginChunk</setting>
  </event>

  <event name="jdk.InitialSystemProperty">
    <setting name="enabled">true</setting>
    <setting name="period">beginChunk</setting>
  </event>

  <event name="jdk.ExecutionSample">
    <setting name="enabled" control="method-sampling-
enabled">true</setting>
    <setting name="period" control="method-sampling-java-
interval">20 ms</setting>

```
    </event>

    <event name="jdk.NativeMethodSample">
      <setting name="enabled" control="method-sampling-
enabled">true</setting>
      <setting name="period" control="method-sampling-native-
interval">20 ms</setting>
    </event>

    <event name="jdk.SafepointBegin">
      <setting name="enabled">true</setting>
      <setting name="threshold">10 ms</setting>
    </event>

    <event name="jdk.SafepointStateSynchronization">
      <setting name="enabled">false</setting>
      <setting name="threshold">10 ms</setting>
    </event>

    <event name="jdk.SafepointWaitBlocked">
      <setting name="enabled">false</setting>
      <setting name="threshold">10 ms</setting>
    </event>

    <event name="jdk.SafepointCleanup">
      <setting name="enabled">false</setting>
      <setting name="threshold">10 ms</setting>
    </event>

    <event name="jdk.SafepointCleanupTask">
      <setting name="enabled">false</setting>
      <setting name="threshold">10 ms</setting>
    </event>

    <event name="jdk.SafepointEnd">
      <setting name="enabled">false</setting>
      <setting name="threshold">10 ms</setting>
    </event>

    <event name="jdk.ExecuteVMOperation">
      <setting name="enabled">true</setting>
      <setting name="threshold">10 ms</setting>
    </event>

    <event name="jdk.Shutdown">
      <setting name="enabled">true</setting>
      <setting name="stackTrace">true</setting>
    </event>

    <event name="jdk.ThreadDump">
      <setting name="enabled" control="thread-dump-
enabled">true</setting>
      <setting name="period" control="thread-dump-
interval">everyChunk</setting>
    </event>

    <event name="jdk.IntFlag">
      <setting name="enabled">true</setting>
      <setting name="period">beginChunk</setting>
    </event>

    <event name="jdk.UnsignedIntFlag">
      <setting name="enabled">true</setting>
      <setting name="period">beginChunk</setting>
    </event>

    <event name="jdk.LongFlag">
      <setting name="enabled">true</setting>
      <setting name="period">beginChunk</setting>
    </event>

    <event name="jdk.UnsignedLongFlag">
      <setting name="enabled">true</setting>
      <setting name="period">beginChunk</setting>
    </event>

    <event name="jdk.DoubleFlag">
      <setting name="enabled">true</setting>
      <setting name="period">beginChunk</setting>
    </event>

    <event name="jdk.BooleanFlag">
      <setting name="enabled">true</setting>
      <setting name="period">beginChunk</setting>
    </event>

    <event name="jdk.StringFlag">
      <setting name="enabled">true</setting>
      <setting name="period">beginChunk</setting>
    </event>

    <event name="jdk.IntFlagChanged">
      <setting name="enabled">true</setting>
    </event>

    <event name="jdk.UnsignedIntFlagChanged">
      <setting name="enabled">true</setting>
    </event>

    <event name="jdk.LongFlagChanged">
      <setting name="enabled">true</setting>
    </event>

    <event name="jdk.UnsignedLongFlagChanged">
      <setting name="enabled">true</setting>
    </event>

    <event name="jdk.DoubleFlagChanged">
      <setting name="enabled">true</setting>
    </event>

    <event name="jdk.BooleanFlagChanged">
      <setting name="enabled">true</setting>
    </event>

    <event name="jdk.StringFlagChanged">
      <setting name="enabled">true</setting>
    </event>

    <event name="jdk.ObjectCount">
      <setting name="enabled" control="memory-profiling-enabled-
all">false</setting>
      <setting name="period">everyChunk</setting>
    </event>

    <event name="jdk.GCConfiguration">
      <setting name="enabled" control="gc-enabled-
normal">true</setting>
      <setting name="period">everyChunk</setting>
    </event>

    <event name="jdk.GCHeapConfiguration">
      <setting name="enabled" control="gc-enabled-
normal">true</setting>
      <setting name="period">beginChunk</setting>
    </event>

    <event name="jdk.YoungGenerationConfiguration">
```

```
    <setting name="enabled" control="gc-enabled-
normal">true</setting>
    <setting name="period">beginChunk</setting>
  </event>

  <event name="jdk.GCTLABConfiguration">
    <setting name="enabled" control="gc-enabled-
normal">true</setting>
    <setting name="period">beginChunk</setting>
  </event>

  <event name="jdk.GCSurvivorConfiguration">
    <setting name="enabled" control="gc-enabled-
normal">true</setting>
    <setting name="period">beginChunk</setting>
  </event>

  <event name="jdk.ObjectCountAfterGC">
    <setting name="enabled">false</setting>
  </event>

  <event name="jdk.GCHeapSummary">
    <setting name="enabled" control="gc-enabled-
normal">true</setting>
  </event>

  <event name="jdk.PSHeapSummary">
    <setting name="enabled" control="gc-enabled-
normal">true</setting>
  </event>

  <event name="jdk.G1HeapSummary">
    <setting name="enabled" control="gc-enabled-
normal">true</setting>
  </event>

  <event name="jdk.MetaspaceSummary">
    <setting name="enabled" control="gc-enabled-
normal">true</setting>
  </event>

  <event name="jdk.MetaspaceGCThreshold">
    <setting name="enabled" control="gc-enabled-
normal">true</setting>
  </event>

  <event name="jdk.MetaspaceAllocationFailure">
    <setting name="enabled" control="gc-enabled-
normal">true</setting>
    <setting name="stackTrace">true</setting>
  </event>

  <event name="jdk.MetaspaceOOM">
    <setting name="enabled" control="gc-enabled-
normal">true</setting>
    <setting name="stackTrace">true</setting>
  </event>

  <event name="jdk.MetaspaceChunkFreeListSummary">
    <setting name="enabled" control="gc-enabled-
normal">true</setting>
  </event>

  <event name="jdk.GarbageCollection">
    <setting name="enabled" control="gc-enabled-
normal">true</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.ParallelOldGarbageCollection">
    <setting name="enabled" control="gc-enabled-
normal">true</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.YoungGarbageCollection">
    <setting name="enabled" control="gc-enabled-
normal">true</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.OldGarbageCollection">
    <setting name="enabled" control="gc-enabled-
normal">true</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.G1GarbageCollection">
    <setting name="enabled" control="gc-enabled-
normal">true</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.GCPhasePause">
    <setting name="enabled" control="gc-enabled-
normal">true</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.GCPhasePauseLevel1">
    <setting name="enabled" control="gc-enabled-
normal">true</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.GCPhasePauseLevel2">
    <setting name="enabled" control="gc-enabled-
normal">true</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.GCPhasePauseLevel3">
    <setting name="enabled" control="gc-enabled-all">false</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.GCPhasePauseLevel4">
    <setting name="enabled" control="gc-enabled-all">false</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.GCPhaseConcurrent">
    <setting name="enabled" control="gc-enabled-all">true</setting>
    <setting name="threshold">0 ms</setting>
  </event>

  <event name="jdk.GCReferenceStatistics">
    <setting name="enabled" control="gc-enabled-
normal">true</setting>
  </event>

  <event name="jdk.PromotionFailed">
    <setting name="enabled" control="gc-enabled-
normal">true</setting>
  </event>

  <event name="jdk.EvacuationFailed">
    <setting name="enabled" control="gc-enabled-
```

```
normal">true</setting>
    </event>

    <event name="jdk.EvacuationInformation">
      <setting name="enabled" control="gc-enabled-
normal">true</setting>
    </event>

    <event name="jdk.G1MMU">
      <setting name="enabled" control="gc-enabled-
normal">true</setting>
    </event>

    <event name="jdk.G1EvacuationYoungStatistics">
      <setting name="enabled" control="gc-enabled-
normal">true</setting>
    </event>

    <event name="jdk.G1EvacuationOldStatistics">
      <setting name="enabled" control="gc-enabled-
normal">true</setting>
    </event>

    <event name="jdk.G1BasicIHOP">
      <setting name="enabled" control="gc-enabled-
normal">true</setting>
    </event>

    <event name="jdk.G1AdaptiveIHOP">
      <setting name="enabled" control="gc-enabled-
normal">true</setting>
    </event>

    <event name="jdk.PromoteObjectInNewPLAB">
      <setting name="enabled" control="memory-profiling-enabled-
medium">false</setting>
    </event>

    <event name="jdk.PromoteObjectOutsidePLAB">
      <setting name="enabled" control="memory-profiling-enabled-
medium">false</setting>
    </event>

    <event name="jdk.ConcurrentModeFailure">
      <setting name="enabled" control="gc-enabled-
normal">true</setting>
    </event>

    <event name="jdk.AllocationRequiringGC">
      <setting name="enabled" control="gc-enabled-all">false</setting>
      <setting name="stackTrace">true</setting>
    </event>

    <event name="jdk.TenuringDistribution">
      <setting name="enabled" control="gc-enabled-
normal">true</setting>
    </event>

    <event name="jdk.G1HeapRegionInformation">
      <setting name="enabled" control="gc-enabled-all">false</setting>
      <setting name="period">everyChunk</setting>
    </event>

    <event name="jdk.G1HeapRegionTypeChange">
      <setting name="enabled" control="gc-enabled-all">false</setting>
    </event>

    <event name="jdk.OldObjectSample">
      <setting name="enabled" control="memory-leak-detection-
enabled">true</setting>
      <setting name="stackTrace" control="memory-leak-detection-
stack-trace">false</setting>
      <setting name="cutoff" control="memory-leak-detection-cutoff">0
ns</setting>
    </event>

    <event name="jdk.CompilerConfiguration">
      <setting name="enabled" control="compiler-
enabled">true</setting>
      <setting name="period">beginChunk</setting>
    </event>

    <event name="jdk.CompilerStatistics">
      <setting name="enabled" control="compiler-
enabled">true</setting>
      <setting name="period">1000 ms</setting>
    </event>

    <event name="jdk.Compilation">
      <setting name="enabled" control="compiler-
enabled">true</setting>
      <setting name="threshold" control="compiler-compilation-
threshold">1000 ms</setting>
    </event>

    <event name="jdk.CompilerPhase">
      <setting name="enabled" control="compiler-
enabled">true</setting>
      <setting name="threshold" control="compiler-phase-threshold">60
s</setting>
    </event>

    <event name="jdk.CompilationFailure">
      <setting name="enabled" control="compiler-enabled-
failure">false</setting>
    </event>

    <event name="jdk.CompilerInlining">
      <setting name="enabled" control="compiler-enabled-
failure">false</setting>
    </event>

    <event name="jdk.CodeSweeperConfiguration">
      <setting name="enabled" control="compiler-
enabled">true</setting>
      <setting name="period">beginChunk</setting>
    </event>

    <event name="jdk.CodeSweeperStatistics">
      <setting name="enabled" control="compiler-
enabled">true</setting>
      <setting name="period">everyChunk</setting>
    </event>

    <event name="jdk.SweepCodeCache">
      <setting name="enabled" control="compiler-
enabled">true</setting>
      <setting name="threshold" control="compiler-sweeper-
threshold">100 ms</setting>
    </event>

    <event name="jdk.CodeCacheConfiguration">
      <setting name="enabled" control="compiler-
enabled">true</setting>
      <setting name="period">beginChunk</setting>
    </event>

    <event name="jdk.CodeCacheStatistics">
```

```
    <setting name="enabled" control="compiler-
enabled">true</setting>
    <setting name="period">everyChunk</setting>
  </event>

  <event name="jdk.CodeCacheFull">
    <setting name="enabled" control="compiler-
enabled">true</setting>
  </event>

  <event name="jdk.OSInformation">
    <setting name="enabled">true</setting>
    <setting name="period">beginChunk</setting>
  </event>

  <event name="jdk.VirtualizationInformation">
   <setting name="enabled">true</setting>
   <setting name="period">beginChunk</setting>
  </event>

  <event name="jdk.CPUInformation">
    <setting name="enabled">true</setting>
    <setting name="period">beginChunk</setting>
  </event>

  <event name="jdk.ThreadContextSwitchRate">
    <setting name="enabled" control="compiler-
enabled">true</setting>
    <setting name="period">10 s</setting>
  </event>

  <event name="jdk.CPULoad">
    <setting name="enabled">true</setting>
    <setting name="period">1000 ms</setting>
  </event>

  <event name="jdk.ThreadCPULoad">
    <setting name="enabled">true</setting>
    <setting name="period">10 s</setting>
  </event>

  <event name="jdk.CPUTimeStampCounter">
    <setting name="enabled">true</setting>
    <setting name="period">beginChunk</setting>
  </event>

  <event name="jdk.SystemProcess">
    <setting name="enabled">true</setting>
    <setting name="period">endChunk</setting>
  </event>

  <event name="jdk.NetworkUtilization">
    <setting name="enabled">true</setting>
    <setting name="period">5 s</setting>
  </event>

  <event name="jdk.InitialEnvironmentVariable">
    <setting name="enabled">true</setting>
    <setting name="period">beginChunk</setting>
  </event>

  <event name="jdk.PhysicalMemory">
    <setting name="enabled">true</setting>
    <setting name="period">everyChunk</setting>
  </event>

  <event name="jdk.ObjectAllocationInNewTLAB">
    <setting name="enabled" control="memory-profiling-enabled-
medium">false</setting>
    <setting name="stackTrace">true</setting>
  </event>

  <event name="jdk.ObjectAllocationOutsideTLAB">
    <setting name="enabled" control="memory-profiling-enabled-
medium">false</setting>
    <setting name="stackTrace">true</setting>
  </event>

  <event name="jdk.NativeLibrary">
    <setting name="enabled">true</setting>
    <setting name="period">everyChunk</setting>
  </event>

  <event name="jdk.ModuleRequire">
    <setting name="enabled">true</setting>
    <setting name="period">endChunk</setting>
  </event>

  <event name="jdk.ModuleExport">
    <setting name="enabled">true</setting>
    <setting name="period">endChunk</setting>
  </event>

  <event name="jdk.FileForce">
    <setting name="enabled">true</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold" control="file-io-threshold">20
ms</setting>
  </event>

  <event name="jdk.FileRead">
    <setting name="enabled">true</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold" control="file-io-threshold">20
ms</setting>
  </event>

  <event name="jdk.FileWrite">
    <setting name="enabled">true</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold" control="file-io-threshold">20
ms</setting>
  </event>

  <event name="jdk.SocketRead">
    <setting name="enabled">true</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold" control="socket-io-threshold">20
ms</setting>
  </event>

  <event name="jdk.SocketWrite">
    <setting name="enabled">true</setting>
    <setting name="stackTrace">true</setting>
    <setting name="threshold" control="socket-io-threshold">20
ms</setting>
  </event>

  <event name="jdk.SecurityPropertyModification">
    <setting name="enabled">false</setting>
    <setting name="stackTrace">true</setting>
  </event>

  <event name="jdk.TLSHandshake">
    <setting name="enabled">false</setting>
    <setting name="stackTrace">true</setting>
  </event>
```

```
    <event name="jdk.X509Validation">
      <setting name="enabled">false</setting>
      <setting name="stackTrace">true</setting>
    </event>

    <event name="jdk.X509Certificate">
      <setting name="enabled">false</setting>
      <setting name="stackTrace">true</setting>
    </event>

    <event name="jdk.JavaExceptionThrow">
      <setting name="enabled" control="enable-
exceptions">false</setting>
      <setting name="stackTrace">true</setting>
    </event>

    <event name="jdk.JavaErrorThrow">
      <setting name="enabled" control="enable-errors">true</setting>
      <setting name="stackTrace">true</setting>
    </event>

    <event name="jdk.ExceptionStatistics">
      <setting name="enabled">true</setting>
      <setting name="period">1000 ms</setting>
    </event>

    <event name="jdk.ActiveRecording">
      <setting name="enabled">true</setting>
    </event>

    <event name="jdk.ActiveSetting">
      <setting name="enabled">true</setting>
    </event>

    <event name="jdk.DataLoss">
      <setting name="enabled">true</setting>
    </event>

    <event name="jdk.DumpReason">
      <setting name="enabled">true</setting>
    </event>

    <event name="jdk.ZPageAllocation">
      <setting name="enabled">true</setting>
      <setting name="threshold">10 ms</setting>
    </event>

    <event name="jdk.ZThreadPhase">
      <setting name="enabled">true</setting>
      <setting name="threshold">0 ms</setting>
    </event>

    <event name="jdk.ZStatisticsCounter">
      <setting name="enabled">true</setting>
      <setting name="threshold">10 ms</setting>
    </event>

    <event name="jdk.ZStatisticsSampler">
      <setting name="enabled">true</setting>
      <setting name="threshold">10 ms</setting>
    </event>

    <!--
      Contents of the control element is not read by the JVM, it's used
      by Java Mission Control to change settings that carry the control
attribute.
    -->
    <control>
      <selection name="gc-level" default="detailed" label="Garbage
Collector">
        <option label="Off" name="off">off</option>
        <option label="Normal" name="detailed">normal</option>
        <option label="All" name="all">all</option>
      </selection>

      <condition name="gc-enabled-normal" true="true" false="false">
        <or>
          <test name="gc-level" operator="equal" value="normal"/>
          <test name="gc-level" operator="equal" value="all"/>
        </or>
      </condition>

      <condition name="gc-enabled-all" true="true" false="false">
        <test name="gc-level" operator="equal" value="all"/>
      </condition>

      <selection name="memory-profiling" default="off" label="Memory
Profiling">
        <option label="Off" name="off">off</option>
        <option label="Object Allocation and Promotion"
name="medium">medium</option>
        <option label="All, including Heap Statistics (May cause long full
GCs)" name="all">all</option>
      </selection>

      <condition name="memory-profiling-enabled-medium" true="true"
false="false">
        <or>
          <test name="memory-profiling" operator="equal"
value="medium"/>
          <test name="memory-profiling" operator="equal" value="all"/>
        </or>
      </condition>

      <condition name="memory-profiling-enabled-all" true="true"
false="false">
        <test name="memory-profiling" operator="equal" value="all"/>
      </condition>

      <selection name="compiler-level" default="normal"
```

```
label="Compiler">
      <option label="Off" name="off">off</option>
      <option label="Normal" name="normal">normal</option>
      <option label="Detailed" name="detailed">detailed</option>
      <option label="All" name="all">all</option>
    </selection>

    <condition name="compiler-enabled" true="false" false="true">
      <test name="compiler-level" operator="equal" value="off"/>
    </condition>

    <condition name="compiler-enabled-failure" true="true"
false="false">
      <or>
        <test name="compiler-level" operator="equal" value="detailed"/>
        <test name="compiler-level" operator="equal" value="all"/>
      </or>
    </condition>

    <condition name="compiler-sweeper-threshold" true="0 ms"
false="100 ms">
      <test name="compiler-level" operator="equal" value="all"/>
    </condition>

    <condition name="compiler-compilation-threshold" true="1000
ms">
      <test name="compiler-level" operator="equal" value="normal"/>
    </condition>

    <condition name="compiler-compilation-threshold" true="100 ms">
      <test name="compiler-level" operator="equal" value="detailed"/>
    </condition>

    <condition name="compiler-compilation-threshold" true="0 ms">
      <test name="compiler-level" operator="equal" value="all"/>
    </condition>

    <condition name="compiler-phase-threshold" true="60 s">
      <test name="compiler-level" operator="equal" value="normal"/>
    </condition>

    <condition name="compiler-phase-threshold" true="10 s">
      <test name="compiler-level" operator="equal" value="detailed"/>
    </condition>

    <condition name="compiler-phase-threshold" true="0 s">
      <test name="compiler-level" operator="equal" value="all"/>
    </condition>

    <selection name="method-sampling-interval" default="normal"
label="Method Sampling">
      <option label="Off" name="off">off</option>
      <option label="Normal" name="normal">normal</option>
      <option label="High" name="high">high</option>
      <option label="Ludicrous (High Overhead)"
name="ludicrous">ludicrous</option>
    </selection>

    <condition name="method-sampling-java-interval" true="999 d">
      <test name="method-sampling-interval" operator="equal"
value="off"/>
    </condition>

    <condition name="method-sampling-java-interval" true="20 ms">
      <test name="method-sampling-interval" operator="equal"
value="normal"/>
    </condition>

    <condition name="method-sampling-java-interval" true="10 ms">
      <test name="method-sampling-interval" operator="equal"
value="high"/>
    </condition>

    <condition name="method-sampling-java-interval" true="1 ms">
      <test name="method-sampling-interval" operator="equal"
value="ludicrous"/>
    </condition>

    <condition name="method-sampling-native-interval" true="999 d">
      <test name="method-sampling-interval" operator="equal"
value="off"/>
    </condition>

    <condition name="method-sampling-native-interval" true="20 ms">
      <or>
        <test name="method-sampling-interval" operator="equal"
value="normal"/>
        <test name="method-sampling-interval" operator="equal"
value="high"/>
        <test name="method-sampling-interval" operator="equal"
value="ludicrous"/>
      </or>
    </condition>

    <condition name="method-sampling-enabled" true="false"
false="true">
      <test name="method-sampling-interval" operator="equal"
value="off"/>
    </condition>

    <selection name="thread-dump-interval" default="normal"
label="Thread Dump">
      <option label="Off" name="off">999 d</option>
      <option label="At least Once"
name="normal">everyChunk</option>
      <option label="Every 60 s" name="everyMinute">60 s</option>
      <option label="Every 10 s" name="everyTenSecond">10
s</option>
      <option label="Every 1 s" name="everySecond">1 s</option>
    </selection>

    <condition name="thread-dump-enabled" true="false" false="true">
      <test name="thread-dump-interval" operator="equal" value="999
d"/>
    </condition>

    <selection name="exception-level" default="errors"
label="Exceptions">
      <option label="Off" name="off">off</option>
      <option label="Errors Only" name="errors">errors</option>
      <option label="All Exceptions, including Errors"
name="all">all</option>
    </selection>

    <condition name="enable-errors" true="true" false="false">
      <or>
        <test name="exception-level" operator="equal" value="errors"/>
        <test name="exception-level" operator="equal" value="all"/>
      </or>
    </condition>

    <condition name="enable-exceptions" true="true" false="false">
      <test name="exception-level" operator="equal" value="all"/>
    </condition>

    <selection name="memory-leak-detection" default="minimal"
label="Memory Leak Detection">
      <option label="Off" name="off">off</option>
```

```
        <option label="Object Types" name="minimal">minimal</option>
        <option label="Object Types + Allocation Stack Traces"
name="medium">medium</option>
        <option label="Object Types + Allocation Stack Traces + Path to
GC Root" name="full">full</option>
      </selection>

      <condition name="memory-leak-detection-enabled" true="false"
false="true">
        <test name="memory-leak-detection" operator="equal"
value="off"/>
      </condition>

      <condition name="memory-leak-detection-stack-trace" true="true"
false="false">
        <or>
          <test name="memory-leak-detection" operator="equal"
value="medium"/>
          <test name="memory-leak-detection" operator="equal"
value="full"/>
        </or>
      </condition>

      <condition name="memory-leak-detection-cutoff" true="1 h"
false="0 ns">
        <test name="memory-leak-detection" operator="equal"
value="full"/>
      </condition>

      <text name="synchronization-threshold" label="Synchronization
Threshold" contentType="timespan" minimum="0 s">20 ms</text>

      <text name="file-io-threshold" label="File I/O Threshold"
contentType="timespan" minimum="0 s">20 ms</text>

      <text name="socket-io-threshold" label="Socket I/O Threshold"
contentType="timespan" minimum="0 s">20 ms</text>

      <flag name="class-loading-enabled" label="Class
Loading">false</flag>

    </control>

</configuration>
, description=Low overhead configuration safe for continuous use in
production environments, typically less than 1 % overhead.,
label=Continuous, name=default, provider=Oracle,
settings=[{key=jdk.ThreadAllocationStatistics#enabled, value=true},
{key=jdk.ThreadAllocationStatistics#period, value=everyChunk},
{key=jdk.ClassLoadingStatistics#enabled, value=true},
{key=jdk.ClassLoadingStatistics#period, value=1000 ms},
{key=jdk.ClassLoaderStatistics#enabled, value=true},
{key=jdk.ClassLoaderStatistics#period, value=everyChunk},
{key=jdk.JavaThreadStatistics#enabled, value=true},
{key=jdk.JavaThreadStatistics#period, value=1000 ms},
{key=jdk.ThreadStart#enabled, value=true},
{key=jdk.ThreadEnd#enabled, value=true},
{key=jdk.ThreadSleep#enabled, value=true},
{key=jdk.ThreadSleep#stackTrace, value=true},
{key=jdk.ThreadSleep#threshold, value=20 ms},
{key=jdk.ThreadPark#enabled, value=true},
{key=jdk.ThreadPark#stackTrace, value=true},
{key=jdk.ThreadPark#threshold, value=20 ms},
{key=jdk.JavaMonitorEnter#enabled, value=true},
{key=jdk.JavaMonitorEnter#stackTrace, value=true},
{key=jdk.JavaMonitorEnter#threshold, value=20 ms},
{key=jdk.JavaMonitorWait#enabled, value=true},
{key=jdk.JavaMonitorWait#stackTrace, value=true},
{key=jdk.JavaMonitorWait#threshold, value=20 ms},
{key=jdk.JavaMonitorInflate#enabled, value=false},
{key=jdk.JavaMonitorInflate#stackTrace, value=true},
{key=jdk.JavaMonitorInflate#threshold, value=20 ms},
{key=jdk.BiasedLockRevocation#enabled, value=true},
{key=jdk.BiasedLockRevocation#stackTrace, value=true},
{key=jdk.BiasedLockRevocation#threshold, value=0 ms},
{key=jdk.BiasedLockSelfRevocation#enabled, value=true},
{key=jdk.BiasedLockSelfRevocation#stackTrace, value=true},
{key=jdk.BiasedLockSelfRevocation#threshold, value=0 ms},
{key=jdk.BiasedLockClassRevocation#enabled, value=true},
{key=jdk.BiasedLockClassRevocation#stackTrace, value=true},
{key=jdk.BiasedLockClassRevocation#threshold, value=0 ms},
{key=jdk.ReservedStackActivation#enabled, value=true},
{key=jdk.ReservedStackActivation#stackTrace, value=true},
{key=jdk.ClassLoad#enabled, value=false},
{key=jdk.ClassLoad#stackTrace, value=true},
{key=jdk.ClassLoad#threshold, value=0 ms},
{key=jdk.ClassDefine#enabled, value=false},
{key=jdk.ClassDefine#stackTrace, value=true},
{key=jdk.ClassUnload#enabled, value=false},
{key=jdk.JVMInformation#enabled, value=true},
{key=jdk.JVMInformation#period, value=beginChunk},
{key=jdk.InitialSystemProperty#enabled, value=true},
{key=jdk.InitialSystemProperty#period, value=beginChunk},
{key=jdk.ExecutionSample#enabled, value=true},
{key=jdk.ExecutionSample#period, value=20 ms},
{key=jdk.NativeMethodSample#enabled, value=true},
{key=jdk.NativeMethodSample#period, value=20 ms},
{key=jdk.SafepointBegin#enabled, value=true},
{key=jdk.SafepointBegin#threshold, value=10 ms},
{key=jdk.SafepointStateSynchronization#enabled, value=false},
{key=jdk.SafepointStateSynchronization#threshold, value=10 ms},
{key=jdk.SafepointWaitBlocked#enabled, value=false},
{key=jdk.SafepointWaitBlocked#threshold, value=10 ms},
{key=jdk.SafepointCleanup#enabled, value=false},
{key=jdk.SafepointCleanup#threshold, value=10 ms},
{key=jdk.SafepointCleanupTask#enabled, value=false},
{key=jdk.SafepointCleanupTask#threshold, value=10 ms},
{key=jdk.SafepointEnd#enabled, value=false},
{key=jdk.SafepointEnd#threshold, value=10 ms},
{key=jdk.ExecuteVMOperation#enabled, value=true},
{key=jdk.ExecuteVMOperation#threshold, value=10 ms},
{key=jdk.Shutdown#enabled, value=true},
{key=jdk.Shutdown#stackTrace, value=true},
{key=jdk.ThreadDump#enabled, value=true},
{key=jdk.ThreadDump#period, value=everyChunk},
{key=jdk.IntFlag#enabled, value=true}, {key=jdk.IntFlag#period,
value=beginChunk}, {key=jdk.UnsignedIntFlag#enabled, value=true},
{key=jdk.UnsignedIntFlag#period, value=beginChunk},
{key=jdk.LongFlag#enabled, value=true}, {key=jdk.LongFlag#period,
value=beginChunk}, {key=jdk.UnsignedLongFlag#enabled,
value=true}, {key=jdk.UnsignedLongFlag#period, value=beginChunk},
{key=jdk.DoubleFlag#enabled, value=true},
{key=jdk.DoubleFlag#period, value=beginChunk},
{key=jdk.BooleanFlag#enabled, value=true},
{key=jdk.BooleanFlag#period, value=beginChunk},
{key=jdk.StringFlag#enabled, value=true}, {key=jdk.StringFlag#period,
value=beginChunk}, {key=jdk.IntFlagChanged#enabled, value=true},
{key=jdk.UnsignedIntFlagChanged#enabled, value=true},
{key=jdk.LongFlagChanged#enabled, value=true},
{key=jdk.UnsignedLongFlagChanged#enabled, value=true},
{key=jdk.DoubleFlagChanged#enabled, value=true},
{key=jdk.BooleanFlagChanged#enabled, value=true},
{key=jdk.StringFlagChanged#enabled, value=true},
{key=jdk.ObjectCount#enabled, value=false},
{key=jdk.ObjectCount#period, value=everyChunk},
{key=jdk.GCConfiguration#enabled, value=true},
{key=jdk.GCConfiguration#period, value=everyChunk},
{key=jdk.GCHeapConfiguration#enabled, value=true},
```

{key=jdk.GCHeapConfiguration#period, value=beginChunk},
{key=jdk.YoungGenerationConfiguration#enabled, value=true},
{key=jdk.YoungGenerationConfiguration#period, value=beginChunk},
{key=jdk.GCTLABConfiguration#enabled, value=true},
{key=jdk.GCTLABConfiguration#period, value=beginChunk},
{key=jdk.GCSurvivorConfiguration#enabled, value=true},
{key=jdk.GCSurvivorConfiguration#period, value=beginChunk},
{key=jdk.ObjectCountAfterGC#enabled, value=false},
{key=jdk.GCHeapSummary#enabled, value=true},
{key=jdk.PSHeapSummary#enabled, value=true},
{key=jdk.G1HeapSummary#enabled, value=true},
{key=jdk.MetaspaceSummary#enabled, value=true},
{key=jdk.MetaspaceGCThreshold#enabled, value=true},
{key=jdk.MetaspaceAllocationFailure#enabled, value=true},
{key=jdk.MetaspaceAllocationFailure#stackTrace, value=true},
{key=jdk.MetaspaceOOM#enabled, value=true},
{key=jdk.MetaspaceOOM#stackTrace, value=true},
{key=jdk.MetaspaceChunkFreeListSummary#enabled, value=true},
{key=jdk.GarbageCollection#enabled, value=true},
{key=jdk.GarbageCollection#threshold, value=0 ms},
{key=jdk.ParallelOldGarbageCollection#enabled, value=true},
{key=jdk.ParallelOldGarbageCollection#threshold, value=0 ms},
{key=jdk.YoungGarbageCollection#enabled, value=true},
{key=jdk.YoungGarbageCollection#threshold, value=0 ms},
{key=jdk.OldGarbageCollection#enabled, value=true},
{key=jdk.OldGarbageCollection#threshold, value=0 ms},
{key=jdk.G1GarbageCollection#enabled, value=true},
{key=jdk.G1GarbageCollection#threshold, value=0 ms},
{key=jdk.GCPhasePause#enabled, value=true},
{key=jdk.GCPhasePause#threshold, value=0 ms},
{key=jdk.GCPhasePauseLevel1#enabled, value=true},
{key=jdk.GCPhasePauseLevel1#threshold, value=0 ms},
{key=jdk.GCPhasePauseLevel2#enabled, value=true},
{key=jdk.GCPhasePauseLevel2#threshold, value=0 ms},
{key=jdk.GCPhasePauseLevel3#enabled, value=false},
{key=jdk.GCPhasePauseLevel3#threshold, value=0 ms},
{key=jdk.GCPhasePauseLevel4#enabled, value=false},
{key=jdk.GCPhasePauseLevel4#threshold, value=0 ms},
{key=jdk.GCPhaseConcurrent#enabled, value=true},
{key=jdk.GCPhaseConcurrent#threshold, value=0 ms},
{key=jdk.GCReferenceStatistics#enabled, value=true},
{key=jdk.PromotionFailed#enabled, value=true},
{key=jdk.EvacuationFailed#enabled, value=true},
{key=jdk.EvacuationInformation#enabled, value=true},
{key=jdk.G1MMU#enabled, value=true},
{key=jdk.G1EvacuationYoungStatistics#enabled, value=true},
{key=jdk.G1EvacuationOldStatistics#enabled, value=true},
{key=jdk.G1BasicIHOP#enabled, value=true},
{key=jdk.G1AdaptiveIHOP#enabled, value=true},
{key=jdk.PromoteObjectInNewPLAB#enabled, value=false},
{key=jdk.PromoteObjectOutsidePLAB#enabled, value=false},
{key=jdk.ConcurrentModeFailure#enabled, value=true},
{key=jdk.AllocationRequiringGC#enabled, value=false},
{key=jdk.AllocationRequiringGC#stackTrace, value=true},
{key=jdk.TenuringDistribution#enabled, value=true},
{key=jdk.G1HeapRegionInformation#enabled, value=false},
{key=jdk.G1HeapRegionInformation#period, value=everyChunk},
{key=jdk.G1HeapRegionTypeChange#enabled, value=false},
{key=jdk.OldObjectSample#enabled, value=true},
{key=jdk.OldObjectSample#stackTrace, value=false},
{key=jdk.OldObjectSample#cutoff, value=0 ns},
{key=jdk.CompilerConfiguration#enabled, value=true},
{key=jdk.CompilerConfiguration#period, value=beginChunk},
{key=jdk.CompilerStatistics#enabled, value=true},
{key=jdk.CompilerStatistics#period, value=1000 ms},
{key=jdk.Compilation#enabled, value=true},
{key=jdk.Compilation#threshold, value=1000 ms},
{key=jdk.CompilerPhase#enabled, value=true},
{key=jdk.CompilerPhase#threshold, value=60 s},
{key=jdk.CompilationFailure#enabled, value=false},
{key=jdk.CompilerInlining#enabled, value=false},
{key=jdk.CodeSweeperConfiguration#enabled, value=true},
{key=jdk.CodeSweeperConfiguration#period, value=beginChunk},
{key=jdk.CodeSweeperStatistics#enabled, value=true},
{key=jdk.CodeSweeperStatistics#period, value=everyChunk},
{key=jdk.SweepCodeCache#enabled, value=true},
{key=jdk.SweepCodeCache#threshold, value=100 ms},
{key=jdk.CodeCacheConfiguration#enabled, value=true},
{key=jdk.CodeCacheConfiguration#period, value=beginChunk},
{key=jdk.CodeCacheStatistics#enabled, value=true},
{key=jdk.CodeCacheStatistics#period, value=everyChunk},
{key=jdk.CodeCacheFull#enabled, value=true},
{key=jdk.OSInformation#enabled, value=true},
{key=jdk.OSInformation#period, value=beginChunk},
{key=jdk.VirtualizationInformation#enabled, value=true},
{key=jdk.VirtualizationInformation#period, value=beginChunk},
{key=jdk.CPUInformation#enabled, value=true},
{key=jdk.CPUInformation#period, value=beginChunk},
{key=jdk.ThreadContextSwitchRate#enabled, value=true},
{key=jdk.ThreadContextSwitchRate#period, value=10 s},
{key=jdk.CPULoad#enabled, value=true}, {key=jdk.CPULoad#period,
value=1000 ms}, {key=jdk.ThreadCPULoad#enabled, value=true},
{key=jdk.ThreadCPULoad#period, value=10 s},
{key=jdk.CPUTimeStampCounter#enabled, value=true},
{key=jdk.CPUTimeStampCounter#period, value=beginChunk},
{key=jdk.SystemProcess#enabled, value=true},
{key=jdk.SystemProcess#period, value=endChunk},
{key=jdk.NetworkUtilization#enabled, value=true},
{key=jdk.NetworkUtilization#period, value=5 s},
{key=jdk.InitialEnvironmentVariable#enabled, value=true},
{key=jdk.InitialEnvironmentVariable#period, value=beginChunk},
{key=jdk.PhysicalMemory#enabled, value=true},
{key=jdk.PhysicalMemory#period, value=everyChunk},
{key=jdk.ObjectAllocationInNewTLAB#enabled, value=false},
{key=jdk.ObjectAllocationInNewTLAB#stackTrace, value=true},
{key=jdk.ObjectAllocationOutsideTLAB#enabled, value=false},
{key=jdk.ObjectAllocationOutsideTLAB#stackTrace, value=true},
{key=jdk.NativeLibrary#enabled, value=true},
{key=jdk.NativeLibrary#period, value=everyChunk},
{key=jdk.ModuleRequire#enabled, value=true},
{key=jdk.ModuleRequire#period, value=endChunk},
{key=jdk.ModuleExport#enabled, value=true},
{key=jdk.ModuleExport#period, value=endChunk},
{key=jdk.FileForce#enabled, value=true},
{key=jdk.FileForce#stackTrace, value=true},
{key=jdk.FileForce#threshold, value=20 ms},
{key=jdk.FileRead#enabled, value=true},
{key=jdk.FileRead#stackTrace, value=true},
{key=jdk.FileRead#threshold, value=20 ms},
{key=jdk.FileWrite#enabled, value=true},
{key=jdk.FileWrite#stackTrace, value=true},
{key=jdk.FileWrite#threshold, value=20 ms},
{key=jdk.SocketRead#enabled, value=true},
{key=jdk.SocketRead#stackTrace, value=true},
{key=jdk.SocketRead#threshold, value=20 ms},
{key=jdk.SocketWrite#enabled, value=true},
{key=jdk.SocketWrite#stackTrace, value=true},
{key=jdk.SocketWrite#threshold, value=20 ms},
{key=jdk.SecurityPropertyModification#enabled, value=false},
{key=jdk.SecurityPropertyModification#stackTrace, value=true},
{key=jdk.TLSHandshake#enabled, value=false},
{key=jdk.TLSHandshake#stackTrace, value=true},
{key=jdk.X509Validation#enabled, value=false},
{key=jdk.X509Validation#stackTrace, value=true},
{key=jdk.X509Certificate#enabled, value=false},
{key=jdk.X509Certificate#stackTrace, value=true},
{key=jdk.JavaExceptionThrow#enabled, value=false},
{key=jdk.JavaExceptionThrow#stackTrace, value=true},

{key=jdk.JavaErrorThrow#enabled, value=true},
{key=jdk.JavaErrorThrow#stackTrace, value=true},
{key=jdk.ExceptionStatistics#enabled, value=true},
{key=jdk.ExceptionStatistics#period, value=1000 ms},
{key=jdk.ActiveRecording#enabled, value=true},
{key=jdk.ActiveSetting#enabled, value=true},
{key=jdk.DataLoss#enabled, value=true},
{key=jdk.DumpReason#enabled, value=true},
{key=jdk.ZPageAllocation#enabled, value=true},
{key=jdk.ZPageAllocation#threshold, value=10 ms},
{key=jdk.ZThreadPhase#enabled, value=true},
{key=jdk.ZThreadPhase#threshold, value=0 ms},
{key=jdk.ZStatisticsCounter#enabled, value=true},
{key=jdk.ZStatisticsCounter#threshold, value=10 ms},
{key=jdk.ZStatisticsSampler#enabled, value=true},
{key=jdk.ZStatisticsSampler#threshold, value=10 ms}]]]

EventTypes

[{categoryNames=[Java Development Kit, Security], description=Serial numbers from X.509 Certificates forming chain of trust, id=7888, label=X509 Validation, name=jdk.X509Validation, settingDescriptors=[{contentType=jdk.jfr.BooleanFlag, defaultValue=false, description=Record event, label=Enabled, name=enabled, typeName=jdk.settings.Enabled}, {contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record event with duration above or equal to threshold, label=Threshold, name=threshold, typeName=jdk.settings.Threshold}, {contentType=jdk.jfr.BooleanFlag, defaultValue=false, description=Record stack traces, label=Stack Trace, name=stackTrace, typeName=jdk.settings.StackTrace}]}, {categoryNames=[Java Development Kit, Security], description=Details of X.509 Certificate parsed by JDK, id=7886, label=X509 Certificate, name=jdk.X509Certificate, settingDescriptors=[{contentType=jdk.jfr.BooleanFlag, defaultValue=false, description=Record event, label=Enabled, name=enabled, typeName=jdk.settings.Enabled}, {contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record event with duration above or equal to threshold, label=Threshold, name=threshold, typeName=jdk.settings.Threshold}, {contentType=jdk.jfr.BooleanFlag, defaultValue=false, description=Record stack traces, label=Stack Trace, name=stackTrace, typeName=jdk.settings.StackTrace}]}, {categoryNames=[Java Development Kit, Security], description=Parameters used in TLS Handshake, id=7884, label=TLS Handshake, name=jdk.TLSHandshake, settingDescriptors=[{contentType=jdk.jfr.BooleanFlag, defaultValue=false, description=Record event, label=Enabled, name=enabled, typeName=jdk.settings.Enabled}, {contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record event with duration above or equal to threshold, label=Threshold, name=threshold, typeName=jdk.settings.Threshold}, {contentType=jdk.jfr.BooleanFlag, defaultValue=false, description=Record stack traces, label=Stack Trace, name=stackTrace, typeName=jdk.settings.StackTrace}]}, {categoryNames=[Java Development Kit, Security], description=Modification of Security property, id=7882, label=Security Property Modification, name=jdk.SecurityPropertyModification, settingDescriptors=[{contentType=jdk.jfr.BooleanFlag, defaultValue=false, description=Record event, label=Enabled, name=enabled, typeName=jdk.settings.Enabled}, {contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record event with duration above or equal to threshold, label=Threshold, name=threshold, typeName=jdk.settings.Threshold}, {contentType=jdk.jfr.BooleanFlag, defaultValue=false, description=Record stack traces, label=Stack Trace, name=stackTrace, typeName=jdk.settings.StackTrace}]}, {categoryNames=[Flight Recorder], description=null, id=7880, label=Flight Recording, name=jdk.ActiveRecording, settingDescriptors=[{contentType=jdk.jfr.BooleanFlag, defaultValue=false, description=Record event, label=Enabled, name=enabled, typeName=jdk.settings.Enabled}, {contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record event with duration above or equal to threshold, label=Threshold, name=threshold, typeName=jdk.settings.Threshold}, {contentType=jdk.jfr.BooleanFlag, defaultValue=false, description=Record stack traces, label=Stack Trace, name=stackTrace, typeName=jdk.settings.StackTrace}]}, {categoryNames=[Flight Recorder], description=null, id=7878, label=Recording Setting, name=jdk.ActiveSetting, settingDescriptors=[{contentType=jdk.jfr.BooleanFlag, defaultValue=false, description=Record event, label=Enabled, name=enabled, typeName=jdk.settings.Enabled}, {contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record event with duration above or equal to threshold, label=Threshold, name=threshold, typeName=jdk.settings.Threshold}, {contentType=jdk.jfr.BooleanFlag, defaultValue=false, description=Record stack traces, label=Stack Trace, name=stackTrace, typeName=jdk.settings.StackTrace}]}, {categoryNames=[Java Application], description=An object derived from java.lang.Error has been created. OutOfMemoryErrors are ignored, id=7876, label=Java Error, name=jdk.JavaErrorThrow, settingDescriptors=[{contentType=jdk.jfr.BooleanFlag, defaultValue=false, description=Record event, label=Enabled, name=enabled, typeName=jdk.settings.Enabled}, {contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record event with duration above or equal to threshold, label=Threshold, name=threshold, typeName=jdk.settings.Threshold}, {contentType=jdk.jfr.BooleanFlag, defaultValue=false, description=Record stack traces, label=Stack Trace, name=stackTrace, typeName=jdk.settings.StackTrace}]}, {categoryNames=[Java Application, Statistics], description=Number of objects derived from java.lang.Throwable that have been created, id=7874, label=Exception Statistics, name=jdk.ExceptionStatistics, settingDescriptors=[{contentType=jdk.jfr.BooleanFlag, defaultValue=false, description=Record event, label=Enabled, name=enabled, typeName=jdk.settings.Enabled}, {contentType=null, defaultValue=everyChunk, description=Record event at interval, label=Period, name=period, typeName=jdk.settings.Period}]}, {categoryNames=[Java Application], description=An object derived from java.lang.Exception has been created, id=7872, label=Java Exception, name=jdk.JavaExceptionThrow, settingDescriptors=[{contentType=jdk.jfr.BooleanFlag, defaultValue=false, description=Record event, label=Enabled, name=enabled, typeName=jdk.settings.Enabled}, {contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record event with duration above or equal to threshold, label=Threshold, name=threshold, typeName=jdk.settings.Threshold}, {contentType=jdk.jfr.BooleanFlag, defaultValue=false, description=Record stack traces, label=Stack Trace, name=stackTrace, typeName=jdk.settings.StackTrace}]}, {categoryNames=[Java Application], description=Writing data to a socket, id=7870, label=Socket Write, name=jdk.SocketWrite, settingDescriptors=[{contentType=jdk.jfr.BooleanFlag, defaultValue=false, description=Record event, label=Enabled, name=enabled, typeName=jdk.settings.Enabled}, {contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record event with duration above or equal to threshold, label=Threshold, name=threshold, typeName=jdk.settings.Threshold}, {contentType=jdk.jfr.BooleanFlag, defaultValue=false, description=Record stack traces, label=Stack Trace, name=stackTrace, typeName=jdk.settings.StackTrace}]}, {categoryNames=[Java Application], description=Reading data from a socket, id=7868, label=Socket Read, name=jdk.SocketRead, settingDescriptors=[{contentType=jdk.jfr.BooleanFlag, defaultValue=false, description=Record event, label=Enabled, name=enabled, typeName=jdk.settings.Enabled}, {contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record event with duration above or equal to threshold, label=Threshold, name=threshold, typeName=jdk.settings.Threshold}, {contentType=jdk.jfr.BooleanFlag, defaultValue=false, description=Record stack traces, label=Stack Trace, name=stackTrace, typeName=jdk.settings.StackTrace}]}, {categoryNames=[Java Application], description=Writing data to a file, id=7866, label=File Write, name=jdk.FileWrite, settingDescriptors=[{contentType=jdk.jfr.BooleanFlag, defaultValue=false, description=Record event, label=Enabled, name=enabled, typeName=jdk.settings.Enabled}, {contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record event with duration above or equal to threshold, label=Threshold, name=threshold, typeName=jdk.settings.Threshold}, {contentType=jdk.jfr.BooleanFlag, defaultValue=false, description=Record stack traces, label=Stack Trace, name=stackTrace, typeName=jdk.settings.StackTrace}]}, {categoryNames=[Java Application], description=Reading data from a file, id=7864, label=File Read, name=jdk.FileRead, settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,

defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold},
{contentType=jdk.jfr.BooleanFlag, defaultValue=false,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}]},
{categoryNames=[Java Application], description=Force updates to be
written to file, id=7862, label=File Force, name=jdk.FileForce,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold},
{contentType=jdk.jfr.BooleanFlag, defaultValue=false,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}]},
{categoryNames=[Java Application], description=null, id=255,
label=Java Thread Start, name=jdk.ThreadStart,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}]},
{categoryNames=[Java Application], description=null, id=256,
label=Java Thread End, name=jdk.ThreadEnd,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}]},
{categoryNames=[Java Application], description=null, id=257,
label=Java Thread Sleep, name=jdk.ThreadSleep,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold},
{contentType=jdk.jfr.BooleanFlag, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}]},
{categoryNames=[Java Application], description=null, id=258,
label=Java Thread Park, name=jdk.ThreadPark,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold},
{contentType=jdk.jfr.BooleanFlag, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}]},
{categoryNames=[Java Application], description=null, id=259,
label=Java Monitor Blocked, name=jdk.JavaMonitorEnter,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold},
{contentType=jdk.jfr.BooleanFlag, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}]},
{categoryNames=[Java Application], description=Waiting on a Java
monitor, id=260, label=Java Monitor Wait, name=jdk.JavaMonitorWait,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold},
{contentType=jdk.jfr.BooleanFlag, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}]},
{categoryNames=[Java Application], description=null, id=261,
label=Java Monitor Inflated, name=jdk.JavaMonitorInflate,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold},
{contentType=jdk.jfr.BooleanFlag, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}]},
{categoryNames=[Java Virtual Machine, Runtime],
description=Revoked bias of object, id=262, label=Biased Lock
Revocation, name=jdk.BiasedLockRevocation,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold},
{contentType=jdk.jfr.BooleanFlag, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}]},
{categoryNames=[Java Virtual Machine, Runtime],
description=Revoked bias of object biased towards own thread,
id=263, label=Biased Lock Self Revocation,
name=jdk.BiasedLockSelfRevocation,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold},
{contentType=jdk.jfr.BooleanFlag, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}]},
{categoryNames=[Java Virtual Machine, Runtime],
description=Revoked biases for all instances of a class, id=264,
label=Biased Lock Class Revocation,
name=jdk.BiasedLockClassRevocation,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold},
{contentType=jdk.jfr.BooleanFlag, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}]},
{categoryNames=[Java Virtual Machine, Runtime],
description=Activation of Reserved Stack Area caused by stack
overflow with ReservedStackAccess annotated method in call stack,
id=265, label=Reserved Stack Activation,
name=jdk.ReservedStackActivation,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.BooleanFlag, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}]},
{categoryNames=[Java Virtual Machine, Class Loading],
description=null, id=266, label=Class Load, name=jdk.ClassLoad,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},

{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold},
{contentType=jdk.jfr.BooleanFlag, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}]},
{categoryNames=[Java Virtual Machine, Class Loading],
description=null, id=267, label=Class Define, name=jdk.ClassDefine,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.BooleanFlag, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}]},
{categoryNames=[Java Virtual Machine, Class Loading],
description=null, id=268, label=Class Unload, name=jdk.ClassUnload,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}]},
{categoryNames=[Java Virtual Machine, Flag], description=null,
id=269, label=Int Flag Changed, name=jdk.IntFlagChanged,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}]},
{categoryNames=[Java Virtual Machine, Flag], description=null,
id=270, label=Unsigned Int Flag Changed,
name=jdk.UnsignedIntFlagChanged,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}]},
{categoryNames=[Java Virtual Machine, Flag], description=null,
id=271, label=Long Flag Changed, name=jdk.LongFlagChanged,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}]},
{categoryNames=[Java Virtual Machine, Flag], description=null,
id=272, label=Unsigned Long Flag Changed,
name=jdk.UnsignedLongFlagChanged,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}]},
{categoryNames=[Java Virtual Machine, Flag], description=null,
id=273, label=Double Flag Changed, name=jdk.DoubleFlagChanged,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}]},
{categoryNames=[Java Virtual Machine, Flag], description=null,
id=274, label=Boolean Flag Changed,
name=jdk.BooleanFlagChanged,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}]},
{categoryNames=[Java Virtual Machine, Flag], description=null,
id=275, label=String Flag Changed, name=jdk.StringFlagChanged,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}]},
{categoryNames=[Java Virtual Machine, GC, Heap], description=null,
id=278, label=Heap Summary, name=jdk.GCHeapSummary,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}]},
{categoryNames=[Java Virtual Machine, GC, Heap], description=null,
id=280, label=Metaspace Summary, name=jdk.MetaspaceSummary,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}]},
{categoryNames=[Java Virtual Machine, GC, Metaspace],
description=null, id=281, label=Metaspace GC Threshold,
name=jdk.MetaspaceGCThreshold,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}]},
{categoryNames=[Java Virtual Machine, GC, Metaspace],
description=null, id=282, label=Metaspace Allocation Failure,
name=jdk.MetaspaceAllocationFailure,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.BooleanFlag, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}]},
{categoryNames=[Java Virtual Machine, GC, Metaspace],
description=null, id=283, label=Metaspace Out of Memory,
name=jdk.MetaspaceOOM,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.BooleanFlag, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}]},
{categoryNames=[Java Virtual Machine, GC, Metaspace],
description=null, id=284, label=Metaspace Chunk Free List Summary,
name=jdk.MetaspaceChunkFreeListSummary,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}]},
{categoryNames=[Java Virtual Machine, GC, Heap], description=null,
id=285, label=Parallel Scavenge Heap Summary,
name=jdk.PSHeapSummary,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}]},
{categoryNames=[Java Virtual Machine, GC, Heap], description=null,
id=286, label=G1 Heap Summary, name=jdk.G1HeapSummary,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}]},
{categoryNames=[Java Virtual Machine, GC, Collector],
description=Garbage collection performed by the JVM, id=287,
label=Garbage Collection, name=jdk.GarbageCollection,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}]},
{categoryNames=[Java Virtual Machine, GC, Collector],
description=Extra information specific to Parallel Old Garbage
Collections, id=288, label=Parallel Old Garbage Collection,
name=jdk.ParallelOldGarbageCollection,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}]},
{categoryNames=[Java Virtual Machine, GC, Collector],
description=Extra information specific to Young Garbage Collections,
id=289, label=Young Garbage Collection,
name=jdk.YoungGarbageCollection,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}]},
{categoryNames=[Java Virtual Machine, GC, Collector],

description=Extra information specific to Old Garbage Collections,
id=290, label=Old Garbage Collection,
name=jdk.OldGarbageCollection,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}]},
{categoryNames=[Java Virtual Machine, GC, Collector],
description=Extra information specific to G1 Garbage Collections,
id=291, label=G1 Garbage Collection,
name=jdk.G1GarbageCollection,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}]},
{categoryNames=[Java Virtual Machine, GC, Detailed],
description=null, id=292, label=G1 MMU Information,
name=jdk.G1MMU,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}]},
{categoryNames=[Java Virtual Machine, GC, Detailed],
description=null, id=293, label=Evacuation Information,
name=jdk.EvacuationInformation,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}]},
{categoryNames=[Java Virtual Machine, GC, Reference],
description=Total count of processed references during GC, id=294,
label=GC Reference Statistics, name=jdk.GCReferenceStatistics,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}]},
{categoryNames=[Java Virtual Machine, GC, Detailed],
description=null, id=296, label=Object Count after GC,
name=jdk.ObjectCountAfterGC,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}]},
{categoryNames=[Java Virtual Machine, GC, Detailed],
description=Memory related evacuation statistics during GC for the
young generation, id=298, label=G1 Evacuation Statistics for Young,
name=jdk.G1EvacuationYoungStatistics,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}]},
{categoryNames=[Java Virtual Machine, GC, Detailed],
description=Memory related evacuation statistics during GC for the old
generation, id=299, label=G1 Evacuation Memory Statistics for Old,
name=jdk.G1EvacuationOldStatistics,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}]},
{categoryNames=[Java Virtual Machine, GC, Detailed],
description=Basic statistics related to current IHOP calculation, id=300,
label=G1 Basic IHOP Statistics, name=jdk.G1BasicIHOP,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}]},
{categoryNames=[Java Virtual Machine, GC, Detailed],
description=Statistics related to current adaptive IHOP calculation,
id=301, label=G1 Adaptive IHOP Statistics,
name=jdk.G1AdaptiveIHOP,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}]},
{categoryNames=[Java Virtual Machine, GC, Detailed],
description=Object survived scavenge and was copied to a new
Promotion Local Allocation Buffer (PLAB). Supported GCs are Parallel
Scavange, G1 and CMS with Parallel New. Due to promotion being
done in parallel an object might be reported multiple times as the GC
threads race to copy all objects., id=302, label=Promotion in new
PLAB, name=jdk.PromoteObjectInNewPLAB,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}]},
{categoryNames=[Java Virtual Machine, GC, Detailed],
description=Object survived scavenge and was copied directly to the
heap. Supported GCs are Parallel Scavange, G1 and CMS with
Parallel New. Due to promotion being done in parallel an object might
be reported multiple times as the GC threads race to copy all objects.,
id=303, label=Promotion outside PLAB,
name=jdk.PromoteObjectOutsidePLAB,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}]},
{categoryNames=[Java Virtual Machine, GC, Detailed],
description=Promotion of an object failed, id=304, label=Promotion
Failed, name=jdk.PromotionFailed,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}]},
{categoryNames=[Java Virtual Machine, GC, Detailed],
description=Evacuation of an object failed, id=305, label=Evacuation
Failed, name=jdk.EvacuationFailed,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}]},
{categoryNames=[Java Virtual Machine, GC, Detailed],
description=Concurrent Mode failed, id=306, label=Concurrent Mode
Failure, name=jdk.ConcurrentModeFailure,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}]},
{categoryNames=[Java Virtual Machine, GC, Phases],
description=null, id=307, label=GC Phase Pause,
name=jdk.GCPhasePause,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}]},
{categoryNames=[Java Virtual Machine, GC, Phases],
description=null, id=308, label=GC Phase Pause Level 1,
name=jdk.GCPhasePauseLevel1,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}]},
{categoryNames=[Java Virtual Machine, GC, Phases],
description=null, id=309, label=GC Phase Pause Level 2,
name=jdk.GCPhasePauseLevel2,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}]},
{categoryNames=[Java Virtual Machine, GC, Phases],
description=null, id=310, label=GC Phase Pause Level 3,
name=jdk.GCPhasePauseLevel3,

settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}]},
{categoryNames=[Java Virtual Machine, GC, Phases],
description=null, id=311, label=GC Phase Pause Level 4,
name=jdk.GCPhasePauseLevel4,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}]},
{categoryNames=[Java Virtual Machine, GC, Phases],
description=null, id=312, label=GC Phase Concurrent,
name=jdk.GCPhaseConcurrent,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}]},
{categoryNames=[Java Virtual Machine, GC, Detailed],
description=null, id=313, label=Allocation Requiring GC,
name=jdk.AllocationRequiringGC,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.BooleanFlag, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}]},
{categoryNames=[Java Virtual Machine, GC, Detailed],
description=null, id=314, label=Tenuring Distribution,
name=jdk.TenuringDistribution,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}]},
{categoryNames=[Java Virtual Machine, GC, Detailed],
description=Information about a G1 heap region type change, id=315,
label=G1 Heap Region Type Change,
name=jdk.G1HeapRegionTypeChange,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}]},
{categoryNames=[Java Virtual Machine, Compiler], description=null,
id=316, label=Compilation, name=jdk.Compilation,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}]},
{categoryNames=[Java Virtual Machine, Compiler], description=null,
id=317, label=Compiler Phase, name=jdk.CompilerPhase,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}]},
{categoryNames=[Java Virtual Machine, Compiler], description=null,
id=318, label=Compilation Failure, name=jdk.CompilationFailure,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}]},
{categoryNames=[Java Virtual Machine, Compiler, Optimization],
description=null, id=320, label=Method Inlining,
name=jdk.CompilerInlining,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}]},
{categoryNames=[Java Virtual Machine, Code Sweeper],
description=null, id=321, label=Sweep Code Cache,
name=jdk.SweepCodeCache,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}]},
{categoryNames=[Java Virtual Machine, Code Cache],
description=null, id=322, label=Code Cache Full,
name=jdk.CodeCacheFull,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}]},
{categoryNames=[Java Virtual Machine, Runtime, Safepoint],
description=Safepointing begin, id=323, label=Safepoint Begin,
name=jdk.SafepointBegin,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}]},
{categoryNames=[Java Virtual Machine, Runtime, Safepoint],
description=Synchronize run state of threads, id=324, label=Safepoint
State Synchronization, name=jdk.SafepointStateSynchronization,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}]},
{categoryNames=[Java Virtual Machine, Runtime, Safepoint],
description=Safepointing begin waiting on running threads to block,
id=325, label=Safepoint Wait Blocked,
name=jdk.SafepointWaitBlocked,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}]},
{categoryNames=[Java Virtual Machine, Runtime, Safepoint],
description=Safepointing begin running cleanup tasks, id=326,
label=Safepoint Cleanup, name=jdk.SafepointCleanup,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}]},
{categoryNames=[Java Virtual Machine, Runtime, Safepoint],
description=Safepointing begin running cleanup tasks, id=327,
label=Safepoint Cleanup Task, name=jdk.SafepointCleanupTask,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}]},
{categoryNames=[Java Virtual Machine, Runtime, Safepoint],
description=Safepointing end, id=328, label=Safepoint End,
name=jdk.SafepointEnd,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,

defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}]},
{categoryNames=[Java Virtual Machine, Runtime],
description=Execution of a VM Operation, id=329, label=VM
Operation, name=jdk.ExecuteVMOperation,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}]},
{categoryNames=[Java Virtual Machine, Runtime], description=JVM
shutting down, id=330, label=JVM Shutdown, name=jdk.Shutdown,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.BooleanFlag, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}]},
{categoryNames=[Java Application], description=Allocation in new
Thread Local Allocation Buffer, id=331, label=Allocation in new TLAB,
name=jdk.ObjectAllocationInNewTLAB,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.BooleanFlag, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}]},
{categoryNames=[Java Application], description=Allocation outside
Thread Local Allocation Buffers, id=332, label=Allocation outside
TLAB, name=jdk.ObjectAllocationOutsideTLAB,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.BooleanFlag, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}]},
{categoryNames=[Java Virtual Machine, Profiling], description=A
potential memory leak, id=333, label=Old Object Sample,
name=jdk.OldObjectSample,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.BooleanFlag, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace},
{contentType=jdk.jfr.Timespan, defaultValue=infinity, description=Limit
running time of event, label=Cutoff, name=cutoff,
typeName=jdk.settings.Cutoff}]},
{categoryNames=[Flight Recorder], description=Who requested the
recording and why, id=334, label=Recording Reason,
name=jdk.DumpReason,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}]},
{categoryNames=[Flight Recorder], description=Data could not be
copied out from a buffer, typically because of contention, id=335,
label=Data Loss, name=jdk.DataLoss,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}]},
{categoryNames=[Java Virtual Machine], description=Description of
JVM and the Java application, id=336, label=JVM Information,
name=jdk.JVMInformation,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]},
{categoryNames=[Operating System], description=null, id=337,
label=OS Information, name=jdk.OSInformation,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]},
{categoryNames=[Operating System], description=null, id=338,
label=Virtualization Information, name=jdk.VirtualizationInformation,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]},
{categoryNames=[Java Virtual Machine], description=System Property
at JVM start, id=339, label=Initial System Property,
name=jdk.InitialSystemProperty,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]},
{categoryNames=[Operating System], description=null, id=340,
label=Initial Environment Variable,
name=jdk.InitialEnvironmentVariable,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]},
{categoryNames=[Operating System], description=null, id=341,
label=System Process, name=jdk.SystemProcess,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]},
{categoryNames=[Operating System, Processor], description=null,
id=342, label=CPU Information, name=jdk.CPUInformation,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]},
{categoryNames=[Operating System, Processor], description=null,
id=343, label=CPU Time Stamp Counter,
name=jdk.CPUTimeStampCounter,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]},
{categoryNames=[Operating System, Processor], description=OS CPU
Load, id=344, label=CPU Load, name=jdk.CPULoad,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]},
{categoryNames=[Operating System, Processor], description=null,
id=345, label=Thread CPU Load, name=jdk.ThreadCPULoad,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]},

{categoryNames=[Operating System, Processor], description=null,
id=346, label=Thread Context Switch Rate,
name=jdk.ThreadContextSwitchRate,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]},
{categoryNames=[Operating System, Network], description=null,
id=347, label=Network Utilization, name=jdk.NetworkUtilization,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]},
{categoryNames=[Java Application, Statistics], description=null,
id=348, label=Java Thread Statistics, name=jdk.JavaThreadStatistics,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]},
{categoryNames=[Java Application, Statistics], description=null,
id=349, label=Class Loading Statistics,
name=jdk.ClassLoadingStatistics,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]},
{categoryNames=[Java Application, Statistics], description=null,
id=350, label=Class Loader Statistics,
name=jdk.ClassLoaderStatistics,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]},
{categoryNames=[Java Application, Statistics], description=null,
id=351, label=Thread Allocation Statistics,
name=jdk.ThreadAllocationStatistics,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]},
{categoryNames=[Operating System, Memory], description=OS
Physical Memory, id=352, label=Physical Memory,
name=jdk.PhysicalMemory,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]},
{categoryNames=[Java Virtual Machine, Profiling],
description=Snapshot of a threads state, id=353, label=Method
Profiling Sample, name=jdk.ExecutionSample,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]},
{categoryNames=[Java Virtual Machine, Profiling],
description=Snapshot of a threads state when in native, id=354,
label=Method Profiling Sample Native,
name=jdk.NativeMethodSample,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]},
{categoryNames=[Java Virtual Machine, Runtime], description=null,
id=355, label=Thread Dump, name=jdk.ThreadDump,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]},
{categoryNames=[Java Virtual Machine, Runtime], description=null,
id=356, label=Native Library, name=jdk.NativeLibrary,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]},
{categoryNames=[Java Virtual Machine, Runtime, Modules],
description=A directed edge representing a dependency, id=357,
label=Module Require, name=jdk.ModuleRequire,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]},
{categoryNames=[Java Virtual Machine, Runtime, Modules],
description=null, id=358, label=Module Export,
name=jdk.ModuleExport,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]},
{categoryNames=[Java Virtual Machine, Compiler], description=null,
id=359, label=Compiler Statistics, name=jdk.CompilerStatistics,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]},
{categoryNames=[Java Virtual Machine, Compiler], description=null,
id=360, label=Compiler Configuration,
name=jdk.CompilerConfiguration,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]},
{categoryNames=[Java Virtual Machine, Code Cache],
description=null, id=361, label=Code Cache Statistics,
name=jdk.CodeCacheStatistics,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]},
{categoryNames=[Java Virtual Machine, Code Cache],
description=null, id=362, label=Code Cache Configuration,
name=jdk.CodeCacheConfiguration,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]},
{categoryNames=[Java Virtual Machine, Code Sweeper],
description=null, id=363, label=Code Sweeper Statistics,
name=jdk.CodeSweeperStatistics,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,

defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]},
{categoryNames=[Java Virtual Machine, Code Sweeper],
description=null, id=364, label=Code Sweeper Configuration,
name=jdk.CodeSweeperConfiguration,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]},
{categoryNames=[Java Virtual Machine, Flag], description=null,
id=365, label=Int Flag, name=jdk.IntFlag,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]},
{categoryNames=[Java Virtual Machine, Flag], description=null,
id=366, label=Unsigned Int Flag, name=jdk.UnsignedIntFlag,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]},
{categoryNames=[Java Virtual Machine, Flag], description=null,
id=367, label=Long Flag, name=jdk.LongFlag,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]},
{categoryNames=[Java Virtual Machine, Flag], description=null,
id=368, label=Unsigned Long Flag, name=jdk.UnsignedLongFlag,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]},
{categoryNames=[Java Virtual Machine, Flag], description=null,
id=369, label=Double Flag, name=jdk.DoubleFlag,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]},
{categoryNames=[Java Virtual Machine, Flag], description=null,
id=370, label=Boolean Flag, name=jdk.BooleanFlag,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]},
{categoryNames=[Java Virtual Machine, Flag], description=null,
id=371, label=String Flag, name=jdk.StringFlag,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]},
{categoryNames=[Java Virtual Machine, GC, Detailed],
description=null, id=372, label=Object Count, name=jdk.ObjectCount,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]},
{categoryNames=[Java Virtual Machine, GC, Detailed],
description=Information about a specific heap region in the G1 GC,
id=373, label=G1 Heap Region Information,
name=jdk.G1HeapRegionInformation,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]},
{categoryNames=[Java Virtual Machine, GC, Configuration],
description=The configuration of the garbage collector, id=374,
label=GC Configuration, name=jdk.GCConfiguration,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]},
{categoryNames=[Java Virtual Machine, GC, Configuration],
description=The configuration of the survivors of garbage collection,
id=375, label=GC Survivor Configuration,
name=jdk.GCSurvivorConfiguration,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]},
{categoryNames=[Java Virtual Machine, GC, Configuration],
description=The configuration of the Thread Local Allocation Buffers
(TLABs), id=376, label=TLAB Configuration,
name=jdk.GCTLABConfiguration,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]},
{categoryNames=[Java Virtual Machine, GC, Configuration],
description=The configuration of the garbage collected heap, id=377,
label=GC Heap Configuration, name=jdk.GCHeapConfiguration,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]},
{categoryNames=[Java Virtual Machine, GC, Configuration],
description=The configuration of the young generation of the garbage
collected heap, id=378, label=Young Generation Configuration,
name=jdk.YoungGenerationConfiguration,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]},
{categoryNames=[Java Virtual Machine, GC, Detailed],
description=Allocation of a ZPage, id=379, label=ZPage Allocation,
name=jdk.ZPageAllocation,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}]},
{categoryNames=[Java Virtual Machine, GC, Detailed],
description=null, id=380, label=ZGC Thread Phase,
name=jdk.ZThreadPhase,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}]},
{categoryNames=[Java Virtual Machine, GC, Detailed],
description=null, id=381, label=Z Statistics Counter,

	name=jdk.ZStatisticsCounter, settingDescriptors=[{contentType=jdk.jfr.BooleanFlag, defaultValue=false, description=Record event, label=Enabled, name=enabled, typeName=jdk.settings.Enabled}, {contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record event with duration above or equal to threshold, label=Threshold, name=threshold, typeName=jdk.settings.Threshold}]}, {categoryNames=[Java Virtual Machine, GC, Detailed], description=null, id=382, label=Z Statistics Sampler, name=jdk.ZStatisticsSampler, settingDescriptors=[{contentType=jdk.jfr.BooleanFlag, defaultValue=false, description=Record event, label=Enabled, name=enabled, typeName=jdk.settings.Enabled}, {contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record event with duration above or equal to threshold, label=Threshold, name=threshold, typeName=jdk.settings.Threshold}]}]
ObjectName	jdk.management.jfr:type=FlightRecorder
Recordings	[]