

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net



## Catalina

### Connector

#### port=80

(Implementation of a Coyote connector)		
URIEncoding	UTF-8	(Character encoding used to decode the URI)
acceptCount	100	(The accept count for this Connector)
address	null	(The IP address on which to bind)
ajpFlush	null	(Send AJP flush package for each explicit flush)
allowTrace	false	(Allow disabling TRACE method)
allowedRequestAttributesPattern	null	(Regular expression that any custom request attributes must match else the request will be rejected)
ciphers	HIGH::aNULL::eNULL::EXPORT::DES::RC4::MD5::RSA	(Comma-separated list of requested cipher suites)
ciphersUsed	null	(Array of ciphers suites in use)
className	null	(Fully qualified class name of the managed object)
connectionLinger	-1	(Linger value on the incoming connection)
connectionTimeout	20 000	(Timeout value on the incoming connection)
enableLookups	false	(The 'enable DNS lookups' flag for this Connector)
executorName	Internal	(The name of the executor - if any - associated with this Connector)
keepAliveTimeout	20 000	(The number of milliseconds Tomcat will wait for a subsequent request before closing the connection)
localPort	80	(The port number on which this connector is listening to requests. If the special value for port of zero is used then this method will report the actual port bound.)
maxHeaderCount	100	(The maximum number of headers that are allowed by the container. 100 by default. A value of less than 0 means no limit.)
maxKeepAliveRequests	100	(Maximum number of Keep-Alive requests to honor per connection)
maxParameterCount	1 000	(The maximum number of parameters (GET plus POST) which will be automatically parsed by the container. 10000 by default. A value of less than 0 means no limit.)
maxPostSize	2 097 152	(Maximum size in bytes of a POST which will be handled by the servlet API provided features)
maxSavePostSize	4 096	(Maximum size of a POST which will be saved by the container during authentication)
maxSwallowSize	2 097 152	(The maximum number of request body bytes to be swallowed by Tomcat for an aborted upload)
maxThreads	200	(The maximum number of request processing threads to be created for the Internal Executor. -1 indicates an external Executor is being used.)
minSpareThreads	10	(The number of request processing threads that will be created for the internal Executor. -1 indicates an external Executor is being used.)
modelerType	null	(Type of the modeled resource. Can be set only once)
packetSize	null	(The ajp packet size.)
port	80	(The port number (excluding any offset) on which this connector is configured to listen for requests. The special value of 0 means select a random free port when the socket is bound.)
portOffset	0	(The offset that will be applied to port to determine the actual port number used.)
portWithOffset	80	(The actual port number (including any offset) on which this connector is configured to listen for requests.)
processorCache	200	(The processor cache size.)
protocol	HTTP/1.1	(Coyote protocol handler in use)
protocolHandlerClassName	org.apache.coyote.http11.Http11NioProtocol	(Coyote Protocol handler class name)
proxyName	null	(The Server name to which we should pretend requests to this Connector)
proxyPort	0	(The Server port to which we should pretend requests to this Connector)
redirectPort	443	(The redirect port (excluding any offset) for non-SSL to SSL redirects)
redirectPortWithOffset	443	(The actual redirect port (including any offset) for non-SSL to SSL redirects.)
scheme	http	(Protocol name for this Connector (http, https))
secretRequired	null	(Must secret be set to a non-null, non-zero-length String?)
secure	false	(Is this a secure (SSL) Connector?)
sslProtocols	null	(Comma-separated list of SSL protocol variants to be enabled)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
tcpNoDelay	true	(Should we use TCP no delay?)
threadPriority	5	(The thread priority for processors using the internal Executor. -1 indicates an external Executor is being used.)
useBodyEncodingForURI	false	(Should the body encoding be used for URI query parameters)
useIPVHosts	false	(Should IP-based virtual hosting be used?)
xpoweredBy	false	(Is generation of X-Powered-By response header enabled/disabled?)

## DataSource

### host=localhost,context=/demo,class=javax.sql.DataSource,name="jdbc/demo\_javamelody"

abandonedUsageTracking	false	(Introspected attribute abandonedUsageTracking)
accessToUnderlyingConnectionAllowed	false	(Introspected attribute accessToUnderlyingConnectionAllowed)
autoCommitOnReturn	true	(Introspected attribute autoCommitOnReturn)
cacheState	true	(Introspected attribute cacheState)
closed	false	(Introspected attribute closed)
connectionFactoryClassName	null	(Introspected attribute connectionFactoryClassName)
connectionInitSqlsAsArray	[]	(Introspected attribute connectionInitSqlsAsArray)
defaultAutoCommit	null	(Introspected attribute defaultAutoCommit)
defaultCatalog	null	(Introspected attribute defaultCatalog)
defaultQueryTimeout	null	(Introspected attribute defaultQueryTimeout)
defaultReadOnly	null	(Introspected attribute defaultReadOnly)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

defaultSchema	null	(Introspected attribute defaultSchema)
defaultTransactionIsolation	-1	(Introspected attribute defaultTransactionIsolation)
disconnectionSqlCodesAsArray	[]	(Introspected attribute disconnectionSqlCodesAsArray)
driverClassName	org.h2.Driver	(Introspected attribute driverClassName)
enableAutoCommitOnReturn	true	(Introspected attribute enableAutoCommitOnReturn)
evictionPolicyClassName	org.apache.tomcat.dbcp.pool2.impl.DefaultEvictionPolicy	(Introspected attribute evictionPolicyClassName)
fastFailValidation	false	(Introspected attribute fastFailValidation)
initialSize	0	(Introspected attribute initialSize)
jmxName	Catalina:type=DataSource,host=localhost,context=/demo,class=javax.sql.DataSource,name="jdbc/demo_javamelody"	(Introspected attribute jmxName)
lifo	true	(Introspected attribute lifo)
logAbandoned	false	(Introspected attribute logAbandoned)
logExpiredConnections	true	(Introspected attribute logExpiredConnections)
maxConnLifetimeMillis	-1	(Introspected attribute maxConnLifetimeMillis)
maxIdle	10	(Introspected attribute maxIdle)
maxOpenPreparedStatements	-1	(Introspected attribute maxOpenPreparedStatements)
maxTotal	100	(Introspected attribute maxTotal)
maxWaitMillis	30 000	(Introspected attribute maxWaitMillis)
minEvictableIdleTimeMillis	1 800 000	(Introspected attribute minEvictableIdleTimeMillis)
minIdle	0	(Introspected attribute minIdle)
modelerType	org.apache.tomcat.dbcp.dbcp2.BasicDataSource	(Type of the modeled resource. Can be set only once)
numActive	11	(Introspected attribute numActive)
numIdle	1	(Introspected attribute numIdle)
numTestsPerEvictionRun	3	(Introspected attribute numTestsPerEvictionRun)
poolPreparedStatements	false	(Introspected attribute poolPreparedStatements)
removeAbandonedOnBorrow	false	(Introspected attribute removeAbandonedOnBorrow)
removeAbandonedOnMaintenance	false	(Introspected attribute removeAbandonedOnMaintenance)
removeAbandonedTimeout	300	(Introspected attribute removeAbandonedTimeout)
rollbackOnReturn	true	(Introspected attribute rollbackOnReturn)
softMinEvictableIdleTimeMillis	-1	(Introspected attribute softMinEvictableIdleTimeMillis)
testOnBorrow	true	(Introspected attribute testOnBorrow)
testOnCreate	false	(Introspected attribute testOnCreate)
testOnReturn	false	(Introspected attribute testOnReturn)
testWhileIdle	false	(Introspected attribute testWhileIdle)
timeBetweenEvictionRunsMillis	-1	(Introspected attribute timeBetweenEvictionRunsMillis)
url	jdbc:h2:/opt/data/demo/h2	(Introspected attribute url)
username	sa	(Introspected attribute username)
validationQuery	null	(Introspected attribute validationQuery)
validationQueryTimeout	-1	(Introspected attribute validationQueryTimeout)

host=localhost,context=/demo,class=javax.sql.DataSource,name="jdbc/demo\_javamelody",connectionpool=connections

AbandonedConfig	false
BlockWhenExhausted	true
BorrowedCount	10 116
Closed	false
CreatedCount	12
CreationStackTrace	java.lang.Exception at org.apache.tomcat.dbcp.pool2.impl.BaseGenericObjectPool.<init>(BaseGenericObjectPool.java:109) at org.apache.tomcat.dbcp.pool2.impl.GenericObjectPool.<init>(GenericObjectPool.java:109) at org.apache.tomcat.dbcp.dbcp2.BasicDataSource.createObjectPool(BasicDataSource.java:628) at org.apache.tomcat.dbcp.dbcp2.BasicDataSource.createConnectionPool(BasicDataSource.java:492) at org.apache.tomcat.dbcp.dbcp2.BasicDataSource.createDataSource(BasicDataSource.java:558) at org.apache.tomcat.dbcp.dbcp2.BasicDataSource.getConnection(BasicDataSource.java:753) at java.base/jdk.internal.reflect.NativeMethodAccessorImpl.invoke0(Native Method) at java.base/jdk.internal.reflect.NativeMethodAccessorImpl.invoke(NativeMethodAccessorImpl.java:62) at java.base/jdk.internal.reflect.DelegatingMethodAccessorImpl.invoke(DelegatingMethodAccessorImpl.java:43) at java.base/java.lang.reflect.Method.invoke(Method.java:566) at net.bull.javamelody.JdbcWrapper\$3.invoke(JdbcWrapper.java:812) at net.bull.javamelody.JdbcWrapper\$DelegatingInvocationHandler.invoke(JdbcWrapper.java:306) at com.sun.proxy.\$Proxy5.getConnection(Unknown Source) at net.bull.javamelody.internal.model.JavaInformations.buildDataBaseVersion(JavaInformations.java:426) at net.bull.javamelody.internal.model.JavaInformations.<init>(JavaInformations.java:200) at net.bull.javamelody.internal.model.UpdateChecker.getAnonymousData(UpdateChecker.java:133) at net.bull.javamelody.internal.model.UpdateChecker.checkForUpdate(UpdateChecker.java:109) at net.bull.javamelody.internal.model.UpdateChecker\$1.run(UpdateChecker.java:83) at java.base/java.util.TimerThread.mainLoop(Timer.java:556) at java.base/java.util.TimerThread.run(Timer.java:506)
DestroyedByBorrowValidationCount	0
DestroyedByEvictorCount	0
DestroyedCount	0

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

FactoryType	org.apache.tomcat.dbcp.dbcp2.PoolableConnectionFactory<org.apache.tomcat.dbcp.dbcp2.PoolableConnection>
Fairness	false
Lifo	true
LogAbandoned	false
MaxBorrowWaitTimeMillis	46
MaxIdle	10
MaxTotal	100
MaxWaitMillis	30 000
MeanActiveTimeMillis	0
MeanBorrowWaitTimeMillis	0
MeanIdleTimeMillis	11 213
MinEvictableIdleTimeMillis	1 800 000
MinIdle	0
NumActive	11
NumIdle	1
NumTestsPerEvictionRun	3
NumWaiters	0
RemoveAbandonedOnBorrow	false
RemoveAbandonedOnMaintenance	false
RemoveAbandonedTimeout	2 147 483 647
ReturnedCount	10 105
TestOnBorrow	true
TestOnCreate	false
TestOnReturn	false
TestWhileIdle	false
TimeBetweenEvictionRunsMillis	-1

host=localhost,context=/demo,class=javax.sql.DataSource,name="jdbc/demo\_javamelody",connectionpool=connections,connection=1

AutoCommit	false
CacheState	true
Catalog	H2
Closed	false
Holdability	1
ReadOnly	false
Schema	PUBLIC
ToString	1371529097, URL=jdbc:h2:/opt/data/demo/h2, UserName=SA, H2 JDBC Driver
TransactionIsolation	2

host=localhost,context=/demo,class=javax.sql.DataSource,name="jdbc/demo\_javamelody",connectionpool=connections,connection=10

AutoCommit	false
CacheState	true
Catalog	H2
Closed	false
Holdability	1
ReadOnly	false
Schema	PUBLIC
ToString	1255676050, URL=jdbc:h2:/opt/data/demo/h2, UserName=SA, H2 JDBC Driver
TransactionIsolation	2

host=localhost,context=/demo,class=javax.sql.DataSource,name="jdbc/demo\_javamelody",connectionpool=connections,connection=11

AutoCommit	false
CacheState	true
Catalog	H2
Closed	false
Holdability	1
ReadOnly	false
Schema	PUBLIC
ToString	101133344, URL=jdbc:h2:/opt/data/demo/h2, UserName=SA, H2 JDBC Driver
TransactionIsolation	2

host=localhost,context=/demo,class=javax.sql.DataSource,name="jdbc/demo\_javamelody",connectionpool=connections,connection=12

CacheState	true
Closed	true
ToString	1261457917, URL=jdbc:h2:/opt/data/demo/h2, UserName=SA, H2 JDBC Driver

host=localhost,context=/demo,class=javax.sql.DataSource,name="jdbc/demo\_javamelody",connectionpool=connections,connection=2

AutoCommit	false
CacheState	true
Catalog	H2
Closed	false
Holdability	1
ReadOnly	false
Schema	PUBLIC
ToString	1435372261, URL=jdbc:h2:/opt/data/demo/h2, UserName=SA, H2 JDBC Driver

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

```
TransactionIsolation          2

host=localhost,context=/demo,class=javax.sql.DataSource,name="jdbc/demo_javamelody",connectionpool=connections,connection=3
AutoCommit                      false
CacheState                       true
Catalog                          H2
Closed                           false
Holdability                      1
ReadOnly                         false
Schema                           PUBLIC
ToString                          1344213788, URL=jdbc:h2:/opt/data/demo/h2, UserName=SA, H2
                                 JDBC Driver
TransactionIsolation          2

host=localhost,context=/demo,class=javax.sql.DataSource,name="jdbc/demo_javamelody",connectionpool=connections,connection=4
AutoCommit                      false
CacheState                       true
Catalog                          H2
Closed                           false
Holdability                      1
ReadOnly                         false
Schema                           PUBLIC
ToString                          530369083, URL=jdbc:h2:/opt/data/demo/h2, UserName=SA, H2
                                 JDBC Driver
TransactionIsolation          2

host=localhost,context=/demo,class=javax.sql.DataSource,name="jdbc/demo_javamelody",connectionpool=connections,connection=5
AutoCommit                      false
CacheState                       true
Catalog                          H2
Closed                           false
Holdability                      1
ReadOnly                         false
Schema                           PUBLIC
ToString                          2075955629, URL=jdbc:h2:/opt/data/demo/h2, UserName=SA, H2
                                 JDBC Driver
TransactionIsolation          2

host=localhost,context=/demo,class=javax.sql.DataSource,name="jdbc/demo_javamelody",connectionpool=connections,connection=6
AutoCommit                      false
CacheState                       true
Catalog                          H2
Closed                           false
Holdability                      1
ReadOnly                         false
Schema                           PUBLIC
ToString                          2071509684, URL=jdbc:h2:/opt/data/demo/h2, UserName=SA, H2
                                 JDBC Driver
TransactionIsolation          2

host=localhost,context=/demo,class=javax.sql.DataSource,name="jdbc/demo_javamelody",connectionpool=connections,connection=7
AutoCommit                      false
CacheState                       true
Catalog                          H2
Closed                           false
Holdability                      1
ReadOnly                         false
Schema                           PUBLIC
ToString                          1882375182, URL=jdbc:h2:/opt/data/demo/h2, UserName=SA, H2
                                 JDBC Driver
TransactionIsolation          2

host=localhost,context=/demo,class=javax.sql.DataSource,name="jdbc/demo_javamelody",connectionpool=connections,connection=8
AutoCommit                      false
CacheState                       true
Catalog                          H2
Closed                           false
Holdability                      1
ReadOnly                         false
Schema                           PUBLIC
ToString                          520855137, URL=jdbc:h2:/opt/data/demo/h2, UserName=SA, H2
                                 JDBC Driver
TransactionIsolation          2

host=localhost,context=/demo,class=javax.sql.DataSource,name="jdbc/demo_javamelody",connectionpool=connections,connection=9
AutoCommit                      false
CacheState                       true
Catalog                          H2
Closed                           false
```

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

Holdability	1	
ReadOnly	false	
Schema	PUBLIC	
ToString	1624610848, URL= jdbc:h2:/opt/data/demo/h2, UserName=SA, H2 JDBC Driver	
TransactionIsolation	2	

## Deployer

### host=localhost

(Startup event listener for a Host that configures the properties of that Host, and the associated defined contexts)		
className	org.apache.catalina.startup.HostConfig	(Fully qualified class name of the managed object)
configBaseName	/opt/apache-tomcat-9.0.33/conf/Catalina/localhost	(The base directory for Context configuration files)
contextClass	org.apache.catalina.core.StandardContext	(The Java class name of the Context implementation we should use)
copyXML	false	(The copy XML config file flag for this component)
deployXML	true	(The deploy XML config file flag for this component)
modelerType	org.apache.catalina.startup.HostConfig	(Type of the modeled resource. Can be set only once)
unpackWARs	false	(The unpack WARs flag)

## Engine

(Standard Engine Component)		
backgroundProcessorDelay	10	(The processor delay for this component.)
catalinaBase	/opt/apache-tomcat-9.0.33	(Base (instance) directory for this Engine, typically same as catalina.base system property)
defaultHost	localhost	(Name of the default Host for this Engine)
jvmRoute	null	(Route used for load balancing)
managedResource	StandardEngine[Catalina]	(The managed resource this MBean is associated with)
modelerType	org.apache.catalina.core.StandardEngine	(Type of the modeled resource. Can be set only once)
name	Catalina	(Unique name of this Engine)
realm	LockOutRealm[StandardEngine[Catalina]]	(Associated realm.)
startChildren	true	(Will children be started automatically when they are added.)
startStopThreads	1	(The number of threads to use when starting and stopping child Hosts)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

## Filter

### WebModule=/localhost/,name=Tomcat WebSocket (JSR356) Filter,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet-filter definition)		
filterClass	org.apache.tomcat.websocket.server.WsFilter	(Fully qualified class name of the filter object)
filterInitParameterMap	{}	(Return the initialization parameters associated with this filter)
filterName	Tomcat WebSocket (JSR356) Filter	(The name used to reference the filter in web.xml)
modelerType	org.apache.catalina.core.ApplicationFilterConfig	(Type of the modeled resource. Can be set only once)

### WebModule=/localhost/demo,name=Tomcat WebSocket (JSR356) Filter,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet-filter definition)		
filterClass	org.apache.tomcat.websocket.server.WsFilter	(Fully qualified class name of the filter object)
filterInitParameterMap	{}	(Return the initialization parameters associated with this filter)
filterName	Tomcat WebSocket (JSR356) Filter	(The name used to reference the filter in web.xml)
modelerType	org.apache.catalina.core.ApplicationFilterConfig	(Type of the modeled resource. Can be set only once)

### WebModule=/localhost/demo,name=forbiddenActions,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet-filter definition)		
filterClass	ForbiddenActionsFilter	(Fully qualified class name of the filter object)
filterInitParameterMap	{}	(Return the initialization parameters associated with this filter)
filterName	forbiddenActions	(The name used to reference the filter in web.xml)
modelerType	org.apache.catalina.core.ApplicationFilterConfig	(Type of the modeled resource. Can be set only once)

### WebModule=/localhost/demo,name=httpSessionInThread,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet-filter definition)		
filterClass	fr.spi4j.filter.HttpSessionFilter	(Fully qualified class name of the filter object)
filterInitParameterMap	{}	(Return the initialization parameters associated with this filter)
filterName	httpSessionInThread	(The name used to reference the filter in web.xml)
modelerType	org.apache.catalina.core.ApplicationFilterConfig	(Type of the modeled resource. Can be set only once)

### WebModule=/localhost/demo,name=javamelody,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet-filter definition)		
filterClass	net.bull.javamelody.MonitoringFilter	(Fully qualified class name of the filter object)
filterInitParameterMap	{}	(Return the initialization parameters associated with this filter)
filterName	javamelody	(The name used to reference the filter in web.xml)
modelerType	org.apache.catalina.core.ApplicationFilterConfig	(Type of the modeled resource. Can be set only once)

### WebModule=/localhost/demo,name=monitoring,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet-filter definition)		
filterClass	net.bull.javamelody.MonitoringFilter	(Fully qualified class name of the filter object)
filterInitParameterMap	{}	(Return the initialization parameters associated with this filter)
filterName	monitoring	(The name used to reference the filter in web.xml)
modelerType	org.apache.catalina.core.ApplicationFilterConfig	(Type of the modeled resource. Can be set only once)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

<b>WebModule=//localhost/demo,name=remoteUser,J2EEApplication=none,J2EEServer=none</b> (Wrapper that represents an individual servlet-filter definition)		
filterClass	fr.spi4j.lib.security.RemoteUserFilter	(Fully qualified class name of the filter object)
filterInitParameterMap	{}	(Return the initialization parameters associated with this filter)
filterName	remoteUser	(The name used to reference the filter in web.xml)
modelerType	org.apache.catalina.core.ApplicationFilterConfig	(Type of the modeled resource. Can be set only once)
<b>WebModule=//localhost/downloads,name=Tomcat WebSocket (JSR356) Filter,J2EEApplication=none,J2EEServer=none</b> (Wrapper that represents an individual servlet-filter definition)		
filterClass	org.apache.tomcat.websocket.server.WsFilter	(Fully qualified class name of the filter object)
filterInitParameterMap	{}	(Return the initialization parameters associated with this filter)
filterName	Tomcat WebSocket (JSR356) Filter	(The name used to reference the filter in web.xml)
modelerType	org.apache.catalina.core.ApplicationFilterConfig	(Type of the modeled resource. Can be set only once)
<b>WebModule=//localhost/usage,name=Tomcat WebSocket (JSR356) Filter,J2EEApplication=none,J2EEServer=none</b> (Wrapper that represents an individual servlet-filter definition)		
filterClass	org.apache.tomcat.websocket.server.WsFilter	(Fully qualified class name of the filter object)
filterInitParameterMap	{}	(Return the initialization parameters associated with this filter)
filterName	Tomcat WebSocket (JSR356) Filter	(The name used to reference the filter in web.xml)
modelerType	org.apache.catalina.core.ApplicationFilterConfig	(Type of the modeled resource. Can be set only once)
<b>WebModule=//localhost/usage,name=basic-auth,J2EEApplication=none,J2EEServer=none</b> (Wrapper that represents an individual servlet-filter definition)		
filterClass	net.bull.javamelody.usagestats.BasicAuthFilter	(Fully qualified class name of the filter object)
filterInitParameterMap	{}	(Return the initialization parameters associated with this filter)
filterName	basic-auth	(The name used to reference the filter in web.xml)
modelerType	org.apache.catalina.core.ApplicationFilterConfig	(Type of the modeled resource. Can be set only once)
<b>WebModule=//localhost/usage,name=gzip,J2EEApplication=none,J2EEServer=none</b> (Wrapper that represents an individual servlet-filter definition)		
filterClass	net.bull.javamelody.usagestats.GzipFilter	(Fully qualified class name of the filter object)
filterInitParameterMap	{}	(Return the initialization parameters associated with this filter)
filterName	gzip	(The name used to reference the filter in web.xml)
modelerType	org.apache.catalina.core.ApplicationFilterConfig	(Type of the modeled resource. Can be set only once)
<b>WebModule=//localhost/usage,name=javamelody,J2EEApplication=none,J2EEServer=none</b> (Wrapper that represents an individual servlet-filter definition)		
filterClass	net.bull.javamelody.MonitoringFilter	(Fully qualified class name of the filter object)
filterInitParameterMap	{}	(Return the initialization parameters associated with this filter)
filterName	javamelody	(The name used to reference the filter in web.xml)
modelerType	org.apache.catalina.core.ApplicationFilterConfig	(Type of the modeled resource. Can be set only once)
<b>GlobalRequestProcessor</b> <b>name="http-nio-80"</b> (Runtime information of a group of requests)		
bytesReceived	28 252	(Amount of data received, in bytes)
bytesSent	1 212 058 302	(Amount of data sent, in bytes)
errorCount	10 744	(Number of errors)
maxTime	80 360	(Maximum time to process a request)
modelerType	org.apache.coyote.RequestGroupInfo	(Type of the modeled resource. Can be set only once)
processingTime	10 921 654	(Total time to process the requests)
requestCount	6 865 448	(Number of requests processed)
<b>Host</b>		
<b>host=localhost</b> (Standard Host Component)		
aliases	[]	(Host aliases)
appBase	webapps	(The application root for this Host)
autoDeploy	true	(The auto deploy flag for this Host)
backgroundProcessorDelay	-1	(The processor delay for this component.)
children	[Catalina:j2eeType=WebModule,name=/localhost/,J2EEApplication=none,J2EEServer=none,Catalina:j2eeType=WebModule,name=/localhost/downloads,J2EEApplication=none,J2EEServer=none,Catalina:j2eeType=WebModule,name=/localhost/demo,J2EEApplication=none,J2EEServer=none,Catalina:j2eeType=WebModule,name=/localhost/usage,J2EEApplication=none,J2EEServer=none]	(Object names of all children)
configClass	org.apache.catalina.startup.ContextConfig	(The configuration class for contexts)
contextClass	org.apache.catalina.core.StandardContext	(The Java class name of the default Context implementation class for deployed web applications.)
copyXML	false	(Should XML files be copied to \$CATALINA_BASE/conf/(engine)/(host) by default when a web application is deployed?)
createDirs	true	(Should we create directories upon startup for appBase and xmlBase? )
deployIgnore	null	(Paths within appBase ignored for automatic deployment)
deployOnStartup	true	(The deploy on startup flag for this Host)
deployXML	true	(deploy Context XML config files property)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

errorReportValveClass	org.apache.catalina.valves.ErrorReportValve	(The Java class name of the default error reporter implementation class for deployed web applications.)
managedResource	StandardEngine[Catalina].StandardHost[localhost]	(The managed resource this MBean is associated with)
modelerType	org.apache.catalina.core.StandardHost	(Type of the modeled resource. Can be set only once)
name	localhost	(Unique name of this Host)
realm	LockOutRealm[StandardEngine[Catalina]]	(Associated realm.)
startChildren	true	(Will children be started automatically when they are added?)
startStopThreads	1	(The number of threads to use when starting, stopping and deploying child Contexts)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
undeployOldVersions	false	(Determines if old versions of applications deployed using parallel deployment are automatically undeployed when no longer used. Requires autoDeploy to be enabled.)
unpackWARs	false	(Unpack WARs property)
valveNames	[Catalina:type=Valve,host=localhost,name=AccessLogValve,Catalina:type=Valve,host=localhost,name=ErrorReportValve,Catalina:type=Valve,host=localhost,name=StandardHostValve]	(Return the MBean Names of the Valves associated with this Host)
workDir	null	(Work Directory base for applications)
xmlBase	null	(The XML root for this Host.)

## JspMonitor

### WebModule=/localhost/,name=jsp,J2EEApplication=none,J2EEServer=none

(JSP Monitoring)

jspCount	1	(The number of JSPs that have been loaded into a webapp)
jspQueueLength	-1	(The length of the JSP queue (if enabled via maxLoadedJsp))
jspReloadCount	0	(The number of JSPs that have been reloaded)
jspUnloadCount	0	(The number of JSPs that have been unloaded)
modelerType	org.apache.jasper.servlet.JspServlet	(Type of the modeled resource. Can be set only once)

### WebModule=/localhost/demo,name=jsp,J2EEApplication=none,J2EEServer=none

(JSP Monitoring)

jspCount	1	(The number of JSPs that have been loaded into a webapp)
jspQueueLength	-1	(The length of the JSP queue (if enabled via maxLoadedJsp))
jspReloadCount	0	(The number of JSPs that have been reloaded)
jspUnloadCount	0	(The number of JSPs that have been unloaded)
modelerType	org.apache.jasper.servlet.JspServlet	(Type of the modeled resource. Can be set only once)

### WebModule=/localhost/downloads,name=jsp,J2EEApplication=none,J2EEServer=none

(JSP Monitoring)

jspCount	0	(The number of JSPs that have been loaded into a webapp)
jspQueueLength	-1	(The length of the JSP queue (if enabled via maxLoadedJsp))
jspReloadCount	0	(The number of JSPs that have been reloaded)
jspUnloadCount	0	(The number of JSPs that have been unloaded)
modelerType	org.apache.jasper.servlet.JspServlet	(Type of the modeled resource. Can be set only once)

### WebModule=/localhost/usage,name=jsp,J2EEApplication=none,J2EEServer=none

(JSP Monitoring)

jspCount	0	(The number of JSPs that have been loaded into a webapp)
jspQueueLength	-1	(The length of the JSP queue (if enabled via maxLoadedJsp))
jspReloadCount	0	(The number of JSPs that have been reloaded)
jspUnloadCount	0	(The number of JSPs that have been unloaded)
modelerType	org.apache.jasper.servlet.JspServlet	(Type of the modeled resource. Can be set only once)

## Loader

### host=localhost,context=/

(ClassLoader implementation which is specialized for handling web applications)

className	org.apache.catalina.loader.WebappLoader	(Fully qualified class name of the managed object)
delegate	false	(The 'follow standard delegation model' flag that will be used to configure our ClassLoader)
loaderRepositories	[]	(Repositories set in the real loader)
loaderRepositoriesString		(Repositories set in the real loader)
modelerType	org.apache.catalina.loader.WebappLoader	(Type of the modeled resource. Can be set only once)
reloadable	false	(The reloadable flag for this Loader)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

### host=localhost,context=/demo

(ClassLoader implementation which is specialized for handling web applications)

className	org.apache.catalina.loader.WebappLoader	(Fully qualified class name of the managed object)
delegate	false	(The 'follow standard delegation model' flag that will be used to configure our ClassLoader)

Monitoring JavaMelody sur /demo\_vps363300.ovh.net

[war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war\*/WEB-INF/classes,  
 war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war\*/WEB-INF/lib/fr.opensagres.xdoreport.core-1.0.4.jar,  
 war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war\*/WEB-INF/lib/ehcache-core-2.6.8.jar,  
 war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war\*/WEB-INF/lib/log4j-1.2.17.jar,  
 war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war\*/WEB-INF/lib/spi4j-lib-security-server-1.7-SNAPSHOT.jar,  
 war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war\*/WEB-INF/lib/slf4j-api-1.6.1.jar,  
 war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war\*/WEB-INF/lib/jta-1.1.jar,  
 war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war\*/WEB-INF/lib/fr.opensagres.xdoreport.template.freemarker-1.0.4.jar,  
 war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war\*/WEB-INF/lib/xpp3\_min-1.1.4c.jar,  
 war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war\*/WEB-INF/lib/gwt-servlet-2.7.0.jar,  
 war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war\*/WEB-INF/lib/spi4j-gwt-1.7-SNAPSHOT.jar,  
 war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war\*/WEB-INF/lib/fr.opensagres.xdoreport.document-1.0.4.jar,  
 war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war\*/WEB-INF/lib/itext-2.1.7.jar,  
 war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war\*/WEB-INF/lib/fr.opensagres.xdoreport.template-1.0.4.jar,  
 war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war\*/WEB-INF/lib/freemarker-2.3.16.jar,  
 war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war\*/WEB-INF/lib/fr.opensagres.xdoreport.converter-1.0.4.jar,  
 war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war\*/WEB-INF/lib/validation-api-1.0.0.GA.jar,  
 war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war\*/WEB-INF/lib/appwhite1-commons-1.7-SNAPSHOT.jar,  
 war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war\*/WEB-INF/lib/fr.opensagres.xdoreport.document.docx-1.0.4.jar,  
 war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war\*/WEB-INF/lib/spi4j-1.7-SNAPSHOT.jar,  
 war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war\*/WEB-INF/lib/jrobin-1.5.9.jar,  
 war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war\*/WEB-INF/lib/fr.opensagres.xdoreport.document.odt-1.0.4.jar,  
 war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war\*/WEB-INF/lib/spi4j-ui-1.7-SNAPSHOT.jar,  
 war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war\*/WEB-INF/lib/javamelody-core-1.98.0.jar,  
 war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war\*/WEB-INF/lib/spi4j-doc-report-1.7-SNAPSHOT.jar,  
 war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war\*/WEB-INF/lib/fr.opensagres.xdoreport.document.pptx-1.0.4.jar,  
 war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war\*/WEB-INF/lib/spi4j-lib-security-commons-1.7-SNAPSHOT.jar,  
 war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war\*/WEB-INF/lib/appwhite1-server-1.7-SNAPSHOT.jar,  
 war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war\*/WEB-INF/lib/referentiel-server-1.7-SNAPSHOT.jar,  
 war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war\*/WEB-INF/lib/h2-1.4.200.jar,  
 war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war\*/WEB-INF/lib/xstream-1.4.11.1.jar,  
 war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war\*/WEB-INF/lib/referentiel-commons-1.7-SNAPSHOT.jar]  
 war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war\*/WEB-INF/classes/war:file:/opt/apache-tomcat-  
 9.0.33/webapps/demo.war\*/WEB-INF/lib/fr.opensagres.xdoreport.core-1.0.4.jar;war:file:/opt/apache-  
 tomcat-9.0.33/webapps/demo.war\*/WEB-INF/lib/ehcache-core-  
 2.6.8.jar;war:file:/opt/apache-tomcat-  
 9.0.33/webapps/demo.war\*/WEB-INF/lib/log4j-  
 1.2.17.jar;war:file:/opt/apache-tomcat-  
 9.0.33/webapps/demo.war\*/WEB-INF/lib/spi4j-lib-security-server-1.7-  
 SNAPSHOT.jar;war:file:/opt/apache-tomcat-  
 9.0.33/webapps/demo.war\*/WEB-INF/lib/slf4j-api-  
 1.6.1.jar;war:file:/opt/apache-tomcat-  
 9.0.33/webapps/demo.war\*/WEB-INF/lib/jta-  
 1.1.jar;war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war\*/WEB-  
 INF/lib/fr.opensagres.xdoreport.template.freemarker-  
 1.0.4.jar;war:file:/opt/apache-tomcat-  
 9.0.33/webapps/demo.war\*/WEB-INF/lib/xpp3\_min-  
 1.1.4c.jar;war:file:/opt/apache-tomcat-  
 9.0.33/webapps/demo.war\*/WEB-INF/lib/gwt-servlet-  
 2.7.0.jar;war:file:/opt/apache-tomcat-  
 9.0.33/webapps/demo.war\*/WEB-INF/lib/spi4j-gwt-1.7-  
 SNAPSHOT.jar;war:file:/opt/apache-tomcat-  
 9.0.33/webapps/demo.war\*/WEB-INF/lib/jrobin-  
 1.5.9.jar;war:file:/opt/apache-tomcat-  
 9.0.33/webapps/demo.war\*/WEB-  
 INF/lib/fr.opensagres.xdoreport.converter-  
 1.0.4.jar;war:file:/opt/apache-tomcat-  
 9.0.33/webapps/demo.war\*/WEB-INF/lib/validation-api-  
 1.0.0.GA.jar;war:file:/opt/apache-tomcat-  
 9.0.33/webapps/demo.war\*/WEB-INF/lib/appwhite1-commons-1.7-  
 SNAPSHOT.jar;war:file:/opt/apache-tomcat-  
 9.0.33/webapps/demo.war\*/WEB-  
 INF/lib/fr.opensagres.xdoreport.document.docx-  
 1.0.4.jar;war:file:/opt/apache-tomcat-  
 9.0.33/webapps/demo.war\*/WEB-INF/lib/spi4j-ui-1.7-  
 SNAPSHOT.jar;war:file:/opt/apache-tomcat-  
 9.0.33/webapps/demo.war\*/WEB-INF/lib/javamelody-core-  
 1.98.0.jar;war:file:/opt/apache-tomcat-  
 9.0.33/webapps/demo.war\*/WEB-INF/lib/spi4j-doc-report-1.7-  
 SNAPSHOT.jar;war:file:/opt/apache-tomcat-  
 9.0.33/webapps/demo.war\*/WEB-  
 INF/lib/fr.opensagres.xdoreport.document.odt-  
 1.0.4.jar;war:file:/opt/apache-tomcat-  
 9.0.33/webapps/demo.war\*/WEB-INF/lib/spi4j-ui-1.7-  
 SNAPSHOT.jar;war:file:/opt/apache-tomcat-  
 9.0.33/webapps/demo.war\*/WEB-INF/lib/appwhite1-server-1.7-  
 SNAPSHOT.jar;war:file:/opt/apache-tomcat-  
 9.0.33/webapps/demo.war\*/WEB-INF/lib/referentiel-server-1.7-  
 SNAPSHOT.jar;war:file:/opt/apache-tomcat-  
 9.0.33/webapps/demo.war\*/WEB-INF/lib/h2-  
 1.4.200.jar;war:file:/opt/apache-tomcat-  
 9.0.33/webapps/demo.war\*/WEB-INF/lib/xstream-  
 1.4.11.1.jar;war:file:/opt/apache-tomcat-  
 9.0.33/webapps/demo.war\*/WEB-INF/lib/referentiel-commons-1.7-  
 SNAPSHOT.jar]

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

stateName	STARTED	(The name of the LifecycleState that this component is currently in)
<b>host=localhost,context=/downloads</b>		
(classloader implementation which is specialized for handling web applications)		
className	org.apache.catalina.loader.WebappLoader	(Fully qualified class name of the managed object)
delegate	false	(The 'follow standard delegation model' flag that will be used to configure our ClassLoader)
loaderRepositories	[]	(Repositories set in the real loader)
loaderRepositoriesString		(Repositories set in the real loader)
modelerType	org.apache.catalina.loader.WebappLoader	(Type of the modeled resource. Can be set only once)
reloadable	false	(The reloadable flag for this Loader)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
<b>host=localhost,context=/usage</b>		
(classloader implementation which is specialized for handling web applications)		
className	org.apache.catalina.loader.WebappLoader	(Fully qualified class name of the managed object)
delegate	false	(The 'follow standard delegation model' flag that will be used to configure our ClassLoader)
loaderRepositories	[war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/classes, war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/text-2.1.7.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/commons-csv-1.10.0.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/log4j-1.2.17.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/jrobin-1.5.9.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/geoip-api-1.3.1.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/gson-2.10.1.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*/WEB-INF/lib/javamelody-core-1.98.0.jar]	(Repositories set in the real loader)
loaderRepositoriesString		(Repositories set in the real loader)
modelerType	org.apache.catalina.loader.WebappLoader	(Type of the modeled resource. Can be set only once)
reloadable	false	(The reloadable flag for this Loader)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
<b>MBeanFactory</b>		
(Factory for MBeans and corresponding components)		
modelerType	org.apache.catalina.mbeans.MBeanFactory	(Type of the modeled resource. Can be set only once)
<b>Manager</b>		
<b>host=localhost,context=/</b>		
(Standard implementation of the Manager interface)		
activeSessions	1	(Number of active sessions at this moment)
className	org.apache.catalina.session.StandardManager	(Fully qualified class name of the managed object)
duplicates	0	(Number of duplicated session ids generated)
expiredSessions	2 126	(Number of sessions that expired ( doesn't include explicit invalidations ))
jvmRoute	null	(Retrieve the JvmRoute for the enclosing Engine)
maxActive	24	(Maximum number of active sessions so far)
maxActiveSessions	-1	(The maximum number of active Sessions allowed, or -1 for no limit)
modelerType	org.apache.catalina.session.StandardManager	(Type of the modeled resource. Can be set only once)
name	StandardManager	(The descriptive name of this Manager implementation (for logging))
pathname	SESSIONS.ser	(Path name of the disk file in which active sessions)
persistAuthentication	false	(Indicates whether sessions shall persist authentication information when being persisted (e.g. across application restarts))
processExpiresFrequency	6	(The frequency of the manager checks (expiration and passivation))
processingTime	161	(Time spent doing housekeeping and expiration)
rejectedSessions	0	(Number of sessions we rejected due to maxActive being reached)
secureRandomAlgorithm	SHA1PRNG	(The secure random number generator algorithm name)
secureRandomClass	null	(The secure random number generator class name)
secureRandomProvider	null	(The secure random number generator provider name)
sessionAttributeNameFilter	null	(The string pattern used for including session attributes in distribution. Null means all attributes are included.)
sessionAttributeValueClassNameFilter	null	(The regular expression used to filter session attributes based on the implementation class of the value. The regular expression is anchored and must match the fully qualified class name.)
sessionAverageAliveTime	18	(Average time an expired session had been alive)
sessionCounter	2 127	(Total number of sessions created by this manager)
sessionCreateRate	0	(Session creation rate in sessions per minute)
sessionExpireRate	0	(Session expiration rate in sessions per minute)
sessionMaxAliveTime	4 119	(Longest time an expired session had been alive)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
warnOnSessionAttributeFilterFailure	false	(Should a WARN level log message be generated if a session attribute fails to match sessionAttributeNameFilter or sessionAttributeValueClassNameFilter?)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

## host=localhost,context=/demo

(Standard implementation of the Manager interface)	
activeSessions	173
className	org.apache.catalina.session.StandardManager
duplicates	0
expiredSessions	28 869
jvmRoute	null
maxActive	595
maxActiveSessions	-1
modelerType	org.apache.catalina.session.StandardManager
name	StandardManager
pathname	SESSIONS.ser
persistAuthentication	false
processExpiresFrequency	6
processingTime	624
rejectedSessions	0
secureRandomAlgorithm	SHA1PRNG
secureRandomClass	null
secureRandomProvider	null
sessionAttributeNameFilter	null
sessionAttributeValueClassNameFilter	null
sessionAverageAliveTime	18
sessionCounter	29 042
sessionCreateRate	5
sessionExpireRate	5
sessionMaxAliveTime	3 249
stateName	STARTED
warnOnSessionAttributeFilterFailure	false

(Number of active sessions at this moment)  
(Fully qualified class name of the managed object)  
(Number of duplicated session ids generated)  
(Number of sessions that expired ( doesn't include explicit invalidations ))  
(Retrieve the JvmRoute for the enclosing Engine)  
(Maximum number of active sessions so far)  
(The maximum number of active Sessions allowed, or -1 for no limit)  
(Type of the modeled resource. Can be set only once)  
(The descriptive name of this Manager implementation (for logging))  
(Path name of the disk file in which active sessions)  
(Indicates whether sessions shall persist authentication information when being persisted (e.g. across application restarts).)  
(The frequency of the manager checks (expiration and passivation))  
(Time spent doing housekeeping and expiration)  
(Number of sessions we rejected due to maxActive being reached)  
(The secure random number generator algorithm name)  
(The secure random number generator class name)  
(The secure random number generator provider name)  
(The string pattern used for including session attributes in distribution. Null means all attributes are included.)  
(The regular expression used to filter session attributes based on the implementation class of the value. The regular expression is anchored and must match the fully qualified class name.)  
(Average time an expired session had been alive)  
(Total number of sessions created by this manager)  
(Session creation rate in sessions per minute)  
(Session expiration rate in sessions per minute)  
(Longest time an expired session had been alive)  
(The name of the LifecycleState that this component is currently in)  
(Should a WARN level log message be generated if a session attribute fails to match sessionAttributeNameFilter or sessionAttributeValueClassNameFilter?)

## host=localhost,context=/downloads

(Standard implementation of the Manager interface)	
activeSessions	0
className	org.apache.catalina.session.StandardManager
duplicates	0
expiredSessions	0
jvmRoute	null
maxActive	0
maxActiveSessions	-1
modelerType	org.apache.catalina.session.StandardManager
name	StandardManager
pathname	SESSIONS.ser
persistAuthentication	false
processExpiresFrequency	6
processingTime	28
rejectedSessions	0
secureRandomAlgorithm	SHA1PRNG
secureRandomClass	null
secureRandomProvider	null
sessionAttributeNameFilter	null
sessionAttributeValueClassNameFilter	null
sessionAverageAliveTime	0
sessionCounter	0
sessionCreateRate	0
sessionExpireRate	0
sessionMaxAliveTime	0
stateName	STARTED
warnOnSessionAttributeFilterFailure	false

(Number of active sessions at this moment)  
(Fully qualified class name of the managed object)  
(Number of duplicated session ids generated)  
(Number of sessions that expired ( doesn't include explicit invalidations ))  
(Retrieve the JvmRoute for the enclosing Engine)  
(Maximum number of active sessions so far)  
(The maximum number of active Sessions allowed, or -1 for no limit)  
(Type of the modeled resource. Can be set only once)  
(The descriptive name of this Manager implementation (for logging))  
(Path name of the disk file in which active sessions)  
(Indicates whether sessions shall persist authentication information when being persisted (e.g. across application restarts).)  
(The frequency of the manager checks (expiration and passivation))  
(Time spent doing housekeeping and expiration)  
(Number of sessions we rejected due to maxActive being reached)  
(The secure random number generator algorithm name)  
(The secure random number generator class name)  
(The secure random number generator provider name)  
(The string pattern used for including session attributes in distribution. Null means all attributes are included.)  
(The regular expression used to filter session attributes based on the implementation class of the value. The regular expression is anchored and must match the fully qualified class name.)  
(Average time an expired session had been alive)  
(Total number of sessions created by this manager)  
(Session creation rate in sessions per minute)  
(Session expiration rate in sessions per minute)  
(Longest time an expired session had been alive)  
(The name of the LifecycleState that this component is currently in)  
(Should a WARN level log message be generated if a session attribute fails to match sessionAttributeNameFilter or sessionAttributeValueClassNameFilter?)

## host=localhost,context=/usage

(Standard implementation of the Manager interface)	
activeSessions	0
className	org.apache.catalina.session.StandardManager
duplicates	0
expiredSessions	0
jvmRoute	null
maxActive	0
maxActiveSessions	-1
modelerType	org.apache.catalina.session.StandardManager
name	StandardManager

(Number of active sessions at this moment)  
(Fully qualified class name of the managed object)  
(Number of duplicated session ids generated)  
(Number of sessions that expired ( doesn't include explicit invalidations ))  
(Retrieve the JvmRoute for the enclosing Engine)  
(Maximum number of active sessions so far)  
(The maximum number of active Sessions allowed, or -1 for no limit)  
(Type of the modeled resource. Can be set only once)  
(The descriptive name of this Manager implementation (for logging))

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

pathname	SESSIONS.ser	(Path name of the disk file in which active sessions)
persistAuthentication	false	(Indicates whether sessions shall persist authentication information when being persisted (e.g. across application restarts).)
processExpiresFrequency	6	(The frequency of the manager checks (expiration and passivation))
processingTime	21	(Time spent doing housekeeping and expiration)
rejectedSessions	0	(Number of sessions we rejected due to maxActive being reached)
secureRandomAlgorithm	SHA1PRNG	(The secure random number generator algorithm name)
secureRandomClass	null	(The secure random number generator class name)
secureRandomProvider	null	(The secure random number generator provider name)
sessionAttributeNameFilter	null	(The string pattern used for including session attributes in distribution. Null means all attributes are included.)
sessionAttributeValueClassNameFilter	null	(The regular expression used to filter session attributes based on the implementation class of the value. The regular expression is anchored and must match the fully qualified class name.)
sessionAverageAliveTime	0	(Average time an expired session had been alive)
sessionCounter	0	(Total number of sessions created by this manager)
sessionCreateRate	0	(Session creation rate in sessions per minute)
sessionExpireRate	0	(Session expiration rate in sessions per minute)
sessionMaxAliveTime	0	(Longest time an expired session had been alive)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
warnOnSessionAttributeFilterFailure	false	(Should a WARN level log message be generated if a session attribute fails to match sessionAttributeNameFilter or sessionAttributeValueClassNameFilter?)

## Mapper

(Maps requests received by the associated connector to Hosts, Contexts and Wrappers)

modelerType	org.apache.catalina.mapper.MapperListener
stateName	STARTED

(Type of the modeled resource. Can be set only once)

(The name of the LifecycleState that this component is currently in)

## NamingResources

(Holds and manages the naming resources defined in the J2EE Enterprise Naming Context and their associated JNDI context)

container	StandardServer[8005]
environments	[]
modelerType	org.apache.catalina.deploy.NamingResourcesImpl
resourceLinks	[]

(The container with which the naming resources are associated.)

(MBean Names of the set of defined environment entries for this web application)

(Type of the modeled resource. Can be set only once)

(MBean Names of all the defined resource link references for this application.)

### host=localhost,context=/

(Holds and manages the naming resources defined in the J2EE Enterprise Naming Context and their associated JNDI context)

container	StandardEngine[Catalina].StandardHost[localhost].StandardContext[]
environments	[]
modelerType	org.apache.catalina.deploy.NamingResourcesImpl
resourceLinks	[]

(The container with which the naming resources are associated.)

(MBean Names of the set of defined environment entries for this web application)

(Type of the modeled resource. Can be set only once)

(MBean Names of all the defined resource link references for this application.)

(MBean Names of all the defined resource references for this application.)

### host=localhost,context=/demo

(Holds and manages the naming resources defined in the J2EE Enterprise Naming Context and their associated JNDI context)

container	StandardEngine[Catalina].StandardHost[localhost].StandardContext[/demo]
environments	[]
modelerType	org.apache.catalina.deploy.NamingResourcesImpl
resourceLinks	[]

(The container with which the naming resources are associated.)

(MBean Names of the set of defined environment entries for this web application)

(Type of the modeled resource. Can be set only once)

(MBean Names of all the defined resource link references for this application.)

(MBean Names of all the defined resource references for this application.)

### host=localhost,context=/downloads

(Holds and manages the naming resources defined in the J2EE Enterprise Naming Context and their associated JNDI context)

container	StandardEngine[Catalina].StandardHost[localhost].StandardContext[/downloads]
environments	[]
modelerType	org.apache.catalina.deploy.NamingResourcesImpl
resourceLinks	[]

(The container with which the naming resources are associated.)

(MBean Names of the set of defined environment entries for this web application)

(Type of the modeled resource. Can be set only once)

(MBean Names of all the defined resource link references for this application.)

(MBean Names of all the defined resource references for this application.)

### host=localhost,context=/usage

(Holds and manages the naming resources defined in the J2EE Enterprise Naming Context and their associated JNDI context)

container	StandardEngine[Catalina].StandardHost[localhost].StandardContext[/usage]
environments	[]
modelerType	org.apache.catalina.deploy.NamingResourcesImpl
resourceLinks	[]

(The container with which the naming resources are associated.)

(MBean Names of the set of defined environment entries for this web application)

(Type of the modeled resource. Can be set only once)

(MBean Names of all the defined resource link references for this application.)

(MBean Names of all the defined resource references for this application.)

## ParallelWebappClassLoader

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

host=localhost,context=/

(Classloader implementation which is specialized for handling web applications and is capable of loading classes in parallel)		
URLs	[]	(The URLs of this loader)
className	org.apache.catalina.loader.ParallelWebappClassLoader	(Fully qualified class name of the managed object)
contextName	ROOT	(Name of the webapp context)
delegate	false	(The 'follow standard delegation model' flag that will be used to configure our ClassLoader)
modelerType	org.apache.catalina.loader.ParallelWebappClassLoader	(Type of the modeled resource. Can be set only once)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

host=localhost,context=/demo

(Classloader implementation which is specialized for handling web applications and is capable of loading classes in parallel)		
URLs	[war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*WEB-INF/classes/, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*WEB-INF/lib/fr.opensagres.xdcoreport.core-1.0.4.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*WEB-INF/lib/ehcache-core-2.6.8.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*WEB-INF/lib/log4j-1.2.17.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*WEB-INF/lib/spi4-lib-security-server-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*WEB-INF/lib/slf4j-api-1.6.1.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*WEB-INF/lib/tt-1.1.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*WEB-INF/lib/fr.opensagres.xdcoreport.template.freemarker-1.0.4.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*WEB-INF/lib/xpp3_min-1.1.4c.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*WEB-INF/lib/gwt-servlet-2.7.0.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*WEB-INF/lib/spi4-gwt-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*WEB-INF/lib/fr.opensagres.xdcoreport.document-1.0.4.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*WEB-INF/lib/text-2.1.7.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*WEB-INF/lib/fr.opensagres.xdcoreport.template-1.0.4.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*WEB-INF/lib/fr.freemarker-2.3.16.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*WEB-INF/lib/fr.opensagres.xdcoreport.converter-1.0.4.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*WEB-INF/lib/validation-api-1.0.0.GA.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*WEB-INF/lib/appwhite1-commons-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*WEB-INF/lib/fr.opensagres.xdcoreport.document.docx-1.0.4.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*WEB-INF/lib/spi4-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*WEB-INF/lib/jrobin-1.5.9.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*WEB-INF/lib/fr.opensagres.xdcoreport.document.odt-1.0.4.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*WEB-INF/lib/spi4-ui-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*WEB-INF/lib/appwhite1-commons-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*WEB-INF/lib/appwhite1-server-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*WEB-INF/lib/referentiel-server-1.7-SNAPSHOT.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*WEB-INF/lib/h2-1.4.200.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*WEB-INF/lib/xstream-1.4.11.1.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/demo.war*WEB-INF/lib/referentiel-commons-1.7-SNAPSHOT.jar]	(The URLs of this loader)
className	org.apache.catalina.loader.ParallelWebappClassLoader	(Fully qualified class name of the managed object)
contextName	demo	(Name of the webapp context)
delegate	false	(The 'follow standard delegation model' flag that will be used to configure our ClassLoader)
modelerType	org.apache.catalina.loader.ParallelWebappClassLoader	(Type of the modeled resource. Can be set only once)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

host=localhost,context=/downloads

(Classloader implementation which is specialized for handling web applications and is capable of loading classes in parallel)		
URLs	[]	(The URLs of this loader)
className	org.apache.catalina.loader.ParallelWebappClassLoader	(Fully qualified class name of the managed object)
contextName	downloads	(Name of the webapp context)
delegate	false	(The 'follow standard delegation model' flag that will be used to configure our ClassLoader)
modelerType	org.apache.catalina.loader.ParallelWebappClassLoader	(Type of the modeled resource. Can be set only once)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

host=localhost,context=/usage

(Classloader implementation which is specialized for handling web applications and is capable of loading classes in parallel)		
URLs	[war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*WEB-INF/classes/, war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*WEB-INF/lib/text-2.1.7.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*WEB-INF/lib/commons-csv-1.10.0.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*WEB-INF/lib/log4j-1.2.17.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*WEB-INF/lib/jrobin-1.5.9.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*WEB-INF/lib/geoip-api-1.3.1.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*WEB-INF/lib/qson-2.10.1.jar, war:file:/opt/apache-tomcat-9.0.33/webapps/usage.war*WEB-INF/lib/javamelody-core-1.98.0.jar]	(The URLs of this loader)
className	org.apache.catalina.loader.ParallelWebappClassLoader	(Fully qualified class name of the managed object)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

contextName	usage	(Name of the webapp context)
delegate	false	(The 'follow standard delegation model' flag that will be used to configure our ClassLoader)
modelerType	org.apache.catalina.loader.ParallelWebappClassLoader	(Type of the modeled resource. Can be set only once)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
ProtocolHandler		
port=80		
acceptCount	100	(Introspected attribute acceptCount)
acceptorThreadCount	1	(Introspected attribute acceptorThreadCount)
acceptorThreadPriority	5	(Introspected attribute acceptorThreadPriority)
algorithm	SunX509	(Introspected attribute algorithm)
allowHostHeaderMismatch	false	(Introspected attribute allowHostHeaderMismatch)
allowedTrailerHeaders		(Introspected attribute allowedTrailerHeaders)
aprRequired	false	(Introspected attribute aprRequired)
ciphers	HIGH:!aNULL:!eNULL:!EXPORT:!DES:!RC4:!MD5:!kRSA	(Introspected attribute ciphers)
clientAuth	NONE	(Introspected attribute clientAuth)
clientCertProvider	null	(Introspected attribute clientCertProvider)
compressibleMimeType	text/html,text/xml,text/plain,text/css,text/javascript,application/javascript,application/json,application/xml	(Introspected attribute compressibleMimeType)
compressibleMimeTypes	[text/html, text/xml, text/plain, text/css, text/javascript, application/javascript, application/json, application/xml]	(Introspected attribute compressibleMimeTypes)
compression	off	(Introspected attribute compression)
compressionMinSize	2 048	(Introspected attribute compressionMinSize)
connectionCount	94	(Introspected attribute connectionCount)
connectionLinger	-1	(Introspected attribute connectionLinger)
connectionTimeout	20 000	(Introspected attribute connectionTimeout)
connectionUploadTimeout	300 000	(Introspected attribute connectionUploadTimeout)
crfFile	null	(Introspected attribute crfFile)
defaultSSLHostConfigName	_default_	(Introspected attribute defaultSSLHostConfigName)
disableUploadTimeout	true	(Introspected attribute disableUploadTimeout)
domain	Catalina	(Introspected attribute domain)
keepAliveTimeout	20 000	(Introspected attribute keepAliveTimeout)
keyAlias	null	(Introspected attribute keyAlias)
keyPass	null	(Introspected attribute keyPass)
keystoreFile	null	(Introspected attribute keystoreFile)
keystorePass	null	(Introspected attribute keystorePass)
keystoreProvider	null	(Introspected attribute keystoreProvider)
keystoreType	null	(Introspected attribute keystoreType)
localPort	80	(Introspected attribute localPort)
maxConnections	8 192	(Introspected attribute maxConnections)
maxExtensionSize	8 192	(Introspected attribute maxExtensionSize)
maxHeaderCount	100	(Introspected attribute maxHeaderCount)
maxHttpHeaderSize	8 192	(Introspected attribute maxHttpHeaderSize)
maxKeepAliveRequests	100	(Introspected attribute maxKeepAliveRequests)
maxSavePostSize	4 096	(Introspected attribute maxSavePostSize)
maxSwallowSize	2 097 152	(Introspected attribute maxSwallowSize)
maxThreads	200	(Introspected attribute maxThreads)
maxTrailerSize	8 192	(Introspected attribute maxTrailerSize)
minSpareThreads	10	(Introspected attribute minSpareThreads)
modelerType	org.apache.coyote.http11.Http11NioProtocol	(Type of the modeled resource. Can be set only once)
name	"http-nio-80"	(Introspected attribute name)
nameIndex	1	(Introspected attribute nameIndex)
noCompressionStrongETag	true	(Introspected attribute noCompressionStrongETag)
noCompressionUserAgents	null	(Introspected attribute noCompressionUserAgents)
objectName	Catalina:type=ProtocolHandler,port=80	(Introspected attribute objectName)
paused	false	(Introspected attribute paused)
pollerThreadCount	1	(Introspected attribute pollerThreadCount)
pollerThreadPriority	5	(Introspected attribute pollerThreadPriority)
port	80	(Introspected attribute port)
portOffset	0	(Introspected attribute portOffset)
portWithOffset	80	(Introspected attribute portWithOffset)
processorCache	200	(Introspected attribute processorCache)
rejectIllegalHeader	true	(Introspected attribute rejectIllegalHeader)
rejectIllegalHeaderName	true	(Introspected attribute rejectIllegalHeaderName)
relaxedPathChars	null	(Introspected attribute relaxedPathChars)
relaxedQueryChars	null	(Introspected attribute relaxedQueryChars)
restrictedUserAgents	null	(Introspected attribute restrictedUserAgents)
sSLCACertificateFile	null	(Introspected attribute sSLCACertificateFile)
sSLCACertificatePath	null	(Introspected attribute sSLCACertificatePath)
sSLCARevocationFile	null	(Introspected attribute sSLCARevocationFile)
sSLCARevocationPath	null	(Introspected attribute sSLCARevocationPath)
sSLCertificateChainFile	null	(Introspected attribute sSLCertificateChainFile)
sSLCertificateFile	null	(Introspected attribute sSLCertificateFile)
sSLCertificateKeyFile	null	(Introspected attribute sSLCertificateKeyFile)
sSLCipherSuite	HIGH:!aNULL:!eNULL:!EXPORT:!DES:!RC4:!MD5:!kRSA	(Introspected attribute sSLCipherSuite)
sSLDisableCompression	true	(Introspected attribute sSLDisableCompression)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

sSLDisableSessionTickets	false	(Introspected attribute sSLDisableSessionTickets)
sSEnabled	false	(Introspected attribute sSEnabled)
sSHonorCipherOrder	false	(Introspected attribute sSHonorCipherOrder)
sSPassword	null	(Introspected attribute sSPassword)
sSProtocol		(Introspected attribute sSProtocol)
sSVerifyClient	NONE	(Introspected attribute sSVerifyClient)
sSVerifyDepth	10	(Introspected attribute sSVerifyDepth)
secure	false	(Introspected attribute secure)
selectorTimeout	1 000	(Introspected attribute selectorTimeout)
sendfileSupported	true	(Introspected attribute sendfileSupported)
server	null	(Introspected attribute server)
serverRemoveAppProvidedValues	false	(Introspected attribute serverRemoveAppProvidedValues)
sessionCacheSize	-1	(Introspected attribute sessionCacheSize)
sessionTimeout	86 400	(Introspected attribute sessionTimeout)
sniParseLimit	65 536	(Introspected attribute sniParseLimit)
sslEnabledProtocols		(Introspected attribute sslEnabledProtocols)
sslImplementationName	null	(Introspected attribute sslImplementationName)
sslProtocol	TLS	(Introspected attribute sslProtocol)
tcpNoDelay	true	(Introspected attribute tcpNoDelay)
threadPriority	5	(Introspected attribute threadPriority)
trustManagerClassName	null	(Introspected attribute trustManagerClassName)
trustMaxCertLength	10	(Introspected attribute trustMaxCertLength)
truststoreAlgorithm	PKIX	(Introspected attribute truststoreAlgorithm)
truststoreFile	null	(Introspected attribute truststoreFile)
truststorePass	null	(Introspected attribute truststorePass)
truststoreProvider	null	(Introspected attribute truststoreProvider)
truststoreType	JKS	(Introspected attribute truststoreType)
useKeepAliveResponseHeader	true	(Introspected attribute useKeepAliveResponseHeader)
useSendfile	true	(Introspected attribute useSendfile)
useServerCipherSuitesOrder	false	(Introspected attribute useServerCipherSuitesOrder)

## Realm

### realmPath=/realm0

(Realm implementation that can be used to wrap existing realms to provide a user lock-out capability)		
allRolesMode	strict	(The all roles mode.)
cacheRemovalWarningTime	3 600	(If a failed user is removed from the cache because the cache is too big before it has been in the cache for at least this period of time (in seconds) a warning message will be logged. Defaults to 3600 (1 hour.)
cacheSize	1 000	(Number of users that have failed authentication to keep in cache. Over time the cache will grow to this size and may not shrink. Defaults to 1000.)
className	org.apache.catalina.realm.LockOutRealm	(Fully qualified class name of the managed object)
failureCount	5	(The number of times in a row a user has to fail authentication to be locked out. Defaults to 5.)
lockOutTime	300	(The time (in seconds) a user is locked out for after too many authentication failures. Defaults to 300 (5 minutes.)
modelerType	org.apache.catalina.realm.LockOutRealm	(Type of the modeled resource. Can be set only once)
realmPath	/realm0	(The realm path)
realms	[Catalina:type=Realm,realmPath=/realm0/realm0]	(The set of realms that the lockout realm is wrapping)
validate	true	(The 'validate certificate chains' flag.)

### realmPath=/realm0/realm0

(Realm connected to a UserDatabase as a global JNDI resource)		
allRolesMode	strict	(The all roles mode.)
className	org.apache.catalina.realm.UserDatabaseRealm	(Fully qualified class name of the managed object)
modelerType	org.apache.catalina.realm.UserDatabaseRealm	(Type of the modeled resource. Can be set only once)
realmPath	/realm0/realm0	(The realm path)
resourceName	UserDatabase	(The global JNDI name of the UserDatabase resource to use)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
validate	true	(The 'validate certificate chains' flag.)

## RequestProcessor

### worker="http-nio-80",name=HttpRequest1

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	823	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	823	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	823	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest1	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest10		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	820	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	820	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	820	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest10	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest100		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	768	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	768	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	768	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest100	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest101		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	767	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	767	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	767	(Introspected attribute processingTime)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest101	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest102		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nulI]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	761	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	761	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	761	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest102	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest103		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nulI]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	766	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	766	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	766	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest103	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest104		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nulI]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	731	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

maxTime	731	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	731	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest104	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest105		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	1 963	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	1	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	698	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	699	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	2	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest105	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest106		
bytesReceived	5 607	(Introspected attribute bytesReceived)
bytesSent	160 728 610	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	1 586	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	0	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/demo/monitoring	(Introspected attribute maxRequestUri)
maxTime	80 320	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	2 335 993	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1 574 204	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest106	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest107		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nul]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	661	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	661	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	661	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest107	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
<b>worker="http-nio-80",name=HttpRequest108</b>		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nul]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	646	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	646	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	646	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest108	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
<b>worker="http-nio-80",name=HttpRequest109</b>		
bytesReceived	5 816	(Introspected attribute bytesReceived)
bytesSent	140 944 031	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	977	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	0	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/	(Introspected attribute maxRequestUri)
maxTime	16 052	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 277 185	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	866 915	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest109	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

worker="http-nio-80",name=HttpRequest11		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nul]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	819	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	819	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	819	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest11	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest110		
bytesReceived	2 483	(Introspected attribute bytesReceived)
bytesSent	64 077 355	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	310	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nul]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	0	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/demo/app1/76D8F506E8C1C9F1C97A7B6838FF8BC4.cache.js	(Introspected attribute maxRequestUri)
maxTime	29 844	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	703 620	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	385 462	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest110	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest111		
bytesReceived	1 869	(Introspected attribute bytesReceived)
bytesSent	79 312 694	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	640	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nul]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	0	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/	(Introspected attribute maxRequestUri)
maxTime	10 098	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	859 269	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	463 308	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest111	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest112		
bytesReceived	162	(Introspected attribute bytesReceived)
bytesSent	105 522 773	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	part=mbeans&format=pdf	(Introspected attribute currentQueryString)
currentUri	/demo/monitoring	(Introspected attribute currentUri)
errorCount	219	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	0	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/demo/appli1/76D8F506E8C1C9F1C97A7B6838FF8BC4.cache.js	(Introspected attribute maxRequestUri)
maxTime	28 825	(Introspected attribute maxTime)
method	GET	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	519 286	(Introspected attribute processingTime)
protocol	HTTP/1.1	(Introspected attribute protocol)
remoteAddr	18.223.106.100	(Introspected attribute remoteAddr)
remoteAddrForwarded	18.223.106.100	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	280 355	(Introspected attribute requestCount)
requestProcessingTime	69	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest12	(Introspected attribute rpName)
serverPort	80	(Introspected attribute serverPort)
stage	3	(Introspected attribute stage)
virtualHost	javamelody.org	(Introspected attribute virtualHost)
workerThreadName	http-nio-80-exec-135	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest113		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	20 406 792	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	139	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	0	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	6 769	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	114 358	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	62 299	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest13	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest114		
bytesReceived	4 833	(Introspected attribute bytesReceived)
bytesSent	46 905 742	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	517	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	0	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/demo/appli1/PersonneService	(Introspected attribute maxRequestUri)
maxTime	17 950	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	678 065	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

requestCount	501 694	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest114	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest115		
bytesReceived	2 526	(Introspected attribute bytesReceived)
bytesSent	62 795 501	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	832	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nul]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/demo/monitoring	(Introspected attribute maxRequestUri)
maxTime	80 360	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	834 819	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	510 963	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest115	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest116		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	4 361 824	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	16	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nul]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	64	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/demo/monitoring	(Introspected attribute maxRequestUri)
maxTime	20 741	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	60 288	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	40 296	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest116	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest117		
bytesReceived	240	(Introspected attribute bytesReceived)
bytesSent	100 334	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nul]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	71	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/demo/appli1/AuthentificationService	(Introspected attribute maxRequestUri)
maxTime	9 984	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	12 591	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	130	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest117	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest118		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	516 832	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	3	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	6 916	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	15 064	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	2 834	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest118	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest119		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	433	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	433	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	433	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest119	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest12		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	813	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	813	(Introspected attribute maxTime)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	813	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest12	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest120		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nul]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	410	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	410	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	410	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest120	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest121		
bytesReceived	240	(Introspected attribute bytesReceived)
bytesSent	1 578 891	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	4	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nul]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	35	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	7 140	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	27 472	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	14 318	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest121	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest122		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	368	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	368	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	368	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest122	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest123		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	297	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	297	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	297	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest123	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest124		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	283	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	283	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	283	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest124	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest125		

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

bytesReceived	162	(Introspected attribute bytesReceived)
bytesSent	158 701 876	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	760	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	0	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/demo/monitoring	(Introspected attribute maxRequestUri)
maxTime	17 803	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	998 776	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	455 823	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest125	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest126		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	98	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	98	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	98	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest126	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest127		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	68	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	68	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	68	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest127	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
 worker="http-nio-80",name=HttpRequest13		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nul]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	812	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	812	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	812	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest13	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
 worker="http-nio-80",name=HttpRequest14		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nul]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	811	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	811	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	811	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest14	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
 worker="http-nio-80",name=HttpRequest15		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nul]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	811	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	811	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	811	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest15	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest16		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	810	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	810	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	810	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest16	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest17		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	810	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	810	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	810	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest17	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest18		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	809	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	809	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	809	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest18	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest19		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	1	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nulI]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	810	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	810	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	810	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest19	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest2		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	6 061	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	2	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	0	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	829	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	837	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	39	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest2	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest20		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nulI]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	809	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	809	(Introspected attribute maxTime)
method	null	(Introspected attribute method)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	809	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest20	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest21		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	809	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	809	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	809	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest21	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest22		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	1	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	808	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	808	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	808	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest22	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest23		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

lastRequestProcessingTime	808	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	808	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	808	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest23	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

  

worker="http-nio-80",name=HttpRequest24		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nul]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	807	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	807	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	807	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest24	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

  

worker="http-nio-80",name=HttpRequest25		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nul]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	806	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	806	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	806	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest25	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

  

worker="http-nio-80",name=HttpRequest26		
-----------------------------------------	--	--

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nul]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	805	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	805	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	805	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest26	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

## worker="http-nio-80",name=HttpRequest27

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nul]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	805	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	805	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	805	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest27	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

## worker="http-nio-80",name=HttpRequest28

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nul]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	804	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	804	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	804	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest28	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
 worker="http-nio-80",name=HttpRequest29		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nul]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	805	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	805	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	805	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest29	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
 worker="http-nio-80",name=HttpRequest3		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	2 024	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	1	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nul]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	829	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	830	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	3	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest3	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
 worker="http-nio-80",name=HttpRequest30		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nul]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	804	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	804	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	804	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest30	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest31		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	1	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	807	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	807	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	807	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest31	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest32		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	803	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	803	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	803	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest32	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest33		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	802	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	802	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	802	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest33	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest34		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nulI]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	802	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	802	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	802	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest34	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest35		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	801	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	801	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	801	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest35	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest36		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nulI]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	804	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	804	(Introspected attribute maxTime)
method	null	(Introspected attribute method)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	804	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest36	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest37		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	805	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	805	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	805	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest37	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest38		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	804	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	804	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	804	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest38	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest39		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

lastRequestProcessingTime	804	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	804	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	804	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest39	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest4		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	183	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nul]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	0	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	827	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	827	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	3	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest4	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest40		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nul]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	798	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	798	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	798	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest40	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest41		

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nul]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	802	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	802	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	802	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest41	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

## worker="http-nio-80",name=HttpRequest42

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nul]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	797	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	797	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	797	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest42	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

## worker="http-nio-80",name=HttpRequest43

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	1	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nul]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	796	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	796	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	796	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest43	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
 worker="http-nio-80",name=HttpRequest44		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nul]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	801	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	801	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	801	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest44	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
 worker="http-nio-80",name=HttpRequest45		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	1	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nul]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	800	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	800	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	800	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest45	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
 worker="http-nio-80",name=HttpRequest46		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nul]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	795	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	795	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	795	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest46	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest47		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	795	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	795	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	795	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest47	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest48		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	795	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	795	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	795	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest48	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest49		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	794	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	794	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	794	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest49	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest5		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nulI]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	822	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	822	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	822	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest5	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest50		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	793	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	793	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	793	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest50	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest51		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nulI]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	793	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	793	(Introspected attribute maxTime)
method	null	(Introspected attribute method)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	793	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest51	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest52		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	792	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	792	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	792	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest52	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest53		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	792	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	792	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	792	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest53	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest54		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

lastRequestProcessingTime	791	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	791	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	791	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest54	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

  

worker="http-nio-80",name=HttpRequest55		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nul]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	792	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	792	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	792	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest55	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

  

worker="http-nio-80",name=HttpRequest56		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nul]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	793	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	793	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	793	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest56	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

  

worker="http-nio-80",name=HttpRequest57		
-----------------------------------------	--	--

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nul]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	793	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	793	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	793	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest57	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

## worker="http-nio-80",name=HttpRequest58

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nul]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	789	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	789	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	789	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest58	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

## worker="http-nio-80",name=HttpRequest59

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nul]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	788	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	788	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	788	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest59	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
<b>worker="http-nio-80",name=HttpRequest6</b>		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nul]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	821	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	821	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	821	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest6	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
<b>worker="http-nio-80",name=HttpRequest60</b>		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nul]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	790	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	790	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	790	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest60	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
<b>worker="http-nio-80",name=HttpRequest61</b>		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nul]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	787	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	787	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	787	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest61	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest62		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	786	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	786	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	786	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest62	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest63		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	789	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	789	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	789	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest63	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest64		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	1	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	785	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	785	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	785	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest64	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest65		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nulI]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	788	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	788	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	788	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest65	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest66		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	788	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	788	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	788	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest66	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest67		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	1	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nulI]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	788	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	788	(Introspected attribute maxTime)
method	null	(Introspected attribute method)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	788	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest67	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest68		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	787	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	787	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	787	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest68	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest69		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	786	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	786	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	786	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest69	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest7		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

lastRequestProcessingTime	821	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	821	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	821	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest7	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

  

worker="http-nio-80",name=HttpRequest70		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nul]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	786	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	786	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	786	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest70	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

  

worker="http-nio-80",name=HttpRequest71		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nul]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	785	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	785	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	785	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest71	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

  

worker="http-nio-80",name=HttpRequest72		
-----------------------------------------	--	--

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nul]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	785	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	785	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	785	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest72	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

## worker="http-nio-80",name=HttpRequest73

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nul]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	784	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	784	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	784	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest73	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

## worker="http-nio-80",name=HttpRequest74

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nul]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	784	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	784	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	784	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest74	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest75		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nul]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	783	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	783	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	783	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest75	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest76		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	1	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nul]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	782	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	782	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	782	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest76	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest77		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nul]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	783	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	783	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	783	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest77	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest78		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	782	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	782	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	782	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest78	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest79		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	1	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	782	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	782	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	782	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest79	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest80		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	821	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	821	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	821	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest8	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest80		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nul]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	776	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	776	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	776	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest80	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest81		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	776	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	776	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	776	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest81	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest82		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nul]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	775	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	775	(Introspected attribute maxTime)
method	null	(Introspected attribute method)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	775	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest82	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest83		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	773	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	773	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	773	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest83	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest84		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	1	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	774	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	774	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	774	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest84	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest85		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

lastRequestProcessingTime	773	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	773	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	773	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest85	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

  

worker="http-nio-80",name=HttpRequest86	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	1	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nul]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	773	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	773	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	773	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest86	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

  

worker="http-nio-80",name=HttpRequest87	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	1	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nul]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	772	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	772	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	772	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest87	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

  

worker="http-nio-80",name=HttpRequest88		
-----------------------------------------	--	--

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	4 277	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	1	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nul]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	0	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	776	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	798	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	60	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest88	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest89		
bytesReceived	1 548	(Introspected attribute bytesReceived)
bytesSent	56 004 448	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	940	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nul]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/demo/monitoring	(Introspected attribute maxRequestUri)
maxTime	23 149	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	535 572	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	343 187	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest89	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest90		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	1	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nul]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	820	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	820	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	820	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest90	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest90		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	1	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nul]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	769	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	769	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	769	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest90	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest91		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	1	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nul]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	768	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	768	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	768	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest91	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest92		
bytesReceived	2 766	(Introspected attribute bytesReceived)
bytesSent	214 502 709	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	2 404	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nul]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	0	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	15 719	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	1 385 186	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1 026 894	(Introspected attribute requestCount)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest92	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest93		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	1 765 238	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	24	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	34	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/demo/monitoring	(Introspected attribute maxRequestUri)
maxTime	1 131	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	11 004	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	6 440	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest93	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest94		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	93 779 962	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	1 350	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	39	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/demo/monitoring	(Introspected attribute maxRequestUri)
maxTime	14 713	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	469 622	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	330 065	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest94	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest95		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	25 888	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	1	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	770	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	883	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	43	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest95	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest96		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	6 011	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	3	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nulI]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	0	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	769	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	774	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	8	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest96	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest97		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[null]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	765	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	765	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	765	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest97	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest98		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nulI]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	764	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	764	(Introspected attribute maxTime)
method	null	(Introspected attribute method)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	764	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest98	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)
worker="http-nio-80",name=HttpRequest99		
bytesReceived	0	(Introspected attribute bytesReceived)
bytesSent	61	(Introspected attribute bytesSent)
contentLength	-1	(Introspected attribute contentLength)
currentQueryString	null	(Introspected attribute currentQueryString)
currentUri	null	(Introspected attribute currentUri)
errorCount	0	(Introspected attribute errorCount)
globalProcessor	BaseModelMbean[nul]	(Introspected attribute globalProcessor)
lastRequestProcessingTime	767	(Introspected attribute lastRequestProcessingTime)
maxRequestUri	/usage/stats	(Introspected attribute maxRequestUri)
maxTime	767	(Introspected attribute maxTime)
method	null	(Introspected attribute method)
modelerType	org.apache.coyote.RequestInfo	(Type of the modeled resource. Can be set only once)
processingTime	767	(Introspected attribute processingTime)
protocol	null	(Introspected attribute protocol)
remoteAddr	null	(Introspected attribute remoteAddr)
remoteAddrForwarded	null	(Introspected attribute remoteAddrForwarded)
requestBytesReceived	0	(Introspected attribute requestBytesReceived)
requestBytesSent	0	(Introspected attribute requestBytesSent)
requestCount	1	(Introspected attribute requestCount)
requestProcessingTime	0	(Introspected attribute requestProcessingTime)
rpName	Catalina:type=RequestProcessor,worker="http-nio-80",name=HttpRequest99	(Introspected attribute rpName)
serverPort	-1	(Introspected attribute serverPort)
stage	7	(Introspected attribute stage)
virtualHost	null	(Introspected attribute virtualHost)
workerThreadName	null	(Introspected attribute workerThreadName)

## Resource

resourcetype=Context,host=localhost,context=/demo,class=javax.sql.DataSource,name="jdbc/demo_javamelody"		
(Representation of a resource reference for a web application)		
auth	Container	(The authorization requirement for this resource)
description	Datasource	(The description of this resource)
name	jdbc/demo_javamelody	(The name of this resource)
scope	Shareable	(The sharing scope of this resource factory)
type	javax.sql.DataSource	(The type of this environment entry)

resourcetype=Global,class=org.apache.catalina.UserDatabase,name="UserDatabase"		
(Representation of a resource reference for a web application)		
auth	Container	(The authorization requirement for this resource)
description	User database that can be updated and saved	(The description of this resource)
name	UserDatabase	(The name of this resource)
scope	Shareable	(The sharing scope of this resource factory)
type	org.apache.catalina.UserDatabase	(The type of this environment entry)

## SSLHostConfig

ThreadPool="http-nio-80",name="_default_"		
(Representation of a resource reference for a web application)		
caCertificateFile	null	(Introspected attribute caCertificateFile)
caCertificatePath	null	(Introspected attribute caCertificatePath)
certificateChainFile	null	(Introspected attribute certificateChainFile)
certificateFile	null	(Introspected attribute certificateFile)
certificateKeyAlias	null	(Introspected attribute certificateKeyAlias)
certificateKeyFile	null	(Introspected attribute certificateKeyFile)
certificateKeyPassword	null	(Introspected attribute certificateKeyPassword)
certificateKeystoreFile	null	(Introspected attribute certificateKeystoreFile)
certificateKeystorePassword	null	(Introspected attribute certificateKeystorePassword)
certificateKeystoreProvider	null	(Introspected attribute certificateKeystoreProvider)
certificateKeystoreType	null	(Introspected attribute certificateKeystoreType)
certificateRevocationListFile	null	(Introspected attribute certificateRevocationListFile)
certificateRevocationListPath	null	(Introspected attribute certificateRevocationListPath)
certificateVerificationAsString	NONE	(Introspected attribute certificateVerificationAsString)
certificateVerificationDepth	10	(Introspected attribute certificateVerificationDepth)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

certificateVerificationDepthConfigured	false	(Introspected attribute certificateVerificationDepthConfigured)
ciphers	HIGH::aNULL::eNULL::EXPORT::DES::RC4::MD5::kRSA	(Introspected attribute ciphers)
disableCompression	true	(Introspected attribute disableCompression)
disableSessionTickets	false	(Introspected attribute disableSessionTickets)
enabledCiphers	null	(Introspected attribute enabledCiphers)
enabledProtocols	null	(Introspected attribute enabledProtocols)
honorCipherOrder	false	(Introspected attribute honorCipherOrder)
hostName	_default_	(Introspected attribute hostName)
insecureRenegotiation	false	(Introspected attribute insecureRenegotiation)
keyManagerAlgorithm	SunX509	(Introspected attribute keyManagerAlgorithm)
modelerType	org.apache.tomcat.util.net.SSLHostConfig	(Type of the modeled resource. Can be set only once)
objectName	Catalina:type=SSLHostConfig,ThreadPool="http-nio-80",name="_default_"	(Introspected attribute objectName)
openSslConf	null	(Introspected attribute openSslConf)
openSslConfContext	0	(Introspected attribute openSslConfContext)
openSslContext	0	(Introspected attribute openSslContext)
revocationEnabled	false	(Introspected attribute revocationEnabled)
sessionCacheSize	-1	(Introspected attribute sessionCacheSize)
sessionTimeout	86 400	(Introspected attribute sessionTimeout)
sslProtocol	TLS	(Introspected attribute sslProtocol)
trustManagerClassName	null	(Introspected attribute trustManagerClassName)
truststoreAlgorithm	PKIX	(Introspected attribute truststoreAlgorithm)
truststoreFile	null	(Introspected attribute truststoreFile)
truststorePassword	null	(Introspected attribute truststorePassword)
truststoreProvider	null	(Introspected attribute truststoreProvider)
truststoreType	JKS	(Introspected attribute truststoreType)

## Server

(Standard Server Component)		
address	localhost	(The address on which we wait for shutdown commands.)
managedResource	StandardServer[8005]	(The managed resource this MBean is associated with)
modelerType	org.apache.catalina.core.StandardServer	(Type of the modeled resource. Can be set only once)
port	8 005	(TCP port (excluding any offset) for shutdown messages)
portOffset	0	(The offset applied to port and to the port attributes of any nested connectors)
portWithOffset	8 005	(Actual TCP port (including any offset) for shutdown messages)
serverBuilt	Mar 11 2020 09:31:38 UTC	(Tomcat server built timestamp)
serverInfo	Apache Tomcat/9.0.33	(Tomcat server release identifier)
serverNumber	9.0.33.0	(Tomcat server's version number)
serviceNames	[Catalina:type=Service]	(Object names of all services we know about)
shutdown	SHUTDOWN	(Shutdown password)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

## Service

(Standard Service Component)		
connectorNames	[Catalina:type=Connector,port=80]	(ObjectNames of the connectors)
managedResource	StandardService[Catalina]	(The managed resource this MBean is associated with)
modelerType	org.apache.catalina.core.StandardService	(Type of the modeled resource. Can be set only once)
name	Catalina	(Unique name of this Service)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

## Servlet

WebModule=/localhost/,name=default,J2EEApplication=none,J2EEServer=none		
(Wrapper that represents an individual servlet definition)		
asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	3 434	(Error count)
loadOnStartup	1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	0	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	13	(Maximum processing time of a request)
minTime	0	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=/localhost/,name=default,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	625	(Total execution time of the servlet's service method)
requestCount	3 434	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	org.apache.catalina.servlets.DefaultServlet	(The run-as identity for this servlet.)
singleThreadModel	false	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

## WebModule=/localhost/,name=jsp,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	1	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	7	(Error count)
loadOnStartup	3	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	1	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	1 147	(Maximum processing time of a request)
minTime	0	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=/localhost/,name=jsp,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	2 137	(Total execution time of the servlet's service method)
requestCount	2 248	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
serverClass	org.apache.jasper.servlet.JspServlet	(The run-as identity for this servlet.)
singleThreadModel	false	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

## WebModule=/localhost/demo,name=AdresseService,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	-1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	0	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	0	(Maximum processing time of a request)
minTime	9 223 372 036 854 775 807	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=/localhost/demo,name=AdresseService,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	0	(Total execution time of the servlet's service method)
requestCount	0	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
serverClass	fr.appwhite1.server.business.annuaire.AdresseGwtServiceImpl	(The run-as identity for this servlet.)
singleThreadModel	null	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

## WebModule=/localhost/demo,name=AuthentificationService,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	1 049	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	-1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	1 049	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	12 329	(Maximum processing time of a request)
minTime	1	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=/localhost/demo,name=AuthentificationService,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	37 131	(Total execution time of the servlet's service method)
requestCount	76	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
serverClass	fr.appwhite1.server.business.secu.AuthentificationGwtServiceImpl	(The run-as identity for this servlet.)
singleThreadModel	false	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

## WebModule=/localhost/demo,name=BuildInfoServlet,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	1	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	1	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	0	(Maximum processing time of a request)
minTime	9 223 372 036 854 775 807	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=/localhost/demo,name=BuildInfoServlet,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	0	(Total execution time of the servlet's service method)
requestCount	0	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
serverClass	fr.appwhite1.Appli1BuildInfoServlet	(The run-as identity for this servlet.)
singleThreadModel	false	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

## WebModule=/localhost/demo,name=CompetenceService,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	-1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	0	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	0	(Maximum processing time of a request)
minTime	9 223 372 036 854 775 807	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=/localhost/demo,name=CompetenceService,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	0	(Total execution time of the servlet's service method)
requestCount	0	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
serverClass	fr.appwhite1.server.business.annuaire.CompetenceGwtServiceImpl	(The run-as identity for this servlet.)
singleThreadModel	null	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

## WebModule=/localhost/demo,name=GradeService,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	1	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	-1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	1	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	4 974	(Maximum processing time of a request)
minTime	1	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=/localhost/demo,name=GradeService,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	5 063	(Total execution time of the servlet's service method)
requestCount	31	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
serverClass	fr.referentiel.server.business.ref.GradeGwtServiceImpl	(The run-as identity for this servlet.)
singleThreadModel	false	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

## WebModule=/localhost/demo,name=MailService,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)		
asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	-1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	0	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	0	(Maximum processing time of a request)
minTime	9 223 372 036 854 775 807	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=/localhost/demo,name=MailService,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	0	(Total execution time of the servlet's service method)
requestCount	0	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
serverClass	fr.appwhite1.server.business.annuaire.MailGwtServiceImpl	(The run-as identity for this servlet.)
singleThreadModel	null	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

## WebModule=/localhost/demo,name=PermissionService,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)		
asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	-1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	0	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	0	(Maximum processing time of a request)
minTime	9 223 372 036 854 775 807	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=/localhost/demo,name=PermissionService,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	0	(Total execution time of the servlet's service method)
requestCount	0	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
serverClass	fr.appwhite1.server.business.secu.PermissionGwtServiceImpl	(The run-as identity for this servlet.)
singleThreadModel	null	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

## WebModule=/localhost/demo,name=PersonneService,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)		
asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	1	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	-1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	1	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	17 950	(Maximum processing time of a request)
minTime	2	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=/localhost/demo,name=PersonneService,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	20 011	(Total execution time of the servlet's service method)
requestCount	49	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
serverClass	fr.appwhite1.server.business.annuaire.PersonneGwtServiceImpl	(The run-as identity for this servlet.)
singleThreadModel	false	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

## WebModule=/localhost/demo,name=PrintUtilsService,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	-1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	0	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	0	(Maximum processing time of a request)
minTime	9 223 372 036 854 775 807	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=/localhost/demo,name=Print UtilsService,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	0	(Total execution time of the servlet's service method)
requestCount	0	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
serverClass	fr.appwhite1.server.business.utils.PrintUtilsGwtServiceImpl	(The run-as identity for this servlet.)
singleThreadModel	null	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

## WebModule=/localhost/demo,name=RoleService,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	-1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	0	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	0	(Maximum processing time of a request)
minTime	9 223 372 036 854 775 807	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=/localhost/demo,name=Role Service,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	0	(Total execution time of the servlet's service method)
requestCount	0	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
serverClass	fr.appwhite1.server.business.secu.RoleGwtServiceImpl	(The run-as identity for this servlet.)
singleThreadModel	null	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

## WebModule=/localhost/demo,name=TelephoneService,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	-1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	0	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	0	(Maximum processing time of a request)
minTime	9 223 372 036 854 775 807	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=/localhost/demo,name=Tele phoneService,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	0	(Total execution time of the servlet's service method)
requestCount	0	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
serverClass	fr.appwhite1.server.business.annuaire.TelephoneGwtServiceImpl	(The run-as identity for this servlet.)
singleThreadModel	null	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

## WebModule=/localhost/demo,name=UtilisateurService,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)		
asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	-1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	0	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	0	(Maximum processing time of a request)
minTime	9 223 372 036 854 775 807	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=/localhost/demo,name=UtilisateurService,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	0	(Total execution time of the servlet's service method)
requestCount	0	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
serverClass	fr.appwhite1.server.business.secu.UtilisateurGwtServiceImpl	(The run-as identity for this servlet.)
singleThreadModel	null	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

## WebModule=/localhost/demo,name=default,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)		
asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	2	(Time taken to load the Servlet class)
countAllocated	1	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	2 619	(Error count)
loadOnStartup	1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	2	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	40 359	(Maximum processing time of a request)
minTime	0	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=/localhost/demo,name=default,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	4 161 410	(Total execution time of the servlet's service method)
requestCount	40 452	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
serverClass	org.apache.catalina.servlets.DefaultServlet	(The run-as identity for this servlet.)
singleThreadModel	false	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

## WebModule=/localhost/demo,name=jsp,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)		
asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	3	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	28	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	0	(Maximum processing time of a request)
minTime	9 223 372 036 854 775 807	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=/localhost/demo,name=jsp,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	0	(Total execution time of the servlet's service method)
requestCount	0	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
serverClass	org.apache.jasper.servlet.JspServlet	(The run-as identity for this servlet.)
singleThreadModel	false	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

## WebModule=/localhost/downloads,name=default,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)		
asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	12	(Error count)
loadOnStartup	1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	0	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	2	(Maximum processing time of a request)
minTime	0	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=/localhost/downloads,name=default,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	5	(Total execution time of the servlet's service method)
requestCount	13	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	org.apache.catalina.servlets.DefaultServlet	(The run-as identity for this servlet.)
singleThreadModel	false	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

## WebModule=/localhost/downloads,name=jsp,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)		
asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	3	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	7	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	0	(Maximum processing time of a request)
minTime	9 223 372 036 854 775 807	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=/localhost/downloads,name=jsp,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	0	(Total execution time of the servlet's service method)
requestCount	0	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	org.apache.jasper.servlet.JspServlet	(The run-as identity for this servlet.)
singleThreadModel	false	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

## WebModule=/localhost/usage,name=admin,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)		
asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	1	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	2	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	0	(Maximum processing time of a request)
minTime	9 223 372 036 854 775 807	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=/localhost/usage,name=admin,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	0	(Total execution time of the servlet's service method)
requestCount	0	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
servletClass	net.bull.javamelody.usagestats.AdminServlet	(The run-as identity for this servlet.)
singleThreadModel	false	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

## WebModule=/localhost/usage,name=default,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	0	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	4	(Maximum processing time of a request)
minTime	0	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=/localhost/usage,name=default,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	18	(Total execution time of the servlet's service method)
requestCount	22	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
serverClass	org.apache.catalina.servlets.DefaultServlet	(The run-as identity for this servlet.)
singleThreadModel	false	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

## WebModule=/localhost/usage,name=jsp,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	0	(Error count)
loadOnStartup	3	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	1	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	0	(Maximum processing time of a request)
minTime	9 223 372 036 854 775 807	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=/localhost/usage,name=jsp,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	0	(Total execution time of the servlet's service method)
requestCount	0	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
serverClass	org.apache.jasper.servlet.JspServlet	(The run-as identity for this servlet.)
singleThreadModel	false	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

## WebModule=/localhost/usage,name=usagestats,J2EEApplication=none,J2EEServer=none

(Wrapper that represents an individual servlet definition)

asyncSupported	false	(Async support)
available	0	(The date and time at which this servlet will become available (in milliseconds since the epoch), or zero if the servlet is available. If this value equals Long.MAX_VALUE, the unavailability of this servlet is considered permanent.)
backgroundProcessorDelay	-1	(The processor delay for this component.)
classLoadTime	0	(Time taken to load the Servlet class)
countAllocated	0	(The count of allocations that are currently active (even if they are for the same instance, as will be true on a non-STM servlet).)
errorCount	41	(Error count)
loadOnStartup	1	(The load-on-startup order value (negative value means load on first call) for this servlet.)
loadTime	368 602	(Time taken to load and initialise the Servlet)
maxInstances	20	(Maximum number of STM instances.)
maxTime	20 001	(Maximum processing time of a request)
minTime	0	(Minimum processing time of a request)
modelerType	org.apache.catalina.core.StandardWrapper	(Type of the modeled resource. Can be set only once)
objectName	Catalina:j2eeType=Servlet,WebModule=/localhost/usage,name=usagestats,J2EEApplication=none,J2EEServer=none	(Name of the object)
processingTime	1 548 278	(Total execution time of the servlet's service method)
requestCount	6 814 545	(Number of requests processed by this wrapper)
runAs	null	(The run-as identity for this servlet.)
serverClass	net.bull.javamelody.usagestats.UsageStatsServlet	(The run-as identity for this servlet.)
singleThreadModel	false	(Does this servlet implement the SingleThreadModel interface?)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

## StringCache

accessCount	27 504 518	(Introspected attribute accessCount)
byteEnabled	true	(Introspected attribute byteEnabled)
cacheSize	200	(Introspected attribute cacheSize)
charEnabled	false	(Introspected attribute charEnabled)
hitCount	20 543 691	(Introspected attribute hitCount)
modelerType	org.apache.tomcat.util.buf.StringCache	(Type of the modeled resource. Can be set only once)
trainThreshold	20 000	(Introspected attribute trainThreshold)

## ThreadPool

name="http-nio-80"		
acceptCount	100	
acceptorThreadCount	1	
acceptorThreadPriority	5	
alpnSupported	false	
bindOnInit	true	
connectionCount	94	
connectionLinger	-1	
connectionTimeout	20 000	
currentThreadCount	61	
currentThreadsBusy	1	
daemon	true	
defaultSSLHostConfigName	_default_	
deferAccept	false	
domain	Catalina	
executorTerminationTimeoutMillis	5 000	
keepAliveCount	1	
keepAliveTimeout	20 000	
localPort	80	
maxConnections	8 192	
maxKeepAliveRequests	100	
maxThreads	200	
minSpareThreads	10	
modelerType	org.apache.tomcat.util.net.NioEndpoint	
name	http-nio-80	
paused	false	
pollerThreadCount	1	
pollerThreadPriority	5	
port	80	
portOffset	0	
portWithOffset	80	
running	true	
sSLEnabled	false	
selectorTimeout	1 000	
sniParseLimit	65 536	
sslImplementation	null	
sslImplementationName	null	
tcpNoDelay	true	
threadPriority	5	
useInheritedChannel	false	
useSendfile	true	

## name="http-nio-80",subType=SocketProperties

appReadBufSize	8 192	(Introspected attribute appReadBufSize)
appWriteBufSize	8 192	(Introspected attribute appWriteBufSize)
bufferPool	500	(Introspected attribute bufferPool)
bufferPoolSize	104 857 600	(Introspected attribute bufferPoolSize)
directBuffer	false	(Introspected attribute directBuffer)
directBufferPool	500	(Introspected attribute directBufferPool)
directSslBuffer	false	(Introspected attribute directSslBuffer)
eventCache	500	(Introspected attribute eventCache)
modelerType	org.apache.tomcat.util.net.SocketProperties	(Type of the modeled resource. Can be set only once)
processorCache	500	(Introspected attribute processorCache)
soLingerOn	false	(Introspected attribute soLingerOn)
soLingerTime	-1	(Introspected attribute soLingerTime)
soTimeout	20 000	(Introspected attribute soTimeout)
tcpNoDelay	true	(Introspected attribute tcpNoDelay)
timeoutInterval	1 000	(Introspected attribute timeoutInterval)
unlockTimeout	250	(Introspected attribute unlockTimeout)

## UtilityExecutor

activeCount	0	(Introspected attribute activeCount)
completedTaskCount	1 252 378	(Introspected attribute completedTaskCount)
continueExistingPeriodicTasksAfterShutdownPolicy	false	(Introspected attribute continueExistingPeriodicTasksAfterShutdownPolicy)
corePoolSize	2	(Introspected attribute corePoolSize)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

executeExistingDelayedTasksAfterShutdownPolicy	false	(Introspected attribute executeExistingDelayedTasksAfterShutdownPolicy)
largestPoolSize	2	(Introspected attribute largestPoolSize)
maximumPoolSize	2 147 483 647	(Introspected attribute maximumPoolSize)
modelerType	java.util.concurrent.ScheduledThreadPoolExecutor	(Type of the modeled resource. Can be set only once)
poolSize	2	(Introspected attribute poolSize)
removeOnCancelPolicy	true	(Introspected attribute removeOnCancelPolicy)
shutdown	false	(Introspected attribute shutdown)
taskCount	1 252 384	(Introspected attribute taskCount)
terminated	false	(Introspected attribute terminated)
terminating	false	(Introspected attribute terminating)
<b>Valve</b>		
host=localhost,context=/,name=NonLoginAuthenticator		
(An Authenticator and Valve implementation that checks only security constraints not involving user authentication)		
cache	true	(Should we cache authenticated Principals if the request is part of an HTTP session?)
changeSessionIdOnAuthentication	true	(Controls if the session ID is changed if a session exists at the point where users are authenticated)
className	org.apache.catalina.authenticator.NonLoginAuthenticator	(Fully qualified class name of the managed object)
disableProxyCaching	true	(Controls the caching of pages that are protected by security constraints)
modelerType	org.apache.catalina.authenticator.NonLoginAuthenticator	(Type of the modeled resource. Can be set only once)
securePagesWithPragma	false	(Controls the caching of pages that are protected by security constraints)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
host=localhost,context=/,name=StandardContextValve		
(Valve that implements the default basic behavior for the StandardContext container implementation)		
asyncSupported	true	(Does this valve support async reporting?)
className	org.apache.catalina.core.StandardContextValve	(Fully qualified class name of the managed object)
modelerType	org.apache.catalina.core.StandardContextValve	(Type of the modeled resource. Can be set only once)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
host=localhost,context=/demo,name=NonLoginAuthenticator		
(An Authenticator and Valve implementation that checks only security constraints not involving user authentication)		
cache	true	(Should we cache authenticated Principals if the request is part of an HTTP session?)
changeSessionIdOnAuthentication	true	(Controls if the session ID is changed if a session exists at the point where users are authenticated)
className	org.apache.catalina.authenticator.NonLoginAuthenticator	(Fully qualified class name of the managed object)
disableProxyCaching	true	(Controls the caching of pages that are protected by security constraints)
modelerType	org.apache.catalina.authenticator.NonLoginAuthenticator	(Type of the modeled resource. Can be set only once)
securePagesWithPragma	false	(Controls the caching of pages that are protected by security constraints)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
host=localhost,context=/demo,name=StandardContextValve		
(Valve that implements the default basic behavior for the StandardContext container implementation)		
asyncSupported	true	(Does this valve support async reporting?)
className	org.apache.catalina.core.StandardContextValve	(Fully qualified class name of the managed object)
modelerType	org.apache.catalina.core.StandardContextValve	(Type of the modeled resource. Can be set only once)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
host=localhost,context=/downloads,name=NonLoginAuthenticator		
(An Authenticator and Valve implementation that checks only security constraints not involving user authentication)		
cache	true	(Should we cache authenticated Principals if the request is part of an HTTP session?)
changeSessionIdOnAuthentication	true	(Controls if the session ID is changed if a session exists at the point where users are authenticated)
className	org.apache.catalina.authenticator.NonLoginAuthenticator	(Fully qualified class name of the managed object)
disableProxyCaching	true	(Controls the caching of pages that are protected by security constraints)
modelerType	org.apache.catalina.authenticator.NonLoginAuthenticator	(Type of the modeled resource. Can be set only once)
securePagesWithPragma	false	(Controls the caching of pages that are protected by security constraints)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
host=localhost,context=/downloads,name=StandardContextValve		
(Valve that implements the default basic behavior for the StandardContext container implementation)		
asyncSupported	true	(Does this valve support async reporting?)
className	org.apache.catalina.core.StandardContextValve	(Fully qualified class name of the managed object)
modelerType	org.apache.catalina.core.StandardContextValve	(Type of the modeled resource. Can be set only once)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
host=localhost,context=/usage,name=NonLoginAuthenticator		
(An Authenticator and Valve implementation that checks only security constraints not involving user authentication)		
cache	true	(Should we cache authenticated Principals if the request is part of an HTTP session?)
changeSessionIdOnAuthentication	true	(Controls if the session ID is changed if a session exists at the point where users are authenticated)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

className	org.apache.catalina.authenticator.NonLoginAuthenticator	(Fully qualified class name of the managed object)
disableProxyCaching	true	(Controls the caching of pages that are protected by security constraints)
modelerType	org.apache.catalina.authenticator.NonLoginAuthenticator	(Type of the modeled resource. Can be set only once)
securePagesWithPragma	false	(Controls the caching of pages that are protected by security constraints)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
<b>host=localhost,context=/usage,name=StandardContextValve</b>		
	(Valve that implements the default basic behavior for the StandardContext container implementation)	
asyncSupported	true	(Does this valve support async reporting?)
className	org.apache.catalina.core.StandardContextValve	(Fully qualified class name of the managed object)
modelerType	org.apache.catalina.core.StandardContextValve	(Type of the modeled resource. Can be set only once)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
<b>host=localhost,name=AccessLogValve</b>		
	(Valve that generates a web server access log)	
asyncSupported	true	(Does this valve support async reporting.)
buffered	true	(Flag to buffering.)
checkExists	false	(Check for file existence before logging.)
className	org.apache.catalina.valves.AccessLogValve	(Fully qualified class name of the managed object)
condition	null	(The value to look for conditional logging. The same as conditionUnless.)
conditionIf	null	(The value to look for conditional logging.)
conditionUnless	null	(The value to look for conditional logging.)
directory	logs	(The directory in which log files are created)
enabled	true	(Enable Access Logging)
encoding	null	(Character set used to write the log file)
fileDateFormat	.yyyy-MM-dd	(The format for the date for date based log rotation)
locale	en_US	(The locale used to format timestamps in the access log lines)
modelerType	org.apache.catalina.valves.AccessLogValve	(Type of the modeled resource. Can be set only once)
pattern	%h %l %u %t "%r" %s %b	(The pattern used to format our access log lines)
prefix	localhost_access_log	(The prefix that is added to log file filenames)
renameOnRotate	false	(Flag to defer inclusion of the date stamp in the log file name until rotation.)
rotatable	true	(Flag to indicate automatic log rotation.)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
suffix	.txt	(The suffix that is added to log file filenames)
<b>host=localhost,name=ErrorReportValve</b>		
	(Implementation of a Valve that outputs HTML error pages)	
asyncSupported	true	(Does this valve support async reporting.)
className	org.apache.catalina.valves.ErrorReportValve	(Fully qualified class name of the managed object)
modelerType	org.apache.catalina.valves.ErrorReportValve	(Type of the modeled resource. Can be set only once)
showReport	true	(Enables/Disables full error reports)
showServerInfo	true	(Enables/Disables server info on error pages)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
<b>host=localhost,name=StandardHostValve</b>		
	(Valve that implements the default basic behavior for the StandardHost container implementation)	
asyncSupported	true	(Does this valve support async reporting?)
className	org.apache.catalina.core.StandardHostValve	(Fully qualified class name of the managed object)
modelerType	org.apache.catalina.core.StandardHostValve	(Type of the modeled resource. Can be set only once)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
<b>name=StandardEngineValve</b>		
	(Valve that implements the default basic behavior for the StandardEngine container implementation)	
asyncSupported	true	(Does this valve support async reporting?)
className	org.apache.catalina.core.StandardEngineValve	(Fully qualified class name of the managed object)
modelerType	org.apache.catalina.core.StandardEngineValve	(Type of the modeled resource. Can be set only once)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
<b>WebModule</b>		
<b>name=/localhost/,J2EEApplication=none,J2EEServer=none</b>		
	(Standard Context Component)	
altDDName	null	(The alternate deployment descriptor name.)
antiResourceLocking	false	(Take care to not lock resources)
baseName	ROOT	(The base name used for directories, WAR files (with .war appended) and context.xml files (with .xml appended).)
children	[Catalina:j2eeType=Servlet,WebModule=/localhost/,name=default,J2EEApplication=none,J2EEServer=none,Catalina:j2eeType=Servlet,WebModule=/localhost/,name=jsp,J2EEApplication=none,J2EEServer=none]	(Object names of all children)
clearReferencesRmiTargets	true	(Should Tomcat look for memory leaks in RMI Targets and clear them if found as a work around for application coding errors?)
clearReferencesStopThreads	false	(Should Tomcat attempt to terminate threads that have been started by the web application? Advisable to be used only in a development environment.)
clearReferencesStopTimerThreads	false	(Should Tomcat attempt to terminate TimerThreads that have been started by the web application? Advisable to be used only in a development environment.)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

clearReferencesThreadLocals	true	(Should Tomcat attempt to clear ThreadLocal variables that have been populated with classes loaded by the web application?)
configFile	null	(Location of the context.xml resource or file)
configured	true	(The correctly configured flag for this Context.)
cookies	true	(Should we attempt to use cookies for session id communication?)
crossContext	false	(Should we allow the ServletContext.getContext() method to access the context of other web applications in this server?)
defaultContextXml	null	(Location of the default context.xml resource or file)
defaultWebXml	null	(Location of the default web.xml resource or file)
delegate	false	
displayName	null	(The display name of this web application)
distributable	false	(The distributable flag for this web application.)
docBase	ROOT	(The document root for this web application)
encodedPath		(The encoded path)
errorCount	3 441	(Cumulative error count of all servlets in this context)
ignoreAnnotations	false	(Ignore annotations flag.)
instanceManager	org.apache.catalina.core.DefaultInstanceManager@1e565df8	(Object that creates and destroys servlets, filters, and listeners. Include dependency injection and postConstruct/preDestroy handling)
javaVMs	null	(The Java virtual machines on which this module is running)
loader	WebappLoader[StandardEngine[Catalina].StandardHost[localhost].StandardContext[]]	(Associated loader.)
logEffectiveWebXml	false	(Should the effective web.xml be logged when the context starts?)
logger	org.apache.juli.logging.DirectJDKLog@3cf92151	(Associated logger.)
managedResource	StandardEngine[Catalina].StandardHost[localhost].StandardContext[]	(The managed resource this MBean is associated with)
manager	StandardManager[StandardEngine[Catalina].StandardHost[localhost].StandardContext[]]	(Associated manager.)
mapperContextRootRedirectEnabled	true	(Should the Mapper be used for context root redirects)
mapperDirectoryRedirectEnabled	false	(Should the Mapper be used for directory redirects)
maxTime	1 147	(Maximum execution time of all servlets in this context)
minTime	0	(Minimum execution time of all servlets in this context)
modelerType	org.apache.catalina.core.StandardContext	(Type of the modeled resource. Can be set only once)
name		(The name of this Context)
namingContextListener	org.apache.catalina.core.NamingContextListener@1512de2a	(Associated naming context listener.)
objectName	Catalina:j2eeType=WebModule,name=/localhost,J2EEApplication=none,J2EEServer=none	(Name of the object)
originalDocBase	null	(The original document root for this web application)
override	false	(The default context.xml override flag for this web application)
parentClassLoader	java.net.URLClassLoader@6536e911	(Parent class loader.)
path		(The context path for this Context)
paused	false	(The request processing pause flag (while reloading occurs))
privileged	false	(Access to tomcat internals)
processingTime	2 762	(Cumulative execution times of all servlets in this context)
publicId	null	(The public identifier of the DTD for the web application deployment descriptor version that is being parsed)
realm	LockOutRealm[StandardEngine[Catalina]]	(Associated realm.)
reloadable	false	(The reloadable flag for this web application)
renewThreadsWhenStoppingContext	true	(Should Tomcat renew the threads of the thread pool when the application is stopped to avoid memory leaks because of uncleaned ThreadLocal variables.)
requestCount	5 682	(Cumulative request count of all servlets in this context)
server	null	(The J2EE Server this module is deployed on)
sessionCookieDomain	null	(The domain to use for session cookies.'null' indicates that the domain is controlled by the application.)
sessionCookieName	null	(The name to use for session cookies.'null' indicates that the name is controlled by the application.)
sessionCookiePath	null	(The path to use for session cookies.'null' indicates that the path is controlled by the application.)
sessionTimeout	30	(The session timeout (in minutes) for this web application)
startTime	1 713 827 260 523	(Time (in milliseconds since January 1, 1970, 00:00:00) when this context was started)
startupTime	0	(Time (in milliseconds) it took to start this context)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
swallowOutput	false	(Flag to set to cause the system.out and system.err to be redirected to the logger when executing a servlet)
tldScanTime	0	(Time spend scanning jars for TLDs for this context)
tldValidation	false	(Should the parsing of *.tld files be performed by a validating parser?)
unloadDelay	2 000	(Amount of ms that the container will wait for servlets to unload)
unpackWAR	true	(Unpack WAR property)
useHttpOnly	true	(Indicates that session cookies should use HttpOnly)
useNaming	true	(Create a JNDI naming context for this application?)
useRelativeRedirects	true	(When generating location headers for 302 responses, should a relative URI be used?)
webappVersion		(The version of this web application - used in parallel deployment to differentiate different versions of the same web application)
welcomeFiles	[index.html, index.htm, index.jsp]	(The welcome files for this context)
workDir	work/Catalina/localhost/ROOT	(The pathname to the work directory for this context)
xmlNamespaceAware	false	(Should the parsing of web.xml and web-fragment.xml files be performed by a namespace aware parser?)
xmlValidation	false	(Should the parsing of web.xml and web-fragment.xml files be performed by a validating parser?)

name=/localhost/demo,J2EEApplication=none,J2EEServer=none

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

(Standard Context Component)		
altDDName	null	(The alternate deployment descriptor name.)
antiResourceLocking	false	(Take care to not lock resources)
baseName	demo	(The base name used for directories, WAR files (with .war appended) and context.xml files (with .xml appended.))
children	[Catalina];2eeType=Servlet,WebModule=/localhost/demo,name=CompetenceService,J2EEApplication=None,J2EEServer=None,Catalina];2eeType=Servlet,WebModule=/localhost/demo,name=Gradeservice,J2EEApplication=None,J2EEServer=None,Catalina];2eeType=Servlet,WebModule=/localhost/demo,name=PersonneService,J2EEApplication=None,J2EEServer=None,Catalina];2eeType=Servlet,WebModule=/localhost/demo,name=PrintUtilisService,J2EEApplication=None,J2EEServer=None,Catalina];2eeType=Servlet,WebModule=/localhost/demo,name=AdresseService,J2EEApplication=None,J2EEServer=None,Catalina];2eeType=Servlet,WebModule=/localhost/demo,name=UtilisateurService,J2EEApplication=None,J2EEServer=None,Catalina];2eeType=Servlet,WebModule=/localhost/demo,name=jsp,J2EEApplication=None,J2EEServer=None,Catalina];2eeType=Servlet,WebModule=/localhost/demo,name=BilletterieService,J2EEApplication=None,J2EEServer=None,Catalina];2eeType=Servlet,WebModule=/localhost/demo,name=PermissionService,J2EEApplication=None,J2EEServer=None,Catalina];2eeType=Servlet,WebModule=/localhost/demo,name=defaut,J2EEApplication=None,J2EEServer=None,Catalina];2eeType=Servlet,WebModule=/localhost/demo,name=MailService,J2EEApplication=None,J2EEServer=None,Catalina];2eeType=Servlet,WebModule=/localhost/demo,name=RoleService,J2EEApplication=None,J2EEServer=None,Catalina];2eeType=Servlet,WebModule=/localhost/demo,name=TelephoneService,J2EEApplication=None,J2EEServer=None,Catalina];2eeType=Servlet,WebModule=/localhost/demo,name=AuthentificationService,J2EEApplication=None,J2EEServer=None]	(Object names of all children)
clearReferencesRmiTargets	true	(Should Tomcat look for memory leaks in RMI Targets and clear them if found as a work around for application coding errors?)
clearReferencesStopThreads	false	(Should Tomcat attempt to terminate threads that have been started by the web application? Advisable to be used only in a development environment.)
clearReferencesStopTimerThreads	false	(Should Tomcat attempt to terminate TimerThreads that have been started by the web application? Advisable to be used only in a development environment.)
clearReferencesThreadLocals	true	(Should Tomcat attempt to clear ThreadLocal variables that have been populated with classes loaded by the web application?)
configFile	file:/opt/apache-tomcat-9.0.33/conf/Catalina/localhost/demo.xml	(Location of the context.xml resource or file)
configured	true	(The correctly configured flag for this Context.)
cookies	true	(Should we attempt to use cookies for session id communication?)
crossContext	false	(Should we allow the ServletContext.getContext() method to access the context of other web applications in this server?)
defaultContextXml	null	(Location of the default context.xml resource or file)
defaultWebXml	null	(Location of the default web.xml resource or file)
delegate	false	
displayName	null	(The display name of this web application)
distributable	false	(The distributable flag for this web application.)
docBase	demo.war	(The document root for this web application)
encodedPath	/demo	(The encoded path)
errorCount	2 619	(Cumulative error count of all servlets in this context)
ignoreAnnotations	false	(Ignore annotations flag.)
instanceManager	org.apache.catalina.core.DefaultInstanceManager@4ddab6d8	(Object that creates and destroys servlets, filters, and listeners. Include dependency injection and postConstruct/preDestroy handling)
javaVMS	null	(The Java virtual machines on which this module is running)
loader	WebappLoader[StandardEngine[Catalina].StandardHost[localhost].StandardContext[/demo]]	(Associated loader.)
logEffectiveWebXml	false	(Should the effective web.xml be logged when the context starts?)
logger	org.apache.juli.logging.DirectJDKLog@47c51cb7	(Associated logger.)
managedResource	StandardEngine[Catalina].StandardHost[localhost].StandardContext[/demo]	(The managed resource this MBean is associated with)
manager	StandardManager[StandardEngine[Catalina].StandardHost[localhost].StandardContext[/demo]]	(Associated manager.)
mapperContextRootRedirectEnabled	true	(Should the Mapper be used for context root redirects)
mapperDirectoryRedirectEnabled	false	(Should the Mapper be used for directory redirects)
maxTime	40 359	(Maximum execution time of all servlets in this context)
minTime	0	(Minimum execution time of all servlets in this context)
modelerType	org.apache.catalina.core.StandardContext	(Type of the modeled resource. Can be set only once)
name	/demo	(The name of this Context)
namingContextListener	org.apache.catalina.core.NamingContextListener@3c49c756	(Associated naming context listener.)
objectName	Catalina];2eeType=WebModule,name=/localhost/demo,J2EEApplication=None,J2EEServer=None	(Name of the object)
originalDocBase	/opt/apache-tomcat-9.0.33/webapps/demo	(The original document root for this web application)
override	false	(The default context.xml override flag for this web application)
parentClassLoader	java.net.URLClassLoader@6536e911	(Parent class loader.)
path	/demo	(The context path for this Context)
paused	false	(The request processing pause flag (while reloading occurs))
privileged	false	(Access to tomcat internals)
processingTime	4 223 615	(Cumulative execution times of all servlets in this context)
publicId	null	(The public identifier of the DTD for the web application deployment descriptor version that is being parsed)
realm	LockOutRealm[StandardEngine[Catalina]]	(Associated realm.)
reloadable	false	(The reloadable flag for this web application)
renewThreadsWhenStoppingContext	true	(Should Tomcat renew the threads of the thread pool when the application is stopped to avoid memory leaks because of uncleaned ThreadLocal variables.)
requestCount	40 608	(Cumulative request count of all servlets in this context)
server	null	(The J2EE Server this module is deployed on)
sessionCookieDomain	null	(The domain to use for session cookies.'null' indicates that the domain is controlled by the application.)
sessionCookieName	null	(The name to use for session cookies.'null' indicates that the name is controlled by the application.)
sessionCookiePath	null	(The path to use for session cookies.'null' indicates that the path is controlled by the application.)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

sessionTimeout	30	(The session timeout (in minutes) for this web application)
startTime	1 713 826 887 843	(Time (in milliseconds since January 1, 1970, 00:00:00) when this context was started)
startupTime	2 067	(Time (in milliseconds) it took to start this context)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
swallowOutput	false	(Flag to set to cause the system.out and system.err to be redirected to the logger when executing a servlet)
tldScanTime	0	(Time spend scanning jars for TLDs for this context)
tldValidation	false	(Should the parsing of *.tld files be performed by a validating parser?)
unloadDelay	2 000	(Amount of ms that the container will wait for servlets to unload)
unpackWAR	true	(Unpack WAR property)
useHttpOnly	true	(Indicates that session cookies should use HttpOnly)
useNaming	true	(Create a JNDI naming context for this application?)
useRelativeRedirects	true	(When generating location headers for 302 responses, should a relative URI be used?)
webappVersion		(The version of this web application - used in parallel deployment to differentiate different versions of the same web application)
welcomeFiles	[index.html]	(The welcome files for this context)
workDir	work/Catalina/localhost/demo	(The pathname to the work directory for this context)
xmlNamespaceAware	false	(Should the parsing of web.xml and web-fragment.xml files be performed by a namespace aware parser?)
xmlValidation	false	(Should the parsing of web.xml and web-fragment.xml files be performed by a validating parser?)
<b>name=/localhost/downloads,J2EEApplication=none,J2EEServer=none</b>		
(Standard Context Component)		
altDDName	null	(The alternate deployment descriptor name.)
antiResourceLocking	false	(Take care to not lock resources)
baseName	downloads	(The base name used for directories, WAR files (with .war appended) and context.xml files (with .xml appended).)
children	[Catalina:j2eeType=Servlet,WebModule=/localhost/downloads,name=default,J2EEApplication=none,J2EEServer=none,Catalina:j2eeType=Servlet,WebModule=/localhost/downloads,name=jsp,J2EEApplication=none,J2EEServer=none]	(Object names of all children)
clearReferencesRmiTargets	true	(Should Tomcat look for memory leaks in RMI Targets and clear them if found as a work around for application coding errors?)
clearReferencesStopThreads	false	(Should Tomcat attempt to terminate threads that have been started by the web application? Advisable to be used only in a development environment.)
clearReferencesStopTimerThreads	false	(Should Tomcat attempt to terminate TimerThreads that have been started by the web application? Advisable to be used only in a development environment.)
clearReferencesThreadLocals	true	(Should Tomcat attempt to clear ThreadLocal variables that have been populated with classes loaded by the web application?)
configFile	null	(Location of the context.xml resource or file)
configured	true	(The correctly configured flag for this Context.)
cookies	true	(Should we attempt to use cookies for session id communication?)
crossContext	false	(Should we allow the ServletContext.getContext() method to access the context of other web applications in this server?)
defaultContextXml	null	(Location of the default context.xml resource or file)
defaultWebXml	null	(Location of the default web.xml resource or file)
delegate	false	
displayName	null	(The display name of this web application)
distributable	false	(The distributable flag for this web application.)
docBase	downloads	(The document root for this web application)
encodedPath	/downloads	(The encoded path)
errorCount	12	(Cumulative error count of all servlets in this context)
ignoreAnnotations	false	(Ignore annotations flag.)
instanceManager	org.apache.catalina.core.DefaultInstanceManager@2228e779	(Object that creates and destroys servlets, filters, and listeners. Include dependency injection and postConstruct/preDestroy handling)
javaVMs	null	(The Java virtual machines on which this module is running)
loader	WebappLoader[StandardEngine[Catalina].StandardHost[localhost].StandardContext[/downloads]]	(Associated loader.)
logEffectiveWebXml	false	(Should the effective web.xml be logged when the context starts?)
logger	org.apache.juli.logging.DirectJDKLog@54cece85	(Associated logger.)
managedResource	StandardEngine[Catalina].StandardHost[localhost].StandardContext[/downloads]	(The managed resource this MBean is associated with)
manager	StandardManager[StandardEngine[Catalina].StandardHost[localhost].StandardContext[/downloads]]	(Associated manager.)
mapperContextRootRedirectEnabled	true	(Should the Mapper be used for context root redirects)
mapperDirectoryRedirectEnabled	false	(Should the Mapper be used for directory redirects)
maxTime	2	(Maximum execution time of all servlets in this context)
minTime	0	(Minimum execution time of all servlets in this context)
modelerType	org.apache.catalina.core.StandardContext	(Type of the modeled resource. Can be set only once)
name	/downloads	(The name of this Context)
namingContextListener	org.apache.catalina.core.NamingContextListener@21c89ee4	(Associated naming context listener.)
objectName	Catalina:j2eeType=WebModule,name=/localhost/downloads,J2EEApplication=none,J2EEServer=none	(Name of the object)
originalDocBase	null	(The original document root for this web application)
override	false	(The default context.xml override flag for this web application)
parentClassLoader	java.net.URLClassLoader@6536e911	(Parent class loader.)
path	/downloads	(The context path for this Context)
paused	false	(The request processing pause flag (while reloading occurs))
privileged	false	(Access to tomcat internals)
processingTime	5	(Cumulative execution times of all servlets in this context)
publicId	null	(The public identifier of the DTD for the web application deployment descriptor version that is being parsed)
realm	LockOutRealm[StandardEngine[Catalina]]	(Associated realm.)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

reloadable	false	(The reloadable flag for this web application)
renewThreadsWhenStoppingContext	true	(Should Tomcat renew the threads of the thread pool when the application is stopped to avoid memory leaks because of uncleaned ThreadLocal variables.)
requestCount	13	(Cumulative request count of all servlets in this context)
server	null	(The J2EE Server this module is deployed on)
sessionCookieDomain	null	(The domain to use for session cookies.'null' indicates that the domain is controlled by the application.)
sessionCookieName	null	(The name to use for session cookies.'null' indicates that the name is controlled by the application.)
sessionCookiePath	null	(The path to use for session cookies.'null' indicates that the path is controlled by the application.)
sessionTimeout	30	(The session timeout (in minutes) for this web application)
startTime	1 713 827 260 498	(Time (in milliseconds since January 1, 1970, 00:00:00) when this context was started)
startupTime	0	(Time (in milliseconds) it took to start this context)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
swallowOutput	false	(Flag to set to cause the system.out and system.err to be redirected to the logger when executing a servlet)
tldScanTime	0	(Time spend scanning jars for TLDs for this context)
tldValidation	false	(Should the parsing of *.tld files be performed by a validating parser?)
unloadDelay	2 000	(Amount of ms that the container will wait for servlets to unload)
unpackWAR	true	(Unpack WAR property)
useHttpOnly	true	(Indicates that session cookies should use HttpOnly)
useNaming	true	(Create a JNDI naming context for this application?)
useRelativeRedirects	true	(When generating location headers for 302 responses, should a relative URI be used?)
webappVersion		(The version of this web application - used in parallel deployment to differentiate different versions of the same web application)
welcomeFiles	[index.html, index.htm, index.jsp]	(The welcome files for this context)
workDir	work/Catalina/localhost/downloads	(The pathname to the work directory for this context)
xmlNamespaceAware	false	(Should the parsing of web.xml and web-fragment.xml files be performed by a namespace aware parser?)
xmlValidation	false	(Should the parsing of web.xml and web-fragment.xml files be performed by a validating parser?)

name=/localhost/usage,J2EEApplication=none,J2EEServer=none

(Standard Context Component)		
allDDName	null	(The alternate deployment descriptor name.)
antiResourceLocking	false	(Take care to not lock resources)
baseName	usage	(The base name used for directories, WAR files (with .war appended) and context.xml files (with .xml appended).)
children	[Catalina:j2eeType=Servlet,WebModule=/localhost/usage,name=default,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=Servlet,WebModule=/localhost/usage,name=jsp,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=Servlet,WebModule=/localhost/usage,name=usagestats,J2EEApplication=none,J2EEServer=none, Catalina:j2eeType=Servlet,WebModule=/localhost/usage,name=admin,J2EEApplication=none,J2EEServer=none]	(Object names of all children)
clearReferencesRmiTargets	true	(Should Tomcat look for memory leaks in RMI Targets and clear them if found as a work around for application coding errors?)
clearReferencesStopThreads	false	(Should Tomcat attempt to terminate threads that have been started by the web application? Advisable to be used only in a development environment.)
clearReferencesStopTimerThreads	false	(Should Tomcat attempt to terminate TimerThreads that have been started by the web application? Advisable to be used only in a development environment.)
clearReferencesThreadLocals	true	(Should Tomcat attempt to clear ThreadLocal variables that have been populated with classes loaded by the web application?)
configFile	file:/opt/apache-tomcat-9.0.33/conf/Catalina/localhost/usage.xml	(Location of the context.xml resource or file)
configured	true	(The correctly configured flag for this Context.)
cookies	true	(Should we attempt to use cookies for session id communication?)
crossContext	false	(Should we allow the ServletContext.getContext() method to access the context of other web applications in this server?)
defaultContextXml	null	(Location of the default context.xml resource or file)
defaultWebXml	null	(Location of the default web.xml resource or file)
delegate	false	
displayName	javamelody-usagestats	(The display name of this web application)
distributable	true	(The distributable flag for this web application.)
docBase	usage.war	(The document root for this web application)
encodedPath	/usage	(The encoded path)
errorCount	41	(Cumulative error count of all servlets in this context)
ignoreAnnotations	false	(Ignore annotations flag.)
instanceManager	org.apache.catalina.core.DefaultInstanceManager@65ff43a4	(Object that creates and destroys servlets, filters, and listeners. Include dependency injection and postConstruct/preDestroy handling)
javaVMs	null	(The Java virtual machines on which this module is running)
loader	WebappLoader[StandardEngine[Catalina].StandardHost[localhost].StandardContext[/usage]]	(Associated loader.)
logEffectiveWebXml	false	(Should the effective web.xml be logged when the context starts?)
logger	org.apache.juli.logging.DirectJDKLog@1902da93	(Associated logger.)
managedResource	StandardEngine[Catalina].StandardHost[localhost].StandardContext[/usage]	(The managed resource this MBean is associated with)
manager	StandardManager[StandardEngine[Catalina].StandardHost[localhost].StandardContext[/usage]]	(Associated manager.)
mapperContextRootRedirectEnabled	true	(Should the Mapper be used for context root redirects)
mapperDirectoryRedirectEnabled	false	(Should the Mapper be used for directory redirects)
maxTime	20 001	(Maximum execution time of all servlets in this context)
minTime	0	(Minimum execution time of all servlets in this context)
modelerType	org.apache.catalina.core.StandardContext	(Type of the modeled resource. Can be set only once)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

name	/usage	(The name of this Context)
namingContextListener	org.apache.catalina.core.NamingContextListener@52770c1	(Associated naming context listener.)
objectName	Catalina:2eeType=WebModule,name=/localhost/usage,J2EApplicat	(Name of the object)
originalDocBase	/opt/apache-tomcat-9.0.33/webapps/usage	(The original document root for this web application)
override	false	(The default context.xml override flag for this web application)
parentClassLoader	java.net.URLClassLoader@6536e911	(Parent class loader.)
path	/usage	(The context path for this Context)
paused	false	(The request processing pause flag (while reloading occurs))
privileged	false	(Access to tomcat internals)
processingTime	1 548 296	(Cumulative execution times of all servlets in this context)
publicId	null	(The public identifier of the DTD for the web application deployment descriptor version that is being parsed)
realm	LockOutRealm[StandardEngine[Catalina]]	(Associated realm.)
reloadable	false	(The reloadable flag for this web application)
renewThreadsWhenStoppingContext	true	(Should Tomcat renew the threads of the thread pool when the application is stopped to avoid memory leaks because of uncleaned ThreadLocal variables.)
requestCount	6 814 567	(Cumulative request count of all servlets in this context)
server	null	(The J2EE Server this module is deployed on)
sessionCookieDomain	null	(The domain to use for session cookies.'null' indicates that the domain is controlled by the application.)
sessionCookieName	null	(The name to use for session cookies.'null' indicates that the name is controlled by the application.)
sessionCookiePath	null	(The path to use for session cookies.'null' indicates that the path is controlled by the application.)
sessionTimeout	30	(The session timeout (in minutes) for this web application)
startTime	1 713 827 260 370	(Time (in milliseconds since January 1, 1970, 00:00:00) when this context was started)
startupTime	158	(Time (in milliseconds) it took to start this context)
stateName	STARTED	(The name of the LifecycleState that this component is currently in)
swallowOutput	false	(Flag to set to cause the system.out and system.err to be redirected to the logger when executing a servlet)
tldScanTime	0	(Time spend scanning jars for TLDs for this context)
tldValidation	false	(Should the parsing of *.tld files be performed by a validating parser?)
unloadDelay	2 000	(Amount of ms that the container will wait for servlets to unload)
unpackWAR	true	(Unpack WAR property)
useHttpOnly	true	(Indicates that session cookies should use HttpOnly)
useNaming	true	(Create a JNDI naming context for this application?)
useRelativeRedirects	true	(When generating location headers for 302 responses, should a relative URI be used?)
webappVersion		(The version of this web application - used in parallel deployment to differentiate different versions of the same web application)
welcomeFiles	[index.html]	(The welcome files for this context)
workDir	work/Catalina/localhost/usage	(The pathname to the work directory for this context)
xmlNamespaceAware	false	(Should the parsing of web.xml and web-fragment.xml files be performed by a namespace aware parser?)
xmlValidation	false	(Should the parsing of web.xml and web-fragment.xml files be performed by a validating parser?)

## WebResourceRoot

host=localhost,context=/		
	(Provides the resources implementation for a web application)	
allowLinking	false	(Does this resources implementation allow the use of symbolic links?)
cachingAllowed	true	(Is in memory caching of resource content and metadata enabled?)
modelerType	org.apache.catalina.webresources.StandardRoot	(Type of the modeled resource. Can be set only once)
stateName	STARTED	(The current Lifecycle state of this object)
trackLockedFiles	false	(Does this resources implementation track requests that lock files?)
trackedResources	[]	(List of resources currently being tracked for possible resource leaks)

## host=localhost,context=/,name=Cache

	(Provides caching of resource metadata and content)	
hitCount	17 570	(The number of requests for resources that were served from the cache)
lookupCount	18 231	(The number of requests for resources)
maxSize	10 240	(The maximum permitted size of the cache in kB)
modelerType	org.apache.catalina.webresources.Cache	(Type of the modeled resource. Can be set only once)
objectMaxSize	512	(The maximum permitted size for a single object in the cache in kB)
size	322	(The current estimate of the cache size in kB)
ttl	5 000	(The time-to-live for cache entries in milliseconds)

## host=localhost,context=/demo

	(Provides the resources implementation for a web application)	
allowLinking	false	(Does this resources implementation allow the use of symbolic links?)
cachingAllowed	true	(Is in memory caching of resource content and metadata enabled?)
modelerType	org.apache.catalina.webresources.StandardRoot	(Type of the modeled resource. Can be set only once)
stateName	STARTED	(The current Lifecycle state of this object)
trackLockedFiles	false	(Does this resources implementation track requests that lock files?)
trackedResources	[]	(List of resources currently being tracked for possible resource leaks)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

## host=localhost,context=/demo,name=Cache

(Provides caching of resource metadata and content)		
hitCount	56 802	(The number of requests for resources that were served from the cache)
lookupCount	57 011	(The number of requests for resources)
maxSize	10 240	(The maximum permitted size of the cache in kB)
modelerType	org.apache.catalina.webresources.Cache	(Type of the modeled resource. Can be set only once)
objectMaxSize	512	(The maximum permitted size for a single object in the cache in kB)
size	2 574	(The current estimate of the cache size in kB)
ttl	5 000	(The time-to-live for cache entries in milliseconds)

## host=localhost,context=/downloads

(Provides the resources implementation for a web application)		
allowLinking	false	(Does this resources implementation allow the use of symbolic links?)
cachingAllowed	true	(Is in memory caching of resource content and metadata enabled?)
modelerType	org.apache.catalina.webresources.StandardRoot	(Type of the modeled resource. Can be set only once)
stateName	STARTED	(The current Lifecycle state of this object)
trackLockedFiles	false	(Does this resources implementation track requests that lock files?)
trackedResources	[]	(List of resources currently being tracked for possible resource leaks)

## host=localhost,context=/downloads,name=Cache

(Provides caching of resource metadata and content)		
hitCount	9	(The number of requests for resources that were served from the cache)
lookupCount	26	(The number of requests for resources)
maxSize	10 240	(The maximum permitted size of the cache in kB)
modelerType	org.apache.catalina.webresources.Cache	(Type of the modeled resource. Can be set only once)
objectMaxSize	512	(The maximum permitted size for a single object in the cache in kB)
size	24	(The current estimate of the cache size in kB)
ttl	5 000	(The time-to-live for cache entries in milliseconds)

## host=localhost,context=/usage

(Provides the resources implementation for a web application)		
allowLinking	false	(Does this resources implementation allow the use of symbolic links?)
cachingAllowed	true	(Is in memory caching of resource content and metadata enabled?)
modelerType	org.apache.catalina.webresources.StandardRoot	(Type of the modeled resource. Can be set only once)
stateName	STARTED	(The current Lifecycle state of this object)
trackLockedFiles	false	(Does this resources implementation track requests that lock files?)
trackedResources	[]	(List of resources currently being tracked for possible resource leaks)

## host=localhost,context=/usage,name=Cache

(Provides caching of resource metadata and content)		
hitCount	140	(The number of requests for resources that were served from the cache)
lookupCount	168	(The number of requests for resources)
maxSize	10 240	(The maximum permitted size of the cache in kB)
modelerType	org.apache.catalina.webresources.Cache	(Type of the modeled resource. Can be set only once)
objectMaxSize	512	(The maximum permitted size for a single object in the cache in kB)
size	32	(The current estimate of the cache size in kB)
ttl	5 000	(The time-to-live for cache entries in milliseconds)

## JMImplementation

### MBeanServerDelegate

(Represents the MBean server from the management point of view.)		
ImplementationName	JMX	(The JMX implementation name (the name of this product))
ImplementationVendor	Oracle Corporation	(the JMX implementation vendor (the vendor of this product).)
ImplementationVersion	11.0.6+10	(The JMX implementation version (the version of this product).)
MBeanServerId	vps363300.ovh.net_1713826760821	(The MBean server agent identification)
SpecificationName	Java Management Extensions	(The full name of the JMX specification implemented by this product.)
SpecificationVendor	Oracle Corporation	(The vendor of the JMX specification implemented by this product.)
SpecificationVersion	1.4	(The version of the JMX specification implemented by this product.)

## Users

### UserDatabase

database=UserDatabase		
(In-memory user and group database)		
groups	[]	(MBean Names of all defined groups)
modelerType	org.apache.catalina.users.MemoryUserDatabase	(Type of the modeled resource. Can be set only once)
pathname	conf/tomcat-users.xml	(Relative or absolute pathname to database file)
readonly	true	(No persistent save of the user database)
roles	[]	(MBean Names of all defined roles)
users	[]	(MBean Names of all defined users)
writable	true	(Check if user database is writable)

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

com.sun.management

DiagnosticCommand  
(Diagnostic Commands)

HotSpotDiagnostic

DiagnosticOptions

```
[{name=HeapDumpBeforeFullGC, origin=DEFAULT, value=false, writeable=true}, {name=HeapDumpAfterFullGC, origin=DEFAULT, value=false, writeable=true}, {name=HeapDumpOnOutOfMemoryError, origin=DEFAULT, value=false, writeable=true}, {name=HeapDumpPath, origin=DEFAULT, value=, writeable=true}, {name=PrintClassHistogram, origin=DEFAULT, value=false, writeable=true}, {name=MinHeapFreeRatio, origin=DEFAULT, value=40, writeable=true}, {name=MaxHeapFreeRatio, origin=DEFAULT, value=70, writeable=true}, {name=PrintConcurrentLocks, origin=DEFAULT, value=false, writeable=true}, {name=CMSSAbortablePrecleanWaitMillis, origin=DEFAULT, value=100, writeable=true}, {name=CMSSWaitDuration, origin=DEFAULT, value=2000, writeable=true}, {name=CMSTriggerInterval, origin=DEFAULT, value=-1, writeable=true}]
```

ObjectName

com.sun.management:type=HotSpotDiagnostic

java.lang

ClassLoader

LoadedClassCount

8 858

ObjectName

java.lang:type=ClassLoader

TotalLoadedClassCount

12 478

UnloadedClassCount

3 620

Verbose

false

CodeCacheManager

type=MemoryManager

MemoryPoolNames

[CodeHeap 'non-nmethods', CodeHeap 'profiled nmethods', CodeHeap 'non-profiled nmethods']

Name

CodeCacheManager

ObjectName

java.lang:type=MemoryManager,name=CodeCacheManager

Valid

true

CodeHeap 'non-nmethods'

type=MemoryPool

CollectionUsage

null

CollectionUsageThresholdSupported

false

MemoryManagerNames

[CodeCacheManager]

Name

CodeHeap 'non-nmethods'

ObjectName

java.lang:type=MemoryPool,name=CodeHeap 'non-nmethods'

PeakUsage

{committed=2 555 904, init=2 555 904, max=5 828 608, used=1 514 240}

Type

NON\_HEAP

Usage

{committed=2 555 904, init=2 555 904, max=5 828 608, used=1 444 352}

UsageThreshold

0

UsageThresholdCount

0

UsageThresholdExceeded

false

UsageThresholdSupported

true

Valid

true

CodeHeap 'non-profiled nmethods'

type=MemoryPool

CollectionUsage

null

CollectionUsageThresholdSupported

false

MemoryManagerNames

[CodeCacheManager]

Name

CodeHeap 'non-profiled nmethods'

ObjectName

java.lang:type=MemoryPool,name=CodeHeap 'non-profiled nmethods'

PeakUsage

{committed=21 430 272, init=2 555 904, max=122 916 864, used=20 479 232}

Type

NON\_HEAP

Usage

{committed=21 430 272, init=2 555 904, max=122 916 864, used=20 206 976}

UsageThreshold

0

UsageThresholdCount

0

UsageThresholdExceeded

false

UsageThresholdSupported

true

Valid

true

CodeHeap 'profiled nmethods'

type=MemoryPool

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

CollectionUsage	null
CollectionUsageThresholdSupported	false
MemoryManagerNames	[CodeCacheManager]
Name	CodeHeap' profiled nmethods'
ObjectName	java.lang:type=MemoryPool,name=CodeHeap 'profiled nmethods'
PeakUsage	{committed=22 937 600, init=2 555 904, max=122 912 768, used=22 470 656}
Type	NON_HEAP
Usage	{committed=22 937 600, init=2 555 904, max=122 912 768, used=15 864 320}
UsageThreshold	0
UsageThresholdCount	0
UsageThresholdExceeded	false
UsageThresholdSupported	true
Valid	true

## Compilation

CompilationTimeMonitoringSupported	true
Name	HotSpot 64-Bit Tiered Compilers
ObjectName	java.lang:type=Compilation
TotalCompilationTime	307 966

## Compressed Class Space

type=MemoryPool	
CollectionUsage	null
CollectionUsageThresholdSupported	false
MemoryManagerNames	[Metaspace Manager]
Name	Compressed Class Space
ObjectName	java.lang:type=MemoryPool,name=Compressed Class Space
PeakUsage	{committed=7 077 888, init=0, max=1 073 741 824, used=6 529 208}
Type	NON_HEAP
Usage	{committed=7 077 888, init=0, max=1 073 741 824, used=6 476 536}
UsageThreshold	0
UsageThresholdCount	0
UsageThresholdExceeded	false
UsageThresholdSupported	true
Valid	true

## Copy

type=GarbageCollector	
CollectionCount	16 562
CollectionTime	485 784
LastGcInfo	{GcThreadCount=1, duration=14, endTime=1 002 264 655, id=16 562, memoryUsageAfterGc=(GcThreadCount=1, duration=14, endTime=1002264655, id=16562, memoryUsageAfterGc=[{key=CodeHeap 'profiled nmethods', value={committed=22937600, init=2555904, max=122912768, used=15845760}], {key=Eden Space, value={committed=77594624, init=8912896, max=137035776, used=0}}, {key=CodeHeap 'non-profiled nmethods', value={committed=21430272, init=2555904, max=122916864, used=20196608}], {key=Survivor Space, value={committed=9633792, init=111412, max=17104896, used=4087224}], {key=Compressed Class Space, value={committed=7077888, init=0, max=1073741824, used=6476536}], {key=Metaspace, value={committed=74354688, init=0, max=-1, used=72150288}], {key=CodeHeap 'non-nmethods', value={committed=2555904, init=2555904, max=5828608, used=1444352}], {key=Tenured Gen, value={committed=193609728, init=22413312, max=342556672, used=58081992}], startTime=1002264641), memoryUsageBeforeGc=(GcThreadCount=1, duration=14, endTime=1002264655, id=16562, memoryUsageAfterGc=[{key=CodeHeap 'profiled nmethods', value={committed=22937600, init=2555904, max=122912768, used=15845760}], {key=Eden Space, value={committed=77594624, init=8912896, max=137035776, used=0}}, {key=CodeHeap 'non-profiled nmethods', value={committed=21430272, init=2555904, max=122916864, used=20196608}], {key=Survivor Space, value={committed=9633792, init=111412, max=17104896, used=4087224}], {key=Compressed Class Space, value={committed=7077888, init=0, max=1073741824, used=6476536}], {key=Metaspace, value={committed=74354688, init=0, max=-1, used=72150288}], {key=CodeHeap 'non-nmethods', value={committed=2555904, init=2555904, max=5828608, used=1444352}], {key=Tenured Gen, value={committed=193609728, init=22413312, max=342556672, used=58081992}], startTime=1002264641), memoryUsageBeforeGc=[{key=CodeHeap 'profiled nmethods', value={committed=22937600, init=2555904, max=122912768, used=15845760}], {key=Eden Space, value={committed=77594624, init=8912896, max=137035776, used=0}}, {key=CodeHeap 'non-profiled nmethods', value={committed=21430272, init=2555904, max=122916864, used=20196608}], {key=Survivor Space, value={committed=9633792, init=111412, max=17104896, used=4087224}], {key=Compressed Class Space, value={committed=7077888, init=0, max=1073741824, used=6476536}], {key=Metaspace, value={committed=74354688, init=0, max=-1, used=72150288}], {key=CodeHeap 'non-nmethods', value={committed=2555904, init=2555904, max=5828608, used=1444352}], {key=Tenured Gen, value={committed=193609728, init=22413312, max=342556672, used=58081992}], startTime=1002264641}, startTime=1 002 264 641}

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

MemoryPoolNames

[Eden Space,  
Survivor Space]

Name

Copy

ObjectName

java.lang:type=GarbageCollector,name=Copy

Valid

true

## Eden Space

type=MemoryPool

CollectionUsage

{committed=77 594 624, init=8 912 896, max=137 035 776, used=0}

CollectionUsageThreshold

0

CollectionUsageThresholdCount

0

CollectionUsageThresholdExceeded

false

CollectionUsageThresholdSupported

true

MemoryManagerNames

[Copy,  
MarkSweepCompact]

Name

Eden Space

ObjectName

java.lang:type=MemoryPool,name=Eden Space

PeakUsage

{committed=137 035 776, init=8 912 896, max=137 035 776,  
used=137 035 776}

Type

HEAP

Usage

{committed=77 594 624, init=8 912 896, max=137 035 776,  
used=61 200 928}

UsageThresholdSupported

false

Valid

true

## MarkSweepCompact

type=GarbageCollector

CollectionCount

452

CollectionTime

202 667

LastGcInfo

{GcThreadCount=1, duration=101, endTime=997 414 575, id=452,  
memoryUsageAfterGc={GcThreadCount=1, duration=101,  
endTime=997414575, id=452,  
memoryUsageAfterGc=[{key=CodeHeap 'profiled nmethods',  
value={committed=22937600, init=2555904, max=122912768,  
used=15973760}], {key=Eden Space, value={committed=98304000,  
init=8912896, max=137035776, used=0}}, {key=CodeHeap 'non-  
profiled nmethods', value={committed=21430272, init=2555904,  
max=122916864, used=20238336}}, {key=Survivor Space,  
value={committed=12255232, init=1141112, max=17104896,  
used=0}}, {key=Compressed Class Space,  
value={committed=7077888, init=0, max=1073741824,  
used=6425200}}, {key=Metaspace, value={committed=74092544,  
init=0, max=-1, used=71786856}}, {key=CodeHeap 'non-nmethods',  
value={committed=2555904, init=2555904, max=5828608,  
used=1444352}}, {key=Tenured Gen, value={committed=245497856,  
init=22413312, max=342556672, used=73648336}}],  
memoryUsageBeforeGc=[{key=CodeHeap 'profiled nmethods',  
value={committed=22937600, init=2555904, max=122912768,  
used=15973760}], {key=Eden Space, value={committed=98304000,  
init=8912896, max=137035776, used=0}}, {key=CodeHeap 'non-  
profiled nmethods', value={committed=21430272, init=2555904,  
max=122916864, used=20238336}}, {key=Survivor Space,  
value={committed=12255232, init=1141112, max=17104896,  
used=0}}, {key=Compressed Class Space,  
value={committed=7077888, init=0, max=1073741824,  
used=6425200}}, {key=Metaspace, value={committed=74092544,  
init=0, max=-1, used=71786856}}, {key=CodeHeap 'non-nmethods',  
value={committed=2555904, init=2555904, max=5828608,  
used=1444352}}, {key=Tenured Gen, value={committed=245497856,  
init=22413312, max=342556672, used=73648336}}],  
startTime=997414474},  
memoryUsageBeforeGc={GcThreadCount=1, duration=101,  
endTime=997414575, id=452,  
memoryUsageAfterGc=[{key=CodeHeap 'profiled nmethods',  
value={committed=22937600, init=2555904, max=122912768,  
used=15973760}], {key=Eden Space, value={committed=98304000,  
init=8912896, max=137035776, used=0}}, {key=CodeHeap 'non-  
profiled nmethods', value={committed=21430272, init=2555904,  
max=122916864, used=20238336}}, {key=Survivor Space,  
value={committed=12255232, init=1141112, max=17104896,  
used=0}}, {key=Compressed Class Space,  
value={committed=7077888, init=0, max=1073741824,  
used=6425200}}, {key=Metaspace, value={committed=74092544,  
init=0, max=-1, used=71786856}}, {key=CodeHeap 'non-nmethods',  
value={committed=2555904, init=2555904, max=5828608,  
used=1444352}}, {key=Tenured Gen, value={committed=245497856,  
init=22413312, max=342556672, used=73648336}}],  
startTime=997414474}, startTime=997 414 474}

MemoryPoolNames

[Eden Space,  
Survivor Space,  
Tenured Gen]

Name

MarkSweepCompact

ObjectName

java.lang:type=GarbageCollector,name=MarkSweepCompact

Valid

true

## Memory

HeapMemoryUsage

{committed=280 838 144, init=33 554 432, max=496 697 344,  
used=125 853 304}

NonHeapMemoryUsage

{committed=128 356 352, init=7 667 712, max=-1, used=116 151 392}

ObjectName

java.lang:type=Memory

ObjectPendingFinalizationCount

0

Verbose

false

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

## Metaspace

type=MemoryPool	
CollectionUsage	null
CollectionUsageThresholdSupported	false
MemoryManagerNames	[Metaspace Manager]
Name	Metaspace
ObjectName	java.lang:type=MemoryPool,name=Metaspace
PeakUsage	{committed=74 354 688, init=0, max=-1, used=72 225 152}
Type	NON_HEAP
Usage	{committed=74 354 688, init=0, max=-1, used=72 153 784}
UsageThreshold	0
UsageThresholdCount	0
UsageThresholdExceeded	false
UsageThresholdSupported	true
Valid	true

## Metaspace Manager

type=MemoryManager	
MemoryPoolNames	[Metaspace, Compressed Class Space]
Name	Metaspace Manager
ObjectName	java.lang:type=MemoryManager,name=Metaspace Manager
Valid	true

## OperatingSystem

Arch	amd64
AvailableProcessors	1
CommittedVirtualMemorySize	2 872 373 248
FreePhysicalMemorySize	350 539 776
FreeSwapSpaceSize	0
MaxFileDescriptorCount	500 000
Name	Linux
ObjectName	java.lang:type=OperatingSystem
OpenFileDescriptorCount	163
ProcessCpuLoad	0
ProcessCpuTime	16 261 950 000 000
SystemCpuLoad	0
SystemLoadAverage	0
TotalPhysicalMemorySize	2 047 422 464
TotalSwapSpaceSize	0
Version	3.10.0-514.2.2.el7.x86_64

## Runtime

BootClassPathSupported	false
ClassPath	/opt/tomcat/bin/bootstrap.jar:/opt/tomcat/bin/tomcat-juli.jar
InputArguments	[-add-opens=java.base/java.io=ALL-UNNAMED, -add-opens=java.base/java.lang=ALL-UNNAMED, -add-opens=java.rmi/sun.rmi.transport=ALL-UNNAMED, -Djava.util.logging.config.file=/opt/tomcat/conf/logging.properties, -Djava.util.logging.manager=org.apache.juli.ClassLoaderLogManager, -Djdk.tls.ephemeralDHKeySize=2048, -Djava.protocol.handler.pkgs=org.apache.catalina.webresources, -Dorg.apache.catalina.security.SecurityListener.UMASK=0027, -Djava.security.egd=file:/dev/urandom, -Dignore.endorsed.dirs= -Dcatalina.base=/opt/tomcat, -Dcatalina.home=/opt/tomcat, -Djava.io.tmpdir=/opt/tomcat/temp]
LibraryPath	/usr/java/packages/lib:/usr/lib64:/lib64:/lib:/usr/lib
ManagementSpecVersion	2.0
Name	5996@vps363300.ovh.net
ObjectName	java.lang:type=Runtime
Pid	5 996
SpecName	Java Virtual Machine Specification
SpecVendor	Oracle Corporation
SpecVersion	11
StartTime	1 713 826 759 727

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

## SystemProperties

```
[{"key": "awt.toolkit", "value": "sun.awt.X11Toolkit"}, {"key": "java.specification.version", "value": "11"}, {"key": "sun.cpu.isalist", "value": ""}, {"key": "sun.jnu.encoding", "value": "ANSI_X3.4-1968"}, {"key": "java.class.path", "value": "/opt/tomcat/bin/bootstrap.jar:/opt/tomcat/bin/tomcat-juli.jar"}, {"key": "pid", "value": "5996"}, {"key": "java.vm.vendor", "value": "AdoptOpenJDK"}, {"key": "sun.arch.data.model", "value": "64"}, {"key": "sun.font.fontmanager", "value": "sun.awt.X11FontManager"}, {"key": "java.vendor.url", "value": "https://adoptopenjdk.net/"}, {"key": "catalina.useNaming", "value": "true"}, {"key": "user.timezone", "value": "Europe/Paris"}, {"key": "os.name", "value": "Linux"}, {"key": "java.vm.specification.version", "value": "11"}, {"key": "sun.java.launcher", "value": "SUN_STANDARD"}, {"key": "user.country", "value": "US"}, {"key": "sun.boot.library.path", "value": "/opt/jdk-11.0.6+10/lib"}, {"key": "sun.java.command", "value": "org.apache.catalina.startup.Bootstrap start"}, {"key": "jdk.debug", "value": "release"}, {"key": "sun.cpu.endian", "value": "little"}, {"key": "user.home", "value": "/root"}, {"key": "user.language", "value": "en"}, {"key": "java.specification.vendor", "value": "Oracle Corporation"}, {"key": "java.naming.factory.url.pkgs", "value": "org.apache.naming"}, {"key": "java.version.date", "value": "2020-01-14"}, {"key": "java.home", "value": "/opt/jdk-11.0.6+10"}, {"key": "ignore.endorsed.dirs", "value": ""}, {"key": "file.separator", "value": "/"}, {"key": "java.vm.compressedOopsMode", "value": "32-bit"}, {"key": "line.separator", "value": "\n"}, {"key": "java.specification.name", "value": "Java Platform API Specification"}, {"key": "java.vm.specification.vendor", "value": "Oracle Corporation"}, {"key": "java.awt.graphicsenv", "value": "sun.awt.X11GraphicsEnvironment"}, {"key": "package.access", "value": "*"}, {"key": "sun.org.apache.catalina.org.apache.coyote.org.apache.jasper .org.apache.tomcat.", "value": ""}, {"key": "package.definition", "value": "sun.java.org.apache.catalina.org.apache.coyote.org.apache.j asper.org.apache.naming.org.apache.tomcat."}, {"key": "jdk.tls.ephemeralDHKeySize", "value": "2048"}, {"key": "server.loader", "value": ""}, {"key": "java.util.logging.config.file", "value": "/opt/tomcat/conf/logging.properties"}, {"key": "java.protocol.handler.pkgs", "value": "org.apache.catalina.webresources"}, {"key": "sun.management.compiler", "value": "HotSpot 64-Bit Tiered Compilers"}, {"key": "java.runtime.version", "value": "11.0.6+10"}, {"key": "java.naming.factory.initial", "value": "org.apache.naming.java.javaURLContextFactory"}, {"key": "user.name", "value": "root"}, {"key": "path.separator", "value": ":"}, {"key": "java.security.egd", "value": "file:/dev/.urandom"}, {"key": "common.loader", "value": "${catalina.base}/lib/*:${catalina.base}/lib/*.jar", "${catalina.home} /lib/*:${catalina.home}/lib/*.jar"}, {"key": "os.version", "value": "3.10-0-514.2.2.el7.x86_64"}, {"key": "java.runtime.name", "value": "OpenJDK Runtime Environment"}, {"key": "file.encoding", "value": "UTF-8"}, {"key": "java.vm.name", "value": "OpenJDK 64-Bit Server VM"}, {"key": "java.vendor.version", "value": "AdoptOpenJDK"}, {"key": "org.apache.catalina.security.SecurityListener.UMASK", "value": "0027"}, {"key": "java.vendor.url.bug", "value": "https://github.com/AdoptOpenJDK/openjdk-support/issues"}, {"key": "java.io.tmpdir", "value": "/opt/tomcat/temp"}, {"key": "tomcat.util.scan.StandardJarScanFilter.jarsToScan", "value": "log4j-taglib*.jar, log4j-web*.jar, log4j-javascript*.jar, slf4j-taglib*.jar"}, {"key": "catalina.home", "value": "/opt/apache-tomcat-9.0.33"}, {"key": "java.version", "value": "11.0.6"}, {"key": "tomcat.util.scan.StandardJarScanFilter.jarsToSkip", "value": "annotations-api.jar, ant-junit*.jar, ant-launcher.jar, ant.jar, asm*.jar, aspect*.jar, bootstrap.jar, catalina-ant.jar, catalina-ha.jar, catalina-ssi.jar, catalina-storeconfig.jar, catalina-tribes.jar, catalina.jar, cglib*.jar, cobertura*.jar, commons-beanutils*.jar, commons-codec*.jar, commons-collections*.jar, commons-daemon*.jar, commons-dbc*.jar, commons-digester*.jar, commons-fileupload*.jar, commons-httpclient*.jar, commons-io*.jar, commons-lang*.jar, commons-logging*.jar, commons-math*.jar, commons-pool*.jar, dom4j*.jar, easyMock*.jar, ejc*.jar, el-api*.jar, geronimo-spec-jaxrpc*.jar, h2*.jar, hamcrest*.jar, hibernate*.jar, httpclient*.jar, icu4j*.jar, jasper-el*.jar, jasper*.jar, jaspic-api*.jar, jaxb*.jar, jaxen*.jar, jdbm*.jar, jetty*.jar, jmx-tools*.jar, jmx*.jar, jsr-api*.jar, jstl*.jar, jta*.jar, junit*.jar, junit*.jar, log4j*.jar, mail*.jar, objenesis*.jar, oraclepkj*.jar, oreo*.jar, servlet-api*.jar, servlet-api*.jar, slf4j*.jar, taglibs-standard-spec-jar, tagsoup*.jar, tomcat-apr*.jar, tomcat-coyote*.jar, tomcat-dbc*.jar, tomcat-18n*.jar, tomcat-jdbc*.jar, tomcat-jni*.jar, tomcat-juli-adapters*.jar, tomcat-juli*.jar, tomcat-util-scan*.jar, tomcat-util*.jar, tomcat-websocket*.jar, tools*.jar, websocket-api*.jar, wsd14*.jar, xercesImpl*.jar, xmlapis*.jar, xmParserAPIs*.jar, xmParserAPIs*.jar, xom*.jar}, {"key": "user.dir", "value": ""}, {"key": "os.arch", "value": "amd64"}, {"key": "java.vm.specification.name", "value": "Java Virtual Machine Specification"}, {"key": "java.awt.printerjob", "value": "sun.print.PSPrinterJob"}, {"key": "sun.os.patch.level", "value": "unknown"}, {"key": "catalina.base", "value": "/opt/apache-tomcat-9.0.33"}, {"key": "shared.loader", "value": ""}, {"key": "util.logging.manager", "value": "org.apache.juli.ClassLoaderLogManager"}, {"key": "java.library.path", "value": "/usr/java/packages/lib/usr/lib64/lib64:/lib:/usr/lib"}, {"key": "java.vendor", "value": "AdoptOpenJDK"}, {"key": "java.vm.info", "value": "mixed mode"}, {"key": "java.version", "value": "11.0.6+10"}, {"key": "sun.io.unicode.encoding", "value": "UnicodeLittle"}, {"key": "tomcat.util.buf.StringCache.byte.enabled", "value": "true"}, {"key": "java.class.version", "value": "55.0"}]
```

## Uptime

1 002 438 219

## VmName

OpenJDK 64-Bit Server VM

## VmVendor

AdoptOpenJDK

## VmVersion

11.0.6+10

## Survivor Space

### type=MemoryPool

#### CollectionUsage

```
{committed=9 633 792, init=1 114 112, max=17 104 896, used=4 087 224}
```

#### CollectionUsageThreshold

0

#### CollectionUsageThresholdCount

0

#### CollectionUsageThresholdExceeded

false

#### CollectionUsageThresholdSupported

true

#### MemoryManagerNames

[Copy, MarkSweepCompact]

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

Name	Survivor Space
ObjectName	java.lang:type=MemoryPool,name=Survivor Space
PeakUsage	{committed=17 104 896, init=1 114 112, max=17 104 896, used=17 104 896}
Type	HEAP
Usage	{committed=9 633 792, init=1 114 112, max=17 104 896, used=4 087 224}
UsageThresholdSupported	false
Valid	true

## Tenured Gen

type=MemoryPool	
CollectionUsage	{committed=245 497 856, init=22 413 312, max=342 556 672, used=58 081 992}
CollectionUsageThreshold	0
CollectionUsageThresholdCount	0
CollectionUsageThresholdExceeded	false
CollectionUsageThresholdSupported	true
MemoryManagerNames	[MarkSweepCompact]
Name	Tenured Gen
ObjectName	java.lang:type=MemoryPool,name=Tenured Gen
PeakUsage	{committed=342 556 672, init=22 413 312, max=342 556 672, used=342 556 672}
Type	HEAP
Usage	{committed=193 609 728, init=22 413 312, max=342 556 672, used=58 587 728}
UsageThreshold	0
UsageThresholdCount	0
UsageThresholdExceeded	false
UsageThresholdSupported	true
Valid	true

## Threading

AllThreadIds	[J@364a28ef
CurrentThreadCpuTime	87 835 587 846
CurrentThreadCpuTimeSupported	true
CurrentThreadUserTime	77 380 000 000
DaemonThreadCount	76
ObjectMonitorUsageSupported	true
ObjectName	java.lang:type=Threading
PeakThreadCount	143
SynchronizerUsageSupported	true
ThreadAllocatedMemoryEnabled	true
ThreadAllocatedMemorySupported	true
ThreadContentionMonitoringEnabled	false
ThreadContentionMonitoringSupported	true
ThreadCount	81
ThreadCpuTimeEnabled	true
ThreadCpuTimeSupported	true
TotalStartedThreadCount	602

## java.nio

### direct

type=BufferPool	
Count	65
MemoryUsed	572 276
Name	direct
ObjectName	java.nio:type=BufferPool,name=direct
TotalCapacity	572 276

### mapped

type=BufferPool	
Count	0
MemoryUsed	0
Name	mapped
ObjectName	java.nio:type=BufferPool,name=mapped
TotalCapacity	0

## java.util.logging

### Logging

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

LoggerNames

```
[  
org.apache.catalina.core.ContainerBase.[Catalina],  
org.apache.catalina.session,  
org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo].[  
default],  
org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo].[  
TelephoneService],  
org.apache.tomcat.dbcp.dbcp2.BasicDataSource,  
org.apache.catalina.core.ApplicationFilterConfig,  
org.apache.jasper,  
org.apache.jasper.servlet.JasperInitializer,  
org.apache.jasper.compiler.Compiler,  
org.apache.catalina.util,  
org.apache.tomcat.util.descriptor.web.WebXmlParser,  
org.apache.catalina.webresources,  
jdk.event,  
org.apache.tomcat.util.net,  
org.apache.tomcat.util.digester.Digester,  
sun.awt.multiplescreen.SunDisplayChanger,  
sun.awt.X11GraphicsEnvironment,  
org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo].[  
GradeService],  
org.apache.jasper.compiler,  
org.apache.tomcat.util.descriptor.web,  
org.apache.jasper.servlet.JspServlet,  
org.apache.tomcat.websocket,  
org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo],  
org.apache.catalina.webresources.JarVarResource,  
org.apache.tomcat.dbcp,  
org.apache.jasper.compiler.SmapUtil$SDEInstaller,  
org.apache.tomcat.dbcp.dbcp2.ObjectNameWrapper,  
org.apache.tomcat.util.descriptor,  
org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo].[  
MailService],  
org.apache.catalina,  
org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo].[  
AdresseService],  
org.apache.tomcat,  
org.apache.jasper.servlet,  
org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo].[  
PersonneService],  
org.apache.catalina.webresources.JarResourceRoot,  
jdk.event.security,  
org.apache.tomcat.util.digester.Digester.sax,  
org.apache.jasper.JspCompilationContext,  
org.apache,  
org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo].[  
CompetenceService],  
org.apache.catalina.core.ContainerBase,  
org.apache.tomcat.util.descriptor.web.WebXml,  
org.apache.jasper.servlet.TldScanner,  
org.apache.jasper.compiler.JDTCompiler,  
org.apache.tomcat.util.descriptor.tld,  
org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo].[  
AuthenticationService],  
sun,  
sun.awt.multiplescreen,  
org.apache.jasper.EmbeddedServletOptions,  
org.apache.tomcat.dbcp.dbcp2,  
org.apache.jasper.compiler.JspConfig,  
org.apache.tomcat.util.scan,  
org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo].[  
PermissionService],  
org.apache.tomcat.dbcp.dbcp2.BasicDataSourceFactory,  
org.apache.jasper.compiler.JspReader,  
org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo].[  
BuildInfoServlet],  
org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo].[  
RoleService],  
org.apache.catalina.core.ContainerBase.[Catalina].[localhost],  
org.apache.tomcat.util.digester,  
org.apache.catalina.util.SessionIdGeneratorBase,  
org.apache.tomcat.util.net.SSLHostConfig,  
org.apache.tomcat.dbcp.dbcp2.PoolableConnectionFactory,  
sun.awt.screen,  
org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo].[  
UtilisateurService],  
sun.awt.screen.X11GraphicsEnvironment,  
org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo].[  
jsp],  
org.apache.tomcat.dbcp.dbcp2.PoolingDataSource,  
sun.awt,  
org,  
org.apache.catalina.session.ManagerBase,  
org.apache.catalina.authenticator.AuthenticatorBase,  
org.apache.catalina.session.StandardManager,  
org.apache.tomcat.util.descriptor.tld.TldParser,  
org.apache.catalina.authenticator,  
org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/demo].[  
PrintUtilsService],  
jdk,  
org.apache.jasper.servlet.JspServletWrapper,  
org.apache.tomcat.util,  
org.apache.tomcat.util.net.SSLHostConfigCertificate,  
org.apache.jasper.compiler.JspRuntimeContext,  
org.apache.catalina.core.StandardWrapper,  
org.apache.tomcat.util.scan.StandardJarScanner,  
org.apache.tomcat.websocket.WsWebSocketContainer,  
org.apache.catalina.core]
```

ObjectName

```
java.util.logging:type=Logging
```

jdk.management.jfr

FlightRecorder

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

## Configurations

```
[{contents=<?xml version="1.0" encoding="UTF-8"?>
<!--
   Recommended way to edit .jfc files is to use Java Mission Control,
   see Window -> Flight Recorder Template Manager.
-->
<configuration version="2.0" label="Profiling" description="Low
overhead configuration for profiling, typically around 2 % overhead."
provider="Oracle">

<event name="jdk.ThreadAllocationStatistics">
<setting name="enabled">true</setting>
<setting name="period">everyChunk</setting>
</event>

<event name="jdk.ClassLoadingStatistics">
<setting name="enabled">true</setting>
<setting name="period">1000 ms</setting>
</event>

<event name="jdk.ClassLoaderStatistics">
<setting name="enabled">true</setting>
<setting name="period">everyChunk</setting>
</event>

<event name="jdk.JavaThreadStatistics">
<setting name="enabled">true</setting>
<setting name="period">1000 ms</setting>
</event>

<event name="jdk.ThreadStart">
<setting name="enabled">true</setting>
</event>

<event name="jdk.ThreadEnd">
<setting name="enabled">true</setting>
</event>

<event name="jdk.ThreadSleep">
<setting name="enabled">true</setting>
<setting name="stackTrace">true</setting>
<setting name="threshold" control="synchronization-threshold">10
ms</setting>
</event>

<event name="jdk.ThreadPark">
<setting name="enabled">true</setting>
<setting name="stackTrace">true</setting>
<setting name="threshold" control="synchronization-threshold">10
ms</setting>
</event>

<event name="jdk.JavaMonitorEnter">
<setting name="enabled">true</setting>
<setting name="stackTrace">true</setting>
<setting name="threshold" control="synchronization-threshold">10
ms</setting>
</event>

<event name="jdk.JavaMonitorWait">
<setting name="enabled">true</setting>
<setting name="stackTrace">true</setting>
<setting name="threshold" control="synchronization-threshold">10
ms</setting>
</event>

<event name="jdk.JavaMonitorInflate">
<setting name="enabled">true</setting>
<setting name="stackTrace">true</setting>
<setting name="threshold" control="synchronization-threshold">10
ms</setting>
</event>

<event name="jdk.BiasedLockRevocation">
<setting name="enabled">true</setting>
<setting name="stackTrace">true</setting>
<setting name="threshold">0 ms</setting>
</event>

<event name="jdk.BiasedLockSelfRevocation">
<setting name="enabled">true</setting>
<setting name="stackTrace">true</setting>
<setting name="threshold">0 ms</setting>
</event>

<event name="jdk.ReservedStackActivation">
<setting name="enabled">true</setting>
<setting name="stackTrace">true</setting>
</event>

<event name="jdk.ClassLoad">
<setting name="enabled" control="class-loading-
enabled">false</setting>
<setting name="stackTrace">true</setting>
<setting name="threshold">0 ms</setting>
</event>

<event name="jdk.ClassDefine">
<setting name="enabled" control="class-loading-
enabled">false</setting>
<setting name="stackTrace">true</setting>
</event>

<event name="jdk.ClassUnload">
<setting name="enabled" control="class-loading-
enabled">false</setting>
</event>

<event name="jdk.JVMInformation">
<setting name="enabled">true</setting>
<setting name="period">beginChunk</setting>
</event>

<event name="jdk.InitialSystemProperty">
<setting name="enabled">true</setting>
<setting name="period">beginChunk</setting>
</event>

<event name="jdk.ExecutionSample">
<setting name="enabled" control="method-sampling-
enabled">true</setting>
<setting name="period" control="method-sampling-java-
interval">10 ms</setting>
</event>

<event name="jdk.NativeMethodSample">
<setting name="enabled" control="method-sampling-
enabled">true</setting>
<setting name="period" control="method-sampling-native-
interval">20 ms</setting>
</event>
```

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

```
<event name="jdk.SafepointBegin">
<setting name="enabled">true</setting>
<setting name="threshold">0 ms</setting>
</event>

<event name="jdk.SafepointStateSynchronization">
<setting name="enabled">false</setting>
<setting name="threshold">0 ms</setting>
</event>

<event name="jdk.SafepointWaitBlocked">
<setting name="enabled">false</setting>
<setting name="threshold">0 ms</setting>
</event>

<event name="jdk.SafepointCleanup">
<setting name="enabled">false</setting>
<setting name="threshold">0 ms</setting>
</event>

<event name="jdk.SafepointCleanupTask">
<setting name="enabled">false</setting>
<setting name="threshold">0 ms</setting>
</event>

<event name="jdk.SafepointEnd">
<setting name="enabled">false</setting>
<setting name="threshold">0 ms</setting>
</event>

<event name="jdk.ExecuteVMOperation">
<setting name="enabled">true</setting>
<setting name="threshold">0 ms</setting>
</event>

<event name="jdk.Shutdown">
<setting name="enabled">true</setting>
<setting name="stackTrace">true</setting>
</event>

<event name="jdk.ThreadDump">
<setting name="enabled" control="thread-dump-enabled">true</setting>
<setting name="period" control="thread-dump-interval">60s</setting>
</event>

<event name="jdk.IntFlag">
<setting name="enabled">true</setting>
<setting name="period">beginChunk</setting>
</event>

<event name="jdk.UnsignedIntFlag">
<setting name="enabled">true</setting>
<setting name="period">beginChunk</setting>
</event>

<event name="jdk.LongFlag">
<setting name="enabled">true</setting>
<setting name="period">beginChunk</setting>
</event>

<event name="jdk.UnsignedLongFlag">
<setting name="enabled">true</setting>
<setting name="period">beginChunk</setting>
</event>

<event name="jdk.DoubleFlag">
<setting name="enabled">true</setting>
<setting name="period">beginChunk</setting>
</event>

<event name="jdk.BooleanFlag">
<setting name="enabled">true</setting>
<setting name="period">beginChunk</setting>
</event>

<event name="jdk.StringFlag">
<setting name="enabled">true</setting>
<setting name="period">beginChunk</setting>
</event>

<event name="jdk.IntFlagChanged">
<setting name="enabled">true</setting>
</event>

<event name="jdk.UnsignedIntFlagChanged">
<setting name="enabled">true</setting>
</event>

<event name="jdk.LongFlagChanged">
<setting name="enabled">true</setting>
</event>

<event name="jdk.UnsignedLongFlagChanged">
<setting name="enabled">true</setting>
</event>

<event name="jdk.DoubleFlagChanged">
<setting name="enabled">true</setting>
</event>

<event name="jdk.BooleanFlagChanged">
<setting name="enabled">true</setting>
</event>

<event name="jdk.StringFlagChanged">
<setting name="enabled">true</setting>
</event>

<event name="jdk.ObjectCount">
<setting name="enabled" control="memory-profiling-enabled-all">false</setting>
<setting name="period">everyChunk</setting>
</event>

<event name="jdk.GCConfiguration">
<setting name="enabled" control="gc-enabled-normal">true</setting>
<setting name="period">everyChunk</setting>
</event>

<event name="jdk.GCHeapConfiguration">
<setting name="enabled" control="gc-enabled-normal">true</setting>
<setting name="period">beginChunk</setting>
</event>

<event name="jdk.YoungGenerationConfiguration">
<setting name="enabled" control="gc-enabled-normal">true</setting>
<setting name="period">beginChunk</setting>
</event>

<event name="jdk.GCTLABConfiguration">
<setting name="enabled" control="gc-enabled-normal">true</setting>
</event>
```

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

```
<setting name="period">beginChunk</setting>
</event>

<event name="jdk.GCSurvivorConfiguration">
<setting name="enabled" control="gc-enabled-normal">true</setting>
<setting name="period">beginChunk</setting>
</event>

<event name="jdk.ObjectCountAfterGC">
<setting name="enabled">false</setting>
</event>

<event name="jdk.GCHeapSummary">
<setting name="enabled" control="gc-enabled-normal">true</setting>
</event>

<event name="jdk.PSHeapSummary">
<setting name="enabled" control="gc-enabled-normal">true</setting>
</event>

<event name="jdk.G1HeapSummary">
<setting name="enabled" control="gc-enabled-normal">true</setting>
</event>

<event name="jdk.Metaspacesummary">
<setting name="enabled" control="gc-enabled-normal">true</setting>
</event>

<event name="jdk.MetaspacesGCThreshold">
<setting name="enabled" control="gc-enabled-normal">true</setting>
</event>

<event name="jdk.MetaspacesAllocationFailure">
<setting name="enabled" control="gc-enabled-normal">true</setting>
<setting name="stackTrace">true</setting>
</event>

<event name="jdk.MetaspacesOOM">
<setting name="enabled" control="gc-enabled-normal">true</setting>
<setting name="stackTrace">true</setting>
</event>

<event name="jdk.MetaspacesChunkFreeListSummary">
<setting name="enabled" control="gc-enabled-normal">true</setting>
</event>

<event name="jdk.GarbageCollection">
<setting name="enabled" control="gc-enabled-normal">true</setting>
<setting name="threshold">0 ms</setting>
</event>

<event name="jdk.ParallelOldGarbageCollection">
<setting name="enabled" control="gc-enabled-normal">true</setting>
<setting name="threshold">0 ms</setting>
</event>

<event name="jdk.YoungGarbageCollection">
<setting name="enabled" control="gc-enabled-normal">true</setting>
<setting name="threshold">0 ms</setting>
</event>

<event name="jdk.OldGarbageCollection">
<setting name="enabled" control="gc-enabled-normal">true</setting>
<setting name="threshold">0 ms</setting>
</event>

<event name="jdk.G1GarbageCollection">
<setting name="enabled" control="gc-enabled-normal">true</setting>
<setting name="threshold">0 ms</setting>
</event>

<event name="jdk.GCPhasePause">
<setting name="enabled" control="gc-enabled-normal">true</setting>
<setting name="threshold">0 ms</setting>
</event>

<event name="jdk.GCPhasePauseLevel1">
<setting name="enabled" control="gc-enabled-normal">true</setting>
<setting name="threshold">0 ms</setting>
</event>

<event name="jdk.GCPhasePauseLevel2">
<setting name="enabled" control="gc-enabled-normal">true</setting>
<setting name="threshold">0 ms</setting>
</event>

<event name="jdk.GCPhasePauseLevel3">
<setting name="enabled" control="gc-enabled-all">false</setting>
<setting name="threshold">0 ms</setting>
</event>

<event name="jdk.GCPhasePauseLevel4">
<setting name="enabled" control="gc-enabled-all">false</setting>
<setting name="threshold">0 ms</setting>
</event>

<event name="jdk.GCPhaseConcurrent">
<setting name="enabled" control="gc-enabled-all">true</setting>
<setting name="threshold">0 ms</setting>
</event>

<event name="jdk.GCReferenceStatistics">
<setting name="enabled" control="gc-enabled-normal">true</setting>
</event>

<event name="jdk.PromotionFailed">
<setting name="enabled" control="gc-enabled-normal">true</setting>
</event>

<event name="jdk.EvacuationFailed">
<setting name="enabled" control="gc-enabled-normal">true</setting>
</event>

<event name="jdk.EvacuationInformation">
<setting name="enabled" control="gc-enabled-normal">true</setting>
</event>
```

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

```
<event name="jdk.G1MMU">
  <setting name="enabled" control="gc-enabled-normal">true</setting>
</event>

<event name="jdk.G1EvacuationYoungStatistics">
  <setting name="enabled" control="gc-enabled-normal">true</setting>
</event>

<event name="jdk.G1EvacuationOldStatistics">
  <setting name="enabled" control="gc-enabled-normal">true</setting>
</event>

<event name="jdk.G1BasicIHOP">
  <setting name="enabled" control="gc-enabled-normal">true</setting>
</event>

<event name="jdk.G1AdaptiveIHOP">
  <setting name="enabled" control="gc-enabled-normal">true</setting>
</event>

<event name="jdk.PromoteObjectInNewPLAB">
  <setting name="enabled" control="memory-profiling-enabled-medium">true</setting>
</event>

<event name="jdk.PromoteObjectOutsidePLAB">
  <setting name="enabled" control="memory-profiling-enabled-medium">true</setting>
</event>

<event name="jdk.ConcurrentModeFailure">
  <setting name="enabled" control="gc-enabled-normal">true</setting>
</event>

<event name="jdk.AllocationRequiringGC">
  <setting name="enabled" control="gc-enabled-all">false</setting>
  <setting name="stackTrace">true</setting>
</event>

<event name="jdk.TenuringDistribution">
  <setting name="enabled" control="gc-enabled-normal">true</setting>
</event>

<event name="jdk.G1HeapRegionInformation">
  <setting name="enabled" control="gc-enabled-all">false</setting>
  <setting name="period">everyChunk</setting>
</event>

<event name="jdk.G1HeapRegionTypeChange">
  <setting name="enabled" control="gc-enabled-all">false</setting>
</event>

<event name="jdk.OldObjectSample">
  <setting name="enabled" control="memory-leak-detection-enabled">true</setting>
  <setting name="stackTrace" control="memory-leak-detection-stack-trace">true</setting>
  <setting name="cutoff" control="memory-leak-detection-cutoff">0ns</setting>
</event>

<event name="jdk.CompilerConfiguration">
  <setting name="enabled" control="compiler-enabled">true</setting>
  <setting name="period">beginChunk</setting>
</event>

<event name="jdk.CompilerStatistics">
  <setting name="enabled" control="compiler-enabled">true</setting>
  <setting name="period">1000 ms</setting>
</event>

<event name="jdk.Compilation">
  <setting name="enabled" control="compiler-enabled">true</setting>
  <setting name="threshold" control="compiler-compilation-threshold">100 ms</setting>
</event>

<event name="jdk.CompilerPhase">
  <setting name="enabled" control="compiler-enabled">true</setting>
  <setting name="threshold" control="compiler-phase-threshold">10s</setting>
</event>

<event name="jdk.CompilationFailure">
  <setting name="enabled" control="compiler-enabled-failure">true</setting>
</event>

<event name="jdk.CompilerInlining">
  <setting name="enabled" control="compiler-enabled-failure">false</setting>
</event>

<event name="jdk.CodeSweeperConfiguration">
  <setting name="enabled" control="compiler-enabled">true</setting>
  <setting name="period">beginChunk</setting>
</event>

<event name="jdk.CodeSweeperStatistics">
  <setting name="enabled" control="compiler-enabled">true</setting>
  <setting name="period">everyChunk</setting>
</event>

<event name="jdk.SweepCodeCache">
  <setting name="enabled" control="compiler-enabled">true</setting>
  <setting name="threshold" control="compiler-sweeper-threshold">100 ms</setting>
</event>

<event name="jdk.CodeCacheConfiguration">
  <setting name="enabled" control="compiler-enabled">true</setting>
  <setting name="period">beginChunk</setting>
</event>

<event name="jdk.CodeCacheStatistics">
  <setting name="enabled" control="compiler-enabled">true</setting>
  <setting name="period">everyChunk</setting>
</event>

<event name="jdk.CodeCacheFull">
  <setting name="enabled" control="compiler-enabled">true</setting>
</event>
```

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

```
</event>
<event name="jdk.OSInformation">
<setting name="enabled">true</setting>
<setting name="period">beginChunk</setting>
</event>
<event name="jdk.VirtualizationInformation">
<setting name="enabled">true</setting>
<setting name="period">beginChunk</setting>
</event>
<event name="jdk.ThreadContextSwitchRate">
<setting name="enabled" control="compiler-enabled">true</setting>
<setting name="period">10 s</setting>
</event>
<event name="jdk.CPULoad">
<setting name="enabled">true</setting>
<setting name="period">1000 ms</setting>
</event>
<event name="jdk.ThreadCPULoad">
<setting name="enabled">true</setting>
<setting name="period">10 s</setting>
</event>
<event name="jdk.CPUTimeStampCounter">
<setting name="enabled">true</setting>
<setting name="period">beginChunk</setting>
</event>
<event name="jdk.SystemProcess">
<setting name="enabled">true</setting>
<setting name="period">endChunk</setting>
</event>
<event name="jdk.NetworkUtilization">
<setting name="enabled">true</setting>
<setting name="period">5 s</setting>
</event>
<event name="jdk.InitialEnvironmentVariable">
<setting name="enabled">true</setting>
<setting name="period">beginChunk</setting>
</event>
<event name="jdk.PhysicalMemory">
<setting name="enabled">true</setting>
<setting name="period">everyChunk</setting>
</event>
<event name="jdk.ObjectAllocationInNewTLAB">
<setting name="enabled" control="memory-profiling-enabled-medium">true</setting>
<setting name="stackTrace">true</setting>
</event>
<event name="jdk.ObjectAllocationOutsideTLAB">
<setting name="enabled" control="memory-profiling-enabled-medium">true</setting>
<setting name="stackTrace">true</setting>
</event>
<event name="jdk.NativeLibrary">
<setting name="enabled">true</setting>
<setting name="period">everyChunk</setting>
</event>
<event name="jdk.ModuleRequire">
<setting name="enabled">true</setting>
<setting name="period">endChunk</setting>
</event>
<event name="jdk.ModuleExport">
<setting name="enabled">true</setting>
<setting name="period">endChunk</setting>
</event>
<event name="jdk.FileForce">
<setting name="enabled">true</setting>
<setting name="stackTrace">true</setting>
<setting name="threshold" control="file-io-threshold">10
ms</setting>
</event>
<event name="jdk.FileRead">
<setting name="enabled">true</setting>
<setting name="stackTrace">true</setting>
<setting name="threshold" control="file-io-threshold">10
ms</setting>
</event>
<event name="jdk.FileWrite">
<setting name="enabled">true</setting>
<setting name="stackTrace">true</setting>
<setting name="threshold" control="file-io-threshold">10
ms</setting>
</event>
<event name="jdk.SocketRead">
<setting name="enabled">true</setting>
<setting name="stackTrace">true</setting>
<setting name="threshold" control="socket-io-threshold">10
ms</setting>
</event>
<event name="jdk.SocketWrite">
<setting name="enabled">true</setting>
<setting name="stackTrace">true</setting>
<setting name="threshold" control="socket-io-threshold">10
ms</setting>
</event>
<event name="jdk.SecurityPropertyModification">
<setting name="enabled">false</setting>
<setting name="stackTrace">true</setting>
</event>
<event name="jdk.TLSHandshake">
<setting name="enabled">false</setting>
<setting name="stackTrace">true</setting>
</event>
<event name="jdk.X509Validation">
<setting name="enabled">false</setting>
<setting name="stackTrace">true</setting>
</event>
<event name="jdk.X509Certificate">
<setting name="enabled">false</setting>
<setting name="stackTrace">true</setting>
</event>
```

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

```
</event>
<event name="jdk.JavaExceptionThrow">
<setting name="enabled" control="enable-exceptions">false</setting>
<setting name="stackTrace">true</setting>
</event>
<event name="jdk.JavaErrorThrow">
<setting name="enabled" control="enable-errors">true</setting>
<setting name="stackTrace">true</setting>
</event>
<event name="jdk.ExceptionStatistics">
<setting name="enabled">true</setting>
<setting name="period">1000 ms</setting>
</event>
<event name="jdk.ActiveRecording">
<setting name="enabled">true</setting>
</event>
<event name="jdk.ActiveSetting">
<setting name="enabled">true</setting>
</event>
<event name="jdk.DataLoss">
<setting name="enabled">true</setting>
</event>
<event name="jdk.DumpReason">
<setting name="enabled">true</setting>
</event>
<event name="jdk.ZPageAllocation">
<setting name="enabled">true</setting>
<setting name="threshold">10 ms</setting>
</event>
<event name="jdk.ZThreadPhase">
<setting name="enabled">true</setting>
<setting name="threshold">0 ms</setting>
</event>
<event name="jdk.ZStatisticsCounter">
<setting name="threshold">10 ms</setting>
<setting name="enabled">true</setting>
</event>
<event name="jdk.ZStatisticsSampler">
<setting name="enabled">true</setting>
<setting name="threshold">10 ms</setting>
</event>
```

```
<!--
   Contents of the control element is not read by the JVM, it's used
   by Java Mission Control to change settings that carry the control
   attribute.
-->
<control>
<selection name="gc-level" default="detailed" label="Garbage
Collector">
<option label="Off" name="off">off</option>
<option label="Normal" name="normal">normal</option>
<option label="All" name="all">all</option>
</selection>
<condition name="gc-enabled-normal" true="true" false="false">
<or>
<test name="gc-level" operator="equal" value="normal"/>
<test name="gc-level" operator="equal" value="all"/>
</or>
</condition>
<condition name="gc-enabled-all" true="true" false="false">
<test name="gc-level" operator="equal" value="all"/>
</condition>
<selection name="memory-profiling" default="medium"
label="Memory Profiling">
<option label="Off" name="off">off</option>
<option label="Object Allocation and Promotion"
name="medium">medium</option>
<option label="All, including Heap Statistics (May cause long full
GCs)" name="all">all</option>
</selection>
<condition name="memory-profiling-enabled-medium" true="true"
false="false">
<or>
<test name="memory-profiling" operator="equal"
value="medium"/>
<test name="memory-profiling" operator="equal" value="all"/>
</or>
</condition>
<condition name="memory-profiling-enabled-all" true="true"
false="false">
<test name="memory-profiling" operator="equal" value="all"/>
</condition>
<selection name="compiler-level" default="detailed"
label="Compiler">
<option label="Off" name="off">off</option>
<option label="Normal" name="normal">normal</option>
<option label="Detailed" name="detailed">detailed</option>
<option label="All" name="all">all</option>
</selection>
```

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

```
<condition name="compiler-enabled" true="false" false="true">
<test name="compiler-level" operator="equal" value="off"/>
</condition>

<condition name="compiler-enabled-failure" true="true"
false="false">
<or>
<test name="compiler-level" operator="equal" value="detailed"/>
<test name="compiler-level" operator="equal" value="all"/>
</or>
</condition>

<condition name="compiler-sweeper-threshold" true="0 ms"
false="100 ms">
<test name="compiler-level" operator="equal" value="all"/>
</condition>

<condition name="compiler-compilation-threshold" true="1000
ms">
<test name="compiler-level" operator="equal" value="normal"/>
</condition>

<condition name="compiler-compilation-threshold" true="100 ms">
<test name="compiler-level" operator="equal" value="detailed"/>
</condition>

<condition name="compiler-compilation-threshold" true="0 ms">
<test name="compiler-level" operator="equal" value="all"/>
</condition>

<condition name="compiler-phase-threshold" true="60 s">
<test name="compiler-level" operator="equal" value="normal"/>
</condition>

<condition name="compiler-phase-threshold" true="10 s">
<test name="compiler-level" operator="equal" value="detailed"/>
</condition>

<condition name="compiler.phase-threshold" true="0 s">
<test name="compiler-level" operator="equal" value="all"/>
</condition>

<selection name="method-sampling-interval" default="normal"
label="Method Sampling">
<option label="Off" name="off">off</option>
<option label="Normal" name="normal">normal</option>
<option label="High" name="high">high</option>
<option label="Ludicrous (High Overhead)" name="ludicrous">ludicrous</option>
</selection>

<condition name="method-sampling-java-interval" true="999 d">
<test name="method-sampling-interval" operator="equal"
value="off"/>
</condition>

<condition name="method-sampling-java-interval" true="20 ms">
<test name="method-sampling-interval" operator="equal"
value="normal"/>
</condition>

<condition name="method-sampling-java-interval" true="10 ms">
<test name="method-sampling-interval" operator="equal"
value="high"/>
</condition>

<condition name="method-sampling-java-interval" true="1 ms">
<test name="method-sampling-interval" operator="equal"
value="ludicrous"/>
</condition>

<condition name="method-sampling-native-interval" true="999 d">
<test name="method-sampling-interval" operator="equal"
value="off"/>
</condition>

<condition name="method-sampling-native-interval" true="20 ms">
<or>
<test name="method-sampling-interval" operator="equal"
value="normal"/>
<test name="method-sampling-interval" operator="equal"
value="high"/>
<test name="method-sampling-interval" operator="equal"
value="ludicrous"/>
</or>
</condition>

<condition name="method-sampling-enabled" true="false"
false="true">
<test name="method-sampling-interval" operator="equal"
value="off"/>
</condition>

<selection name="thread-dump-interval" default="everyMinute"
label="Thread Dump">
<option label="Off" name="off">999 d</option>
<option label="At least Once" name="normal">everyChunk</option>
<option label="Every 60 s" name="everyMinute">60 s</option>
<option label="Every 10 s" name="everyTenSecond">10
s</option>
<option label="Every 1 s" name="everySecond">1 s</option>
</selection>

<condition name="thread-dump-enabled" true="false" false="true">
<test name="thread-dump-interval" operator="equal" value="999
d"/>
</condition>

<selection name="exception-level" default="errors"
label="Exceptions">
<option label="Off" name="off">off</option>
<option label="Errors Only" name="errors">errors</option>
<option label="All Exceptions, including Errors" name="all">all</option>
</selection>

<condition name="enable-errors" true="true" false="false">
<or>
<test name="exception-level" operator="equal" value="errors"/>
<test name="exception-level" operator="equal" value="all"/>
</or>
</condition>

<condition name="enable-exceptions" true="true" false="false">
<test name="exception-level" operator="equal" value="all"/>
</condition>

<selection name="memory-leak-detection" default="medium"
label="Memory Leak Detection">
<option label="Off" name="off">off</option>
<option label="Object Types" name="minimal">minimal</option>
<option label="Object Types + Allocation Stack Traces"
name="medium">medium</option>
<option label="Object Types + Allocation Stack Traces + Path to
GC Root" name="full">full</option>
</selection>
```

```
<condition name="memory-leak-detection-enabled" true="false"
false="true">
<test name="memory-leak-detection" operator="equal"
value="off"/>
</condition>

<condition name="memory-leak-detection-stack-trace" true="true"
false="false">
<or>
<test name="memory-leak-detection" operator="equal"
value="medium"/>
<test name="memory-leak-detection" operator="equal"
value="full"/>
</or>
</condition>

<condition name="memory-leak-detection-cutoff" true="1 h"
false="0 ns">
<test name="memory-leak-detection" operator="equal"
value="full"/>
</condition>

<text name="synchronization-threshold" label="Synchronization
Threshold" contentType="timespan" minimum="0 s">10 ms</text>

<text name="file-io-threshold" label="File I/O Threshold"
contentType="timespan" minimum="0 s">10 ms</text>

<text name="socket-io-threshold" label="Socket I/O Threshold"
contentType="timespan" minimum="0 s">10 ms</text>

<flag name="class-loading-enabled" label="Class
Loading">false</flag>

</control>

</configuration>
<description>Low overhead configuration for profiling, typically around
2 % overhead., label=Profiling, name=profile, provider=Oracle,
settings=[{key=jdk.ThreadAllocationStatistics#enabled, value=true},
{key=jdk.ThreadAllocationStatistics#period, value=everyChunk},
{key=jdk.ClassLoadingStatistics#enabled, value=true},
{key=jdk.ClassLoadingStatistics#period, value=1000 ms},
{key=jdk.ClassLoaderStatistics#enabled, value=true},
{key=jdk.ClassLoaderStatistics#period, value=everyChunk},
{key=jdk.JavaThreadStatistics#enabled, value=true},
{key=jdk.JavaThreadStatistics#period, value=1000 ms},
{key=jdk.ThreadStart#enabled, value=true},
{key=jdk.ThreadEnd#enabled, value=true},
{key=jdk.ThreadSleep#enabled, value=true},
{key=jdk.ThreadSleep#stackTrace, value=true},
{key=jdk.ThreadSleep#threshold, value=10 ms},
{key=jdk.ThreadPark#enabled, value=true},
{key=jdk.ThreadPark#stackTrace, value=true},
{key=jdk.ThreadPark#threshold, value=10 ms},
{key=jdk.JavaMonitorEnter#stackTrace, value=true},
{key=jdk.JavaMonitorEnter#threshold, value=10 ms},
{key=jdk.JavaMonitorWait#enabled, value=true},
{key=jdk.JavaMonitorWait#stackTrace, value=true},
{key=jdk.JavaMonitorInflate#enabled, value=true},
{key=jdk.JavaMonitorInflate#stackTrace, value=true},
{key=jdk.BiasedLockRevocation#enabled, value=true},
{key=jdk.BiasedLockRevocation#threshold, value=0 ms},
{key=jdk.BiasedLockSelfRevocation#enabled, value=true},
{key=jdk.BiasedLockSelfRevocation#stackTrace, value=true},
{key=jdk.BiasedLockSelfRevocation#threshold, value=0 ms},
{key=jdk.BiasedLockClassRevocation#enabled, value=true},
{key=jdk.BiasedLockClassRevocation#stackTrace, value=true},
{key=jdk.ReservedStackActivation#enabled, value=true},
{key=jdk.ReservedStackActivation#stackTrace, value=true},
{key=jdk.ClassLoad#enabled, value=false},
{key=jdk.ClassLoad#stackTrace, value=true},
{key=jdk.ClassDefine#stackTrace, value=false},
{key=jdk.ClassUnload#enabled, value=false},
{key=jdk.JVMInformation#enabled, value=true},
{key=jdk.JVMInformation#period, value=beginChunk},
{key=jdk.InitialSystemProperty#enabled, value=true},
{key=jdk.InitialSystemProperty#period, value=beginChunk},
{key=jdk.ExecutionSample#enabled, value=true},
{key=jdk.ExecutionSample#period, value=10 ms},
{key=jdk.NativeMethodSample#enabled, value=true},
{key=jdk.NativeMethodSample#period, value=20 ms},
{key=jdk.SafepointBegin#enabled, value=true},
{key=jdk.SafepointBegin#threshold, value=0 ms},
{key=jdk.SafepointStateSynchronization#enabled, value=false},
{key=jdk.SafepointStateSynchronization#threshold, value=0 ms},
{key=jdk.SafepointWaitBlocked#enabled, value=false},
{key=jdk.SafepointWaitBlocked#threshold, value=0 ms},
{key=jdk.SafepointCleanup#enabled, value=false},
{key=jdk.SafepointCleanup#threshold, value=0 ms},
{key=jdk.SafepointCleanupTask#enabled, value=false},
{key=jdk.SafepointCleanupTask#threshold, value=0 ms},
{key=jdk.SafepointEnd#enabled, value=false},
{key=jdk.SafepointEnd#threshold, value=0 ms},
{key=jdk.ExecuteVMOperation#enabled, value=true},
{key=jdk.ExecuteVMOperation#threshold, value=0 ms},
{key=jdk.Shutdown#enabled, value=true},
{key=jdk.Shutdown#stackTrace, value=true},
{key=jdk.ThreadDump#enabled, value=true},
{key=jdk.ThreadDump#period, value=60 s}, {key=jdk.IntFlag#enabled,
value=true}, {key=jdk.UlongFlag#enabled, value=beginChunk},
{key=jdk.UsignedIntFlag#enabled, value=true},
{key=jdk.UsignedIntFlag#period, value=beginChunk},
{key=jdk.LongFlag#enabled, value=true}, {key=jdk.LongFlag#period,
value=beginChunk}, {key=jdk.UsignedLongFlag#enabled,
value=true}, {key=jdk.UsignedLongFlag#period, value=beginChunk},
{key=jdk.DoubleFlag#enabled, value=true},
{key=jdk.DoubleFlag#period, value=beginChunk},
{key=jdk.BooleanFlag#enabled, value=true},
{key=jdk.BooleanFlag#period, value=beginChunk},
{key=jdk.StringFlag#enabled, value=true}, {key=jdk.StringFlag#period,
value=beginChunk}, {key=jdk.IntFlagChanged#enabled, value=true},
{key=jdk.UsignedIntFlagChanged#enabled, value=true},
{key=jdk.LongFlagChanged#enabled, value=true},
{key=jdk.UsignedLongFlagChanged#enabled, value=true},
{key=jdk.DoubleFlagChanged#enabled, value=true},
{key=jdk.BooleanFlagChanged#enabled, value=true},
{key=jdk.StringFlagChanged#enabled, value=true},
{key=jdk.ObjectCount#enabled, value=false},
{key=jdk.ObjectCount#period, value=everyChunk},
{key=jdk.GCConfiguration#enabled, value=true},
{key=jdk.GCConfiguration#period, value=everyChunk},
{key=jdk.GCHHeapConfiguration#enabled, value=true},
{key=jdk.GCHHeapConfiguration#period, value=beginChunk},
{key=jdk.GCHHeapConfiguration#threshold, value=beginChunk},
{key=jdk.YoungGenerationConfiguration#enabled, value=true},
{key=jdk.YoungGenerationConfiguration#period, value=beginChunk},
{key=jdk.GCConfiguration#enabled, value=true},
{key=jdk.GCConfiguration#period, value=beginChunk},
{key=jdk.GCTLABConfiguration#enabled, value=true},
{key=jdk.GCTLABConfiguration#period, value=beginChunk},
{key=jdk.GCSurvivorConfiguration#enabled, value=true},
{key=jdk.GCSurvivorConfiguration#period, value=beginChunk},
{key=jdk.ObjectCountAfterGC#enabled, value=false},
```

```
{key=dk.GCHeapSummary#enabled, value=true},  
{key=dk.PSHHeapSummary#enabled, value=true},  
{key=dk.G1HeapSummary#enabled, value=true},  
{key=dk.MetaspaceSummary#enabled, value=true},  
{key=dk.MetaspaceGCThreshold#enabled, value=true},  
{key=dk.MetaspaceAllocationFailure#enabled, value=true},  
{key=dk.MetaspaceAllocationFailure#stackTrace, value=true},  
{key=dk.MetaspaceOOM#enabled, value=true},  
{key=dk.MetaspaceOOM#stackTrace, value=true},  
{key=dk.MetaspaceChunkFreeListSummary#enabled, value=true},  
{key=dk.GarbageCollection#enabled, value=true},  
{key=dk.GarbageCollection#threshold, value=0 ms},  
{key=dk.ParallelOldGarbageCollection#enabled, value=true},  
{key=dk.ParallelOldGarbageCollection#threshold, value=0 ms},  
{key=dk.YoungGarbageCollection#enabled, value=true},  
{key=dk.YoungGarbageCollection#threshold, value=0 ms},  
{key=dk.OldGarbageCollection#enabled, value=true},  
{key=dk.OldGarbageCollection#threshold, value=0 ms},  
{key=dk.G1GarbageCollection#enabled, value=true},  
{key=dk.G1GarbageCollection#threshold, value=0 ms},  
{key=dk.GCPhasePause#enabled, value=true},  
{key=dk.GCPhasePause#threshold, value=0 ms},  
{key=dk.GCPhasePauseLevel1#enabled, value=true},  
{key=dk.GCPhasePauseLevel1#threshold, value=0 ms},  
{key=dk.GCPhasePauseLevel2#enabled, value=true},  
{key=dk.GCPhasePauseLevel2#threshold, value=0 ms},  
{key=dk.GCPhasePauseLevel3#enabled, value=false},  
{key=dk.GCPhasePauseLevel3#threshold, value=0 ms},  
{key=dk.GCPhasePauseLevel4#enabled, value=false},  
{key=dk.GCPhasePauseLevel4#threshold, value=0 ms},  
{key=dk.GCPhaseConcurrent#enabled, value=true},  
{key=dk.GCPhaseConcurrent#threshold, value=0 ms},  
{key=dk.GCReferenceStatistics#enabled, value=true},  
{key=dk.PromotionFailed#enabled, value=true},  
{key=dk.EvacuationFailed#enabled, value=true},  
{key=dk.EvacuationInformation#enabled, value=true},  
{key=dk.G1MMU#enabled, value=true},  
{key=dk.G1EvacuationYoungStatistics#enabled, value=true},  
{key=dk.G1EvacuationOldStatistics#enabled, value=true},  
{key=dk.G1BasicIOP#enabled, value=true},  
{key=dk.G1AdaptiveIOP#enabled, value=true},  
{key=dk.PromoteObjectInNewPLAB#enabled, value=true},  
{key=dk.PromoteObjectOutsidePLAB#enabled, value=true},  
{key=dk.ConcurrentModeFailure#enabled, value=true},  
{key=dk.AllocationRequiringGC#enabled, value=false},  
{key=dk.AllocationRequiringGC#stackTrace, value=true},  
{key=dk.TenuringDistribution#enabled, value=true},  
{key=dk.G1HeapRegionInformation#enabled, value=false},  
{key=dk.G1HeapRegionInformation#period, value=everyChunk},  
{key=dk.G1HeapRegionTypeChange#enabled, value=false},  
{key=dk.OldObjectSample#enabled, value=true},  
{key=dk.OldObjectSample#stackTrace, value=true},  
{key=dk.OldObjectSample#cutoff, value=0 ns},  
{key=dk.CompilerConfiguration#enabled, value=true},  
{key=dk.CompilerConfiguration#period, value=beginChunk},  
{key=dk.CompileStatistics#enabled, value=true},  
{key=dk.CompilerStatistics#period, value=1000 ms},  
{key=dk.Compilation#enabled, value=true},  
{key=dk.Compilation#threshold, value=100 ms},  
{key=dk.CompilerPhase#enabled, value=true},  
{key=dk.CompilerPhase#threshold, value=10 s},  
{key=dk.CompilationFailure#enabled, value=true},  
{key=dk.CompilerInlining#enabled, value=false},  
{key=dk.CodeSweeperConfiguration#enabled, value=true},  
{key=dk.CodeSweeperConfiguration#period, value=beginChunk},  
{key=dk.CodeSweeperStatistics#enabled, value=true},  
{key=dk.CodeSweeperStatistics#period, value=everyChunk},  
{key=dk.SweepCodeCache#enabled, value=true},  
{key=dk.SweepCodeCache#threshold, value=100 ms},  
{key=dk.CodeCacheConfiguration#enabled, value=true},  
{key=dk.CodeCacheConfiguration#period, value=beginChunk},  
{key=dk.CodeCacheStatistics#enabled, value=true},  
{key=dk.CodeCacheStatistics#period, value=everyChunk},  
{key=dk.CodeCacheFull#enabled, value=true},  
{key=dk.OSInformation#enabled, value=true},  
{key=dk.OSInformation#period, value=beginChunk},  
{key=dk.VirtualizationInformation#enabled, value=true},  
{key=dk.VirtualizationInformation#period, value=beginChunk},  
{key=dk.CPUInformation#enabled, value=true},  
{key=dk.CPUInformation#period, value=beginChunk},  
{key=dk.ThreadContextSwitchRate#enabled, value=true},  
{key=dk.ThreadContextSwitchRate#period, value=10 s},  
{key=dk.CPULoad#enabled, value=true}, {key=dk.CPULoad#period, value=1000 ms}, {key=dk.ThreadCPULoad#period, value=10 s},  
{key=dk.CPUTimeStampCounter#enabled, value=true},  
{key=dk.CPUTimeStampCounter#period, value=beginChunk},  
{key=dk.SystemProcess#enabled, value=true},  
{key=dk.SystemProcess#period, value=endChunk},  
{key=dk.NetworkUtilization#enabled, value=true},  
{key=dk.NetworkUtilization#period, value=5 s},  
{key=dk.InitialEnvironmentVariable#enabled, value=true},  
{key=dk.InitialEnvironmentVariable#period, value=beginChunk},  
{key=dk.PhysicalMemory#enabled, value=true},  
{key=dk.PhysicalMemory#period, value=everyChunk},  
{key=dk.ObjectAllocationInNewTLAB#enabled, value=true},  
{key=dk.ObjectAllocationInNewTLAB#stackTrace, value=true},  
{key=dk.ObjectAllocationOutsideTLAB#enabled, value=true},  
{key=dk.ObjectAllocationOutsideTLAB#stackTrace, value=true},  
{key=dk.NativeLibrary#enabled, value=true},  
{key=dk.NativeLibrary#period, value=everyChunk},  
{key=dk.ModuleRequire#enabled, value=true},  
{key=dk.ModuleRequire#period, value=endChunk},  
{key=dk.ModuleExport#enabled, value=true},  
{key=dk.ModuleExport#period, value=endChunk},  
{key=dk.FileForce#enabled, value=true},  
{key=dk.FileForce#stackTrace, value=true},  
{key=dk.FileForce#threshold, value=10 ms},  
{key=dk.FileRead#enabled, value=true},  
{key=dk.FileRead#stackTrace, value=true},  
{key=dk.FileRead#threshold, value=10 ms},  
{key=dk.FileWrite#enabled, value=true},  
{key=dk.FileWrite#stackTrace, value=true},  
{key=dk.FileWrite#threshold, value=10 ms},  
{key=dk.SocketRead#enabled, value=true},  
{key=dk.SocketRead#stackTrace, value=true},  
{key=dk.SocketRead#threshold, value=10 ms},  
{key=dk.SocketWrite#enabled, value=true},  
{key=dk.SocketWrite#stackTrace, value=true},  
{key=dk.SocketWrite#threshold, value=10 ms},  
{key=dk.SecurityPropertyModification#enabled, value=false},  
{key=dk.SecurityPropertyModification#stackTrace, value=true},  
{key=dk.TLSHandshake#enabled, value=false},  
{key=dk.TLSHandshake#stackTrace, value=true},  
{key=dk.X509Validation#enabled, value=false},  
{key=dk.X509Validation#stackTrace, value=true},  
{key=dk.X509Certificate#enabled, value=false},  
{key=dk.X509Certificate#stackTrace, value=true},  
{key=dk.JavaExceptionThrow#enabled, value=false},  
{key=dk.JavaExceptionThrow#stackTrace, value=true},  
{key=dk.JavaErrorThrow#enabled, value=true},  
{key=dk.JavaErrorThrow#stackTrace, value=true},  
{key=dk.ExceptionStatistics#enabled, value=true},  
{key=dk.ExceptionStatistics#period, value=1000 ms},  
{key=dk.ActiveRecording#enabled, value=true},  
{key=dk.ActiveSetting#enabled, value=true},  
{key=dk.DataLoss#enabled, value=true},  
{key=dk.DumpReason#enabled, value=true},
```

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

```
{key=jdk.ZPageAllocation#enabled, value=true},  
{key=jdk.ZPageAllocation#threshold, value=10 ms},  
{key=jdk.ZThreadPhase#enabled, value=true},  
{key=jdk.ZThreadPhase#threshold, value=0 ms},  
{key=jdk.ZStatisticsCounter#threshold, value=10 ms},  
{key=jdk.ZStatisticsCounter#enabled, value=true},  
{key=jdk.ZStatisticsSampler#enabled, value=true},  
{key=jdk.ZStatisticsSampler#threshold, value=10 ms}}],  
{contents=<?xml version="1.0" encoding="UTF-8"?>  
<!--  
Recommended way to edit .jfc files is to use Java Mission Control,  
see Window -> Flight Recorder Template Manager.  
-->  
<configuration version="2.0" label="Continuous" description="Low  
overhead configuration safe for continuous use in production  
environments, typically less than 1 % overhead." provider="Oracle">  
<event name="jdk.ThreadAllocationStatistics">  
<setting name="enabled">true</setting>  
<setting name="period">everyChunk</setting>  
</event>  
<event name="jdk.ClassLoadingStatistics">  
<setting name="enabled">true</setting>  
<setting name="period">1000 ms</setting>  
</event>  
<event name="jdk.ClassLoaderStatistics">  
<setting name="enabled">true</setting>  
<setting name="period">everyChunk</setting>  
</event>  
<event name="jdk.JavaThreadStatistics">  
<setting name="enabled">true</setting>  
<setting name="period">1000 ms</setting>  
</event>  
<event name="jdk.ThreadStart">  
<setting name="enabled">true</setting>  
</event>  
<event name="jdk.ThreadEnd">  
<setting name="enabled">true</setting>  
</event>  
<event name="jdk.ThreadSleep">  
<setting name="enabled">true</setting>  
<setting name="stackTrace">true</setting>  
<setting name="threshold" control="synchronization-threshold">20  
ms</setting>  
</event>  
<event name="jdk.ThreadPark">  
<setting name="enabled">true</setting>  
<setting name="stackTrace">true</setting>  
<setting name="threshold" control="synchronization-threshold">20  
ms</setting>  
</event>  
<event name="jdk.JavaMonitorEnter">  
<setting name="enabled">true</setting>  
<setting name="stackTrace">true</setting>  
<setting name="threshold" control="synchronization-threshold">20  
ms</setting>  
</event>  
<event name="jdk.JavaMonitorWait">  
<setting name="enabled">true</setting>  
<setting name="stackTrace">true</setting>  
<setting name="threshold" control="synchronization-threshold">20  
ms</setting>  
</event>  
<event name="jdk.JavaMonitorInflate">  
<setting name="enabled">false</setting>  
<setting name="stackTrace">true</setting>  
<setting name="threshold" control="synchronization-threshold">20  
ms</setting>  
</event>  
<event name="jdk.BiasedLockRevocation">  
<setting name="enabled">true</setting>  
<setting name="stackTrace">true</setting>  
<setting name="threshold">0 ms</setting>  
</event>  
<event name="jdk.BiasedLockSelfRevocation">  
<setting name="enabled">true</setting>  
<setting name="stackTrace">true</setting>  
<setting name="threshold">0 ms</setting>  
</event>  
<event name="jdk.BiasedLockClassRevocation">  
<setting name="enabled">true</setting>  
<setting name="stackTrace">true</setting>  
<setting name="threshold">0 ms</setting>  
</event>  
<event name="jdk.ReservedStackActivation">  
<setting name="enabled">true</setting>  
<setting name="stackTrace">true</setting>  
</event>  
<event name="jdk.ClassLoad">  
<setting name="enabled" control="class-loading-  
enabled">false</setting>  
<setting name="stackTrace">true</setting>  
<setting name="threshold">0 ms</setting>  
</event>  
<event name="jdk.ClassDefine">  
<setting name="enabled" control="class-loading-  
enabled">false</setting>  
<setting name="stackTrace">true</setting>  
</event>  
<event name="jdk.ClassUnload">  
<setting name="enabled" control="class-loading-  
enabled">false</setting>  
<setting name="stackTrace">true</setting>  
</event>  
<event name="jdk.JVMInformation">  
<setting name="enabled">true</setting>  
<setting name="period">beginChunk</setting>  
</event>  
<event name="jdk.InitialSystemProperty">  
<setting name="enabled">true</setting>  
<setting name="period">beginChunk</setting>  
</event>  
<event name="jdk.ExecutionSample">  
<setting name="enabled" control="method-sampling-  
enabled">true</setting>  
<setting name="period" control="method-sampling-java-  
interval">20 ms</setting>
```

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

```
</event>
<event name="jdk.NativeMethodSample">
<setting name="enabled" control="method-sampling-enabled">true</setting>
<setting name="period" control="method-sampling-native-interval">20 ms</setting>
</event>
<event name="jdk.SafepointBegin">
<setting name="enabled">true</setting>
<setting name="threshold">10 ms</setting>
</event>
<event name="jdk.SafepointStateSynchronization">
<setting name="enabled">false</setting>
<setting name="threshold">10 ms</setting>
</event>
<event name="jdk.SafepointWaitBlocked">
<setting name="enabled">false</setting>
<setting name="threshold">10 ms</setting>
</event>
<event name="jdk.SafepointCleanup">
<setting name="enabled">false</setting>
<setting name="threshold">10 ms</setting>
</event>
<event name="jdk.SafepointCleanupTask">
<setting name="enabled">false</setting>
<setting name="threshold">10 ms</setting>
</event>
<event name="jdk.SafepointEnd">
<setting name="enabled">false</setting>
<setting name="threshold">10 ms</setting>
</event>
<event name="jdk.ExecuteVMOperation">
<setting name="enabled">true</setting>
<setting name="threshold">10 ms</setting>
</event>
<event name="jdk.Shutdown">
<setting name="enabled">true</setting>
<setting name="stackTrace">true</setting>
</event>
<event name="jdk.ThreadDump">
<setting name="enabled" control="thread-dump-enabled">true</setting>
<setting name="period" control="thread-dump-interval">everyChunk</setting>
</event>
<event name="jdk.IntFlag">
<setting name="enabled">true</setting>
<setting name="period">beginChunk</setting>
</event>
<event name="jdk.UnsignedIntFlag">
<setting name="enabled">true</setting>
<setting name="period">beginChunk</setting>
</event>
<event name="jdk.LongFlag">
<setting name="enabled">true</setting>
<setting name="period">beginChunk</setting>
</event>
<event name="jdk.UnsignedLongFlag">
<setting name="enabled">true</setting>
<setting name="period">beginChunk</setting>
</event>
<event name="jdk.DoubleFlag">
<setting name="enabled">true</setting>
<setting name="period">beginChunk</setting>
</event>
<event name="jdk.BooleanFlag">
<setting name="enabled">true</setting>
<setting name="period">beginChunk</setting>
</event>
<event name="jdk.StringFlag">
<setting name="enabled">true</setting>
<setting name="period">beginChunk</setting>
</event>
<event name="jdk.IntFlagChanged">
<setting name="enabled">true</setting>
</event>
<event name="jdk.UnsignedIntFlagChanged">
<setting name="enabled">true</setting>
</event>
<event name="jdk.LongFlagChanged">
<setting name="enabled">true</setting>
</event>
<event name="jdk.UnsignedLongFlagChanged">
<setting name="enabled">true</setting>
</event>
<event name="jdk.DoubleFlagChanged">
<setting name="enabled">true</setting>
</event>
<event name="jdk.BooleanFlagChanged">
<setting name="enabled">true</setting>
</event>
<event name="jdk.StringFlagChanged">
<setting name="enabled">true</setting>
</event>
<event name="jdk.ObjectCount">
<setting name="enabled" control="memory-profiling-enabled-all">false</setting>
<setting name="period">everyChunk</setting>
</event>
<event name="jdk.GCConfiguration">
<setting name="enabled" control="gc-enabled-normal">true</setting>
<setting name="period">everyChunk</setting>
</event>
<event name="jdk.GCHHeapConfiguration">
<setting name="enabled" control="gc-enabled-normal">true</setting>
<setting name="period">beginChunk</setting>
</event>
<event name="jdk.YoungGenerationConfiguration">
```

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

```
<setting name="enabled" control="gc-enabled-normal">true</setting>
<setting name="period">beginChunk</setting>
</event>

<event name="jdk.GCTLABConfiguration">
<setting name="enabled" control="gc-enabled-normal">true</setting>
<setting name="period">beginChunk</setting>
</event>

<event name="jdk.GCSurvivorConfiguration">
<setting name="enabled" control="gc-enabled-normal">true</setting>
<setting name="period">beginChunk</setting>
</event>

<event name="jdk.ObjectCountAfterGC">
<setting name="enabled" control="gc-enabled">false</setting>
</event>

<event name="jdk.GCHeapSummary">
<setting name="enabled" control="gc-enabled-normal">true</setting>
</event>

<event name="jdk.PSHeapSummary">
<setting name="enabled" control="gc-enabled-normal">true</setting>
</event>

<event name="jdk.G1HeapSummary">
<setting name="enabled" control="gc-enabled-normal">true</setting>
</event>

<event name="jdk.Metaspacesummary">
<setting name="enabled" control="gc-enabled-normal">true</setting>
</event>

<event name="jdk.MetaspacesGCThreshold">
<setting name="enabled" control="gc-enabled-normal">true</setting>
</event>

<event name="jdk.MetaspacesAllocationFailure">
<setting name="enabled" control="gc-enabled-normal">true</setting>
<setting name="stackTrace">true</setting>
</event>

<event name="jdk.MetaspacesOOM">
<setting name="enabled" control="gc-enabled-normal">true</setting>
<setting name="stackTrace">true</setting>
</event>

<event name="jdk.MetaspacesChunkFreeListSummary">
<setting name="enabled" control="gc-enabled-normal">true</setting>
</event>

<event name="jdk.GarbageCollection">
<setting name="enabled" control="gc-enabled-normal">true</setting>
<setting name="threshold">0 ms</setting>
</event>

<event name="jdk.ParallelOldGarbageCollection">
<setting name="enabled" control="gc-enabled-normal">true</setting>
<setting name="threshold">0 ms</setting>
</event>

<event name="jdk.YoungGarbageCollection">
<setting name="enabled" control="gc-enabled-normal">true</setting>
<setting name="threshold">0 ms</setting>
</event>

<event name="jdk.OldGarbageCollection">
<setting name="enabled" control="gc-enabled-normal">true</setting>
<setting name="threshold">0 ms</setting>
</event>

<event name="jdk.G1GarbageCollection">
<setting name="enabled" control="gc-enabled-normal">true</setting>
<setting name="threshold">0 ms</setting>
</event>

<event name="jdk.GCPhasePause">
<setting name="enabled" control="gc-enabled-normal">true</setting>
<setting name="threshold">0 ms</setting>
</event>

<event name="jdk.GCPhasePauseLevel1">
<setting name="enabled" control="gc-enabled-normal">true</setting>
<setting name="threshold">0 ms</setting>
</event>

<event name="jdk.GCPhasePauseLevel2">
<setting name="enabled" control="gc-enabled-normal">true</setting>
<setting name="threshold">0 ms</setting>
</event>

<event name="jdk.GCPhasePauseLevel3">
<setting name="enabled" control="gc-enabled-all">false</setting>
<setting name="threshold">0 ms</setting>
</event>

<event name="jdk.GCPhasePauseLevel4">
<setting name="enabled" control="gc-enabled-all">false</setting>
<setting name="threshold">0 ms</setting>
</event>

<event name="jdk.GCPhaseConcurrent">
<setting name="enabled" control="gc-enabled-all">true</setting>
<setting name="threshold">0 ms</setting>
</event>

<event name="jdk.GCReferenceStatistics">
<setting name="enabled" control="gc-enabled-normal">true</setting>
</event>

<event name="jdk.PromotionFailed">
<setting name="enabled" control="gc-enabled-normal">true</setting>
</event>

<event name="jdk.EvacuationFailed">
<setting name="enabled" control="gc-enabled">false</setting>
</event>
```

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

```
normal">true</setting>
</event>
<event name="jdk.EvacuationInformation">
<setting name="enabled" control="gc-enabled-normal">true</setting>
</event>
<event name="jdk.G1MMU">
<setting name="enabled" control="gc-enabled-normal">true</setting>
</event>
<event name="jdk.G1EvacuationYoungStatistics">
<setting name="enabled" control="gc-enabled-normal">true</setting>
</event>
<event name="jdk.G1EvacuationOldStatistics">
<setting name="enabled" control="gc-enabled-normal">true</setting>
</event>
<event name="jdk.G1BasiclHOP">
<setting name="enabled" control="gc-enabled-normal">true</setting>
</event>
<event name="jdk.G1AdaptiveLHOP">
<setting name="enabled" control="gc-enabled-normal">true</setting>
</event>
<event name="jdk.PromoteObjectInNewPLAB">
<setting name="enabled" control="memory-profiling-enabled-medium">false</setting>
</event>
<event name="jdk.PromoteObjectOutsidePLAB">
<setting name="enabled" control="memory-profiling-enabled-medium">false</setting>
</event>
<event name="jdk.ConcurrentModeFailure">
<setting name="enabled" control="gc-enabled-normal">true</setting>
</event>
<event name="jdk.AllocationRequiringGC">
<setting name="enabled" control="gc-enabled-all">false</setting>
<setting name="stackTrace">true</setting>
</event>
<event name="jdk.TenuringDistribution">
<setting name="enabled" control="gc-enabled-normal">true</setting>
</event>
<event name="jdk.G1HeapRegionInformation">
<setting name="enabled" control="gc-enabled-all">false</setting>
<setting name="period">everyChunk</setting>
</event>
<event name="jdk.G1HeapRegionTypeChange">
<setting name="enabled" control="gc-enabled-all">false</setting>
</event>
<event name="jdk.OldObjectSample">
<setting name="enabled" control="memory-leak-detection-enabled">true</setting>
<setting name="stackTrace" control="memory-leak-detection-stack-trace">false</setting>
<setting name="cutoff" control="memory-leak-detection-cutoff">0ns</setting>
</event>
<event name="jdk.CompilerConfiguration">
<setting name="enabled" control="compiler-enabled">true</setting>
<setting name="period">beginChunk</setting>
</event>
<event name="jdk.CompilerStatistics">
<setting name="enabled" control="compiler-enabled">true</setting>
<setting name="period">1000 ms</setting>
</event>
<event name="jdk.Compilation">
<setting name="enabled" control="compiler-enabled">true</setting>
<setting name="threshold" control="compiler-compilation-threshold">1000 ms</setting>
</event>
<event name="jdk.CompilerPhase">
<setting name="enabled" control="compiler-enabled">true</setting>
<setting name="threshold" control="compiler-phase-threshold">60s</setting>
</event>
<event name="jdk.CompilationFailure">
<setting name="enabled" control="compiler-enabled-failure">false</setting>
</event>
<event name="jdk.CompilerInlining">
<setting name="enabled" control="compiler-enabled-failure">false</setting>
</event>
<event name="jdk.CodeSweeperConfiguration">
<setting name="enabled" control="compiler-enabled">true</setting>
<setting name="period">beginChunk</setting>
</event>
<event name="jdk.CodeSweeperStatistics">
<setting name="enabled" control="compiler-enabled">true</setting>
<setting name="period">everyChunk</setting>
</event>
<event name="jdk.SweepCodeCache">
<setting name="enabled" control="compiler-enabled">true</setting>
<setting name="threshold" control="compiler-sweeper-threshold">100 ms</setting>
</event>
<event name="jdk.CodeCacheConfiguration">
<setting name="enabled" control="compiler-enabled">true</setting>
<setting name="period">beginChunk</setting>
</event>
<event name="jdk.CodeCacheStatistics">
```

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

```
<setting name="enabled" control="compiler-enabled">true</setting>
<setting name="period">everyChunk</setting>
</event>

<event name="jdk.CodeCacheFull">
<setting name="enabled" control="compiler-enabled">true</setting>
<setting name="period">beginChunk</setting>
</event>

<event name="jdk.OSInformation">
<setting name="enabled">true</setting>
<setting name="period">beginChunk</setting>
</event>

<event name="jdk.VirtualizationInformation">
<setting name="enabled">true</setting>
<setting name="period">beginChunk</setting>
</event>

<event name="jdk.CPUInformation">
<setting name="enabled">true</setting>
<setting name="period">beginChunk</setting>
</event>

<event name="jdk.ThreadContextSwitchRate">
<setting name="enabled" control="compiler-enabled">true</setting>
<setting name="period">10 s</setting>
</event>

<event name="jdk.CPULoad">
<setting name="enabled">true</setting>
<setting name="period">1000 ms</setting>
</event>

<event name="jdk.ThreadCPULoad">
<setting name="enabled">true</setting>
<setting name="period">10 s</setting>
</event>

<event name="jdk.CPUTimeStampCounter">
<setting name="enabled">true</setting>
<setting name="period">beginChunk</setting>
</event>

<event name="jdk.SystemProcess">
<setting name="enabled">true</setting>
<setting name="period">endChunk</setting>
</event>

<event name="jdk.NetworkUtilization">
<setting name="enabled">true</setting>
<setting name="period">5 s</setting>
</event>

<event name="jdk.InitialEnvironmentVariable">
<setting name="enabled">true</setting>
<setting name="period">beginChunk</setting>
</event>

<event name="jdk.PhysicalMemory">
<setting name="enabled">true</setting>
<setting name="period">everyChunk</setting>
</event>

<event name="jdk.ObjectAllocationInNewTLAB">
<setting name="enabled" control="memory-profiling-enabled-medium">false</setting>
<setting name="stackTrace">true</setting>
</event>

<event name="jdk.ObjectAllocationOutsideTLAB">
<setting name="enabled" control="memory-profiling-enabled-medium">false</setting>
<setting name="stackTrace">true</setting>
</event>

<event name="jdk.NativeLibrary">
<setting name="enabled">true</setting>
<setting name="period">everyChunk</setting>
</event>

<event name="jdk.ModuleRequire">
<setting name="enabled">true</setting>
<setting name="period">endChunk</setting>
</event>

<event name="jdk.ModuleExport">
<setting name="enabled">true</setting>
<setting name="period">endChunk</setting>
</event>

<event name="jdk.FileForce">
<setting name="enabled">true</setting>
<setting name="stackTrace">true</setting>
<setting name="threshold" control="file-io-threshold">20 ms</setting>
</event>

<event name="jdk.FileReader">
<setting name="enabled">true</setting>
<setting name="stackTrace">true</setting>
<setting name="threshold" control="file-io-threshold">20 ms</setting>
</event>

<event name="jdk.FileWrite">
<setting name="enabled">true</setting>
<setting name="stackTrace">true</setting>
<setting name="threshold" control="file-io-threshold">20 ms</setting>
</event>

<event name="jdk.SocketRead">
<setting name="enabled">true</setting>
<setting name="stackTrace">true</setting>
<setting name="threshold" control="socket-io-threshold">20 ms</setting>
</event>

<event name="jdk.SocketWrite">
<setting name="enabled">true</setting>
<setting name="stackTrace">true</setting>
<setting name="threshold" control="socket-io-threshold">20 ms</setting>
</event>

<event name="jdk.SecurityPropertyModification">
<setting name="enabled">false</setting>
<setting name="stackTrace">true</setting>
</event>

<event name="jdk.TLSHandshake">
<setting name="enabled">false</setting>
<setting name="stackTrace">true</setting>
</event>
```

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

```
<event name="jdk.X509Validation">
<setting name="enabled">false</setting>
<setting name="stackTrace">true</setting>
</event>

<event name="jdk.X509Certificate">
<setting name="enabled">false</setting>
<setting name="stackTrace">true</setting>
</event>

<event name="jdk.JavaExceptionThrow">
<setting name="enabled" control="enable-exceptions">false</setting>
<setting name="stackTrace">true</setting>
</event>

<event name="jdk.JavaErrorThrow">
<setting name="enabled" control="enable-errors">true</setting>
<setting name="stackTrace">true</setting>
</event>

<event name="jdk.ExceptionStatistics">
<setting name="enabled">true</setting>
<setting name="period">1000 ms</setting>
</event>

<event name="jdk.ActiveRecording">
<setting name="enabled">true</setting>
</event>

<event name="jdk.ActiveSetting">
<setting name="enabled">true</setting>
</event>

<event name="jdk.DataLoss">
<setting name="enabled">true</setting>
</event>

<event name="jdk.DumpReason">
<setting name="enabled">true</setting>
</event>

<event name="jdk.ZPageAllocation">
<setting name="enabled">true</setting>
<setting name="threshold">10 ms</setting>
</event>

<event name="jdk.ZThreadPhase">
<setting name="enabled">true</setting>
<setting name="threshold">0 ms</setting>
</event>

<event name="jdk.ZStatisticsCounter">
<setting name="enabled">true</setting>
<setting name="threshold">10 ms</setting>
</event>

<event name="jdk.ZStatisticsSampler">
<setting name="enabled">true</setting>
<setting name="threshold">10 ms</setting>
</event>
```

```
<!--
  Contents of the control element is not read by the JVM, it's used
  by Java Mission Control to change settings that carry the control
  attribute.
-->
<control>
<selection name="gc-level" default="detailed" label="Garbage
Collector">
<option label="Off" name="off">off</option>
<option label="Normal" name="detailed">normal</option>
<option label="All" name="all">all</option>
</selection>

<condition name="gc-enabled-normal" true="true" false="false">
<or>
<test name="gc-level" operator="equal" value="normal"/>
<test name="gc-level" operator="equal" value="all"/>
</or>
</condition>

<condition name="gc-enabled-all" true="true" false="false">
<test name="gc-level" operator="equal" value="all"/>
</condition>

<selection name="memory-profiling" default="off" label="Memory
Profiling">
<option label="Off" name="off">off</option>
<option label="Object Allocation and Promotion"
name="medium">medium</option>
<option label="All, including Heap Statistics (May cause long full
GCs)" name="all">all</option>
</selection>

<condition name="memory-profiling-enabled-medium" true="true"
false="false">
<or>
<test name="memory-profiling" operator="equal"
value="medium"/>
<test name="memory-profiling" operator="equal" value="all"/>
</or>
</condition>

<condition name="memory-profiling-enabled-all" true="true"
false="false">
<test name="memory-profiling" operator="equal" value="all"/>
</condition>

<selection name="compiler-level" default="normal"
```

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

```
label="Compiler">
  <option label="Off" name="off">off</option>
  <option label="Normal" name="normal">normal</option>
  <option label="Detailed" name="detailed">detailed</option>
  <option label="All" name="all">all</option>
</selection>

<condition name="compiler-enabled" true="false" false="true">
  <test name="compiler-level" operator="equal" value="off"/>
</condition>

<condition name="compiler-enabled-failure" true="true" false="false">
  <or>
    <test name="compiler-level" operator="equal" value="detailed"/>
    <test name="compiler-level" operator="equal" value="all"/>
  </or>
</condition>

<condition name="compiler-sweeper-threshold" true="0 ms" false="100 ms">
  <test name="compiler-level" operator="equal" value="all"/>
</condition>

<condition name="compiler-compilation-threshold" true="1000 ms">
  <test name="compiler-level" operator="equal" value="normal"/>
</condition>

<condition name="compiler-compilation-threshold" true="100 ms">
  <test name="compiler-level" operator="equal" value="detailed"/>
</condition>

<condition name="compiler-compilation-threshold" true="0 ms">
  <test name="compiler-level" operator="equal" value="all"/>
</condition>

<condition name="compiler-phase-threshold" true="60 s">
  <test name="compiler-level" operator="equal" value="normal"/>
</condition>

<condition name="compiler-phase-threshold" true="10 s">
  <test name="compiler-level" operator="equal" value="detailed"/>
</condition>

<condition name="compiler-phase-threshold" true="0 s">
  <test name="compiler-level" operator="equal" value="all"/>
</condition>

<selection name="method-sampling-interval" default="normal">
  label="Method Sampling"
  <option label="Off" name="off">off</option>
  <option label="Normal" name="normal">normal</option>
  <option label="High" name="high">high</option>
  <option label="Ludicrous (High Overhead)" name="ludicrous">ludicrous</option>
</selection>

<condition name="method-sampling-java-interval" true="999 d">
  <test name="method-sampling-interval" operator="equal" value="off"/>
</condition>

<condition name="method-sampling-java-interval" true="20 ms">
  <test name="method-sampling-interval" operator="equal" value="normal"/>
</condition>

<condition name="method-sampling-java-interval" true="10 ms">
  <test name="method-sampling-interval" operator="equal" value="high"/>
</condition>

<condition name="method-sampling-java-interval" true="1 ms">
  <test name="method-sampling-interval" operator="equal" value="ludicrous"/>
</condition>

<condition name="method-sampling-native-interval" true="999 d">
  <test name="method-sampling-interval" operator="equal" value="off"/>
</condition>

<condition name="method-sampling-native-interval" true="20 ms">
  <or>
    <test name="method-sampling-interval" operator="equal" value="normal"/>
    <test name="method-sampling-interval" operator="equal" value="high"/>
    <test name="method-sampling-interval" operator="equal" value="ludicrous"/>
  </or>
</condition>

<condition name="method-sampling-enabled" true="false" false="true">
  <test name="method-sampling-interval" operator="equal" value="off"/>
</condition>

<selection name="thread-dump-interval" default="normal">
  label="Thread Dump"
  <option label="Off" name="off">999 d</option>
  <option label="At least Once" name="normal">everyChunk</option>
  <option label="Every 60 s" name="everyMinute">60 s</option>
  <option label="Every 10 s" name="everyTenSecond">10 s</option>
  <option label="Every 1 s" name="everySecond">1 s</option>
</selection>

<condition name="thread-dump-enabled" true="false" false="true">
  <test name="thread-dump-interval" operator="equal" value="999 d"/>
</condition>

<selection name="exception-level" default="errors">
  label="Exceptions"
  <option label="Off" name="off">off</option>
  <option label="Errors Only" name="errors">errors</option>
  <option label="All Exceptions, including Errors" name="all">all</option>
</selection>

<condition name="enable-errors" true="true" false="false">
  <or>
    <test name="exception-level" operator="equal" value="errors"/>
    <test name="exception-level" operator="equal" value="all"/>
  </or>
</condition>

<condition name="enable-exceptions" true="true" false="false">
  <test name="exception-level" operator="equal" value="all"/>
</condition>

<selection name="memory-leak-detection" default="minimal">
  label="Memory Leak Detection"
  <option label="Off" name="off">off</option>
</selection>
```

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

```
<option label="Object Types" name="minimal">minimal</option>
<option label="Object Types + Allocation Stack Traces" name="medium">medium</option>
<option label="Object Types + Allocation Stack Traces + Path to GC Root" name="full">full</option>
</selection>

<condition name="memory-leak-detection-enabled" true="false" false="true">
    <test name="memory-leak-detection" operator="equal" value="off"/>
</condition>

<condition name="memory-leak-detection-stack-trace" true="true" false="false">
    <test name="memory-leak-detection" operator="equal" value="medium"/>
    <test name="memory-leak-detection" operator="equal" value="full"/>
    </or>
</condition>

<condition name="memory-leak-detection-cutoff" true="1 h" false="0 ns">
    <test name="memory-leak-detection" operator="equal" value="full"/>
</condition>

<text name="synchronization-threshold" label="Synchronization Threshold" contentType="timespan" minimum="0 s">20 ms</text>

<text name="file-io-threshold" label="File I/O Threshold" contentType="timespan" minimum="0 s">20 ms</text>
<text name="socket-io-threshold" label="Socket I/O Threshold" contentType="timespan" minimum="0 s">20 ms</text>

<flag name="class-loading-enabled" label="Class Loading" value="false">
</control>

</configuration>
, description=Low overhead configuration safe for continuous use in production environments, typically less than 1 % overhead., label=Continous, name=default, provider=Oracle, settings=[{key=jdk.ThreadAllocationStatistics#enabled, value=true}, {key=jdk.ThreadAllocationStatistics#period, value=everyChunk}, {key=jdk.ClassLoadingStatistics#enabled, value=true}, {key=jdk.ClassLoadingStatistics#period, value=1000 ms}, {key=jdk.ClassLoaderStatistics#enabled, value=true}, {key=jdk.ClassLoaderStatistics#period, value=everyChunk}, {key=jdk.JavaThreadStatistics#enabled, value=true}, {key=jdk.JavaThreadStatistics#period, value=1000 ms}, {key=jdk.ThreadStart#enabled, value=true}, {key=jdk.ThreadEnd#enabled, value=true}, {key=jdk.ThreadSleep#stackTrace, value=true}, {key=jdk.ThreadSleep#threshold, value=20 ms}, {key=jdk.ThreadPark#enabled, value=true}, {key=jdk.ThreadPark#stackTrace, value=true}, {key=jdk.ThreadPark#threshold, value=20 ms}, {key=jdk.JavaMonitorEnter#enabled, value=true}, {key=jdk.JavaMonitorEnter#stackTrace, value=true}, {key=jdk.JavaMonitorEnter#threshold, value=20 ms}, {key=jdk.JavaMonitorWait#enabled, value=true}, {key=jdk.JavaMonitorWait#stackTrace, value=true}, {key=jdk.JavaMonitorWait#threshold, value=20 ms}, {key=jdk.JavaMonitorInflate#enabled, value=false}, {key=jdk.JavaMonitorInflate#stackTrace, value=true}, {key=jdk.JavaMonitorInflate#threshold, value=20 ms}, {key=jdk.BiasedLockRevocation#enabled, value=true}, {key=jdk.BiasedLockRevocation#stackTrace, value=true}, {key=jdk.BiasedLockRevocation#threshold, value=0 ms}, {key=jdk.BiasedLockSelfRevocation#enabled, value=true}, {key=jdk.BiasedLockSelfRevocation#stackTrace, value=true}, {key=jdk.BiasedLockActivation#enabled, value=true}, {key=jdk.ReservedStackActivation#stackTrace, value=true}, {key=jdk.ClassLoad#enabled, value=false}, {key=jdk.ClassLoad#stackTrace, value=true}, {key=jdk.ClassLoad#threshold, value=0 ms}, {key=jdk.ClassDefine#enabled, value=false}, {key=jdk.ClassDefine#stackTrace, value=true}, {key=jdk.ClassUnload#enabled, value=false}, {key=jdk.JVMInformation#enabled, value=true}, {key=jdk.JVMInformation#period, value=beginChunk}, {key=jdk.InitialSystemProperty#enabled, value=true}, {key=jdk.InitialSystemProperty#period, value=beginChunk}, {key=jdk.ExecutionSample#enabled, value=true}, {key=jdk.ExecutionSample#period, value=20 ms}, {key=jdk.NativeMethodSample#enabled, value=true}, {key=jdk.NativeMethodSample#period, value=20 ms}, {key=jdk.SafepointBegin#enabled, value=true}, {key=jdk.SafepointBegin#threshold, value=10 ms}, {key=jdk.SafepointStateSynchronization#enabled, value=false}, {key=jdk.SafepointStateSynchronization#threshold, value=10 ms}, {key=jdk.SafepointWaitBlocked#enabled, value=false}, {key=jdk.SafepointWaitBlocked#threshold, value=10 ms}, {key=jdk.SafepointCleanup#enabled, value=false}, {key=jdk.SafepointCleanup#threshold, value=10 ms}, {key=jdk.SafepointCleanupTask#enabled, value=false}, {key=jdk.SafepointCleanupTask#threshold, value=10 ms}, {key=jdk.SafepointEnd#enabled, value=false}, {key=jdk.SafepointEnd#threshold, value=10 ms}, {key=jdk.ExecuteVMOperation#enabled, value=true}, {key=jdk.ExecuteVMOperation#threshold, value=10 ms}, {key=jdk.Shutdown#enabled, value=true}, {key=jdk.Shutdown#stackTrace, value=true}, {key=jdk.ThreadDump#enabled, value=true}, {key=jdk.ThreadDump#period, value=everyChunk}, {key=jdk.IntFlag#enabled, value=true}, {key=jdk.IntFlag#period, value=beginChunk}, {key=jdk.UnsignedIntFlag#enabled, value=true}, {key=jdk.UnsignedIntFlag#period, value=beginChunk}, {key=jdk.LongFlag#enabled, value=true}, {key=jdk.LongFlag#period, value=beginChunk}, {key=jdk.UnsignedLongFlag#enabled, value=true}, {key=jdk.UnsignedLongFlag#period, value=beginChunk}, {key=jdk.DoubleFlag#enabled, value=true}, {key=jdk.DoubleFlag#period, value=beginChunk}, {key=jdk.BooleanFlag#enabled, value=true}, {key=jdk.BooleanFlag#period, value=beginChunk}, {key=jdk.StringFlag#enabled, value=true}, {key=jdk.StringFlag#period, value=beginChunk}, {key=jdk.IntFlagChanged#enabled, value=true}, {key=jdk.UnsignedIntFlagChanged#enabled, value=true}, {key=jdk.LongFlagChanged#enabled, value=true}, {key=jdk.UnsignedLongFlagChanged#enabled, value=true}, {key=jdk.DoubleFlagChanged#enabled, value=true}, {key=jdk.BooleanFlagChanged#enabled, value=true}, {key=jdk.StringFlagChanged#enabled, value=true}, {key=jdk.ObjectCount#enabled, value=false}, {key=jdk.ObjectCount#period, value=everyChunk}, {key=jdk.GCConfiguration#enabled, value=true}, {key=jdk.GCConfiguration#period, value=everyChunk}, {key=jdk.GCHHeapConfiguration#enabled, value=true},
```

```
{key=dk.GCHeapConfiguration#period, value=beginChunk},  
{key=dk.YoungGenerationConfiguration#enabled, value=true},  
{key=dk.YoungGenerationConfiguration#period, value=beginChunk},  
{key=dk.GCTLABConfiguration#enabled, value=true},  
{key=dk.GCCTLABConfiguration#period, value=beginChunk},  
{key=dk.GCSurvivorConfiguration#enabled, value=true},  
{key=dk.GCSurvivorConfiguration#period, value=beginChunk},  
{key=dk.ObjectCountAfterGC#enabled, value=false},  
{key=dk.GCHeapSummary#enabled, value=true},  
{key=dk.PSHHeapSummary#enabled, value=true},  
{key=dk.G1HeapSummary#enabled, value=true},  
{key=dk.MetaspaceSummary#enabled, value=true},  
{key=dk.MetaspaceGCTThreshold#enabled, value=true},  
{key=dk.MetaspaceAllocationFailure#enabled, value=true},  
{key=dk.MetaspaceAllocationFailure#stackTrace, value=true},  
{key=dk.MetaspaceOOM#enabled, value=true},  
{key=dk.MetaspaceOOM#stackTrace, value=true},  
{key=dk.MetaspaceChunkFreeListSummary#enabled, value=true},  
{key=dk.GarbageCollection#enabled, value=true},  
{key=dk.GarbageCollection#threshold, value=0 ms},  
{key=dk.ParallelOldGarbageCollection#enabled, value=true},  
{key=dk.ParallelOldGarbageCollection#threshold, value=0 ms},  
{key=dk.YoungGarbageCollection#enabled, value=true},  
{key=dk.YoungGarbageCollection#threshold, value=0 ms},  
{key=dk.OldGarbageCollection#enabled, value=true},  
{key=dk.OldGarbageCollection#threshold, value=0 ms},  
{key=dk.G1GarbageCollection#enabled, value=true},  
{key=dk.G1GarbageCollection#threshold, value=0 ms},  
{key=dk.GCPhasePause#enabled, value=true},  
{key=dk.GCPhasePause#threshold, value=0 ms},  
{key=dk.GCPhasePauseLevel1#enabled, value=true},  
{key=dk.GCPhasePauseLevel1#threshold, value=0 ms},  
{key=dk.GCPhasePauseLevel2#enabled, value=true},  
{key=dk.GCPhasePauseLevel2#threshold, value=0 ms},  
{key=dk.GCPhasePauseLevel3#enabled, value=false},  
{key=dk.GCPhasePauseLevel3#threshold, value=0 ms},  
{key=dk.GCPhasePauseLevel4#enabled, value=false},  
{key=dk.GCPhasePauseLevel4#threshold, value=0 ms},  
{key=dk.GCPhaseConcurrent#enabled, value=true},  
{key=dk.GCPhaseConcurrent#threshold, value=0 ms},  
{key=dk.GCReferenceStatistics#enabled, value=true},  
{key=dk.PromotionFailed#enabled, value=true},  
{key=dk.EvacuationFailed#enabled, value=true},  
{key=dk.EvacuationInformation#enabled, value=true},  
{key=dk.G1MMU#enabled, value=true},  
{key=dk.G1EvacuationOldStatistics#enabled, value=true},  
{key=dk.G1BasicIOP#enabled, value=true},  
{key=dk.AdaptiveIOP#enabled, value=true},  
{key=dk.PromoteObjectInNewPLAB#enabled, value=false},  
{key=dk.PromoteObjectOutsidePLAB#enabled, value=false},  
{key=dk.ConcurrentModeFailure#enabled, value=true},  
{key=dk.AllocationRequiringGC#enabled, value=false},  
{key=dk.AllocationRequiringGC#stackTrace, value=true},  
{key=dk.TenuringDistribution#enabled, value=true},  
{key=dk.G1HeapRegionInformation#enabled, value=false},  
{key=dk.G1HeapRegionInformation#period, value=everyChunk},  
{key=dk.G1HeapRegionTypeChange#enabled, value=false},  
{key=dk.OldObjectSample#enabled, value=false},  
{key=dk.OldObjectSample#stackTrace, value=false},  
{key=dk.OldObjectSample#cutoff, value=0 ns},  
{key=dk.CompilerConfiguration#enabled, value=true},  
{key=dk.CompilerConfiguration#period, value=beginChunk},  
{key=dk.CompilerStatistics#enabled, value=true},  
{key=dk.CompilerStatistics#period, value=1000 ms},  
{key=dk.Compilation#enabled, value=true},  
{key=dk.Compilation#threshold, value=1000 ms},  
{key=dk.CompilerPhase#enabled, value=true},  
{key=dk.CompilerPhase#threshold, value=60 s},  
{key=dk.CompilationFailure#enabled, value=false},  
{key=dk.CompilerInlining#enabled, value=false},  
{key=dk.CodeSweeperConfiguration#enabled, value=true},  
{key=dk.CodeSweeperConfiguration#period, value=beginChunk},  
{key=dk.CodeSweeperStatistics#enabled, value=true},  
{key=dk.CodeSweeperStatistics#period, value=everyChunk},  
{key=dk.SweepCodeCache#enabled, value=true},  
{key=dk.SweepCodeCache#threshold, value=100 ms},  
{key=dk.CodeCacheConfiguration#enabled, value=true},  
{key=dk.CodeCacheConfiguration#period, value=beginChunk},  
{key=dk.CodeCacheStatistics#enabled, value=true},  
{key=dk.CodeCacheStatistics#period, value=everyChunk},  
{key=dk.CodeCacheFull#enabled, value=true},  
{key=dk.OSInformation#enabled, value=true},  
{key=dk.OSInformation#period, value=beginChunk},  
{key=dk.VirtualizationInformation#enabled, value=true},  
{key=dk.VirtualizationInformation#period, value=beginChunk},  
{key=dk.CPUInformation#enabled, value=true},  
{key=dk.CPUInformation#period, value=beginChunk},  
{key=dk.ThreadContextSwitchRate#enabled, value=true},  
{key=dk.ThreadContextSwitchRate#period, value=10 s},  
{key=dk.CPULoad#enabled, value=true}, {key=dk.CPULoad#enabled, value=true},  
{key=dk.ThreadCPULoad#period, value=1000 ms}, {key=dk.ThreadCPULoad#enabled, value=true},  
{key=dk.ThreadCPULoad#period, value=10 s},  
{key=dk.CPUTimeStampCounter#enabled, value=true},  
{key=dk.CPUTimeStampCounter#period, value=beginChunk},  
{key=dk.SystemProcess#enabled, value=true},  
{key=dk.SystemProcess#period, value=endChunk},  
{key=dk.NetworkUtilization#enabled, value=true},  
{key=dk.NetworkUtilization#period, value=5 s},  
{key=dk.InitialEnvironmentVariable#enabled, value=true},  
{key=dk.InitialEnvironmentVariable#period, value=beginChunk},  
{key=dk.PhysicalMemory#enabled, value=true},  
{key=dk.PhysicalMemory#period, value=everyChunk},  
{key=dk.ObjectAllocationInNewTLAB#enabled, value=false},  
{key=dk.ObjectAllocationInNewTLAB#stackTrace, value=true},  
{key=dk.ObjectAllocationOutsideTLAB#enabled, value=false},  
{key=dk.ObjectAllocationOutsideTLAB#stackTrace, value=true},  
{key=dk.NativeLibrary#enabled, value=true},  
{key=dk.NativeLibrary#period, value=everyChunk},  
{key=dk.ModuleRequire#enabled, value=true},  
{key=dk.ModuleRequire#period, value=endChunk},  
{key=dk.ModuleExport#enabled, value=true},  
{key=dk.ModuleExport#period, value=endChunk},  
{key=dk.FileForce#enabled, value=true},  
{key=dk.FileForce#stackTrace, value=true},  
{key=dk.FileRead#threshold, value=20 ms},  
{key=dk.FileRead#enabled, value=true},  
{key=dk.FileRead#stackTrace, value=true},  
{key=dk.FileRead#threshold, value=20 ms},  
{key=dk.FileWrite#enabled, value=true},  
{key=dk.FileWrite#stackTrace, value=true},  
{key=dk.FileWrite#threshold, value=20 ms},  
{key=dk.SocketRead#enabled, value=true},  
{key=dk.SocketRead#stackTrace, value=true},  
{key=dk.SocketRead#threshold, value=20 ms},  
{key=dk.SocketWrite#enabled, value=true},  
{key=dk.SocketWrite#stackTrace, value=true},  
{key=dk.SocketWrite#threshold, value=20 ms},  
{key=dk.SecurityPropertyModification#enabled, value=false},  
{key=dk.SecurityPropertyModification#stackTrace, value=true},  
{key=dk.TLSHandshake#enabled, value=false},  
{key=dk.TLSHandshake#stackTrace, value=true},  
{key=dk.X509Validation#enabled, value=false},  
{key=dk.X509Validation#stackTrace, value=true},  
{key=dk.X509Certificate#enabled, value=false},  
{key=dk.X509Certificate#stackTrace, value=true},  
{key=dk.JavaExceptionThrow#enabled, value=false},  
{key=dk.JavaExceptionThrow#stackTrace, value=true},
```

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

```
{key=dk.JavaErrorThrow#enabled, value=true},  
{key=dk.JavaErrorThrow#stackTrace, value=true},  
{key=dk.ExceptionStatistics#enabled, value=true},  
{key=dk.ExceptionStatistics#period, value=1000 ms},  
{key=dk.ActiveRecording#enabled, value=true},  
{key=dk.ActiveSetting#enabled, value=true},  
{key=dk.DataLoss#enabled, value=true},  
{key=dk.DumpReason#enabled, value=true},  
{key=dk.ZPageAllocation#enabled, value=true},  
{key=dk.ZPageAllocation#threshold, value=10 ms},  
{key=dk.ZThreadPhase#enabled, value=true},  
{key=dk.ZThreadPhase#threshold, value=0 ms},  
{key=dk.ZStatisticsCounter#enabled, value=true},  
{key=dk.ZStatisticsCounter#threshold, value=10 ms},  
{key=dk.ZStatisticsSampler#enabled, value=true},  
{key=dk.ZStatisticsSampler#threshold, value=10 ms}}}]
```

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

EventTypes

```
[{"categoryNames":["Java Development Kit, Security"],  
description="Modification of Security property, id=9013, label=Security  
Property Modification, name=jdk.jfr.SecurityPropertyModification,  
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,  
defaultValue=false, description=Record event, label=Enabled,  
name=enabled, typeName=jdk.settings.Enabled},  
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record  
event with duration above or equal to threshold, label=Threshold,  
name=threshold, typeName=jdk.settings.Threshold},  
{contentType=jdk.jfr.BooleanFlag, defaultValue=false,  
description=Record stack traces, label=Stack Trace,  
name=stackTrace, typeName=jdk.settings.StackTrace}]],  
, {"categoryNames":["Java Development Kit, Security"],  
description="Parameters used in TLS Handshake, id=8602, label=TLS  
Handshake, name=jdk.TLSHandshake,  
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,  
defaultValue=false, description=Record event, label=Enabled,  
name=enabled, typeName=jdk.settings.Enabled},  
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record  
event with duration above or equal to threshold, label=Threshold,  
name=threshold, typeName=jdk.settings.Threshold},  
{contentType=jdk.jfr.BooleanFlag, defaultValue=false,  
description=Record stack traces, label=Stack Trace,  
name=stackTrace, typeName=jdk.settings.StackTrace}]],  
, {"categoryNames":["Java Development Kit, Security"], description=Serial  
numbers from X.509 Certificates forming chain of trust, id=8513,  
label=X509 Validation, name=jdk.X509Validation,  
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,  
defaultValue=false, description=Record event, label=Enabled,  
name=enabled, typeName=jdk.settings.Enabled},  
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record  
event with duration above or equal to threshold, label=Threshold,  
name=threshold, typeName=jdk.settings.Threshold},  
{contentType=jdk.jfr.BooleanFlag, defaultValue=false,  
description=Record stack traces, label=Stack Trace,  
name=stackTrace, typeName=jdk.settings.StackTrace}]],  
, {"categoryNames":["Java Development Kit, Security"], description=Details  
of X.509 Certificate parsed by JDK, id=7954, label=X509 Certificate,  
name=idk.X509Certificate,  
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,  
defaultValue=false, description=Record event, label=Enabled,  
name=enabled, typeName=jdk.settings.Enabled},  
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record  
event with duration above or equal to threshold, label=Threshold,  
name=threshold, typeName=jdk.settings.Threshold},  
{contentType=jdk.jfr.BooleanFlag, defaultValue=false,  
description=Record stack traces, label=Stack Trace,  
name=stackTrace, typeName=jdk.settings.StackTrace}]],  
, {"categoryNames":["Flight Recorder"], description=null, id=9011,  
label=Flight Recording, name=jdk.ActiveRecording,  
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,  
defaultValue=false, description=Record event, label=Enabled,  
name=enabled, typeName=jdk.settings.Enabled},  
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record  
event with duration above or equal to threshold, label=Threshold,  
name=threshold, typeName=jdk.settings.Threshold},  
{contentType=jdk.jfr.BooleanFlag, defaultValue=false,  
description=Record stack traces, label=Stack Trace,  
name=stackTrace, typeName=jdk.settings.StackTrace}]],  
, {"categoryNames":["Flight Recorder"], description=null, id=9009,  
label=Recording Setting, name=jdk.ActiveSetting,  
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,  
defaultValue=false, description=Record event, label=Enabled,  
name=enabled, typeName=jdk.settings.Enabled},  
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record  
event with duration above or equal to threshold, label=Threshold,  
name=threshold, typeName=jdk.settings.Threshold},  
{contentType=jdk.jfr.BooleanFlag, defaultValue=false,  
description=Record stack traces, label=Stack Trace,  
name=stackTrace, typeName=jdk.settings.StackTrace}]],  
, {"categoryNames":["Java Application"], description=An object derived  
from java.lang.Error has been created. OutOfMemoryErrors are  
ignored, id=9007, label=Java Error, name=jdk.JavaErrorThrow,  
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,  
defaultValue=false, description=Record event, label=Enabled,  
name=enabled, typeName=jdk.settings.Enabled},  
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record  
event with duration above or equal to threshold, label=Threshold,  
name=threshold, typeName=jdk.settings.Threshold},  
{contentType=jdk.jfr.BooleanFlag, defaultValue=false,  
description=Record stack traces, label=Stack Trace,  
name=stackTrace, typeName=jdk.settings.StackTrace}]],  
, {"categoryNames":["Java Application, Statistics"], description=Number of  
objects derived from java.lang.Throwable that have been created,  
id=9005, label=Exception Statistics, name=jdk.ExceptionStatistics,  
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,  
defaultValue=false, description=Record event, label=Enabled,  
name=enabled, typeName=jdk.settings.Enabled},  
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record  
event with duration above or equal to threshold, label=Threshold,  
name=threshold, typeName=jdk.settings.Threshold},  
{contentType=jdk.jfr.BooleanFlag, defaultValue=false,  
description=Record event interval, label=Period, name=period, typeName=jdk.settings.Period}]],  
, {"categoryNames":["Java Application"], description=An object derived  
from java.lang.Exception has been created, id=9003, label=Java  
Exception, name=jdk.JavaExceptionThrow,  
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,  
defaultValue=false, description=Record event, label=Enabled,  
name=enabled, typeName=jdk.settings.Enabled},  
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record  
event with duration above or equal to threshold, label=Threshold,  
name=threshold, typeName=jdk.settings.Threshold},  
{contentType=jdk.jfr.BooleanFlag, defaultValue=false,  
description=Record stack traces, label=Stack Trace,  
name=stackTrace, typeName=jdk.settings.StackTrace}]],  
, {"categoryNames":["Java Application"], description=Writing data to a  
socket, id=9001, label=Socket Write, name=jdk.SocketWrite,  
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,  
defaultValue=false, description=Record event, label=Enabled,  
name=enabled, typeName=jdk.settings.Enabled},  
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record  
event with duration above or equal to threshold, label=Threshold,  
name=threshold, typeName=jdk.settings.Threshold},  
{contentType=jdk.jfr.BooleanFlag, defaultValue=false,  
description=Record stack traces, label=Stack Trace,  
name=stackTrace, typeName=jdk.settings.StackTrace}]],  
, {"categoryNames":["Java Application"], description=Reading data from a  
socket, id=8999, label=Socket Read, name=jdk.SocketRead,  
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,  
defaultValue=false, description=Record event, label=Enabled,  
name=enabled, typeName=jdk.settings.Enabled},  
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record  
event with duration above or equal to threshold, label=Threshold,  
name=threshold, typeName=jdk.settings.Threshold},  
{contentType=jdk.jfr.BooleanFlag, defaultValue=false,  
description=Record stack traces, label=Stack Trace,  
name=stackTrace, typeName=jdk.settings.StackTrace}]],  
, {"categoryNames":["Java Application"], description=Writing data to a file,  
id=8997, label=File Write, name=jdk.FileWrite,  
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,  
defaultValue=false, description=Record event, label=Enabled,  
name=enabled, typeName=jdk.settings.Enabled},  
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record  
event with duration above or equal to threshold, label=Threshold,  
name=threshold, typeName=jdk.settings.Threshold},  
{contentType=jdk.jfr.BooleanFlag, defaultValue=false,  
description=Record stack traces, label=Stack Trace,  
name=stackTrace, typeName=jdk.settings.StackTrace}]],  
, {"categoryNames":["Java Application"], description=Reading data from a  
file, id=8995, label=File Read, name=jdk.FileReader,  
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
```

```
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold},
{contentType=jdk.jfr.BooleanFlag, defaultValue=false,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}}),
{categoryNames=[Java Application], description=Force updates to be
written to file, id=8993, label=File Force, name=jdk.FileForce,
settingDescriptors={[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold},
{contentType=jdk.jfr.BooleanFlag, defaultValue=false,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}}),
{categoryNames=[Java Application], description=null, id=255,
label=Java Thread Start, name=jdk.ThreadStart,
settingDescriptors={[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled]},
{categoryNames=[Java Application], description=null, id=256,
label=Java Thread End, name=jdk.ThreadEnd,
settingDescriptors={[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled]},
{categoryNames=[Java Application], description=null, id=257,
label=Java Thread Sleep, name=jdk.ThreadSleep,
settingDescriptors={[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled]},
{categoryNames=[Java Application], description=null, id=258,
label=Java Thread Park, name=jdk.ThreadPark,
settingDescriptors={[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold},
{contentType=jdk.jfr.BooleanFlag, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}}),
{categoryNames=[Java Application], description=null, id=259,
label=Java Monitor Blocked, name=jdk.JavaMonitorEnter,
settingDescriptors={[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold},
{contentType=jdk.jfr.BooleanFlag, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}}),
{categoryNames=[Java Application], description=Waiting on a Java
monitor, id=260, label=Java Monitor Wait, name=jdk.JavaMonitorWait,
settingDescriptors={[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold},
{contentType=jdk.jfr.BooleanFlag, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}}),
{categoryNames=[Java Virtual Machine, Runtime],
description=Revoked bias of object, id=262, label=Biased Lock
Revocation, name=jdk.BiasedLockRevocation,
settingDescriptors={[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold},
{contentType=jdk.jfr.BooleanFlag, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}}),
{categoryNames=[Java Virtual Machine, Runtime],
description=Revoked bias of object biased towards own thread,
id=263, label=Biased Lock Self Revocation,
name=jdk.BiasedLockSelfRevocation,
settingDescriptors={[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold},
{contentType=jdk.jfr.BooleanFlag, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}}),
{categoryNames=[Java Virtual Machine, Runtime],
description=Revoked biases for all instances of a class, id=264,
label=Biased Lock Class Revocation,
name=jdk.BiasedLockClassRevocation,
settingDescriptors={[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold},
{contentType=jdk.jfr.BooleanFlag, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}}),
{categoryNames=[Java Virtual Machine, Runtime],
description=Activation of Reserved Stack Area caused by stack
overflow with ReservedStackAccess annotated method in call stack,
id=265, label=Reserved Stack Activation,
name=jdk.ReservedStackActivation,
settingDescriptors={[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold},
{contentType=jdk.jfr.BooleanFlag, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}}),
{categoryNames=[Java Virtual Machine, Class Loading],
description=null, id=266, label=Class Load, name=jdk.ClassLoad,
settingDescriptors={[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled]}
```

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

```
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record event with duration above or equal to threshold, label=Threshold, name=threshold, typeName=jdk.settings.Threshold}, {contentType=jdk.jfr.BooleanFlag, defaultValue=true, description=Record stack traces, label=Stack Trace, name=stackTrace, typeName=jdk.settings.StackTrace)}, {categoryNames=[Java Virtual Machine, Class Loading], description=null, id=267, label=Class Define, name=jdk.ClassDefine, settingDescriptors=[{contentType=jdk.jfr.BooleanFlag, defaultValue=false, description=Record event, label=Enabled, name=enabled, typeName=jdk.settings.Enabled}], {contentType=jdk.jfr.BooleanFlag, defaultValue=true, description=Record stack traces, label=Stack Trace, name=stackTrace, typeName=jdk.settings.StackTrace)}}, {categoryNames=[Java Virtual Machine, Class Loading], description=null, id=268, label=Class Unload, name=jdk.ClassUnload, settingDescriptors=[{contentType=jdk.jfr.BooleanFlag, defaultValue=false, description=Record event, label=Enabled, name=enabled, typeName=jdk.settings.Enabled}], {categoryNames=[Java Virtual Machine, Flag], description=null, id=269, label=Int Flag Changed, name=jdk.IntFlagChanged, settingDescriptors=[{contentType=jdk.jfr.BooleanFlag, defaultValue=false, description=Record event, label=Enabled, name=enabled, typeName=jdk.settings.Enabled}]}}, {categoryNames=[Java Virtual Machine, Flag], description=null, id=270, label=Unsigned Int Flag Changed, name=jdk.UnsignedIntFlagChanged, settingDescriptors=[{contentType=jdk.jfr.BooleanFlag, defaultValue=false, description=Record event, label=Enabled, name=enabled, typeName=jdk.settings.Enabled}], {categoryNames=[Java Virtual Machine, Flag], description=null, id=271, label=Long Flag Changed, name=jdk.LongFlagChanged, settingDescriptors=[{contentType=jdk.jfr.BooleanFlag, defaultValue=false, description=Record event, label=Enabled, name=enabled, typeName=jdk.settings.Enabled}], {categoryNames=[Java Virtual Machine, Flag], description=null, id=273, label=Double Flag Changed, name=jdk.DoubleFlagChanged, settingDescriptors=[{contentType=jdk.jfr.BooleanFlag, defaultValue=false, description=Record event, label=Enabled, name=enabled, typeName=jdk.settings.Enabled}]}}, {categoryNames=[Java Virtual Machine, Flag], description=null, id=272, label=Unsigned Long Flag Changed, name=jdk.UnsignedLongFlagChanged, settingDescriptors=[{contentType=jdk.jfr.BooleanFlag, defaultValue=false, description=Record event, label=Enabled, name=enabled, typeName=jdk.settings.Enabled}], {categoryNames=[Java Virtual Machine, Flag], description=null, id=274, label=Boolean Flag Changed, name=jdk.BooleanFlagChanged, settingDescriptors=[{contentType=jdk.jfr.BooleanFlag, defaultValue=false, description=Record event, label=Enabled, name=enabled, typeName=jdk.settings.Enabled}], {categoryNames=[Java Virtual Machine, Flag], description=null, id=275, label=String Flag Changed, name=jdk.StringFlagChanged, settingDescriptors=[{contentType=jdk.jfr.BooleanFlag, defaultValue=false, description=Record event, label=Enabled, name=enabled, typeName=jdk.settings.Enabled}], {categoryNames=[Java Virtual Machine, GC, Heap], description=null, id=278, label=Heap Summary, name=jdk.GCHeapSummary, settingDescriptors=[{contentType=jdk.jfr.BooleanFlag, defaultValue=false, description=Record event, label=Enabled, name=enabled, typeName=jdk.settings.Enabled}]}}, {categoryNames=[Java Virtual Machine, GC, Heap], description=null, id=280, label=Metaspace Summary, name=jdk.MetaspaceSummary, settingDescriptors=[{contentType=jdk.jfr.BooleanFlag, defaultValue=false, description=Record event, label=Enabled, name=enabled, typeName=jdk.settings.Enabled}], {categoryNames=[Java Virtual Machine, GC, Metaspace], description=null, id=281, label=Metaspace GC Threshold, name=jdk.MetaspaceGCThreshold, settingDescriptors=[{contentType=jdk.jfr.BooleanFlag, defaultValue=false, description=Record event, label=Enabled, name=enabled, typeName=jdk.settings.Enabled}], {categoryNames=[Java Virtual Machine, GC, Metaspace], description=null, id=282, label=Metaspace Allocation Failure, name=jdk.MetaspaceAllocationFailure, settingDescriptors=[{contentType=jdk.jfr.BooleanFlag, defaultValue=false, description=Record event, label=Enabled, name=enabled, typeName=jdk.settings.Enabled}], {categoryNames=[Java Virtual Machine, GC, Metaspace], description=null, id=283, label=Metaspace Out of Memory, name=jdk.MetaspaceOOM, settingDescriptors=[{contentType=jdk.jfr.BooleanFlag, defaultValue=false, description=Record event, label=Enabled, name=enabled, typeName=jdk.settings.Enabled}], {categoryNames=[Java Virtual Machine, GC, Metaspace], description=null, id=284, label=Metaspace Chunk Free List Summary, name=jdk.MetaspaceChunkFreeListSummary, settingDescriptors=[{contentType=jdk.jfr.BooleanFlag, defaultValue=false, description=Record event, label=Enabled, name=enabled, typeName=jdk.settings.Enabled}], {categoryNames=[Java Virtual Machine, GC, Heap], description=null, id=286, label=G1 Heap Summary, name=jdk.G1HeapSummary, settingDescriptors=[{contentType=jdk.jfr.BooleanFlag, defaultValue=false, description=Record event, label=Enabled, name=enabled, typeName=jdk.settings.Enabled}]}}, {categoryNames=[Java Virtual Machine, GC, Collector], description=Garbage collection performed by the JVM, id=287, label=Garbage Collection, name=jdk.GarbageCollection, settingDescriptors=[{contentType=jdk.jfr.BooleanFlag, defaultValue=false, description=Record event, label=Enabled, name=enabled, typeName=jdk.settings.Enabled}], {categoryNames=[Java Virtual Machine, GC, Collector], description=Extra information specific to Parallel Old Garbage Collections, id=288, label=Parallel Old Garbage Collection, name=jdk.ParallelOldGarbageCollection, settingDescriptors=[{contentType=jdk.jfr.BooleanFlag, defaultValue=false, description=Record event, label=Enabled, name=enabled, typeName=jdk.settings.Enabled}], {categoryNames=[Java Virtual Machine, GC, Collector], description=Extra information specific to Young Garbage Collections, id=289, label=Young Garbage Collection, name=jdk.YoungGarbageCollection, settingDescriptors=[{contentType=jdk.jfr.BooleanFlag, defaultValue=false, description=Record event, label=Enabled, name=enabled, typeName=jdk.settings.Enabled}], {categoryNames=[Java Virtual Machine, GC, Collector], description=Extra information specific to Young Garbage Collections, id=290, label=Young Garbage Collection, name=jdk.YoungGarbageCollection, settingDescriptors=[{contentType=jdk.jfr.BooleanFlag, defaultValue=false, description=Record event, label=Enabled, name=enabled, typeName=jdk.settings.Enabled}], {categoryNames=[Java Virtual Machine, GC, Collector], description=Extra information specific to Young Garbage Collections, id=291, label=Young Garbage Collection, name=jdk.YoungGarbageCollection, settingDescriptors=[{contentType=jdk.jfr.BooleanFlag, defaultValue=false, description=Record event, label=Enabled, name=enabled, typeName=jdk.settings.Enabled}]}]}
```

```
description=Extra information specific to Old Garbage Collections,
id=290, label=Old Garbage Collection,
name=jdk.OldGarbageCollection,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}],
{categoryNames=[Java Virtual Machine, GC, Collector],
description=Extra information specific to G1 Garbage Collections,
id=291, label=G1 Garbage Collection,
name=jdk.G1GarbageCollection,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}],
{categoryNames=[Java Virtual Machine, GC, Detailed],
description=null, id=292, label=G1 MMU Information,
name=jdk.G1MMU,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{categoryNames=[Java Virtual Machine, GC, Detailed],
description=null, id=293, label=Evacuation Information,
name=jdk.EvacuationInformation,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{categoryNames=[Java Virtual Machine, GC, Reference],
description=Total count of processed references during GC, id=294,
label=GC Reference Statistics, name=jdk.GCReferenceStatistics,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}],
{categoryNames=[Java Virtual Machine, GC, Detailed],
description=Memory related evacuation statistics during GC for the
young generation, id=298, label=G1 Evacuation Statistics for Young,
name=jdk.G1EvacuationYoungStatistics,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}],
{categoryNames=[Java Virtual Machine, GC, Detailed],
description=Memory related evacuation statistics during GC for the old
generation, id=299, label=G1 Evacuation Memory Statistics for Old,
name=jdk.G1EvacuationOldStatistics,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}],
{categoryNames=[Java Virtual Machine, GC, Detailed],
description=Basic statistics related to current IHOP calculation, id=300,
label=G1 Basic IHOP Statistics, name=jdk.G1BasicIHOP,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}],
{categoryNames=[Java Virtual Machine, GC, Detailed],
description=Statistics related to current adaptive IHOP calculation,
id=301, label=G1 Adaptive IHOP Statistics,
name=jdk.G1AdaptiveIHOP,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}],
{categoryNames=[Java Virtual Machine, GC, Detailed],
description=Object survived scavenger and was copied to a new
Promotion Local Allocation Buffer (PLAB). Supported GCs are Parallel
Scavenge, G1 and CMS with Parallel New. Due to promotion being
done in parallel an object might be reported multiple times as the GC
threads race to copy all objects., id=302, label=Promotion in new
PLAB, name=jdk.PromoteObjectInNewPLAB,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}],
{categoryNames=[Java Virtual Machine, GC, Detailed],
description=Object survived scavenger and was copied directly to the
heap. Supported GCs are Parallel Scavenge, G1 and CMS with
Parallel New. Due to promotion being done in parallel an object might
be reported multiple times as the GC threads race to copy all objects.,
id=303, label=Promotion outside PLAB,
name=jdk.PromoteObjectOutsidePLAB,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}],
{categoryNames=[Java Virtual Machine, GC, Detailed],
description=Promotion of an object failed, id=304, label=Promotion
Failed, name=jdk.PromotionFailed,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}],
{categoryNames=[Java Virtual Machine, GC, Detailed],
description=Evacuation of an object failed, id=305, label=Evacuation
Failed, name=jdk.EvacuationFailed,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}],
{categoryNames=[Java Virtual Machine, GC, Detailed],
description=Concurrent Modo failed, id=306, label=Concurrent Mode
Failure, name=jdk.ConcurrentModeFailure,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}],
{categoryNames=[Java Virtual Machine, GC, Phases],
description=null, id=308, label=GC Phase Pause,
name=jdk.CCPhasePause,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}],
{categoryNames=[Java Virtual Machine, GC, Phases],
description=null, id=308, label=GC Phase Pause Level 1,
name=jdk.CCPhasePauseLevel1,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}],
{categoryNames=[Java Virtual Machine, GC, Phases],
description=null, id=309, label=GC Phase Pause Level 2,
name=jdk.CCPhasePauseLevel2,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}],
{categoryNames=[Java Virtual Machine, GC, Phases],
description=null, id=310, label=GC Phase Pause Level 3,
name=jdk.CCPhasePauseLevel3,
```

```
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false,description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}],
{categoryNames=[Java Virtual Machine, GC, Phases],
description=null, id=311, label=GC Phase Pause Level 4,
name=jdk.GCPhasePauseLevel4,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false,description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}],
{categoryNames=[Java Virtual Machine, GC, Phases],
description=null, id=312, label=GC Phase Concurrent,
name=jdk.GCPhaseConcurrent,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false,description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}],
{categoryNames=[Java Virtual Machine, GC, Detailed],
description=null, id=313, label=Allocation Requiring GC,
name=jdk.AllocationRequiringGC,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false,description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.BooleanFlag, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}],
{categoryNames=[Java Virtual Machine, GC, Detailed],
description=null, id=314, label=Tenuring Distribution,
name=jdk.TenuringDistribution,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false,description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}],
{categoryNames=[Java Virtual Machine, GC, Detailed],
description=Information about a G1 heap region type change, id=315,
label=G1 Heap Region Type Change,
name=jdk.G1HeapRegionTypeChange,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false,description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}],
{categoryNames=[Java Virtual Machine, Compiler], description=null,
id=316, label=Compilation, name=jdk.Compilation,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false,description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}],
{categoryNames=[Java Virtual Machine, Compiler], description=null,
id=317, label=Compiler Phase, name=jdk.CompilerPhase,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false,description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}],
{categoryNames=[Java Virtual Machine, Compiler], description=null,
id=318, label=Compilation Failure, name=jdk.CompilationFailure,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false,description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}],
{categoryNames=[Java Virtual Machine, Compiler, Optimization],
description=null, id=320, label=Method Inlining,
name=jdk.CompilerInlining,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false,description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{categoryNames=[Java Virtual Machine, Code Sweeper],
description=null, id=321, label=Sweep Code Cache,
name=jdk.SweepCodeCache,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false,description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}],
{categoryNames=[Java Virtual Machine, Code Cache],
description=null, id=322, label=Code Cache Full,
name=jdk.CodeCacheFull,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false,description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}],
{categoryNames=[Java Virtual Machine, Runtime, Safepoint],
description=Safepointing begin, id=323, label=Safepoint Begin,
name=jdk.SafepointBegin,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false,description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}],
{categoryNames=[Java Virtual Machine, Runtime, Safepoint],
description=Synchronizing run state of threads, id=324, label=Safepoint
State Synchronization, name=jdk.SafepointStateSynchronization,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false,description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}],
{categoryNames=[Java Virtual Machine, Runtime, Safepoint],
description=Safepointing begin waiting on running threads to block,
id=325, label=Safepoint Wait Blocked,
name=jdk.SafepointWaitBlocked,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false,description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}],
{categoryNames=[Java Virtual Machine, Runtime, Safepoint],
description=Safepointing begin running cleanup tasks, id=326,
label=Safepoint Cleanup, name=jdk.SafepointCleanup,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false,description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}],
{categoryNames=[Java Virtual Machine, Runtime, Safepoint],
description=Safepointing begin running cleanup tasks, id=327,
label=Safepoint Cleanup Task, name=jdk.SafepointCleanupTask,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false,description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}],
{categoryNames=[Java Virtual Machine, Runtime, Safepoint],
description=Safepointing end, id=328, label=Safepoint End,
name=jdk.SafepointEnd,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
```

```
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}},
{categoryNames=[Java Virtual Machine, Runtime],
description=Execution of a VM Operation, id=329, label=VM
Operation, name=jdk.ExecuteVMOperation,
settingDescriptors={[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold]},
{categoryNames=[Java Virtual Machine, Runtime], description=JVM
shutting down, id=330, label=VM Shutdown, name=jdk.Shutdown,
settingDescriptors={[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.BooleanFlag, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}}},
{categoryNames=[Java Application], description=Allocation in new
Thread Local Allocation Buffer, id=331, label=Allocation in new TLAB,
name=jdk.ObjectAllocationInNewTLAB,
settingDescriptors={[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.BooleanFlag, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}}},
{categoryNames=[Java Application], description=Allocation outside
Thread Local Allocation Buffers, id=332, label=Allocation outside
TLAB, name=jdk.ObjectAllocationOutsideTLAB,
settingDescriptors={[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.BooleanFlag, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace}}},
{categoryNames=[Java Virtual Machine, Profiling], description=A
potential memory leak, id=333, label=Old Object Sample,
name=jdk.OldObjectSample,
settingDescriptors={[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.BooleanFlag, defaultValue=true,
description=Record stack traces, label=Stack Trace,
name=stackTrace, typeName=jdk.settings.StackTrace},
{contentType=jdk.jfr.Timespan, defaultValue=infinity, description=Limit
running time for event, label=Cutoff, name=cutoff,
typeName=jdk.settings.Cutoff}}},
{categoryNames=[Flight Recorder], description=Who requested the
recording and why, id=334, label=Recording Reason,
name=jdk.DumpReason,
settingDescriptors={[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}}},
{categoryNames=[Flight Recorder], description=Data could not be
copied out from a buffer, typically because of contention, id=335,
label=Data Loss, name=jdk.DataLoss,
settingDescriptors={[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}}},
{categoryNames=[Java Virtual Machine], description=Description of
JVM and the Java application, id=336, label=JVM Information,
name=jdk.JVMInformation,
settingDescriptors={[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, (contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period)}},
{categoryNames=[Operating System], description=null, id=337,
label=OS Information, name=jdk.OSInformation,
settingDescriptors={[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, (contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period)}},
{categoryNames=[Java Virtual Machine], description=System Property
at JVM start, id=339, label=Initial System Property,
name=jdk.InitialSystemProperty,
settingDescriptors={[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, (contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period)}},
{categoryNames=[Operating System], description=null, id=340,
label=Initial Environment Variable,
name=jdk.InitialEnvironmentVariable,
settingDescriptors={[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, (contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period)}},
{categoryNames=[Operating System], description=null, id=341,
label=System Process, name=jdk.SystemProcess,
settingDescriptors={[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, (contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period)}},
{categoryNames=[Operating System, Processor], description=null,
id=342, label=CPU Information, name=jdk.CPUInformation,
settingDescriptors={[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, (contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period)}},
{categoryNames=[Operating System, Processor], description=null,
id=343, label=CPU Time Stamp Counter,
name=jdk.CPUTimeStampCounter,
settingDescriptors={[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, (contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period)}},
{categoryNames=[Operating System, Processor], description=OS CPU
Load, id=344, label=CPU Load, name=jdk.CPULoad,
settingDescriptors={[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, (contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period)}},
{categoryNames=[Operating System, Processor], description=null,
id=345, label=Thread CPU Load, name=jdk.ThreadCPULoad,
settingDescriptors={[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, (contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period)}]
```

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

```
{categoryNames=[Operating System, Processor], description=null,
id=346, label=Thread Context Switch Rate,
name=jdk.ThreadContextSwitchRate,
settingDescriptors=[[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]],
{categoryNames=[Operating System, Network], description=null,
id=347, label=Network Utilization, name=jdk.NetworkUtilization,
settingDescriptors=[[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]],
{categoryNames=[Java Application, Statistics], description=null,
id=348, label=Java Thread Statistics, name=jdk.JavaThreadStatistics,
settingDescriptors=[[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]],
{categoryNames=[Java Application, Statistics], description=null,
id=349, label=Class Loading Statistics,
name=jdk.ClassLoadingStatistics,
settingDescriptors=[[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]],
{categoryNames=[Java Application, Statistics], description=null,
id=350, label=Class Loader Statistics,
name=jdk.ClassLoaderStatistics,
settingDescriptors=[[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]],
{categoryNames=[Java Application, Statistics], description=null,
id=351, label=Thread Allocation Statistics,
name=jdk.ThreadAllocationStatistics,
settingDescriptors=[[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]],
{categoryNames=[Operating System, Memory], description=OS Physical Memory, id=352, label=Physical Memory,
name=jdk.PhysicalMemory,
settingDescriptors=[[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]],
{categoryNames=[Java Virtual Machine, Profiling],
description=Snapshot of a threads state, id=353, label=Method Profiling Sample, name=jdk.ExecutionSample,
settingDescriptors=[[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]],
{categoryNames=[Java Virtual Machine, Profiling],
description=Snapshot of a threads state when in native, id=354,
label=Method Profiling Sample Native,
name=jdk.NativeMethodSample,
settingDescriptors=[[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]],
{categoryNames=[Java Virtual Machine, Runtime], description=null,
id=355, label=Thread Dump, name=jdk.ThreadDump,
settingDescriptors=[[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]],
{categoryNames=[Java Virtual Machine, Runtime], description=null,
id=356, label=Native Library, name=jdk.NativeLibrary,
settingDescriptors=[[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]],
{categoryNames=[Java Virtual Machine, Runtime, Modules],
description=A directed edge representing a dependency, id=357,
label=Module Require, name=jdk.ModuleRequire,
settingDescriptors=[[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]],
{categoryNames=[Java Virtual Machine, Runtime, Modules],
description=null, id=358, label=Module Export,
name=jdk.ModuleExport,
settingDescriptors=[[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]],
{categoryNames=[Java Virtual Machine, Compiler], description=null,
id=359, label=Compiler Statistics, name=jdk.CompilerStatistics,
settingDescriptors=[[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]],
{categoryNames=[Java Virtual Machine, Compiler], description=null,
id=360, label=Compiler Configuration,
name=jdk.CompilerConfiguration,
settingDescriptors=[[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]],
{categoryNames=[Java Virtual Machine, Code Cache],
description=null, id=361, label=Code Cache Statistics,
name=jdk.CodeCacheStatistics,
settingDescriptors=[[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]],
{categoryNames=[Java Virtual Machine, Code Cache],
description=null, id=362, label=Code Cache Configuration,
name=jdk.CodeCacheConfiguration,
settingDescriptors=[[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}]],
{categoryNames=[Java Virtual Machine, Code Sweeper],
description=null, id=363, label=Code Sweeper Statistics,
name=jdk.CodeSweeperStatistics,
settingDescriptors=[[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled}, {contentType=null,
```

```
defaultValue=everyChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period}],
{categoryNames=[Java Virtual Machine, Code Sweeper],
description=null, id=364, label=Code Sweeper Configuration,
name=jdk.CodeSweeperConfiguration,
settingDescriptors={[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled], [contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period]},
{categoryNames=[Java Virtual Machine, Flag], description=null,
id=365, label=Int Flag, name=jdk.IntFlag,
settingDescriptors={[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled], [contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period]},
{categoryNames=[Java Virtual Machine, Flag], description=null,
id=366, label=Unsigned Int Flag, name=jdk.UnsignedIntFlag,
settingDescriptors={[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled], [contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period]},
{categoryNames=[Java Virtual Machine, Flag], description=null,
id=367, label=Long Flag, name=jdk.LongFlag,
settingDescriptors={[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled], [contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period]},
{categoryNames=[Java Virtual Machine, Flag], description=null,
id=368, label=Unsigned Long Flag, name=jdk.UnsignedLongFlag,
settingDescriptors={[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled], [contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period]},
{categoryNames=[Java Virtual Machine, Flag], description=null,
id=369, label=Double Flag, name=jdk.DoubleFlag,
settingDescriptors={[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled], [contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period]},
{categoryNames=[Java Virtual Machine, Flag], description=null,
id=370, label=Boolean Flag, name=jdk.BooleanFlag,
settingDescriptors={[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled], [contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period]},
{categoryNames=[Java Virtual Machine, GC, Detailed],
description=null, id=371, label=String Flag, name=jdk.StringFlag,
settingDescriptors={[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled], [contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period]},
{categoryNames=[Java Virtual Machine, GC, Detailed],
description=Information about a specific heap region in the G1 GC,
id=373, label=G1 Heap Region Information,
name=jdk.G1HeapRegionInformation,
settingDescriptors={[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled], [contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period]},
{categoryNames=[Java Virtual Machine, GC, Detailed],
description=The configuration of the garbage collector, id=374,
label=GC Configuration, name=jdk.GCConfiguration,
settingDescriptors={[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled], [contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period]},
{categoryNames=[Java Virtual Machine, GC, Configuration],
description=The configuration of the survivors of garbage collection,
id=375, label=GC Survivor Configuration,
name=jdk.GCSurvivorConfiguration,
settingDescriptors={[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled], [contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period]},
{categoryNames=[Java Virtual Machine, GC, Configuration],
description=The configuration of the Thread Local Allocation Buffers
(TLABs), id=376, label=TLAB Configuration,
name=jdk.GCTLABConfiguration,
settingDescriptors={[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled], [contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period]},
{categoryNames=[Java Virtual Machine, GC, Configuration],
description=The configuration of the garbage collected heap, id=377,
label=GC Heap Configuration, name=jdk.GCHHeapConfiguration,
settingDescriptors={[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled], [contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period]},
{categoryNames=[Java Virtual Machine, GC, Configuration],
description=The configuration of the young generation of the garbage
collected heap, id=378, label=Young Generation Configuration,
name=jdk.YoungGenerationConfiguration,
settingDescriptors={[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled], [contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period]},
{categoryNames=[Java Virtual Machine, GC, Detailed],
description=Allocation of a ZPage, id=379, label=ZPage Allocation,
name=jdk.ZPageAllocation,
settingDescriptors={[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled], [contentType=null,
defaultValue=endChunk, description=Record event at interval,
label=Period, name=period, typeName=jdk.settings.Period]},
{categoryNames=[Java Virtual Machine, GC, Detailed],
description=Allocation of a ZPage, id=380, label=ZGC Thread Phase,
name=jdk.ZThreadPhase,
settingDescriptors={[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled], [contentType=null,
defaultValue=endChunk, description=Record event at threshold,
label=Threshold,
name=threshold, typeName=jdk.settings.Threshold]},
{categoryNames=[Java Virtual Machine, GC, Detailed],
description=null, id=380, label=ZGC Thread Phase,
name=jdk.ZThreadPhase,
settingDescriptors={[contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled], [contentType=null,
defaultValue=endChunk, description=Record event at threshold,
label=Threshold,
name=threshold, typeName=jdk.settings.Threshold]},
{categoryNames=[Java Virtual Machine, GC, Detailed],
description=null, id=381, label=Z Statistics Counter,
```

# Monitoring JavaMelody sur /demo\_vps363300.ovh.net

```
name=jdk.ZStatisticsCounter,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}],
{categoryNames=[Java Virtual Machine, GC, Detailed],
description=null, id=382, label=Z Statistics Sampler,
name=jdk.ZStatisticsSampler,
settingDescriptors=[{contentType=jdk.jfr.BooleanFlag,
defaultValue=false, description=Record event, label=Enabled,
name=enabled, typeName=jdk.settings.Enabled},
{contentType=jdk.jfr.Timespan, defaultValue=0 ns, description=Record
event with duration above or equal to threshold, label=Threshold,
name=threshold, typeName=jdk.settings.Threshold}]]}
ObjectName
Recordings
[]
```